(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
26 February 2004 (26.02.2004)

PCT

(10) International Publication Number
WO 2004/016899 A3

(51) International Patent Classification[7]: E21B 7/12

(21) International Application Number:
PCT/US2003/025749

(22) International Filing Date: 18 August 2003 (18.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/222,259 16 August 2002 (16.08.2002) US

(71) Applicant *(for all designated States except US)*: **DRIL-QUIP, INC.** [US/US]; 13550 Hempstead Highway, Houston, TX 77040 (US).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **DEBERRY, Blake** [—/—]; 68 Holland Grove View, Singapore 276225 (SG).


(74) Agent: **HELMREICH, Loren, G.**; Browning Bushman, P.C., 5718 Westheimer, Suite 1800, Houston, TX 77057 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: HORIZONTAL SPOOL TREE WELLHEAD SYSTEM AND METHOD



(57) Abstract: A horizontal spool tree wellhead system 10 utilizes a casing 18, 19 installed in a well bore and a wellhead housing 20 at the upper end of the casing. A spool 23 of the horizontal tree 22 is connected to the upper end of wellhead housing, and includes at least one radially extending side port. The BOP 28 is also installed at the upper end of the housing with a bore aligned with the wellhead housing bore. After drilling the well, the casing string 19 carrying a casing hanger 42 may be lowered through the bores of the BOP, the spool tree, and the wellhead housing and into the well. An orientation/isolation sleeve 60 may be installed in a predetermined rotational orientation with the spool tree. A tubing hanger 70 having a side port is landed onto the orientation sleeve and is automatically oriented to align the tubing hanger side port with the spool side port.

WO 2004/016899 A3

Published:
— *with international search report*
— *with amended claims*

(88) Date of publication of the international search report:
5 August 2004

Date of publication of the amended claims: 14 October 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.