(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
2 December 2004 (02.12.2004)

PCT

(10) International Publication Number
WO 2004/105135 A1

(51) International Patent Classification[7]: H01L 27/08, 21/02

(21) International Application Number: PCT/US2004/000764

(22) International Filing Date: 9 January 2004 (09.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/440,605 19 May 2003 (19.05.2003) US

(71) Applicant *(for all designated States except US)*: **ADVANCED MICRO DEVICES, INC.** [US/US]; One AMD Place, Mailstop 68, P.O. Box 3453, Sunnyvale, CA 94088-3453 (US).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **WU, David, Donggang** [US/US]; 10222 Dianella Lane, Austin, TX 78759 (US). **CHEEK, Jon, D.** [—/US]; 11441 Carnelian Drive, Austin, TX 78739 (US).


(74) Agent: **DRAKE, Paul, S.**; Advanced Micro Devices, Inc., 5204 East Ben White Boulevard, M/S 562, Austin, TX 78741 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: METHOD OF FORMING RESISTIVE STRUCTURES



(57) Abstract: A resistive structure (102) formed overlying a semiconductor substrate is masked with a silicide block layer (120) to define a portion of the resistive structure that is to be unsilicided and a portion of the resistive structure to be silicided. The silicide block layer (120) is changed to facilitate different processes.

WO 2004/105135 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.