

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 May 2003 (22.05.2003)

PCT

(10) International Publication Number
WO 03/041485 A2

(51) International Patent Classification⁷: **A01D**
(21) International Application Number: PCT/US02/35835
(22) International Filing Date:
8 November 2002 (08.11.2002)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
09/986,705 9 November 2001 (09.11.2001) US
(71) Applicant: **ESCO CORPORATION** [US/US]; 2141
N.W. 25th Avenue, Portland, OR 97210 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors: **OLLINGER, Charles, G., IV.**; 20570 S.W. Anna Court, Aloha, OR 97006 (US). **COWGILL, Noah, D.**; 7920 North Edison Street, Portland, OR 97203 (US).

Published:
— *without international search report and to be republished upon receipt of that report*

(74) Agent: **SCHAD, Steven, P.**; Banner & Witcoff, Ltd., Eleventh floor, 1001 G Street, N.W., Washington, DC 20001-4597 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ASSEMBLY FOR SECURING A WEAR MEMBER

(57) Abstract: An assembly for mounting an excavating tooth particularly suited for a dredge cutterhead includes a base, an adapter, and a lock. The base includes a convex, curved bearing surface that abuts a concave, curved bearing surface on the adapter. The curved bearing surfaces are able to maintain substantially full contact with each other under transverse loading.



WO 03/041485 A2