

SHADER PROGRAM GENERATION SYSTEM AND METHOD

RELATED APPLICATION

5

The present application is a continuation of an application filed 03/20/02 under application serial number 10/102,989, which is incorporated herein by reference in its entirety.

10

FIELD OF THE INVENTION

The present invention relates to computer graphics, and more particularly to shading operations within a graphics pipeline.

15

BACKGROUND OF THE INVENTION

20

25

Rendering and displaying 3-D graphics typically involves many calculations and computations. For example, to render a 3-D object, a set of coordinate points or vertices that define the object to be rendered must be formed. Vertices can be joined to form polygons that define the surface of the object to be rendered and displayed. Once the vertices that define an object are formed, the vertices must be transformed from an object or model frame of reference to a world frame of reference and finally to 2-D coordinates that can be displayed on a flat display device, such as a monitor. Along the way, vertices may be rotated, scaled, eliminated or clipped because they fall outside of a viewable area, lit by various lighting schemes and sources, colorized, and so forth. The processes involved in rendering and displaying a 3-D object can be computationally intensive and may involve a large number of vertices.

To create a 3-D computer graphical representation, the first step is to represent the objects to be depicted as mathematical models within the computer. 3-D models are made up of geometric points within a coordinate system consisting of an x, y and z axis; these axes correspond to width, height, and depth respectively.

- 5 Objects are defined by a series of points, called vertices. The location of a point, or vertex, is defined by its x, y and z coordinates. When three or more of these points are connected, a polygon is formed. The simplest polygon is a triangle.

- 3-D shapes are created by connecting a number of 2-D polygons. Curved
10 surfaces are represented by connecting many small polygons. The view of a 3-D shape composed of polygon outlines is called a wire frame view. In sum, the computer creates 3-D objects by connecting a number of 2-D polygons. Before the 3-D object is ultimately rendered on a 2-D display screen, however, the data of sophisticated graphics objects undergoes many different mathematical
15 transformations that implicate considerably specialized equations and processing unique to 3-D representation.

- For a long time now, 3-D rendering systems have been able to describe the "appearance" of objects according to parameters. These and later methods provide
20 for the parameterization of the perceived color of an object based on the position and orientation of its surface and the light sources illuminating it. In so doing, the appearance of the object is calculated therefrom. Parameters further include values such as diffuse color, the specular reflection coefficient, the specular color, the reflectivity, and the transparency of the material of the object. Such parameters are
25 globally referred to as the shading parameters of the object.

- Early systems could only ascribe a single value to shading parameters and hence they remained constant and uniform across the entire surface of the object. Later systems allowed for the use of non-uniform parameters (transparency for
30 instance) which might have different values over different parts of the object. Two prominent and distinct techniques have been used to describe the values taken by

these non-uniform parameters on the various parts of the object's surface: procedural shading and texture mapping. Texture mapping is pixel based and resolution dependent.

5 Procedural shading describes the appearance of a material at any point of a 1-D, 2-D or 3-D space by defining a function (often called the procedural shader) in this space into shading parameter space. The object is "immersed" in the original 1-D, 2-D or 3-D space and the values of the shading parameters at a given point of the surface of the object are defined as a result of the procedural shading function at this
10 point. For instance, procedural shaders that approximate appearance of wood, marble or other natural materials have been developed and can be found in the literature.

 The rendering of graphics data in a computer system is a collection of resource intensive processes. The process of shading i.e., the process of performing
15 complex techniques upon set(s) of specialized graphics data structures, used to determine values for certain primitives, such as color, etc. associated with the graphics data structures, exemplifies such a computation intensive and complex process. For each application developer to design these shading techniques for each program developed and/or to design each program for potentially varying third party
20 graphics hardware would be a Herculean task, and would produce much inconsistency.

 Consequently, generally the process of shading has been normalized to some degree. By passing source code designed to work with a shader into an application, a
25 shader becomes an object that the application may create/utilize in order to facilitate the efficient drawing of complex video graphics. Vertex shaders and pixel shaders are examples of such shaders.

 Prior to their current implementation in specialized hardware chips, vertex
30 and pixel shaders were sometimes implemented wholly or mostly as software code, and sometimes implemented as a combination of more rigid pieces of hardware with

software for controlling the hardware. These implementations frequently contained a CPU or emulated the existence of one using the system's CPU. For example, the hardware implementations directly integrated a CPU chip into their design to perform the processing functionality required of shading tasks. While a CPU adds a lot of flexibility to the shading process because of the range of functionality that a standard processing chip offers, the incorporation of a CPU adds overhead to the specialized shading process. Without today's hardware state of the art, however, there was little choice.

10 Today, though, existing advances in hardware technology have facilitated the ability to move functionality previously implemented in software into specialized hardware. As a result, today's pixel and vertex shaders are implemented as specialized and programmable hardware chips.

15 Unfortunately, programming such new vertex and pixel engines necessitates a meld of art and code resources never before required. Several digital content creation (DCC) applications have done an admirable job of supporting vertex and pixel shaders as far as they go, but it is not obvious how to allow artists to play with various shading options without having them become full-fledged shader
20 programmers.

SUMMARY

5 A method and computer program product are provided for generating a
shader program. Initially, a file associated with a graphics effect is selected. Such
file is then read and processed. A shader program is subsequently generated based
on the processing of the file to apply the graphics effect to an object. Thus, a shader
program may be correctly applied to an object for display or other purposes.

10 In one embodiment, the file may be selected from a library of files each
associated with a unique graphics effect. Further, the file may include interface data
capable of being processed to generate the shader program for different graphics
application program interfaces. In a similar manner, the file may include
implementation data capable of being processed to generate the shader program for
15 different hardware graphics pipeline platforms. Thus, the file may be processed in a
way to generate shader programs for working in conjunction with various different
graphics application program interfaces (i.e. OpenGL®, Direct 3D™, etc.), and a
variety of platforms (i.e. hardware graphics chips manufactured by different
companies).

20 In another embodiment, the file may be written in an extensible markup
language (XML). Moreover, the file may include a text file. Still yet, the selecting,
reading, processing, and generating may be carried out utilizing an interface [i.e.
Component Object Model (COM)], plug-in, etc.

25 As an option, the file may take the form of a data structure having a textual
descriptive object for identifying a graphics effect associated with the file. Further
provided may be a requirements object for identifying requirements necessary to
generate the shader program.

30

Thus, the file may include requirements, with the shader program being generated based on the requirements. In general, the requirements may include a default set of requirements, which may be optionally custom tailored. Optionally, the requirements may include a call back function.

5

The file may further include a plurality of shader code segments capable of executing the graphics effect in a plurality of operating environments (i.e. platform implementation, interface, etc.). Such shader code segments may be organized in terms of the different operating environments. Thus, the present embodiment may optionally be used as a reference for obtaining desired shader code segments.

10

During operation of one particular embodiment, the processing may include initializing an interface. Such processing may further include registering custom types and/or custom functions. Thus, the shader program may be generated based on the registered custom types and/or custom functions. By this feature, the present embodiment allows a user to customize the resulting shader program.

15

Still yet, the processing may include setting up a plurality of objects, selecting one of the objects, selecting one of a plurality of graphics effects, selecting a render pass, setting up the render pass, and drawing the object with the selected graphics effect. As an option, the render pass may be set up by pointing to parameters so that the shader program may be generated based on the parameters. Further, the object may be drawn with the selected graphics effect utilizing attributes supplied by an application.

20

25

During a rendering pass, it may be determined whether more render passes exist, and another render pass selected if more render passes exist. Further, it may be determined whether more objects exist, and another object selected if more objects exist. Still yet, it may be determined whether more graphics effects exist, and another graphics effect selected if more graphics effects exist.

30

One exemplary system that may be used to carry the foregoing functionality may include an interface and an application program for working in conjunction to process a file. Thus, the shader program is generated based on the processing of the file to apply the graphics effect to the object.

5

As mentioned earlier, the processing includes setting up a plurality of objects. From the perspective of the application in the context of the present system embodiment, this may be accomplished by selecting a file associated with a graphics effect, selecting a graphics application program interface, and receiving
10 implementation data representing a plurality of different hardware graphics pipeline platforms based on the selection. Next, parameters are received based on the implementation data. Further, it may be decided which of the hardware graphics pipeline platforms to use based at least in part on the parameters. By this design, the shader program is generated for use with the appropriate hardware graphics pipeline
15 platform.

As an option, the decision as to which of the hardware graphics pipeline platforms is to be used may be based on whether the parameters are capable of being supplied. Still yet, the decision as to which of the hardware graphics pipeline
20 platforms may be used is based on whether the parameters are understood (i.e., able to be correctly interpreted) by the application. Once such decisions have been made, attributes of an object are mapped to the parameters.

From the perspective of the interface in the context of the present system
25 embodiment, the objects are set up by generating implementation data representing a plurality of different hardware graphics pipeline platforms. Parameters are then generated based on the implementation data. Still yet, the interface works in conjunction with the application to decide as to which of the hardware graphics pipeline platforms to use based on the parameters.

30

Optionally, the implementation data may be generated by determining whether the different hardware graphics pipeline platforms meet a plurality of requirements. Moreover, the implementation data may be further generated by sorting the different hardware graphics pipeline platforms that meet the
5 requirements.

Associated with the foregoing framework is a computer-implemented method for generating a license agreement. Initially, a license agreement stored in memory is identified. Next, files associated with the license agreement are
10 identified. It is then determined as to whether one or more files are not distributable. If it is determined that one or more files are not distributable, a non-disclosure term is included in the license agreement.

Another computer implemented method is provided for determining whether
15 a file is distributable. Such method may include identifying a file stored in memory, determining whether the file is distributable, and simply indicating whether the file is distributable.

In order to allow a user to visually experiment and use the shader program,
20 an optional graphical user interface is provided. In use, the aforementioned graphics effect may be displayed utilizing such graphical user interface. Further, the graphics effect may be capable of being altered by a user utilizing the graphical user interface. In particular, the graphics effect may be capable of being altered by altering parameters, and the shader program may be generated based on the altered
25 parameters. Such parameters may altered by tweaking the aforementioned file.

Another graphical user interface may also be provided in which a plurality of graphics effects are displayed for allowing a user to select one graphics effect. Such selected graphics effect is then displayed as applied to an object using a file.
30 Further, the file is modified based on user input and the file is processed. Thus, the shader program may be generated based on the processing of the file.

As a further option, the interface may be capable of generating primitives. Further, the file may include a syntax including a name, a type and a content. Still yet, the file may be capable of referencing both compiled and un-compiled code.

5

These and other advantages of the present invention will become apparent upon reading the following detailed description and studying the various figures of the drawings.

10

BRIEF DESCRIPTION OF THE DRAWINGS

5 The foregoing and other aspects and advantages are better understood from the following detailed description of a preferred embodiment of the invention with reference to the drawings, in which:

10 Figure 1A is a block diagram of a digital processing system, in accordance with one embodiment.

Figure 1A-1 illustrates a more detailed diagram showing the internal structure of one exemplary embodiment of the hardware graphics pipeline of Figure 1A.

15 Figure 1A-2 illustrates an exemplary file that may be used to generate a shader program, in accordance with one embodiment.

20 Figures 1B and 1C each illustrate a method for generating a shader program, in accordance with one embodiment.

Figure 2 illustrates an “effect binding” method by which objects are set up in accordance with operation 1080 of Figures 1B and 1C.

25 Figure 3 illustrates a method for generating implementation data representing a plurality of different hardware graphics pipeline platforms, in accordance with operation 212 of Figure 2.

30 Figure 4 illustrates an exemplary method by which it may be decided which of the hardware graphics pipeline platforms to use, in accordance with operation 218 of Figure 2.

Figure 5 illustrates a business method associated with the present invention.

5

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figure 1A is a block diagram of a digital processing system, in accordance with one embodiment. With reference to Figure 1A, a computer graphics system is provided that may be implemented using a computer 10. The computer 10 includes one or more processors, such as processor 11, which is connected to a communication bus 12. The bus 12 can be implemented with one or more integrated circuits, and perform some logic functions; for example, a typical personal computer includes chips known as north bridge and south bridge chips. The computer 10 also includes a main memory 14. Control logic (software) and data are stored in the main memory 14 which may take the form of random access memory (RAM). The computer also includes a hardware graphics pipeline 18 and a display 20, i.e. a computer monitor.

The computer 10 may also include a secondary storage 16. The secondary storage 16 includes, for example, a hard disk drive and/or a removable storage drive, representing a floppy disk drive, a magnetic tape drive, a compact disk drive, etc. The removable storage drive reads from and/or writes to a removable storage unit in a well known manner. Computer programs, or computer control logic algorithms, are stored in the main memory 14 and/or the secondary storage 16. Such computer programs, when executed, enable the computer 10 to perform various functions. Memory 14 and storage 16 are thus examples of computer-readable media.

In one embodiment, the techniques to be set forth are performed by the hardware graphics pipeline 18 which may take the form of hardware. Such hardware implementation may include a microcontroller or any other type of custom or application specific integrated circuit (ASIC). In yet another embodiment, the method of the present invention may be carried out in part on the processor 11 by way of a computer program stored in the main memory 14 and/or the secondary

storage 16 of the computer 10. One exemplary architecture for the hardware graphics pipeline 18 will be set forth during reference to Figure 1A-1.

Figure 1A-1 illustrates a more detailed diagram showing the internal structure of one exemplary embodiment of the hardware graphics pipeline 18 of Figure 1A. As shown, a geometry stage 151 is provided which transforms primitives into a screen-aligned coordinate system. Other computations may be performed by the geometry stage 151 such as lighting to determine the visual properties (e.g., color, surface normal, texture coordinates) of each vertex describing the primitives.

The transformed vertices form the input for a rasterizer 152. The rasterizer 152 computes a fragment for each pixel covered by each of the primitives. A coverage mask stored with the fragment indicates which portions of the pixel the fragment covers.

Also included is a shader 153 that computes the final fragment, e.g. by applying texture maps or shader programs to the fragment. Such shader programs may be generated in various ways. One system and method for generating the shader programs will be set forth hereinafter in greater detail. It should be noted that in the context of the present description, shader programs may refer to vertex shader programs, pixel shader programs, or any other type of program capable of shading. An optional sample expansion stage 154 generates multiple samples for each fragment.

With continuing reference to Figure 1A-1, after multi-sampling, the individual samples are sent to a raster-processor (ROP) 155 as if they were regular fragments. The raster-processor 155 performs various operations on the fragments, including z/stencil testing and color or alpha blending. This may require the raster-processor 155 to read a frame buffer memory 156 in order to retrieve the destination

Z or the destination color. To this end, the final pixel color and Z are written back to the frame buffer memory **156**.

When all primitives in the scene have been rendered in this manner, the
5 contents of the frame buffer memory **156** are scanned out by a video refresh unit **157** and sent to the display **20**.

In one embodiment, all of the foregoing components of the graphics system
106 except the frame buffer memory **156** (and possibly other memories, such as
10 texture memory) may be situated on a single semiconductor platform. Of course, the various modules may also be situated separately or in various combinations of semiconductor platforms per the desires of the user.

An interface may be used in conjunction with the various components set
15 forth in Figures **1A** and **1A-1**. In one embodiment, such interface may include at least in part the Open Graphics Library (OpenGL[®]), Direct3D[™] application program interfaces (APIs), a proprietary application program interface, or the like.

In use, a shader program may be generated for use with the shader **153** of
20 Figure **1A-1**. Initially, a single file associated with a graphics effect is selected. Such file is then read and processed. In the context of the present description, a file may include any type of data structure, stream of data, network connection, etc. capable of communicating information. A shader program is subsequently generated based on the processing of the file to apply the graphics effect to an object. More
25 information will now be set forth regarding various exemplary techniques in carrying out such functionality.

Figure **1A-2** illustrates an exemplary file **160** that may be used to generate a shader program, in accordance with one embodiment. It should be noted that the
30 present file **160** may be used to generate a shader program in the context of the foregoing architecture of Figures **1A** and **1A-1**, or any another architecture desired.

An exemplary file **160** is set forth in Appendix A. The lines in Appendix A are numbered for reference.

5 In one embodiment, the file **160** may be selected from a library of files each associated with a unique graphics effect. Internally, such libraries may use a particular class. Such class may be a hierarchical database very similar to a file system. It may support links and functions, and allow user-defined types and functions to override and intermix with the pre-existing functions. Other functions
10 may also be involved including volatile functions that have the same structure as a regular function, however, volatile functions are always executed. Additionally, no time is spent checking if parameter dependencies have changed, as in the case of a regular function. Any function called by a volatile function is also treated as volatile for the duration of the function. The class is where files **160** may be stored and
15 accessed at runtime. Further, the class may be dumped to text at any time to facilitate debugging and archiving.

 As an option, the class may be compiled in order to make sure that links point to a valid field of the same type, and that functions are well formed. As an
20 option, the function strings may be compiled into an internal byte-code style representation. The class may also support just-in-time compilation, so that if a function is never called, it is never compiled. One may compile sub-trees of the class as needed to ensure links and functions are correct and fully specified.

25 In another embodiment, the file **160** may be written in an extensible markup language (XML). Moreover, the file **160** may include a text file. The example file **160** shown in Appendix A is in XML.

 As an option, the file **160** may include implementation data **161** capable of
30 being processed to generate the shader program for different hardware graphics pipeline platforms. For example, the implementation data **161** may represent a

variety of platforms (i.e. hardware graphics chips manufactured by different graphics companies for various purposes).

Still yet, the file **160** may include interface data **162** capable of being
5 processed to generate the shader program for different graphics application program interfaces. In particular, the file **160** may be processed in a way to generate shader programs for working in conjunction with various different graphics application program interfaces (i.e. OpenGL®, Direct 3D™, etc). In Appendix A, the tag “<imps>” at line 30 designates implementations, and lines 31 and 378 designate the
10 beginning of DirectX™8 and OpenGL® implementations, respectively.

With continuing reference to **1A-2**, a textual descriptive object **164** may be provided for identifying a graphics effect associated with the file using intuitive text. For example, the graphics effect may include a “shiny” characteristic, as shown in
15 Figure **1A-2**, and at lines 2 and 3 in Appendix A. Of course, any other type of visual effect (i.e. motion blur, etc.) may be described by the textual descriptive object **164**. Ideally, such textual descriptive object **164** allows an intuitive identification of the graphics effect associated with a shader program to be generated.

20 Further provided is at least one requirements object **166** for identifying requirements necessary to generate the shader program. As shown, various requirements are set forth for each of a plurality of render passes identified by way of pass identifiers **168**. For example, each render pass may have different required textures, render states, multi-pass effects, and sources of L-vectors, as well as
25 tangent space requirements, texture type requirements, or any other type of capability required to display a shader program correctly. Optionally, the requirements may even include a call back function.

In Appendix A, the requirements for the DirectX8 are potentially different
30 for the three implementations shown: (1) implementation 1, starting at line 32, has its requirements described in lines 37 through 50; (2) implementation 2, starting at

line 185, has its requirements described in lines 190 through 199; and (3) implementation 3, starting at line 282, has its requirements described in lines 287 through 296. Note that implementations 2 and 3 have the same requirements, but implementation 1 has different requirements.

5

In general, the requirements may include a default set of requirements, which may be optionally custom tailored. Such tailorable requirements, or “tweakables,” represent artist-controllable parameters for shader-specific items. Tweakables are required by a shader program, but are not necessarily exposed through standard tool paths. Shader program authors may decide which parts of the shader program to expose to artist manipulation. Tweakables may refer to any requirement ranging from a transparency factor to an alpha blend factor. Table 1 illustrates exemplary tweakables in the context of the file 160 of Figure 1A-1.

15

Table 1

```

    <tweakables>
      <shininess>
        <string name = "description" type = "value"
20         content = "Relative Opacity" />
        <string name = "type" type = "value"
        content = "float" />
        <string name = "field" type = "value"
        content = "../..//settings/opacity" />
25         <string name = "gui" type = "value"
        content = "slider" />
        <float name = "min" type = "value"
        content = "0.0" />
        <float name = "max" type = "value"
30         content = "1.0" />
        <float name = "step" type = "value"
        content = "0.1" />
      </shininess>
    </tweakables>
35
```

35

In Appendix A, the tweakables are designated at lines 14 through 29. The tweakables are generally outside the designation of any of the implementations because they generally apply to all the implementations. In this example, a minimum value (lines 22 and 23), a maximum value (lines 24 and 25), and a step size (lines 26 and 27) are included.

40

Further provided with the file 160 is a plurality of shader code segments 170 capable of executing the graphics effect in a plurality of operating environments. As shown, such shader code segments 170 include a syntax including a name, a type and a content. Still yet, the file may be capable of referencing both compiled and un-compiled shader program code.

As shown in Figure 1A-2, the shader code segments 170 may be organized in terms of the different operating environments. Thus, the present embodiment may optionally be used as a reference for obtaining desired shader code segments 170.

In Appendix A, an example of shader code is shown at lines 60 through 88.

Table 2 illustrates a summary of various elements of an exemplary shader implementation in Direct3D® 8.

Table 2

1. Preamble/declaration: These elements provide a priority for a particular implementation/interface, and a string description of the implementation/interface.
2. Requirements: These specify the various requirements for the implementation/interface to run correctly. In particular, they include the Dx8 caps that are required for the shader. All requirements evaluate to type 'bool'.
3. Texture handles: These refer to texture handles that are created either from data in texture files (i.e. png, dds, tga, etc.) or generated textures such as normalization cube maps. The handles can be referenced in subsequent sections of the file, and are independent of the render pass or texture unit.
4. Vertex shader & Pixel Shader Handles: These are the dx8-provided handles that are created either compiled shader

strings or from precompiled shader files. The handles can be referenced in subsequent sections of the file, and are independent of the render pass or texture unit. If a user does not want a vertex shader applied, the handle may be set to the FVF code being used. If the user does not specify a pixel shader for a pass, it may be set to zero, thus turning off pixel shading.

5

10

15

5. Vertex Mapping: This section is highly recommended and encouraged, but optional. This is where one may specify the meaning of the various vertex attributes, (such as v0, v1, v5) in a shader program. By specifying the mapping and exposing the shader program in string form, an application with a different geometry layout may have the shader program re-written with the new geometry format.

20

6. A shader implementation can comprise multiple render passes, each with unique render states, texture stage states, vertex mapping, pixel and vertex shaders.

25

7. There may be a file that represents the default render and texture stage states for the system. If one does not specify a renderstate or texture stage state in a pass of a shader program, it is reset to the default state in the file. By using the file, one may gain improved interoperability with shader programs that use the same file. If one does not wish to make changes, he or she can do so, but at the cost of having to update shaders to reflect the render state changes.

30

Table 3 illustrates a summary of various elements of an exemplary shader implementation in OpenGL®.

Table 3

35

1. Preamble/declaration: These elements provide a priority for the implementation/interface, and a string description of the implementation/interface.

2. Requirements: These specify the various requirements for the implementation/interface to run correctly. In particular, they include the OpenGL® extensions that are required for the shader. If these are not available, the OpenGL implementation may not load the shader program.
3. Texture handles: These refer to texture handles that are created either from data in texture files (i.e. png, dds, tga, etc.) or generated textures such as normalization cube maps. The handles can be referenced in subsequent sections of the file, and are independent of the render pass or texture unit.
4. A shader implementation can comprise multiple render passes, each with a unique vertex program, texture shader and register combiner definitions.

Figure 1B illustrates a method 1000 for generating a shader program, in accordance with one embodiment. This method 1000 is generally done under control of an application program that renders an image with one or more three-dimensional objects. While the present method 1000 may be implemented in the context of the framework of the foregoing figures, it may readily be implemented in the context of any desired architecture and data structure. As an option, the various operations may be carried out utilizing an interface [i.e. Component Object Model (COM)], plug-in, etc. Moreover, various steps may be optionally excluded and/or reordered during the course of the processing that is required to generate the shader program.

Initially, in operation 1020, the processing may include initializing an interface. In a preferred embodiment, the interface is an API to the library of effects, and can be implemented as a plug-in. Next, any number of custom types and custom functions are registered in operation 1040. Thus, the shader program may be generated based on the registered custom types and/or custom functions. By this

feature, the present embodiment allows a user to customize the resulting shader program.

Next, one of the objects to be rendered is selected in operation **1060** after
5 which such object is set up in operation **1080**. This set up process is carried out for
each of a plurality of objects to be rendered, as indicated by decision **1090**. Thus, a
plurality of objects is set up. This preparation facilitates the generation of the shader
program by taking various information relating to the implementation and interface
associated with the environment in which the shader program is to be used. More
10 information relating to an exemplary embodiment of such set up operation will be
set forth in greater detail during reference to Figures 2 through 4.

With continuing reference to Figure **1B**, one of the objects is selected along
with one of a plurality of graphics effects, and a render pass. See operations **1100-**
15 **1140**. The selected render pass is then set up in operation **1160** after which the
selected object is drawn with the selected graphics effect. See operation **1180**. As
an option, the render pass may be set up by pointing to parameters. The shader
program may then be generated based on the parameters. Further, the object may be
drawn with the selected graphics effect utilizing attributes supplied by an
20 application. Parameters that are not passed in during render pass setup **1160**
generally use default values supplied in the file **160**. The parameters can be supplied
in any order, and the use of pointers to the parameters provides a mechanism for
parameters to be shared amongst a plurality of objects.

25 During a rendering pass, it may be determined whether more render passes
exist, and another render pass selected if more render passes exist. See decision
1200. Further, it may be determined whether more graphics effects exist, and
another graphics effect selected if more graphics effects exist. Note decision **1220**.
Still yet, it may be determined whether more objects exist, and another object
30 selected if more objects exist, as indicated by decision **1240**.

It should be noted that the various operations included in the box **1300** may be carried out in any order. See, for example, Figure **1C**. Of course, any feasible permutation of the operations may be employed.

5 Figure **2** illustrates an “effect binding” method **200** by which objects are set up in accordance with operation **1080** of Figures **1B** and **1C**. Such method **200** is carried out in the context of an exemplary system including an interface **204** and an application program **202** for working in conjunction to process the file. Thus, the shader program is generated based on the processing of the file to apply the graphics
10 effect to the object. Of course, the present method **200** may be implemented in the context of any desired system.

As mentioned earlier, the processing includes setting up a plurality of objects. From the perspective of the application program **202** in the context of the
15 present system embodiment, this may be accomplished by selecting a file associated with a desired graphics effect in operation **206**. In one embodiment, a .dll file may be used by a tool or graphics engine to read the file.

Next, in operation **208**, a graphics application program interface is selected.
20 Thereafter, the interface **204** is called. See operation **210**. In response to such call, implementation data representing a plurality of different hardware graphics pipeline platforms is received based on the selection of the particular graphics application program interface. In one embodiment, any platform that supports the selected graphics application program interface may be represented by the implementation
25 data.

Next, parameters are requested and received based on the implementation data, as indicated by operation **214**. Further, it may be decided which of the hardware graphics pipeline platforms to use based on the parameters in operation
30 **218**. As will soon become apparent, this decision may be made using the application

program **202** in conjunction with the interface **204**. More information relating to such decisions will be set forth in greater detail during reference to Figure 4.

From the perspective of the interface **204** in the context of the present system
5 embodiment, the objects are set up by generating implementation data representing a plurality of different hardware graphics pipeline platforms, in response to the call of operation **210**. Note operation **212**. More information as how this may be accomplished in accordance with one embodiment will be set forth with reference to Figure 3. Parameters are then generated based on the implementation data in
10 operation **216**. As mentioned earlier, the interface **204** works in conjunction with the application **202** in operation **218** to decide as to which of the hardware graphics pipeline platforms to use based on the parameters.

As an option, the interface **204** may be capable of generating primitives. For
15 example, a sphere may be generated from a point and radius, etc. This can be done by defining a geometry generator (for example, with a tag "<geogenerator>"), which is analogous to the pixel shader (as shown with the tag "<pixelshader>") or the vertex shader (as shown with the tag "<vertexshader>"). This primitive generation technique may be useful in many contexts. For example, it may be used when
20 generating grass or other similar objects.

Figure 3 illustrates a method **300** for generating implementation data representing a plurality of different hardware graphics pipeline platforms, in accordance with operation **212** of Figure 2. This method **300** is done within the
25 interface **204**. It should be noted that the present method **300** is set forth for illustrative purposes only, and should not be construed as limiting in any manner.

As shown in Figure 3, implementation data is retrieved in operation **302**, which, for example, finds all the implementations (inside the designation "<imps>",
30 shown at line30 in Appendix A) in the file **160**. Next, it is determined whether the implementation data meets the requirements outlined under the appropriate graphics

application program interface in the current file. If it is determined in decision 304 that the requirements are met, the implementation data is sorted in a list in operation 306. This may be accomplished using a floating point priority provided by a user. This process is continued for all implementation data associated with the selected
5 graphics application program interface. Note decision 308.

Figure 4 illustrates an exemplary method 400 by which it may be decided which of the hardware graphics pipeline platforms to use, in accordance with operation 218 of Figure 2. Generally, this method 400 is performed by the
10 application 202. Again, it should be noted that the present method 400 is set forth for illustrative purposes only, and should not be construed as limiting in any manner.

Initially, in operation 402, the parameters associated with a particular implementation are identified. This is done by calling the interface and requesting
15 the list of parameters for an implementation. Again, each implementation may correspond with a specific platform (i.e. hardware graphics chips manufactured by different graphics companies).

It is then determined, in decision 404, whether the parameters supplied by the
20 interface are understood by the application (i.e., whether the parameter names can be correctly interpreted by the application). Further, it is determined whether the parameters can be supplied by the application. See decision 406. Both of these decisions must render a positive response if the present implementation is to be utilized by the application program. As an option, the current decisions can be
25 carried out in a place other than the application program.

Next, in operation 408, it is determined whether data is matching. If not, any mismatching data is corrected in operation 407. The correction operation 407 can include, for example, swapping the order of the data and/or making the needed data
30 from existing data. Unlike the previous decisions, the present decision 408 may optionally be carried out by the interface.

The foregoing decisions are made for each of the implementations that are available. See decision **410**. Next, graphic effects are assigned to the object in operation **412**. Generally, the application selects from the implementations kept in
5 operation **402**.

In order to allow a user to visually experiment and use a shader program, an optional graphical user interface is provided. In use, the aforementioned graphics effect may be displayed utilizing a graphical user interface. Further, the graphics
10 effect may be capable of being altered by a user utilizing the graphical user interface. In particular, the graphics effect may be capable of being altered by altering parameters (i.e. tweakables), and the shader program may be generated based on the altered parameters. This may be accomplished by way of a sliders, edit boxes, etc. The parameters may be altered by tweaking the associated file.

15

Another graphical user interface may also be provided in which a plurality of graphics effects are displayed for allowing a user to select one graphics effect. Such selected graphics effect is then displayed as applied to an object using a file. Further, the file is modified based on user input and the file is processed. Thus, the
20 shader program may be generated based on the processing of the file.

Figure **5** illustrates a business method **500** associated with the present invention. In use, the file (i.e. see Figure **1A-1**) may be sold or otherwise distributed by way of a license agreement. The various shader programs or portions thereof in
25 the file may or may not be distributable to the public for one reason or another. The present computer-implemented business method **500** allows the automated generation of a license agreement that takes into consideration whether non-distributable shader programs exist in a particular file to be licensed.

30 Initially, in operation **502**, a license agreement stored in memory is identified. Further, files associated with the license agreement are identified.

It is then determined as to whether one or more of the files are not distributable at least in part. See decision 506. This may be accomplished by specifically tagging non-distributable code, or comparing the contents of the file
5 with a database of known non-distributable code.

If it is determined that one or more files are not distributable in decision 506, a non-disclosure term is included in the license agreement. This non-disclosure term may be of a boilerplate nature and incorporated into the license agreement
10 automatically in any other manner that is well known to those of ordinary skill. See operation 508.

In a simplified associated computer-implemented method, a technique is provided for determining whether a file is distributable. Such method may include
15 identifying a file stored in memory, determining whether the file is distributable, and simply indicating whether the file is distributable.

While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not
20 limitation. Thus, the breadth and scope of a preferred embodiment should not be limited by any of the above described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents. The order of elements within claims does not indicate any particular order of steps or operations.

25

APPENDIX A

```
1  <depot>
2    <description type = "string"
3      value = "Apply Diffuse Texture and Glossy Reflection" />
4    <equation type = "string"
5      value = "object/diffuseTexture" />
6    <categories>
7      <Shiny type = "string"
8        value = "Plain" />
9    </categories>
10   <settings>
11     <shininess type = "float"
12       value = "0.800000" />
13   </settings>
14   <tweakables>
15     <shininess>
16       <description type = "string"
17         value = "Object Shininess" />
18       <element type = "float"
19         link = "sfx/[self]/settings/shininess" />
20       <gui type = "string"
21         value = "slider" />
22       <min type = "float"
23         value = "0.000000" />
24       <max type = "float"
25         value = "1.000000" />
26       <step type = "float"
27         value = "0.100000" />
```

```
28     </shininess>
29 </tweakables>
30 <imps>
31     <dx8>
32         <imp1>
33             <priority type = "float"
34                 value = "1.000000" />
35             <description type = "string"
36                 value = "Shiny with Gloss Alpha Channel" />
37         <requirements>
38             <os type = "bool"
39                 function = "GreaterEqual_float( parameters/os/version, float(
5.0 ) )" />
40             <api type = "bool"
41                 function = "GreaterEqual_float( parameters/api/version, float(
8.0 ) )" />
42             <CubeTextureSupport type = "bool"
43                 function = "AllSet( D3DCAPS8/TextureCaps, bitset(
D3DPTTEXTURECAPS_CUBEMAP ) )" />
44             <TextureSupport type = "bool"
45                 function = "GreaterEqual_uint(
D3DCAPS8/MaxSimultaneousTextures, uint( 2 ) )" />
46             <VertexShaders type = "bool"
47                 function = "GreaterEqual_float(
D3DCAPS8/VertexShaderVersion, float( 1.1 ) )" />
48             <PixelShaders type = "bool"
49                 function = "GreaterEqual_float(
D3DCAPS8/PixelShaderVersion, float( 1.1 ) )" />
50         </requirements>
51     <passes>
```

```
52      <passCount type = "uint"
53          value = "1" />

54      <pass0>

55          <renderstates>

56              <D3DRS_CULLMODE type = "D3DCULL"
57                  value = "D3DCULL_NONE" />

58          </renderstates>

59      <vertexshader>

60          <shader type = "string"
61              value = "vs.1.1
62                  mov oT0, v7

63                  mul r0,    v0.x, c10
64                  mad r0,    v0.y, c11, r0
65                  mad r0,    v0.z, c12, r0
66                  mad oPos,  v0.w, c13, r0

67                  mul r0.xyz, v3.x, c4
68                  mad r0.xyz, v3.y, c5, r0
69                  mad r0.xyz, v3.z, c6, r0

70                  dp3 r0.w, r0.xyz, r0.xyz
71                  rsq r0.w, r0.w
72                  mul r0,    r0, r0.w
73                  sge r0.w, r0.w, r0.w

74                  mul r1, v0.x, c4
75                  mad r1, v0.y, c5, r1
76                  mad r1, v0.z, c6, r1
77                  mad r1, v0.w, c7, r1

78                  dp3 r1.w, r1.xyz, r1.xyz
79                  rsq r1.w, r1.w
80                  mul r1,    r1, r1.w
81                  sge r1.w, r1.w, r1.w

82                  dp3 r2, r0, r1
83                  add r2, r2, r2
84                  mul r4.xyz, r1, r2
85                  add oT1.xyz, r0, -r4
86                  sge oT1.w, r0.w, r0.w
```

```
87             mov oD0, v5
88             mov oD1, v5 " />

89             <handle type = "uint"
90             function = "compile_dx8_vs( ../shader )" />

91             <equation type = "string"
92             value = "dp3 R_DOT2, R_EYE_VECTOR,
R_EYE_NORMAL
93             add R_DOT2, R_DOT2, R_DOT2
94             mul R_EYE_NORMAL, R_EYE_NORMAL,
R_DOT2
95             add oT0, R_EYE_VECTOR, -R_EYE_NORMAL
96             mov oT0.w, c[CV_ONE].x " />

97             <mapping>

98             <v6 type = "string"
99             value = "position" />

100            <v3 type = "string"
101            value = "normal" />

102            <v5 type = "string"
103            value = "diffuse" />

104            <v7 type = "string"
105            value = "tex0" />

106            </mapping>

107            <constants>

108            <c20 type = "vector4"
109            value = "0.500000 0.500000 0.500000 0.000000" />

110            <c10 type = "matrix4"
111            link = "parameters/transforms/mvp" />

112            <c4 type = "matrix4"
113            function = "PostMul( parameters/transforms/world,
parameters/transforms/view )" />

114            </constants>

115            </vertexshader>
```

```
116      <pixelshader>

117          <smooth_shader type = "string"
118              value = "ps.1.1
119                  tex t0
120                  tex t1
121                  tex t2

122                  sub r0, t0, t1
123                  dp3 r0, r0, r0

124                  sub r1, t2, t1
125                  dp3 r1, r1, r1

126                  sub t0.a, r0.a, r1.a

127                  add_sat r0.a, t0.a, c0.a

128                  cnd r0, r0.a, t0, t2

129                  lrp r0.rgb, t1.a, t1, r0
130                  + mov r0.a, t1.a " />

131      <shader type = "string"
132          value = "ps.1.1

133          tex t0
134          tex t1
135          mul_x2_sat r1, 1-t0.a, c0.a
136          mad_sat r0, r1, t1, t0" />

137      <DVC_shader type = "string"
138          value = "ps.1.1
139          tex t0

140          dp3_sat r0, t0, c0

141          sub_sat r1, t0, r0

142          mad_sat r0, c1.a, r1, t0 " />

143      <handle type = "uint"
144          function = "compile_dx8_ps( ../shader )" />

145      <constants>
```

```
146         <c0 type = "vector4"
147             function = "Construct_vector4_floats( float( 0.11 ),
148                 float( 0.20 ),
149                 float( 0.59 ),
150                 sfx/[self]/settings/shininess )" />

151         <c1 type = "vector4"
152             function = "Construct_vector4_floats( float( 0.5 ),
153                 float( 0.5 ),
154                 float( 0.5 ),
155                 float( 0.8 ) ) " />

156     </constants>

157 </pixelshader>

158 <texturestages>

159     <stage0>

160         <D3DTSS_MINFILTER type =
161             "D3DTEXTUREFILTERTYPE"
162             value = "D3DTEXF_LINEAR" />

163         <D3DTSS_MIPFILTER type =
164             "D3DTEXTUREFILTERTYPE"
165             value = "D3DTEXF_LINEAR" />

166         <D3DTSS_MAGFILTER type =
167             "D3DTEXTUREFILTERTYPE"
168             value = "D3DTEXF_LINEAR" />

169     </stage0>

170     <stage1>

171         <D3DTSS_MINFILTER type =
172             "D3DTEXTUREFILTERTYPE"
173             value = "D3DTEXF_LINEAR" />

174         <D3DTSS_MIPFILTER type =
175             "D3DTEXTUREFILTERTYPE"
176             value = "D3DTEXF_LINEAR" />

177         <D3DTSS_MAGFILTER type =
178             "D3DTEXTUREFILTERTYPE"
179             value = "D3DTEXF_LINEAR" />

180     </stage1>

181 </texturestages>
```

```
173             value = "D3DTEXF_LINEAR" />
174         </stage1>
175     </texturestages>
176     <textures>
177         <t0 type = "uint"
178             link =
179                 "parameters/object/texture/diffuse/_2D/R8G8B8A8/handle" />
180         <t1 type = "uint"
181             link =
182                 "parameters/object/texture/normal/_2D/R8G8B8A8/handle" />
183     </textures>
184 </pass0>
185 </passes>
186 </imp1>
187 <imp2>
188     <priority type = "float"
189         value = "0.500000" />
190     <description type = "string"
191         value = "Shiny with Gloss Alpha Channel Fixed Function" />
192     <requirements>
193         <os type = "bool"
194             function = "GreaterEqual_float( parameters/os/version, float(
195                 5.0 ) )" />
196         <CubeTextureSupport type = "bool"
197             function = "AllSet( D3DCAPS8/TextureCaps, bitset(
198                 D3DPTTEXTURECAPS_CUBEMAP ) )" />
199         <api type = "bool"
200             function = "GreaterEqual_float( parameters/api/version, float(
201                 8.0 ) )" />
202         <TextureSupport type = "bool"
```

```
198             function = "GreaterEqual_uint(  
D3DCAPS8/MaxSimultaneousTextures, uint( 2 ) )" />  
199         </requirements>  
200     <passes>  
201         <passCount type = "uint"  
202             value = "1" />  
203     <pass0>  
204         <renderstates>  
205             <D3DRS_CULLMODE type = "D3DCULL"  
206                 value = "D3DCULL_NONE" />  
207             <D3DRS_TEXTUREFACTOR type = "uint"  
208                 function = "vector4_to_d3dcolor(  
Construct_vector4_floats( float( 0.0 ),  
209                     float( 0.0 ),  
210                     float( 0.0 ),  
211                     sfx/[self]/settings/shininess ) )" />  
212         </renderstates>  
213     <transforms>  
214         <D3DTS_WORLD type = "matrix4"  
215             link = "parameters/transforms/world" />  
216         <D3DTS_VIEW type = "matrix4"  
217             link = "parameters/transforms/view" />  
218         <D3DTS_PROJECTION type = "matrix4"  
219             link = "parameters/transforms/projection" />  
220         <D3DTS_TEXTURE1 type = "matrix4"  
221             function = "Transpose( parameters/transforms/world )" />  
222     </transforms>  
223     <vertexshader>  
224         <handle type = "uint"  
225             link = "parameters/object/vertex/FVF" />
```

```
226          </vertexshader>
227          <texturestages>
228              <stage0>
229                  <D3DTSS_MINFILTER type =
230                  "D3DTEXTUREFILTERTYPE"
231                      value = "D3DTEXF_LINEAR" />
232                  <D3DTSS_MIPFILTER type =
233                  "D3DTEXTUREFILTERTYPE"
234                      value = "D3DTEXF_LINEAR" />
235                  <D3DTSS_MAGFILTER type =
236                  "D3DTEXTUREFILTERTYPE"
237                      value = "D3DTEXF_LINEAR" />
238                  <D3DTSS_COLORARG1 type = "D3DTA"
239                  value = "D3DTA_TEXTURE" />
240                  <D3DTSS_COLOROP type = "D3DTEXTUREOP"
241                  value = "D3DTOP_SELECTARG1" />
242                  <D3DTSS_ALPHAARG1 type = "D3DTA"
243                  value = "D3DTA_TEXTURE |
244                  D3DTA_COMPLEMENT" />
245                  <D3DTSS_ALPHAOP type = "D3DTEXTUREOP"
246                  value = "D3DTOP_MODULATE2X" />
247                  <D3DTSS_ALPHAARG2 type = "D3DTA"
248                  value = "D3DTA_TFACTOR" />
249              </stage0>
250              <stage1>
251                  <D3DTSS_TEXCOORDINDEX type = "D3DTSS_TCI"
252                  value =
253                  "D3DTSS_TCI_CAMERASPACEREFLECTIONVECTOR | 1" />
254                  <D3DTSS_TEXTURETRANSFORMFLAGS type =
255                  "D3DTEXTURETRANSFORMFLAGS"
256                      value = "D3DTTFF_COUNT3" />
257              </stage1>
258          </texturestages>
259      </vertexshader>
```

```
251          <D3DTSS_MINFILTER type =  
          "D3DTEXTUREFILTERTYPE"  
252          value = "D3DTEXF_LINEAR" />  
  
253          <D3DTSS_MIPFILTER type =  
          "D3DTEXTUREFILTERTYPE"  
254          value = "D3DTEXF_LINEAR" />  
  
255          <D3DTSS_MAGFILTER type =  
          "D3DTEXTUREFILTERTYPE"  
256          value = "D3DTEXF_LINEAR" />  
  
257          <D3DTSS_COLORARG0 type = "D3DTA"  
258          value = "D3DTA_CURRENT" />  
  
259          <D3DTSS_COLORARG1 type = "D3DTA"  
260          value = "D3DTA_TEXTURE" />  
  
261          <D3DTSS_COLORARG2 type = "D3DTA"  
262          value = "D3DTA_CURRENT |  
          D3DTA_ALPHAREPLICATE" />  
  
263          <D3DTSS_COLOROP type = "D3DTEXTUREOP"  
264          value = "D3DTOP_MULTIPLYADD" />  
  
265          <D3DTSS_ALPHAOP type = "D3DTEXTUREOP"  
266          value = "D3DTOP_SELECTARG1" />  
  
267          <D3DTSS_ALPHAARG1 type = "D3DTA"  
268          value = "D3DTA_CURRENT" />  
  
269      </stage1>  
  
270  </texturestages>  
  
271  <pixelshader>  
272  </pixelshader>  
  
273  <textures>  
  
274      <t0 type = "uint"  
275      link =  
      "parameters/object/texture/diffuse/_2D/R8G8B8A8/handle" />  
  
276      <t1 type = "uint"
```

```
277             link =  
"parameters/locale/texture/environment/cube/R8G8B8A8/handle" />  
278         </textures>  
279     </pass0>  
280 </passes>  
281 </imp2>  
282 <imp3>  
283     <priority type = "float"  
284         value = "0.600000" />  
285     <description type = "string"  
286         value = "Shiny with Gloss Alpha Channel Fixed Function" />  
287     <requirements>  
288         <os type = "bool"  
289             function = "GreaterEqual_float( parameters/os/version, float(  
5.0 ) )" />  
290         <CubeTextureSupport type = "bool"  
291             function = "AllSet( D3DCAPS8/TextureCaps, bitset(  
D3DPTTEXTURECAPS_CUBEMAP ) )" />  
292         <api type = "bool"  
293             function = "GreaterEqual_float( parameters/api/version, float(  
8.0 ) )" />  
294         <TextureSupport type = "bool"  
295             function = "GreaterEqual_uint(  
D3DCAPS8/MaxSimultaneousTextures, uint( 2 ) )" />  
296     </requirements>  
297 </passes>  
298     <passCount type = "uint"  
299         value = "1" />  
300 <pass0>  
301     <renderstates>
```

```
302         <D3DRS_CULLMODE type = "D3DCULL"
303             value = "D3DCULL_NONE" />

304         <D3DRS_TEXTUREFACTOR type = "uint"
305             function = "vector4_to_d3dcolor(
Construct_vector4_floats( float( 0.0 ),
306                         float( 0.0 ),
307                         float( 0.0 ),
308                         sfx/[self]/settings/shininess ) )" />

309     </renderstates>

310     <transforms>

311         <D3DTS_WORLD type = "matrix4"
312             link = "parameters/transforms/world" />

313         <D3DTS_VIEW type = "matrix4"
314             link = "parameters/transforms/view" />

315         <D3DTS_PROJECTION type = "matrix4"
316             link = "parameters/transforms/projection" />

317         <D3DTS_TEXTURE1 type = "matrix4"
318             function = "Transpose( parameters/transforms/world )" />

319     </transforms>

320     <vertexshader>

321         <handle type = "uint"
322             link = "parameters/object/vertex/FVF" />

323     </vertexshader>

324     <texturestages>

325         <stage0>

326             <D3DTSS_MINFILTER type =
"D3DTEXTUREFILTERTYPE"
327                 value = "D3DTEXF_LINEAR" />

328             <D3DTSS_MIPFILTER type =
"D3DTEXTUREFILTERTYPE"
329                 value = "D3DTEXF_LINEAR" />
```

```
330          <D3DTSS_MAGFILTER type =  
          "D3DTEXTUREFILTERTYPE"  
331          value = "D3DTEXF_LINEAR" />  
  
332          <D3DTSS_COLORARG1 type = "D3DTA"  
333          value = "D3DTA_TEXTURE" />  
  
334          <D3DTSS_COLOROP type = "D3DTEXTUREOP"  
335          value = "D3DTOP_SELECTARG1" />  
  
336          <D3DTSS_ALPHAARG1 type = "D3DTA"  
337          value = "D3DTA_TFACTOR" />  
  
338          <D3DTSS_ALPHAOP type = "D3DTEXTUREOP"  
339          value = "D3DTOP_MODULATE2X" />  
  
340          <D3DTSS_ALPHAARG2 type = "D3DTA"  
341          value = "D3DTA_TEXTURE" />  
  
342      </stage0>  
  
343      <stage1>  
  
344          <D3DTSS_TEXCOORDINDEX type = "D3DTSS_TCI"  
345          value =  
          "D3DTSS_TCI_CAMERASPACEREFLECTIONVECTOR | 1" />  
  
346          <D3DTSS_TEXTURETRANSFORMFLAGS type =  
          "D3DTEXTURETRANSFORMFLAGS"  
347          value = "D3DTTFF_COUNT3" />  
  
348          <D3DTSS_MINFILTER type =  
          "D3DTEXTUREFILTERTYPE"  
349          value = "D3DTEXF_LINEAR" />  
  
350          <D3DTSS_MIPFILTER type =  
          "D3DTEXTUREFILTERTYPE"  
351          value = "D3DTEXF_LINEAR" />  
  
352          <D3DTSS_MAGFILTER type =  
          "D3DTEXTUREFILTERTYPE"  
353          value = "D3DTEXF_LINEAR" />  
  
354          <D3DTSS_COLORARG0 type = "D3DTA"  
355          value = "D3DTA_CURRENT" />
```

```
356         <D3DTSS_COLOROP type = "D3DTEXTUREOP"  
357             value =  
            "D3DTOP_MODULATEALPHA_ADDCOLOR" />  
  
358         <D3DTSS_COLORARG1 type = "D3DTA"  
359             value = "D3DTA_TEXTURE" />  
  
360         <D3DTSS_ALPHAARG1 type = "D3DTA"  
361             value = "D3DTA_TEXTURE" />  
  
362         <D3DTSS_ALPHAOP type = "D3DTEXTUREOP"  
363             value = "D3DTOP_SELECTARG1" />  
  
364     </stage1>  
  
365 </texturestages>  
  
366 <pixelshader>  
367 </pixelshader>  
  
368 <textures>  
  
369     <t0 type = "uint"  
370         link =  
        "parameters/object/texture/diffuse/_2D/R8G8B8A8/handle" />  
371     <t1 type = "uint"  
372         link =  
        "parameters/locale/texture/environment/cube/R8G8B8A8/handle" />  
  
373 </textures>  
  
374 </pass0>  
  
375 </passes>  
  
376 </imp3>  
  
377 </dx8>  
  
378 <ogl>  
  
379 <imp1>  
  
380     <element name = "priority"  
381         type = "float"  
382         value = "1.000000" />
```

```
383         <element name = "description"
384             type = "string"
385             value = "Shiny with Gloss Alpha Channel" />

386     <requirements>

387         <element name = "os"
388             type = "bool"
389             function = "GreaterEqual_float( parameters/os/version, float(
5.0 ))" />

390         <element name = "api"
391             type = "bool"
392             function = "GreaterEqual_float( parameters/api/version, float(
1.0 ))" />

393         <element name = "registerCombinerSupport"
394             type = "bool"
395             function = "RequiredNumRegisterCombiners(uint(2))" />

396     <extensions>
397         <element name = "GL_NV_vertex_program"
398             type = "bool"
399             function =
"InitExtension(string(GL_NV_vertex_program))" />

400         <element name = "GL_NV_register_combiners"
401             type = "bool"
402             function =
"InitExtension(string(GL_NV_register_combiners))" />

403         <element name = "GL_ARB_texture_compression"
404             type = "bool"
405             function =
"InitExtension(string(GL_ARB_texture_compression))" />

406         <element name = "GL_EXT_texture_compression_s3tc"
407             type = "bool"
408             function =
"InitExtension(string(GL_EXT_texture_compression_s3tc))" />

409     </extensions>

410 </requirements>

411 <textureHandles>
```

```
412      <handle0>

413          <element name = "name"
414              type = "string"
415              value = "decalTex" />

416          <element name = "handle"
417              type = "GLuint"
418              function = "sfx_glGenTexture()" />

419          <element name = "data"
420              type = "sfxTexData"
421              function =
422          "LoadTextureDataFromFile(string(stonearchaic.tga),string(rgb))" />

423          <element name = "mipmap"
424              type = "bool"
425              value = "true" />

426          <element name = "target"
427              type = "sfx_GLenum"
428              value = "GL_TEXTURE_2D" />

429          <element name = "internalFormat"
430              type = "sfx_GLenum"
431              value = "GL_RGB8" />

432          <element name = "externalFormat"
433              type = "sfx_GLenum"
434              value = "GL_RGB" />

435          <element name = "dataType"
436              type = "sfx_GLenum"
437              value = "GL_UNSIGNED_BYTE" />
438      </handle0>

439      <handle1>
440          <element name = "name"
441              type = "string"
442              value = "envmap" />

443          <element name = "data"
444              type = "sfxTexData"
445              function =
446          "LoadTextureDataFromFile(string(sky_cube_mipmap.dds),string(null))" />
```

```
447         <element name = "mipmap"
448             type = "bool"
449             value = "true" />
450
451         <element name = "target"
452             type = "sfx_GGLenum"
453             value = "GL_TEXTURE_CUBE_MAP_EXT" />
454
455         <element name = "GL_TEXTURE_WRAP_S"
456             type = "sfx_GGLenum"
457             value = "GL_CLAMP_TO_EDGE" />
458
459         <element name = "GL_TEXTURE_WRAP_T"
460             type = "sfx_GGLenum"
461             value = "GL_CLAMP_TO_EDGE" />
462
463         <element name = "GL_TEXTURE_WRAP_R"
464             type = "sfx_GGLenum"
465             value = "GL_CLAMP_TO_EDGE" />
466
467         <element name = "GL_TEXTURE_MIN_FILTER"
468             type = "sfx_GGLenum"
469             value = "GL_LINEAR" />
470
471         <element name = "GL_TEXTURE_MAG_FILTER"
472             type = "sfx_GGLenum"
473             value = "GL_LINEAR" />
474
475     </handle1>
476
477 </textureHandles>
478
479 <passes>
480
481     <element name = "passCount"
482         type = "uint"
483         value = "1" />
484
485     <pass0>
486         <transforms>
487             <model type = "matrix4"
488                 link = "parameters/transforms/world" />
489
490             <view type = "matrix4"
491                 link = "parameters/transforms/view" />
```

```
480         <projection type = "matrix4"
481         link = "parameters/transforms/projection" />

482     </transforms>

483     <vertexshader>

484         <mapping>

485             <element name = "v[OPOS]"
486             type = "string"
487             value = "position" />

488             <element name = "v[NRML]"
489             type = "string"
490             value = "normal" />

491             <element name = "v[COL0]"
492             type = "string"
493             value = "diffuse" />

494             <element name = "v[TEX0]"
495             type = "string"
496             value = "tex0" />

497         </mapping>

498         <element name = "shader"
499         type = "string"
500         value = "!!VP1.0
501             MOV o[TEX0], v[TEX0];
502             DP4 o[HPOS].x, c[0], v[OPOS];
503             DP4 o[HPOS].y, c[1], v[OPOS];
504             DP4 o[HPOS].z, c[2], v[OPOS];
505             DP4 o[HPOS].w, c[3], v[OPOS];

506             DP4 R0.x, c[8], v[NRML];
507             DP4 R0.y, c[9], v[NRML];
508             DP4 R0.z, c[10], v[NRML];
509             DP3 R0.w, R0, R0;
510             RSQ R0.w, R0.w;
511             MUL R0, R0, R0.w;
512             SGE R0.w, R0.w, R0.w;

513             DP4 R1.x, c[4], v[OPOS];
514             DP4 R1.y, c[5], v[OPOS];
```

```
515          DP4 R1.z, c[6], v[OPOS];
516          DP4 R1.w, c[7], v[OPOS];
517          DP3 R1.w, R1, R1;
518          RSQ R1.w, R1.w;
519          MUL R1, R1, R1.w;
520          SGE R1.w, R1.w, R1.w;

521          DP3 R2, R0, R1;
522          ADD R2, R2, R2;
523          MUL R4.xyz, R1, R2;
524          ADD o[TEX1].xyz, R0, -R4;
525          SGE o[TEX1].w, R0.w, R0.w;
526          MOV o[COL0], v[COL0];
527          MOV o[COL1], v[COL0];
528          END" />
529      <element name = "handle"
530          type = "ogl_vs_handle"
531          function = "compile_ogl_vs_handle( ../shader )" />

532      <constants>
533          <element name = "c0"
534              type = "nvTrackMatrixParams"
535              value = "GL_MODELVIEW_PROJECTION_NV
GL_IDENTITY_NV" />

536          <element name = "c4"
537              type = "nvTrackMatrixParams"
538              value = "GL_MODELVIEW GL_IDENTITY_NV"
/>

539          <element name = "c8"
540              type = "nvTrackMatrixParams"
541              value = "GL_MODELVIEW
GL_INVERSE_TRANSPOSE_NV" />

542      </constants>

543  </vertexshader>

544  <textures>

545      <unit0>

546          <element name = "handle"
547              type = "string"
548              link =
"sfx/[self]/imps/ogl/imp1/textureHandles/handle0/name" />
```

```
549          </unit0>

550          <unit1>
551              element name = "handle"
552              type = "string"
553              link =
554                  "sfx/[self]/imps/ogl/imp1/textureHandles/handle1/name" />
555          </unit1>
556      </textures>

556      <registercombiners>
557          <constants>

558              <element name = "const0"
559                  type = "vector4"
560                  function = "Construct_vector4_floats( float( 0.0 ),
561                      float( 0.0 ),
562                      float( 0.0 ),
563                      sfx/[self]/settings/shininess )" />
564          </constants>

565          <element name = "nvparseInlineRegisterCombiner"
566              type = "string"
567              value = "!!RC1.0
568              {
569                  rgb {
570                      spare0 = unsigned_invert(tex0.a) * const0.a;
571                      scale_by_two();
572                  }
573              }
574              {
575                  rgb {
576                      discard = unsigned(spare0)*tex1;
577                      discard = tex0;
578                      spare0 = sum();
579                  }
580              }
581              out.rgb = spare0; " />

582          <element name = "handle"
583              type = "ogl_rc_handle"
584              function = "compile_ogl_rc_handle(
585                  ../nvparseInlineRegisterCombiner )" />

585      </registercombiners>

586  </pass0>
```

587 </passes>

588 </impl>

589 </ogl>

590 </imps>

591</depot>

CLAIMS

What is claimed is:

1. A system for generating a shader program, comprising:
an interface; and
an application program for working in conjunction with the interface to process a file;
wherein a shader program is capable of being generated based on the processing of the file to apply a graphics effect to an object.
2. The system as recited in claim 1, wherein the file includes a plurality of interface data capable of being processed to generate the shader program for different graphics application program interfaces.
3. The system as recited in claim 1, wherein the file includes a plurality of implementation data capable of being processed to generate the shader program for different hardware graphics pipeline platforms.
4. The system as recited in claim 1, wherein the file is written in an extensible markup language (XML).
5. The system as recited in claim 1, wherein at least one of the processing, and the generating is carried out utilizing a plug-in.
6. The system as recited in claim 1, wherein the processing is carried out utilizing an interface.
7. The system as recited in claim 6, wherein the interface includes a Component Object Model (COM) interface.

8. The system as recited in claim 6, wherein the processing includes initializing the interface.
9. The system as recited in claim 1, wherein the processing includes registering at least one of custom types and custom functions, the shader program being generated based on the at least one of registered custom types and custom functions.
10. The system as recited in claim 1, wherein the processing includes selecting one of a plurality of objects.
11. The system as recited in claim 1, wherein the processing includes selecting one of a plurality of graphics effects.
12. The system as recited in claim 1, wherein the processing includes determining whether more than one render pass exists, and selecting another render pass if more than one render pass exists.
13. The system as recited in claim 1, wherein the processing includes determining whether more than one object exists, and selecting another object if more than one object exists.
14. The system as recited in claim 1, wherein a default set of requirements is included in the file.
15. The system as recited in claim 1, wherein the shader program is capable of being altered by tweaking the file.
16. The system as recited in claim 1, wherein the file includes a syntax including at least one of a name, a type and a content.

17. The system as recited in claim 1, wherein the file is capable of referencing both compiled and un-compiled code.
18. A computer program product for generating a shader program, comprising:
computer code for selecting a file associated with a graphics effect;
computer code for processing the file; and
computer code for generating the shader program based on the processing of the file to apply the graphics effect to an object.
19. A data structure stored in memory, comprising:
a file identifying a graphics effect;
wherein a shader program is capable of being generated based on the file.