

DOCKING INTERFACE FOR PORTABLE DEVICE

FIELD OF THE INVENTION

The present invention relates to a low profile interface for portable
5 electronic devices. In particular, the present invention pertains to a low
profile, versatile and reliable interface for docking portable electronic
devices with a docking station to facilitate recharging of power source,
auxiliary power and transfer of data.

BACKGROUND OF THE INVENTION

10 Portable electronic devices such as cellular telephones, electronic
organizers and lately audio players have achieved reduction in size and
weight while offering increased functions as a result of advances in
semiconductor designs. A bottle neck to further miniaturization in portable
15 electronic devices is the availability of reliable and low profile docking
interface for the purposes of recharging of power source and transfer of
data. At the same time, the incentive to reduce the size and weight
continues to grow for portable electronic devices.

20 Existing docking interface for portable electronic devices comprises of well
known male and female connectors whose high profile poses severe
constraints in size reduction and design consideration. Other existing
docking interface for portable electronic devices are less reliable as the
contacts are exposed to ambient environment and electrical connectivity
25 are not assured after a period of repeated usage.

OBJECT OF THE INVENTION

It is an object of the present invention to feature a low profile and reliable docking interface for portable electronic devices in order to meet size and weight design considerations.

5

It is a further object of the present invention to feature a low profile and reliable docking interface for portable electronic devices to facilitate the recharging of power source and transfer of data.

10 It is yet another object of the present invention to feature a low profile and reliable docking interface for portable electronic devices that are not only economical but also sourceable readily.

SUMMARY OF THE INVENTION

15 The present invention is a docking interface for portable electronic devices that feature at least a printed circuit board (PCB) contact and a set of spring loaded contact pins for facilitating the recharging of power source and transfer of data between the devices and their hosts. Because of the thickness of a PCB and the retraction of the spring loaded pins, the overall
20 profile of the present invention is reduced to a minimum. At the same time, the reliability of the contact between the portable device and the docking station is assured. As such, the present invention offers an economical and reliable solution for docking interface in portable electronic devices that permit further reduction in size and weight without imposing
25 constraints on the availability of increased functionality.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top, right side, elevational and perspective view of a portable electronic device incorporating the present invention.

5 FIG. 2 is a top, right side, elevational and perspective view of a docking station incorporating the present invention.

FIG. 3 is top, right side, elevational and exploded perspective view of the various components of the portable device in FIG. 1.

10

FIG. 4 is a top, right side, elevational and perspective view of the PCB contact and the cover docking of the present invention.

FIG. 5 is a right side, plan view of the PCB contact and the cover docking in

15 FIG. 4.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 is a top, right side, elevational and perspective view of a portable electronic device 30 incorporating the present invention. The portable
20 device 30 is a new product code name Nomad 2 that will soon be produced by the applicant of the present invention. It is a device for downloading compressed audio data; the device also records such data and replays the uncompressed data.

Like most modern portable electronic devices, the portable device 30 is compact, lightweight and versatile. It fits neatly in the palm of any user, and the controls and key buttons enable the user to activate various functions by maneuvering the fingers of one's hand. As will be elaborated
5 in the detailed description of FIGS. 1 to 3, the portable electronic device 30 achieves its size and weight by overcoming the limitations of prior art docking interface.

Referring again to FIG. 1, the portable device 30 features at the bottom a
10 docking base 24 with a plurality of openings 31 for exposing a plurality of contacts of a docking PCB 26 (See, FIG. 4 for details). The portable electronic device 30 cooperates with a docking station 40 as illustrated in FIG. 2. The docking station 40 comprises a receptacle 35 that contours the rear, side and bottom portions of the portable electronic device 30. A
15 series of spring loaded contacts 37 disposed at the bottom of the receptacle 35 mates with the docking PCB 26 of the portable electronic device 30 for providing auxiliary power, recharging the power source and transferring data between the device 30 and a host (not shown but understood). The docking PCB 26 and the spring loaded contacts 37
20 comprise one of the novel features of the present invention. By docking PCB, the present invention refers to a general class of thin film contacts for achieving low profile interface in electronic devices. The present invention envisage the PCB to be either rigid or semi rigid.

In FIG. 2, a lock pin 36 is disposed near the top portion of the receptacle 35 of the docking station 30 for fixing the portable electronic device 30 (not shown but understood) onto the spring loaded contacts 37. Without the lock pin 36, the docking PCB 26 may not engage the spring loaded contacts 37 each and every occasion.

FIG. 3 is top, right side, elevational and exploded perspective view of the various components of the electronic portable device 30 as shown in FIG. 1. The portable electronic device 30 comprises a front cab 3, a rear cab 17, a battery cover 21, printed circuit boards 7 and 9, key and function pads 4 and 5, the docking PCB 26 coupled with the printed circuit boards with a flexible cable 27, a docking cover 23 that doubles as a batter compartment, a docking cover 24 and a plurality of knobs and controls 11, 12, and 16. The portable electronic device 30 further comprises a Universal Serial Bus (USB) jack 44 disposed on the print circuit board 9 for interfacing with a personal computer or similar controller. Through the USB jack, compressed audio data such as MP3 music are downloaded onto the device 30 and subsequently replayed. A battery 28 provides power source for the portable electronic device 30. Again in FIG. 3, protective covers such as a LCD panel 2, a LCD cushion 6, a USB cover 14 are also provided to secure critical areas of the print circuit board. As mentioned above, a lock pin 36 disposed on docking station 40 fixes the portable electronic device 30 onto the receptacle 35. An opening 43 which mates with the lock pin 36 is disposed on the rear cab 17 for accomplishing this important task. Optionally, a belt clip 18 may be affixed

onto the rear portion of the rear cab 17 with a screw 19 for allowing the user to carry the device 30 on his or her belt.

FIG. 4 is a top, right side, elevational and perspective view of the docking
5 PCB 26 and the docking cover 23 of the present invention. Not shown but understood by one skilled in the art is the flexible cable that connects the print circuit boards and the docking PCB. The docking cover 23 receives the battery 28 (not shown) that provides the power source of the portable electronic device 30 when it is not being recharged. In the preferred
10 embodiment of the present invention, the docking PCB 26 features eight contact pads 32, 33, 34, 38, 39, 41 and 42 respectively. Contacts 32, 34, 38 and 41 are for facilitating the transfer of signals, while contacts 33 and 42 are for the terminals of the battery 28 (not shown). Finally, contacts 39 are the power and ground contacts of the device 30. The docking base 24
15 is coupled to the exterior facing of the docking cover 23 for providing protective cover for the docking PCB 26.

FIG. 5 is a right side, plan view of the docking PCB and the docking cover in FIG. 4. When the portable electronic device 30 is fully assembled, the
20 docking PCB 26 is disposed in a narrow gap of about 1.1mm between the docking cover 23 and the docking base 24. The applicant has found it virtually impossible to identify a prior art connector or interface that will provide such a low profile and reliable interface for the device 30 until it came up with the present invention.

The present invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The presently disclosed embodiments are, therefore, to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by
5 the appended claims and all changes which come within the meaning and range of equivalency of the claims are, therefore, to be embraced therein.

CLAIMS

1. A docking interface for portable device, said device having at least one printed circuit board and at least one source of power, said device further comprising:

at least one docking printed circuit board (PCB) disposed on said device and having a plurality of contact pads for signals and power;

at least one series of spring loaded contacts disposed on a docking station and having the same number contacts as that of contact pads on said docking PCB,

such that said portable device is recharged and draws power source from said docking station reliably.

2. A docking interface for portable device, said device having at least one printed circuit board and at least one source of power, said device further comprising:

at least one docking printed circuit board (PCB) disposed on said device and having a plurality of contact pads for signals and power;

at least one series of spring loaded contacts disposed on a docking station and having the same number of contacts as that of contact pads on said docking PCB; and

at least one lock pin disposed on said docking station for positioning the portable device optimally, such that said portable device is recharged and draws power source from said docking station reliably.

3. A portable device comprising: a low profile docking interface for mating with an external docking station, the docking interface including:

at least one docking printed circuit board, the docking printed circuit board having a plurality of thin-film contact pads for electrically coupling directly with one or more contact pins formed in the external docking station for transferring signals and power therebetween;

a docking cover; and

a docking base coupled with the docking cover with a narrow gap therebetween, in which the docking printed circuit board is mounted, the docking

base being coupled to an exterior facing of the docking cover so that the docking cover and the docking base provides a protective cover for the docking printed circuit board; wherein the docking cover doubles as a battery compartment.

5 4. A portable device as claimed in claim 3, wherein the contact pads are at an end of the docking printed circuit board.

5. A portable device as claimed in claim 3, wherein the docking base has a plurality of openings therethrough for exposing the plurality of thin-film contact pads,
10 the number of openings being the same as the number of thin-film contact pads.

6. A portable device as claimed in claim 4, wherein the docking base has a plurality of openings therethrough for exposing the plurality of thin-film contact pads, the number of openings being the same as the number of thin-film contact pads.

15 7. A portable device as claimed in claim 6, wherein the contact pads are at an end of the docking printed circuit board.

8. A low profile docking interface for a portable device for docking with an
20 external docking station, the low profile docking interface comprising:

a docking printed circuit board with one or more thin film contact pads for electrically coupling directly with one or more contacts formed in an external docking station for transferring signals and power therebetween;

a docking cover with an exterior facing; and

25 a docking base coupled to the exterior facing of the docking cover with the docking printed circuit board being mounted in a narrow gap formed between the docking cover and the docking base for providing a protective cover for the docking printed circuit board;

wherein the docking cover doubles as a battery compartment.

30 9. A docking interface as claimed in claim 8, wherein the contact pads are at an end of the docking printed circuit board.

10

10. A docking interface as claimed in claim 8, wherein the docking base has a plurality of openings therethrough for exposing the plurality of thin-film contact pads, the number of openings being the same as the thin-film contact pads.

5 11. A docking interface as claimed in claim 10, wherein the contact pads are at an edge of the docking printed circuit board.

12. A docking station for use with a portable device, the portable device having a rear portion, a side portion, and a bottom portion, the portable device having a
10 docking interface comprising:

a docking printed circuit board with one or more thin film contact pads;

a docking cover with an exterior facing; and

a docking base coupled to the exterior facing of the docking cover with the
docking printed circuit board being mounted in a narrow gap formed between the
15 docking cover and the docking base for providing a protective cover for the docking
printed circuit board;

wherein the docking cover doubles as a battery compartment;

wherein the docking station includes a receptacle with a rear surface, a side
surface and a bottom surface, the rear surface, the side surface, and the bottom
20 surface contouring the rear portion, the side portion, and the bottom portion of the
portable device, the receptacle having a pin disposed adjacent to a top portion of
the receptacle for fixing the portable device in the receptacle and in such a manner
that the contact pads electrically couple directly with one or more spring loaded
contacts mounted in the bottom surface of the receptacle.

25

13. A docking station as claimed in claim 12, wherein the receptacle has an open front.

ABSTRACT

DOCKING INTERFACE FOR PORTABLE DEVICE

5 The present invention is a docking interface for portable electronic devices that feature at least a printed circuit board (PCB) contact and a set of spring loaded contact pins for facilitating the recharging of power source and transfer of data between the devices and their hosts. Because of the thickness of a PCB and the retraction of the spring loaded pins, the overall profile of the present invention is reduced to a minimum. At the same time, the reliability of the contact between the 10 portable device and the docking station is assured. As such, the present invention offers an economical and reliable solution for docking interface in portable electronic devices that permit further reduction in size and weight without imposing constraints on the availability of increased functionality.

15

Fig. 4