

A GESTURE BASED SYSTEM FOR TRANSLATION AND TRANSLITERATION OF INPUT TEXT AND A METHOD THEREOF

CROSS REFERENCE TO RELATED APPLICATIONS

5 [0001] This patent application claims the priority of the Indian Provisional
entitled "METHOD AND SYSTEM FOR REAL TIME LANGUAGE
TRANSLATION AND TRANSLITERATION", with serial number.
3161/MUM/2013 filed at Government of India Patent Office on 4th October, 2013,
the contents of which is incorporated by reference herein.

10

BACKGROUND

Technical Field

[0002] The present disclosure relates to the field of user interfaces.
Particularly, the present disclosure relates to Indian language interfaces. More
15 particularly, the present disclosure relates to user interfaces with translation and
transliteration capabilities.

Description of the Related Art

[0003] In view of the recent technological advancements in the domain of
communication, there has been a substantial increase in the number of people using
20 mobile phones for the purpose of communicating with one other. Mobile phones

available in the market today enable users to verbally communicate with one another, and also enable users to exchange text messages.

[0004] Further, some of the mobile phones also provide users with machine
5 translation facilities. Typically, machine translation facilities are provided on mobile phones as separate, installable software applications. Further, a user also has the option of accessing the World Wide Web on his mobile phone to avail the machine translation facilities provided on the internet.

10 [0005] However, one of the drawbacks associated with prior-art machine translation facilities and applications thereof is that these applications are not integrated with the operating system of the mobile phone and in order to make use of these facilities to get the input text translated, the user will have to manually copy the input text and feed the same to the translation application. The aforementioned
15 process of availing machine translation on prior art translation facilities (applications) not only makes the translation process cumbersome and difficult to implement.

[0006] To alleviate the aforementioned problems and to simplify the entire process of translation/transliteration of input text, US Patent Application Publication
20 US20070255554 proposed 'a system and method for providing automatic language translation in a telecommunications network'. However, the system envisaged by

US20070255554 involved routing a communication call via a service center for automatic translation. The use of a third party service center for automatic translation means that firstly, the secrecy/confidentiality of the input text is compromised as it is being re-routed to a third-party service center, and secondly the user would not be
5 able to compare the original text and the translated text since the actual translation takes place while the message is in transit. Further, the prior art systems do not provide the facility of transliterating from an Indic language to English language.

OBJECTS OF THE EMBODIMENTS

10 [0007] An object of the present disclosure is to provide a system that enables efficient and effective translation of input text.

[0008] Yet another object of the present disclosure is to provide a system that enables effective and efficient transliteration of the input text.

15

[0009] Still a further object of the present disclosure is to provide a system that enables translation and transliteration of the input text based on predetermined gestures performed by the user.

20 [0010] One more objective of the present disclosure is to provide a system that is user friendly and easy to use.

[0011] Yet another object of the present disclosure is to make available a system that provides for translation and transliteration of input text from a plurality of Indic languages to English and vice-versa.

5 [0012] Still a further object of the present disclosure is to provide a system that enables a user to provide the input text in a native (Indic) language, and subsequently covert the input text into English before transmission of the input text as SMS/E-mail.

[0013] Yet another objective of the present disclosure is to provide a system
10 that enables a user to receive a text string in English, and subsequently covert the received text string into any of the predetermined Indic languages.

SUMMARY

[0014] The present disclosure envisages a computer implemented system for
15 selectively expressing an input text in a language other than the input language. The system envisaged by the present disclosure translates/transliterates the input text based on the gestures performed by a user. The system comprises a user interface configured to receive the text, as input from the user.

20 [0015] The system further includes a recognition module cooperating with the user interface. The recognition module is configured to recognize the gestures

performed by the user on the user interface, and convert predetermined gestures of the user into corresponding electrical signals. The electrical signals include instructions for expressing the input text in a language other than the input language.

5 [0016] The system further includes a translation module cooperating with the recognition module to selectively receive the electrical signals, the translation module further configured to translate the input text subsequent to receiving the electrical signals from the recognition module.

10 [0017] The system further includes a transliteration module cooperating with the recognition module to selectively receive the electrical signals, the transliteration module further configured to transliterate the input text subsequent to receiving the electrical signals from the recognition module.

15 [0018] In accordance with the present disclosure, the user interface further cooperates with the translation module and transliteration module to receive translated text and transliterated text, the user interface still further configured to selectively display at least the input text, the translated text and the transliterated text, based on the predetermined gestures performed by the user.

20

[0019] In accordance with the present disclosure, the recognition module is further configured to recognize at least a swipe left gesture and a swipe right gesture performed by the user, on the user interface.

5 [0020] In accordance with the present disclosure, the recognition module is further configured to covert the swipe left gesture into electric signals for transliterating the input text provided by the user, the recognition module further configured to convert the swipe right gesture into electric signals for translating the input text provided by the user.

10

[0021] The present disclosure further envisages a computer implemented method for selectively expressing an input text in a language other than the input language, based on the gestures performed by a user. In accordance with the present disclosure, the computer implemented method comprises the following steps:

15 receiving input text from the user, via a user interface; recognizing, using a recognition module, predetermined gestures performed by the user on the user interface; converting the predetermined gestures from the user into corresponding electrical signals, wherein the electrical signals comprise instructions for expressing the input text in a language other than the input language; selectively transmitting the

20 electrical signals to a translation module and a transliteration module; translating the input text, subsequent to receiving the electrical signals from the recognition module;

transliterating the input text, subsequent to receiving the electrical signals from the recognition module; and receiving translated text and transliterated text using the user interface; and selectively displaying the input text, the translated text and the transliterated text, on the user interface, based on the predetermined gestures
5 performed by the user.

[0022] In accordance with the present disclosure, the step of recognizing predetermined gestures performed by the user on the user interface, further includes the step of recognizing at least a swipe left gesture and a swipe right gesture
10 performed by the user, on the user interface.

[0023] In accordance with the present disclosure, the step of recognizing at least a swipe left gesture and a swipe right gesture, further includes the step of converting the swipe left gesture into electric signals for transliterating the input text
15 provided by the user, and converting the swipe right gesture into electric signals for translating the input text provided by the user.

[0024] A non transitory computer readable medium having computer readable instructions stored thereupon, the computer readable instructions, when executed by a
20 processor, cause a computer enabled device to: receive input text from the user, via a user interface; recognize, using a recognition module, predetermined gestures

performed by the user on the user interface; convert the predetermined gestures from the user into corresponding electrical signals, wherein the electrical signals comprise instructions for expressing the input text in a language other than the input language; selectively transmit the electrical signals to a translation module and a transliteration module; translate the input text, subsequent to receiving the electrical signals from the recognition module; transliterate the input text, subsequent to receiving the electrical signals from the recognition module; and receive translated text and transliterated text using the user interface; and selectively display the input text, the translated text and the transliterated text, on the user interface, based on the predetermined gestures performed by the user.

[0025] In accordance with the present disclosure, the computer readable instructions are further configured to enable the computer enabled device to recognize at least a swipe left gesture and a swipe right gesture performed by the user, on the user interface.

[0026] In accordance with the present disclosure, the computer readable instructions are further configured to enable the computer enabled device to convert the swipe left gesture into electric signals for transliterating the input text provided by the user, and convert the swipe right gesture into electric signals for translating the input text provided by the user.

BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWINGS

[0027] The present disclosure will be better understood from the following detailed description, with reference to the accompanying drawings, in which:

5

[0028] **FIG.1** illustrates a computer implemented system-level block diagram corresponding to a system for translation and transliteration of input text;

[0029] **FIG.2** is a flow chart illustrating the steps involved in a computer-
10 implemented method for translation and transliteration of input text;

[0030] **FIGS. 3A and 3B** depict an example user interface for translating input text; and

15 [0031] **FIGS. 4A and 4B** depict an example user interface for transliterating input text.

DETAILED DESCRIPTION OF THE EMBODIMENTS HEREIN

[0032] The present disclosure envisages a computer implemented, gesture
20 based system for selective translation and transliteration of input text. The translation and transliteration are selective in the sense that the translated/transliterated input text

is displayed to a user, only in response to predetermined gestures performed by the user. The system envisaged by the present disclosure enables efficient and effective translation & transliteration of input text from English to a plurality of Indic languages and vice-versa. The system envisaged by the present disclosure enables a user to provide the input text in a native (Indic) language, and subsequently covert the input text into English before transmission of the input text as SMS/E-mail. Further, the system also enables the user to receive a text string in English, and subsequently covert the received text string into any of the predetermined Indic languages.

10 [0033] Referring to the accompanying drawings, FIG.1 illustrates a computer implemented, gesture based system 100 for translation and transliteration of input text. The system 100, in accordance with the present disclosure includes a user interface 10. The user interface 10 is configured to, inter-alia, receive text as input from the user. The text input by the user can either be in English or in any of the
15 predetermined Indic languages including but not restricted to Bengali, Gujarati, Assamese, Oriya, Kannada, Tamil, Telugu and Malayalam. Further, the user interface 10 is also configured to display text received in the form of emails/SMS/web pages and the like.

[0034] The user interface 10, in accordance with the present disclosure is further configured to enable a user to communicate with the user interface 10 via a predetermined set of gestures. In a preferred embodiment, the user interface 10 being hosted on a touch sensitive/responsive display screen enables the user to interact by performing certain gestures including but not restricted to a left swipe gesture, right
5 swipe gesture, tapping gesture, tap and hold gesture, circular gesture, semi-circular gesture, and double tap gesture. Further, the user interface 10 is further configured to enable the user to input text by the way of selectively tapping on the alphabet keys, alphanumeric keys, and the numeric keys displayed thereon.

10

[0035] The system 100, in accordance with the present disclosure further comprises a recognition module 12 cooperating with the user interface 10. The recognition module 12, in accordance with the present disclosure is configured to recognize and interpret the gestures performed by the user on the user interface 10.

15 The recognition module 12 is configured to recognize the point of contact of the user's finger on the user interface 10 (using well known techniques including resistive technique, capacitive technique and surface acoustic wave technique) and accordingly interpret the 'touch' from the user as selection of corresponding characters/numerals/functions displayed in the form of selectable keys.

20

[0036] Further, the characters/numerals whose corresponding keys are touched/selected by the user are considered as input text, by the recognition module 12. The term input text, in the context of the present disclosure is considered as a string of characters. Further, the 'input text' can also be construed as comprising a combination of alphabets and numerals. Further, the 'input text' can also be construed as a combination of alphabets, numerals and special characters. However, in a preferred embodiment of the present disclosure, for the sake of explanation, the input text is considered as a string of alphabets.

10 [0037] In accordance with the present disclosure, the recognition module 12 is further configured to interpret predetermined gestures of the user as gestures indicative of requesting for translation and transliteration of the input text.

[0038] In accordance with the preferred embodiment of the present disclosure, a left swipe gesture performed by the user on the user interface 10 is interpreted by the recognition module 12 as a request for transliteration of the input text. In accordance with the preferred embodiment of the present disclosure, a swipe right gesture performed by the user on the user interface 10, is interpreted by the recognition module 12 as a request for translation of the input text. The interpretations performed by the recognition module 12 in response to swap left gesture and swap right gesture are hardcoded on to the recognition module 12, in

accordance with the preferred embodiment of the present disclosure. However, it is with the scope of the present disclosure to substitute the swipe left and swipe right gestures with other appropriate gestures and hardcode the substituted gestures to be corresponding to translation and transliteration requests.

5

[0039] In accordance with the preferred embodiment of the present disclosure, the recognition module 12 cooperates with the user interface to identify a left swipe gesture and a right swipe gesture respectively. After the input text is keyed-in, if the user performs a left swipe on the user interface 10, the recognition module 12 triggers a transliteration module 16 and subsequently instructs the transliteration module 16 to transliterate the input text into a language chosen by the user. In the event that the user performs a right-swipe soon after entering the input text, the recognition module 12 triggers a translation module 14 and subsequently instructs the translation module 16 to translate the input text into a language chosen by the user. Even though, the functionalities of the translation module 14 and transliteration module 16 have been explained with reference to text input by the user, the translation module 14 and the transliteration module 16 are also configured to respectively translate and transliterate any text, for example, text received in the form of SMS/email/web-pages and the like, from the native language to the language prescribed by the user.

20

[0040] Referring to FIG.3A, there is shown an example user interface 10, using which the user has keyed-in the sentence 'how are you' in English. Subsequent to keying-in the input text, in the event that the user performs a swipe-left gesture, the transliteration module 16 is invoked and the English text 'how are you' is
5 transliterated into any of the Indic languages selected by the user, as shown in the FIG.3B.

[0041] Referring to FIG.4A, there is shown another example user interface 10, using which the user has keyed-in the sentence 'how are you' in English. Subsequent
10 to keying-in the input text, in the event that the user performs a swipe-right gesture, the translation module 14 is invoked and the English text 'how are you' is translated into any of the Indic languages selected by the user as shown in FIG. 4B.

[0042] In accordance with the present disclosure, the user interface 10 is
15 configured to enable the user to firstly select a language for keying-in the input text. The language selected by the user could include but is not restricted to English, Hindi, Bengali, Gujarati, Assamese, Oriya, Urdu, Tamil, Telugu, Malayalam and Kannada. Further, the aforementioned non-exhaustive list of languages is also available for selection as the language to which the input text has to be translated
20 and/or transliterated. Further, the recognition module 12 is configured to invoke the translation module 14 and the transliteration module 16 by the way of transmitting

electric signals having instructions embedded thereupon for activating the translation module 14 and the transliteration module 16.

[0043] Further, in accordance with the present disclosure, the default screen of the user interface 10 is the screen used for keying-in the input text (as shown in FIG.3A), after the input text is keyed-in and in the event the user performs a left-swipe gesture, the user interface 10 would change to the view shown in FIG.3B, and in the event that the user performs a right swipe on the user interface 10 exemplified in FIG.3B, the user interface 10 would be restored to the default screen shown in FIG.3A.

[0044] Further, in accordance with the present disclosure, the default screen of the user interface 10 is the screen used for keying-in the input text (as shown in FIG.4A), after the input text is keyed-in and in the event the user performs a right-swipe gesture, the user interface 10 would change to the view shown in FIG.4B, and in the event that the user performs a left swipe on the user interface 10 exemplified in FIG.4B, the user interface 10 would be restored to the default screen shown in FIG.4A.

[0045] Referring to FIG.2, there is shown a flow chart illustrating the steps involved in the method for translation and transliteration of input text. The method

envisaged by the present disclosure is responsive to the gestures performed by the user. The method, in accordance with the present disclosure comprises the following steps:

- receiving input text from the user, via a user interface (200);
- 5 recognizing, using a recognition module, predetermined gestures performed by the user on the user interface (202);
- converting said predetermined gestures from the user into corresponding electrical signals, wherein said electrical signals comprise instructions for expressing the input text in a language other
- 10 than the input language (204);
- selectively transmitting said electrical signals to a translation module and a transliteration module (206);
- translating the input text, subsequent to receiving said electrical signals from the recognition module (208);
- 15 transliterating the input text, subsequent to receiving said electrical signals from the recognition module (210); and
- receiving translated text and transliterated text using the user interface;
- and selectively displaying the input text, the translated text and the transliterated text, on the user interface, based on the predetermined
- 20 gestures performed by the user (212).

[0046] In accordance with the present disclosure, the step of recognizing predetermined gestures performed by the user on the user interface, further includes the step of recognizing at least a swipe left gesture and a swipe right gesture performed by the user, on the user interface.

5

[0047] In accordance with the present disclosure, the step of recognizing at least a swipe left gesture and a swipe right gesture, further includes the step of converting the swipe left gesture into electric signals for transliterating the input text provided by the user, and converting the swipe right gesture into electric signals for
10 translating the input text provided by the user.

[0048] Another embodiment of the present disclosure discloses a non transitory computer readable medium having computer readable instructions stored thereupon, the computer readable instructions, when executed by a processor, cause a
15 computer enabled device to: receive input text from the user, via a user interface; recognize, using a recognition module, predetermined gestures performed by the user on the user interface; convert said predetermined gestures from the user into corresponding electrical signals, wherein said electrical signals comprise instructions for expressing the input text in a language other than the input language; selectively
20 transmit said electrical signals to a translation module and a transliteration module; translate the input text, subsequent to receiving said electrical signals from the

recognition module; transliterate the input text, subsequent to receiving said electrical signals from the recognition module; and receive translated text and transliterated text using the user interface; and selectively display the input text, the translated text and the transliterated text, on the user interface, based on the predetermined gestures
5 performed by the user.

[0049] In accordance with the present disclosure, the computer readable instructions are further configured to enable the computer enabled device to recognize at least a swipe left gesture and a swipe right gesture performed by the
10 user, on the user interface.

[0050] In accordance with the present disclosure, the computer readable instructions are further configured to enable the computer enabled device to convert the swipe left gesture into electric signals for transliterating the input text provided by
15 the user, and convert the swipe right gesture into electric signals for translating the input text provided by the user.

TECHNICAL ADVANTAGES

[0051] The technical advantages envisaged by the present disclosure include
20 the realization of a system that enables efficient and effective translation of input text. The system envisaged by the present disclosure also provides for effective and

efficient transliteration of the input text. Further, the system envisaged by the present disclosure enables translation and transliteration of the input text based on predetermined gestures performed by the user. The system envisaged by the present disclosure is easy-to-use and user friendly. The system provides for translation and
5 transliteration of input text from a plurality of Indic languages to English and vice-versa. The system envisaged by the present disclosure enables a user to provide the input text in a native (Indic) language, and subsequently covert the input text into English before transmission of the input text as SMS/E-mail. Further, the system also enables the user to receive a text string in English, and subsequently covert the
10 received text string into any of the predetermined Indic languages.

CLAIMS

We Claim:

1. A computer implemented system for selectively expressing an input text in a language other than the input language, based on the gestures performed by a user,
5 said computer implemented system comprising:

a user interface accessible to the user, said user interface configured to receive the text, as input from the user;

a recognition module cooperating with the user interface, said recognition module configured to recognize the gestures performed by the user on the user
10 interface, said recognition module further configured to convert predetermined gestures of the user into corresponding electrical signals, said electrical signals comprising instructions for expressing the input text in a language other than the input language;

a translation module cooperating with the recognition module to selectively
15 receive said electrical signals, said translation module further configured to translate the input text subsequent to receiving said electrical signals from the recognition module; and

a transliteration module cooperating with the recognition module to selectively receive said electrical signals, said transliteration module further

configured to transliterate the input text subsequent to receiving said electrical signals from the recognition module;

said user interface further cooperating with said translation module and transliteration module to receive translated text and transliterated text, said user interface still further configured to selectively display the input text, the translated text and the transliterated text, based on the predetermined gestures performed by the user.

2. The system as claimed in claim 1, wherein said recognition module is further configured to recognize at least a swipe left gesture and a swipe right gesture performed by the user, on the user interface.

3. The system as claimed in claim 2, wherein said recognition module is further configured to convert the swipe left gesture into electric signals for transliterating the input text provided by the user, said recognition module further configured to convert the swipe right gesture into electric signals for translating the input text provided by the user.

4. A computer implemented method for selectively expressing an input text in a language other than the input language, based on the gestures performed by a user, said computer implemented method comprising the following steps:

receiving input text from the user, via a user interface;

recognizing, using a recognition module, predetermined gestures performed by the user on the user interface;

converting said predetermined gestures from the user into corresponding electrical signals, wherein said electrical signals comprise instructions for
5 expressing the input text in a language other than the input language;

selectively transmitting said electrical signals to a translation module and a transliteration module;

translating the input text, subsequent to receiving said electrical signals from the recognition module;

10 transliterating the input text, subsequent to receiving said electrical signals from the recognition module; and

receiving translated text and transliterated text using the user interface; and

selectively displaying the input text, the translated text and the transliterated text, on the user interface, based on the predetermined gestures

15 performed by the user.

5. The method as claimed in claim 4, wherein the step of recognizing predetermined gestures performed by the user on the user interface, further includes the step of recognizing at least a swipe left gesture and a swipe right gesture performed by the user, on the user interface.

6. The method as claimed in claim 5, wherein the step of recognizing at least a swipe left gesture and a swipe right gesture, further includes the step of converting the swipe left gesture into electric signals for transliterating the input text provided by the user, and converting the swipe right gesture into electric signals for translating the input text provided by the user.

7. A non transitory computer readable medium having computer readable instructions stored thereupon, said computer readable instructions, when executed by a processor, cause a computer enabled device to:

receive input text from the user, via a user interface;

10 recognize, using a recognition module, predetermined gestures performed by the user on the user interface;

convert said predetermined gestures from the user into corresponding electrical signals, wherein said electrical signals comprise instructions for expressing the input text in a language other than the input language;

15 selectively transmit said electrical signals to a translation module and a transliteration module;

translate the input text, subsequent to receiving said electrical signals from the recognition module;

transliterate the input text, subsequent to receiving said electrical signals from the recognition module; and


receive translated text and transliterated text using the user interface; and selectively display the input text, the translated text and the transliterated text, on the user interface, based on the predetermined gestures performed by the user.

8. The non-transitory computer readable medium as claimed in claim 1, wherein said computer readable instructions are further configured to enable the computer enabled device to recognize at least a swipe left gesture and a swipe right gesture performed by the user, on the user interface.

9. The non-transitory computer readable medium as claimed in claim 8, wherein said computer readable instructions are further configured to enable the computer enabled device to convert the swipe left gesture into electric signals for transliterating the input text provided by the user, and convert the swipe right gesture into electric signals for translating the input text provided by the user.

Date: 26-Sep-2014

Place: Bangalore



Rakesh Prabhu

Counsel for the Applicant