

Description

The invention relates to a connector assembly comprising a plug-in connector and a socket connector adapted to mate with and detach from one another, the plug-in connector having at least one contact member of a first type and the socket connector having at least one contact member of a second type, said contact members being adapted to cooperate when the connectors mate, the plug-in connector having a housing of electrically insulating material, at least one lever-type locking element extending along an external side of said plug-in connector housing and having a first and second free end, at least one projecting latching element being provided at the first free end of said lever-type locking element near the mating side of the plug-in connector, said latching element projecting outward away from the plug-in connector housing, the second free end of said lever-type locking element being designed as a gripping end for application of a force to release the mating connectors, the socket connector also having a housing of electrically insulating material, provided with at least one slotted opening in a side of the socket connector housing for receiving the projecting latching element from within the socket connector housing; whereby when the plug-in connector is inserted into the socket connector, the first free end of the lever-type locking element extends within said socket connector housing along the side containing the slotted opening and the outwardly projecting latching element snaps into the slotted opening from within the socket connector housing to latch the two connectors together.

An example of a plug-in and socket connector assembly of this type is shown in an embodiment of a connector assembly disclosed by U.S. Patent 3,842,388. In said prior art connector assembly the lever-type locking element is fixed to the housing of the plug-in connector by means of a single pivot point. The gripping end of the locking element projects outward beyond the housing of the plug-in connector, to facilitate the disconnection of mated connectors.

To disconnect the plug-in connector from the socket connector a force directed outward away from the plug-in connector housing has to be exerted at the gripping end of the lever-type locking element thereof, such to disengage its latching element from the corresponding slotted opening of the socket connector, as well as a pulling force in the direction away from the socket connector. However, for a readily manually disconnection of the plug-in connector from the socket connector a two handed operation is required, i.e. applying the outwardly directed disengagement force by using one hand and simultaneously applying the pulling force by using another hand.

U.S. Patent 4,787,860 discloses a prior art connector assembly, wherein a lever-type locking ele-

ment having two free ends is fixed to the plug-in connector by means of a single pivot point, such that when the plug-in connector mates with the socket connector, the lever-type locking element comes to rest along the outside surface of the housing of the socket connector. The latching element at one free end of the lever-type locking element is directed inward toward the plug-in connector housing, and engages with a corresponding slotted opening in the socket connector from the outside thereof. To disconnect the connector an inwardly directed disengagement force with respect to the housing of the plug-in connector has to be exerted on the gripping end of the locking element, as well as a pulling force.

Although with this type of locking element, because of the inwardly directed disconnection force, the connector assembly can be readily disconnected by one hand, the fact that in the locking position the lever-type locking element is outside of the socket connector is undesirable for various reasons. It makes the installation of such a connector assembly in an apparatus particularly difficult.

Summary of the Invention

The object of the present invention is now to provide a connector assembly in which both the locking of the lever-type locking element of the plug-in connector on the inside of the socket connector, and the disconnection of the connectors by one hand, applying a disengagement force directed toward the housing of the plug-in connector, are advantageously combined.

This object is achieved by the present invention in that said at least one lever-type locking element is supported at two pivot points spaced apart along the length of the plug-in connector, whereby when the mating connectors are to be disconnected, a force directed inward toward the plug-in connector housing is exerted at the gripping end of the lever-type locking element, said force causing the latching element to move away from the side of the socket connector housing in the same direction as the gripping end of the lever-type locking element and to disengage from the slotted opening.

By providing the locking element with two pivot points, it is achieved that when the plug-in connector and the socket connector are pushed into each other, such that the first free end of the lever-type locking element having the latching element fits into the corresponding slotted opening of the socket connector from the inside thereof, by exerting an inward-directed gripping force at the second free end of the locking element, the latching element is disengaged from the slot. Accordingly, the force for disengaging the latching means and pulling the connectors apart can also be exerted with just one hand, whereas the lever-type locking element fits from the inside of the socket con-

connector housing.

The lever-type locking element advantageously has a portion between the pivot points having a part of reduced thickness inwardly towards the plug-in connector housing. For example an inward-curved part between the pivot points. This means that on disengagement of the connectors, the part of the lever-type locking element situated between the pivot points does not bend outwards.

In another advantageous embodiment of the invention, the pivot points of the lever-type locking element have laterally projecting parts for slidably accommodation in two parallel grooves. The grooves are disposed running from an edge of the external side of the plug-in connector housing where the lever-type locking element is situated, at a distance from each other and with their open sides facing each other. Provision is made for means for fixing the locking element to the housing of the plug-in connector.

The projecting parts at the pivot point disposed near the latching element are preferably formed of laterally projecting parts of a lip-type element having a free end and which extends from this pivot point in the direction towards the other pivot point. The lip-type element extends essentially at a distance from and parallel to the lever part lying between the pivot points.

In this embodiment, the entire locking element, including the pivot parts, can be produced separately, for example by injection molding, and subsequently connected to the plug-in connector. It is, however, in practice not possible here to ensure that in the end product the lip-type element runs absolutely parallel to the lever part lying between the pivot points. On the contrary, this lip-type element will run slightly slanted towards the above-mentioned lever so that when the laterally projecting parts of the lip-type element are pushed into the grooves, a bending force is exerted on the front part of the lever carrying the latching element. This means that this latching element could be moved too far outwards.

In order to prevent this, provision is made between the free end of the lip-type element and the second pivot point for a projection whose end lies opposite the end of the lip-type element. In addition, the latching element also provides a measure of pre-tensioning to correct positioning of the lever part, and may be for example pawl-type in shape.

In a preferred embodiment the means for fixing the locking element to the housing of the plug-in connector comprises a saw tooth shaped projection extending between the two parallel grooves. Said projection has opposite steep and gradual sides. The gradual side faces the edge of the external side of the connector housing from which the parallel grooves running. Whereby when the laterally projecting parts of the lever-type locking element are accommodated in said grooves, the lip-type element engages the

steep side of said saw tooth shaped projection, as a result of which the lever-type locking element being locked to the plug-in connector housing.

The separate production of the locking element has certain advantages. Both the locking element and the relevant connector part can be manufactured more easily. They can be made from different materials. If desired, a connector can be supplied without locking. A locking lever can be replaced if necessary.

However, the lever-type locking element may be secured to the plug-in connector housing by means of at least one of the pivot points. The lever-type locking element can also be made up of two lever parts, each of which is fixed by means of a pivot point to a side face of the plug-in connector. The lever parts have overlapping ends situated between these pivot points, the end of the lever part carrying the latching element being situated on the outside.

The contact members of said first and second type may be designed for electrically, optically or magnetically contacting each other. The invention relates also to a plug-in connector, a socket connector, a separately provide lever-type locking element and/or a plug-in connector housing according to any of the preceding embodiments.

The invention is explained in greater detail below with reference to the exemplary embodiments shown in the drawings.

Brief Description of the Drawings

Fig. 1 shows the plug-in and socket connectors according to the invention, in perspective;
Figs. 2 and 3 show other embodiments of the lever-type locking element;
Fig. 4 shows yet another embodiment of the lever-type locking element;
Fig. 5 shows the locking element according to Fig. 4, in top view;
Fig. 6 shows the locking element according to Figs. 4 and 5 in the position fitted on the plug-in connector, in side view; and
Fig. 7 is a side view in the direction of the arrow A in Fig. 6.

Detailed Description of the Embodiments

As shown in Fig. 1, the connector assembly comprises a plug-in connector 1 and a socket connector 2. The socket connector is provided with a number of projecting contact pins 3 of electrically conductive material which are to be received within a corresponding number of socket contacts of electrically conductive material in recesses 4 of the plug-in connector 1 when the two connectors are mated.

A lever-type locking element 5 is connected to a side of the plug-in connector 1 at two elastic pivot points 6, 7 spaced apart along the length of connector

1. The locking element 5 has latching elements 8 with a ramp face 8' projecting at one free end. The projecting elements 8 may be pawl-type or boss-type elements. The other free end part 5' of the locking element is designed as a ribbed handling end and projects outwards beyond the short side of the housing of the plug-in connector to facilitate disconnecting of the connector assembly for example if mounted in places difficult to reach. When an inward-directed gripping force is exerted on the end part 5', the boss-type elements 8 also move inward towards the side of connector 1.

When the plug-in connector 1 is inserted into the socket connector 2, the ramp faces 8' of the boss-type elements 8 abut against the inside 2' of an end edge of the socket connector 2. The boss-type elements 8 are pressed inward and slide under pre-tension along the inside faces of the socket connector 2 until they go into the slots 9 formed in a side wall of the socket part 2. On further pushing forward of connector 1, elements 8 snap into the slots, thereby latching the connector assembly together.

To detach connector 1 and 2 from each other, a gripping force is exerted on the part 5' of the locking element 5. This causes the boss-type elements 8 to disengage from the slots 9, thereby disconnecting the connectors.

Reference numbers 10 and 11 represent coding elements. Coding element 10 is fixed by means of the slots 9 inside the socket connector 2. Coding element 11 is connected by means of the slots 12 to the plug-in connector 1. The coding elements provide a polarizing feature which permits the two connectors to be mated in only one way.

Another embodiment of the lever-type locking element is shown as element 15 in Fig. 2 which is also connected by means of elastic pivot points 16 and 17 to plug-in connector (not shown). The free end part 15' is again designed as a handling part, while the other free end part bears the boss-type elements 18 with a ramp face 18'.

Part 15" of the locking element is the portion between the pivot points 16 and 17 of reduces thickness and is curved inward. This prevents part 15" from bending outwards when the connectors are being disconnected.

The lever-type locking element 25 shown in Fig. 3 comprises two parts 25" and 25". Part 25" is connected by means of the elastic pivot point 26 to a plug-in connector (not shown). Part 25" has a free handling end 25'. Part 25" has the boss-type elements 28 with a ramp face 28'. The ends 30, 31 of the lever parts 25" and 25" lying between the pivot points 26 and 27 are bevelled, so that they overlap.

The lever-type locking element 40 shown in Figs. 4 and 5 is prefabricated separately and subsequently connected to the plug-in connector. The locking element 40 again bears at one free end the boss-type

elements 41, each having a ramp face 41'. The other free end is again designed as a handling end 40'.

One pivot point 42 bears a lip-type element 43, the sides 43' of which project beyond the locking element 40, as shown in Fig. 5. The second pivot point 44 also has laterally projecting parts 44'.

Figs. 6 and 7 show the locking element 40 being fixed to a plug-in connector 45. The connector 45 is provided with an elongated recess 46 which is bounded along the sides by grooves 47 running from the edge 53, the open sides of which grooves face each other. When the locking element 40 is being installed, the projecting parts 43' and 44' are pushed into the grooves 47 so that the pivot point 44 is slidable. The free end 43" of the lip-type element 43 engages in the assembled state the steep side 56 of a saw tooth shaped projection 54 between the grooves 47. The gradual side 55 of this projection 54 faces the edge 53 to facilitate assembling of the lever-type locking element 40 and the plug-in connector 45. With this projection 54 the locking element 40 is securely latched to the housing of the connector 45.

The connector assembly and in particular the locking elements are preferably made of plastic. The locking elements of Figs. 2, 3 and 4 may be manufactured separately by, for example, injection molding. It is extremely difficult, however, to ensure that in the end product the lip-type element 43 runs absolutely parallel to the lever part lying opposite it, as shown by the solid lines in Fig. 4. On the contrary, the lip-type element 43 will mostly slope slightly inward, as shown in an exaggerated manner in Fig. 4 by broken lines 43". This position of the lip-type element 43 means that during insertion of the projecting parts 43' into the grooves 47, an outward-directed bending force is exerted on the front lever part carrying the boss-type elements 41. As a result, the bosses 41 are moved outwards too far so that during mating of the plug-in connector into the socket connector, the ramp face 41' will not abut against the inside edge 2' (see Fig. 1) of the socket connector. In order to prevent this, the projection 52 is disposed on the locking element 40, such that its end lies opposite the free end 43" of the lip-type element 43.

Figs 6 and 7 also show that the plug-in connector 45 has a projection 50 along which a cable 51 of wires is guided with a binding loop 48. A cord 49 runs through this loop 48 and cord 49 is fixed by one free end to the lever-type locking element 40, while the other free end is formed into a pulling loop. Thus by pulling on the pulling loop 48, both a pulling force can be exerted on the plug-in connector 45 and an inward-directed force can be exerted on the free end 40' of the lever-type locking element 40 to facilitate disconnecting of the plug-in and socket connectors.

Although the present invention is illustrated by means of a socket connector and a plug-in connector having corresponding contact elements of electrically

conductive material, the lever-type locking element may be advantageously used in other type of connector assemblies. For example in optical connectors, power connectors, coaxial connectors and the like.

Claims

1. A connector assembly comprising a plug-in connector (1; 45) and a socket connector (2) adapted to mate with and detach from one another, the plug-in connector (1; 45) having at least one contact member of a first type and the socket connector (2) having at least one contact member of a second type, said contact members being adapted to cooperate when the connectors (1; 45; 2) mate, the plug-in connector (1; 45) having a housing of electrically insulating material, at least one lever-type locking element (5; 15; 25; 40) extending along an external side of said plug-in connector housing and having a first and second free end, at least one projecting latching element (8; 18; 28; 41) being provided at the first free end of said lever-type locking element (5; 15; 25; 40) near the mating side of the plug-in connector (1; 45), said latching element (8; 18; 28; 41) projecting outward away from the plug-in connector housing, the second free end of said lever-type locking element (5; 15; 25; 40) being designed as a gripping end (5'; 15'; 25'; 40') for application of a force to release the mating connectors (1; 45; 2), the socket connector (2) also having a housing of electrically insulating material, provided with at least one slotted opening (9) in a side of the socket connector housing for receiving the projecting latching element (8; 18; 28; 41) from within the socket connector housing; whereby when the plug-in connector (1; 45) is inserted into the socket connector (2), the first free end of the lever-type locking element (5; 15; 25; 40) extends within said socket connector housing along the side containing the slotted opening (9) and the outwardly projecting latching element (8; 18; 28; 41) snaps into the slotted opening (9) from within the socket connector housing to latch the two connectors (1; 45; 2) together, characterized in that, said at least one lever-type locking element (5; 15; 25; 40) is supported at two pivot points (6, 7; 16, 17; 26, 27; 42, 44) spaced apart along the length of the plug-in connector (1; 45), whereby when the mating connectors (1; 45; 2) are to be disconnected, a force directed inward toward the side of the plug-in connector housing is exerted at the gripping end (5'; 15'; 25'; 40') of the lever-type locking element (5; 15; 25; 40), said force causing the latching element (8; 18; 28; 41) to move away from the side of the socket connector housing in the same direction as the gripping end (5'; 15'; 25'; 40') of the lever-type locking element (5; 15; 25; 40) and to disengage from the slotted opening (9).
2. The connector assembly of claim 1, wherein the portion (15'') of the lever-type locking element (5; 15; 40) between the pivot points (6, 7; 16, 17; 42, 44) has a part of reduced thickness inwardly toward the plug-in connector housing.
3. The connector assembly of claim 2, wherein said portion (15'') of the lever-type locking element (15) between the pivot points (16, 17) is curved inwardly toward the side of the plug-in connector housing.
4. The connector assembly of claims 1, 2 or 3, wherein the pivot points (42, 44) of the lever-type locking element (40) have laterally projecting parts (43', 44') for slidably accommodation in two parallel grooves (47), said grooves (47) being disposed at said external side of the plug-in connector housing running from an edge thereof at a distance from each other and having their open sides facing each other, and wherein provision is made for means (54) for fixing the lever-type locking element (40) to the housing of the plug-in connector.
5. The connector assembly of claim 4, wherein the laterally projecting parts (43') of the lever-type locking element (40) at the pivot point (42) nearest to the latching element (41) are preferably a lip-type element (43) having a free end (43'') and which extends from this pivot point (42) in the direction towards the other pivot point (44), and which runs essentially at a distance from and parallel to the portion of the lever-type locking element (40) lying between the pivot points (42, 44).
6. The connector assembly of claim 5, wherein provision is made between the free end (43'') of the lip-type element (43) and the second pivot point (44) for a projection (52) whose end lies opposite the free end (43'') of the lip-type element (43).
7. The connector assembly of claims 5 or 6, wherein provision is made between the two parallel grooves (47) of the plug-in connector housing for a saw tooth shaped projection (54), having opposite steep (56) and gradual sides (55), such that the gradual side (55) faces the edge of the external side of the plug-in connector housing from which the grooves (47) are running, and whereby when the laterally projecting parts (43', 44') of the lever-type locking element (40) are accommodated in said grooves (47), the free end (43'') of the lip-type element (43) engages the steep side (56)



conductive material, the lever-type locking element may be advantageously used in other type of connector assemblies. For example in optical connectors, power connectors, coaxial connectors and the like.

Claims

1. A connector assembly comprising a plug-in connector (1; 45) and a socket connector (2) adapted to mate with and detach from one another, the plug-in connector (1; 45) having at least one contact member of a first type and the socket connector (2) having at least one contact member of a second type, said contact members being adapted to cooperate when the connectors (1; 45; 2) mate, the plug-in connector (1; 45) having a housing of electrically insulating material, at least one lever-type locking element (5; 15; 25; 40) extending along an external side of said plug-in connector housing and having a first and second free end, at least one projecting latching element (8; 18; 28; 41) being provided at the first free end of said lever-type locking element (5; 15; 25; 40) near the mating side of the plug-in connector (1; 45), said latching element (8; 18; 28; 41) projecting outward away from the plug-in connector housing, the second free end of said lever-type locking element (5; 15; 25; 40) being designed as a gripping end (5'; 15'; 25'; 40') for application of a force to release the mating connectors (1; 45; 2), the socket connector (2) also having a housing of electrically insulating material, provided with at least one slotted opening (9) in a side of the socket connector housing for receiving the projecting latching element (8; 18; 28; 41) from within the socket connector housing; whereby when the plug-in connector (1; 45) is inserted into the socket connector (2), the first free end of the lever-type locking element (5; 15; 25; 40) extends within said socket connector housing along the side containing the slotted opening (9) and the outwardly projecting latching element (8; 18; 28; 41) snaps into the slotted opening (9) from within the socket connector housing to latch the two connectors (1; 45; 2) together, characterized in that, said at least one lever-type locking element (5; 15; 25; 40) is supported at two pivot points (6; 7; 16; 17; 26; 27; 42, 44) spaced apart along the length of the plug-in connector (1; 45), whereby when the mating connectors (1; 45; 2) are to be disconnected, a force directed inward toward the side of the plug-in connector housing is exerted at the gripping end (5; 15; 25; 40) of the lever-type locking element (5; 15; 25; 40), said force causing the latching element (8; 18; 28; 41) to move away from the side of the socket connector housing in the same direction as the gripping end (5'; 15';

25'; 40') of the lever-type locking element (5; 15; 25; 40) and to disengage from the slotted opening (9).

2. The connector assembly of claim 1, wherein the portion (15") of the lever-type locking element (5; 15; 40) between the pivot points (6, 7; 16, 17; 42, 44) has a part of reduced thickness inwardly toward the plug-in connector housing.
3. The connector assembly of claim 2, wherein said portion (15") of the lever-type locking element (15) between the pivot points (16, 17) is curved inwardly toward the side of the plug-in connector housing.
4. The connector assembly of claims 1, 2 or 3, wherein the pivot points (42, 44) of the lever-type locking element (40) have laterally projecting parts (43', 44') for slidably accommodation in two parallel grooves (47), said grooves (47) being disposed at said external side of the plug-in connector housing running from an edge thereof at a distance from each other and having their open sides facing each other, and wherein provision is made for means (54) for fixing the lever-type locking element (40) to the housing of the plug-in connector.
5. The connector assembly of claim 4, wherein the laterally projecting parts (43') of the lever-type locking element (40) at the pivot point (42) nearest to the latching element (41) are preferably a lip-type element (43) having a free end (43") and which extends from this pivot point (42) in the direction towards the other pivot point (44), and which runs essentially at a distance from and parallel to the portion of the lever-type locking element (40) lying between the pivot points (42, 44).
6. The connector assembly of claim 5, wherein provision is made between the free end (43") of the lip-type element (43) and the second pivot point (44) for a projection (52) whose end lies opposite the free end (43") of the lip-type element (43).
7. The connector assembly of claims 5 or 6, wherein provision is made between the two parallel grooves (47) of the plug-in connector housing for a saw tooth shaped projection (54), having opposite steep (56) and gradual sides (55), such that the gradual side (55) faces the edge of the external side of the plug-in connector housing from which the grooves (47) are running, and whereby when the laterally projecting parts (43', 44') of the lever-type locking element (40) are accommodated in said grooves (47), the free end (43") of the lip-type element (43) engages the steep side (56)



of said saw tooth shaped projection (54), as a result of which the lever-type locking element (40) being locked to the plug-in connector housing.

8. The connector assembly of claims 1, 2, or 3, wherein the lever-type locking element (5; 15) is secured to the plug-in connector housing by means of at least one of the pivot points (6; 7; 16; 17).
9. The connector assembly of claim 1, wherein the lever-type locking element (25) comprises two lever parts (25", 25'''), each attached to the plug-in connector housing by means of one of the two pivot points (26, 27), said lever parts (25", 25''') each having an end (30, 31) between the two pivot points (26, 27) which overlaps one another, the overlapping end (31) of the lever part (25'') with the latching element (28) at its other end being the further outward of the overlapping ends (30, 31).
10. The connector assembly of any of the preceding claims wherein said outward projecting latching element (8; 18; 28; 41) comprises at least one element pawl-type in shape.
11. The connector assembly of any of the preceding claims, wherein the contact members of said first and second type are designed for electrically, optically or magnetically contacting each other.
12. A plug-in connector (1; 45) for cooperation with a socket connector (2) of the connector assembly of claim 1, said plug-in connector comprises at least one contact member of a first type for mating with at least one contact member of a second type provided in the socket connector (2), the plug-in connector (1; 45) having a housing of electrically insulating material, at least one lever-type locking element (5; 15; 25; 40) extending along an external side of said plug-in connector housing and having a first and second free end, at least one projecting latching element (8; 18; 28; 41) provided at the first free end of said lever-type locking element (5; 15; 25; 40) near the mating side of the plug-in connector (1; 45), said latching element (8; 18; 28; 41) projecting outward away from the plug-in connector housing, to engage a slotted opening (9) of the socket connector (2), the second free end of said lever-type locking element (5; 15; 25; 40) being designed as a gripping end (5'; 15'; 25'; 40') for application of a force to disconnect the plug-in connector (1; 45) from a mating socket connector (2), characterized in that, said at least one lever-type locking element (5; 15; 25; 40) is supported at two pivot points (6; 7; 16; 17; 26; 27; 42, 44) spaced apart along the

length of the plug-in connector (1; 45), whereby when the plug-in connector (1; 45) is to be disconnected, a force directed inward toward the side of the plug-in connector housing is exerted at the gripping end (5; 15; 25; 40) of the lever-type locking element (5; 15; 25; 40), said force causing the latching element (8; 18; 28; 41) to move away from the side of the socket connector housing in the same direction as the gripping end (5'; 15'; 25'; 40') of the lever-type locking element and to disengage from the slotted opening (9) of the mating socket connector (2).

Patentansprüche

1. Verbindervorrichtung, welche einen Steckverbinder (1; 45) und einen Aufnahmeverbinder (2) aufweist, welche derart ausgelegt sind, daß sie zueinander passen und voneinander lösbar sind, wobei der Steckverbinder (1; 45) wenigstens ein Kontaktelement einer ersten Bauart und der Aufnahmeverbinder (2) wenigstens ein Kontaktelement einer zweiten Bauart hat, die Kontaktelemente derart ausgelegt sind, daß sie zusammenarbeiten, wenn die Verbinder (1; 45; 2) passend zueinander angeordnet sind, der Steckverbinder (1; 45), der versehen ist mit einem Gehäuse aus elektrisch isolierendem Material, wenigstens ein Sperrelement (5; 15; 25; 40) der Hebelbauart, welches sich längs einer Außenseite des Steckverbindergehäuses erstreckt und ein erstes und ein zweites freies Ende hat, wenigstens ein vorspringendes Verriegelungselement (8; 18; 28; 41) am ersten freien Ende des Sperrelements (5; 15; 25; 40) der Hebelbauart in der Nähe der Paßseite des Steckverbinders (1; 45) vorgesehen ist, das Verriegelungselement (8; 18; 28; 41) von dem Steckverbindergehäuse weg nach außen vorspringt, das zweite freie Ende des Sperrelements (5; 15; 25; 40) der Hebelbauart als ein Greifende (5'; 15'; 25'; 40') zum Aufbringen einer Kraft ausgelegt ist, um die Paßverbinder (1; 45; 2) zu lösen, der Aufnahmeverbinder (2) ebenfalls ein Gehäuse aus elektrisch isolierendem Material hat, welches mit wenigstens einer geschlitzten Öffnung (9) auf einer Seite des Aufnahmeverbindergehäuses zur Aufnahme des vorspringenden Verriegelungselements (8; 18; 28; 41) vom Inneren des Aufnahmeverbindergehäuses her versehen ist; wobei, wenn der Steckverbinder (1; 45) in den Aufnahmeverbinder (2) eingeführt ist, das erste freie Ende des Sperrelements (5; 15; 25; 40) der Hebelbauart in dem Aufnahmeverbindergehäuse entlang der Seite verläuft, welche die geschlitzte Öffnung (9) enthält, und das nach außen vorspringende Verriegelungselement (8; 18; 28; 41) in die geschlitzte Öffnung (9) von dem Inne-



ren des Aufnahmeverbindergehäuses schnappt, um die beiden Verbinder (1; 45; 2) miteinander zu verriegeln, dadurch gekennzeichnet, daß das wenigstens eine Sperrelement (5; 15; 25; 40) der Hebelbauart an zwei Drehpunkten (6, 7; 16, 17; 26, 27; 42, 44) in Abstand angeordnet entlang der Längserstreckung des Steckverbinders (1; 45) gelagert ist, wobei, wenn die Paßverbinder (1; 45; 2) voneinander zu trennen sind, eine nach innen in Richtung auf die Seite des Steckverbindergehäuses gerichtete Kraft an dem Greifende (5; 15; 25; 40) des Sperrelements (5; 15; 25; 40) der Hebelbauart ausgeübt wird, wobei die Kraft bewirkt, daß das Verriegelungselement (8; 18; 28; 41) von der Seite des Aufnahmeverbindergehäuses weg in die gleiche Richtung wie das Greifende (5; 15; 25; 40) des Sperrelements (5; 15; 25; 40) der Hebelbauart bewegt wird und von der geschlitzten Öffnung (9) freikommt.

2. Verbindervorrichtung nach Anspruch 1, bei der der Abschnitt (15'') des Sperrelements (5; 15; 40) der Hebelbauart zwischen den Drehpunkten (6, 7; 16, 17; 42, 44) einen Teil mit verminderter Dicke nach innen in Richtung des Steckverbindergehäuses weisend hat.
3. Verbindervorrichtung nach Anspruch 2, bei der der Abschnitt (15'') des Sperrelements (15) zwischen den Drehpunkten (16, 17) nach innen in Richtung der Seite des Steckverbindergehäuses gekrümmt ist.
4. Verbindervorrichtung nach den Ansprüchen 1, 2 oder 3, bei der die Drehpunkte (42, 44) des Sperrelements (40) der Hebelbauart seitlich vorspringende Teile (43', 44') zur gleitbeweglichen Aufnahme in zwei parallelen Ausnehmungen (47) haben, die Ausnehmungen (47) an der Außenseite des Steckverbindergehäuses derart angeordnet sind, daß sie von einem Rand desselben ausgehen und in einem Abstand voneinander verlaufen, und an ihren offenen Seiten einander zugewandt sind, und bei der Vorkehrungen für Mittel (54) zum Fixieren des Sperrelements (40) der Hebelbauart an dem Gehäuse des Steckverbinders getroffen sind.
5. Verbindervorrichtung nach Anspruch 4, bei der die seitlich vorspringenden Teile (43') des Sperrelements (40) der Hebelbauart an dem Drehpunkt (42), welcher dem Verriegelungselement (41) am nächsten liegt, vorzugsweise ein lippenartiges Element (43) sind, welches ein freies Ende (43'') hat, und welches sich von diesem Drehpunkt (42) in Richtung auf den anderen Drehpunkt (44) erstreckt, und welches im wesentlichen sich über eine Strecke aus-

gehend von und parallel zu dem Abschnitt des Sperrelements (40) der Hebelbauart erstreckt, welcher zwischen den Drehpunkten (42, 44) liegt.

6. Verbindervorrichtung nach Anspruch 5, bei der Vorkehrungen zwischen dem freien Ende (43'') des lippenförmigen Elements (43) und dem zweiten Drehpunkt (44) für einen Vorsprung (52) getroffen sind, dessen Ende dem freien Ende (43'') des lippenförmigen Elements (43) gegenüberliegt.
7. Verbindervorrichtung nach Anspruch 5 oder 6, bei der Vorkehrungen zwischen den beiden parallelen Ausnehmungen (47) des Steckverbindergehäuses für einen sägezahnförmigen Vorsprung (54) getroffen sind, welcher gegenüberliegende steile und weniger steile Seiten (55) derart hat, daß die weniger steile Seite (55) dem Rand der Außenseite des Steckverbindergehäuses zugewandt ist, von der die Ausnehmungen (47) ausgehen, und bei der, wenn die seitlich vorspringenden Teile (43', 44') des Sperrelements (40) der Hebelbauart in den Ausnehmungen (47) aufgenommen sind, das freie Ende (43'') des lippenförmigen Elements (43) an der steilen Seite (56) des sägezahnförmigen Vorsprungs (54) angreift, woraus resultiert, daß das Sperrelement (40) der Hebelbauart in dem Steckverbindergehäuse gesperrt ist.
8. Verbindervorrichtung nach den Ansprüchen 1, 2 oder 3, bei der das Sperrelement (5; 15) der Hebelbauart fest mit dem Steckverbindergehäuse mit Hilfe wenigstens einer der Drehpunkte (6, 7; 16, 17) verbunden ist.
9. Verbindervorrichtung nach Anspruch 1, bei der das Sperrelement (25) der Hebelbauart zwei Hebelteile (25'', 25''') aufweist, welche jeweils an dem Steckverbindergehäuse mit Hilfe einer der beiden Drehpunkte (26, 27) angebracht sind, wobei die Hebelteile (25'', 25''') jeweils ein Ende (30, 31) zwischen den beiden Drehpunkten (26, 27) haben, welche einander überlappen, und wobei das sich mit dem Sperrelement (28) an dem anderen Ende überlappende Ende (31) des Hebelteils (25''') das weiter nach aussen liegende Ende der sich überlappenden Enden (30, 31) ist.
10. Verbindervorrichtung nach einem der vorangehenden Ansprüche, bei der das nach außen vorspringende Verriegelungselement (8; 18; 28; 41) wenigstens ein Element mit einer sperrklinkenförmigen Gestalt aufweist.
11. Verbindervorrichtung nach einem der vorangehenden Ansprüche, bei der die Kontaktelemente



der ersten und der zweiten Bauart derart ausgelegt sind, daß sie elektrisch, optisch oder magnetisch miteinander in Kontakt bringbar sind.

12. Steckverbinder (1; 45) zum Zusammenarbeiten mit einem Aufnahmeverbinder (2) der Verbinder-
vorrichtung nach Anspruch 1, wobei der Steck-
verbinder wenigstens ein Kontaktelement einer
ersten Bauart passend zu wenigstens einem
Kontaktelement einer zweiten Bauart aufweist,
welches in dem Aufnahmeverbinder (2) vorgese-
hen ist, der Steckverbinder (1; 45), der versehen
ist mit einem Gehäuse aus elektrisch isolieren-
dem Material, wenigstens ein Sperrelement (5;
15; 25; 40) der Hebelbauart, welches sich ent-
lang einer Außenseite des Steckverbindergehäu-
ses erstreckt, und ein erstes und ein zweites frei-
es Ende hat, wenigstens ein vorspringendes Ver-
riegelungselement (8; 18; 28; 41) an dem ersten
freien Ende des Sperrelements (5; 15; 25; 40) der
Hebelbauart in der Nähe der Paßseite des Steck-
verbinders (1; 45) vorgesehen ist, das Verriege-
lungselement (8; 18; 28; 41) von dem Steckver-
bindergehäuse weg weisend nach außen vor-
springt, um an einer geschlitzten Öffnung (9) des
Aufnahmeverbinders (2) anzugreifen,
das zweite freie Ende des Sperrelements (5; 15;
25; 40) der Hebelbauart als ein Greifende (5'; 15';
25'; 40') zum Aufbringen einer Kraft zum Lösen
des Steckverbinders (1; 45) von einem passen-
den Aufnahmeverbinder (2) ausgelegt ist, da-
durch gekennzeichnet, daß das wenigstens ei-
ne Sperrelement (5; 15; 25; 40) der Hebelbauart
an zwei Drehpunkten (6; 7; 16; 17; 26; 27; 42; 44)
in Abstand angeordnet entlang der Längs-
streckung des Steckverbinders (1; 45) gelagert
ist, wobei, wenn der Steckverbinder (1; 45) zu lö-
sen ist, eine nach innen in Richtung auf die Seite
des Steckverbindergehäuses gerichtete Kraft auf
das Greifende (5; 15; 25; 40) des Sperrelements
(5; 15; 25; 40) der Hebelbauart ausgeübt wird,
wobei die Kraft bewirkt, daß das Sperrelement (8;
18; 28; 41) von der Seite des Steckverbinderge-
häuses in die gleiche Richtung wie das Greifende
(5'; 15'; 25'; 40') des Sperrelements der Hebel-
bauart bewegt und von der geschlitzten Öffnung
(9) des passenden Aufnahmeverbinders (2)
freikommt.

Revendications

1. Un assemblage connecteur comprenant un
connecteur à enfichage (1; 45) et un connecteur
à embase (2) susceptibles de s'enficher en
correspondance et de se détacher l'un de l'autre,
le connecteur à enfichage (1; 45) comprenant au
moins un organe de contact d'un premier type et

le connecteur à embase (2) comprenant au moins
un organe de contact d'un second type, lesdits
organes de contact étant susceptibles de coopé-
rer lorsque les connecteurs (1; 45; 2) sont enfi-
chés en correspondance, le connecteur à enfi-
chage (1; 45) comprenant un boîtier en un maté-
riau électriquement isolant, au moins un élément
de verrouillage du type à levier (5; 15; 25; 40)
s'étendant le long d'une face extérieure dudit boî-
tier de connecteur à enfichage et présentant une
première et une seconde extrémités libres, au
moins un élément de verrouillage en saillie (8; 18;
28; 41) étant prévu à la première extrémité libre
dudit élément de verrouillage du type à levier (5;
15; 25; 40) à proximité de la face d'enfichage du
connecteur à enfichage (1; 45), ledit élément de
verrouillage (8; 18; 28; 41) faisant saillie vers l'ex-
térieur en s'éloignant du boîtier de connecteur à
enfichage, la seconde extrémité libre dudit élé-
ment de verrouillage du type à levier (5; 15; 25;
40) étant réalisée sous la forme d'une extrémité
d'accrochage (5'; 15'; 25'; 40') pour l'application
d'une force destinée à détacher les connecteurs
enfichés l'un sur l'autre (1; 45; 2), le connecteur à
embase (2) comprenant également un boîtier en
matériau électriquement isolant, muni d'au moins
une ouverture à fente (9) dans une face du boîtier
de connecteur à embase pour recevoir l'élément
de verrouillage en saillie (8; 18; 28; 41) depuis
l'intérieur du boîtier de connecteur à embase; de
telle manière que, lorsque le connecteur à enfi-
chage (1; 45) est inséré dans le connecteur à em-
base (2), la première extrémité libre de l'élément
de verrouillage du type à levier (5; 15; 25; 40)
s'étende à l'intérieur dudit boîtier de connecteur
à embase le long de la face contenant l'ouverture
à fente (9) et que l'élément de verrouillage en
saillie vers l'extérieur (8; 18; 28; 41) se détende
à l'ouverture à fente (9) depuis l'intérieur du boî-
tier de connecteur à embase pour verrouiller en-
semble les deux connecteurs (1; 45; 2), caracté-
risé en ce que ledit au moins un élément de
verrouillage du type à levier (5; 15; 25; 40) est
supporté en deux points de pivotement (6; 7; 16;
17; 26; 27; 42; 44) espacés sur la longueur du
connecteur à enfichage (1; 45), de telle manière
que, lorsque les connecteurs (1; 45; 2) enfichés
doivent être déconnectés, une force dirigée vers
l'intérieur en direction de la face du boîtier de
connecteur à enfichage, soit exercée à l'extrémi-
té d'accrochage (5; 15; 25; 40) de l'élément de
verrouillage du type à levier (5; 15; 25; 40) ladite
force obligeant l'élément de verrouillage (8; 18;
28; 41) à se déplacer en s'éloignant de la face du
boîtier de connecteur à embase dans la même di-
rection que l'extrémité d'accrochage (5'; 15'; 25';
40') de l'élément de verrouillage du type à levier
(5; 15; 25; 40) et à se désengager de l'ouverture



à fente (9).

2. L'assemblage connecteur selon la revendication 1, dans lequel la partie (15") de l'élément de verrouillage du type à levier (5; 15; 40) entre les points de pivotement (6, 7; 16, 17; 42, 44) comporte une partie d'épaisseur réduite vers l'intérieur en direction du boîtier de connecteur à enfichage. 5
3. L'assemblage connecteur de la revendication 2, dans lequel ladite partie (15") de l'élément de verrouillage du type à levier (15) entre les points de pivotement (16, 17) est incurvé vers l'intérieur en direction de la face du boîtier de connecteur à enfichage. 10 15
4. L'assemblage connecteur selon les revendications 1, 2 ou 3, dans lequel les points de pivotement (42, 44) de l'élément de verrouillage du type à levier (40) comportent des parties en saillie latérale (43', 44') destinées à être logées de façon coulissante dans deux rainures parallèles (47), lesdites rainures (47) étant disposées sur ladite face extérieure du boîtier de connecteur à enfichage courant depuis l'un de ses bords, à une distance l'un de l'autre, et présentant des faces ouvertes situées en face l'une de l'autre, et dans lequel on prévoit des moyens (54) pour fixer l'élément de verrouillage du type à levier (40) au boîtier du connecteur à enfichage. 20 25 30
5. L'assemblage connecteur de la revendication 4, dans lequel les parties en saillie latérale (43') de l'élément de verrouillage du type à levier (40) au point de pivotement (42) le plus proche de l'élément de verrouillage (41) sont constitués de préférence par un élément du type à lèvres (43) muni d'une extrémité libre (43") et qui s'étend depuis ce point de pivotement (42) dans la direction vers l'autre point de pivotement (44) et qui court sensiblement sur une distance à partir de la partie de l'élément de verrouillage du type à levier (40) disposée entre les points de pivotement (42, 44) et parallèlement à ladite partie. 35 40
6. L'assemblage connecteurs selon la revendication 5, dans lequel entre l'extrémité libre (43") de l'élément du type à lèvres (43) et le second point de pivotement (44) est prévue une partie en saillie (52) dont l'extrémité est disposée en face de l'extrémité libre (43") de l'élément du type à lèvres (43). 45 50
7. L'assemblage connecteur selon les revendications 5 ou 6, dans lequel entre les deux rainures parallèles (47) du boîtier de connecteur à enfichage, est prévue une partie en saillie en forme

de dent de scie (54) comprenant des faces opposées respectivement à pente raide (56) et à pente progressive (55), de telle façon que la face à pente progressive (55) soit située en face du bord de la face extérieure du boîtier de connecteur à enfichage, à partir duquel s'étendent les rainures (47), et de telle manière que lorsque les parties en saillie latérale (43', 44') de l'élément de verrouillage du type à levier (40) sont logées dans lesdites rainures (47), l'extrémité libre (43") de l'élément du type à lèvre (43) vienne en contact avec la face à pente raide (56) de ladite partie en saillie en forme de dent de scie (54), et qu'il en résulte que l'élément de verrouillage du type à levier (40) soit verrouillé au boîtier de connecteur à enfichage.

8. L'assemblage connecteur selon les revendications 1, 2 ou 3, dans lequel l'élément de verrouillage du type à levier (5, 15) est fixé au boîtier de connecteur à enfichage à l'aide d'au moins l'un des points de pivotement (6, 16; 16, 17). 55
9. L'assemblage connecteur selon la revendication 1, dans lequel l'élément de verrouillage du type à levier (25) comporte deux parties de levier (25", 25"), chacune étant fixée au boîtier de connecteur à enfichage au moyen de l'un des deux points de pivotement (26, 27), lesdites parties de levier (25", 25") comprenant chacune une extrémité (30, 31) entre les deux points de pivotement (26, 27) qui se recouvrent mutuellement, l'extrémité de recouvrement (31) de la partie de levier (25") avec l'élément de verrouillage (28) à son autre extrémité constituant l'extrémité la plus extérieure, des extrémités en recouvrement (30, 31).
10. L'assemblage connecteur selon l'une quelconque des revendications précédentes, dans lequel ledit élément de verrouillage en saillie vers l'extérieur (8; 18; 28; 41) comporte au moins un élément présentant une forme du type cliquet.
11. L'assemblage connecteur selon l'une quelconque des revendications précédentes, dans lequel les organes de contact desdits premier et second types sont prévus pour venir en contact électriquement, optiquement ou magnétiquement l'un avec l'autre.
12. Un connecteur à enfichage (1,; 45) destiné à coopérer avec un connecteur à embase (2) de l'assemblage connecteur selon la revendication 1, ledit connecteur à enfichage comprenant au moins un organe de contact d'un premier type pour venir en engagement avec au moins un organe de contact d'un second type prévu dans le connecteur à embase (2), le connecteur à affi-



chage (1; 45) comprenant un boîtier en un matériel électriquement isolant, au moins un élément de verrouillage du type à levier (5; 15; 25; 40) s'étendant le long d'une face extérieure dudit boîtier de connecteur à enfichage et comportant une première et une seconde extrémités libres, au moins un élément de verrouillage en saillie (8; 18; 28; 41) prévu à la première extrémité libre dudit élément de verrouillage du type à levier (5; 15; 25; 40) à proximité de la face d'engagement du connecteur à enfichage (1; 45), ledit élément de verrouillage (8; 18; 28; 41) faisant saillie vers l'extérieur en s'éloignant du boîtier de connecteur à enfichage pour venir s'engager dans une ouverture à fente (9) du connecteur à embase (2), la seconde extrémité libre dudit élément de verrouillage du type à levier (5; 15; 25; 40) étant réalisée sous la forme d'une extrémité d'accrochage (5'; 15'; 25'; 40') pour l'application d'une force destinée à déconnecter le connecteur à enfichage (1; 45) d'un connecteur à embase (2) sur lequel il est enfiché, caractérisé en ce que ledit au moins un élément de verrouillage du type à levier (5; 15; 25; 40) est supporté en deux points de pivotement (6; 7; 16; 17; 26; 27; 42, 44) espacés l'un de l'autre sur la longueur du connecteur à enfichage (1; 45), de telle manière que, lorsque le connecteur à enfichage (1; 45) doit être déconnecté, une force dirigée vers l'intérieur en direction de la face du boîtier de connecteur à enfichage soit exercée sur l'extrémité d'accrochage (5; 15; 25; 40) de l'élément de verrouillage du type à levier (5; 15; 25; 40), ladite force obligeant l'élément de verrouillage (8; 18; 28; 41) à se déplacer en s'éloignant de la face du boîtier de connecteur à embase dans la même direction que l'extrémité d'accrochage (5'; 15'; 25'; 40') de l'élément de verrouillage du type à levier et à se désengager de l'ouverture à fente (9) du connecteur à embase (2) sur lequel il est enfiché.

5

10

15

20

25

30

35

40

45

50

55

10