

[Document Name] Specification
[Title of Invention] CONTAINER WITH SPOUT AND MANUFACTURING
METHOD THEREFOR

[Technical Field]

[0001]

The present invention relates to a spout-equipped container and method of manufacturing the same and, in particular, relates to a spout-equipped pouch for containing, for example, hydrogen water, the pouch formed of a laminated film or the like having a spout attached thereto.

In more detail, the present invention relates to a spout-equipped pouch having accommodated and hermetically sealed therein hydrogen water, from which hydrogen is less prone to flow out.

[Background Art]

[0002]

Conventionally, various pouches formed of laminated films have been widely used to accommodate hydrogen water, and a pouch equipped with a spout has also been known.

This known spout-equipped pouch is manufactured by first laminating films and heat-sealing peripheral edge portions on three sides to form a pouch with an opening on one side, then inserting a spout into the opening, and then heat-sealing the films together and the films and the spout from outside the films positioned on both sides of the opening.

In this spout-equipped pouch formed of films, liquid contents of foods and so forth such as hydrogen water, juice, soup, stew, and jelly are accommodated, and a user can take out the contents from the spout.

A basic pouch material structure has been known in which a base layer, an intermediate layer formed of a film with gas barrier property and light-shielding property or the like, and a sealant layer are sequentially laminated via adhesive layers formed of an adhesive agent, anchor coat agent, heat bonding resin, or the like.

Also, a spout material structure made of polyethylene resin and polypropylene resin has been widely used.

(For example, refer to Patent Document 1.).

[Prior Art Documents]

[Patent Document]

[0003]

[Patent Document 1] Japanese Patent Application Laid-Open No. 2004-315067

[Patent Document 2] Japanese Patent Application Laid-Open No. 2007-161254

[Summary of Invention]

[Problem to be solved by the Invention]

[0004]

However, a normally-used spout made of polyethylene resin has a drawback in which hydrogen gets out of the container having hydrogen water accommodated therein.

Therefore, a main object of the present invention is to provide a spout-equipped container that is excellent in hermetical sealing performance and method of manufacturing the same.

[Solution to Problem]

[0005]

A spout-equipped container of the present invention described in claim 1 is comprising a container including an accommodating unit for accommodating hydrogen water and a spout attached to an end edge of the container and fronting the accommodating unit, wherein the spout is provided with a hermetically-sealing sheet for hermetically sealing the hydrogen water in the accommodating unit of the container, and with an aluminum region of the hermetically-sealing sheet and an aluminum region of the accommodating unit of the container in close contact with each other, hydrogen contained in the hydrogen water is less prone to get out of the accommodating unit of the container. Thereby, a spout-equipped container that is excellent in hermetical sealing performance can be provided.

A spout-equipped container of the present invention described in claim 2, wherein the spout includes a spout main body; an opening body accommodated in a cylinder of the spout main body and having formed therein a spout through hole penetrating in an axial direction; and an activating body which moves the opening body, the hermetically-sealing sheet is provided so as to cover an inner opening which fronts the accommodating unit of the container in the spout main body, the opening body is formed so as not to get out of the spout main body and is formed so as to move toward the hermetically-sealing sheet, the activating body is attached to an outer opening side of the spout main body and is formed so as to move the opening body toward the hermetically-sealing sheet, and the hermetically-sealing sheet is formed so as to be partially torn by the opening body moved toward the hermetically-sealing sheet and so that the accommodating unit of the container and an outer opening of the spout main body connect with each other via the spout through hole of the opening body. Since the spout-equipped container is formed so that the accommodated substance in the

accommodating unit of the container is poured outside from an outer opening, it is possible to provide a spout-equipped container that is excellent hermetical sealing performance before use and, when in use, allows the contents to be taken out from a suction opening by boring a hole in the hermetically-sealing sheet.

A spout-equipped container of the present invention described in claim 3, wherein the spout includes a spout main body having formed therein a through hole in an axial direction, an activating body to be screwed in one end of the spout main body in the axial direction, and an opening body inserted in the through hole of the spout main body, the through hole of the spout main body, the activating body, and the opening body are each formed in a substantially cylindrical shape concentrically in a planar view, the hermetically-sealing sheet is fixed to a bottom surface positioned at another end of the spout main body, the spout main body has a male screw unit formed on an outer surface of the one end in the axial direction and for the activating body to move in a first direction along the axial direction away from the hermetically-sealing sheet by being rotated in a connection rotating direction along a circumferential direction for making the accommodating unit of the container and the through hole of the spout main body connect with each other, and a helical guide tilted surface formed on an inner wall of the other end of the through hole in the axial direction, in the activating body, a top portion and a hanging-down portion hanging down from an end edge of the top portion to form a side wall are provided, an operating unit hanging down in a identical direction to the hanging-down portion is provided to project on an inner surface of the top portion, and a female screw unit to be screwed to the male screw unit is provided on an inner surface of the hanging-down portion, in the opening body, a blade unit in a substantially cylindrical shape formed at the other end in the axial direction and a passive shaft unit provided to protrude so as to extend in the axial direction from a top portion of the blade unit are provided, and a spout through hole is provided in the blade unit and the passive shaft unit to connect in the axial direction to penetrate therethrough, on an outer surface of the blade unit, a helical guided tilted surface corresponding to the guide tilted surface of the spout main body is formed and, when the opening body is rotated in the connection rotating direction, the guided tilted surface of the blade unit makes contact with the guide tilted surface of the spout main body to be guided, thereby causing the opening body to move in a second direction along the axial direction approaching the accommodating unit of the container, on an outer surface of the passive shaft unit, a passive unit is provided to protrude, the passive unit being pressed by the operating unit of the activating body when the activating body is rotated in the connection rotating direction, when the activating body is rotated in the connection

rotating direction, the operating unit presses the passive unit of the opening body in the connection rotating direction to proceed, and the activating body moves in the first direction so as to be removed from the spout main body, with the passive unit being pressed by the operating unit of the activating body in the connection rotating direction to proceed and rotated in the connection rotating direction, the guided tilted surface of the blade unit makes contact with the guide tilted surface of the spout main body to be guided, thereby causing the opening body to move in the second direction and causing the blade unit to protrude from a bottom surface side of the through hole formed in the spout main body while rotating, and when the blade unit protrudes from the bottom surface side of the through hole formed in the spout main body while rotating, part of the hermetically-sealing sheet is torn so as to draw an arc at a central angle smaller than 360° , thereby making the accommodating unit of the container and the through hole of the spout main body connect with each other.

A spout-equipped container of the present invention described in claim 4 is the spout-equipped container according to claim 3, wherein the spout main body further has a rotation regulating and engaging unit formed near a terminating end of the guide tilted surface, and the opening body further has a rotation regulating and engaging unit formed near a terminating end of the guided tilted surface, and with the rotation regulating and engaging unit of the spout main body and the rotation regulating and engaging unit of the opening body engaged with each other, the opening body is regulated and stopped so that a rotation central angle of the opening body in the connection rotating direction is an angle smaller than 360° .

A spout-equipped container of the present invention described in claim 5 can be provided a spout-equipped container wherein the blade unit has a blade tip portion which linearly extends and a notch portion notched upward from the blade tip portion in a side view.

A spout-equipped container of the present invention described in claim 6 can be provided a spout-equipped container wherein the blade tip portion linearly extends in parallel with a direction in which the hermetically-sealing sheet extends in a side view and has a blade protruding portion provided to protrude from a position adjacent to the notch portion toward the hermetically-sealing sheet, and the blade protruding portion includes a sharp cutting edge at a head portion in a connection rotating direction to cut into the hermetically-sealing sheet.

A spout-equipped container of the present invention described in claim 7, wherein the opening body further has a flange portion which abuts on an upper surface of the hermetically-sealing sheet after the part of the hermetically-sealing sheet is torn.

Thereby, it is possible to prevent the opening body from falling down to the accommodating unit of the container after partially tearing the hermetically-sealing sheet.

A spout-equipped container of the present invention described in claim 8 can be provided a spout-equipped container wherein the blade unit has a dimension in a radial direction larger than a dimension of an upper portion of the blade unit of the opening body in the radial direction, an opening-body accommodating unit for accommodating the blade unit of the opening body is formed in a lower portion of the through hole of the spout main body and, with the opening-body accommodating unit having a dimension in the radial direction being larger than a dimension of an upper portion of the opening-body accommodating unit of the through hole in the radial direction, a step is formed at a connecting portion between the opening-body accommodating unit and the upper portion of the opening-body accommodating unit of the through hole, with an upper end of the blade unit abutting on the step of the spout main body, movement of the opening body in the first direction away from the hermetically-sealing sheet is regulated, and the opening body does not get out of the through hole of the spout main body.

A spout-equipped container of the present invention described in claim 9 wherein the spout includes a spout main body having formed therein a through hole in an axial direction, an activating body to be screwed in one end of the spout main body in the axial direction, and an opening body inserted in the through hole of the spout main body, the through hole of the spout main body, the activating body, and the opening body are each formed in a substantially cylindrical shape concentrically in a planar view, the spout main body has a male screw unit formed on an outer surface near the one end in the axial direction and for the activating body to move in a first direction along the axial direction away from the hermetically-sealing sheet by being rotated in a connection rotating direction along a circumferential direction for making the accommodating unit of the container and the through hole of the spout main body connect with each other, in the activating body, a top portion and a hanging-down portion hanging down from an end edge of the top portion to form a side wall are provided, and a female screw unit to be screwed to the male screw unit is formed on an inner surface of the hanging-down portion, in the opening body, a spout through hole connecting in the axial direction to penetrate is formed, one end in the axial direction is integrally formed with an inner surface of the top portion of the activating body, and another end in the axial direction is fixed to the hermetically-sealing sheet, and with the activating body being rotated in the connection rotating direction to move in the first direction so as to be removed from

the spout main body, the opening body also moves in the first direction to screw part of the hermetically-sealing sheet out, thereby making the accommodating unit of the container and the through hole of the spout main body connect with each other. Thereby, a spout-equipped container in a simple structure that can be easily formed can be provided.

A spout-equipped container of the present invention described in claim 10 can be provided a spout-equipped container wherein the spout main body includes a cylindrical portion having a through hole connecting with outside, an attachment portion interposed between an end edge of a first container sheet and an end edge of a second container sheet configuring the container, and a male screw unit for screwably attaching a movable body which moves the opening body movably disposed in the through hole of the cylindrical portion, the attachment portion provided to the cylindrical portion on an accommodating unit side of the container has an inlet connecting with the spout through hole of the opening body, the activating body has a cap and a stopper, and is formed so as to form a movement gap portion by separating and removing the stopper from the cap and press the opening body in order for the cap to move the opening body toward the hermetically-sealing sheet, the opening body has, on a hermetically-sealing sheet side, a blade unit for tearing the hermetically-sealing sheet, and the blade unit has the spout through hole, the hermetically-sealing sheet is formed so as to be pasted on a container accommodating unit side surface of the attachment portion so as to cover an opening of the attachment portion, make close contact with the accommodating unit of the container, and is torn by the opening body to make the through hole of the spout main body and the accommodating unit of the container connect with each other, the opening body has a cylindrical sliding shaft unit and a blade unit for tearing the hermetically-sealing sheet, the blade unit is continuously connected to the sliding shaft unit so as to protrude in a flange shape at an end of the sliding shaft unit, the blade unit is formed so as to be in contact with a step portion or an engaging portion provided on periphery of the through hole of the spout main body to prevent the opening body from moving to a through hole side, the activating body is formed so that a pressing unit for pressing the opening body is provided inside the cap to protrude, a female screw unit is provided inside the cap, the stopper is coupled by a coupling unit intermittently provided at a lower end of the cap, a movement gap portion is formed by rotating the cap and/or rotating the stopper in a circumferential direction to remove the stopper from the cap, and the cap is moved toward the movement gap portion opening in a circumferential direction of the cylindrical portion of the spout main body to cause the pressing unit to press the

opening body.

A spout-equipped container of the present invention described in claim 11, wherein the spout main body includes a ship-shaped attachment portion to be attached to a container sheet configuring the container and a cylindrical portion continuously connected to an upper portion of the attachment portion, the attachment portion and the cylindrical portion have a through hole penetrating therethrough, the through hole has an outer opening in an upper portion of the attachment portion and an inner opening in a lower portion of the attachment portion, and the outer opening opens outside the container, and the inner opening opens toward the accommodating unit of the container. Thereby, a spout-equipped container is excellent hermetical sealing performance before use and, when in use, allows the contents to be taken out easily.

A spout-equipped container of the present invention described in claim 12, wherein the spout main body has a male screw unit circumferentially provided on an outer peripheral surface of the cylindrical portion and has an activating-body stopping unit for stopping the activating body circumferentially provided on the outer peripheral surface of the cylindrical portion below the male screw unit, the activating body includes a cap to be screwably attached to the cylindrical portion of the spout main body and a stopper removably coupled to a lower portion of the cap, and a movement regulating unit is formed so that the cap of the activating body moves downward in a height range of the movement gap portion formed when the stopper is removed to stop at a predetermined position. Thereby, it is possible to reliably open at ease.

A spout-equipped container of the present invention described in claim 13, wherein the opening body has a blade unit which tears the hermetically-sealing sheet and a sliding shaft unit provided to an upper portion of the blade unit to protrude, the blade unit and the sliding shaft unit continuously provided to the upper portion of the blade unit are in a columnar and/or pole shape, the blade unit and the sliding shaft unit have a spout through hole provided to penetrate therethrough, the spout through hole has an outlet facing the outer opening of the spout main body and an inlet facing the accommodating unit of the container, and the sliding shaft unit is formed so as to slidably fit in the through hole of the cylindrical portion of the spout main body and be pressed by the activating body to move downward. Thereby, it is possible to reliably open at ease.

A spout-equipped container of the present invention described in claim 14, wherein the opening body has a blade unit which tears the hermetically-sealing sheet and a sliding shaft unit provided to an upper portion of the blade unit to protrude, the blade unit and/or the sliding shaft unit has a rotation stop unit formed therein, the

spout main body has an attachment portion to be attached to the container and a cylindrical portion provided to an upper portion of the attachment portion to protrude, and in the attachment portion and/or the cylindrical portion, a rotation stop unit is formed for stopping rotation of the opening body for engaging or inserting the rotation stop unit of the opening body. Thereby, it is possible to reliably open at ease.

A method of manufacturing a spout-equipped container of the present invention described in claim 15, wherein a method of attaching a spout to a spout unit of a container comprises, when the spout including a cylindrical spout main body, an opening body accommodated in a cylinder of the spout main body, and an activating body which moves the opening body is manufactured, inserting the opening body in the cylinder of the spout main body and, with the opening body prevented from getting outside from the spout main body, adhering a hermetically-sealing sheet which covers an inner opening which fronts an accommodating unit in the spout main body to periphery of the inner opening in a region which fronts a container accommodating unit of the spout main body to form the spout, and welding a first container sheet and a second container sheet configuring the container on periphery of an attachment portion of the spout. Thereby, a spout-equipped container that is excellent in hermetical sealing performance can be provided.

[Advantageous Effects of Invention]

[0006]

According to the invention, a spout-equipped container is comprising a container including an accommodating unit for accommodating hydrogen water and a spout attached to an end edge of the container and fronting the accommodating unit, wherein the spout is provided with a hermetically-sealing sheet for hermetically sealing the hydrogen water in the accommodating unit of the container, and with an aluminum region of the hermetically-sealing sheet and an aluminum region of the accommodating unit of the container in close contact with each other, hydrogen contained in the hydrogen water is less prone to get out of the accommodating unit of the container. Thereby, a spout-equipped container that is excellent in hermetical sealing performance can be provided.

According to the invention described in claim 2, it is possible to provide a spout-equipped container wherein the spout includes a spout main body; an opening body accommodated in a cylinder of the spout main body and having formed therein a spout through hole penetrating in an axial direction; and an activating body which moves the opening body, the hermetically-sealing sheet is provided so as to cover an inner opening which fronts the accommodating unit of the container in the spout main

body, the opening body is formed so as not to get out of the spout main body and is formed so as to move toward the hermetically-sealing sheet, the activating body is attached to an outer opening side of the spout main body and is formed so as to move the opening body toward the hermetically-sealing sheet, and the hermetically-sealing sheet is formed so as to be partially torn by the opening body moved toward the hermetically-sealing sheet and so that the accommodating unit of the container and an outer opening of the spout main body connect with each other via the spout through hole of the opening body.

According to the invention described in claim 3, it is possible to provide a spout-equipped container wherein the spout includes a spout main body having formed therein a through hole in an axial direction, an activating body to be screwed in one end of the spout main body in the axial direction, and an opening body inserted in the through hole of the spout main body, the through hole of the spout main body, the activating body, and the opening body are each formed in a substantially cylindrical shape concentrically in a planar view, the hermetically-sealing sheet is fixed to a bottom surface positioned at another end of the spout main body, the spout main body has

a male screw unit formed on an outer surface of the one end in the axial direction and for the activating body to move in a first direction along the axial direction away from the hermetically-sealing sheet by being rotated in a connection rotating direction along a circumferential direction for making the accommodating unit of the container and the through hole of the spout main body connect with each other, and a helical guide tilted surface formed on an inner wall of the other end of the through hole in the axial direction, in the activating body, a top portion and a hanging-down portion hanging down from an end edge of the top portion to form a side wall are provided, an operating unit hanging down in a identical direction to the hanging-down portion is provided to project on an inner surface of the top portion, and a female screw unit to be screwed to the male screw unit is provided on an inner surface of the hanging-down portion, in the opening body, a blade unit in a substantially cylindrical shape formed at the other end in the axial direction and a passive shaft unit provided to protrude so as to extend in the axial direction from a top portion of the blade unit are provided, and a spout through hole is provided in the blade unit and the passive shaft unit to connect in the axial direction to penetrate therethrough, on an outer surface of the blade unit, a helical guided tilted surface corresponding to the guide tilted surface of the spout main body is formed and, when the opening body is rotated in the connection rotating direction, the guided tilted surface of the blade unit makes contact with the guide tilted surface of the spout main body to be guided, thereby causing the opening body to move

in a second direction along the axial direction approaching the accommodating unit of the container, on an outer surface of the passive shaft unit, a passive unit is provided to protrude, the passive unit being pressed by the operating unit of the activating body when the activating body is rotated in the connection rotating direction, when the activating body is rotated in the connection rotating direction, the operating unit presses the passive unit of the opening body in the connection rotating direction to proceed, and the activating body moves in the first direction so as to be removed from the spout main body, with the passive unit being pressed by the operating unit of the activating body in the connection rotating direction to proceed and rotated in the connection rotating direction, the guided tilted surface of the blade unit makes contact with the guide tilted surface of the spout main body to be guided, thereby causing the opening body to move in the second direction and causing the blade unit to protrude from a bottom surface side of the through hole formed in the spout main body while rotating, and when the blade unit protrudes from the bottom surface side of the through hole formed in the spout main body while rotating, part of the hermetically-sealing sheet is torn so as to draw an arc at a central angle smaller than 360° , thereby making the accommodating unit of the container and the through hole of the spout main body connect with each other.

According to the invention described in claim 4, it is possible to provide a spout-equipped container wherein the spout main body further has a rotation regulating and engaging unit formed near a terminating end of the guide tilted surface, and the opening body further has a rotation regulating and engaging unit formed near a terminating end of the guided tiled surface, and with the rotation regulating and engaging unit of the spout main body and the rotation regulating and engaging unit of the opening body engaged with each other, the opening body is regulated and stopped so that a rotation central angle of the opening body in the connection rotating direction is an angle smaller than 360° .

According to the invention described in claim 5, it is possible to provide a spout-equipped container wherein the blade unit has a blade tip portion which linearly extends and a notch portion notched upward from the blade tip portion in a side view. wherein the blade unit has a blade tip portion which linearly extends and a notch portion notched upward from the blade tip portion in a side view.

According to the invention described in claim 6, it is possible to provide a spout-equipped container wherein the blade tip portion linearly extends in parallel with a direction in which the hermetically-sealing sheet extends in a side view and has a blade protruding portion provided to protrude from a position adjacent to the notch

portion toward the hermetically-sealing sheet, and the blade protruding portion includes a sharp cutting edge at a head portion in a connection rotating direction to cut into the hermetically-sealing sheet.

According to the invention described in claim 7, it is possible to provide a spout-equipped container wherein the opening body further has a flange portion which abuts on an upper surface of the hermetically-sealing sheet after the part of the hermetically-sealing sheet is torn.

According to the invention described in claim 8, it is possible to provide a spout-equipped container wherein the blade unit has a dimension in a radial direction larger than a dimension of an upper portion of the blade unit of the opening body in the radial direction, an opening-body accommodating unit for accommodating the blade unit of the opening body is formed in a lower portion of the through hole of the spout main body and, with the opening-body accommodating unit having a dimension in the radial direction being larger than a dimension of an upper portion of the opening-body accommodating unit of the through hole in the radial direction, a step is formed at a connecting portion between the opening-body accommodating unit and the upper portion of the opening-body accommodating unit of the through hole, with an upper end of the blade unit abutting on the step of the spout main body, movement of the opening body in the first direction away from the hermetically-sealing sheet is regulated, and the opening body does not get out of the through hole of the spout main body.

According to the invention described in claim 9, it is possible to provide a spout-equipped container wherein the spout includes a spout main body having formed therein a through hole in an axial direction, an activating body to be screwed in one end of the spout main body in the axial direction, and an opening body inserted in the through hole of the spout main body, the through hole of the spout main body, the activating body, and the opening body are each formed in a substantially cylindrical shape concentrically in a planar view, the spout main body has a male screw unit formed on an outer surface near the one end in the axial direction and for the activating body to move in a first direction along the axial direction away from the hermetically-sealing sheet by being rotated in a connection rotating direction along a circumferential direction for making the accommodating unit of the container and the through hole of the spout main body connect with each other, in the activating body, a top portion and a hanging-down portion hanging down from an end edge of the top portion to form a side wall are provided, and a female screw unit to be screwed to the male screw unit is formed on an inner surface of the hanging-down portion, in the opening body, a spout through hole connecting in the axial direction to penetrate is

formed, one end in the axial direction is integrally formed with an inner surface of the top portion of the activating body, and another end in the axial direction is fixed to the hermetically-sealing sheet, and with the activating body being rotated in the connection rotating direction to move in the first direction so as to be removed from the spout main body, the opening body also moves in the first direction to screw part of the hermetically-sealing sheet out, thereby making the accommodating unit of the container and the through hole of the spout main body connect with each other.

According to the invention described in claim 10, it is possible to provide a spout-equipped container wherein the spout main body includes a cylindrical portion having a through hole connecting with outside, an attachment portion interposed between an end edge of a first container sheet and an end edge of a second container sheet configuring the container, and a male screw unit for screwably attaching a movable body which moves the opening body movably disposed in the through hole of the cylindrical portion, the attachment portion provided to the cylindrical portion on an accommodating unit side of the container has an inlet connecting with the spout through hole of the opening body, the activating body has a cap and a stopper, and is formed so as to form a movement gap portion by separating and removing the stopper from the cap and press the opening body in order for the cap to move the opening body toward the hermetically-sealing sheet, the opening body has, on a hermetically-sealing sheet side, a blade unit for tearing the hermetically-sealing sheet, and the blade unit has the spout through hole, the hermetically-sealing sheet is formed so as to be pasted on a container accommodating unit side surface of the attachment portion so as to cover an opening of the attachment portion, make close contact with the accommodating unit of the container, and is torn by the opening body to make the through hole of the spout main body and the accommodating unit of the container connect with each other, the opening body has a cylindrical sliding shaft unit and a blade unit for tearing the hermetically-sealing sheet, the blade unit is continuously connected to the sliding shaft unit so as to protrude in a flange shape at an end of the sliding shaft unit, the blade unit is formed so as to be in contact with a step portion or an engaging portion provided on periphery of the through hole of the spout main body to prevent the opening body from moving to a through hole side, the activating body is formed so that a pressing unit for pressing the opening body is provided inside the cap to protrude, a female screw unit is provided inside the cap, the stopper is coupled by a coupling unit intermittently provided at a lower end of the cap, a movement gap portion is formed by rotating the cap and/or rotating the stopper in a circumferential direction to remove the stopper from the cap, and the cap is moved toward the movement gap portion opening in a

circumferential direction of the cylindrical portion of the spout main body to cause the pressing unit to press the opening body.

According to the invention described in claim 11, it is possible to provide a spout-equipped container wherein the spout main body includes a ship-shaped attachment portion to be attached to a container sheet configuring the container and a cylindrical portion continuously connected to an upper portion of the attachment portion, the attachment portion and the cylindrical portion have a through hole penetrating therethrough, the through hole has an outer opening in an upper portion of the attachment portion and an inner opening in a lower portion of the attachment portion, and the outer opening opens outside the container, and the inner opening opens toward the accommodating unit of the container.

According to the invention described in claim 12, it is possible to provide a spout-equipped container wherein the spout main body has a male screw unit circumferentially provided on an outer peripheral surface of the cylindrical portion and has an activating-body stopping unit for stopping the activating body circumferentially provided on the outer peripheral surface of the cylindrical portion below the male screw unit, the activating body includes a cap to be screwably attached to the cylindrical portion of the spout main body and a stopper removably coupled to a lower portion of the cap, and a movement regulating unit is formed so that the cap of the activating body moves downward in a height range of the movement gap portion formed when the stopper is removed to stop at a predetermined position.

According to the invention described in claim 13, it is possible to provide a spout-equipped container wherein the opening body has a blade unit which tears the hermetically-sealing sheet and a sliding shaft unit provided to an upper portion of the blade unit to protrude, the blade unit and the sliding shaft unit continuously provided to the upper portion of the blade unit are in a columnar and/or pole shape, the blade unit and the sliding shaft unit have a spout through hole provided to penetrate therethrough, the spout through hole has an outlet facing the outer opening of the spout main body and an inlet facing the accommodating unit of the container, and the sliding shaft unit is formed so as to slidably fit in the through hole of the cylindrical portion of the spout main body and be pressed by the activating body to move downward.

According to the invention described in claim 14, it is possible to provide a spout-equipped container wherein the opening body has a blade unit which tears the hermetically-sealing sheet and a sliding shaft unit provided to an upper portion of the blade unit to protrude, the blade unit and/or the sliding shaft unit has a rotation stop unit formed therein, the spout main body has an attachment portion to be attached to

the container and a cylindrical portion provided to an upper portion of the attachment portion to protrude, and in the attachment portion and/or the cylindrical portion, a rotation stop unit is formed for stopping rotation of the opening body for engaging or inserting the rotation stop unit of the opening body.

According to the invention described in claim 15, it is possible to provide a method of manufacturing a spout-equipped container, wherein a method of attaching a spout to a spout unit of a container comprises, when the spout including a cylindrical spout main body, an opening body accommodated in a cylinder of the spout main body, and an activating body which moves the opening body is manufactured, inserting the opening body in the cylinder of the spout main body and, with the opening body prevented from getting outside from the spout main body, adhering a hermetically-sealing sheet which covers an inner opening which fronts an accommodating unit in the spout main body to periphery of the inner opening in a region which fronts a container accommodating unit of the spout main body to form the spout, and welding a first container sheet and a second container sheet configuring the container on periphery of an attachment portion of the spout.

[Brief Description of Drawings]

[0007]

FIG. 1 is a schematic front view depicting a spout-equipped container according to a first embodiment of the present invention.

FIG. 2 is a schematic illustrative perspective view of a spout according to the first embodiment of the present invention.

FIG. 3 is a schematic illustrative perspective view of the spout according to the first embodiment of the present invention.

FIG. 4A depicts illustrative views of a cap, (a) being an illustrative plan view, (b) being an illustrative side view, and (c) being an illustrative front view.

FIG. 4B depicts illustrative views of the cap, (a) being an illustrative longitudinal sectional view, Fig. 1 being an end face view near a top portion, and (c) being a bottom view.

FIG. 5A depicts illustrative views of a spout main body, (a) being an illustrative plan view, (b) being an illustrative side view, and (c) being an illustrative front view.

FIG. 5B depicts illustrative views of the spout main body, (a) being an illustrative longitudinal sectional view and (b) being an illustrative bottom view.

FIG. 6A depicts illustrative views of an opening body, (a) being an illustrative plan view, (b) being an illustrative side view, and (c) being an illustrative front view.

FIG. 6B depicts illustrative views of the opening body, (a) being an illustrative

longitudinal sectional view and (b) being a bottom view.

FIG. 7A is an illustrative perspective view depicting how to assemble the spout according to the first embodiment of the present invention.

FIG. 7B is an illustrative longitudinal sectional view depicting how to assemble the spout according to the first embodiment of the present invention.

FIG. 8 depicts illustrative views after the spout is attached to the container according to the first embodiment of the present invention, (a) being an illustrative front view and (b) being an illustrative enlarged side view.

FIG. 9 depicts enlarged sectional views after the spout is attached to the container according to the first embodiment of the present invention, (a) being an illustrative side view, (b) being an illustrative enlarged sectional view of an H portion of (a), and (c) being an illustrative enlarged sectional view of an I portion of (a).

FIG. 10A depicts illustrative partially-enlarged sectional views depicting a method of using the spout-equipped container according to the first embodiment of the present invention, (a) being an illustrative view in which a stopper is removed, (b) being an illustrative view depicting a state in which the cap is fastened, and (c) being an illustrative view depicting a state in which the hermetically-sealing sheet is torn.

FIG. 10B (a) is an illustrative bottom view of the hermetically-sealing sheet, (b) is an illustrative bottom view depicting a state in which the hermetically-sealing sheet is torn, and (c) is an illustrative cross-sectional view of the stopper and the spout main body.

FIG. 11A depicts illustrative views depicting a method of manufacturing the spout-equipped container according to the first embodiment of the present invention, (1) being an illustrative view depicting a first step, (2) being an illustrative view depicting a second step, and (3) being an illustrative view depicting a third step.

FIG. 11B depicts illustrative views depicting the method of manufacturing the spout-equipped container according to the first embodiment of the present invention, (4) being an illustrative view depicting a fourth step, and (5) being an illustrative view depicting a fifth step.

FIG. 11C depicts illustrative views depicting the method of manufacturing the spout-equipped container according to the first embodiment of the present invention, (6) being an illustrative view depicting a sixth step, and (7) being an illustrative view depicting a seventh step.

FIG. 12 is a front view depicting a spout-equipped container according to a second embodiment of this invention.

FIG. 13 is a perspective view depicting a spout included in the spout-equipped

container according to the second embodiment of this invention, with its bottom surface viewable.

FIG. 14 is a front view depicting a spout main body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 15A is a plan view depicting the spout main body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 15B is a side view depicting the spout main body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 15C is a bottom view depicting the spout main body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 16 depicts diagrams depicting the spout main body included in the spout-equipped container according to another embodiment the second embodiment of this invention, (A) being a sectional view along XVIA-XVIA of FIG. 15A and (B) being a sectional view along XVIB-XVIB of FIG. 15A.

FIG. 17 is a front view depicting an opening body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 18A is a plan view depicting the opening body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 18B is a side view depicting the opening body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 18C is a bottom view depicting the opening body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 19 is a sectional view depicting the opening body included in the spout-equipped container according to the second embodiment of this invention, along XIX-XIX of FIG. 18A.

FIG. 20 is a front view depicting an activating body included in the spout-equipped container according to the second embodiment of this invention.

FIG. 21 depicts diagrams depicting the activating body included in the spout-equipped container according to the second embodiment of this invention, (A) being a plan view and (B) being a bottom view.

FIG. 22 depicts diagrams depicting the activating body included in the spout-equipped container according to the second embodiment of this invention, (A) being a sectional view along XXIIA-XXIIA of FIG. 21(A) and (B) being a sectional view along XXIIB-XXIIB of FIG. 22

FIG. 23 is a perspective view depicting a tamper evidence included in the spout-equipped container according to the second embodiment of this invention.

FIG. 24 is a perspective view of the spout main body, the opening body, and the activating body included in the spout-equipped container according to the second embodiment of this invention when arranged in order of assembling and viewed from a bottom side.

FIG. 25 is a perspective view when arranged in order in a direction of fixing a hermetically-sealing sheet to the spout-equipped container according to the second embodiment of this invention and viewed from a bottom side.

FIG. 26 is a sectional view depicting the spout included in the spout-equipped container according to the second embodiment of this invention along a height direction.

FIG. 27 depicts diagrams depicting the spout included in the spout-equipped container according to the second embodiment of this invention, (A) being an end face view along XXVII-XXVII of FIG. 26 and (B) being a schematic view depicting a relation between wing pressing units and wing portions when the activating body is rotated leftward.

FIG. 28 depicts schematic development views depicting a state in which a left female screw unit of the spout main body and a left male screw unit of the opening body included in the spout-equipped container according to the second embodiment of this invention are screwed together, (A) being a diagram with a rotation angle of 0° of the opening body, (B) being a diagram with a rotation angle of 150° of the opening body, and (C) being a diagram with a rotation angle of 300° of the opening body.

FIG. 29 depicts sectional views along a width direction at the height of a rotation stop male unit of the spout main body included in the spout-equipped container according to the second embodiment of this invention, (A) being a sectional view along XXIXA-XXIXA of FIG. 26, (B) being a sectional view along XXIXB-XXIXB of FIG. 31, and (C) being a sectional view along XXIXC-XXIXC of FIG. 32.

FIG. 30 depicts schematic plan views depicting a state in which part of the hermetically-sealing sheet included in the spout-equipped container according to the second embodiment of this invention is torn, (A) being a diagram with a rotation angle of 0° of the opening body, (B) being a diagram with a rotation angle of 150° of the opening body, and (C) being a diagram with a rotation angle of 300° of the opening body.

FIG. 31 is a diagram depicting a state in which part of the hermetically-sealing sheet included in the spout-equipped container according to the second embodiment of this invention is torn, and is a sectional view along a height direction with a rotation angle of 150° of the opening body.

FIG. 32 is a diagram depicting a state in which part of the hermetically-sealing sheet included in the spout-equipped container according to the second embodiment of

this invention is torn, and is a sectional view along a height direction with a rotation angle of 300° of the opening body.

FIG. 33 is a sectional view of a portion near a flange portion of FIG. 32 depicting the spout main body according to the second embodiment of this invention.

FIG. 34 is a perspective view of a state in which part of the hermetically-sealing sheet included in the spout-equipped container according to the second embodiment of this invention is torn when viewed from a bottom side.

FIG. 35 depicts diagrams when the activating body included in the spout-equipped container according to the second embodiment of this invention is removed from the spout main body and then attached thereto again, (A) being a schematic view depicting a relation between the wing pressing units and the wing portions and (B) being a sectional view along the height direction.

FIG. 36 is an enlarged sectional view after the spout is attached to the container according to the second embodiment of this invention.

FIG. 37 is a perspective view depicting an opening body included in a spout-equipped container according to a third embodiment of this invention.

FIG. 38 is a front view depicting the opening body included in the spout-equipped container according to the third embodiment of this invention.

FIG. 39 depicts diagrams depicting the opening body included in the spout-equipped container according to the third embodiment of this invention, (A) being a plan view, (B) being a side view, and (C) being a bottom view.

FIG. 40 depicts diagrams depicting the opening body included in the spout-equipped container according to the third embodiment of this invention, (A) being a sectional view along XXXXA-XXXXA of FIG. 39(C) and (B) being a sectional view along XXXXB-XXXXB of FIG. 39(C).

FIG. 41 is a perspective view depicting an opening body included in a spout-equipped container according to a fourth embodiment of this invention.

FIG. 42 is a front view depicting the opening body included in the spout-equipped container according to the fourth embodiment of this invention.

FIG. 43 depicts diagrams depicting the opening body included in the spout-equipped container according to the fourth embodiment of this invention, (A) being a plan view, (B) being a sectional view along XXXXIIB-XXXXXIIB of (C), and (C) being a bottom view.

FIG. 44 is a perspective view of a spout included in the spout-equipped container according to the fourth embodiment of this invention, with its bottom viewable.

FIG. 45 is a front view depicting an activating body and an opening body included in a spout-equipped container according to a fifth embodiment of this invention.

FIG. 46 is a bottom view depicting the activating body and the opening body included in the spout-equipped container according to the fifth embodiment of this invention.

FIG. 47 depicts diagrams depicting a state before the activating body of a spout included in the spout-equipped container according to the fifth embodiment of this invention is moved upward, (A) being a perspective view of a state in which a bottom is viewable and (B) being a sectional view along an axial direction.

FIG. 48 depicts diagrams depicting a state after the activating body of the spout included in the spout-equipped container according to the fifth embodiment of this invention is moved upward, (A) being a perspective view of a state in which the bottom is viewable and (B) being a sectional view along the axial direction.

FIG. 49 is a bottom view depicting the spout included in the spout-equipped container according to the fifth embodiment of this invention.

FIG. 50 depicts bottom views depicting modification examples of the spout included in the spout-equipped container according to the fifth embodiment of this invention, (A) being a bottom view depicting a modification example of the spout-equipped container including a hermetically-sealing sheet fixing portion having a substantially circular shape in the bottom view and (B) being a bottom view depicting a modification example of the spout-equipped container including a hermetically-sealing sheet fixing portion having a substantially quadrangular shape in the bottom view.

FIG. 51 is an illustrative perspective view of the spout-equipped container according to the present invention.

FIG. 52 is a descriptive diagram of the spout-equipped container according to the present invention.

[Description of Embodiments]

[0008]

A standing-pouch-type spout-equipped container of an embodiment of the present invention is described further in detail with reference to the drawings and so forth.

As a result of diligent studies, the inventors have found that the above object can be achieved by contrivance so that an aluminum region of a hermetically-sealing sheet which covers a peripheral region of an inner opening of a spout inserted into an accommodating unit of a container and an aluminum region inside the accommodating unit are in close contact with each other, and have completed the present invention.

[0009]

A spout-equipped container 10 is to accommodate hydrogen water with hydrogen mixed into water, includes the container 10 which accommodates hydrogen water and a spout 12 attached to the container 10, and includes a hermetically-sealing sheet 14 which covers an inner opening 30 which fronts an accommodating unit 200 in a spout main body 20 of the spout 12.

An aluminum region of the hermetically-sealing sheet 14 and an aluminum region of an inner surface of the accommodating unit 200 of the container 10 are in close contact with each other. Therefore, the accommodating unit 200 of the container 10 is hermetically sealed, and hydrogen in hydrogen water is less prone to get out of the container 10 and the spout main body 20.

Note that the capacity of hydrogen water the spout-equipped container 10 can accommodate can be 150 ml, 300 ml, 500 ml, or the like, and is not particularly restrictive.

[0010]

The spout 12 includes the spout main body 20 in a cylindrical shape, an opening body 50 accommodated in the cylinder of the spout main body 20, an activating body 80 which moves the opening body 50, and

the hermetically-sealing sheet 14 which covers the inner opening 30 which fronts the accommodating unit 200 in the spout main body 20. An aluminum sheet configuring the hermetically-sealing sheet 14 has a size approximately equal to the bottom surface of the spout main body 20.

[0011]

The opening body 50 moves inside the cylinder of the spout main body 20 and tears the hermetically-sealing sheet 14, is formed so as not to get out of the spout main body 20 and so as to move toward the hermetically-sealing sheet 14, and has formed at its center a spout through hole 56.

The activating body 80 is attached to an outer opening 28 side of the spout main body 20, and is formed so as to move the opening body 50 on a hermetically-sealing sheet 14 side toward the hermetically-sealing sheet 14.

The opening body 50 is formed so as to move inside the cylinder of a cylindrical portion 24 directly below in its longitudinal direction.

[0012]

The hermetically-sealing sheet 14 is formed so as to be partially torn by the opening body 50 so that the accommodating unit 200 of the container 10 and an outer opening 28 of the spout main body 20 connect outside via the spout through hole 56 of

the opening body 50, and is formed so that an accommodated substance in the accommodating unit 200 of the container 10 is poured outside from the outer opening 28.

[0013]

The spout main body 20 in a cylindrical shape includes the cylindrical portion 24 having a through hole 26 which connects outside, an attachment portion 22 interposed between an end edge of a first container sheet 210 and an end edge of a second container sheet 220 configuring the container 10, and

a male screw unit 32 for screwably attaching the activating body 80 which moves the opening body 50 movably disposed in the through hole 26 of the cylindrical portion 24.

The cylindrical portion 24 of the spout main body 20 is in a cylindrical shape in a longitudinal direction. The through hole 26 formed in the cylindrical portion 24 has a circular cross section, and has the same shape from the outer opening 28 to an attachment portion 22 side in the longitudinal direction of the cylindrical portion 24.

The attachment portion 22 provided to the cylindrical portion 24 on an accommodating unit 200 side of the container 10 has an inlet 58 which connects with the spout through hole 56 of the opening body 50. The attachment portion 22 protrudes around the cylindrical portion 24 in a width direction crossing the longitudinal direction of the cylindrical portion 24 in a radial direction of the cylindrical portion 24.

[0014]

The activating body 80 has a cap 82 and a stopper 84, and is formed so as to form a movement gap portion 100 by separating and removing the stopper 84 from the cap 82 and press the opening body 50 in order to move the opening body 50 toward the hermetically-sealing sheet 14.

The activating body 80 is attached to a suction opening of the cylindrical portion 24 of the spout main body 20 by being rotated clockwise (tap-closing direction) and screwed.

[0015]

The activating body 80 has a pressing unit 86 for pressing the opening body 50 projected inside the cap 82, and is provided with a female screw unit 88 inside the cap 82. By a coupling unit 96 intermittently provided at a lower end of the cap 82, the stopper 84 is coupled.

The activating body 80 is formed so that the cap 82 is rotated in a

circumferential direction and in an opening direction (counterclockwise) to cause the stopper 84 to be removed from the cap 82 to form the movement gap portion 100 and the cap 82 is moved toward the movement gap portion 100 that is open in the circumferential direction of the cylindrical portion 24 of the spout main body 20 to cause the pressing unit 86 to press the opening body 50.

[0016]

The opening body 50 has a blade unit 52 for tearing the hermetically-sealing sheet 14 to a hermetically-sealing sheet 14 side, and that blade unit 52 has the spout through hole 56.

The opening body 50 is formed so as to move inside the cylinder of the cylindrical portion 24 of the spout main body 20 in its longitudinal direction and tear the hermetically-sealing sheet 14 directly below with the blade unit 52.

[0017]

The opening body 50 has a cylindrical sliding shaft unit 54 and the blade unit 52 for tearing the hermetically-sealing sheet 14.

The blade unit 52 is consecutively connected to the sliding shaft unit 54 so as to project in a flange shape at an end of the sliding shaft unit 54.

The blade unit 52 is formed so as to be in contact with a step portion 34 or an engaging portion provided on the periphery of the through hole 26 of the spout main body 20 and so that the opening body 50 does not move to an outer opening 28 side. Thus, in the opening body 50, the sliding shaft unit 54 abuts on the step portion 34, and is prevented from moving inside the cylinder of the cylindrical portion 24 of the spout main body 20 and projecting outward from an outer opening 28 side.

[0018]

The hermetically-sealing sheet 14 is pasted on a surface of the attachment portion 22 on an accommodating unit 200 side of the container 10 so as to cover the opening of the attachment portion 22 and is in close contact with the accommodating unit 200 of the container 10, and is formed so as to be torn by the opening body 50 to make the through hole 26 of the spout main body 20 and the accommodating unit 200 of the container 10 connect with each other.

[0019]

The spout main body 20 includes

the ship-shaped attachment portion 22 attached to the container sheets (the first container sheet 210 and the second container sheet 220) configuring the container 10, and the cylindrical portion 24 consecutively connected to an upper portion of the attachment portion 22.

The attachment portion 22 and the cylindrical portion 24 are provided with the through hole 26 penetrating therethrough.

The through hole 26 has the outer opening 28 at an upper portion of the attachment portion 22 and the inner opening 30 at a lower portion of the attachment portion 22.

The outer opening 28 opens outside the container 10. The inner opening 30 opens toward the accommodating unit 200 of the container 10.

[0020]

The spout main body 20 has the male screw unit 32 circumferentially provided on an outer peripheral surface of the cylindrical portion 24, and has an activating-body stopping unit 36 for stopping the activating body 80 circumferentially provided on the outer peripheral surface of the cylindrical portion 24 below the male screw unit 32. The male screw unit 32 is formed above from a position below the outer opening 28 by a length shorter than the length of the cap 82 of the activating body 80 in a height direction (the height of a hanging-down portion 92 of the activating body 80).

[0021]

The activating-body stopping unit 36 of the spout main body 20 has a circumferential flange shape projecting in order to engage, when the cap 82 and the stopper 84 of the activating body 80 are attached to the suction opening of the cylindrical portion 24 of the spout main body 20 and rotated in the tap-closing direction (clockwise), a lower end of the stopper 84 of the activating body 80 descending as being screwed for stopping, the flange shape having a diameter slightly longer than the cap 82 of the activating body 80.

[0022]

The activating body 80 includes the cap 82 screwably attached to the cylindrical portion 24 of the spout main body 20 and the stopper 84 removably coupled to a lower portion of the cap 82.

When the activating body 80 is placed on an outer opening 28 side of the spout main body 20 and rotated and screwed in the tap-closing direction (clockwise) to descend, the lower end of the stopper 84 abuts on an upper surface of the activating-body stopping unit 36 and stops.

[0023]

The spout main body 20 has a movement regulating unit 102 formed so that the cap 82 of the activating body 80 moves downward to stop at a predetermined position in a range of the height of the movement gap portion 100 formed when the stopper 84 is removed.

[0024]

The cap 82 includes a top portion 90 in a circular shape in a planar view and the hanging-down portion 92 hanging down from a peripheral edge of the top portion 90 to form a side wall.

The cap 82 includes the pressing unit 86 hanging down from an inner side surface of the top portion 90 in parallel with the hanging-down portion 92 with a space from the hanging-down portion 92.

On the inner peripheral surface of the hanging-down portion 92, the female screw unit 88 screwed into the screw unit 32 formed on the outer peripheral surface of the cylindrical portion 24 of the spout main body 20 is formed.

The pressing unit 86 has a length shorter than the height of the movement gap portion 100 formed by removing the stopper 84, and is formed so as to press down the sliding shaft unit 54 of the opening body 50 by the length shorter than the height of the movement space portion 100 to stop the movement. The hanging-down portion 92 has a cylindrical shape and a diameter longer than the outer diameter of the cylindrical portion 24 of the spout main body 20.

[0025]

The cap 82 configures the movement regulating unit 102, which is formed so that, when the cap 82 is pressed down to tear the hermetically-sealing sheet 14 with the stopper 84 removed, the inner surface (lower surface) of the top portion 90 abuts on the upper portion of the cylindrical portion 24 of the spout main body 20 to stop the activating body 80 at an optimal position to tear the hermetically-sealing sheet 14.

The movement regulating unit 102 is configured of the pressing unit 86 of the activating body 80 and the top portion 90, and is configured so as to press the opening body 50 by the length of the pressing unit 86 of the cap 82 and so that the lower surface (inner surface) of the top portion 90 of the cap 82 abuts on the upper portion (on an outer opening 28 side) of the cylindrical portion 24 of the spout main body 20 to regulate the amount of movement of the opening body 50.

[0026]

The stopper 84 is to regulate a screw-down width of the cap 82 and, by being removed, the cap 82 can be screwed downward to a predetermined position.

In the depicted example, the stopper 84 has an upper end coupled to the lower surface of the peripheral wall of the cap 82 via the coupling unit 96 that is easy to be cut out, thereby forming an annular band shape.

The cap 82 is screwed to the outer perimeter of the cylindrical portion 24, with the screw-down width regulated by the stopper 84. In the depicted example, the cap 82

is configured to have a top-covered cylindrical shape having the top portion 90 extended from an upper end edge of the hanging-down portion 92, with an opening at a lower end and to screw the female screw unit 88 circumferentially provided to the inner perimeter of the hanging-down portion 92 into the screw unit 32. Also, the pressing unit 86 for doing the opening body 50 from the periphery of the inner surface of the top portion 90 is provided to hang down.

[0027]

The length (height) of the stopper 84 in a vertical direction (width direction) is substantially equal to or slightly longer than the length (height) of the pressing unit 86 in a vertical direction (longitudinal direction).

The length (height) of the stopper 84 in the vertical direction (width direction) is substantially equal to or slightly longer than a movement interval of the blade unit 52 when descending to tear the hermetically-sealing sheet 14 by the blade unit 52 of the opening body 50.

The length (height) of the pressing unit 86 in the vertical direction (longitudinal direction) is substantially equal to or slightly longer than a movement interval of the blade unit 52 when descending to tear the hermetically-sealing sheet 14 by the blade unit 52 of the opening body 50.

[0028]

The opening body 50 has the blade unit 52 which tears the hermetically-sealing sheet 14 and the sliding shaft unit 54 provided to protrude from an upper portion of the blade unit 52.

The blade unit 52 and the sliding shaft unit 54 consecutively connected to the upper portion of the blade unit 52 have a columnar shape.

The blade unit 52 and the sliding shaft unit 54 have the spout through hole 56 penetrating therethrough.

The spout through hole 56 have an outlet 60 which fronts the outer opening 28 of the spout main body 20 and the inlet 58 which fronts the accommodating unit 200 of the container 10.

The sliding shaft unit 54 is formed so as to slidably fit into the through hole 26 of the cylindrical portion 24 of the spout main body 20 and be pressed by the activating body 80 to move downward.

The sliding shaft unit 54 has a cylindrical shape having a diameter slightly shorter than the diameter of the cylindrical portion 24 of the spout main body 20. The sliding shaft unit 54 has a circular cross section, and has the same shape from the outlet 60 to the upper end of the blade unit 52 in the longitudinal direction of the sliding shaft

unit 54.

The sliding shaft unit 54 of the opening body 50 concentrically overlaps the cylindrical portion 24 of the spout main body 20 in a double cylindrical shape and is slidably disposed in the cylinder of the cylindrical portion 24 so as to be vertically slidable.

The hanging-down portion 92 of the cap 82 of the activating body 80 is disposed so as to concentrically overlap the cylindrical portion 24 of the spout main body 20 in a double cylindrical shape, and is screwably disposed outside the cylinder of the cylindrical portion 24 so as to be vertically screwable.

[0029]

The blade unit 52 extends off the sliding shaft unit 54 in a direction crossing the longitudinal direction of the sliding shaft unit 54, and has an outer shape configured to be accommodated in the attachment portion 22 of the spout main body 20.

The blade unit 52 includes columnar base units 62, cutting edge units 64 projecting from the base units 62 downward, inflow ports 66 each provided to among the cutting edge units 64 and a rotation stop unit 68 provided on the periphery of the base units 62.

The base units 62 are arranged laterally in an annular shape at an appropriate space, and a space is formed between the base units 62.

Of the base units 62, the left and right base units 62 are the shortest. The length gradually increases on a front side and a backward side from the left and right base units 62.

The cutting edge unit 64 is in an annular shape continuously connected to the lower end of the base units 62 to couple the base units 61 laterally arranged together.

[0030]

In the blade unit 52, the sum of the height of the base units 62 and the height of the cutting edge unit 64 is equal to or slightly shorter than the length between the step portion 34 and the inner opening 30 of the spout main body 20.

The cutting edge unit 64 is divided forward and backward, including a forward first cutting-edge unit 70 and a backward second cutting-edge unit 72.

The first cutting-edge unit 70 is in an arc shape in a bottom view, and the second cutting-edge unit 72 is in an arc shape in a bottom view. The first cutting-edge unit 70 and the second cutting-edge unit 72 face each other.

The first cutting-edge unit 70 and the second cutting-edge unit 72 are formed so that part of the left and right blades from a center portion first in contact with the hermetically-sealing sheet 14 when the hermetically-sealing sheet 14 is cut has a height

gradually decreasing as laterally moving to cut the hermetically-sealing sheet 14.

Thus, in the hermetically-sealing sheet 14, with a region (semi-arc shape) cut by the first cutting-edge unit 70 and a region (semi-arc shape) cut by the second cutting-edge unit 72 facing each other, a semi-circular hole ringed by the region cut by the first cutting-edge unit 70 and a half-moon hole ringed by the region cut by the second cutting-edge unit 72 are bored.

However, between the region cut by the first cutting-edge unit 70 and the region cut by the second cutting-edge unit 72, an uncut residual region may remain, and the hermetically-sealing sheet 14 cut by the blade unit 52 may be configured so that a portion on the periphery of the cut portion becomes a movable region to fluidize its contents.

[0031]

On the cylindrical portion 24 of the spout main body 20, a protrusion 40 is circumferentially provided above the activating-body stopping unit 36 to regulate and protect the movement of the cap 82 and the stopper 84 of the activating body 80.

On the cylindrical portion 24 of the spout main body 20, rotation stopping units 42 are provided to protrude slightly above the activating-body stopping unit 36 for rotating only the cap 82 and stopping the rotation of the stopper 84 when the coupling unit 96 which couples the cap 82 and the stopper 84 of the activating body 80 together is separated.

The rotation stopping units 42 are configured to abut to stop the rotation of the stopper 84 when rotated in the tap-closing direction (clockwise) to close the cap 82.

[0032]

The stopper 84 of the activating body 80 is in a cylindrical shape, and has rotation stopping units 98 provided to protrude on an inner peripheral surface for rotating only the cap 82 and stopping the rotation of the stopper 84 when the coupling unit 96 which couples the cap 82 and the stopper 84 of the activating body 80 together is separated.

The rotation stopping units 98 of the activating body 80 are configured to abut on the rotation stopping units 42 of the spout main body 20 to stop the rotation of the stopper 84 when rotated in the opening direction (counterclockwise) to loosen the cap 82.

[0033]

The attachment portion 22 of the spout main body 20 is in a columnar shape with a ship-shaped cross section, and has an opening-body accommodating unit 44 for accommodating the blade unit 52 of the opening body 50 provided to be bored at the

center.

The opening-body accommodating unit 44 is a cylindrical hole concentric with the inner opening 30 and the through hole 26. The opening-body accommodating unit 44 has the step portion 34 formed near a boundary portion with the cylindrical portion 24 above.

The opening-body accommodating unit 44 has a capacity for accommodating the blade unit 52 of the opening body 50 as a whole, and has a depth length equal to or slightly longer than the sum of the height of the base units 62 and the height of the cutting edge unit 64.

The opening-body accommodating unit 44 has a diameter slightly longer than the diameter of the through hole 26 of the cylindrical portion 24.

In the opening-body accommodating unit 44, the blade unit 52 of the opening body 50 is disposed so as to be vertically movable.

[0034]

In the attachment portion 22 and/or the cylindrical portion 24, a rotation stop unit 68 is formed, wherein the rotation stop unit 68 of the opening body 50 is engaged with or inserted into to stop the rotation of the opening body 50.

The rotation stop unit insertion hole 38 of the spout main body 20 configures to accommodate the rotation stop unit 68 which stops the rotation of the opening body 50, and is a slit-shaped long groove continuously provided to the opening-body accommodating unit 44 of the attachment portion 22.

The rotation stop unit insertion hole 38 extends in a height direction of the attachment portion 22, that is, a longitudinal direction of the cylindrical portion 24, from the inner opening 30 toward the cylindrical portion 24.

In the rotation stop unit insertion hole 38 of the spout main body 20, the rotation stop unit 68 of the opening body 50 is inserted when the opening body 50 is inserted to fit in the spout main body 20 and the blade unit 52 of the opening body 50 is inserted to fit in the opening-body accommodating unit 44 of the spout main body 20.

[0035]

In the rotation stopping unit 42, as depicted in FIG. 10B(C), with respect to the rotating direction (counterclockwise) when the cap 82 is opened, a guide surface 42a is formed on a front side of the rotation stopping unit 42 and a stopper surface 42b is formed on a rear side of the rotation stopping unit 42. The guide surface 42a has a tilted shape so that, when the cap 82 is rotated in the tap-closing direction, the cap 82 can move in the tap-closing direction while a rotation stopping unit 98, which will be described below, slides on the guide surface 42a.

[0036]

The stopper surface 42b of the rotation stopping unit 42 has a shape standing in a radial direction of the cylindrical portion 24 of the spout 12. As for the stopper surface 42b, when the cap 82 is rotated in the opening direction, a tip of the rotation stopping unit 98, which will be described below, abuts on the stopper surface 42b.

[0037]

The stopper 84 has flexibility capable of being warped to some extent when an external force is applied.

The cap 82 and the stopper 84 are integrally molded with synthetic resin such as, for example, polyethylene or polypropylene.

The stopper 84 is connected to the lower end of the cap 82 via the bridge-shaped coupling unit 96.

The stopper 84 is annularly connected via a narrow-width fracture-expected portion which is fractured at the time of tap opening.

[0038]

As will be described below, the fracture-expected portion is not fractured before the cap 82 is opened. The fracture-expected portion is fractured when the cap 82 is opened.

The stopper 84 may be configured of a plurality of band elements dividable in a circumferential direction of the cap 82, and therefore may be configured of, for example, three or more band elements.

[0039]

As depicted in FIG. 10B(C), on the inner surface of the stopper 84, the paired rotation stopping units 98 are formed at portions facing at a central angle of 180° in the circumferential direction. When the cap 82 is rotated in the tap-closing direction (clockwise), these rotation stopping units 98 can move in the tap-closing direction while sliding on the outer surfaces of the rotation stopping units 42.

Conversely, when the cap 82 is rotated in the opening direction (counterclockwise), the rotation stopping units 98 each have a shape diagonally standing so that the tip of the rotation stopping unit 98 abuts on the stopper surface 42b of the rotation stopping unit 42.

[0040]

As depicted in FIG. 4, a hook unit 94 is formed on the stopper 84. The periphery of the hook unit 94 has a function of not being fractured at the time of tap-closing of the cap 82 and being fractured at the time of opening. The periphery of the hook unit 94 configures a fracture-expected portion.

[0041]

With an accommodated substance accommodated in the accommodating unit 200 of the container 10 and the cap 82 inserted into the male screw unit 32 of the cylindrical portion 24 of the spout 12, an opening end of the spout 12 (the outer opening 28 of the spout main body 20 and the outlet 60 of the opening body 50) is closed.

When the cap 82 is rotated in the tap-closing direction (clockwise), the rotation stopping unit 98 of the stopper 84 gets over the rotating stopping unit 42 while sliding on the guide surface 42a of the rotating stopping unit 42 of the spout main body 20, thereby allowing the cap 82 to rotate in the tap-closing direction.

For this reason, at the time of tap closing, the fracture-expected portion is not fractured and, with the cap 82 and the stopper 84 integrated together, the cap 82 can be screwed into a predetermined tap-closing position.

[0042]

When the cap 82 is removed from the stopper 84, the cap 82 is rotated in the opening direction (counterclockwise). As depicted in FIG. 10B(C), when the cap 82 is rotated in the opening direction (counterclockwise), the tip of each rotating stopping unit 98 abuts on the stopper surface 42b of the rotation stopping unit 42, thereby stopping the rotation of the stopper 84.

[0043]

In this state, when the stopper 84 is further rotated in the opening direction (counterclockwise), the cap 82 relatively rotates in the opening direction with respect to the stopped stopper 84.

When the cap 82 is rotated in the opening direction with the tip of the rotation stopping unit 98 abutting on the stopper surface 42b, the coupling unit 96 is separated.

Next, a finger (nail) is hooked on the hook unit 94 to fracture the fracture-expected portion on the periphery of the hook portion 94, the annular hook unit 94 is separated and removed from the cylindrical operation 24 of the spout main body 20.

[0044]

After pressing and fracturing a thin fracture line, the opening body 50 has the fractured hermetically-sealing sheet 14 fixed to the periphery of the inner opening 30 of the attachment portion 22. Therefore, inconvenience of the torn hermetically-sealing sheet 14 hanging to obstruct suction of the accommodated substance or the like can be prevented. Also, taking the trouble to discard the hermetically-sealing sheet 14 can be omitted. Since the cap 82 is screwed with the screw-down width regulated by the removable stopper 84, it is impossible to open as long as the stopper 84 is removed,

thereby reliably preventing inadvertent opening.

[0045]

Next, how to assemble the spout is described based mainly on FIG. 7.

With the rotation stop unit 68 matched to the rotation stop unit insertion hole 38 of the attachment portion 22 of the spout main body 20, the opening body 50 is inserted inside the through hole 26 of the attachment portion 22 and the cylindrical portion 24 from an inner opening 30 side of the attachment portion 22.

The opening body 50 inserted inside the through hole 26 of the spout main body 20 is in a state in which the cutting edge unit 64 at its lowermost portion does not protrude outside from the inner opening 30 of the attachment portion 22.

Then, the hermetically-sealing sheet 14 is bonded to the periphery of the inner opening 30 of the attachment portion 22.

Next, the cap 82 of the activating body 80 is rotated clockwise to be screwed in the suction opening of the cylindrical portion 24 of the spout main body 20 for attachment.

The stopper 84 of the activating body 80 abuts on the activating-body stopping unit 36 to cause the activating body 80 to stop at the predetermined position of the spout main body 20.

[0046]

Subsequently, a method of attaching the spout 12 to the container 10 is described based mainly on FIG. 11.

An original stuff (sheet-like stuff) having the first container sheet 210, the second container sheet 220, and a bottom sheet 230 continuously connected between the first container sheet 210 and the second container sheet 220 configuring the container 10 is prepared.

The original stuff (sheet-like stuff) is wound into a roll shape.

This roll-shaped original stuff (sheet-like stuff) is drawn, and the bottom sheet 230 is folded and molded to form a bottom portion 204 of a standing pouch, thereby causing the first container sheet 210 and the second container sheet 220 to face each other.

Next, a left side edge 212 of the first container sheet 210 and a left side edge 222 of the second container sheet 220 facing each other are thermally welded to form a left side portion 206.

The first container sheet 210 and the second container sheet 220 have one side portion (left side portion 206) and the bottom portion 204 connected together.

The attachment portion 22 of the spout 12 is inserted between an upper side

edge 216 of the first container sheet 210 and an upper side edge 226 of the second container sheet 220 on an upper portion opposite to the bottom portion 204.

Next, the attachment portion 22 is interposed between an inner side surface of the upper side edge 216 of the first container sheet 210 and an inner side surface of the upper side edge 226 of the second container sheet 220.

The attachment portion 22 is interposed between the inner side surface of the upper side edge 216 of the first container sheet 210 and the inner side surface of the upper side edge 226 of the second container sheet 220.

Then, the inner side surface of the upper side edge 216 of the first container sheet 210 and the inner side surface of the upper side edge 226 of the second container sheet 220 are welded together in their peripheral region, and are also welded to an outer peripheral surface of the attachment portion 22 interposed between the inner side surface of the upper side edge 216 of the first container sheet 210 and the inner side surface of the upper side edge 226 of the second container sheet 220.

Next, with one welded side portion (the left side portion 206 of the container 10) placed below and a right side edge 214 of the first container sheet 210 and a right side edge 224 of the second container sheet 220 configuring an unwelded side (a right side portion 208 of the container 10) placed above, a nozzle of an injection machine which injects an accommodated substance (hydrogen water) is inserted between the first container sheet 210 and the second container sheet 220 to fill a spout unit 202 of the container 10 with the accommodate substance (hydrogen water).

Next, an inner side surface of the right side edge 214 configuring the other side portion of the first container sheet 210 and an inner side surface of the right side edge 224 configuring the other side portion of the second container sheet 220 are welded together on their periphery to form the right side portion 208.

Hydrogen water is enclosed in the accommodating unit 200 ringed by the spout unit 202 as an upper portion, the left side portion 206, the right side portion 208, and the bottom portion 204.

Thus, the accommodated substance fills the container 10, and is hermetically closed.

[0047]

In a coupled body of the containers 10 manufactured by arranging the plurality of containers 10 in parallel, the left side portion 206 of an upper container 10 and the left side portion 206 the right side portion 208 of a lower container 10 adjacent thereto are linked together.

To separate these respective containers 10 arranged in parallel, a cut is made

as appropriate between the left side portion 206 of the upper container 10 and the right side portion 208 of the lower container 10, thereby manufacturing individual containers 10.

[0048]

As a material configuring the spout 12 of the present invention, a plastic film configuring the container 10 and a thermoplastic resin with heat-sealing property are used.

As this thermoplastic resin, for example, thermoplastic resins can be listed as follows: polyolefins such as polypropylene, propylene-ethylene copolymer, crystalline polybutene-1, crystalline poly 4-methylpentene-1, low-, medium- or high-density polyethylene, linear low-density polyethylene, ethylene-vinyl acetate copolymer (EVA), ethylene-acrylic acid copolymer (EAA), ethylene-acrylic acid ethyl copolymer (EEA), and ion-crosslinking olefin copolymer (ionomer); aromatic vinyl copolymers such as polystyrene and styrene-butadiene copolymer; vinyl halide polymers such as polyvinyl chloride and vinylidene chloride resin; nitrile polymers such as acrylonitrile-styrene copolymer and acrylonitrile-styrene-butadiene copolymer; polyamides such as nylon 6, nylon 66, and para- or meta-xylylene adipamide; polyesters such as polyethylene terephthalate, polybutylene terephthalate, poly tetra methylene terephthalate, poly-1,4- cyclohexane dimethylene terephthalate, and polyethylene naphthalate; various polycarbonates; and thermoplastic resins such as polyacetals such as polyoxymethylene.

As a particularly favorable material, for example, polyolefin resins can be listed, such as low-density polyethylene, linear low-density polyethylene, medium-density polyethylene, high-density polyethylene, polypropylene, and propylene-ethylene copolymer.

The spout main body 20, the opening body 50, and the activating body 80 can be molded by a known method, for example, injection molding or compression molding.

A gas barrier layer formed in the spout main body 20, the opening body 50, and the activating body 80 is configured of a gas-barrier-property resin layer of polyvinylidene chloride resin, EVA saponified product, nylon or cyclic olefin copolymer or the like; a resin layer having a metal oxide evaporated film of aluminum, silicon oxide, or the like; a resin layer containing a clay mineral; a metal foil of aluminum or the like, etc.

The gas barrier layer can be formed by a known method such as, for example, co-injection molding, multilayer compression molding, multicolor molding, or vapor deposition.

[0049]

As a plastic film configuring the container 10 to which the spout 12 is fixed, it is possible to use a single layer film formed of a thermoplastic resin with heat-sealing property or a laminated film having a layer structure of two or more layers with a thermoplastic resin film with heat-sealing property being taken as a bag inner layer and other films being laminated.

As a thermoplastic resin film with heat-sealing property, for example, thermoplastic resins can be listed as follows: polyolefins such as polypropylene, propylene-ethylene copolymer, crystalline polybutene-1, crystalline poly 4-methylpentene-1, low-, medium- or high-density polyethylene, linear low-density polyethylene, ethylene-vinyl acetate copolymer (EVA), ethylene-acrylic acid copolymer (EAA), ethylene-acrylic acid ethyl copolymer (EEA), and ion-crosslinking olefin copolymer (ionomer); aromatic vinyl copolymers such as polystyrene and styrene-butadiene copolymer; vinyl halide polymers such as polyvinyl chloride and vinylidene chloride resin; nitrile polymers such as acrylonitrile-styrene copolymer and acrylonitrile-styrene-butadiene copolymer; polyamides such as nylon 6, nylon 66, and para- or meta-xylylene adipamide; polyesters such as polyethylene terephthalate, polybutylene terephthalate, poly tetra methylene terephthalate, poly-1,4- cyclohexane dimethylene terephthalate, and polyethylene naphthalate; various polycarbonates; and thermoplastic resins such as polyacetals such as polyoxymethylene.

As a particularly favorable material, for example, any of olefin-based resins such as low-density polyethylene, linear low-density polyethylene, medium-density polyethylene, high-density polyethylene, polypropylene, propylene-ethylene copolymer, ethylene-vinyl acetate copolymer, and olefin-based resin graft-degenerated with ethylene-based unsaturated carboxylic acid or its anhydride; ionomer resin; relatively low melting-point or low softening-point polyamide or copolyamide resin; or polyester or copolyester resin is used.

When a laminated film is used as a plastic film configuring the container 10, a laminated film is used formed by taking the above-described thermoplastic resin film with heat-sealing property as an inner layer of the container 10 and laminating other films, via an adhesive-agent layer as required.

As a material forming the adhesive-agent layer, an adhesive resin selected from polyethylene imine resin, alkyl titanate resin, polyester-isocyanate-based resin, urethane resin, epoxy resin, polyether-based resin, olefin-based resin with a polar base introduced thereto, and so forth is used.

A film to be laminated with the heat-sealing resin is not particularly restrictive,

and any for use as a normal package bag can be used. As a material suitable for this film, any material described above for use as a heat-sealing resin can be used. However, a resin with a melting point higher than that of the resin for use for the inner layer is preferably selected.

Also, as a film configuring a region of the accommodating unit 200 of the container 10, a film formed by laminating a metal foil such as aluminum and one or two or more types of the above-described plastic films is used. In particular, in the case of hydrogen water, a laminated film including a metal foil such as aluminum is preferably used. In addition, a resin layer of polyvinylidene chloride resin, EVA saponified product, nylon or cyclic olefin copolymer, or the like; a resin layer having a metal oxide evaporated film of aluminum, silicon oxide, or the like; and a resin layer containing a clay mineral are also possible.

[0050]

The aluminum region is formed of an aluminum layer or an aluminum foil, and the aluminum layer or the aluminum foil is formed, without a gap, over an entire surface of a holding layer which holds the aluminum layer or the aluminum foil.

[0051]

The aluminum regions of the first container sheet 210, the second container sheet 220, and the hermetically-sealing sheet 14 each include an adhesive-agent layer on one main surface side of aluminum and a holding layer on the other main surface side of aluminum.

The aluminum region of the container includes an adhesive-agent layer on one main surface side of aluminum and a holding layer on the other main surface side of aluminum, and the adhesive-agent layer of the first container sheet 210 configuring the container and the adhesive-agent of the second container sheet 220 configuring the container are bonded together for adhesion.

The aluminum region of the hermetically-sealing sheet 14 adhered to the spout includes an adhesive-agent layer on one main surface side of aluminum and a holding layer on the other main surface side of aluminum.

Peripheral end edges of aluminum of the container and aluminum of the hermetically-sealing sheet 14 of the spout are close to each other so that hydrogen contained in hydrogen water do not get out thereof.

[0052]

The spout 12 is provided with the hermetically-sealing sheet 14 which covers the inner opening 30, near the inner opening 30 which fronts the accommodating unit 200 in the spout main body 20,.

[0053]

This spout-equipped container has accommodated therein liquid contents of foods and so forth such as hydrogen water, juice, fruit juice, soup, stew, jelly, and coffee, and a user can take out the contents from the spout.

In particular, even if the contents are prone to oxidation such as juice and fruit juice, by adding hydrogen, the hydrogen concentration can be kept, and the contents become resistant to oxidation due to reducing action of hydrogen.

[0054]

(Spout-Equipped Container 10 According to Second Embodiment)

In the following, a spout-equipped container 10 according to a second embodiment of this invention is described with reference to FIG. 12 to FIG. 35. FIG. 12 is a front view depicting the spout-equipped container according to the second embodiment of this invention. FIG. 13 is a perspective view depicting a spout included in the spout-equipped container according to the second embodiment of this invention, with its bottom surface viewable.

[0055]

The spout-equipped container 10 according to this embodiment includes a container 10 which accommodates hydrogen water and a spout main body 1020 attached to the container 10, and further includes a hermetically-sealing sheet 1014 which covers an inner opening 1030 which fronts an accommodating unit 200 in the spout main body 1020.

An aluminum sheet configuring the hermetically-sealing sheet 1014 has a size approximately equal to the bottom surface of the spout main body 1020.

An aluminum region of the hermetically-sealing sheet 1014 and an aluminum region of an inner surface of the accommodating unit 200 of the container 10 are in close contact with each other, and hydrogen in hydrogen water is less prone to get out of the container 10 and the spout main body 1020.

The spout-equipped container 10 according to this embodiment includes a spout 1012 for spouting hydrogen water accommodated in the container 10 to the outside.

Note that the capacity of hydrogen water the spout-equipped container 10 can accommodate can be 150 ml, 300 ml, 500 ml, or the like, and is not particularly restrictive.

[0056]

(Spout 1012)

The spout 1012 includes the spout main body 1020, an opening body 1050, and

an activating body 1080. To the bottom surface of the spout main body 1020, the hermetically-sealing sheet 1014 is fixed. The opening body 1050 is configured to be inserted into a through hole 1026 formed in the spout main body 1020 to move in a vertical direction (axial direction), and is formed so as to tear part of the hermetically-sealing sheet 1014.

The activating body 1080 is screwed to an outer opening 1028 of the through hole 1026 formed in the spout main body 1020 to hermetically seal the container 10, and is also configured to be opened at the time of spouting and move the opening body 1050 in a direction of the hermetically-sealing sheet 1014.

[0057]

(Spout Main Body 1020)

The spout main body included in the spout-equipped container 10 according to this embodiment is described based on FIG. 14 to FIG. 16. FIG. 14 is a front view depicting a spout main body included in the spout-equipped container according to the second embodiment of this invention. FIG. 15A is a plan view depicting the spout main body included in the spout-equipped container according to the second embodiment of this invention. FIG. 15B is a side view depicting the spout main body included in the spout-equipped container according to the second embodiment of this invention. FIG. 15C is a bottom view depicting the spout main body included in the spout-equipped container according to the second embodiment of this invention. FIG. 16 depicts diagrams depicting the spout main body included in the spout-equipped container according to the another embodiment second embodiment of this invention, (A) being a sectional view along XVIA-XVIA of FIG. 15A and (B) being a sectional view along XVIB-XVIB of FIG. 15A.

[0058]

The spout main body 1020 has an attachment portion 1022 attached to the container 10 and a cylindrical portion 1024 provided to protrude upward at a substantially center portion of an upper surface of a top portion of the attachment portion 1022 and serving as a portion where the opening body 1050 is inserted into a suction opening when hydrogen water is spouted.

The attachment portion 1022 and the cylindrical portion 1024 are integrally molded of a material, for example, synthetic resin or the like. In the spout main body 1020, the through hole 1026 penetrating through a substantially center thereof in a vertical direction and having a substantially circular shape in a planar view is formed. That is, the through hole 1026 penetrates from a bottom surface of the attachment portion 1022 over an upper surface of the cylindrical portion 1024.

The through hole 1026 has the inner opening 1030 formed in the bottom surface of the attachment portion 1022 and an outer opening 1028 formed in the upper surface of the cylindrical portion 1024.

[0059]

The attachment portion 1022 is attached to the container 10 so as to be interposed between an end edge of a first container sheet 1210 and an end edge of a second container sheet 1220 configuring the container 10. The attachment portion 1022 has a bottom portion having a substantially diamond shape in a planar view, side portions standing from an end edge of the bottom portion, and a top portion with a shape approximately similar to the bottom portion.

On a side portion of the attachment portion 1022 on one side, three lateral rib portion 1330a, 1330b, and 1330c, and three longitudinal rib portion 1340a, 1340b, and 1340c are provided to protrude.

The three lateral rib portion 1330a, 1330b, and 1330c linearly extend in a left-and-right direction (lateral direction). Also, the lateral rib portion 1330a, 1330b, and 1330c are parallel to each other, and are equidistantly provided in a vertical direction.

At a substantially center of the lateral rib portion 1330b, a test-purpose hole 1332 in a substantially circular shape in a planar view is formed toward the width direction so as to penetrate to the through hole 1026 described above.

[0060]

The three longitudinal rib portion 1340a, 1340b, and 1340c linearly extend in a vertical direction (longitudinal direction). The three longitudinal rib portion 1340a, 1340b, and 1340c are parallel to each other, and are equidistantly provided in a left-and-right direction.

Note that since a side portion of the attachment portion 1022 on the other side has a structure similar to the side portion on the one side except that the test-purpose hole 1332 is not formed, similar description is not repeated herein.

[0061]

The test-purpose hole 1332 is provided to check a hermetically-sealing state of the spout-equipped container after the spout 1012 is assembled. The test-purpose hole 1332 is formed so that a dedicated nozzle is thrust into the test-purpose hole 1332 to inject air to measure a change in atmospheric pressure inside the spout main body 1020.

With this, it can be checked whether an inlet 1058 (the inner opening 1030 of the through hole 1026 formed in the spout main body 1020) of a spout through hole 1056

formed in the opening body 1050 by the hermetically-sealing sheet 1014 is reliably hermetically sealed and whether an outlet 1060 (the outer opening 1028 of the through hole 1026) of the spout through hole 1056 is reliably hermetically sealed by the activating body 1080.

[0062]

At a substantially center of the attachment portion 1022, the through hole 1026 in a substantially circular shape in a planar view is formed. The through hole 1026 formed in the attachment portion 1022 has an opening-body accommodating unit 1044 serving as a space for accommodating a blade unit 1052 of the opening body 1050. The opening-body accommodating unit 1044 has a diameter and height approximately equal to or slightly larger than the diameter and height of the blade unit 1052 of the opening body 1050. On an inner wall of the opening-body accommodating unit 1044 (that is, a lower portion of a side wall of the through hole 1026), a guide tilted surface 1310d formed as a helical tilted surface is formed. A lower end of the guide tilted surface 1310d (that is, a terminating portion of the guide tilted surface 1310d) is positioned slightly above the inner opening 1030 of the through hole 1026.

And, near this terminating portion, a rotation stop male unit 1312 in a substantially quadrangular shape in a side view is provided to protrude downward (in a second direction). The rotation stop male unit 1312 configures a rotation regulating and engaging unit of the spout main body, and is formed to stop rotational motion (left rotation and right rotation in a planar view) of the opening body 1050 in a planar view and stop vertical motion of the opening body 1050 as rotating. The rotation stop male unit 1312 is in a substantially quadrangular shape in a side view.

[0063]

The cylindrical portion 1024 is in a substantially cylindrical shape having a diameter as a suction opening and a length capable of screwing and fitting the activating body 1080. On an outer surface of the cylindrical portion 1024, a right male screw unit 1032 (first male screw unit), a protrusion 1040, and rotation stopping units 1042 are provided to protrude.

[0064]

The right male screw unit 1032 is formed on an upper portion on the outer surface of the cylindrical portion 1024, and configures a male unit of a screw (hereinafter referred to as a "right screw") proceeding when the screw is turned by right rotation (clockwise) in a planar view.

The protrusion 1040 is provided over an entire circumference of the outer surface of the cylindrical portion 1024 at a lower portion of the right male screw unit

1032. The protrusion 1040 has a shape with its dimension in a radial direction gradually increasing from an upper end toward a lower end. That is, the protrusion 1040 has a shape tilted from the upper end toward the lower end. Four rotation stopping units 1042 are provided equidistantly with regard to a circumferential direction at a lower portion of the protrusion 1040.

[0065]

The rotation stopping units 1042 each has a guide surface 1042a and a stopper surface 1042b. When the cylindrical portion 1024 is viewed at right turn (clockwise) in a planar view, the guide surface 1042a is a surface which appears first, and the stopper surface 1042b is a surface which appears later. Note that appearing first when viewed at right turn (clockwise) in a planar view means that the surface is positioned on an upstream side when viewed at right turn in a planar view and appearing later when viewed at right turn (clockwise) in a planar view means that the surface is positioned on a downstream side when viewed at right turn in a planar view. The same goes for the following. The guide surface 1042a is tilted so as to have a dimension in a radial direction increasing from an end edge appearing first (end edge positioned on the upstream side) toward an end edge appearing later (end edge positioned on the downstream side) when viewed at right turn (clockwise) in a planar view. On the other hand, the stopper surface 1042b is in a shape extending in a radial direction of the cylindrical portion 1042. That is, the rotation stopping units 1042 are each in a substantially right triangle shape in a planar view.

[0066]

(Opening Body 1050)

The opening body included in the spout-equipped container 10 according to this embodiment is described based on FIG. 17 to FIG. 19. FIG. 17 is a front view depicting an opening body included in the spout-equipped container according to the second embodiment of this invention. FIG. 18A is a plan view depicting the opening body included in the spout-equipped container according to the second embodiment of this invention. FIG. 18B is a side view depicting the opening body included in the spout-equipped container according to the second embodiment of this invention. FIG. 18C is a bottom view depicting the opening body included in the spout-equipped container according to the second embodiment of this invention. FIG. 19 is a sectional view depicting the opening body included in the spout-equipped container according to the second embodiment of this invention, along XIX-XIX of FIG. 18A.

[0067]

The opening body 1050 is formed so as to move downward inside the through

hole 1026 of the spout main body 1020 so as not to get out of the spout main body 1020. The opening body 1050 has a passive shaft unit 1054 extending in an axial direction and a blade unit 1052 formed so as to cover an outer wall of a lower end of the passive shaft unit 1054. The blade unit 1052 and the passive shaft unit 1054 are integrally molded of a material such as, for example, synthetic resin. The opening body 1050 has a dimension in the vertical direction (dimension of the passive shaft unit 1054 in the vertical direction) slightly smaller than that of the spout main body 1020. In the opening body 1050, a spout through hole 1056 in a substantially circular shape in a planar view is formed, which penetrates through a substantially center of the opening body 1050 over the vertical direction, that is, penetrates therethrough from a bottom surface of the blade unit 1052 over an upper surface of the passive shaft unit 1054. The spout through hole 1056 has an inlet 1058 formed on the bottom surface of the blade unit 1052 and the outlet 1060 formed on the upper surface of the passive shaft unit 1054.

[0068]

The blade unit 1052 has its outer diameter approximately equal to or slight smaller than the inner diameter of the opening-body accommodating unit 1044 formed in the spout main body 1020. Also, the blade unit 1052 has a dimension in the vertical direction approximately equal to or slightly smaller than that of the opening-body accommodating unit 1044 formed in the spout main body 1020. The blade unit 1052 has a base unit 1062 from its upper end to a portion near a lower end and a cutting edge unit 1064 at its lower end. On an outer surface of the base unit 1062, a guided tilted surface 1360c configuring a male unit of a left screw is formed. This guided tilted surface 1360c has a helical tilted surface corresponding to the guide tilted surface 1310d formed on the inner surface of the spout main body 1020 described above. With the opening body 1050 being rotated in a connection rotating direction (left rotation in a planar view), the guided tilted surface 1360c makes contact with the guide tilted surface 1310d of the spout main body 1020 to be guided downward (second direction). Near a starting end of the guided tilted surface 1360c, a rotation stop female unit 1362 (rotation regulating and engaging unit of the opening body) is formed so as to be recessed in a substantially quadrangular shape in a side view. This rotation stop female unit 1362 operates in cooperation with the rotation stop male unit 1312 formed at the terminating portion of the guide tilted surface 1310d described above. Details of this cooperative mode will be described below. On a lower portion of the guided tilted surface 1360c in the base unit 1062, a flange portion 1370 is formed over the entire circumference as a step having a dimension in a radial direction decreasing so as to be

recessed in the radial direction.

[0069]

The cutting edge unit 1064 has a cutting-edge root portion 1066 in a substantially cylindrical shape extending from its upper end (a connecting portion to the base unit 1062) along an axial direction and a cutting-edge bottom portion 1068 having a dimension in the radial direction gradually decreasing from a lower end of the cutting-edge root portion 1066. The cutting-edge bottom portion 1068 has a blade tip portion 1070 linearly extending in a direction orthogonal to the axial direction in a side view. The blade tip portion 1070 is in a substantially annular shape having a substantially perfect circle shape in a bottom view. Also, the cutting-edge bottom portion 1068 has a notch portion 1380 in a substantially quadrangular shape in a side view notched upward from the blade tip portion 1070. The notch portion 1380 is formed at a position shifted from the rotation stop female unit 1362 formed near the starting end of the guided tilted surface 1360c described above by a central angle of approximately 300° in a planar view. Note that the notch portion 1380 preferably has a length dimension of a lower bottom slightly larger than that of an upper bottom and is formed in a trapezoidal shape with interior angles at both ends of the lower bottom (and interior angles at both ends of the upper end) being equal to each other.

[0070]

The passive shaft unit 1054 is in a substantially cylindrical shape having a dimension in the vertical direction slightly smaller than that of the cylindrical portion 1024 of the spout main body 1020. On the outer surface of the passive shaft unit 1054, as passive portions extending from its upper end to lower end in the vertical direction, three wing portions 1390 are provided to protrude. The wing portions 1390 each have a similar shape, and are equidistantly formed in a circumferential direction of the passive shaft unit 1054. In the passive shaft unit 1054, a diameter of a circle drawn when apexes of the three wing portions 1390 are connected (that is, an outer diameter including the wing portions 1390 of the passive shaft unit 1054) is approximately equal to or slightly smaller than the inner diameter of the cylindrical portion 1024 of the spout main body 1020. The wing portions 1390 have a structure for causing the opening body 1050 to rotate leftward in conjunction with left rotation (counterclockwise) of the activating body 1080. The wing portions 1390 are each formed so that, in a planar view, an angle formed by a direction in which a surface appearing first when viewed at left turn (counterclockwise) (a surface positioned on an upstream side) protrudes and a tangential direction of the outer surface of the passive shaft unit 1054 is smaller than an angle formed by a direction in which a surface appearing later when viewed at left

turn (a surface positioned on a downstream side) protrudes and the tangential direction of the outer surface of the passive shaft unit 1054. That is, the wing portions 1390 are each tilted in a planar view and when viewed at left turn so as to retreat from its root (that is, a connecting portion with the outer surface of the passive shaft unit 1054) toward its tip. Note that the outer surface of the passive shaft unit 1054 is preferably formed so as to have a dimension in the radial direction slightly decreasing from its upper end toward its lower end.

[0071]

(Activating Body 1080)

The activating body included in the spout-equipped container 10 according to this embodiment is described based on FIG. 20 to FIG. 23. FIG. 20 is a front view depicting an activating body included in the spout-equipped container according to the second embodiment of this invention. FIG. 21 depicts diagrams depicting the activating body included in the spout-equipped container according to the second embodiment of this invention, (A) being a plan view and (B) being a bottom view. FIG. 22 depicts diagrams depicting the activating body included in the spout-equipped container according to the second embodiment of this invention, (A) being a sectional view along XXIIA-XXIIA of FIG. 21(A) and (B) being a sectional view along XXII B-XXII B of FIG. 22(A). FIG. 23 is a perspective view depicting a tamper evidence included in the spout-equipped container according to the second embodiment of this invention.

[0072]

The activating body 1080 is formed so as to be removably screwable into one end of the spout main body 1020 in the axial direction and so as to move the opening body 1050 inside the through hole 1026 of the spout main body 1020 downward. The activating body 1080 includes a cap 1082 and a tamper evidence 1084 for clarifying that the cap 1082 in an initial state has been tampered.

[0073]

The cap 1082 includes a top portion 1090 in a substantially circular shape in a planar view and a hanging-down portion 1092 as a side wall hanging down from an end edge of the top portion 1090. That is, the cap 1082 is in a substantially columnar shape with an opening in its bottom surface. The top portion 1090 and the hanging-down portion 1092 are integrally molded of synthetic resin. The cap 1082 has an inner diameter approximately equal to or slightly larger than the outer diameter of the cylindrical portion 1024 of the spout main body 1020. Also, the cap 1082 has a dimension in the vertical direction approximately equal to the dimension of the spout main body 1020 from an upper end to the protrusion 1040. On an inner surface of the

top portion 1090, wing pressing units 1086 are disposed as three operating portions hanging down in the same direction as that of the hanging-down portion 1092. On an inner surface of the hanging-down portion 1092, a right female screw unit 1088 (first female screw unit) configuring a female unit of the right screw is formed. The three wing pressing units 1086 are each formed in a substantially arc shape in a planar view. Furthermore, the three wing pressing units 1086 have a similar shape. Still further, the three wing pressing units 1086 are disposed so as to draw one circle when connected to each other in a planar view. Still further, the three wing pressing units 1086 each preferably have a dimension of an end appearing later (an end positioned on a downstream side) in a radial direction when viewed at left turn in a planar view slightly larger than that of an end appearing first (an end positioned on an upstream side). This right female screw unit 1088 is screwed into the right male screw unit 1032 formed on the outer surface of the spout main body 1020 described above.

[0074]

The tamper evidence 1084 is formed in an annular shape with its inner diameter and outer diameter approximately equal to those of the cap 1082. Also, the tamper evidence 1084 has a dimension in a height direction approximately equal to that of the rotation stopping units 1042 of the spout main body 1020. The tamper evidence 1084 has two coupling units 1410 and four upper-surface preliminary coupling units 1412 provided to protrude on its upper surface, four side-surface preliminary coupling units 1414 provided to protrude on its outer surface of its side surface, and rotation stopping units 1098 provided to protrude on its inner surface of the side surface. In the activating body 1080, in an initial state at shipping (that is, in a state in which, with the hermetically-sealing sheet 1014 fixed to the bottom surface of the spout 1012 formed by assembling the spout main body 1020, the opening body 1050, and the activating body 1080, the spout 1012 is attached to the end edge of the container 10 having hydrogen water accommodated in the accommodating unit 200 for hermetical sealing), the lower end of the cap 1082 and tips of the respective two coupling units 1410 and tips of the respective four upper-surface preliminary coupling units 1412 of the tamper evidence 1084 are coupled together. Also, in an initial state, the tamper evidence 1084 is coupled over the entire circumference by the four side-surface preliminary coupling units 1414. The two coupling units 1410 are in a substantially L shape in a side view. Also, coupling of the four upper-surface preliminary coupling units 1412 and the four side-surface preliminary coupling units 1414 is configured to be easily fractured. These rotation stopping units 1098 operate in cooperation with the rotation stopping units 1042 described above. Details of this cooperation mode will be described below.

[0075]

(Procedure of Assembling Spout 1012)

Subsequently, an example of procedure of assembling the spout 1012 is described based on FIG. 24 to FIG. 26. FIG. 24 is a perspective view of the spout main body, the opening body, and the activating body included in the spout-equipped container according to the second embodiment of this invention when arranged in order of assembling and viewed from a bottom side. FIG. 25 is a perspective view when arranged in order in a direction of fixing a hermetically-sealing sheet to the spout-equipped container according to the second embodiment of this invention and viewed from a bottom side. FIG. 26 is a sectional view depicting the spout included in the spout-equipped container according to the second embodiment of this invention along a height direction.

[0076]

First, in a planar view, the activating body 1080 fits from an upper surface side of the spout main body 1020 (upper surface side of the cylindrical portion 1024) so that the center of the activating body 1080 and the center of the cylindrical portion 1024 of the spout main body 1020 are concentric with each other.

[0077]

Then, the upper end of the right male screw unit 1032 (that is, the terminating portion of the right male screw unit 1032) formed on the outer surface of the upper portion (cylindrical portion 1024) of the spout main body 1020 abuts on the lower end of the right female screw unit 1088 (that is, the starting end of the right female screw unit 1088) formed on the inner surface of the activating body 1080.

[0078]

From here, by rotating the activating body 1080 rightward (clockwise) in a planar view, the right female screw unit 1088 and the right male screw unit 1032 are screwed. With this, the activating body 1080 proceeds downward of the spout main body 1020.

[0079]

When the right female screw unit 1088 and the right male screw unit 1032 are being screwed to cause the activating body 1080 to proceed downward, the rotation stopping units 1098 provided to protrude on the inner surface of the side wall of the tamper evidence 1084 abut on the guide surfaces 1042a of the rotation stopping units 1042 provided to protrude on the outer surface of the spout main body 1020. Here, as described above, when the spout main body 1020 is viewed at right turn (clockwise) in a planar view, the guide surface 1042a is tilted so as to have a dimension in a radial

direction increasing from an end edge appearing first (end edge positioned on an upstream side) toward an end edge appearing later (end edge positioned on a downstream side). With the rotation stopping units 1042 of the spout main body 1020 having this shape, the rotation stopping units 1098 of the tamper evidence 1084 easily get over the guide surfaces 1042a of the rotation stopping units 1042 of the spout main body 1020. Therefore, the tamper evidence 1084 (activating body 1080) can continuously rotate at right turn (clockwise).

[0080]

The activating body 1080 is rotated rightward (clockwise) until the inner surface of the top portion 1090 of the activating body 1080 and the upper end of the spout main body 1020 abut or approximately abut on each other, thereby proceeding downward. When the activating body 1080 is screwed till the end, the lower end of the cap 1082 is positioned near an upper portion of the protrusion 1040 of the spout main body 1020, and the tamper evidence 1084 is positioned at a height approximately equal to the rotation stopping units 1042 of the spout main body 1020. That is, the inner surface of the hanging-down portion 1092 of the cap 1082 faces the outer surface above the protrusion 1040 of the spout main body 1020, and the inner surface of the tamper evidence 1084 faces the outer surface of the rotation stopping units 1042 of the spout main body 1020. In this manner, the activating body 1080 is screwed into the upper portion of the spout main body 1020.

[0081]

Next, the opening body 1050 is inserted from an inner opening 1030 side of the through hole 1026 of the spout main body 1020 (that is, a bottom surface side of the spout main body 1020) so that the center of the opening-body accommodating unit 1044 of the spout main body 1020 and the center of the opening body 1050 are concentric with each other in a planar view. Here, the opening body 1050 is inserted into the through hole 1026 from the upper end of the passive shaft unit 1054.

[0082]

Here, the opening body 1050 is inserted into the through hole 1026 of the spout main body 1020 so that the rotation stop male unit 1312 formed on the spout main body 1020 is at a position shifted from the rotation stop female unit 1362 formed on the opening body 1050 by a central angle of approximately 300° in a planar view. Here, the rotation stop male unit 1312 formed on the spout main body 1020 is at a position approximately equal to the notch portion 1380 formed in the opening body 1050.

[0083]

When the opening body 1050 is inserted into the through hole 1026 of the spout

main body 1020 until the guide tilted surface 1310d formed on the opening body 1050 abuts on the tip of the rotation stop male unit 1312 of the spout main body 1020, the blade unit 1052 of the opening body 1050 is completely accommodated in the opening-body accommodating unit 1044 of the spout main body 1020. Here, the upper surface of the blade unit 1052 and the upper wall of the opening-body accommodating unit 1044 in contact with or are positioned closely to each other, and the bottom surface of the blade unit 1052 and the bottom surface of the opening-body accommodating unit 1044 are at an approximately same height. That is, the bottom surface of the opening body 1050 and the bottom surface of the spout main body 1020 are at an approximately same height. Also, here, in the opening body 1050, its passive shaft unit 1054 extends inside the cylindrical portion 1024 of the spout main body 1020. That is, in the opening body 1050, its passive shaft unit 1054 extends above the opening-body accommodating unit 1044 of the through hole 1026. Note that the center of the passive shaft unit 1054 of the opening body 1050 and the center of the cylindrical portion 1024 of the spout main body 1020 are concentric with each other in a planar view. Furthermore, here, the surfaces appearing first (surfaces positioned on an upstream side) of the three wing portions 1390 provided to protrude on the outer surface of the passive shaft unit 1054 of the opening body 1050 when viewed at left turn (counterclockwise) in a planar view face the ends appearing first (ends positioned on an upstream side) of the three wing pressing units 1086 formed so as to extend downward from the top portion 1090 of the activating body 1080 when viewed at left turn (counterclockwise) in a planar view.

[0084]

In the above-described manner, the activating body 1080 is screwed to the upper portion of the spout main body 1020, and the opening body 1050 is inserted into the through hole 1026 of the spout main body 1020, thereby assembling the spout 1012. Then, the hermetically-sealing sheet 1014 is fixed to the bottom surface of the spout 1012 (that is, the bottom surface of the spout main body 1020). Here, the hermetically-sealing sheet 1014 is fixed so as to hermetically seal the inner opening 1030 of the through hole 1026. Note that the structure of the hermetically-sealing sheet 1014 is similar to the embodiment described above, and therefore similar description is not repeated herein. Then, the spout 1012 with the hermetically-sealing sheet 1014 fixed to its bottom surface is attached to the container 10. Also this attachment is similar to the embodiment described above, similar description is not repeated herein. In thus obtained spout-equipped container 10, the accommodating unit 200 of the container 10 and the through hole 1026 formed in the spout 1012 are shielded by the hermetically-sealing sheet 1014. Therefore, it is possible to prevent

hydrogen accommodated in the accommodating unit 200 of the container 10 from leaking from the through hole 1026 of the attachment portion 1022 and the spout 1012. As depicted in FIG. 26, the cap 1082, the spout main body 1020, and the opening body 1050 thus assembled as described above have a center axis C extending in the axial direction in common. That is, the cap 1082, the through hole 1026 of the spout main body 1020, and the opening body 1050 are concentric with each other and each in a substantially cylindrical shape.

[0085]

The initial state of the spout 1012 assembled as described above (a position relation among the spout main body 1020, the opening body 1050, the activating body 1080, and the hermetically-sealing sheet 1014 immediately after assembling) is as follows.

The cylindrical portion 1024 in a substantially cylindrical shape and the through hole 1026 of the spout main body 1020, the passive shaft unit 1054 in a substantially cylindrical shape and the blade unit 1052 of the opening body 1050, and the top portion 1090 and the hanging-down portion 1092 in a substantially cylindrical shape of the activating body 1080 are disposed so that the center axis C is concentric.

The activating body 1080 screwed into the upper end (one end) of the spout main body 1020 has an inner surface of the top portion 1090 in contact with the upper end of the cylindrical portion 1024 of the spout main body 1020.

The activating body 1080 screwed into the upper end (one end) of the spout main body 1020 is screwed into the upper end (one end) of the spout main body 1020, with an inner surface of the hanging-down portion 1092 along the outer surface of the cylindrical portion 1024 of the spout main body 1020 and the right female screw unit 1088 formed at the upper end of the cylindrical portion 1024 of the spout main body 1020 or the inner surface of the hanging-down portion 1092 screwed into the right male screw unit 1032 formed on the outer surface of the cylindrical portion 1024 of the spout main body 1020.

Furthermore, the tamper evidence 1084 in a substantially annular shape formed at the lower end of the activating body 1080 is at the same position as the rotation stopping units 1098 formed on the lower portion of the protrusion 1040 on the outer surface of the cylindrical portion 1024 of the spout main body 1020 in an axial direction. Then, the inner surface of the tamper evidence 1084 and the outer surface of the rotation stopping units 1098 face each other.

The opening body 1050 inserted into the through hole 1026 of the spout main body 1020 extends in an axial direction from a portion near the upper end to the lower

end of the through hole 1026 of the spout main body 1020.

The upper end of the opening body 1050 (that is, upper end of the passive shaft unit 1054) is positioned slightly below the upper end of the spout main body 1020 (that is, the upper end of the cylindrical portion 1024).

On the other hand, the lower end of the opening body 1050 (that is, the lower end of the blade unit 1052) and the lower end of the spout main body 1020 (that is, the bottom surface of the attachment portion 1022) are positioned at an approximately same height.

The upper end of the blade unit 1052 (that is, the upper end face protruding from the outer surface of the passive shaft unit 1054 in a radial direction) makes contact with a lower surface of the step portion 1034 formed on the inner wall of the through hole 1026 of the spout main body 1020.

The lower end of the opening body 1050, that is, the lower end of the blade unit 1052, makes contact with a substantially center of an upper surface (a surface on a side fixed to the bottom surface of the spout main body 1020) of the hermetically-sealing sheet 1014 fixed to the bottom surface of the spout main body 1020.

The wing pressing units 1086 hanging down from the top portion 1090 of the activating body 1080 each have an end positioned on a tip side when viewed at left turn (counterclockwise) making contact with a tip side in a radial direction of the surface appearing later (the surface positioned on the downstream side) of the wing portion 1390 of the opening body 1050 when viewed at left turn (counterclockwise) in a planar view.

Also, the wing portions 1390 provided to protrude from the outer surface of the passive shaft unit 1054 each have a tip side in a radial direction of the surface appearing later (the surface positioned on the downstream side) when viewed at left turn (counterclockwise) making contact with an end positioned on a tip side when viewed at left turn (counterclockwise) of the wing pressing unit 1086 hanging down from the top portion 1090 of the activating body 1080 in a planar view.

The rotation stop male unit 1312 formed on the inner wall of the spout main body 1020 and the rotation stop female unit 1362 formed on the outer wall of the opening body 1050 are separated from each other by a rotation angle of 300° in a circumferential direction when viewed at left turn (counterclockwise) in a planar view.

The guided tilted surface 1360c of the opening body 1050 is an upward path ascending as heading leftward from an initial state, and the guide tilted surface 1310d of the spout main body 1020 is a downward path ascending as heading leftward from an initial state.

The guided tilted surface 1360c of the opening body 1050 is positioned below the guide tilted surface 1310d of the spout main body 1020, and a lower region of the guided tilted surface 1360c is positioned near the rotation stop male unit 1312 of the spout main body 1020. The guided tilted surface 1360c of the opening body 1050 faces the guide tilted surface 1310d of the spout main body 1020.

The rotation stop female unit 1362 of the opening body 1050 is disposed at a height position substantially equal to an upper region of the guide tilted surface 1310d of the spout main body 1020 and slightly separated leftward.

[0086]

The base unit 1062 of the blade unit 1052 of the opening body 1050 has a large-diameter portion 1352 having a dimension in a radial direction equal to that of the flange portion 1370 and extending above the flange portion 1370, a small-diameter portion 1354 having a dimension in a radial direction slightly smaller than that of the flange portion 1370, and a step 1360 formed on a connecting portion between the large-diameter portion 1352 and the small-diameter portion 1354.

The step 1360 has a left-and-right-direction extending portion 1360a extending in parallel with the flange portion 1370 (that is, along a circumferential direction in a left-and-right direction in a side view) near the flange portion 1370, a standing portion 1360b slightly standing upward from one end of the left-and-right direction extending portion 1360a, a guided tilted surface 1360c tilted upper-leftward in a side view from an upper end of the standing portion 1360b and extending along the circumferential direction in the left-and-right direction in a side view to reach an upper end of the base unit 1062, and a vertical-direction extending portion 1360e tilted slightly upper-rightward from the other end of the left-and-right-direction extending portion 1360a and extending upward to reach the upper end of the base unit 1062.

An upper end of the guided tilted surface 1360c and an upper end of the vertical-direction extending portion 1360e are separated from each other in the circumferential direction. That is, part of the upper end of the base unit 1062 is configured of the upper end of the large-diameter portion 1352. One end of the upper end of the large-diameter portion 1352 in the circumferential direction is the upper end of the guided tilted surface 1360c, and the other end thereof is the upper end of the vertical-direction extending portion 1360e. The rotation stop female unit 1362 is a recess in a substantially quadrangular shape in a side view formed at a substantially center portion of the upper end of the large-diameter portion 1352 in the circumferential direction configuring part of the upper end of the base unit 1062.

The rotation stop female unit 1362 is formed near a right side (in a planar

view) of the left-and-right-direction extending portion 1360a.

The notch portion 1380 is formed below the left-and-right-direction extending portion 1360a and near a left side (in a planar view) of the rotation stop female unit 1362.

[0087]

The opening-body accommodating unit 1044 configuring a lower portion of the through hole 1026 of the spout main body 1020 has an opening-body accommodating large-diameter portion 1302 having a dimension in a radial direction corresponding to the large-diameter portion of the opening body 1050 described above, an opening-body accommodating small-diameter portion 1304 having a dimension in the radial direction corresponding to the small-diameter portion of the opening body 1050 described above, and a step 1310 formed on a connecting portion between the opening-body accommodating large-diameter portion 1302 and the opening-body accommodating small-diameter portion 1304.

The opening-body accommodating large-diameter portion 1302 extends above the inner opening 1030, and the opening-body accommodating small-diameter portion 1304 extends above the opening-body accommodating large-diameter portion 1302.

That is, the opening-body accommodating large-diameter portion 1302 has a side wall positioned on an outer diameter side of the through hole 1026 rather than a side wall of the opening-body accommodating small-diameter portion 1304.

The step has a left-and-right-direction extending portion 1310a extending in the left-and-right direction in a side view along the circumferential direction of the wall surface of the through hole 1026, a vertical-direction extending portion 1310b extending downward from one end (left end) of the left-and-right-direction extending portion 1310a in the circumferential direction along the wall surface of the through hole 1026, a lower end portion 1310c extending leftward in a side view from a lower end of the vertical-direction direction extending portion 1310b along the circumferential direction of the wall surface of the through hole 1026, and the guide tilted surface 1310d tilted upper-leftward in a side view from a left end of the lower end portion 1310c and extending in the circumferential direction of the wall surface of the through hole 1026.

The rotation stop male unit 1312 is a projection in a quadrangular shape in a side view formed at a substantially center portion of the lower end of the step 1310 in the circumferential direction. The rotation stop male unit 1312 is a projection provided to protrude downward at the lower end portion 1310c configuring the step 1310.

[0088]

(Procedure for Tearing Part of Hermetically-Sealing Sheet 1014)

Subsequently, description is made to an example of a mode in which the accommodating unit 200 of the container 10 and the through hole 1026 formed in the spout 1012 connect with each other by tearing part of the hermetically-sealing sheet 1014 to allow hydrogen water to be drunk, based on FIG. 27 to FIG. 34. FIG. 27 depicts diagrams depicting the spout included in the spout-equipped container according to the second embodiment of this invention, (A) being an end face view along XXVII-XXVII of FIG. 26 and (B) being a schematic view depicting a relation between wing pressing units and wing portions when the activating body is rotated leftward. FIG. 28 depicts schematic development views depicting a state in which a left female screw unit of the spout main body and a left male screw unit of the opening body included in the spout-equipped container according to the second embodiment of this invention are screwed together, (A) being a diagram with a rotation angle of 0° of the opening body, (B) being a diagram with a rotation angle of 150° of the opening body, and (C) being a diagram with a rotation angle of 300° of the opening body. FIG. 29 depicts sectional views along a width direction at the height of a rotation stop male unit of the spout main body included in the spout-equipped container according to the second embodiment of this invention, (A) being a sectional view along XXIXA-XXIXA of FIG. 26, (B) being a sectional view along XXIXB-XXIXB of FIG. 31, and (C) being a sectional view along XXIXC-XXIXC of FIG. 32. FIG. 30 depicts schematic plan views depicting a state in which part of the hermetically-sealing sheet included in the spout-equipped container according to the second embodiment of this invention is torn, (A) being a diagram with a rotation angle of 0° of the opening body, (B) being a diagram with a rotation angle of 150° of the opening body, and (C) being a diagram with a rotation angle of 300° of the opening body. FIG. 31 is a diagram depicting a state in which part of the hermetically-sealing sheet included in the spout-equipped container according to the second embodiment of this invention is torn, and is a sectional view along a height direction with a rotation angle of 150° of the opening body. FIG. 32 is a diagram depicting a state in which part of the hermetically-sealing sheet included in the spout-equipped container according to the second embodiment of this invention is torn, and is a sectional view along a height direction with a rotation angle of 300° of the opening body. FIG. 33 is a sectional view of a portion near a flange portion of FIG. 32 depicting the spout main body according to the second embodiment of this invention. FIG. 34 is a perspective view of a state in which part of the hermetically-sealing sheet included in the spout-equipped container according to the second embodiment of this invention is torn when viewed from a bottom side.

[0089]

The activating body 1080 is rotated leftward (counterclockwise) in a planar view by holding its hanging-down portion 1092 (rotated in a communication rotating direction), and the activating body 1080 is moved upward (first direction). With this, coupling of the four upper-surface preliminary coupling units 1412 of the tamper evidence 1084 and the lower end of the cap 1082 is fractured. Also, simultaneously with this, the rotation stopping units 1098 provided to protrude on the inner surface of the side wall of the tamper evidence 1084 each abut on the stopper surface 1042b of the rotation stopping unit 1042 provided to protrude on the outer surface of the spout main body 1020 to try to get over this. Here, since the inner diameter of the tamper evidence 1084 is spread by the rotation stopping units 1042 of the spout main body 1020, the four side-surface preliminary coupling units 1414 preliminarily coupling the tamper evidence 1084 in the circumferential direction are also fractured. Note that the two coupling units 1410 in a substantially L shape in a planar view of the tamper evidence 1084 are warped in a direction in which the inner diameter of the tamper evidence 1084 is spread, and the state of coupling with the lower end of the cap 1082 is kept.

[0090]

When the coupling of the upper-surface preliminary coupling units 1412 and the side-surface preliminary coupling units 1414 of the tamper evidence 1084 is fractured, it becomes clear that the hermetically-sealed cap 1082 has been tampered. With this, safety can be ensured. Furthermore, even if the coupling of the upper-surface preliminary coupling units 1412 and the side-surface preliminary coupling units 1414 is fractured, the tamper evidence 1084 keeps a state in which the coupling unit 1410 is coupled to the lower end of the cap 1082. That is, since the state is such that the cap 1082 and the tamper evidence 1084 are always coupled together by the coupling unit 1410, operability at the time of opening and closing the spout 1012 is favorable.

[0091]

As described above, by rotating the activating body 1080 leftward (counterclockwise) in a planar view for movement upward (first direction), the coupling of the upper-surface preliminary coupling units 1412 and the side-surface preliminary coupling units 1414 is fractured. Simultaneously with this, an end appearing first (an end positioned on an upstream side) at left turn (counterclockwise) in a planar view of each of the three wing pressing units 1086 formed so as to extend downward from the top portion 1090 of the activating body 1080 abuts on a surface appearing first at left turn (counterclockwise) (a surface positioned on the upstream side) of each of the three wing portions 1390 provided to protrude on the outer surface of the passive shaft unit

1054 of the opening body 1050, and presses the surface forward as sliding thereon. With this, the opening body 1050 inserted in the spout main body 1020 is also rotated leftward (counterclockwise) in a planar view.

[0092]

When the opening body 1050 is rotated leftward (counterclockwise) in a planar view, the guided tilted surface 1360c formed on the lower portion of the outer surface is guided and guided by the guide tilted surface 1310d formed on the inner wall of the spout main body 1020 to proceed downward (second direction). That is, the opening body 1050 moves in a downward direction (second direction) opposite to the upper direction (first direction) in which the activating body 1080 moves.

[0093]

In an initial state, the opening body 1050 has a height of the bottom surface equal to or approximately equal to the height of the bottom surface of the spout main body 1020 (that is, the height of the inner opening 1030 of the through hole 1026). From this initial state, when the opening body 1050 moves downward by being rotated leftward (counterclockwise) in a planar view, the blade unit 1052 formed at the lower end protrudes as rotating from the bottom surface of the spout main body 1020. Here, an edge portion 1380a positioned at lower left of FIG. 28 of the notch portion 1380 formed at the lower end of the blade unit 1052 tears the hermetically-sealing sheet 1014 fixed to the bottom surface of the spout main body 1020 so as to draw a circle as rotating. That is, as depicted in FIG. 30(B) (a diagram of a state in which the opening body 1050 is rotated leftward at a central angle of 150°), the edge portion tears the hermetically-sealing sheet 1014 so as to draw an arc from a tearing starting end portion 1017. In an initial state, the edge portion 1380a is in contact with or approximately in contact with the upper surface of the hermetically-sealing sheet 1014, and is positioned as rotated rightward by 60° from the most front side of the lower end of the blade unit 1052 in a substantially perfect circle shape in a planar view. From there, the edge portion 1380a rotates leftward in a planar view and tears the hermetically-sealing sheet 1014 so as to draw an arc.

[0094]

By rotating leftward (counterclockwise) at a central angle of 300°, the opening body 1050 (edge portion 1380a) tears the hermetically-sealing sheet 1014 from the tearing starting end portion 1017 to a tearing terminating portion 1018 so as to draw an arc, as depicted in FIG. 30(C). Here, the edge portion 1380a is at a position rotated leftward at 60° from the most back side of the lower end of the blade unit 1052 in a substantially perfect circle in a planar view. In this manner, a drooping portion 1016

having a tearing end edge 1019 in an arc shape at a central angle of 300° is formed. When the opening body 1050 rotates leftward from the initial state at a central angle of 300° , the opening body 1050 moves downward to cause the wing pressing units 1086 and the wing portions 1390 not to be in contact with each other, thereby stopping the rotation of the opening body 1050 and causing the rotation stop male unit 1312 formed near a start end of the guide tilted surface 1310d of the spout main body 1020 to fit in the rotation stop female unit 1362 formed near a termination end of the guided tilted surface 1360c. With this, the rotation of the opening body 1050 is regulated in a state of being rotated leftward (counterclockwise) at a central angle of 300° from the initial state, and cannot move also in the vertical direction.

[0095]

With the cap 1082 nipped by hand and rotated leftward (counterclockwise) in a planar view, the activating body 1080 moves upward (first direction, that is, a direction away from the hermetically-sealing sheet 1014) along the outer wall of the spout main body 1020. Then, when rotating leftward (counterclockwise) at a rotation angle of 300° by taking the center axis C as the center, the activating body 1080 moves upward by $5/6$ winding (winding at a central angle of 300°) from the lower end of the right female screw unit 1088 formed on the inner surface of the hanging-down portion 1092.

The opening body 1050 is pressed by the wing portions 1390 by the rotation of the activating body 1080 to rotate leftward (counterclockwise) in a planar view by taking the center axis C as the center, thereby moving downward (second direction, that is, a side of the hermetically-sealing sheet 1014) inside the through hole 1026 of the spout main body 1020. Then, when the opening body 1050 is rotated leftward (counterclockwise) at a rotation angle of 300° from the initial state by taking the center axis C as the center, the guided tilted surface 1360c of the opening body 1050 slides on the guide tilted surface 1310d of the spout main body 1020 to move downward by a distance from its lower end (that is, the lower end of the blade unit 1052) to the flange portion 1370. That is, when the opening body 1050 rotates leftward (counterclockwise) at a rotation angle of 300° by taking the center axis C as the center from the initial state, a portion from its lower end to the flange portion 1370 protrudes from the hermetically-sealing sheet 1014.

Here, the lower end face of the flange portion 1370 is in a state of being mounted on the upper surface of the warped hermetically-sealing sheet 1014.

Also, the lower end of the wing pressing units 1086 hanging down from the top portion 1090 of the activating body 1080 and the upper end of the opening body 1050 (that is, the upper end of the passive shaft unit 1054) are at an approximately same

position in an axial direction.

Then, the rotation stop male unit 1312 formed on the inner wall of the spout main body 1020 and the rotation stop female unit 1362 formed on the outer wall of the opening body 1050 are engaged with each other.

The activating body 1080 and the opening body 1050 each move along the axial direction while rotating leftward (counterclockwise) in a planar view. Therefore, the cylindrical portion 1024 of the spout main body 1020, the opening body 1050, and the activating body 1080 are each in a substantially cylindrical shape concentric with the center axis C even in a state in which the activating body 1080 and the opening body 1050 are rotated leftward (counterclockwise) at a rotation angle of 300°.

[0096]

The cylindrical portion 1024 of the spout main body 1020, the opening body 1050, and the activating body 1080 are each in a substantially cylindrical shape concentric with the center axis C. Therefore, the cylindrical portion 1024 of the spout main body 1020, the opening body 1050, and the activating body 1080 are each in a substantially perfect circle shape concentric with the center axis C (center point) in a planar view.

In the spout 1012, the center axis C linearly extends along the axial direction at the center of the cylindrical portion 1024 and the through hole 1026 in a planar view of the cylindrical portion 1024 and the through hole 1026 and at the center of the spout 1012 and the through hole 1026 in the width direction in a front view of the cylindrical portion 1024 and the through hole 1026.

Also in the spout 1012, the center axis C serves as a center point, in a planar view, of the cylindrical portion 1024 of the spout main body 1020, the opening body 1050, and the activating body 1080 each in a substantially perfect circle shape in a planar view.

[0097]

Since the activating body 1080 is in a substantially cylindrical shape, when the top portion 90 and the hanging-down portion 92 are in a planar view, these are in a substantially perfect circle shape. And, with the outer surface of the activating body 1080 held and the activating body 1080 rotated leftward (counterclockwise) in a planar view by taking the center axis C extending along the axial direction at the center of the top portion 90 and the hanging-down portion 92 and the center in the width direction of the hanging-down portion 92 as a virtual rotation axis, the activating body 1080 moves upward (first direction) along the axial direction.

Since the opening body 1050 is in a substantially cylindrical shape, when the

sliding shaft unit 54 and the blade unit 52 are in a planar view, these are in a substantially perfect circle shape. And, in the opening body 1050, the wing portions 1390 are pressed to the wing pressing units 1086 of the activating body 1080, and the opening body 1050 is rotated leftward (counterclockwise) in a planar view by taking the center axis C extending along the center of the blade unit 52 and the sliding shaft unit 54 and the center in the width direction toward the blade unit 52 and the sliding shaft unit 54 as a virtual rotation axis. With this, the opening body 1050 moves downward (second direction) along the axial direction.

When the activating body 1080 is rotated leftward (counterclockwise) in a planar view from the initial state by taking the center axis C as a virtual rotation axis, the wing pressing units 1086 of the activating body 1080 press the wing portions 1390 of the opening body 1050 forward, and the opening body 1050 is also rotated leftward (counterclockwise) in a planar view from the initial state by taking the center axis C as a virtual rotation axis.

When opening body 1050 is rotated leftward (counterclockwise) at a rotation angle of 300° in a planar view from the initial state by taking the center axis C as a virtual rotation axis, the rotation stop male unit 1312 of the spout main body 1020 engages with the rotation stop female unit 1362, and left rotation (and right rotation) by taking the center axis C as a virtual rotation axis is stopped.

[0098]

By being rotated leftward (counterclockwise) in a planar view from the initial state, the opening body 1050 moves downward (second direction). Here, the opening body 1050 rotates rightward (clockwise) when viewed from a bottom surface side.

That is, when the initial state of the spout 1012 is viewed from the bottom, the rotation stop female unit 1362 of the opening body 1050 is at a position retreated by a central angle of 300° by taking the center axis C as the center when viewed at right turn from the rotation stop male unit 1312 of the spout main body 1020, that is, at a position facing the left-and-right-direction extending portion 1310a of the step 1310 formed on a connecting portion between the opening-body accommodating large-diameter portion 1302 and the opening-body accommodating small-diameter portion 1304. From there, by being rotated rightward at a central angle of 300° in a bottom view (rotated leftward in a planar view at a central angle of 300° by taking the center axis C as the center) by taking the center axis C as the center, the rotation stop female unit 1362 proceeds via the guide tilted surface 1310d and the lower end portion 1310c configuring the step 1310 formed on the opening-body accommodating unit 1044 to engage with the rotation stop male unit 1312.

[0099]

In an initial state, the rotation stop male unit 1312 formed in the through hole 1026 of the spout main body 1020 makes contact with or approximately makes contact with the left-and-right extending portion of the step 1360 formed on the blade unit 1052 of the opening body 1050. Then, when the opening body 1050 is rotated leftward (counterclockwise) in a planar view, the rotation stop male unit 1312 of the spout main body 1020 rotates relatively to the opening body 1050, and proceeds via the left-and-right-direction extending portion 130a of the step 1360 formed on the blade unit 1052 of the opening body 1050, the standing portion 1360b, the guide tilted surface 1360c, and the upper end portion 1360d to engage with the rotation stop female unit 1362.

[0100]

As described above, by rotating the opening body 1050 leftward (counterclockwise) at a central angle of 300° , part of the hermetically-sealing sheet 1014 is torn, and the accommodating unit 200 of the container 10 and the spout through hole 1056 of the opening body 1050 and the through hole 1026 of the spout main body 1020 connect with each other. Note that the hermetically-sealing sheet 1014 is torn by the notch portion 1380 as described above only at a central angle of 300° . That is, since the remaining 60° portion of the hermetically-sealing sheet 1014 is still linked to the other portion, the state is such that the arc-shaped drooping portion 1016 droops with respect to the other portion of the hermetically-sealing sheet 1014. Therefore, no chip occurs due to tearing of the hermetically-sealing sheet 1014. As a result, since no chip falls down to the accommodating unit 200 of the container 10, it is possible to erroneously swallow a chip. Note that while the opening body 1050 is rotated leftward at a central angle of 300° in the above description, this is not restrictive, and with rotation at another angle smaller than a central angle of 360° , the state may be such that a portion obtained by tearing the hermetically-sealing sheet 1014 and other portion may be linked together.

[0101]

The blade unit 1052 is formed so as to have a dimension in the radial direction increasing upward from the lower end. Therefore, in the hermetically-sealing sheet 1014, the dimension in the radial direction of the circularly-torn portion is spread by the outer surface of the blade unit 1052 as the opening body 1050 proceeds downward, and is gradually increased. Then, after the opening body 1050 is rotated leftward (counterclockwise) at a central angle of 300° , the state is such that the bottom surface of the flange portion 1370 of the opening body 1050 is mounted on an outer edge of the

circularly-torn portion on the upper surface (inner surface) of the hermetically-sealing sheet 1014. The hermetically-sealing sheet 1014 has sufficient tension. Therefore, when torn by the blade unit 1052, the drooping portion 1016 droops from the other portion, but the other portion except the drooping portion 1016 (in particular, a portion near the tearing end edge 1019) keeps a so-called strained state. In the opening body 1050, since the flange portion 1370 abuts on the other portion except this drooping portion 1016 of the hermetically-sealing sheet 1014, it is possible to prevent falling-down to the accommodating unit 200 of the container 10 after part of the hermetically-sealing sheet 1014 is torn.

[0102]

As described above, by rotating the activating body 1080 leftward (counterclockwise) in a planar view, the activating body 1080 moves upward. With this, preliminary coupling of the tamper evidence 1084 is fractured, and it becomes clear that the hermetically-sealed cap 1082 has been tampered. Also, simultaneously with this, the opening body 1050 moves downward as rotating leftward (counterclockwise) in a planar view. With this, part of the hermetically-sealing sheet 1014 is torn, and the accommodating unit 200 of the container 10 and the through hole 1026 of the spout main body 1020 connect with each other. And, the accommodating unit 200 of the container 10 and the spout through hole 1056 of the opening body 1050 connect with each other. Here, the state is such that the activating body 1080 is rotated leftward (counterclockwise) at a central angle of approximately 300°. From here, by further rotating the activating body 1080 leftward (counterclockwise) in a planar view, the activating body 1080 is moved upward, the screwed state between the right female screw unit 1088 formed on the inner surface of the activating body 1080 and the right male screw unit 1032 formed on the outer surface of the spout main body 1020 is released, and the activating body 1080 is removed from the spout main body 1020. In this manner, the outlet 1060 of the spout through hole 1056 formed in the opening body 1050 and the outer opening 1028 formed in the spout main body 1020 are opened.

[0103]

(Regarding Mode when Activating body 1080 is Attached Again to Spout Main Body 1020)

Note that by removing the activating body 1080 from the spout main body 1020 and then attaching again, the outer opening 1028 of the through hole 1026 formed in the spout main body 1020 and the outlet 1060 of the spout through hole 1056 formed in the passive shaft unit 1054 can be closed, and hydrogen water can be prevented from leaking outside from the accommodating unit 200 of the container 10. When the

activating body 1080 covers the upper end of the spout main body 1020 and is screwed at right turn in a planar view in order to be attached to the spout main body 1020, the lower ends of the three wing portions 1390 formed on the activating body 1080 are about to abut on the upper ends of the wing pressing units 1086 of the passive shaft unit 1054 inserted in the through hole 1026.

[0104]

FIG. 35 depicts diagrams when the activating body included in the spout-equipped container according to the second embodiment of this invention is removed from the spout main body and then attached thereto again, (A) being a schematic view depicting a relation between the wing pressing units and the wing portions and (B) being a sectional view along the height direction. Here, the lower end (tip portion) of the wing pressing unit 1086 is formed smaller in width dimension than its upper end (root portion). Therefore, when the activating body 1080 is removed from the initial state and attached again, the wing pressing unit 1086 is less prone to be in contact with the wing portion 1390 of the opening body 1050. Note that, as described above, the three wing portions 1390 formed on the activating body 1080 are each formed so that, in a planar view, the angle formed by the direction in which the surface appearing first when viewed at left turn (counterclockwise) (the surface positioned on the upstream side) protrudes and the tangential direction of the outer surface of the passive shaft unit 1054 is smaller than the angle formed by the direction in which the surface appearing later when viewed at left turn protrudes and the tangential direction of the outer surface of the passive shaft unit 1054. Also, as described above, the three wing pressing units 1086 formed on the activating body 1080 are each formed so that the dimension of the end appearing later in the radial direction is slightly larger than that of the end appearing first (end positioned on an upstream side) when viewed at left turn in a planar view. With the wing portions 1390 and the wing pressing units 1086 having these shapes, even if they interfere with each other immediately before finishing to attach the activating body 1080, they can be deformed to escape forces.

[0105]

(Effects)

In the spout-equipped container 10 according to this embodiment, as described above, only by rotating the activating body 1080 leftward (counterclockwise) in a planar view from the initial state for removal from the spout main body 1020, it becomes clear that the hermetically-sealed cap 1082 has been tampered, and the accommodating unit 200 of the container 10, the through hole 1026 of the spout main body 1020, and the spout through hole 1056 of the opening body 1050 connect with one another to cause a

state in which hydrogen water is drinkable. Therefore, since no particular procedure for tearing the hermetically-sealing sheet 1014 is required, the spout-equipped container 10 with favorable operability can be provided.

[Examples]

[0106]

An example according to the first embodiment is described. FIG. 9 depicts enlarged sectional views after the spout is welded to the container according to the first embodiment of the present invention. The spout-equipped container is a suction-opening-equipped standing pouch having the spout 12 attached to the container 10.

As for the container 10, the first container sheet 210 in a substantially rectangular shape in a planar view and the second container sheet 220 in a substantially rectangular shape in a planar view are welded to a bottom sheet in a ship shape at their peripheral edges, and also welded with the left side portion 206 orthogonal to the bottom portion 204. To the resultant subject, the spout 12 is attached between the upper side edge 216 of the first container sheet 210 and the upper side edge 226 of the second container sheet 220 as upper edges on a suction opening side opposite to the bottom portion 204, with upper edges welded, for preparation.

Next, as for the container 10, hydrogen water (substance obtained by mixing hydrogen into water) is poured into the accommodating unit 200 between the right side edge 214 of the first container sheet 210 and the right side edge 224 of the second container sheet 220 that are orthogonal to the bottom portion 204, that is, between a space obtained by separation of the first container sheet 210 and the second container sheet 220, and then the right side edge 214 of the first container sheet 210 and the right side edge 224 of the second container sheet 220 are welded together, to enclose hydrogen water in the accommodating unit 200.

The first container sheet 210 and the second container sheet 220 have the same layer structure, that is, a four-layer structure, with the outside first layer made of polyethylene terephthalate (PET), the second layer inside thereof made of nylon (NY), the third layer inside thereof made of an aluminum foil (AL), and the fourth layer inside thereof made of linear low-density polyethylene (LLDPE).

The linear low-density polyethylene (LLDPE) of the fourth layer on the innermost side makes contact with hydrogen water in the accommodating unit 200.

The hermetically-sealing sheet 14 (thickness equal to or larger than 0.0006 mm and equal to or smaller than 0.2 mm) is thermally welded to the spout main body 20 of the spout 12 on a first layer side, and the first layer of the hermetically-sealing sheet 14,

the first container sheet 210, and the second container sheet 220 are welded to be in close contact with one another.

The spout 12 is molded of polyethylene.

• The hermetically-sealing sheet 14 adhered to the spout main body 20 of the spout 12 has a four-layer structure, with the first layer closest to the spout main body 20 side made of polyethylene terephthalate (PET), the second layer thereabove made of low-density polyethylene (PE), the third layer thereabove made of an aluminum foil (AL), and the fourth layer thereabove made of linear low-density polyethylene (PE).

In the hermetically-sealing sheet 14, the first layer forms a thermal welding layer configuring an adhesive-agent layer, the second layer is an intermediate layer to protect the aluminum foil of the third layer, the third layer is a layer with barrier property such as preventing hydrogen of hydrogen water or the like from getting out of the container 10 through the spout 12, and the fourth layer is a layer for retaining so that a portion rounded by a cut region at the time of tearing the hermetically-sealing sheet 14 is prevented from being cut off from the hermetically-sealing sheet 14 and falling down.

[0107]

The hermetically-sealing sheet 14 is in close contact with the fourth layer of the first container sheet 210 and the fourth layer of the second container sheet 220 of the container 10.


The fourth layer on the lowermost side makes contact with hydrogen water in the accommodating unit 200.

The container has a size of 210 mm in height, 120 mm in width, and 40 mm in thickness of the bottom portion. The aluminum sheet configuring the hermetically-sealing sheet 14 has a size size approximately equal to the bottom surface of the spout main body 1020. Hydrogen water accommodated in the container 10 is 300 ml.

In this container 10, as depicted in Table 1, hydrogen water did not get out thereof for a long period of time, while hydrogen condensation decreases in a comparative example without an aluminum sheet being pasted.

[0108]

[Table 1]



[0109]

An example according to the second embodiment is described. FIG. 36 is an enlarged sectional view after the spout is attached to the container according to the second embodiment of this invention.

The spout-equipped container is a suction-opening-equipped standing pouch

having the spout 1012 attached to the container 10.

As for the container 10, the first container sheet 210 in a substantially rectangular shape in a planar view and the second container sheet 220 in a substantially rectangular shape in a planar view are welded to a bottom sheet in a ship shape at their peripheral edges, and also welded with the left side portion 206 orthogonal to the bottom portion 204. To the resultant subject, the spout 1012 is attached between the upper side edge 216 of the first container sheet 210 and the upper side edge 226 of the second container sheet 220 as upper edges on a suction opening side opposite to the bottom portion 204, with upper edges welded, for preparation.

Next, as for the container 10, hydrogen water (substance obtained by mixing hydrogen into water) is poured into the accommodating unit 200 between the right side edge 214 of the first container sheet 210 and the right side edge 224 of the second container sheet 220 that are orthogonal to the bottom portion 204, that is, between a space obtained by separation of the first container sheet 210 and the second container sheet 220, and then the right side edge 214 of the first container sheet 210 and the right side edge 224 of the second container sheet 220 are welded together, to enclose hydrogen water in the accommodating unit 200.

The first container sheet 210 and the second container sheet 220 have the same layer structure, that is, a four-layer structure, with the outside first layer made of polyethylene terephthalate (PET), the second layer inside thereof made of an aluminum foil (AL), the third layer inside thereof made of nylon (NY) and the fourth layer inside thereof made of linear low-density polyethylene (LLDPE).

The hermetically-sealing sheet 1014 (thickness equal to or larger than 0.0006 mm and equal to or smaller than 0.2 mm) adhered to the spout main body 1020 of the spout 1012 has a four-layer structure, with the first layer on the most spout main body 1020 side made of low-density polyethylene (PE), the second layer thereabove made of an aluminum foil (AL), the third layer thereabove made of low-density polyethylene (PE), and the fourth layer thereabove made of polyethylene terephthalate (PET).

The hermetically-sealing sheet 1014 is thermally welded to the spout main body 1020 of the spout 1012 on a first layer side, and the first layer of the hermetically-sealing sheet 1014, the first container sheet 210, and the second container sheet 220 are welded to be in close contact with one another.

The spout 1012 is molded of polyethylene.

In the hermetically-sealing sheet 1014, the first layer forms a thermal welding layer configuring an adhesive-agent layer, the second layer is a layer with barrier property such as preventing hydrogen of hydrogen water or the like from getting out of

the container 10 through the spout 1012, and the third layer and the fourth layers are layers for retaining so that a portion rounded by a cut region at the time of tearing the hermetically-sealing sheet 1014 is prevented from being cut off from the hermetically-sealing sheet 1014 and falling down.

[0110]

The hermetically-sealing sheet 1014 is in close contact with the fourth layer of the first container sheet 210 and the fourth layer of the second container sheet 220 of the container 10.

The fourth layer on the lowermost side makes contact with hydrogen water in the accommodating unit 200.

The container has a size of 210 mm in height, 120 mm in width, and 40 mm in thickness of the bottom portion. The aluminum sheet configuring the hermetically-sealing sheet 14 has a size approximately equal to the bottom surface of the spout main body 1020. Hydrogen water accommodated in the container 10 is 300 ml.

[0111]

(Spout-Equipped Container 10 According to Third Embodiment)

Next, a spout-equipped container according to a third embodiment of this invention is described based on FIG. 37 to FIG. 40. Note that the spout-equipped container according to the third embodiment of this invention has a structure similar to that of the spout-equipped container according to the second embodiment described above except the blade unit of the opening body (that is, the container 10, the spout main body 1020, the cap 1082, and the hermetically-sealing sheet 1014, and a portion above the blade unit 1052 of the opening body 1050 are identical to those of the second embodiment described above). Therefore, identical portions are provided with the same reference character, and similar description is not repeated. FIG. 37 is a perspective view depicting an opening body included in a spout-equipped container according to a third embodiment of this invention. FIG. 38 is a front view depicting the opening body included in the spout-equipped container according to the third embodiment of this invention. FIG. 39 depicts diagrams depicting the opening body included in the spout-equipped container according to the third embodiment of this invention, (A) being a plan view, (B) being a side view, and (C) being a bottom view. FIG. 40 depicts diagrams depicting the opening body included in the spout-equipped container according to the third embodiment of this invention, (A) being a sectional view along XXXXA-XXXXA of FIG. 36(C) and (B) being a sectional view along XXXXB-XXXXB of FIG. 36(C).

[0112]

The blade unit 1052 according to this embodiment has a blade protruding portion 1072 in a substantially quadrangular shape in a side view provided to protrude downward from a position adjacent to the notch portion 1380 of the blade tip portion 1070 at a lower end of the blade unit 1052.

That is, the blade unit 1052 has a sharp cutting edge for a head portion in a connection rotating direction of the blade tip portion 1070 to cut into the hermetically-sealing sheet 1014. A right end side of the blade protruding portion 1072 is formed so as to linearly extend in the vertical direction continuously with a left end side of the notch portion 1380. A lower end side of the blade protruding portion 1072 is parallel with the blade tip portion 1070 in a side view. As with the blade unit 1052 according to the second embodiment described above, with the opening body 1050 moving while rotating downward (a side of the hermetically-sealing sheet 1014), the hermetically-sealing sheet 1014 is torn by a corner portion formed of the right end side and the lower end side of the blade protruding portion 1072. In the blade unit 1052 according to this embodiment, with this blade protruding portion 1072, sharpness becomes more favorable. Therefore, in the spout-equipped container 10 according to this embodiment, the hermetically-sealing sheet 1014 can be easily torn, and the drooping portion 1016 of the hermetically-sealing sheet 1014 becomes less prone to fall down to the accommodating unit 200 of the container 10.

[0113]

(Spout-Equipped Container 10 According to Fourth Embodiment)

Next, a spout-equipped container 10 according to a fourth embodiment of this invention is described with reference to FIG. 41 to FIG. 44. Note that the spout-equipped container according to this embodiment has a structure similar to the spout-equipped container according to the second embodiment described above, except an opening body (that is, the container 10, the spout main body 1020, the cap 1082, and the hermetically-sealing sheet 1014 are identical to those of the second and third embodiments described above). Therefore, identical portions are provided with a same reference character, and similar description is not repeated herein. FIG. 41 is a perspective view depicting an opening body included in a spout-equipped container according to a fourth embodiment of this invention. FIG. 42 is a front view depicting the opening body included in the spout-equipped container according to the fourth embodiment of this invention. FIG. 43 depicts diagrams depicting the opening body included in the spout-equipped container according to the fourth embodiment of this invention, (A) being a plan view, (B) being a sectional view along XXXXIIB-XXXIIB

of (C), and (C) being a bottom view. FIG. 44 is a perspective view of a spout included in the spout-equipped container according to the fourth embodiment of this invention, with its bottom viewable.

[0114]

The passive shaft unit 1054 of the opening body 1050 according to the second embodiment described above has an approximately same shape along the axial direction from its upper end to lower end. That is, at any position in the axial direction, the passive shaft unit 1054 according to the second embodiment described above has an approximately same cross-section shape along a plane orthogonal to the axial direction, that is, a plane extending in parallel with the bottom surface of the spout main body 1020. On the other hand, in the passive shaft unit 1054 according to this embodiment, the shape of a lower end is different from the shape of other portion. Specifically, in the passive shaft unit 1054 according to this embodiment, a portion from its upper end to a portion around a substantially center portion of the blade unit 1052 in the axial direction has the same shape as the passive shaft unit 1054 according to the second embodiment described above, a portion from the portion around the substantially center portion of the blade unit 1052 in the axial direction to a lower end is a hermetically-sealing-sheet abutment support unit 1074 formed so as to be in a substantial cross in a bottom view. The hermetically-sealing-sheet abutment support unit 1074 has a first plate-shaped portion 1076 in a flat plate shape extending along the axial direction and a second plate-shaped portion 1077 in a flat plate shape extending along the axial direction and orthogonal to the first plate-shaped portion 1076 in a bottom view. The first plate-shaped portion 1076 and the second plate-shaped portion 1077 have the same shape. The first plate-shaped portion 1076 and the second plate-shaped portion 1077 cross at their substantially center portions in a bottom view, and are integrally formed at their crossing portion. And, a lower end of the hermetically-sealing-sheet abutment support unit 1074 (that is, lower end faces of the first plate-shaped portion 1076 and the second plate-shaped portion 1077) abuts on the upper surface of the hermetically-sealing sheet 1014 in an initial state.

[0115]

In the spout container 10 according to this embodiment, by providing the hermetically-sealing-sheet abutment support unit 1074 as described above, the hermetically-sealing sheet 1014 can be supported from its upper surface in an initial state. Therefore, it is possible to prevent the hermetically-sealing sheet 1014 from being inadvertently broken. Also, with the hermetically-sealing-sheet abutment support unit 1074 having a substantially cross shape in a bottom view, a sufficiently

large space is formed on the periphery of the hermetically-sealing-sheet abutment support unit 1074 (such as the periphery of a portion where the first plate-shaped portion 1076 and the second plate-shaped portion 1077 cross). With this, penetration in the axial direction including the spout through hole 1056 of the opening body 1050 can be ensured, and therefore the hermetically-sealing-sheet abutment support unit 1074 is not an obstruction when hydrogen water is spouted from the accommodating unit 200 of the container 10.

[0116]

(Spout-Equipped Container 10 According to Fifth Embodiment)

Next, a spout-equipped container 10 according to a fifth embodiment of this invention is described with reference to FIG. 45 to FIG. 49. FIG. 45 is a front view depicting an activating body and an opening body included in a spout-equipped container according to a fifth embodiment of this invention. FIG. 46 is a bottom view depicting the activating body and the opening body included in the spout-equipped container according to the fifth embodiment of this invention. FIG. 47 depicts diagrams depicting a state before the activating body of a spout included in the spout-equipped container according to the fifth embodiment of this invention is moved upward, (A) being a perspective view of a state in which a bottom is viewable and (B) being a sectional view along an axial direction. FIG. 48 depicts diagrams depicting a state after the activating body of the spout included in the spout-equipped container according to the fifth embodiment of this invention is moved upward, (A) being a perspective view of a state in which the bottom is viewable and (B) being a sectional view along the axial direction. FIG. 49 is a bottom view depicting the spout included in the spout-equipped container according to the fifth embodiment of this invention.

[0117]

In the spout-equipped container 10 according to this embodiment, the activating body 1080 and the opening body 1050 are integrally formed. Specifically, an inner surface (bottom surface) of the top portion 1090 of the activating body 1080 and an upper end (one end in the axial direction) of the opening body 1050 are integrally formed. And, a lower end (the other end in the axial direction) of the opening body 1050 is fixed to the upper surface of the hermetically-sealing sheet 1014 in an initial state. Note that an opening-body main shaft unit 1078 in a substantially columnar shape is formed in a portion nearby from the upper end to the lower end of the opening body 1050, and a hermetically-sealing sheet fixing portion 1079 in a substantially cross shape in a bottom view is formed at the lower end of the opening body 1050. That is, the upper surface of the hermetically-sealing sheet 1014 is fixed to a lower end face of

the hermetically-sealing sheet fixing portion 1079.

[0118]

In the spout container 10 according to this embodiment, with the activating body 1080 being rotated in a connection rotating direction and the activating body 1080 and the opening body 1050 moving upward (first direction) so as to be removed from the spout main body 1020, part of the hermetically-sealing sheet 1014 with its upper surface fixed to the activating body 1080 is screwed out, thereby making the accommodating unit 200 of the container 10 and the through hole 1026 of the spout main body 1020 connect with each other.

[0119]

The spout 1012 according to the second embodiment described above has the structure for rotating the opening body 1050 (the guide tilted surface 1310d of the spout main body 1020, the wing pressing units 1086 of the activating body 1080, and the guided tilted surface 1360c and the wing portions 1390 of the opening body 1050). Furthermore, the activating body 1080 according to the embodiment described above has the spout through hole 1056 penetrating in the axial direction. On the other hand, the spout 1012 according to this embodiment does not have (is not required to have) these structures, and therefore has a simple structure and can be easily formed.

[0120]

FIG. 50 depicts bottom views depicting modification examples of the spout included in the spout-equipped container according to the fifth embodiment of this invention. The hermetically-sealing sheet fixing portion 1079 of the opening body 1050 included in the spout container 10 according to the fifth embodiment described above is not restricted to have a substantial cross in a bottom view. That is, the hermetically-sealing sheet fixing portion 1079 may be in a substantially circular shape in a bottom view as depicted in FIG. 50(A), or the hermetically-sealing sheet fixing portion 1079 may be in a substantially quadrangular shape in a bottom view as depicted in FIG. 50(B). Thus-shaped hermetically-sealing sheet fixing portion 1079 has a larger area to be fixed to the hermetically-sealing sheet 1014, and therefore the hermetically-sealing sheet 1014 can be neatly cut.

[0121]

Note that in the embodiments described above, description has been made to the case in which the male screw unit and the female screw unit are the right male screw unit 1032 and the right female screw unit 1088 and the guide tilted surface and the guided tilted surface are the guide tilted surface 1310d and the guided tilted surface 1360c that are sinistral. However, this is not meant to be restrictive, and the male

screw unit and the female screw unit may be left screws and the guide tilted surface and the guided tilted surface may be dextral.

[0122]

Note that in the embodiments described above, description has been made to the case in which the rotation regulating and engaging unit of the spout main body 1020 is the rotation stop male unit 1312 as a male unit and the rotation regulating and engaging unit of the opening body 1050 is the rotation stop female unit 1362 as a female unit. However, this is not meant to be restrictive, and the rotation regulating and engaging unit of the spout main body 1020 may be the rotation stop male unit 1312 as a female unit and the rotation regulating and engaging unit of the opening body 1050 may be the rotation stop female unit 1362 as a male unit.

[Reference Signs List]

[0123]

10	container
200	accommodating unit
202	spout unit
204	bottom portion
206	left side portion
208	right side portion
210	first container sheet
212	left side edge
214	right side edge
216	upper side edge
220	second container sheet
222	left side edge
224	right side edge
226	upper side edge
230	bottom sheet
12	spout
14	hermetically-sealing sheet
20	spout main body
22	attachment portion
24	cylindrical portion
26	through hole
28	outer opening
30	inner opening

32	male screw unit
34	step portion
36	activating-body stopping unit
38	rotation stop unit insertion hole
40	protrusion
42a	guide surface
42b	stopper surface
42	rotation stopping unit
44	opening-body accommodating unit
102	movement regulating unit
50	opening body
52	blade unit
54	sliding shaft unit
56	spout through hole
58	inlet
60	outlet
62	base unit
64	cutting edge unit
66	inflow port
68	rotation stop unit
70	first cutting-edge unit
72	second cutting-edge unit
90	activating body
82	cap
84	stopper
86	pressing unit
88	female screw unit
90	top portion
92	hanging-down portion
94	hook unit
96	coupling unit
98	rotation stopping unit
100	movement gap portion
1012	spout
1014	hermetically-sealing sheet
1016	drooping portion

1017	tearing starting end portion
1018	tearing terminating portion
1019	tearing end edge
1020	spout main body
1022	attachment portion
1024	cylindrical portion
1026	through hole
1028	outer opening
1030	inner opening
1032	right male screw unit
1034	step portion
1040	protrusion
1042	rotation stopping unit
1042a	guide surface
1042b	stopper surface
1044	opening-body accommodating unit
1050	opening body
1052	blade unit
1054	passive shaft unit
1056	spout through hole
1058	inlet
1060	outlet
1062	base unit
1064	cutting edge unit
1066	cutting-edge root portion
1068	cutting-edge bottom portion
1070	blade tip portion
1072	blade protruding portion
1074	hermetically-sealing-sheet abutment support unit
1076	first plate-shaped portion
1077	second plate-shaped portion
1078	opening-body main shaft unit
1079	hermetically-sealing sheet fixing portion
1080	activating body
1082	cap
1084	tamper evidence

1086	wing pressing unit
1088	right female screw unit
1090	top portion
1092	hanging-down portion
1098	rotation stopping unit
1302	opening-body accommodating large-diameter portion
1304	opening-body accommodating small-diameter portion
1310	step
1310a	left-and-right-direction extending portion
1310b	vertical-direction extending portion
1310c	lower end portion
1310d	guide tilted surface
1312	rotation stop male unit
1330	lateral rib portion
1332	test-purpose hole
1340	longitudinal rib portion
1352	large-diameter portion
1354	small-diameter portion
1360	step
1360a	left-and-right-direction extending portion
1360b	standing portion
1360c	guided tilted surface
1360d	upper end portion
1360e	vertical-direction extending portion
1362	rotation stop female unit
1370	flange portion
1380	notch portion
1380a	edge portion
1390	wing portion
1410	coupling unit
1412	upper-surface preliminary coupling unit
1414	side-surface preliminary coupling unit
C	center axis

[Document Name] Claims

[Claim 1]

A spout-equipped container comprising a container including an accommodating unit for accommodating hydrogen water and a spout attached to an end edge of the container and fronting the accommodating unit, wherein

the spout is provided with a hermetically-sealing sheet for hermetically sealing the hydrogen water in the accommodating unit of the container, and

with an aluminum region of the hermetically-sealing sheet and an aluminum region of the accommodating unit of the container in close contact with each other, hydrogen contained in the hydrogen water is less prone to get out of the accommodating unit of the container.

[Claim 2]

The spout-equipped container according to claim 1, wherein
the spout includes

a spout main body;

an opening body accommodated in a cylinder of the spout main body and having formed therein a spout through hole penetrating in an axial direction; and

an activating body which moves the opening body,

the hermetically-sealing sheet is provided so as to cover an inner opening which fronts the accommodating unit of the container in the spout main body,

the opening body is formed so as not to get out of the spout main body and is formed so as to move toward the hermetically-sealing sheet,

the activating body is attached to an outer opening side of the spout main body and is formed so as to move the opening body toward the hermetically-sealing sheet, and

the hermetically-sealing sheet is formed so as to be partially torn by the opening body moved toward the hermetically-sealing sheet and so that the accommodating unit of the container and an outer opening of the spout main body connect with each other via the spout through hole of the opening body.

[Claim 3]

The spout-equipped container according to claim 1, wherein

the spout includes a spout main body having formed therein a through hole in an axial direction, an activating body to be screwed in one end of the spout main body in the axial direction, and an opening body inserted in the through hole of the spout main body,

the through hole of the spout main body, the activating body, and the opening

body are each formed in a substantially cylindrical shape concentrically in a planar view,

the hermetically-sealing sheet is fixed to a bottom surface positioned at another end of the spout main body,

the spout main body has

a male screw unit formed on an outer surface of the one end in the axial direction and for the activating body to move in a first direction along the axial direction away from the hermetically-sealing sheet by being rotated in a connection rotating direction along a circumferential direction for making the accommodating unit of the container and the through hole of the spout main body connect with each other, and

a helical guide tilted surface formed on an inner wall of the other end of the through hole in the axial direction,

in the activating body,

a top portion and a hanging-down portion hanging down from an end edge of the top portion to form a side wall are provided,

an operating unit hanging down in an identical direction to the hanging-down portion is provided to project on an inner surface of the top portion, and

a female screw unit to be screwed to the male screw unit is provided on an inner surface of the hanging-down portion,

in the opening body,

a blade unit in a substantially cylindrical shape formed at the other end in the axial direction and a passive shaft unit provided to protrude so as to extend in the axial direction from a top portion of the blade unit are provided, and a spout through hole is provided in the blade unit and the passive shaft unit to connect in the axial direction to penetrate therethrough,

on an outer surface of the blade unit, a helical guided tilted surface corresponding to the guide tilted surface of the spout main body is formed and, when the opening body is rotated in the connection rotating direction, the guided tilted surface of the blade unit makes contact with the guide tilted surface of the spout main body to be guided, thereby causing the opening body to move in a second direction along the axial direction approaching the accommodating unit of the container,

on an outer surface of the passive shaft unit, a passive unit is provided to protrude, the passive unit being pressed by the operating unit of the activating body when the activating body is rotated in the connection rotating direction,

when the activating body is rotated in the connection rotating direction, the

operating unit presses the passive unit of the opening body in the connection rotating direction to proceed, and the activating body moves in the first direction so as to be removed from the spout main body,

with the passive unit being pressed by the operating unit of the activating body in the connection rotating direction to proceed and rotated in the connection rotating direction, the guided tilted surface of the blade unit makes contact with the guide tilted surface of the spout main body to be guided, thereby causing the opening body to move in the second direction and causing the blade unit to protrude from a bottom surface side of the through hole formed in the spout main body while rotating, and

when the blade unit protrudes from the bottom surface side of the through hole formed in the spout main body while rotating, part of the hermetically-sealing sheet is torn so as to draw an arc at a central angle smaller than 360° , thereby making the accommodating unit of the container and the through hole of the spout main body connect with each other.

[Claim 4]

The spout-equipped container according to claim 3, wherein

the spout main body further has a rotation regulating and engaging unit formed near a terminating end of the guide tilted surface, and

the opening body further has a rotation regulating and engaging unit formed near a terminating end of the guided tiled surface, and

with the rotation regulating and engaging unit of the spout main body and the rotation regulating and engaging unit of the opening body engaged with each other, the opening body is regulated and stopped so that a rotation central angle of the opening body in the connection rotating direction is an angle smaller than 360° .

[Claim 5]

The spout-equipped container according to claim 3 or 4, wherein

the blade unit has a blade tip portion which linearly extends and a notch portion notched upward from the blade tip portion in a side view.

[Claim 6]

The spout-equipped container according to claim 5, wherein

the blade tip portion linearly extends in parallel with a direction in which the hermetically-sealing sheet extends in a side view and has a blade protruding portion provided to protrude from a position adjacent to the notch portion toward the hermetically-sealing sheet, and

the blade protruding portion includes a sharp cutting edge at a head portion in a connection rotating direction to cut into the hermetically-sealing sheet.

[Claim 7]

The spout-equipped container according to any of claims 3 to 6, wherein
the opening body further has a flange portion which abuts on an upper surface
of the hermetically-sealing sheet after the part of the hermetically-sealing sheet is torn.

[Claim 8]

The spout-equipped container according to any of claims 3 to 7, wherein
the blade unit has a dimension in a radial direction larger than a dimension of
an upper portion of the blade unit of the opening body in the radial direction,

an opening-body accommodating unit for accommodating the blade unit of the
opening body is formed in a lower portion of the through hole of the spout main body
and, with the opening-body accommodating unit having a dimension in the radial
direction being larger than a dimension of an upper portion of the opening-body
accommodating unit of the through hole in the radial direction, a step is formed at a
connecting portion between the opening-body accommodating unit and the upper
portion of the opening-body accommodating unit of the through hole,

with an upper end of the blade unit abutting on the step of the spout main body,
movement of the opening body in the first direction away from the hermetically-sealing
sheet is regulated, and the opening body does not get out of the through hole of the
spout main body.

[Claim 9]

The spout-equipped container according to claim 1, wherein
the spout includes a spout main body having formed therein a through hole in
an axial direction, an activating body to be screwed in one end of the spout main body in
the axial direction, and an opening body inserted in the through hole of the spout main
body,

the through hole of the spout main body, the activating body, and the opening
body are each formed in a substantially cylindrical shape concentrically in a planar
view,

the spout main body has

a male screw unit formed on an outer surface near the one end in the
axial direction and for the activating body to move in a first direction along the axial
direction away from the hermetically-sealing sheet by being rotated in a connection
rotating direction along a circumferential direction for making the accommodating unit
of the container and the through hole of the spout main body connect with each other,

in the activating body,

a top portion and a hanging-down portion hanging down from an end

edge of the top portion to form a side wall are provided, and

a female screw unit to be screwed to the male screw unit is formed on an inner surface of the hanging-down portion,

in the opening body,

a spout through hole connecting in the axial direction to penetrate is formed, one end in the axial direction is integrally formed with an inner surface of the top portion of the activating body, and another end in the axial direction is fixed to the hermetically-sealing sheet, and

with the activating body being rotated in the connection rotating direction to move in the first direction so as to be removed from the spout main body, the opening body also moves in the first direction to screw part of the hermetically-sealing sheet out, thereby making the accommodating unit of the container and the through hole of the spout main body connect with each other.

[Claim 10]

The spout-equipped container according to claim 1 or 2, wherein

the spout main body includes

a cylindrical portion having a through hole connecting with outside,

an attachment portion interposed between an end edge of a first container sheet and an end edge of a second container sheet configuring the container, and

a male screw unit for screwably attaching a movable body which moves the opening body movably disposed in the through hole of the cylindrical portion,

the attachment portion provided to the cylindrical portion on an accommodating unit side of the container has an inlet connecting with the spout through hole of the opening body,

the activating body has a cap and a stopper, and is formed so as to form a movement gap portion by separating and removing the stopper from the cap and press the opening body in order for the cap to move the opening body toward the hermetically-sealing sheet,

the opening body has, on a hermetically-sealing sheet side, a blade unit for tearing the hermetically-sealing sheet, and the blade unit has the spout through hole,

the hermetically-sealing sheet is formed so as to be pasted on a container accommodating unit side surface of the attachment portion so as to cover an opening of the attachment portion, make close contact with the accommodating unit of the container, and is torn by the opening body to make the through hole of the spout main body and the accommodating unit of the container connect with each other,

the opening body has a cylindrical sliding shaft unit and a blade unit for

tearing the hermetically-sealing sheet,

the blade unit is continuously connected to the sliding shaft unit so as to protrude in a flange shape at an end of the sliding shaft unit,

the blade unit is formed so as to be in contact with a step portion or an engaging portion provided on periphery of the through hole of the spout main body to prevent the opening body from moving to a through hole side,

the activating body is formed so that a pressing unit for pressing the opening body is provided inside the cap to protrude, a female screw unit is provided inside the cap, the stopper is coupled by a coupling unit intermittently provided at a lower end of the cap, a movement gap portion is formed by rotating the cap and/or rotating the stopper in a circumferential direction to remove the stopper from the cap, and the cap is moved toward the movement gap portion opening in a circumferential direction of the cylindrical portion of the spout main body to cause the pressing unit to press the opening body.

[Claim 11]

The spout-equipped container according to claim 1, 2 or 10, wherein

the spout main body includes a ship-shaped attachment portion to be attached to a container sheet configuring the container and a cylindrical portion continuously connected to an upper portion of the attachment portion,

the attachment portion and the cylindrical portion have a through hole penetrating therethrough,

the through hole has an outer opening in an upper portion of the attachment portion and an inner opening in a lower portion of the attachment portion, and

the outer opening opens outside the container, and the inner opening opens toward the accommodating unit of the container.

[Claim 12]

The spout-equipped container according to claim 1, 2, 10, or 11, wherein

the spout main body has a male screw unit circumferentially provided on an outer peripheral surface of the cylindrical portion and has an activating-body stopping unit for stopping the activating body circumferentially provided on the outer peripheral surface of the cylindrical portion below the male screw unit,

the activating body includes a cap to be screwably attached to the cylindrical portion of the spout main body and a stopper removably coupled to a lower portion of the cap, and

a movement regulating unit is formed so that the cap of the activating body moves downward in a height range of the movement gap portion formed when the

stopper is removed to stop at a predetermined position.

[Claim 13]

The spout-equipped container according to any of claims 1, 2, and 10 to 12, wherein

the opening body has a blade unit which tears the hermetically-sealing sheet and a sliding shaft unit provided to an upper portion of the blade unit to protrude,

the blade unit and the sliding shaft unit continuously provided to the upper portion of the blade unit are in a columnar and/or pole shape,

the blade unit and the sliding shaft unit have a spout through hole provided to penetrate therethrough,

the spout through hole has an outlet facing the outer opening of the spout main body and an inlet facing the accommodating unit of the container, and

the sliding shaft unit is formed so as to slidably fit in the through hole of the cylindrical portion of the spout main body and be pressed by the activating body to move downward.

[Claim 14]

The spout-equipped container according to any of claims 1, 2, and 10 to 13, wherein

the opening body has a blade unit which tears the hermetically-sealing sheet and a sliding shaft unit provided to an upper portion of the blade unit to protrude,

the blade unit and/or the sliding shaft unit has a rotation stop unit formed therein,

the spout main body has an attachment portion to be attached to the container and a cylindrical portion provided to an upper portion of the attachment portion to protrude, and

in the attachment portion and/or the cylindrical portion, a rotation stop unit is formed for stopping rotation of the opening body for engaging or inserting the rotation stop unit of the opening body.

[Claim 15]

A method of manufacturing a spout-equipped container, wherein a method of attaching a spout to a spout unit of a container comprises, when the spout including a cylindrical spout main body, an opening body accommodated in a cylinder of the spout main body, and an activating body which moves the opening body is manufactured,

inserting the opening body in the cylinder of the spout main body and, with the opening body prevented from getting outside from the spout main body, adhering a hermetically-sealing sheet which covers an inner opening which fronts an

accommodating unit in the spout main body to periphery of the inner opening in a region which fronts a container accommodating unit of the spout main body to form the spout, and

welding a first container sheet and a second container sheet configuring the container on periphery of an attachment portion of the spout.