Patent application no. PCT/NO2012/050230
Applicant Marine Aluminium AS
Date December 30, 2013

Amended claims

1. Anchoring device (1) in a helicopter deck (2),comprising a housing (11) that is provided with an open top (111) and lowered into the helicopter deck (2), contains a fastener (12) which is vertically displaceable between a withdrawn, inactive position and an active position where an upper fastener portion (121) extends at least partly up from the helicopter deck (2) and where the upper fastener portion (121) is arranged to be detachably connected to anchoring means (3), the housing (11) being provided with a detachable lid (13) arranged, in its closed position, to close fluid tightly against the housing (11); and an upper end surface (114) of the housing (11) is planar with the surface (21) of the helicopter deck, characterized in that
   - the fastener (12) in its pulled-up, active position closes fluid tightly against the housing (11), the fastener (12) comprising a sealing portion (123) arranged to abut against a contact surface (116) in an upper portion of the housing (11).

2. Anchoring device (1) in accordance with claim 1, where the upper fastener portion (121) comprises a cut-out (122) arranged to receive a portion of the anchoring means (3).

3. Anchoring device (1) in accordance with claim 1, where the upper fastener portion (121) comprises a coupling portion (122a) arranged to be able to go into locking engagement with a fixing element (31) associated with the anchoring means (3).

4. Anchoring device (1) in accordance with claim 1, where the housing (11) comprises a bottom portion (113) provided with a drainage opening (115) which leads into a discharge conduit (4).

5. Anchoring device (1) in accordance with claim 1, where the fastener (12) is provided with an outer thread portion (124, 124a) arranged to be able to go into engagement with an inner thread portion (117) in the housing (11).

6. Anchoring device (1) in accordance with claim 1, where one of the fastener (12) and the housing (11) is provided with one or more outwardly protruding, respectively inwardly protruding locking elements (125) arranged to be able to go into locking engagement with a corresponding latch groove (118) in the second of the fastener (12) and the housing (11) when the fastener (12) is displaced up to its active position.

7. Anchoring device (1) in accordance with claim 6, where the locking element (125) is an resilient pin or ball (126) arranged in a second cut-out (127) in one of the fastener (12) and the housing (11).

8. Anchoring device (1) in accordance with claim 6, where the locking element (125) is a fixed pin (126a) protruding respectively outwardly and inwardly from one of the fastener (12) and the housing (11), and when the fastener (12) is displaced from its active position, is in sliding engagement with a guide track (119) arranged in the second of the fastener (12) and the housing (11).

9. Anchoring device (1) in accordance with claim 1, where the lid (13) is provided with an upwardly protruding, non-circular centre portion (131).

10. Anchoring device (1) in accordance with claim 1, where a tool (5) comprises a first engagement portion (51) arranged to be able to go into locking engagement with the upwardly protruding centre portion (131) of the lid (13), and a second engagement portion (52) arranged to be able to go into locking engagement with the upper portion (121) of the fastener.