

TITLE OF THE INVENTION CLOTHING HAVING CUP PORTIONS

BACKGROUND OF THE INVENTION

Field of the Invention

[0001]

The present invention relates to clothing having cup portions to which pads are attached, in particular, to clothing having cup portions that are unlikely to get out of alignment from breasts while being worn.

Description of the Related Art

[0002]

In recent years, in particular in summer, thin outer clothes are frequently used, meanwhile, clothing having cups portions where pads so formed as to yield desired breast shapes, in order not to affect on external appearances are attached to the cup portions, or are made into the cup portions themselves are frequently used.

[0003]

Further, in diversified recent clothes, as formal or summer outer clothes, opportunities are increasing where clothes designed to expose shoulders, and clothes with plunging neckline or cut low in the back are used. When these outer clothes are used, clothing especially having cup portions such as brassieres having 1/2 cup type cup portions are frequently used as inner clothing without strap portions, or with strap portions removed.

[0004]

However, clothing having the cup portions using pads formed as the above can not completely follow the body actions while being worn, and the top of the cup portion may lift up to cause a gap, and the flesh at the side may hang out of the cup portion and the breast shape may become misshapen, which have been problems in the prior art.

BRIEF SUMMARY OF THE INVENTION

[0005]

Accordingly, embodiments of the present invention seek to provide clothing having cup portions where pads are attached to the cup portions, and the cup portions deform so as to follow the body actions when the clothing having cup portions is worn, and thereby it may be possible to reduce the facts that the top of the cup portion may lift up to

cause a gap, and the flesh at the side may hang out of the cup portion and the breast shape may become misshapen, and keep beautiful breast silhouettes.

[0006]

[0007]

(1) According to a first aspect of the present invention, there is provided clothing having cup portions, comprising at least two cup portions and back portions, and pads attached to the cup portions, wherein each of the pads has a cut portion that extends from the upper part of the front center side when the clothing is attached along a verge's line when the clothing is worn, or in parallel with the vicinity of the verge's line, and the cut end portion of the cut portion is at a more front center side than the lowest point of the verge's line when the clothing is worn.

[0008]

(2) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (1), wherein the length from the intersection point of a lone drawn from the cut end portion orthogonally down to the verge's line when the clothing is worn to the lowest point of the verge's line is in the range 5 ~ 50mm along the verge's line.

[0009]

(3) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (1), wherein wires are arranged on the lower circumferential edges of the cup portions.

[0010]

(4) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (1), wherein stretching members are arranged along the positions corresponding to the upper parts of the pads.

[0011]

(5) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (4), wherein the cup portions are 1/2 cup type cup portions, and strap portions are not arranged, or detachable strap portions are arranged.

[0012]

(6) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (5), wherein, with regard to the fixing portion of the stretching member to the cup portion, one end portion thereof is at the upper end of underarm side when the clothing is worn, and the other end portion thereof is at a more front center side than 1/3 of the length along the upper part of the pad, from the front center side when the clothing is worn, to the intersection point of a vertical line extend upward from the lowest point of the verge's line when the clothing is worn and the upper part of the pad.

[0013]

(7) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (4), wherein the cup portions are 3/4 cup type cup portions.

[0014]

(8) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (7), wherein the fixing portion of the stretching member to the cup portion is the entire upper part of the pad.

[0015]

(9) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (1), wherein in the cup portions, the front sides and the skin sides of the pads are covered with stretching cloth.

[0016]

(10) According to an embodiment of the present invention, there is provided clothing having cup portions according to the above (1), that is clothing selected from a brassiere, bra slip, tops, bra camisole, body suit, teddy with cup portions, and swim suit.

[0017]

In clothing having cup portions according to embodiments of the present invention, where the cup portions deform so as to follow the body actions when the clothing having cup portions is worn, and thereby it may be possible to reduce the facts that the top of the cup portion may lift up to cause a gap, and the flesh at the side may hang out of the cup portion and the breast shape may become misshapen, and keep beautiful breast silhouettes, and obtain preferable feeling of wearing.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0042]

FIG. 1 is a front view showing a pad to be attached to cup portions of clothing having cup portions as a preferred embodiment according to the present invention.

FIG. 2 is a front view for explaining the range of the cut portion of the pad to be attached to cup portions in clothing having cup portions in the present invention.

FIG. 3 is a front view showing the arrangement relation of a wire and a pad in clothing having cup portions in the present invention.

FIG. 4 is an explanatory figure showing the attachment condition of the pad in FIG. 3 viewed from the side.

FIG. 5 is a front view for explaining the range of the fixing portion of the stretching member to be attached along the positions corresponding to the upper parts of the pads, in the clothing having cup portions according to the present invention.

FIG. 6 is an explanatory figure for explaining the function of the clothing having 1/2 cup type cup portions according to the present invention.

FIG. 7 is a partial cross sectional view showing examples of the fixing methods

of the stretching members along the positions corresponding to the upper parts of the pads, in the clothing having cup portions according to the present invention.

FIG. 8 is a back view of a preferred embodiment of a brassiere as an example of the clothing having 1/2 cup type cup portions according to the present invention.

FIG. 9 is a front view showing another preferred embodiment of a pad to be attached to the cup portions in the clothing having cup portions according to the present invention.

FIG. 10 is an explanatory figure for explaining the function in the clothing having the cup portions shown in FIG. 9.

FIG. 11 is a back view showing a preferred embodiment of a brassiere having 3/4 cup type cup portions according to the present invention.

FIG. 12 is a perspective view showing the external appearance of a body suit as clothing having cup portions according to the present invention.

FIG. 13 is a perspective view showing the external appearance of a swim suit as clothing having cup portions according to the present invention.

Description of Codes

[0043]

1, 1'	Pad
2	Top side
3	Verge's line
4, 4'	Cup portion
4a	Cup portion end portion
5	Wire
6, 6'	Stretching member
7, 7'	Fixing portion of stretching member
8	Front center side end portion of fixing portion of stretching member
10, 10'	Brassiere
11, 11'	Cup portion
12	Back portion
13	Front center portion
14, 15	Fastening member
16	Strap portion
20, 24, 27	Cloth at front side
21, 25, 28	Cloth at skin side
22, 29	Stretching member
23, 26a, 26b, 30	Fixing portion by stitching

40, 41 Body portion
 F Front center side
 B Underarm side
 S Front center side (upper part)
 X Lowest point of the verge's line when the clothing is worn
 Y Intersection point of the line drawn from the cut end portion orthogonally down to the verge's line when the clothing is worn and the verge's line
 Z Intersection point of a vertical line extended upward from the lowest point of the verge's line when the clothing is worn and the upper part of the pad

DETAILED DESCRIPTION OF THE INVENTION

[0018]

The present invention is illustrated in more details with reference to the attached drawings hereinafter, meanwhile, the present invention is not limited to the following preferred embodiments.

[0019]

[First Preferred Embodiment]

FIG. 1 is a front view showing a structure of a pad to be attached to cup portions of clothing having cup portions as a preferred embodiment according to the present invention. The pad 1 in FIG. 1 is a pad to be attached to 1/2 cup type cup portions, and has a cut portion 4 that extends from the upper part 2 of the front center side S when the clothing is worn in parallel with the vicinity of a verge's line 3 when the clothing is worn, and the cut portion end portion 4a of the cut portion 4 is at a more front center side (shown by F in the figure) than the lowest point X of the verge's line when the clothing is worn.

[0020]

According to the above structure, in clothing having cup portions where the pad 1 is attached to the cup portions, and the cup portions deform following the body actions when the clothing is worn, therefore, even if a strap portion is not arranged, or detached, it is possible to reduce the facts that the top of the cup portion may lift up to cause a gap, and the flesh at the side may hang out of the cup portion and the breast shape may become misshapen. FIG. 6 is an explanatory figure for explaining the function of the clothing having cup portions where the pad 1 is attached to the cup portions in FIG. 1. A brassiere 10 as the clothing having cup portions in FIG. 6 has two cup portions 11, 11, back portions 12, 12 (only one side illustrated), and a front center portion 13, and the pad 1 in FIG. 1 is attached to each cup portion 11.

Air gaps that are formed by the cut portions 4 arranged in the pads 1 open and close, and thereby, the pad 1 deforms in the direction shown by arrow mark m in the figure, and the pad follows the body actions.

[0021]

The arrangement of the cut portion to be arranged in the pad used in the present invention may be made in parallel with the vicinity of the verge's line when the clothing is worn, and in some pads shapes, the cut portion may be arranged so as to extend along the verge's line when the clothing is worn.

[0022]

The length of the cut portion to be arranged in the pad used in the present invention is not specifically limited, so long as the cut end portion of the cut portion is at a more front center side than the lowest point of the verge's line when the clothing is worn, meanwhile it is preferable that the length from the intersection point of a line drawn from the cut end portion orthogonally down to the verge's line when the clothing is worn to the lowest point of the verge's line is in the range 5 ~ 50mm along the verge's line. FIG. 2 is a front view for explaining the range of the cut portion of the pad used in the present invention. FIG. 2 is for explaining the range of the cut portion of the pad used in FIG. 1. In FIG. 2, when the length along the verge's line from the intersection point Y of the line drawn from the cut end portion 4a orthogonally down to the verge's line when the clothing is worn to the lowest point X of the verge's line is defined as L, it is preferable that this length L is in the range 5 ~ 50mm. When the length of the cut portion is set in the above range, the deformation of the pad following the body actions gets into a further preferable range, and the effect of the present invention can be attained effectively.

[0023]

In the pad used in the present invention, the plain shape of other portion than the cut portion is not specifically limited, so long as it is roughly same the shape of the cup portion. Further, the pad in the present invention is so formed as to yield desired breast shapes beforehand, and since the cut portion is arranged, the pad shape deforms appropriately so as to follow the deformation of the breasts at actions, and it is possible to keep the breast shape without misshaping the breast shape.

[0024]

In the present invention, as the raw material to structure the pad, same materials as used generally in the cup portion, for example, urethane foam, unwoven cloth, double knit, double russell and the like may be employed. The method of manufacturing the pad including formation and the like may be appropriately selected

according to the raw materials used, meanwhile in the present invention, in the case when the pad is formed by molding in particular urethane foam and the like, the cut portion can be formed easily, and the effect that the pad shape deforms following the deform of the breast can be attained in particular highly.

[0025]

The clothing having cup portions according to the present invention has a structure where pads having the cut portion of the above structure are attached to the cup portions. The clothing having cup portions according to the present invention has at least two cup portions and back portions.

[0026]

In the clothing having cup portions according to the present invention, the cup portions may be structured of only pads, or with pads as main parts, other members such as cloth and the like may be used in the front side and/or the skin side, in the scope where the function of the present invention should not be hindered, from viewpoints of the pad holding property, improvement of feeling of wearing, and design. In particular, it is preferable that, in the cup portion, to use stretching cloth to cover the front side and the skin side of the pad, since the pad holding property and the feeling of wearing are improved, and the deformation of the pad following the body actions is not hindered.

[0027]

The above stretching cloth is not specifically limited, but those used generally in clothing having cup portions, for example, latch needle circular knitted cloth, power net, tricot and the like may be employed. Further, cloth of a same kind or cloth of different kinds may be employed to the front side and the skin side.

[0028]

The clothing having cup portions according to the present invention may be of a structure where wires are arranged on the lower circumferential edges of the cup portions in order to increase the breast holding force. FIG. 3 is a front view showing the arrangement relation of a wire and a pad, and FIG. 4 is an explanatory figure showing the attachment condition of the pad in FIG. 3 viewed from the side. Same codes are allotted to other identical members in the pad in FIG. 1 than the wire 5, and their explanations thereof are omitted herein. Meanwhile, same wire as those generally used may be employed.

[0029]

In the clothing having cup portions according to the present invention, it is preferable that stretching members are arranged along the positions corresponding to the upper parts of the pads. By arranging stretching members along the positions

corresponding to the upper parts of the pads, stretching properties in the direction along the the upper part of the vicinity of the positions corresponding to the upper parts of the pads (shown by arrow mark n in the clothing having cup portions according to the present invention in FIG. 6) are added, and the function for the pad to deform following the body actions is further increased.

[0030]

In the clothing having cup portions according to the present invention, when stretching members are arranged along the positions corresponding to the upper parts of the pads, in the case where the cup portions are 1/2 cup type cup portions, it is further preferable that, with regard to the fixing portion of the stretching member to the cup portion, one end portion thereof is at the upper end of underarm side when the clothing is worn, and the other end portion thereof is at a more front center side than 1/3 of the length along the upper part of the pad, from the front center side when the clothing is worn, to the intersection point of a vertical line extended upward from the lowest point of the verge's line when the clothing is worn and the upper part of the pad. By making the fixing portion of the stretching member to the cup portion in the above range, stretching properties in the direction along the positions corresponding to the upper parts of the pads are added more effectively. FIG. 5 is a front view for explaining the range of the fixing portion of the stretching member to the cup portion, in the clothing having cup portions according to the present invention. In FIG. 5, same codes are allotted to identical members in the pad in FIG. 1, and their explanations thereof are omitted herein. One end portion of the fixing portion 7 of the stretching member 6 to the cup portion is at the upper end of underarm side (shown by B in the figure) when the clothing is worn. The other end portion 8 thereof is at a more front center side (shown by F in the figure) than 1/3 of the length along the upper part of the pad, from the front center side S when the clothing is worn, to the intersection point (shown by Z in the figure) of a vertical line (shown by dashed line T in the figure) extended upward from the lowest point X of the verge's line when the clothing is worn and the upper part of the pad. That is, when the length along the upper part of the pad from the front center side S to the intersection point Z is defined as L2, and the length along the upper part of the pad from the front center side S to the end portion 8 is defined as L3, it is preferable to set L3/L2 so as to become 1/3 or below.

[0031]

In the clothing having cup portions according to the present invention, in the case when stretching members are arranged along the positions corresponding to the upper parts of the pads, the arrangement or attaching method of the stretching

members to the front side and the rear side are not specifically limited. FIG. 7 is a partial cross sectional view showing examples of the fixing methods of the stretching members along the positions corresponding to the upper parts of the pads, in the clothing having cup portions according to the present invention. The present invention is of course not limited to these examples. In FIG. 7, the front side and the skin side of the pad 1 are both covered with stretching cloth. In FIG. 7 (a), the upper part of the cloth 21 to cover the skin side of the pad 1 is at the same position as that of the upper part of the pad 1, meanwhile the cloth 20 to cover the front side of the pad 1 extends so as to wrap the pad 1 and the upper part of the cloth 21, and the stretching member 22 is arranged at the skin side of the pad 1 so as to be sandwiched between the extending portion of the cloth 20 and the cloth 21, and by a stitching portion 23, the upper parts of the pad 1, the cloth 20, the cloth 21, and the stretching member 22 are fixed. In FIG. 7 (b), the arrangement of the pad 1, and the upper part of the cloth 24 to cover the front side of the pad 1, and the upper part of the cloth 25 to cover the skin side of the pad 1 is same as that in FIG. 7 (a), the stretching member 22 is arranged at further skin side at the extending portion of the cloth 24, and by the stitching portion, the upper parts of the pad 1, the cloth 24, the cloth 25, and the stretching member 22 are fixed. Meanwhile, in FIG. 7 (b), first, the cloth 24 and the cloth 25 are stitched with each other by the stitching portion 26a, and further, the pad 1, the cloth 24, the cloth 25, and the stretching member 22 are stitched by the stitching portion 26b, and the stitching portion does not appear on the front side (the stitching portions 26a, 26b are piled actually, but they are shown in displaced state for explanation). In FIG. 7 (c), the upper part of the cloth 27 to cover the front side of the pad 1, and the upper part of the cloth 28 to cover the skin side are at the same position as that of the upper part of the pad 1, and the stretching member 29 is arranged so as to wrap the upper parts of the pad 1, the cloth 27, and the cloth 28, and are fixed by the stitching portion 30. The fixing method is not limited to stitching, but according to raw materials and the like to be used, other methods such as heat fusion, adhesion and the like may be employed. In the case when stitching is used, it is preferable that one stitch uses three stitches.

[0032]

As the above stretching members, a tape material as shown in FIGS. 7 (a), (b), a wide cloth piece as shown in FIG. 7 (c) and the like may be used. Further, a plurality of members may be used. Besides, the raw material thereof is not specifically limited, but, for example, stretching tape and the like may be employed.

[0033]

FIG. 8 is a back view of a preferred embodiment of a brassiere having 1/2 cup

type cup portions as an example of the clothing having cup portions according to the present invention. A brassiere 10 in FIG. 8 is a back open type brassiere having two cup portions 11, 11, back portions 12, 12, and a front center portion 13 arranged at the lower sides of the cup portions. Fastening members 14 and 15 attached to the respective ends of the back portions 12, 12 are engaged with each other, and thereby it is possible to hold the brassiere. To the cup portions 11, 11, the pad 1 in FIG. 1 is used, and the front side and the skin side thereof are covered with stretching cloth, and further in the same manner as the range in FIG. 5, stretching members are arranged and fixed along the upper parts of the cup portions.

[0034]

In the clothing having cup portions according to the present invention, in the case when the cup portions are 1/2 cup type ones, the function of stretching properties in the direction along the position corresponding to the upper part of pad is attained in particular effectively in the state without a strap portion, and accordingly, as the clothing having cup portions according to the present invention, such an embodiment as one without a strap portion like the brassiere 10 in FIG. 8 is listed up, however, such clothing as ones having detachable strap portions in the same manner as the clothing having general cup portions, like a body suit as shown in FIG. 12 to be explained later herein are also included.

[0035]

In the clothing having cup portions according to the present invention, in the case when stretching members are arranged along the positions corresponding to the upper parts of the pads as described previously, in the case where the cup portions are 3/4 cup type cup portions, it is further preferable that the fixing portion of the stretching member to the cup portion is the entire upper part of the pad. In the case where the cup portions are 3/4 cup type cup portions, there are provided strap portions, and the force pulled by the strap portions becomes larger than the stretching function in the direction along the position corresponding to the upper part of the pad, and accordingly, in comparison with the case where the fixing portion of the stretching member to the cup portion is the entire upper part of the pad, it is possible to prevent the cut portion from opening in excess, and to attain appropriate deformation. FIG. 9 is a front view showing the structure of a pad to be attached to the cup portions of 3/4 cup type, as another preferred embodiment of a pad to be attached to the cup portions of the clothing having cup portions according to the present invention. A pad 1' in FIG. 9 has a cut portion 4' same as that in the pad 1 in FIG. 1, and further over the entire upper part of the pad, a stretching member 6' is fixed by a fixing portion 7'. Meanwhile, the range of the fixing

portion of the stretching member, the plane shape of the pad, and other structure than the arrangement of strap portions are same as those in the clothing having 1/2 cup type cup portions.

[0036]

According to the above structure, in the clothing having cup portions where the pad 1' is attached to the cup portions, the cup portions deform appropriately so as to follow the body actions, and it is possible to reduce the facts that the top of the cup portion may lift up to cause a gap, and the flesh at the side may hang out of the cup portion and the breast shape may become misshapen, when the clothing having cup portions is worn. FIG. 10 is an explanatory figure for explaining the function in the clothing having cup portions to which the above pad 1' is attached. A brassiere 10' as clothing having cup portions in FIG. 10 has two cup portions 11', 11', back portions 12, 12 (only one illustrated), and a front center portion 13, and the pad 1' in FIG. 9 is attached to the respective cup portions 11'. Air gaps formed by cut portions 4' formed in the pads 1' open and close, and the stretching member prevents the upper parts of the cut portions from opening and closing, and thereby, the pad 1' deforms in the direction shown by arrow mark m' in the figure, and the pad follows the body actions. The deformation of the pad 1' is large at the center portion of the cut portion, small at the lower portion, and middle at the top portion.

[0037]

FIG. 11 is a back view showing a preferred embodiment of a brassiere having 3/4 cup type cup portions as an example of the clothing having cup portions according to the present invention. A brassiere 10' in FIG. 11 is a back open type brassiere having two cup portions 11', 11', back portions 12, 12, a front center portion 13 arranged at the lower sides of the cup portions, and strap portions 16, 16. Fastening members 14 and 15 attached to the respective ends of the back portions 12, 12 are engaged with each other, and thereby it is possible to hold the brassiere. To the cup portions 11', 11', the pad 1' in FIG. 9 is used, and the front side and the skin side thereof are covered with stretching cloth, and further over the entire upper part of the pad, stretching members are arranged and fixed along the upper parts of the cup portions.

[0038]

In the present invention, the structure of clothing having cup portions of other structure than the above is not specifically limited, but the shape, raw material, manufacture method and the like thereof may be structured in the same manner as the clothing having general cup portions, in the scope where the function of the present invention should not be hindered, and for example, other structure of a bone and the

like may be included. Further, although in the brassiere 10 in FIG. 8, the front center portion 13 is attached onto the lower sides of the cup portions 11, from convenience of design or the like, part or whole of an under bust portion may be not arranged.

[0039]

As the clothing having cup portions according to the present invention, in concrete, besides the brassieres as described in the above preferred embodiments, bra slip, tops, bra camisole, body suit, teddy with cup portions, swim suit and the like may be listed up. The clothing having cup portions according to the present invention has a body portion, under the cup portions, or the front center portion, extending to the vicinity of the waist or the under side thereof.

[0040]

FIG. 12 and FIG. 13 show other preferred embodiments of clothing having cup portions according to the present invention. FIG. 12 is a perspective view showing the external appearance of a body suit as clothing having cup portions according to the present invention, and FIG. 13 is a perspective view showing the external appearance of a swim suit as clothing having cup portions according to the present invention, and each has a structure including a body portion (shown by codes 40, 41 respectively in the figures). Furthermore, the body suit in FIG. 12 has detachable strap portions 16, 16. Meanwhile, same codes are allotted to identical members in the brassiere in FIG. 8, and their explanations thereof are omitted herein.

[0041]

The cup portions deform so as to follow the body actions when the clothing having cup portions is worn, and thereby it is possible to reduce the facts that the top of the cup portion may lift up to cause a gap, and the flesh at the side may hang out of the cup portion and the breast shape may become misshapen, and keep beautiful breast silhouettes, and obtain preferable feeling of wearing, and accordingly, the clothing having cup portions according to the present invention is useful when used as inner clothing in the case when thin clothing is worn as an outer, and in particular, the clothing having 1/2 cup type cup portions, whether without a strap portion, or with a strap portion detached, can keep beautiful breast silhouettes, and accordingly, it is useful when used as inner clothing in the case when clothing designed to expose shoulders, and clothing with plunging neckline or cut low in the back are used as an outer.

WHAT IS CLAIMED IS:

- 1 Clothing having cup portions, comprising at least two cup portions and back portions, and pads attached to the cup portions, wherein each of the pads has a cut portion that extends from the upper part of the front center side when the clothing is attached along a verge's line when the clothing is worn, or in parallel with the vicinity of the verge's line, and the cut end portion of the cut portion is at a more front center side than the lowest point of the verge's line when the clothing is worn.
- 2 Clothing having cup portions according to claim 1, wherein the length from the intersection point of a line drawn from the cut end portion orthogonally down to the verge's line when the clothing is worn and the verge's line to the lowest point of the verge's line is in the range 5 ~ 50mm along the verge's line.
- 3 Clothing having cup portions according to claim 1, wherein wires are arranged on the lower circumferential edges of the cup portions.
- 4 Clothing having cup portions according to claim 1, wherein stretching members are arranged along the positions corresponding to the upper parts of the pads.
- 5 Clothing having cup portions according to claim 4, wherein the cup portions are 1/2 cup type cup portions, and strap portions are not arranged, or detachable strap portions are arranged.
- 6 Clothing having cup portions according to claim 5, wherein, with regard to the fixing portion of the stretching member to the cup portion, one end portion thereof is at the upper end of underarm side when the clothing is worn, and the other end portion thereof is at a more front center side than 1/3 of the length along the upper part of the pad, from the front center side when the clothing is worn, to the intersection point of a vertical line extended upward from the lowest point of the verge's line when the clothing is worn and the upper part of the pad.
- 7 Clothing having cup portions according to claim 4, wherein the cup portions are 3/4 cup type cup portions.
- 8 Clothing having cup portions according to claim 7, wherein the fixing portion of the stretching member to the cup portion is the entire upper part of the pad.
- 9 Clothing having cup portions according to claim 1, wherein in the cup portions, the front sides and the skin sides of the pads are covered with stretching cloth.
- 10 Clothing having cup portions according to claim 1, wherein clothing is selected from a brassiere, bra slip, tops, bra camisole, body suit, teddy with cup portions, and swim suit.

ABSTRACT OF THE DISCLOSURE

The object of the present invention is to provide clothing having cup portions where pads are attached to the cup portions, and the cup portions deform so as to follow the body actions when the clothing having cup portions is worn, and thereby it is possible to reduce the facts that the top of the cup portion may lift up to cause a gap, and the flesh at the side may hang out of the cup portion and the breast shape may become misshapen, and to keep beautiful breast silhouettes.