

Description

Technical Field

The present invention relates to a holder for holding a magnetic sensitive element to secure it at a predetermined position. More specifically, the present invention relates to a holder for magnetic sensitive elements which can be applied to a magnetic encoder.

Technical Terms

In the specification of the present application, the term "holder" means a part for securing a magnetic sensitive element and includes signal lines for input/output terminals. The term "magnetic sensitive element" is what can be described as a magnetism sensor for detecting magnetic energy, and embraces a magneto-resistance element, a Hall element, a thin-film magnetic head and the like.

Background Art

Conventionally, a magnetic sensitive element 4, which is used with a magnetic encoder or the like, is secured to a holder 11 as shown in Fig. 12, and so arranged therein as to opposingly face a magnetic drum with a predetermined gap provided therebetween. As disclosed in, for example, Japanese Utility Model Laid-Open Publication No. Sho. 62-20,313, the holder 11 for such a magnetic sensitive element 4 comprises a positioning pin 11b and an adjustment slot 11a such that a machine screw 10 is inserted through the slot 11a with the pin 11b fitted into a positioning hole formed in a circuit board, thereby securing the holder 11 to the circuit board. The gap between the magnetic drum and the holder 11 can be adjusted by utilizing the slot 11a. Another type of holder is known in which, as shown in Fig. 13, an H-shaped separable holder 13, having the magnetic sensitive element 4 secured thereto, is combined with a fixed holder 12 having a pair of right and left guide walls 12a and a pair of right and left grooves 12b, the H-shaped separable holder 13 being fitted vertically in between the guide walls 12a and the grooves 12b. This holder is also arranged to enable the aforesaid gap to be adjusted by moving the fixed holder 12 per se via right and left slots 12c formed in the fixed holder 12. The holder disclosed in Japanese Patent Laid-Open Publication No. Sho. 61-165,621 is, as shown in Fig. 18, separated into a movable holder 14 in which is secured a magnetic sensitive element and a fixed holder 15 for holding the movable holder 14. The movable holder 14 is movably accommodated in the fixed holder 15, and to

move the movable holder 14 forwardly and backwardly via a gap adjustment screw 16 and spring 17 will effect a positional adjustment of the movable holder 14 relative to the fixed one 15.

However, if the slot 11a or 12c is to be formed which allows the holder 11 or 12 to be secured to the circuit board or the like so that the holder 11 or 12 can be moved for fine adjustment, it is necessary to form the holder into a shape projecting in the rightward and leftward directions. This results in disadvantage that it is impossible to miniaturize the holder because of the increased holder size. The holder shown in Fig. 18 also has the problem that the holder size increases since screw-mounting holes 18 for securing the fixed holder 15 to the board need to be formed on right and left sides. As a result, such a holder occupies a wide area on the board. Another problem is that costs increase since the machine screw 10 is used for securing the holder to the board and thus such working step as a tapping is needed. The arrangement in which the movable holder 14 is moved for adjustment by means of the gap adjustment screw 16 has the disadvantage that an extremely complicated and large structure is needed for accommodating the adjustment screw 16 and the spring 17.

As shown in Fig. 14, the magneto-resistive element 4 has a resistance pattern which is generally formed by a plurality of resistors R_1 , R_2 , R_3 and R_4 . It is desirable that this resistance pattern, which faces towards a magnetic drum 8, should be disposed parallel to a tangent T extending to touch one point closest to the center of the magnetic sensitive surface 4a of a magnetic recording medium 9 secured to the magnetic drum 8. With the magnetic sensitive element 4 inclined by an angle θ with respect to the magnetic recording medium 9, the resistor R_1 , closest to the magnetic recording medium 9, is exposed to the strongest magnetic field, while the resistor R_4 , the most remote from the magnetic recording medium 9, is exposed to the weakest magnetic field. This can also be seen from Fig. 15 which shows the effective magnetic field strength of the magnetic sensitive element 4 with respect to the gap between the magnetic recording medium and the magnetic sensitive element 4. However, turning to Fig. 12, the holder structure is such that adjustment of the gap is performed by means of the positioning pin 11b and slot 11a, according to which, the magnetic sensitive surface 4a is inclined by angle of θ relative to a plane T parallel to the tangent T, with movement of the holder 11 for the gap widening purpose, and consequently the resistance pattern is not set in parallel with the magnetic sensitive surface 4a. The holder structure as in Fig. 13, which has the slots 12c on the right and left sides, has a similar problem in that it is difficult to move the magnetic

sensitive element 4 in parallel. In the case of the holder structure of Fig. 18 in which the movable holder 14 is moved for fine adjustment and secured in position by using the adjustment screw 16, since the movable holder 14 is not fixed to the fixed holder 15, the position or the inclination of the movable holder 14 may be shifted due to various factors such as vibration or a change in the position or the direction in which the elastic force of the spring 17 is to be imparted. This may possibly lead to a deterioration in output characteristics.

The resistors R_1 to R_4 are generally connected together as shown in Fig. 16, and, if difference occurs in magnetic field strength among those resistors, an A-phase output becomes larger than a B-phase output. In addition, difference also occurs in sensitivity among the resistors R_1 to R_4 , affecting resulting output waveform to show a biased ratio of the positive part to negative part in that waveform and producing the fluctuation of an output signal due to jitters. The smaller is the magnetizing pitch of the magnetic recording medium, the more serious becomes such output problem. Hence, in this particular prior art, with increase of the angle θ between the magnetic sensitive surface 4a and the tangent T (or the parallel plane T_1) associated with the magnetic recording medium 9, several electrical characteristics involved are more subject to enormous variations. Such is the case as shown in Fig. 17, wherein, as the angle θ is greater, a resulting waveform is shown to be distorted by the solid line d in reference to a dashed line c indicative of " $\theta=0$ ", which means deterioration of the output characteristics involved.

Disclosure of the Invention

It is an object of the present invention to provide a holder for magnetic sensitive elements in which a fixed holder is so miniaturized and simplified as to provide a reduced area to be occupied by the magnetic sensitive element and attain good output characteristics.

Accordingly, the present invention provides a holder for magnetic sensitive elements, comprising: a movable holder for holding a magnetic sensitive element to which a flexible signal input/output member is connected, wherein a magnetic sensitive surface of said magnetic sensitive element is disposed opposite to a magnetic recording medium with a gap, a fixed holder fixed to a board, said fixed holder being adapted for holding said movable holder; and a guide means for guiding said movable holder for movement in one direction between said fixed holder and said movable holder,

characterized in that said fixed holder is made from a metallic sheet and includes a positioning means by which said holder is positioned at a

predetermined position on said board and that said movable holder is movable on said fixed holder in a direction defined by said guide means, which is identical to a direction perpendicular to said magnetic sensitive surface of said magnetic sensitive element to thereby permit adjustment of said gap between said magnetic sensitive surface and said magnetic recording medium.

Accordingly, in an arrangement where the holder for magnetic sensitive elements according to the present invention is disposed in opposition to the magnetic drum or the like, by mounting the fixed holder on the board so that a moving axis at the center of the magnetic sensitive surface of the movable holder coincides with an arbitrary normal of the magnetic drum, a tangent which extends to touch one point which is the closest to the holder for the magnetic recording medium is made parallel to the magnetic sensitive surface, and the magnetic sensitive surface moves parallel to the aforesaid tangent. Accordingly, gap adjustment can be easily accomplished and A- and B-phase outputs can be made uniform. It is therefore possible to improve output characteristics while reducing variations in characteristics. The holder according to the present invention is separated into the movable holder including the flexible signal input/output member and the fixed holder. Accordingly, if the fixed holder is formed as a solderable chip, the fixed holder can be automatically mounted on a circuit board together with another circuit element by a chip mounter or the like, whereby connection can be easily achieved by soldering or the like and an improvement in productivity and a great reduction in the cost of assembly can be achieved. In addition, according to the present invention, it is not necessary to make the holder partially project to the right and left sides for the purpose of forming screw-mounting holes for securing the fixed holder to the board, whereby the entire holder can be miniaturized and the area occupied by the holder can be reduced. In addition, since parts such as adjustment screws or springs for moving the movable holder for fine movement are not needed, a simple, small and inexpensive structure can be adopted. According to the invention, the fixed holder is formed from a metallic plate and thus the holder is not only of a certain rigidity of an unchangeable hard nature, but also allows for being formed into a very thin structure. Further, the area of the fixed holder may suffice if it is equal to that of the movable holder, which render smaller the entire size of the holder.

Furthermore, in the present invention, if the fixed holder 2 is formed from a magnetic metallic sheet, this serves as a magnetic shield. Accordingly, when the holder is used in a motor or the like, it is possible to suppress magnetic noise gen-

erated from a driving magnet or other disturbance factors.

In another aspect of the invention, an adhesive reservoir is formed in an upper portion of the guide portion formed on the movable holder, and thus, by simply injecting an adhesive agent into the reservoir, the movable holder is fixed unmoved at a given position relative to the fixed holder.

In still another aspect, an holder, having the magnetic sensitive element retained thereon, is applied an elastic urging force from the fixed holder soldered on the circuit board, with the magnetic sensitive surface of the magnetic sensitive element being disposed opposite to a magnetic recording medium and a gap being provided therebetween.

Brief Description of the Drawings

Figs. 1 through 11 show embodiments of the present invention, wherein

Fig. 1 is a perspective view showing in assembled form one embodiment of a holder for magnetic sensitive elements, where the holder is shown as holding a magnetic sensitive element; Fig. 2 is an exploded perspective view of the holder;

Fig. 3 is a plan view showing the holder for magnetic sensitive elements and a portion of a magnetic recording medium;

Fig. 4 is a cross-sectional side elevational view showing the essential portion of a movable holder;

Fig. 5 is a perspective view showing one example of a magnetic encoder to which the holder for magnetic sensitive holders according to the present invention is applied;

Fig. 6 is a side elevational view showing one embodiment which is mounted on a circuit board whose circuit pattern is formed on the reverse side;

Figs. 7 to 9 show modifications;

Fig. 7 is a perspective view showing a modification in which a fixed holder is modified;

Fig. 8 is a perspective view showing another modification in which lead frames are modified;

Fig. 9 is a perspective view showing yet another modification in which lead frames are modified;

Fig. 10 is perspective view showing another embodiment in which a fixed holder is secured by a machine screw;

Figs. 11A and 11B are perspective views showing holder structures according to other embodiments;

Fig. 12 is a perspective view showing another example of a conventional holder;

Fig. 13 is an exploded perspective view showing yet another conventional holder;

Fig. 14 is an explanatory view showing the relationship between a magnetic recording medium and a magnetic sensitive surface when gap adjustment is effected by means of a conventional holder for magnetic sensitive holders;

Fig. 15 is a graph showing the relationships between the gap, the effective magnetic field strength and a magnetizing pitch;

Fig. 16 is a connection diagram of the resistors of the magnetic sensitive element;

Fig. 17 is an output waveform diagram of the magnetic sensitive element; and

Fig. 18 is a plan view showing a conventional holder.

Best Mode for Carrying Out the Invention

The arrangement of the present invention will be explained in detail below with reference to the embodiments shown in the accompanying drawings.

A holder for magnetic sensitive elements according to the present invention comprises: a movable holder 3 for holding a magnetic sensitive element 4 to which flexible signal input/output member 5 are connected; a fixed holder 2 fixed to a board 1 for holding the movable holder 3; and a pair of guide means 2b, 3b for guiding the movable holder 3 for movement in one direction between the fixed holder 2 and the movable holder 3, such that the movable holder 3 is moved in a direction perpendicular to a magnetic sensitive surface 4a of the magnetic sensitive element 4.

In the case of the illustrated embodiment, the fixed holder 2 is of a magnetic metal sheet made from a tin-plated iron sheet and bent formed into a configuration having a dovetail groove therein as shown. Guide portions 2b are formed in a manner inclined inwardly from the upper portions of the respective side walls of the fixed holder 2, thereby yielding an elastic nature therein structurally. Those guide portions 2b, therefore, serve to hold and guide the movable holder 3, allowing the same to move therein in one direction only. In the illustrated embodiment, an elasticity is structurally given to the guide portions 2b by way of bending them, but an elastic material such as spring steel may be employed. Projections 2a are formed on both sides of the fixed holder 2, respectively, so that they can be fitted into mating positioning through-holes 1a formed in the board 1 or the like. In the illustrated embodiment, the projections 2a are formed by being cut part-way and erected from the bottom of the fixed holder 2 and thus integral with the fixed holder 2. However, this arrangement is not exclusive and separately formed members analogous to the projections 2 may be fixed likewise to the bottom of the fixed holder 2. The fixed holder 2 is

secured to the circuit board 1 by inserting the projections 2a into the respective through-holes 1a formed in the board 1, positioning them at a given point, and soldering a boundary A between the fixed holder 2 and the board 1 or the boundary between the board 1 and the leading end of each projections 2a as shown in Fig. 6. It is noted that the aforesaid movable holder's movement is effected in the fixed holder in a direction perpendicular to the magnetic sensitive surface 4a of the magnetic sensitive element 4 fixed to the entire surface of the movable holder 3. The material of the fixed holder 2 is not limited to a specific kind but, in terms of productivity, preferably, such a material should be used, which is solderable to the board 1, for example, an iron sheet plated with tin and other magnetic metallic sheets, magnetic powdered alloy, non-magnetic metal such as aluminum alloy, most preferably, a solderable magnetic metal plate which can assume an elastic structure.

The aforesaid movable holder 3 is bodily formed from a synthetic resin or the like, of an insulating nature, and guide portions 3b are formed integrally with the movable holder 3, projecting from the opposite sides thereof, respectively. The guide portions 3b engage with the respective guide portions 2b of the fixed holder 2 to constitute guide means. A recess 3a is formed on the frontal surface of the movable holder 3, and the magnetic sensitive element 4 is securely fitted in the recess 3a. The guide portions 3b include inclined surfaces which are slidably movable with respect to the corresponding guide portions 2b of the fixed holder 2. The sliding direction is perpendicular to the magnetic sensitive surface 4a of the magnetic sensitive element 4. Adhesive reservoirs 3c are formed at locations above the respective guide portions 3b, whereby an adhesive agent is received in the reservoirs 3c so as to secure the movable holder 3c to the fixed holder 2. Also, a biasing magnet 7 is buried in the reverse side of the magnetic sensitive element 4 of the movable holder 3. The guide means, which is arranged between the aforesaid fixed holder 2 and the movable holder 3, is preferably of such material and configuration that can give the movable holder 3 an elastic pressing property against the movable holder 3 at a degree sufficient to temporarily secure the movable holder 3 at an arbitrary position.

A plurality of flexible lead frames 5 are secured to the movable holder 3 by means of an insert molding or the like, the frames being used as the above-mentioned input/output members. In the illustrated embodiment, as shown in Fig. 4, the leading ends 5a of the respective lead frames 5 are bent upwardly and electrically connected to the front terminal portion of the magnetic sensitive element 4, while the other ends of the same project

from the rear face of the movable holder 3 in a direction identical to the above-mentioned direction in which the movable holder 3 is moved. Those other ends of the lead frames 5 are so configured to permit their being secured to the circuit board 1. The portions of the respective lead frames 5 which project from the movable holder 3, are formed into bent parts 5b and rear terminal parts 5c, wherein the latter 5c is soldered fast upon the circuit board 1. Thus, it is seen that, while the rear terminal portions 5c are secured to the board 1, the movable holder 3 remains movable owing to the flexibility of the lead frames 5 per se. The leading portions 5a of the respective lead frames 5 are electrically connected to the terminal portion of the magnetic sensitive element 4 and protected with a sealant 6.

Several examples, each having the similar holder for magnetic sensitive elements arranged in the above-described manner, and applied to a magnetic encoder, will now be explained below with reference to Figs. 1 to 3 and 5.

The holder for magnetic sensitive elements is secured at a predetermined position on the circuit board 1 by soldering or other fixing means. Positioning of the holder is accomplished by inserting the projections 2a of the fixed holder 2 into the corresponding through-holes 1a of the circuit board 1. The through-holes 1a are formed on the board 1 in a parallel relation with a tangent T of the magnetic recording medium 9. As shown in Figs. 3 and 5, the magnetic drum 8 is rotatably disposed in front of the magnetic sensitive element 4 of the movable holder 3 incorporated in the fixed holder 2. Also, the drum 8 is provided on its outer periphery with the magnetic recording medium 9 having a series of alternating magnetic poles N and S thereabout.

In the above-described embodiment, the fixed holder 2 and the terminal portions 5c of the lead frames 5 are secured to the circuit-pattern side of the circuit board 1 by soldering. However, as shown in Fig. 6, the circuit pattern is formed on the reverse side of the board 1, and the projections 2a of the fixed holder 2 may be penetrated through the board 1 to project at the reverse side thereof and secured thereto by dip soldering or the like.

Now, hereinafter, a description will be made regarding the assembling of the magnetic sensitive element holder as well as the mounting of the same upon a circuit board, which are all related above.

Firstly, the movable holder 3, which holds the magnetic sensitive element 4, inserted into between the guide portions 2b of the fixed holder 2, and then, the guide portions 3b of the movable holder 3 are clamped within the guide portions 2b by applying the elastic pressing force of the latter

to the former, so as to secure the movable holder 3 in a provisionally unmoved state.

Next, the projections 2a of the fixed holder 2 are inserted into the corresponding through-holes 1a of the circuit board 1 and located there in position. Then, soldering is effected, which preferably consists of an automatic or dip soldering, using a reflow oven, in order to fix to the circuit board 1 the boundaries A defined between the side faces of the fixed holder 2 and the board 1, and such is done also for fixing the terminal portions 5c of the lead frame 5 to the board 1. During such process, preferably, to bend flat the projections 2a passing through the through-holes 1a, 1a, of the board 1, before soldering them, will ensure preventing the fixed holder 2 against separation from the board, against fall therefrom, and against dislocation.

Then an adjustment is made for varying the gap between the magnetic sensitive element 4 and magnetic recording medium 9: The adjustment involves rotating the magnetic drum 8, displacing the movable holder 3, during such rotation, while observing output values of the element 4, until the values reach an optimum one. In this respect, the fixed holder 2 has been positioned unmoved in parallel with the tangent T of the magnetic recording medium 9, by means of which fixed holder 2, the movable holder 3 is retained for movement in a sole direction perpendicular to the tangent T of the magnetic recording medium 9. This surely permits movement of the magnetic sensitive surface 4a of the element 4 to be executed in a parallel relation with the recording medium 9, simply by moving the movable holder 3, thus rendering much easy the gap adjustment. The movable holder 3 in the illustrated embodiment is secured to the circuit board 1 by soldering together the circuit board 1 and the rear terminal portions 5c of the respective lead frames 5. However, the flexibility of bent portions 5b respectively of the lead frames 5, enables the movable holder 3 to be moved freely toward and away from the magnetic recording medium 9. As may be required, the element holder 3, to which is fixed the signal input/output member 5, may be retained on the fixed holder and subjected to a soldering upon the circuit board 1.

When the gap adjustment has been completed, the movable holder 3 and fixed holder 2, which are temporarily secured by the elastic pressures applied from the guide portions 2b and 3b, are completely fixed in position by charging an adhesive between the corresponding guide portions 2b and 3b or by a mechanical fixing process such as caulking. In the case of fixation using the adhesive, the strength of adhesion can be increased by charging the adhesive into the adhesive reservoirs 3c.

Although the aforesaid embodiment is a preferred embodiment of the present invention, various modifications can be employed without depart from the gist of the present invention. For example, as shown in Fig. 7, a platform-like projection 2c is formed at the bottom of the fixed holder 2, and the movable holder 3 may be mounted on the projection 2c. In this arrangement, reduced is the area of contact between the fixed holder 2 and bottom face of the movable holder 3, in comparison with the other embodiments described above, which therefore creates a less frictional, easy movement of the movable holder 3 during the gap adjustment. Additionally, it advantageously impedes a heat conductivity in soldering process for fixation of the fixed holder to the board 1.

As needed, the lead frames 5 may be so formed that it projects from the upper part of the reverse face of the movable holder 3, as shown in Fig. 8, or from one lateral wall of the movable holder 3, as in Fig. 9. In the holder structure shown in Fig. 9, it is essentially desired that the signal input/output element be made of a material having a non-directional flexibility, such as a lead wire, instead of the lead frames 5 having unidirectional flexibility.

Referring to Fig. 10, the fixed holder 2 may be provided with a positioning pin 2d and a screw-mounting hole 2e. The fixed holder 2 may be fixed in position by means of the pin 2d being securely inserted in a positioning hole (not shown) formed in the circuit board 1, as well as by means of the machine screw 10 being driven into the board 1 through the screw-mounting hole 2e.

As another mode for engaging together the movable and fixed holders 3, 2, a dovetail engagement means may be provided on both bottom surfaces of the movable and fixed holders 3, 2, in order to permit guiding and moving the movable holder 3 in a sole one direction along the fixed holder 2. Reference is made to Fig. 11A, for instance, from which it can be seen that a magnetic metallic plate, forming the fixed holder 2, is bent formed such as to define two guide portions 2b which constitutes a male dovetail engagement part as illustrated, or otherwise a female one, whereas the bottom face of the movable holder 3 is formed with a mating female dovetail engagement part, or otherwise a male one, to define two guide portions 3b, whereupon, as indicated, engaging together those guide portions 2b, 3b results in retaining the movable holder 3 for movement in a sole direction perpendicular to the magnetic sensitive surface 4a. In this arrangement, the fixing of the movable holder 3 to the fixed holder 2 is accomplished by charging an adhesive between the side faces of the fixed holder 2 and the side faces of the movable holder 3 and into the adhesive reservoirs 3c. As

shown in Fig. 11B, the fixed holder 2 may be a thin sheet fixed holder which is formed from the guide portions 2b made from male or female dovetails by machining such as cutting or extrusion. In this arrangement, since the fixed holder 2 is made of elastic material or since the guide portions 3b of the movable holder 3 have elasticity, predetermined elastic pressures can be produced between the guide portions 2b and 3b. In the holder structure shown in Figs. 11A and 11B, it suffices to form the positioning projections 2a with the fixed holder 2 made equal in width to the movable holder 3. Accordingly, it is possible to make the entire holder compact.

Claims

1. A holder for magnetic sensitive elements, comprising: a movable holder (3) for holding a magnetic sensitive element (4) to which a flexible signal input/output member (5) is connected, wherein a magnetic sensitive surface (4a) of said magnetic sensitive element (4) is disposed opposite to a magnetic recording medium (9) with a gap, a fixed holder (2) fixed to a board (1), said fixed holder (2) being adapted for holding said movable holder (3); and a guide means (2b,3b) for guiding said movable holder (3) for movement in one direction between said fixed holder (2) and said movable holder (3),

characterized in that said fixed holder (2) is made from a metallic sheet and includes a positioning means (2a) by which said holder (2) is positioned at a predetermined position on said board (1) and that said movable holder (3) is movable on said fixed holder (2) in a direction defined by said guide means (2b,3b), which is identical to a direction perpendicular to said magnetic sensitive surface (4a) of said magnetic sensitive element (4) to thereby permit adjustment of said gap between said magnetic sensitive surface (4a) and said magnetic recording medium (9).

2. The holder for magnetic sensitive elements according to claim 1, wherein said fixed holder (2) is made from a magnetic metallic sheet.
3. The holder for magnetic sensitive elements according to claim 1, wherein, as said guide means, a pair of right and left guide portions (2b) having inwardly inclined surfaces are formed on said fixed holder (2), while a pair of right and left guide portions (3b) having inclined surfaces which slide on said respective guide portions (2b) of said fixed holder (2) are formed to project from said movable holder

(3), and wherein said guide means (2b,3b) is formed by fitting said guide portions of said movable holder (3) between the guide portions of said fixed holder.

4. The holder for magnetic sensitive elements according to claim 2, wherein said fixed holder (2) is formed of an elastic material, and wherein said guide portions (3b) of said movable holder (3) are held by the elastic pressures applied by said guide portions (2b) of said fixed holder (2).
5. The holder for magnetic sensitive elements according to claim 3, wherein said guide portions (2b) of said fixed holder (2) are structurally given an elasticity.
6. The holder for magnetic sensitive elements according to claim 1, wherein a recess having a surface perpendicular to said direction of movement is formed on a front face of said movable holder (3), and wherein said magnetic sensitive element (4) is securely fitted in said recess.
7. The holder for magnetic sensitive elements according to claim 1, wherein said fixed holder (2) is positioned and secured parallel, by said positioning means (2a), to a tangent of said magnetic recording medium (9), and wherein said magnetic sensitive surface (4a) of said magnetic sensitive element (4) is in parallel with said magnetic recording medium (9).
8. The holder according to claim 1, wherein said signal input/output member (5) is so bent as to yield a flexibility for enabling movement of said movable holder (3), to thereby permit adjustment of said gap present between said magnetic sensitive surface (4a) and said magnetic recording medium (9).
9. The holder according to claim 2, wherein said positioning means (2a) comprises at least two projections (2a) provided at said fixed holder (2) and positioning through holes (1a) formed in said board (1), so that said fixed holder (2) is solderable on said board (1) so as to be fixed thereon, with projections (1a) inserted in said respective through holes (1a) of said board (1).
10. The holder according to claim 3, wherein an adhesive reservoir means is formed in said guide means.



shown in Fig. 11B, the fixed holder 2 may be a thin sheet fixed holder which is formed from the guide portions 2b made from male or female dovetails by machining such as cutting or extrusion. In this arrangement, since the fixed holder 2 is made of elastic material or since the guide portions 3b of the movable holder 3 have elasticity, predetermined elastic pressures can be produced between the guide portions 2b and 3b. In the holder structure shown in Figs. 11A and 11B, it suffices to form the positioning projections 2a with the fixed holder 2 made equal in width to the movable holder 3. Accordingly, it is possible to make the entire holder compact.

Claims

1. A holder for magnetic sensitive elements, comprising: a movable holder (3) for holding a magnetic sensitive element (4) to which a flexible signal input/output member (5) is connected, wherein a magnetic sensitive surface (4a) of said magnetic sensitive element (4) is disposed opposite to a magnetic recording medium (9) with a gap, a fixed holder (2) fixed to a board (1), said fixed holder (2) being adapted for holding said movable holder (3); and a guide means (2b,3b) for guiding said movable holder (3) for movement in one direction between said fixed holder (2) and said movable holder (3),
characterized in that said fixed holder (2) is made from a metallic sheet and includes a positioning means (2a) by which said holder (2) is positioned at a predetermined position on said board (1) and that said movable holder (3) is movable on said fixed holder (2) in a direction defined by said guide means (2b,3b), which is identical to a direction perpendicular to said magnetic sensitive surface (4a) of said magnetic sensitive element (4) to thereby permit adjustment of said gap between said magnetic sensitive surface (4a) and said magnetic recording medium (9).
2. The holder for magnetic sensitive elements according to claim 1, wherein said fixed holder (2) is made from a magnetic metallic sheet.
3. The holder for magnetic sensitive elements according to claim 1, wherein, as said guide means, a pair of right and left guide portions (2b) having inwardly inclined surfaces are formed on said fixed holder (2), while a pair of right and left guide portions (3b) having inclined surfaces which slide on said respective guide portions (2b) of said fixed holder (2) are formed to project from said movable holder (3), and wherein said guide means (2b,3b) is formed by fitting said guide portions of said movable holder (3) between the guide portions of said fixed holder.
4. The holder for magnetic sensitive elements according to claim 2, wherein said fixed holder (2) is formed of an elastic material, and wherein said guide portions (3b) of said movable holder (3) are held by the elastic pressures applied by said guide portions (2b) of said fixed holder (2).
5. The holder for magnetic sensitive elements according to claim 3, wherein said guide portions (2b) of said fixed holder (2) are structurally given an elasticity.
6. The holder for magnetic sensitive elements according to claim 1, wherein a recess having a surface perpendicular to said direction of movement is formed on a front face of said movable holder (3), and wherein said magnetic sensitive element (4) is securely fitted in said recess.
7. The holder for magnetic sensitive elements according to claim 1, wherein said fixed holder (2) is positioned and secured parallel, by said positioning means (2a), to a tangent of said magnetic recording medium (9), and wherein said magnetic sensitive surface (4a) of said magnetic sensitive element (4) is in parallel with said magnetic recording medium (9).
8. The holder according to claim 1, wherein said signal input/output member (5) is so bent as to yield a flexibility for enabling movement of said movable holder (3), to thereby permit adjustment of said gap present between said magnetic sensitive surface (4a) and said magnetic recording medium (9).
9. The holder according to claim 2, wherein said positioning means (2a) comprises at least two projections (2a) provided at said fixed holder (2) and positioning through holes (1a) formed in said board (1), so that said fixed holder (2) is solderable on said board (1) so as to be fixed thereon, with projections (1a) inserted in said respective through holes (1a) of said board (1).
10. The holder according to claim 3, wherein an adhesive reservoir means is formed in said guide means.



11. The holder for magnetic sensitive elements according to claim 3, wherein an adhesive reservoir (3c) is formed in an upper portion of said guide portion (3b) of said movable holder (3).
12. The holder according to claim 1, wherein said guide means (2b,3b) is formed by a guide portion (2b) of said fixed holder (2) and a mating guide portion (3b) of said movable holder (3), wherein said guide portions (2b,3b) of said fixed and movable holders slidably engage such that said movable holder (2) may be moved back and forth for said gap adjustment.
13. The holder according to claim 1, wherein said fixed holder (2) is fixed by soldering to said board (1).
14. The holder according to claim 1, wherein said movable and fixed holders (2,3) are formed generally in dovetail shape at their respective portions (2b,3b) corresponding to said guide means (2b,3b).
15. The holder according to claim 14, wherein one of said movable and fixed holders (2) is formed with a male dovetail engagement portion (2b) whereas another of said movable and fixed holders (3) is formed with a female dovetail portion (3b), wherein said male and female dovetail portions constitute said guide means (2b,3b) and wherein both said movable and fixed holders (2,3) slidably engage at said male and female dovetail portions.
16. The holder according to claim 1, wherein said fixed holder (2) is provided with a means (2c) for reducing the area of contact of said fixed holder (2) with said movable holder (3).
17. The holder according to claim 16, wherein said reducing means (2c) comprises a platform-like projected portion (2c) formed at a bottom wall of said fixed holder.
18. The holder according to claim 1, wherein said fixed holder (2) is provided with a positioning pin (2d) and a screw-mounting hole (2e) and wherein said fixed holder (2) is fixed in position upon said board (1) by a machine screw driven (10) into said board (1) through said screw-mounting hole (2e) as well as by said positioning pin (2d).

Patentansprüche

1. Halter für magnetisch empfindliche bzw. magnetempfindliche Elemente, umfassend: einen verschiebbaren Halter (3) zum Halten eines magnetempfindlichen Elements (4), mit dem ein flexibles Signaleingabe/ausgabeelement (5) verbunden ist, wobei eine magnetempfindliche Fläche (4a) des magnetempfindlichen Elements (4) mit einem Spalt dazwischen in Gegenüberstellung zu einem magnetischen Aufzeichnungsmedium (9) angeordnet ist, einen an einer Leiterplatte (1) befestigten festen (feststehenden) Halter (2), welcher den verschiebbaren Halter (3) zu halten vermag, und eine Führungseinrichtung (2b, 3b) zum Führen des verschiebbaren Halters (3) für Verschiebung in einer Richtung zwischen dem festen Halter (2) und dem verschiebbaren Halter (3),
dadurch gekennzeichnet, daß der feste Halter (2) aus einem Metallblech hergestellt ist und (ein) Positioniermittel (2a) aufweist, mit dessen (deren) Hilfe der Halter (2) in einer vorbestimmten Position auf der Leiterplatte (1) positioniert ist, und daß der verschiebbare Halter (3) auf dem festen Halter (2) in einer durch die Führungseinrichtung (2b, 3b) definierten Richtung verschiebbar ist, welche mit einer Richtung senkrecht zur magnetempfindlichen Fläche (4a) des magnetempfindlichen Elements (4) identisch ist, um damit eine Einstellung des Spalts zwischen der magnetempfindlichen Fläche (4a) und dem magnetischen Aufzeichnungsmedium (9) zuzulassen.
2. Halter für magnetempfindliche Elemente nach Anspruch 1, wobei der feste Halter (2) aus einem magnetischen Metallblech geformt ist.
3. Halter für magnetempfindliche Elemente nach Anspruch 1, wobei als Führungseinrichtung am festen Halter (2) zwei rechte und linke Führungsteile (2b) mit schräg einwärts (nach oben) verlaufenden Flächen angeformt sind, während am verschiebbaren Halter (3) zwei rechte und linke Führungsteile (3b) mit Schrägflächen, die auf den jeweiligen Führungsteilen (2b) des festen Halters (2) gleiten, angeformt sind, und wobei die Führungseinrichtung (2b, 3b) durch (passendes) Einschieben der Führungsteile des verschiebbaren Halters (3) zwischen die Führungsteile des festen Halters gebildet ist.
4. Halter für magnetempfindliche Elemente nach Anspruch 2, wobei der feste Halter (2) aus einem elastischen Werkstoff geformt ist und wobei die Führungsteile (3b) des verschiebbaren Halters (3) durch die von den Führungstei-



- len (2b) des festen Halters (2) ausgeübten elastischen Drücke (fest) gehalten sind.
5. Halter für magnetempfindliche Elemente nach Anspruch 3, wobei den Führungsteilen (2b) des festen Halters (2) eine strukturelle Elastizität verliehen ist. 5
 6. Halter für magnetempfindliche Elemente nach Anspruch 1, wobei an (in) einer Stirnfläche des verschiebbaren Halters (3) eine Ausnehmung mit einer senkrecht zur Verschieberichtung liegenden Fläche geformt ist und wobei das magnetempfindliche Element (4) mit sicherem Sitz in die Ausnehmung eingepaßt ist. 10 15
 7. Halter für magnetempfindliche Elemente nach Anspruch 1, wobei der feste Halter (2) mit Hilfe des (der) Positioniermittel (2a) parallel zu einer Tangente des magnetischen Aufzeichnungsmediums (9) positioniert und festgelegt ist und wobei die magnetempfindliche Fläche (4a) des magnetempfindlichen Elements (4) parallel zum magnetischen Aufzeichnungsmedium (9) angeordnet ist. 20 25
 8. Halter nach Anspruch 1, wobei das Signaleingabe/ausgabeelement (5) so gebogen ist, daß es Flexibilität zur Ermöglichung einer Verschiebung des verschiebbaren Halters (3) zwecks Ermöglichung einer Einstellung des zwischen der magnetempfindlichen Fläche (4a) und dem magnetischen Aufzeichnungsmedium (9) bestehenden Spalts aufweist. 30 35
 9. Halter nach Anspruch 2, wobei das (die) Positioniermittel (2a) mindestens zwei am festen Halter (2) vorgesehene Nasen (2a) sowie in der Leiterplatte (1) ausgebildete durchgehende Positionieröffnungen (1a) umfaßt (umfassen), so daß der feste Halter (2) zu seiner Befestigung an der Leiterplatte (1) an dieser anlötfar ist, während die Nasen (1a bzw. 2a) in die betreffenden durchgehenden Öffnungen (1a) (in) der Leiterplatte (1) eingesteckt sind. 40 45
 10. Halter nach Anspruch 3, wobei in der Führungseinrichtung eine Klebmittelreservoir-einrichtung geformt ist. 50
 11. Halter für magnetempfindliche Elemente nach Anspruch 3, wobei in einem oberen Abschnitt des Führungsteils (3b) des verschiebbaren Halters (3) ein Klebmittelreservoir (3c) geformt ist. 55
 12. Halter nach Anspruch 1, wobei die Führungseinrichtung (2b, 3b) durch ein Führungsteil (2b) des festen Halters (2) und ein komplementäres Führungsteil (3b) des verschiebbaren Halters (3) gebildet ist und wobei die Führungsteile (2b, 3b) von festem und verschiebbarem Halter derart verschiebbar zusammengreifen, daß der verschiebbare Halter (2) für die Spalteinstellung rückwärts und vorwärts verschiebbar ist.
 13. Halter nach Anspruch 1, wobei der feste Halter (2) durch Löten an der Leiterplatte (1) befestigt ist.
 14. Halter nach Anspruch 1, wobei der verschiebbare und der feste Halter (2, 3) an ihren jeweiligen, der Führungseinrichtung (2b, 3b) entsprechenden Abschnitten im wesentlichen mit einer Schwalbenschwanz(führungs)form ausgebildet sind.
 15. Halter nach Anspruch 14, wobei einer (2) der verschiebbaren und festen Halter mit einem Innen-Schwalbenschwanzzeiggreifabschnitt (2b) ausgebildet ist, während der andere (3) der verschiebbaren und festen Halter mit einem Außen-Schwalbenschwanzabschnitt (3b) versehen ist, wobei die Innen- und Außen-Schwalbenschwanzabschnitte die Führungseinrichtung (2b, 3b) bilden und wobei verschiebbarer und fester Halter (2, 3) an den Innen- und Außen-Schwalbenschwanzabschnitten verschiebbar miteinander in Eingriff gebracht sind.
 16. Halter nach Anspruch 1, wobei der feste Halter (2) mit einem Mittel (2c) zur Verkleinerung der Kontaktfläche zwischen dem festen Halter (2) und dem verschiebbaren Halter (3) versehen ist.
 17. Halter nach Anspruch 16, wobei das (Flächen-)Verkleinerungsmittel (2c) einen an einer Bodenwand des festen Halters angeformten, plattenförmig erhabenen Abschnitt (2c) umfaßt.
 18. Halter nach Anspruch 1, wobei der feste Halter (2) mit einem Positionierzapfen (2d) und einer Schrauben-(aufnahme)bohrung (2e) versehen ist und wobei der feste Halter (2) mittels einer durch die Schraubenbohrung (2e) hindurch in die Leiterplatte (1) eingeschraubten Maschinenschraube (10) sowie mittels des Positionierzapfens (2d) in seiner Position auf der Leiterplatte (1) festgelegt ist.

Revendications

1. Support pour éléments magnéto-sensibles, comprenant : un support mobile (3) pour tenir un élément magnéto-sensible (4) auquel est



- connecté un élément flexible d'entrée et de sortie de signaux (5), dans lequel une surface magnéto-sensible (4a) dudit élément magnéto-sensible (4) est disposée en face d'un moyen d'enregistrement magnétique (9) avec un jeu, un support fixe (2) fixé sur une plaque (1), ledit support fixe (2) étant adapté pour tenir ledit support mobile (3) ; et un moyen de guidage (2b, 3b) pour guider ledit support mobile (3) dans un mouvement selon une direction entre ledit support fixe (2) et ledit support mobile (3), caractérisé en ce que ledit support fixe (2) est constitué par une feuille métallique et comprend un moyen de positionnement (2a) par lequel ledit support (2) est positionné à une position prédéterminée sur ladite plaque (1), et en ce que ledit support mobile (3) est mobile sur ledit support fixe (2) selon une direction définie par ledit moyen de guidage (2b, 3b) qui est identique à une direction perpendiculaire à ladite surface magnéto-sensible (4a) dudit élément magnéto-sensible (4) pour permettre ainsi un réglage dudit jeu entre ladite surface magnéto-sensible (4a) et ledit moyen d'enregistrement magnétique (9).
2. Support pour éléments magnéto-sensibles selon la revendication 1, dans lequel ledit support fixe (2) est constitué par une feuille métallique magnétique.
 3. Support pour éléments magnéto-sensibles selon la revendication 1, dans lequel, en tant que ledit moyen de guidage, une paire de parties de guidage droite et gauche (2b), ayant des surfaces inclinées vers l'intérieur, est formée sur ledit support fixe (2), tandis qu'une paire de parties de guidage droite et gauche (3b), ayant des surfaces inclinées qui glissent sur lesdites parties de guidage respectives (2b) dudit support fixe (12), est formée pour faire saillie à partir dudit support mobile (3), et dans lequel ledit moyen de guidage (2b, 3b) est formé en montant lesdites parties de guidage dudit support mobile (3) entre les parties de guidage dudit support fixe.
 4. Support pour des éléments magnéto-sensibles selon la revendication 2, dans lequel ledit support fixe (2) est formé à partir d'un matériau élastique, et dans lequel lesdites parties de guidage (3b) dudit support mobile (3) sont tenues par la pression élastique appliquée par lesdites parties de guidage (2b) dudit support fixe (2).
 5. Support pour éléments magnéto-sensibles selon la revendication 3, dans lequel lesdites parties de guidage (2b) dudit support fixe (2) reçoivent une élasticité par construction.
 6. Support pour éléments magnéto-sensibles selon la revendication 1, dans lequel un évidement ayant une surface perpendiculaire à ladite direction du mouvement est formé sur la surface frontale dudit support mobile (3), et dans lequel l'élément magnéto-sensible (4) est fixé fermement dans ledit évidement.
 7. Support pour éléments magnéto-sensibles selon la revendication 1, dans lequel ledit support fixe (2) est positionné et fixé parallèlement par lesdits moyens de positionnement (2a), suivant une tangente dudit moyen d'enregistrement magnétique (9), et dans lequel ladite surface magnéto-sensible (4a) dudit élément magnéto-sensible (4) est parallèle audit moyen d'enregistrement magnétique (9).
 8. Support selon la revendication 1, dans lequel ledit élément d'entrée et de sortie de signaux (5) est plié de façon à avoir une flexibilité rendant possible le mouvement dudit support mobile (3), permettant ainsi le réglage dudit jeu présent entre ladite surface magnéto-sensible (4a) et ledit moyen d'enregistrement magnétique (9).
 9. Support selon la revendication 2, dans lequel ledit moyen de positionnement (2a) comprend au moins deux saillies (2a) prévues sur ledit support fixe (2) et positionnées par des trous (1a) formés sur ladite plaque (1), de façon que ledit support fixe (2) puisse être brasé sur ladite plaque (1) pour y être fixé, avec des saillies (1a) introduites dans les trous respectifs (1a) sur ladite plaque (1).
 10. Support selon la revendication 3, dans lequel un moyen formant réservoir adhésif est constitué dans ledit moyen de guidage.
 11. Support pour éléments magnéto-sensibles selon la revendication 3, dans lequel un réservoir adhésif (3c) est formé à la partie supérieure de ladite partie de guidage (3b) sur ledit support mobile (3).
 12. Support selon la revendication 1, dans lequel ledit moyen de guidage (2b, 3b) est constitué par une partie de guidage (2b) sur ledit support fixe (2) et une partie de guidage conjuguée (3b) dudit support mobile (3), dans lequel les parties de guidage (2b, 3b) desdits supports fixe et mobile viennent en prise en glissant de façon que ledit support mobile (2)



puisse être déplacé vers l'avant et vers l'arrière pour ledit réglage du jeu.

13. Support selon la revendication 1, dans lequel ledit support fixe (2) est fixé par brasage sur ladite plaque (1). 5

14. Support selon la revendication 1, dans lequel lesdits supports mobile et fixe (2, 3) sont formés globalement en forme de queue d'aronde à leurs parties respectives (2b, 3b) correspondant audit moyen de guidage (2b, 3b). 10

15. Support selon la revendication 14, dans lequel l'un desdits supports mobile et fixe (2) est formé avec une partie de montage à queue d'aronde mâle (2b), tandis que l'autre desdits supports mobile et fixe (3) est formé par une partie en queue d'aronde femelle (3b), et dans lequel les parties en queues d'aronde mâle et femelle constituent ledit moyen de guidage (2b, 3b), et dans lequel lesdits deux supports mobile et fixe (2, 3) viennent en prise en glissant sur lesdites parties en queues d'aronde mâle et femelle. 15
20
25

16. Support selon la revendication 1, dans lequel ledit support fixe (2) est pourvu d'un moyen (2c) pour réduire la surface de contact dudit support fixe (2) avec ledit support mobile (3). 30

17. Support selon la revendication 16, dans lequel ledit moyen de réduction (2c) comprend une partie faisant saillie en forme de plate-forme (2c) formée sur une paroi de fond dudit support fixe. 35

18. Support selon la revendication 1, dans lequel ledit support fixe (2) est muni d'une broche de position (2d) et un perçage de fixation par vis (2e) et dans lequel ledit support fixe (2) est maintenu en position sur ladite plaque (1) par une vis mécanique (10) introduite dans ladite plaque (1) par ledit perçage de fixation par vis (2e), ainsi que par ladite broche de positionnement (2d). 40
45

50

55