

Description

Brief Description Of The Invention

5 There is described a process for the transvinylation of a vinyl derivative of a Bronsted acid with a different Bronsted acid which comprises providing a liquid phase mixture containing said vinyl derivative and said Bronsted acid in the presence of a ruthenium compound at a temperature at which transvinylation occurs and recovering as a product of transvinylation the vinyl derivative of the different Bronsted acid.

10 Background To The Invention

Transvinylation or vinyl interchange technology has existed for several decades. The reaction can be illustrated by the reaction of a vinyl ester or vinyl ether with an active hydrogen containing compound, as in the following:



20 wherein R is carboxy, amido, aroxy, alkoxy, and the like; X is hydrogen, hydroxyl, alkyl, aryl, and the like; and R' is carboxyl, amido, alkyl, substituted alkyl, aryl or substituted aryl.

Adelman, Journal Organic Chemistry, 14, pp.1057-1077, 1949, at p.1057, termed transvinylation "the Vinyl Interchange" Reaction, to differentiate it from typical ester interchange and ester-acid interchange reactions"... Adelman noted the following advantages for this reaction:

25 "The very mild reaction conditions and the low yields of by-products lead to high yields of monomers of greater purity and activity than those prepared by the reaction of acetylene with acids.

"Furthermore, vinyl esters of dibasic acids are prepared much more easily by vinyl interchange than through the acetylene route, and recent work in this laboratory has shown that the reaction of vinyl acetate catalyzed with mercuric salts is not restricted to carboxylic acids, but will occur with other compounds containing active hydrogen, such as acetoacetic ester and glycolic esters."

30 McKeon, et al., Tetrahedron, 28, pp. 227 - 232 (1972) show the vinyl interchange reaction between a vinyl ether and an alcohol using a palladium catalyst. Other sources report the transvinylation reaction between vinyl chloride and a carboxylic acid.

The literature suggests that the preferred catalysts for transvinylation reactions have been mercury and palladium based compounds. However, Pt(II) and Rh (III) have been reported by A. Sabel, J. Smidt, R. Jira and H. Prigge, Chem. Ber., 102, pp. 2939-2950 (1969), to catalyze the reaction. In addition, Young, U.S. Patent 3,755,387, patented August 26, 1973, entitled: "A Vapor Phase Transvinylation Process", claims the use of supported Hg, Pd, Pt, Ir, Rh, Ru, or Os salt catalysts in a vapor phase transvinylation process. The experimental portion discloses the use of only palladium on carbon, copper on carbon, iron on carbon, palladium/copper on carbon, palladium/copper/iron on silica, mercuric acetate on carbon, and mercuric chloride on carbon. Hg and Pd are cited, at col. 1, line 67, as the preferred metals. There is no recognition by this patentee of any special advantages to (i) the use of ruthenium compounds as catalysts for transvinylation reactions and (ii) effecting the reaction in a liquid phase reaction using a ruthenium compound as the catalyst.

45 FR-A-1304569 discloses a process for the transesterification of vinylesters in presence, as catalyst, of salts of a metal of the family of platinum and more particularly of Pd, Pt and Rh salts (see examples 1-14) carried out in liquid conditions. No exemplification of Ru-salt catalyzed processes may be found nor are the particular selection of ruthenium or its advantageous properties suggested.

Significant deficiencies in these prior art technologies are:

- 50 1. The mercury-based catalyst is toxic, undesirably volatile, and is typically activated with sulfuric acid to promote reaction and then deactivated by neutralization with base prior to product distillation. Traces of adventitious free acid generated by this system tend to promote ethylidene diester formation.
2. Palladium-based catalysts are not sufficiently thermally stable to allow product removal by distillation at elevated temperatures; the catalyst often deactivates forming metallic Pd.

55 M Rotem, et al, Organometallics, 2, pp. 1689-1691 (1983), T. Mitsudo, et al., J. Org. Chem., 50, pp. 1566-1568 (1985), and T. Mitsudo, et al, J. Org. Chem., 52, pp. 2230-2239 (1987) show the use of ruthenium based catalysts to promote the addition of carboxylic acids to alkynes and producing alkenyl carboxylates. In particular, the reaction of carboxylic acids with substituted alkynes is facile. The reaction of

carboxylic acids with acetylene (vinylation) to give vinyl esters is also possible, but at a much slower rate. Various catalyst precursors have been studied which include ruthenium carbonyl, bis(eta 5-cyclooctadienyl)-ruthenium (II)/tri-n-butylphosphine, and bis(eta 5-cyclooctadienyl)ruthenium (II)/trialkylphosphine/maleic anhydride.

5 The use of these and similar ruthenium compositions as transvinylation catalysts has apparently not been recognized until this invention. The beneficial use of ruthenium-containing compounds as catalysts for transvinylation processes which overcome several of the deficiencies noted for the prior art catalysts has not been appreciated until this invention.

10 There is a need in the transvinylation art for a catalyst having high catalytic activity at convenient elevated temperatures which would allow the facile removal of the desired product of the reaction without interfering with other components present in the reaction product mixture.

The Invention

15 The invention relates to a process for the transvinylation of a vinyl derivative of a Bronsted acid with a different Bronsted acid which comprises providing a liquid phase mixture containing said vinyl derivative and said Bronsted acid in the presence of a catalyst at elevated temperature and recovering the vinyl derivative of the different Bronsted acid characterized in that the catalyst is a ruthenium compound.

Further embodiments of the invention are set forth in dependent claims 2 to 18.

20

Details Of The Invention

Transvinylations are equilibrium reactions. The efficiency of the reaction is measured by the extent the desired transvinylation reaction product is present in the equilibrium reaction products. In other words, the reaction generates more than one product and the effectiveness of the process is frequently measured by the proportion of the desired product to the other products of the transvinylation reaction.

The reaction of the invention involves the combination of
 a vinyl derivative of a Bronsted acid (I);
 a different Bronsted acid (II) with which to interchange;
 30 a ruthenium compound; and
 liquid phase reaction conditions.

The vinyl derivative is any compound in which there is a vinyl group bonded to a Bronsted acid. They may be characterized as vinylated Bronsted acids. Vinyl embraces groups of the formula

35 $R^0R^1C=CH-$

wherein R^0 and R^1 are each individually one of hydrogen, alkyl of 1 to about 12 carbon atoms, cycloalkyl, aryl, alkyl ethers, and the like. The Bronsted acid is any species which can act as a source of protons.

40 Illustrative of suitable vinyl derivatives of a Bronsted acid (I) for the practice of the invention, are vinyl acetate, vinyl pivalate, vinyl benzoate, vinyl methacrylate, vinyl acrylate, divinyl isophthalate, divinyl terephthalate, divinyl adipate, vinyl propionate, vinyl stearate, vinyl salicylate, vinyl cinnamate, vinyl 2-ethylhexanoate, vinyl cyclohexanoate, N-vinyl pyrrolidinone, N-vinylsuccinimide, vinyl phenyl ether, vinyl methyl ether, vinyl ethyl ether, N-vinyl 2-oxazolidinone, N-vinyl ethyleneurea, N-vinyl N-acetylmethylurea, 2-vinyloxyethyl acetate, 2-vinyloxyethyl pivalate, 2-vinyloxyethylacrylate, vinyl chloride, vinyl sulfonamides, and the like.

45 Preferred vinyl derivatives are the vinyl esters of carboxylic acids and the vinyl alkyl or aryl ethers, mainly because they are more commercially available.

50 Illustrative of suitable Bronsted acids (II) for the practice of the invention are carboxylic acids such as monocarboxylic and polycarboxylic acids illustrated by acetic acid, propionic acid, butyric acid, pivalic acid and other neo acids, stearic acid, and other vinyl esters of fatty acids, benzoic acid, terephthalic acid, isophthalic acid, phthalic acid, adipic acid, succinic acid, malic acid, maleic acid, polyacrylic acids, crotonic acid, acrylic acid, methacrylic acid, salicylic acid, cinnamic acid, 2-ethylhexanoic, and cyclohexanoic acid; amides such as 2-pyrrolidinone, 2-pyrrolidone, ε-caprolactam, 2-oxazolidinone, ethyleneurea, N-acetyl ethyleneurea, and succinimide; alcohols such as methanol, ethanol, n-propanol, isobutanol, fluorinated alkanols
 55 such as 1,1,1,3,3,3-hexafluoro-2-propanol, monoethanolamine, diethanolamine, and triethanolamine; phenolic compounds such as phenol, resorcinol, and Bisphenol A [2,2-bis(4-hydroxyphenyl)propane]; amino compounds which are sufficiently acidic such as secondary aromatic amines, azoles, blocked amines and imines, silazanes, and the like; hydroxy esters such as hydroxalkyl acrylates (viz., 2-hydroxyethyl acrylate, 2-

hydroxyethyl methacrylate) and hydroxyalkyl alkanoates (viz., 2-hydroxyethyl acetate, 2-hydroxyethyl pivalate); sulfonamides such as diethyl sulfonamide and toluene sulfonamide; silanols such as phenyl silane triol, diphenyl silane diol, triphenyl silane mono-ol, dimethyl silane diol, trimethylsilane mono-ol, and the like.

The preferred Bronsted acids (II) are the carboxylic acids, the alcohols, the imines, the amides, the imides, the phenolics, and the like.

Illustrative of transvinylation reactions that may be carried out by the process of the invention, are the following:

	<u>Vinyl Derivative</u>		<u>Bronsted Acid(II)</u>		<u>Product</u>
10	vinyl acetate	+	pivalic acid	→	vinyl pivalate
	vinyl benzoate	+	pivalic acid	→	vinyl pivalate
15	vinyl acetate	+	methacrylic acid	→	vinyl methacrylate
	vinyl acetate	+	acrylic acid	→	vinyl acrylate
20	vinyl acetate	+	isophthalic acid	→	divinyl isophthalate
	vinyl acetate	+	terephthalic acid	→	divinyl terephthalate
	vinyl propionate	+	adipic acid	→	divinyl adipate
25	vinyl acetate	+	benzoic acid	→	vinyl benzoate
	vinyl acetate	+	propionic acid	→	vinyl propionate
	vinyl pivalate	+	stearic acid	→	vinyl stearate
30	vinyl acetate	+	salicylic acid	→	vinyl salicylate
	vinyl acetate	+	cinnamic acid	→	vinyl cinnamate
35	vinyl propionate	+	2-ethylhexanoic acid	→	vinyl 2-ethylhexanoate
	vinyl acetate	+	cyclohexanoic acid	→	vinyl cyclohexanoate
40	vinyl acetate	+	2-pyrrolidinone	→	N-vinyl 2-pyrrolidinone
	vinyl pivalate	+	2-pyrrolidinone	→	N-vinyl 2-pyrrolidinone
45	vinyl pivalate	+	succinimide	→	N-vinyl succinimide
	vinyl methyl ether	+	phenol	→	vinyl phenyl ether
50	vinyl chloride	+	methanol	→	vinyl methyl ether

	vinyl methyl ether	+	ethanol	→	vinyl ethyl ether
5	vinyl acetate	+	2-oxazolidinone	→	N-vinyl 2-oxazolidinone
	vinyl acetate	+	ethyleneurea	→	N-vinyl ethyleneurea
10	vinyl acetate	+	N-acetyl ethyleneurea	→	N-vinyl N-acetylethyleneurea
	vinyl acetate	+	2-hydroxyethyl acetate	→	2-vinyloxyethyl acetate
15	vinyl pivalate	+	2-hydroxyethyl pivalate	→	2-vinyloxyethyl pivalate
20	vinyl pivalate	+	2-hydroxyethylacrylate	→	2-vinyloxyethyl acrylate

The process of this invention provides an excellent route to many hard to produce vinyl compounds because of the desirable physical and chemical properties of the ruthenium compounds which provide the basis for the catalytic reaction. The ruthenium catalysts are easily obtainable as soluble components and can be used in the form of non-volatile compounds possessing high thermal stability, and exhibiting high catalytic activity only at elevated temperatures. Unlike palladium, the ruthenium-based catalyst does not lead to observable metal precipitation, even when reaction is conducted at temperatures above 150°C. From a practical standpoint, the physical and chemical properties of the ruthenium catalyst (soluble, non-volatile, and possessing high thermal stability) permit product removal by distillation. These properties suggest that the ruthenium catalyst system is far superior to prior art transvinilation technologies using palladium and mercury.

The selection of a suitable ruthenium compound to provide the catalytic activity for the transvinilation reaction is not narrowly critical. Essentially any ruthenium compound can be effectively employed to carry out the transvinilation reaction. However, the invention is believed to involve novel ruthenium-based catalysts which to promote the vinyl interchange (transvinilation) between vinyl derivatives and the Bronsted acids. It is believed the primary requirement for the generation of such catalysts and the requisite catalytic activity are ruthenium precursors to the catalyst which can be converted to $[\text{Ru}(\text{CO})_2\text{RCO}_2]$ or similar compounds even if the precursor during the reaction fails to be converted to such structures. $[\text{Ru}(\text{CO})_2\text{RCO}_2]$ or similar compounds may or may not be the transvinilation catalyst of the invention but it has been noted that the use of such compounds assures the effective catalytic reaction and the results herein characterized. The process of this invention may be practiced with a vast array of ruthenium compounds. Even instances where the ruthenium compound is too stable for catalyzing the reaction, catalysis can be effected by including a compound which does not adversely affect the transvinilation reaction and stimulates the ruthenium compound to be converted to a species having catalytic activity. For example, ruthenium chloride is a sluggish catalyst but is made quite active by the addition of an alkali such as an alkali metal salt of a carboxylic acid, viz. sodium acetate. It is not presumed that simple ruthenium salt compounds are the catalyst or that many of the ruthenium compounds herein used to effect the catalytic reaction are the catalyst. The exact ruthenium containing compound or compounds that constitute the catalyst of this invention is not appreciated but what is appreciated is that many ruthenium compounds can be used to *in situ* generate the catalyst. The diversity of the selection of ruthenium compounds suitably employable as precursors to catalysts in the process of the invention is quite broad; illustrative of this point - the precursor compounds may range from supported ruthenium such as ruthenium on carbon, alumina, and the like, to ruthenium carbonyl to bis(eta - 5-cyclooctadienyl)ruthenium(II)/tri-n-butylphosphine and to bis(eta 5-cyclooctadienyl)ruthenium(II)/trialkyl-phosphine/maleic anhydride.

The most preferred catalysts are formed from ruthenium carbonyl carboxylates, or precursors which can convert into these species. Based on an analysis of the literature, certain assumptions of the likely structure of the catalyst have been made. Based on the recognition that ruthenium carbonyl reacts with carboxylic acids to produce soluble orange-yellow complexes, possessing the empirical formula $[\text{Ru}(\text{CO})-$

2RCO_2], and the fact these complexes appear sufficiently labile to accommodate coordination of vinyl acetate and subsequently catalyze exchanges between vinyl-bound and ruthenium-bound carboxylates, it is believed that such structures are involved in the catalysis of the transvinylolation process. For example, it is known that in the presence of carbon monoxide, $[\text{Ru}(\text{CO})_2\text{RCO}_2]_n$ is readily converted to $\text{Ru}_2(\text{CO})_8(\text{RCO}_2)_2$ dimer. Analogously, substitution with other ligands such as phosphines gives $\text{Ru}_2(\text{CO})_4(\text{L})_2(\text{RCO}_2)_2$ complexes. Similar affinity for coordination is thus proposed for vinyl esters. The addition of one equivalent of triphenylphosphine (per ruthenium) to a ruthenium carbonyl-based catalyst reduced transvinylolation rate by a factor of about ten, indicating the presumably formed complex, $\text{Ru}_2(\text{CO})_4(\text{L})_2(\text{RCO}_2)_2$, is a less active precursor. Similarly, the addition of one equivalent of the phosphonium ylide, 2-(triphenylphosphoranylidene) succinic anhydride, resulted in reduced reaction rates. The complex, hydrido(acetato)tris-(triphenyl-phosphine)ruthenium(II), exhibited meager activity, indicating that higher phosphorus to ruthenium ratios lead to a more serious rate inhibition. Tetrahydridotetraruthenium dodecacarbonyl, $\text{H}_4\text{Ru}_4(\text{CO})_{12}$, can also be used to form the catalyst. Ruthenium(III) chloride, ruthenium(III) iodide, tris(2,2-bipyridyl)ruthenium(II) chloride hexahydrate, and ruthenocene exhibited only very slight catalytic activity, which further substantiates that the level of catalyst activity intimately depends upon the form of the ruthenium precursor.

It has been found that the presumed catalyst precursor, $[\text{Ru}(\text{CO})_2\text{RCO}_2]_n$, can be generated in several ways. For example, the trinuclear complex, $[\text{Ru}_3\text{O}(\text{OAc})_6(\text{H}_2\text{O})_3]\text{OAc}$, gives an efficient transvinylolation catalyst. Infrared analysis indicates that $[\text{Ru}_3\text{O}(\text{OAc})_6(\text{H}_2\text{O})_3]\text{OAc}$ can convert to $[\text{Ru}(\text{CO})_2\text{RCO}_2]_n$ under transvinylolation reaction conditions. This is even observed when the reaction is conducted under nitrogen atmosphere, rather than carbon monoxide. Frequently, there is sufficient adventitious carbon monoxide available to *in situ* convert all of the Ru to a carbonyl form.

As was previously stated, ruthenium trihalide-based precursors, e.g., ruthenium(III) chloride and ruthenium(III) iodide, exhibit only slight activity. However, a very active and more selective catalyst can be generated *in situ* from ruthenium chloride and sodium acetate. This presumably produces the $[\text{Ru}_3\text{O}(\text{OAc})_6(\text{H}_2\text{O})_3]\text{OAc}$ precursor and insoluble sodium chloride salt. The conditions useful for effective catalyst generation includes a ruthenium carboxylate precursor or a mixture of reagents which can generate a ruthenium carboxylate precursor. Dichlorotricarbonylruthenium(II) dimer, $[\text{RuCl}_2(\text{CO})_3]_2$, also gives an active, but non-selective catalyst which produces significant quantities of heavier by-products, tentatively believed to be ethylidene- and glycol-diester. It is postulated that upon conversion to catalyst, $[\text{RuCl}_2(\text{CO})_3]_2$ also forms traces of hydrochloric acid which are principally responsible for the by-product formation. There is some very good evidence to substantiate these assumptions. Under similar reaction conditions, but in the absence of ruthenium, hydrochloric acid has been shown to readily promote heavy by-product formation. The salient conclusion is that ruthenium halide precursors can be used in the invention, however they are best used in conjunction with alkali metal carboxylates (typically sodium acetate) to facilitate precipitation of the alkali metal halide (typically sodium chloride). Non-carbonyl and non-carboxylate containing ruthenium compounds can also lead to highly active catalysts. In experiments conducted under carbon monoxide atmosphere, ruthenium(III) acetyl-acetonate, ruthenium(IV) oxide, ruthenium on carbon, and ruthenium on alumina have all shown catalytic activity. Under these conditions, ruthenium powder shows trace activity. A route to transvinylolation catalysts from ruthenium halides involves, as pointed above, displacing the halide from the ruthenium precursor. It is also likely that other metal salts, known to precipitate halides (Ag^+ , Cu^+ , Hg^+) would also be effective in combination with ruthenium halides to provide the catalyst precursor.

The amount of the ruthenium catalyst useful for effecting the transvinylolation reaction is not narrowly critical. The typical amount is a catalytically effective amount, that is, an amount which is sufficient to effect the desired vinyl interchange. For example, it has been established that ruthenium catalyst concentrations ranging roughly from 30,000 parts to 0.5 part per million (ppm) ruthenium based on the weight of the liquid phase reaction medium can be used to effect the reaction. It is believed that larger and smaller amounts of the catalyst may be used to effect the reaction. The most preferred range is from 0.1 ppm to 500 ppm ruthenium, same basis.

It is desirable that the transvinylolation reaction be carried out in the absence of an amount of water in the reaction mixture that inhibits the production of the desired vinyl interchanged product. However, as shown in the Examples 60-63 below, the reaction can be carried out in the presence of significant quantities of water. The inhibiting effects of water are reactant dependent. Increasing the concentration of ruthenium catalyst in the reaction mixture is a facile method of overcoming water inhibition in many cases, if not most cases. It has been noted that there is a correlation between the amount of ruthenium catalyst employed and the amount of water usable in the process. The more ruthenium present, the more water that may be present in the reaction without affecting the reaction. It is desirable to use a system which is substantially water-free. As a rule, the amount of water present in the reaction is desirably less than about 25 weight % of the weight of the reaction mixture. Preferably, the amount of water in the reaction is less than about 15 weight

% of the weight of the mixture. The smaller the amount of water present the better the reaction operates and greater the yield of desired reaction product. Essentially anhydrous reaction systems as herein characterized are preferred. For example, it is more desirable that the amount of water in the reaction be less than about 10 weight % of the weight of the mixture. Preferably, the amount of water in the reaction is less than about 5 weight % of the weight of the mixture, more preferably less than about 2.5 weight % of the weight of the mixture, most preferably less than about 1 weight % of the weight of the mixture. Water concentration in the reaction mixture can be controlled by conventional procedures, such as by drying the reactants carefully, azeotropically distilling the water from the reaction when an azeotrope is formed, and by the addition of molecular sieve drying agent.

The temperature at which the reaction can be carried out is also not narrowly critical. The reaction rate varies with the identity of the Bronsted acid to be transvinylated. The more acidic acids tend to be reactive at lower temperatures. It is also desirable to operate at a temperature at which the acid reactant is dissolved or liquid. The process is favorably effected by keeping the reaction temperature below the boiling point of the highest boiling reactant or at sufficient pressure to maintain the liquid state. When feasible, the liquid phase condition can best be accomplished by operating at temperatures above the melting point of the acid. Nonetheless, terephthalic acid (mp. > 300° C), which is insoluble in most catalyst-compatible solvents, was transvinylated to divinyl terephthalate by conducting the reaction in aromatic ester solvents at elevated temperatures (ca. 150° C). These conditions presumably facilitate transvinylated by achieving slight solubility of the terephthalic acid. Overall, the temperature at which the reaction may be carried out range up to 300° C, preferably up to 200° C.

The optimum reaction conditions depend chiefly on the Bronsted acid (such as a carboxylic acid) to be transvinylated. If the acid is soluble at the reaction temperature, it is better to operate without solvent. It is also preferred, when feasible, to conduct the reaction at temperatures above the melting point of the acid.

Transvinylation works best without solvents or in nonpolar solvents. Suitable results have been achieved in solvents such as toluene, heptane, silicone oil, mineral oil, phenylbenzoate, dimethylterephthalate, and dioctylphthalate. More highly polar solvents such as alcohols, water, sulfolane, Carbowaxes®, and N-methylpyrrolidinone tend to inhibit reaction rates. Oxygenated aromatics such as diphenylether, methylbenzoate, dimethylterephthalate, and dioctylphthalate are desirable solvents in the synthesis of divinylterephthalate and divinylisophthalate.

The invention is operational over a broad range of mole ratios of Bronsted acid (such as carboxylic acid) to vinyl derivative. The preferred ratio depends mostly on the transformation sought. In general, ratios of 100/1 to 1/100 are preferred and ratios of 1/10 to 10/1 are most preferred.

The mole ratio of the Bronsted acid (viz., carboxylic acid or carboxylate) to ruthenium should be at least 0.5 to 1. The ruthenium concentration in the reaction mixture is a catalytically effective amount and this is typically in the parts per million range while the acid is typically a major component of the reaction mixture. Most preferably the mole ratio of the Bronsted acid to ruthenium is 50/1 to 1,000,000/1.

Several reaction atmospheres, such as carbon monoxide, air, nitrogen, and ethylene, are compatible with the transvinylation catalyst. Nitrogen and ethylene are suitable in most situations. Carbon monoxide appears to improve catalyst selectivity. Air has been employed in conjunction with phenothiazine (polymerization inhibitor) for the synthesis of vinyl acrylates. In some instances the catalytic reaction produces small amounts of methane, carbon monoxide, and carbon dioxide by-products which obviously augment the initially charged reaction atmosphere. The reaction may be carried out at pressures which are subatmospheric, atmospheric or superatmospheric. In some situations, reaction can also be conducted under vacuum, such as in a distillation apparatus. A desirable reaction pressure is from 1.33×10^{-5} mbar (10^{-6} torr) to 345 bar.abs. (5,000 psia). The more desirable reaction pressure is from 1.33×10^{-4} mbar (10^{-5} torr) to 55 bar.abs. (800 psia). The preferred reaction pressure is from 1.33×10^{-3} mbar (10^{-4} torr) to 38 bar.abs. (550 psia). The preferred reaction pressure is superatmospheric pressure, typically from 1.1-345 bar.abs. (16 to 5,000 psia).

As pointed out previously the reaction is carried out under conditions at which all of the reactants are in the liquid phase. This does not require that the reaction environment be wholly in the liquid phase. It simply means that sufficient of the reactants and the catalyst be in the liquid phase that the reaction can occur in the liquid phase. For example, solid ruthenium on a solid support can be used as a catalyst precursor. In the presence of reactant, solvent and/or carbon monoxide, sufficient ruthenium can be converted to a liquid soluble compound such that the catalytic reaction is attainable. In another case, reactant can be supplied in a super-critical fluid condition which is sufficiently "liquid" to support the liquid phase conditions of this invention. Much of the reaction system can be in the gas or solid phase, and this would be acceptable so long as enough of the reaction system is in the liquid phase to support the transvinylation reaction of the invention.

A favorable aspect of the process of the invention is to shift the equilibrium of the reaction in the direction of the favored product so that higher concentrations of the product can be obtained based on the amount of starting materials employed. This can be done by the continuous removal of one of the products of the reaction so as to shift the equilibrium in a favorable direction without adversely affecting the catalyst and/or the ruthenium values.

Example 1

To a Fischer-Porter bottle were charged ruthenium carbonyl (0.318 grams), benzoic acid (183 grams, 1.50 moles), and vinyl acetate (258 grams, 3.00 moles). The bottle was attached to the reaction apparatus, purged and pressurized to 1.7 bar (25 psig) with carbon monoxide, and heated to 150°C for 3 hours. The reaction mixture was cooled to ambient temperature, transferred to a 1 liter flask, and distilled by rotary evaporation under reduced pressure. The fraction taken at approximately 20 mbar (15 torr) and 84°C (187.8 grams) was redistilled through a 15 cm Vigreux column. Vinyl benzoate (100.4 grams, > 99% pure by GC) was collected in fractions boiling from 90-101°C at 20 mbar (15 torr).

Example 2

To a Fischer-Porter bottle were charged tris(aquo)-hexa- μ -aceto- μ_3 -oxo-triruthenium acetate (0.032 grams), 2-ethylhexanoic acid (42.37 grams, 0.294 moles), and vinyl acetate (25.3 grams, 0.294 moles). The bottle was attached to the reaction apparatus, purged and pressurized to 1.7 bar (25 psig) with carbon monoxide, and heated to 150°C for 3 hours. The reaction mixture was stripped of volatiles by rotary evaporation and the residue was distilled through a 15 cm Vigreux column. A fraction collected at 49°C/6.65 mbar (5 torr) was vinyl 2-ethylhexanoate (9.0 grams, > 99 % pure by GC).

Example 3

To a Fischer-Porter bottle were charged ruthenium carbonyl (0.118 grams), pivalic acid (68.43 grams, 0.67 moles), and vinyl benzoate (48.87 grams, 0.33 moles). The bottle was attached to the reaction apparatus, purged and pressurized to 1.7 bar (25 psig) with carbon monoxide, and heated to 150°C for 2 hours. The cooled reaction mixture was charged to a 250 ml flask and vacuum distilled through a 15 cm Vigreux column. A fraction collected at 60.5-65°C /200 mbar (150 torr) (31.7 grams) was redistilled at atmospheric pressure (bp = 114°C, 24.2 grams). It comprised vinyl pivalate.

Example 4

To a Fischer-Porter bottle were charged ruthenium carbonyl (0.211 grams), adipic acid (7.3 grams, 0.05 moles), and vinyl acetate (21.5 grams, 0.25 moles). The bottle was attached to the reaction apparatus, purged and pressurized to 1.7 bar (25 psig) with nitrogen, and heated to 130°C for 4.5 hours. The reaction mixture was stripped of volatiles by rotary evaporation and the residue was distilled through a 15 cm Vigreux column. A fraction collected at 72°C -79°C /1 mbar (0.75 torr) was divinyl adipate (1.5 grams, > 98 % pure by GC).

Example 5

To a Fischer-Porter bottle were charged tris(aquo)-hexa- μ -aceto- μ_3 -oxo-triruthenium acetate (0.9 grams), dioctylphthalate (150 grams), terephthalic acid (75 grams, 0.45 moles), and vinyl acetate (150 grams, 1.74 moles). The bottle was attached to the reaction apparatus, purged and pressurized to 1.7 bar (25 psig) with carbon monoxide, and heated to 175°C for 4.5 hours. The reaction mixture was stripped of volatiles by rotary evaporation. Distillation through a short path column afforded a fraction boiling at 111°C / (0.7 torr) which solidified upon condensing (mp = 76.5 - 80.5°C). It contained divinyl terephthalate.

Example 6

Using a procedure similar to that of Example 5, isophthalic acid (75 grams) was converted to divinyl isophthalate at successive reaction temperatures of 150°C. for 3.5 hours and 175°C for 2.25 hours. Distillation through a short path column afforded a fraction boiling at 117-145°C / (1.2 torr) (7.1 grams) which solidified upon condensing (mp. = 53.5-56.5°C). It comprised divinyl isophthalate.

Examples 7 - 12

The following examples in the following table show a number of ruthenium catalyzed transvinylations conducted between vinyl acetate and a variety of carboxylic acids in which the vinyl ester products, in lieu of isolation, were characterized by either GC/IR/Mass Spec or by GC retention time compared with an authentic sample. The table lists the reaction conditions.

Ex. No.	CARBOXYLIC ACID	VINYL ESTER PRODUCT	MAX. TEMP.	REACT. ATMOS.
7	propionic acid	vinyl propionate	130 °C	N ₂
8	pivalic acid	vinyl pivalate	130 °C	N ₂
9	acrylic acid ¹	vinyl acrylate	100 °C	Air
10	methacrylic acid ²	vinyl methacrylate	100 °C	Air
11	succinic acid	divinyl succinate	150 °C	CO
12	terephthalic acid ³	divinyl terephthalate	170 °C	CO

1. Phenothiazine was added to the reaction mixture to inhibit polymerization.
2. Phenothiazine was added to the reaction mixture to inhibit polymerization.
3. The reaction was conducted in dimethyl terephthalate solvent.

Example 13

In three batches which were later combined, ruthenium carbonyl (44.4 grams, total of the three batches), pivalic acid (510 grams, total of the three batches), and vinyl acetate (432 grams, total of the three batches) were charged to Fischer-Porter bottles, flushed and pressurized 1.7 bar (25 psig) with carbon monoxide, and heated for approximately 2 hours at 145-160 °C. This procedure resulted in a highly concentrated ruthenium catalyst solution (2.15% ruthenium or 21,500 ppm ruthenium) which as a result of the reaction conditions, was dissolved in an equilibrated mixture of vinyl acetate, pivalic acid, vinyl pivalate, and acetic acid. When charged to the 113.5 l (30 gallon) stainless steel reactor as described below with 37.8 l (10 gallons) each of vinyl acetate and pivalic acid to make vinyl pivalate, a 300 ppm ruthenium catalyst concentration was achieved.

Vinyl pivalate (91 pounds) was prepared in two, 75.7 l (20 gallon)-batch runs in a 113.5 l (30 gallon) stainless steel reactor. In two batches, pivalic acid 34 kg (75.5 lbs), 37.8 l (10 gallons) and vinyl acetate 35 kg (77.9 lbs), 37.8 l (10 gallons) were transvinylated in the presence of 300 ppm ruthenium catalyst, described in the preceding paragraph, at 145 °C using a 3.45 bar (50 psig) carbon monoxide reaction atmosphere for 5 hours. Reaction product was removed from the reactor by vacuum distillation (60-130 °C, -320 mbar-240 mm Hg) from the ruthenium catalyst without difficulty. Based on gas chromatographic analysis, 90.4% and 94.7% of the vinyl pivalate respectively formed in the two reaction batches, could be accounted for after distillation. This demonstrates that reequilibration of vinyl pivalate (and acetic acid) to vinyl acetate (and pivalic acid) was successfully controlled during distillation within 9.6% (batch 1) and 5.3% (batch 2), respectively. Mass balances for all components were better than 98%.

Examples 14 - 32

Catalytic activity of numerous ruthenium precursor compounds was evaluated according to the following procedure. A mixture of the ruthenium compound, vinyl acetate (17.2 grams), benzoic acid (12.2 grams) and nonane (internal standard for gas chromatographic analysis) were charged to a Fischer-Porter bottle, sealed, purged three times with carbon monoxide and finally pressurized to 1.7 bar (25 psig). The magnetically-stirred reaction mixture was heated in an oil bath to the desired reaction temperature for a specified time period (both specified in the table). Gas chromatographic analysis on an DB-1 fused silica capillary column (30M) revealed the amount of vinyl benzoate formed by transvinylation (shown in the table).

Ex. No.	Catalyst Precursor (grams)	Temp./Time °C/h	Vinyl Benzoate, grams
14	tris(aquo)-hexa- μ_3 - -oxo-triruthenium heptaacetate (0.211 g)	102/19 ⁴	5.704
15	$\text{RuCl}_3 \cdot x\text{H}_2\text{O}$ (0.211 g)	130/3 ⁵	0.287
16	$\text{RuCl}_3 \cdot x\text{H}_2\text{O}$ (0.211) sodium acetate (1.0 g)	130/1	4.072
17	$\text{Ru}_3(\text{CO})_{12}$ (0.211 g)	130/2 ⁶	6.180
18	$\text{Ru}_3(\text{CO})_{12}$ (0.21 g)	130/2 ⁷	5.025
19	$\text{Ru}_3(\text{CO})_{12}$ (0.002 g)	130/2 ⁸	1.759
20	$\text{Ru}_3(\text{CO})_{12}$ (0.021 g)	130/2 ⁹	4.722

4. The Fischer-Porter bottle was purged and pressurized with 1.7 bar (25 psig) nitrogen instead of 1.7 bar (25 psig) carbon monoxide

5. See previous footnote

6. See previous footnote

7. See previous footnote

8. See previous footnote

9. The Fischer-Porter bottle was purged and pressurized with 1.7 bar (25 psig) ethylene instead of 1.7 bar (25 psig) carbon monoxide

	21	$\text{Ru}_3(\text{CO})_{12}$ (0.021 g)	130/2	5.027
5	22	$\text{Ru}_3(\text{CO})_{12}$ (0.211 g) triphenylphosphine (0.262 g)	130/18 ¹⁰	5.723
	23	ruthenium [5% on carbon], (1.0 g)	150/4	6.067
10	24	ruthenium [5% on alumina], (1.0 g)	150/18	5.421
	25	ruthenium(III) 2,4- pentanedioate (0.06 g)	150/4	5.957
15	26	ruthenium powder 99.9% (0.06 g)	150/2	0.126
20	27	dichlorotricarbonyl- ruthenium(II) dimer (0.06 g)	150/2	4.277
	28	ruthenium(IV) oxide, hydrate (0.06 g)	150/2	2.762
25	29	tris(2,2'-bipyridyl) ruthenium(II) chloride, hexahydrate (0.2 g)	150/2	NA
30	30	ruthenium(IV) oxide, anhydrous (0.06 g)	150/2	0.045
	31	$\text{H}_4\text{Ru}_4(\text{CO})_{12}$ (0.06 g)	150/2	7.008
35	32	ruthenium(III) iodide (0.06 g)	150/2	0.029

40 10. The Fischer-Porter bottle was purged and pressurized with 1.7 bar (25 psig) nitrogen instead of 1.7 bar (25 psig) carbon monoxide

45 Examples 33 - 46

The following table demonstrates transvinylation without product isolation. In the examples recited in the table, ruthenium catalyzed transvinylations (300 ppm ruthenium) of various acidic compounds with either vinyl acetate (VA) or vinyl pivalate (VP) were conducted in a manner in which the vinyl monomer products, in lieu of isolation were characterized by GC/IR/MASS SPEC or GC retention time compared with an authentic sample. The table lists the reaction conditions.

Ex. No.	Acidic Compound	Vinyl Source	•C/h	Product(s)	Verification Technique
33	stearic acid	VA	150/18	vinyl stearate	retention
34	palmitic acid	VA	150/5	vinyl palmitate	GC/IR/MS
35	succinimide	VA	150/3	vinyl succinimide	GC/IR/MS
36	salicylate acid	VA	180/2	vinyl salicylate	GC/IR/MS
37	phenol	VA	180/2	phenyl vinyl ether	GC/IR/MS
38	2-pyrrolidinone	VA	180/0.5	N-vinyl pyrrolidinone	GC/IR/MS
39	2-pyrrolidinone	VP	160/7 ¹¹	N-vinyl pyrrolidinone	retention
40	ethylene glycol	VA	150/2	2-methyl 1-3-dioxolane	retention
41	2-oxazolidinone	VA	180/1	N-vinyl-2-oxazolidinone	GC/IR/MS
42	ethyleneurea	VA	180/3	N-vinyl ethyleneurea	GC/IR/MS
43	2-hydroxyethylethyleneurea	VA	180/3	2-hydroxyethyl 5-vinyl ethyleneurea 1-(2-acetoxyethyl)-2-vinyloxy-imidazoline 2-acetoxyethyl-5-vinyl ethylene urea	GC/IR/MS
44	2-hydroxyethyl acetate	VA	115/2.5 130/2.5 150/2	2-vinyloxyethyl acetate	GC/IR/MS
45	2-hydroxyethyl pivalate	VP	150/7	2-vinyloxyethyl pivalate	GC/IR/MS
46	1,1,1,3,3,3-hexafluoro-2-propanol	VP		vinyl (1,1,1,3,3,3-hexafluoro-2-propyl) ether	GC/IR/MS

11. 3,000 ppm ruthenium catalyst

Examples 47- 55

Using the procedure for Examples 33 - 46, the vinyl products recited in Examples 47 - 55 were made using 300 ppm of ruthenium added as ruthenium carbonyl. Verification was not or has not yet been accomplished, but G-C product peaks are located at logical retention times for these products.

Ex. No.	Acidic Compound	Vinyl Source	•C/h	Product(s)	Verification Technique
47	2,2-diphenyl acetic acid	VA	150/6	vinyl (2,2-diphenyl acetate)	logical retention
48	2-benzoyl benzoic acid	VA	150/3	vinyl 2-benzoyl benzoate	logical retention
49	Exxon Neo Acid 913 (C ₆ -,C ₇ -,C ₈ -mixed neo acids)	VA	145/3	vinyl pivalate vinyl neo-heptanoate vinyl neo-nonanoate	logical retention
50	1-hexanol	VP	150/4	hexyl vinyl ether	logical retention
51	6-amino-caproic acid	VA	160/4	vinyl (N-acetylaminocaproate)	logical retention
52	6-amino-caproic acid	VP	160/7	vinyl (N-pivoylaminocaproate)	logical retention
53	tri-n-propyl silanol	VP		vinyloxy (tri-n-propyl-silane	logical retention
54	2-hydroxyethyl acrylate	VP		2-vinyloxyethyl acrylate	logical retention
55	trimellitic anhydride	VP		5-isobenzofurancarboxylic acid, 1,3-dihydro-1,3-dioxoethenyl ester	logical retention
56	o-toluenesulfonamide	VP		N-vinyl o-toluene sulfonamide	logical retention

Example 57

To a Fischer-Porter bottle were charged cyclohexanecarboxylic acid (100.0 grams, 0.78 moles), vinyl acetate (134.3 grams, 1.56 moles), and ruthenium carbonyl (0.056 grams). The bottle was sealed, purged

four times with carbon monoxide, and pressurized to 1.7 bar (25 psig). The bottle was placed in a 150 °C oil bath and stirred for 4.5 hours. The resultant solution after cooling to ambient temperature, was concentrated by rotary evaporation. The residue was distilled through a vigreux column giving a fraction (53.2 grams, 54-64 °C/5.7 mbar (4.3 mm Hg)) which was vinyl cyclohexane carboxylate.

Example 58

To a Fischer Porter bottle were charged salicylic acid (13.8 grams, 100 mmoles), vinyl acetate (34.4 grams, 400 mmoles), and ruthenium carbonyl (0.03304 grams). The bottle was sealed, purged four times with carbon monoxide, and pressurized to 1.7 bar (25 psig). The bottle was placed in an oil bath and stirred for 2 hours at a 130 °C to 140 °C. The resultant solution, after cooling to ambient temperature, was concentrated by rotary evaporation. The residue was distilled through a vigreux column giving a fraction (3.81 grams, 60-74 °C/1.33 mbar - 1.0 mm Hg -) which was vinyl salicylate.

Example 59

To a Fischer-Porter bottle were charged trans-cinnamic acid (148 grams, 1 mole), vinyl acetate (172 grams, 2 moles), and ruthenium carbonyl (0.201 grams). The bottle was sealed, purged three times with carbon monoxide and pressurized to 1.7 bar (25 psig). The bottle was placed in an oil bath and stirred for 3 hours at 145 °C. The resultant solution, after cooling to ambient temperature, was concentrated by rotary evaporation. The residue was distilled through a vigreux column giving a fraction (57 grams 112-130 °C/1.33 mbar - 1.0 mm Hg -) which was vinyl cinnamate.

Example 60

A mixture consisting of propionic acid (12.2 grams), vinyl acetate (17.2 grams), distilled water (0.5011 grams), nonane internal standard (0.864 grams) and ruthenium carbonyl (0.211 grams, a calculated 3,340 ppm Ru concentration) was charged to a Fischer-Porter reaction vessel, purged and pressurized to 1.7 bar (25 psig) with nitrogen, and heated to 130 °C for 15 h. Analysis of the cooled reaction mixture by gas chromatography indicated that the following product composition was present:

vinyl acetate	9.893 grams
acetic acid	5.032 grams
vinyl propionate	7.398 grams
propionic acid	7.488 grams

Example 61

A mixture consisting of propionic acid (12.2 grams), vinyl acetate (17.2 grams,) nonane internal standard (0.8395 grams), and ruthenium carbonyl (0.021 grams, a calculated 334 ppm Ru concentration) was charged to a Fischer-Porter reaction vessel, purged and pressurized to 1.7 bar (25 psig) with nitrogen, and heated to 150 °C for 2 h. Analysis of the reaction mixture by gas chromatography indicated that the following product composition was present.

vinyl acetate	9.759 grams
acetic acid	2.811 grams
vinyl propionate	8.232 grams
propionic acid	5.897 grams

Example 62

The transvinylation of a crude vinyl acetate waste stream from an industrial plant which is contaminated with ethyl acetate, vinyl propionate, and approximately 2% water was used to convert the contained vinyl acetate into vinyl propionate. The crude "wet" vinyl acetate (5.0 grams), propionic acid (25.0 grams),

nonane standard (0.4225 grams) and ruthenium carbonyl (0.019 grams, 300 ppm Ru) were charged to a Fischer-Porter bottle, purged and pressurized to 1.7 bar (25 psig) carbon monoxide and heated 3 h at 160 °C and sampled. The following products are tabulated:

vinyl acetate	1.227 grams
acetic acid	0.654 grams
vinyl propionate	1.684 grams

Example 63

In this example, the vinyl acetate of Example 62 was azeotropically dried prior to use. The crude vinyl acetate was dried by azeotropic refluxing on a Dean-Stark apparatus for several hours. The "anhydrous" crude vinyl acetate (5.0 grams), propionic acid (25.0 grams), nonane standard (0.4398 grams) and ruthenium carbonyl (0.019 grams, 300 ppm Ru) were charged to a Fischer-Porter bottle, purged and pressurized to 1.7 bar (25 psig) carbon monoxide and heated 3 h at 140 °C and sample. The following products are tabulated

vinyl acetate	1.290 grams
acetic acid	0.468 grams
vinyl propionate	3.249 grams

Claims

1. A process for the transvinylation of a vinyl derivative of a Bronsted acid with a different Bronsted acid which comprises providing a liquid phase mixture containing said vinyl derivative and said Bronsted acid in the presence of a catalyst at elevated temperature and recovering the vinyl derivative of the different Bronsted acid characterized in that the catalyst is a ruthenium compound.
2. The process of claim 1 wherein the ruthenium compound is soluble in the liquid mixture.
3. The process of claim 1 or 2 wherein the vinyl derivative is a vinyl ester of a carboxylic acid.
4. The process of claim 3 wherein a product of transvinylation is a vinyl ester of a carboxylic acid.
5. The process of claim 3 or 4 wherein the vinyl ester of a carboxylic acid is vinyl acetate, pivalate, benzoate, vinyl acrylate, vinyl methacrylate or hydroxyalkyl carboxylate.
6. The process of claims 1 to 5 wherein the liquid phase mixture is substantially water-free or essentially anhydrous.
7. The process of claim 6 wherein the amount of water in the reaction is less than about 25 weight % of the weight of the mixture, preferably is less than about 15 weight % of the weight of the mixture, especially less than about 10 weight % of the weight of the mixture.
8. The process of claims 1 to 7 wherein the Bronsted acid is a nitrogen containing compound.
9. The process of claim 8 wherein the nitrogen containing compound is an amino containing compound.
10. The process of claims 1 to 9 wherein the process is carried out in the presence of carbon monoxide.
11. The process of claims 1 to 10 wherein the process is carried out at a temperature of up to 300 °C preferably up to 200 °C.

nonane standard (0.4225 grams) and ruthenium carbonyl (0.019 grams, 300 ppm Ru) were charged to a Fischer-Porter bottle, purged and pressurized to 1.7 bar (25 psig) carbon monoxide and heated 3 h at 160°C and sampled. The following products are tabulated:

vinyl acetate	1.227 grams
acetic acid	0.654 grams
vinyl propionate	1.684 grams

Example 63

In this example, the vinyl acetate of Example 62 was azeotropically dried prior to use. The crude vinyl acetate was dried by azeotropic refluxing on a Dean-Stark apparatus for several hours. The "anhydrous" crude vinyl acetate (5.0 grams), propionic acid (25.0 grams), nonane standard (0.4398 grams) and ruthenium carbonyl (0.019 grams, 300 ppm Ru) were charged to a Fischer-Porter bottle, purged and pressurized to 1.7 bar (25 psig) carbon monoxide and heated 3 h at 140°C and sample. The following products are tabulated

vinyl acetate	1.290 grams
acetic acid	0.468 grams
vinyl propionate	3.249 grams

Claims

1. A process for the transvinylation of a vinyl derivative of a Bronsted acid with a different Bronsted acid which comprises providing a liquid phase mixture containing said vinyl derivative and said Bronsted acid in the presence of a catalyst at elevated temperature and recovering the vinyl derivative of the different Bronsted acid characterized in that the catalyst is a ruthenium compound.
2. The process of claim 1 wherein the ruthenium compound is soluble in the liquid mixture.
3. The process of claim 1 or 2 wherein the vinyl derivative is a vinyl ester of a carboxylic acid.
4. The process of claim 3 wherein a product of transvinylation is a vinyl ester of a carboxylic acid.
5. The process of claim 3 or 4 wherein the vinyl ester of a carboxylic acid is vinyl acetate, pivalate, benzoate, vinyl acrylate, vinyl methacrylate or hydroxyalkyl carboxylate.
6. The process of claims 1 to 5 wherein the liquid phase mixture is substantially water-free or essentially anhydrous.
7. The process of claim 6 wherein the amount of water in the reaction is less than about 25 weight % of the weight of the mixture, preferably is less than about 15 weight % of the weight of the mixture, especially less than about 10 weight % of the weight of the mixture.
8. The process of claims 1 to 7 wherein the Bronsted acid is a nitrogen containing compound.
9. The process of claim 8 wherein the nitrogen containing compound is an amino containing compound.
10. The process of claims 1 to 9 wherein the process is carried out in the presence of carbon monoxide.
11. The process of claims 1 to 10 wherein the process is carried out at a temperature of up to 300°C preferably up to 200°C.



12. The process of claims 1 to 11 wherein the pressure of the reaction is subatmospheric, atmospheric or superatmospheric.
13. The process of claim 12 wherein the reaction pressure is from $1.33 \cdot 10^{-5}$ mbar to 345 bar abs., preferably from $1.33 \cdot 10^{-4}$ mbar to 55 bar abs., especially from $1.33 \cdot 10^{-3}$ mbar to 38 bar abs.
14. The process of claim 1 wherein the mole ratio of the Brønsted acid to ruthenium is at least 0.5/1, preferably 50/1 to 1,000,000/1.
15. The process of claim 1 wherein the ruthenium catalyst concentration is from 30,000 to 0.5 ppm based on the weight of the liquid phase reaction mixture.
16. The process of claims 1 to 15 wherein there is present a solvent non-reactant for at least one of the reactants.
17. The reaction of claim 12 wherein the pressure ranges from 1.1 to 345 bar abs.
18. The process of claim 4 wherein the product of transvinilation is divinyl adipate, -isophthalate, -terephthalate, vinylpropionate, -stearate, -salicylate, -cinnamate, -2-ethylhexanoate, -cyclohexanoate, N-vinylpyrrolidinone, -succinimide, vinyl-phenyl ether, N-vinyl-2-oxazolidinone, -ethyleneurea, 2-vinyloxyethyl acetate, 2-vinyloxyethyl acrylate, 2-vinyloxyethyl methacrylate, 2-vinyloxyethyl pivalate, vinyl palmitate, 2-hydroxyethyl-5-vinyl ethylene-urea, 1-(2-acetoxyethyl)-2-vinyloxy-imidazoline, 2-acetoxyethyl-5-vinyl ethylene urea, vinyl-(1,1,1,3,3,3-hexafluoro-2-propyl)ether, vinyl-(2,2-di-phenyl acetate), vinyl-2-benzoyl benzoate, vinyl-neo-heptanoate, vinyl-neo-nonanoate, hexyl vinyl ether, vinyl-(N-acetylamino-caproate), vinyl-(n-pivoylamino-caproate), vinyloxy-(tri-n-propyl)silane, 5-isobenzofuran-carboxylic acid, 1,3-dihydro-1,3-dioxo-ethylen ester or N-vinyl-o-toluene sulfonamide.

Patentansprüche

1. Verfahren für die Transvinilierung eines Vinylderivats einer Brønsted-Säure mit einer anderen Brønsted-Säure, das die Bereitstellung einer Flüssigphasenmischung, die das Vinylderivat und die Brønsted-Säure enthält, in Gegenwart eines Katalysators bei erhöhter Temperatur und die Wiedergewinnung des Vinylderivats der anderen Brønsted-Säure umfaßt, dadurch gekennzeichnet, daß der Katalysator eine Ruthenium-Verbindung ist.
2. Verfahren nach Anspruch 1, worin die Ruthenium-Verbindung in der flüssigen Mischung löslich ist.
3. Verfahren nach Anspruch 1 oder 2, worin das Vinylderivat ein Vinylester einer Carbonsäure ist.
4. Verfahren nach Anspruch 3, worin ein Produkt der Transvinilierung ein Vinylester einer Carbonsäure ist.
5. Verfahren nach Anspruch 3 oder 4, worin der Vinylester einer Carbonsäure Vinylacetat, -pivalat, -benzoat, Vinylacrylat, Vinylmethacrylat oder -hydroxyalkylcarboxylat ist.
6. Verfahren nach Anspruch 1 bis 5, worin die Flüssigphasenmischung im wesentlichen wasserfrei oder im wesentlichen entwässert ist.
7. Verfahren nach Anspruch 6, worin die Wassermenge in der Reaktion weniger als etwa 25 Gew.-% des Gewichts der Mischung, vorzugsweise weniger als etwa 15 Gew.-% des Gewichts der Mischung und insbesondere weniger als etwa 10 Gew.-% des Gewichts der Mischung beträgt.
8. Verfahren nach Anspruch 1 bis 7, worin die Brønsted-Säure eine Stickstoff enthaltende Verbindung ist.
9. Verfahren nach Anspruch 8, worin die Stickstoff enthaltende Verbindung eine eine Aminogruppe enthaltende Verbindung ist.



10. Verfahren nach Anspruch 1 bis 9, worin das Verfahren in Gegenwart von Kohlenmonoxid durchgeführt wird.

11. Verfahren nach Anspruch 1 bis 10, worin das Verfahren bei einer Temperatur von bis zu 300 °C, vorzugsweise bis zu 200 °C, durchgeführt wird.

12. Verfahren nach Anspruch 1 bis 11, worin der Druck der Reaktion kleiner, gleich oder größer als der Atmosphärendruck ist.

13. Verfahren nach Anspruch 12, worin der Reaktionsdruck von $1,33 \cdot 10^{-5}$ mbar bis 345 bar abs. beträgt, vorzugsweise von $1,33 \cdot 10^{-4}$ mbar bis 55 bar abs., insbesondere von $1,33 \cdot 10^{-3}$ mbar bis 38 bar abs.

14. Verfahren nach Anspruch 1, worin das Molverhältnis der Brönsted-Säure zu Ruthenium mindestens 0,5/1, vorzugsweise 50/1 bis 1 000 000/1 beträgt.

15. Verfahren nach Anspruch 1, worin die Konzentration des Ruthenium-Katalysators von 30 000 bis 0,5 ppm beträgt, bezogen auf das Gewicht der Flüssigphasenreaktionsmischung.

16. Verfahren nach Anspruch 1 bis 15, worin ein reaktionsunfähiges Lösungsmittel für mindestens einen der Reaktanten anwesend ist.

17. Reaktion nach Anspruch 12, worin der Druck zwischen 1,1 bis 345 bar abs. liegt.

18. Verfahren nach Anspruch 4, worin das Produkt der Transvinylierung Divinyladipat, -isophthalat, -terephthalat, Vinylpropionat, -stearat, -salicylat, -cinnamat, -2-ethylhexanoat, -cyclohexanoat, N-Vinylpyrrolidinon, -succinimid, Vinylphenylether, N-Vinyl-2-oxazolidinon, -ethylenharnstoff 2-Vinyloxyethylacetat, 2-Vinyloxyethylacrylat, 2-Vinyloxyethylmethacrylat, 2-Vinyloxyethylpivalat, Vinylpalmitat, 2-Hydroxyethyl-5-vinylethylenharnstoff 1-(2-acetoxyethyl)-2-vinyloxyimidazolin, 2-Acetoxyethyl-5-vinylethylenharnstoff, Vinyl-(1,1,1,3,3,3-hexafluor-2-propyl)ether, Vinyl-(2,2-diphenylacetat), Vinyl-2-benzoylbenzoat, Vinyl-neoheptanoat, Vinyl-neo-nonanoat, Hexylvinylether, Vinyl-(N-acerylaminocaproat), Vinyl-(n-pivoylaminocaproat), Vinyloxy-(tri-n-propyl)silan, 5-iso-Benzofurancarbonsäure, 1,3-Dihydro-1,3-dioxoethylenester oder N-Vinyl-o-toluolsulfonamid ist.

Revendications

1. Procédé pour la transvinylation d'un dérivé vinylique d'un acide de Bronsted avec un acide de Bronsted différent, qui comprend la formation d'un mélange en phase liquide contenant ledit dérivé vinylique et ledit acide de Bronsted en présence d'un catalyseur à température élevée et la séparation du dérivé vinylique de l'acide de Bronsted différent, caractérisé en ce que le catalyseur est un composé de ruthénium.

2. Procédé suivant la revendication 1, dans lequel le composé de ruthénium est soluble dans le mélange liquide.

3. Procédé suivant la revendication 1 ou 2, dans lequel le dérivé vinylique est un ester vinylique d'un acide carboxylique.

4. Procédé suivant la revendication 3, dans lequel le produit de transvinylation est un ester vinylique d'un acide carboxylique.

5. Procédé suivant la revendication 3 ou 4, dans lequel l'ester vinylique d'un acide carboxylique est l'acétate de vinyle, le pivalate de vinyle, le benzoate de vinyle, l'acrylate de vinyle, le méthacrylate de vinyle ou un hydroxyalkylcarboxylate de vinyle.

6. Procédé suivant les revendications 1 à 5, dans lequel le mélange en phase liquide est pratiquement dépourvu d'eau ou essentiellement anhydre.



7. Procédé suivant la revendication 6, dans lequel la quantité d'eau dans le mélange réactionnel est inférieure à environ 25 % en poids du poids du mélange, de préférence inférieure à environ 15 % en poids du poids du mélange, notamment inférieure à environ 10 % en poids du poids du mélange.

8. Procédé suivant les revendications 1 à 7, dans lequel l'acide de Bronsted est un composé contenant de l'azote.

9. Procédé suivant la revendication 8, dans lequel le composé contenant de l'azote est un composé à fonction amino.

10. Procédé suivant les revendications 1 à 9, qui est mis en oeuvre en présence d'oxyde de carbone.

11. Procédé suivant les revendications 1 à 10, qui est mis en oeuvre à une température allant jusqu'à 300 °C, de préférence jusqu'à 200 °C.

12. Procédé suivant les revendications 1 à 11, dans lequel la pression de réaction est inférieure à la pression atmosphérique, égale à la pression atmosphérique ou supérieure à la pression atmosphérique.

13. Procédé suivant la revendication 12, dans lequel la pression absolue de réaction va de $1,33 \cdot 10^{-5}$ mbar à 345 bars, de préférence de $1,33 \cdot 10^{-4}$ mbar à 55 bars, notamment de $1,33 \cdot 10^{-3}$ mbar à 38 bars.

14. Procédé suivant la revendication 1, dans lequel le rapport molaire de l'acide de Bronsted au ruthénium est au moins égal à 0,5/1, de préférence de 50/1 à 1 000 000/1.

15. Procédé suivant la revendication 1, dans lequel la concentration du catalyseur au ruthénium va de 30 000 à 0,5 ppm sur la base du poids du mélange réactionnel en phase liquide.

16. Procédé suivant les revendications 1 à 15, dans lequel est présent un solvant non-réactionnel pour au moins un des corps réactionnels.

17. Réaction suivant la revendication 12, dans laquelle la pression absolue est comprise dans l'intervalle de 1,1 à 345 bars.

18. Procédé suivant la revendication 4, dans lequel le produit de transvinylation est l'adipate de divinyle, l'isophthalate de divinyle, le téréphthalate de divinyle, le propionate de vinyle, le stéarate de vinyle, le salicylate de vinyle, le cinnamate de vinyle, le 2-éthylhexanoate de vinyle, le cyclohexanoate de vinyle, la N-vinylpyrrolidinone, le N-vinylsuccinimide, l'éther de vinyle et de phényle, la N-vinyl-2-oxazolidinone, la N-vinyléthylène-urée, l'acétate de 2-vinyloxyéthyle, l'acrylate de 2-vinyloxyéthyle, le méthacrylate de 2-vinyloxyéthyle, le pivalate de 2-vinyloxyéthyle, le palmitate de vinyle, la 2-hydroxyéthyl-5-vinyléthylène-urée, la 1-(2-acétoxyéthyl)-2-vinyloxy-imidazoline, la 2-acétoxyéthyl-5-vinyl-éthylène-urée, l'éther de vinyle et de (1,1,1,3,3,3-hexafluoro-2-propyle), le vinyl-(acétate de 2,2-diphényl), le 2-benzoylbenzoate de vinyle, le néo-heptanoate de vinyle, le néo-nonanoate de vinyle, l'éther d'hexyle et de vinyle, le N-acéthylaminocaproate de vinyle, le n-pivoylaminocaproate de vinyle, le vinyloxy-tri-n-propylsilane, l'ester de 1,3-dihydro-1,3-dioxo-éthényl d'acide 5-isobenzofuranne-carboxylique ou le N-vinyl-o-toluène-sulfamide.

