INHALATION DEVICE

The present invention relates to a device for inhalation of a pharmaceutically active substance comprising means for generating a negative pressure or vacuum and to a method by which any suitable substance may be prepared in a dispersed state.

Inhalable pharmaceutically active substances are generally used for the treatment of diseases in the bronchial and pulmonary area, such as asthma and chronic bronchitis. Various types of inhalation devices or apparatus are used for this purpose.

One type of inhalation device is the breath-actuated inhaler, particularly but not necessarily a dry powder inhaler, containing multiple doses of a medicament containing an active substance. The inhaler has a manoeuvring means comprising a manoeuvring element for loading one dose of the medicament to a dosing unit and providing said dose in a position for inhalation. An inhaler of the prescribed type is described in EP-A-0 069 715 and EP-A-0 237 507.

The function of this type of known device depends on the creation of an airflow through the inhalation device resulting from inhalation by the patient. The airflow causes the active substance to be moved from a release position in a dosing unit into the airflow in which it is dispersed. A break down of aggregated particles must also be achieved during inhalation, because aggregates always occur in powders having fine particles, especially finely divided powders of the type generally used for inhalation. A particularly advantageous inhaler of the above mentioned type is the dry-powder, breath-actuated, multi dose inhaler Turbuhaler®, generally described in the above mentioned EP-patents.

Some patients such as small children and elderly people with diseases in the bronchial area are not able to use breath-actuated inhalers as it can be hard or even impossible for these patients to achieve the necessary inhalation flow. Airflow needed is about 30 - 60 l/min and many patients such as small children and elderly people are not capable of producing the

necessary inhalation flow. These patients have to use inhalers with pressurised gas, i.e. freon (CFC). Such inhalers suffer from many known disadvantages, such as unwanted side effects both for the environment and the patients.

In order to facilitate the inhalation of pharmaceutically active substances which are administered by the use of pressurised metered dose inhalers, so called pMDI:s, it is known to provide dispersion chambers having a considerable volume, e.g. up to 2000 ml, into which the substance, with the pressurised gas, is dispersed. These devices are generally called "spacers" and a typical spacer is known from GB 1 565 029.

Inhalation devices including dispersion chambers have also been developed for breath-actuated, dry-powder inhalers of the above mentioned type. Such an inhalation device is described in EP-A-0 548 152. This device comprises a reservoir for the active substance (this can be part of a dry powder inhaler arranged inside the inhalation device) and a dispersion chamber. The dispersion chamber has a movable wall part which varies the volume of the dispersion chamber between minimum and maximum volumes so as to draw active substance into the dispersion chamber from the dry powder inhaler. The movement of the movable part is achieved by the movement of a piston which when lowered creates a negative pressure within the dispersion chamber. The active substance is thereby drawn out into the chamber. A patient may then inhale the dispersed substance in the dispersion chamber through a face mask or mouth piece. This device is complicated and difficult to use. Furthermore, contact with powder and the design of several mechanical parts make the function of the device less reliable.

It is therefore an object of the present invention to provide an inhalation device including a dispersion chamber which can be used by patients having reduced ability and which can create the air flow necessary to lift a dose from a release position into an inhalation channel, disperse it in the air flow and achieve the required break up of aggregated particles when using a breath-actuated inhaler. Preferably, the device should be simple and reliable to activate for inhalation and to use. The device should preferably be light, robust and

attractive to take with you, since patients, for example asthma sufferers, always have to have their devices available.

According to the present invention, there is provided an inhalation device for use with an inhaler, the inhaler being for providing a dose of a substance for inhalation, the device having:

a section for receiving the inhaler;

a dispersion chamber in fluid connection with said section; and

a suction chamber of variable internal volume and in fluid connection with said dispersion chamber; wherein

by increasing the internal volume of said suction chamber, a negative pressure is produced in said dispersion chamber, thereby drawing substance from the inhaler into the dispersion chamber for subsequent inhalation.

According to the present invention, there is also provided an inhalation device having:

an inhaler for providing a dose of a substance for inhalation;

a dispersion chamber in fluid connection with said inhaler; and

a suction chamber of variable internal volume and in fluid connection with said dispersion chamber; wherein

by increasing the internal volume of said suction chamber, a negative pressure is produced in said dispersion chamber, thereby drawing substance from the inhaler into the dispersion chamber for subsequent inhalation.

The significance of this is that the substance for inhalation does not come into contact with any parts of the suction chamber creating the negative pressure. Furthermore, the dispersion chamber may have fixed simple internal surfaces which minimize retention of substance. Preferably, the suction chamber displaces a smaller volume than the volume of the dispersion chamber and is connected to the dispersion chamber substantially at an opposite end to the connection with the inhaler. In this way, dispersed substance drawn into the dispersion chamber does not reach the connection to the suction chamber.

Further preferred features are described in the appended claims 3 to 16.

Thus, there may be provided an inhalation device which facilitates the use of especially a Turbuhaler® for patients presently having to use pressurised metered-dose inhalers.

The device according to the invention may be especially designed for patients who are not capable of using a breath actuated inhaler of the above mentioned type for the reason that they are not capable of creating the inhalation flow necessary to release and lift the dose of the substance into the inhalation channel and to the lungs.

It is also an object of the present invention to provide a method of preparing a substance in a dispersed state.

According to the present invention, there is also provided a method of preparing a substance in a dispersed state in a dispersion chamber by drawing the substance into the dispersion chamber from a dispenser, wherein a suction chamber of variable internal volume is provided in fluid connection with the dispersion chamber and the method includes the steps of:

increasing the internal volume of the suction chamber so as to produce a negative pressure in said dispersion chamber to thereby draw said substance from the dispenser into the dispersion chamber.

As mentioned above, inhalation devices, including those with expandable dispersion chambers, can include moveable parts which allow a substance to be sucked into a dispersion chamber. Of course, these parts may be operated manually with the force for filling the dispersion chamber being provided directly by the user. However, this force is preferably provided by a sprung device such that the user merely has to release the tension in the device. Unfortunately, however, due to the very nature of elasticity, the force provided by a spring decreases as the spring expands. Thus the gas flow into the dispersion chamber is much higher for the first part of the filling of the chamber. This is particularly

undesirable when the gas flow is used to pick up the substance from an inhaler, for instance to pick up dry powder and disperse it in the gas.

According to the present invention, there is provide an inhalation device comprising:

a dispersion chamber for containing a substance dispersed in a gas;

a sprung device for creating a change in pressure so as to cause said dispersed substance to flow into said dispersion chamber; and

a flow regulating valve of variable restriction for restricting said flow of said dispersed substance into said dispersion chamber; wherein

the restriction of said flow regulating valve is arranged to vary in conjunction with operation of said sprung device so as to compensate for characteristics of the sprung device.

In order to restrict or regulate the flow, the valve may be located anywhere in the fluid path, i.e. in the inlet or outlet of the dispersion chamber or upstream or downstream thereof.

The position, construction and characteristics of the valve should be chosen according to the type of inhalation device, the characteristics of the sprung device and the substance. In general though, a sprung device will tend to create a much higher flow into the dispersion chamber during the first part of the its operation than during its last part. Therefore, the flow regulating valve should be designed to compensate for this and offer the most restriction during the first part of the operation of the sprung device. For instance, where the sprung device includes a piston moveable from a first to a second position, the restriction should decrease as the piston moves from the first to the second position.

In any device with a dispersion chamber, including those of the prior art using an expandable dispersion chamber, some of the dispersed substance can fall out of its suspended state in the gas and collect on internal surfaces of the dispersion chamber. If the user then tips the device, the collected substance, which might be powder or liquid, can be poured out of the dispersion chamber outlet and, if fitted, a mouthpiece. This is undesirable.

According to the present invention, there is provided an inhalation device for providing a substance dispersed in a gas for inhalation, the device comprising:

walls defining a dispersion chamber for containing said dispersed substance and defining an outlet in said dispersion chamber through which said dispersed substance may leave said dispersion chamber in a dispersed state; wherein

said walls also define at least one channelled region at least partly surrounding said outlet such that any substance on said walls cannot be caused to travel across the walls defining said channelled region and to pass through said outlet.

The channelled region may be provided as an inwardly extending funnel or cone or merely as an inwardly extending pipe. The important aspect is that, if the user turns the device upside down, any substance which has collected on the sides will travel along the walls and into the channelled region rather than out through the outlet. Since the outlet is positioned inwardly of the general periphery of the chamber, substance cannot be poured out of it.

The inhalation device according to the present invention will now be described by way of example with reference to the accompanying drawing, in which:

Fig. 1 is a side view of an inhalation device when the device is retracted and closed in its inactive position,

Fig. 2 shows the first step of the activation of the device,

Fig. 3 shows the inhalation device of fig. 1 in position for inhalation,

Fig. 4 shows schematically the flow of the air when the substance is released and dispersed in the dispersion chamber just after the device has been activated for inhalation,

Fig. 5 shows a device with a preferred mouthpiece valve,

Figs. 6 a-c show components of a mouthpiece valve,

Figs. 7 a-f show various flow regulating valves,

Fig. 8a is a view along lines IV-IV in fig. 1 in the first step of activation of the device corresponding to fig. 2,

Fig. 8b is a view along lines IV-IV in fig. 1 in the position where the spacer has been activated and the dose released corresponding to fig. 3,

Fig. 9 shows a gear linkage for the mounting element of the device,

Fig. 10 shows a device with an insert to prevent collected powder falling out,

Fig. 11a and 11b show variations of the insert of Fig. 10.

The inhalation device comprises a housing 1 containing a first chamber 2, in which a suction chamber of variable volume is formed, and a second chamber 3, the dispersion chamber, having a constant volume. In the preferred embodiment the chambers are cylindrical but any other form is possible. The two chambers 2 and 3 are arranged axially and telescopically movable in relation to each other and a fluid connection is provided between the two chambers.

The second, or dispersion, chamber 3 is provided with a lid 31 covering its upper part. The lid 31 may be a separate component or formed integrally with the chamber 3. Said lid 31 is provided with a mouth piece 32 intended to be inserted into the mouth of the user when the device is to be used. The mouthpiece is preferably detachable from the lid 31 for instance by means of a bayonet fitting. In this way, it may be removed for cleaning.

Inside the lid, an inhalation channel 33 is arranged between and in fluid connection with the dispersion chamber 3 and the mouth piece 32. When the device is to be used, said mouth piece is moved between a retracted position as can be seen in fig. 1 and 2 and an active position as can be seen in fig. 3 and 4. If an infant is to use the inhalation device a face mask of any known kind can be mounted on the mouth piece or the mouth piece can be exchanged for such a face mask.

A one way valve 5 is provided in said inhalation channel 33. When the device is used and the user inhales through the mouth piece 32, the valve opens in order to let the inhalation air enter through the mouth piece into the mouth of the user. When the user exhales, the valve 5 closes in order to prevent exhalation air to enter into the channel and the dispersion chamber 3. In the preferred embodiment, the one way valve 5 is a so called flap valve, but any other type of valve could be used, such as a torpedo or ball valve.

Fig. 5 shows a device with a preferred mouthpiece valve and Fig. 6a to 6c illustrate the components of a similar valve. The valve comprises an insert 51 having a valve seat 52, an aperture 53 and a bearing 54. The valve flap 55 shown in Figs 6b and 6c comprises a shaft 56 for insertion into bearing 54 such that the flap may freely rotate. When the insert 51 is fitted in the mouthpiece, the wall of the mouthpiece closes bearing 54.

Inside the housing 1, means 6 are provided for mounting and activating an inhaler 7 which may be an internal part of or detachably mounted in the housing 1. In the preferred embodiment, the inhaler is of the type sold under the trademark Turbuhaler® and is mounted in a chamber provided adjacent chamber 2. The inhaler 7 comprises a reservoir for the substance to be inhaled, a dosing unit provided in the inhalation channel of the inhaler, manoeuvring means 71 for feeding a dose of the substance to the dosing unit and to place it in position for inhalation in the inhalation channel and a mouth piece 72. Although the inhaler is a Turbuhaler® in the preferred embodiment any other inhaler of this or similar types could be placed in a device according to the invention.

The manoeuvring means 71 of the inhaler 7 is mounted in a mounting and activating means 6 of the inhalation device in a manner which will be described in more detail below.

When mounted in the housing 1, the mouth piece 72 of the inhaler 7 is connected to the dispersion chamber 3 via the first end of a substantially L-shaped channel 8. When the device is ready for inhalation, the other end of the channel 8 is arranged to be in fluid connection with the dispersion chamber 3 via an opening 34 provided in the wall 37 of the dispersion chamber 3. A seal 81 is arranged close to the end of the channel 8. When the device is in its retracted position, the opening 34 is located remote from the L-shaped channel 8 and a fluid tight seal is established between the inhaler and the dispersion chamber 3.

Many pharmaceutically active substances are hydroscopical. They are sensitive to humidity and must be kept in an environment with a stable humidity. In order to avoid moisture entering into the inhaler the chamber in which the inhaler is arranged is sealed against environmental air in an air tight manner. This sealing is broken when the device is activated for inhalation, i.e. when the dispersion chamber 3 is turned to the active position. When in the active position, an opening in the wall adjacent the first chamber 2 is opened and an air inlet 75 is created. When inhalation has been completed and the dispersion chamber is turned and lowered into its retracted position, the opening or air inlet is closed again and the air tight sealing is achieved again.

As mentioned above, the first chamber 2 and the dispersion chamber 3 are movable and telescopically arranged in relation to each other. Guiding elements are preferably provided which guide the movement of the chambers in relation to each other. These guiding elements can be provided as a pin on the surface of one of the chambers and a corresponding groove provided on the surface of the wall of the other chamber. The function of the guiding means will be further described below in relation to the function of the device.

The dispersion chamber 3 is arranged inside the first chamber 2 so that the bottom wall 35 of the dispersion chamber defines the top wall of the first chamber. A piston 4 is arranged inside the first chamber 2. The piston 4 is movable between a retracted first position and a released second position as can be seen in fig. 2 and 3 respectively. The piston 4, the wall 35 and the sides of the first chamber 2, together define a suction chamber. The volume of the suction chamber is varied by the movement of the piston. The piston 4 is provided with a seal 41 providing a fluid tight seal against the walls of the first chamber during most of the movement of the piston. Between the bottom wall 35 of the dispersion chamber and the piston 4 biasing means 43 are provided which force the piston to its released second position when the piston is released from its retracted first position. The biasing means is preferably a spring. Lugs 42 are provided on the piston latching into grooves 21 provided on the bottom of the dispersion chamber 3 thereby holding the piston against the biasing force of the spring and locking it in its first position.

In order to achieve the optimum flow profile for the air and/or gas drawn through the inhaler where the flow rate increases in a controlled way to a maximum rate about 60 l/min, an air/gas flow regulating device 9 is arranged in the dispersion chamber 3. This compensates for the characteristics of the sprung device, i.e. the piston 4 and biasing means 43, described above.

The air regulating device is preferably constructed as a flow regulating valve 9 and is attached to the piston 4. The flow regulating valve 9 is formed as a needle valve having a stand pipe 91 and a cone shaped needle 92 arranged inside the stand pipe 91. The stand pipe is mounted in the bottom wall 35 of the dispersion chamber 3 and protrudes upwardly inside the dispersion chamber 3. A one way valve 93 is arranged at the upper part of the stand pipe allowing fluid, i.e. air or even gas, to enter into the stand pipe and down into the variable volume of the suction chamber.

The cone shaped needle 92 is provided on the piston 4 and protrudes upwardly into the stand pipe 91. In the retracted first position of the piston 4, the needle 92 is provided inside

the stand pipe along its whole length. When the piston is released from its retracted position and moves downwardly so as to increase the volume of the suction chamber, the needle will move with the piston and out of the stand pipe. The needle restricts the cross section of the stand pipe and thereby restricts the valve clearance in the stand pipe. The air flow down through the stand pipe is thus most restricted at the point of release of the piston, but this restriction will decrease as the needle moves downwardly out of the stand pipe and into the first chamber. In order to make the most optimal use of the inhaler arranged inside the device, the air flow during the suction of air through the device should be the same every time the device is used. This can be achieved by the arrangement of the stand pipe and the needle. With the described construction, the speed, force and air flow profile of the air flow through the device is optimised. The shape and length of the needle 92 has been determined out of the object to achieve said optimised inhalation air flow.

Fig 7a illustrates a partial cross section through the standpipe 91 and shows the conical shape of needle 92. Of course, any other form with any other cross section could also be used as long as the requirement of flow restriction is achieved. Other possible valve arrangements are illustrated in Figs 7b to 7f. Figs 7b and 7c show variations on the embodiments of Fig 7a. Fig 7d shows a valve with a variable cross section standpipe. Figs 7e and 7f illustrate a valve having a hollow needle and a series of apertures down the side of the standpipe. For this latter embodiment, to avoid dispersed substance being drawn into the standpipe, the device of Figs. 1 to 4 should preferably be modified to move the dispersion chamber inlet away from the series of apertures. These and other suitable regulating valves can be used with other dispersion chambers such as described above in conjunction with EP-A-0548152.

The mounting and activating means 6 mentioned above comprises a shaft, having a square or rectangular cross section 11, mounted in the bottom wall of the housing 1 and protruding into the first and dispersion chambers 2, 3 through holes 44 and 36 arranged in the piston and the bottom wall 35 of the dispersion chamber respectively.

According to one embodiment, a lever 61 is connected to the shaft 11 at its lower end. As illustrated in Figures 8a and 8b, at least one, preferably two, further levers 62a, 62b are connected to the first lever 61 at their first ends. The second ends of these further levers 62a, 62b are connected to a mounting element 63 in which the manoeuvring means 71 of the inhaler 7 is arranged. The further levers are connected to the mounting element 63 in such a manner that movement of the levers 62a and 62b will cause the mounting element 63 to turn, whereby the manoeuvring means 71 of the inhaler will also be turned. The turning movement of the manoeuvring means 71 corresponds to the required movement of the means for feeding a dose into the inhalation channel of the inhaler. The length and form of the further levers is determined by the required turning movement of the manoeuvring means 71.

An alternative embodiment is illustrated in Figure 9. In this embodiment a gear 261 is connected to the shaft 11 at its lower end. The gear 261 is then connected via an intermediate gear 262 to a mounting gear 263 which is attached to an integral part of mounting element 63.

The function of the device will now be described.

Initially the inhalation device is in the position shown in fig. 1 with the dispersion chamber 3 retracted into the first chamber 2 and with the mouth piece 32 placed in its retracted position. When the user is to inhale, the dispersion chamber is raised in relation to the first chamber 2 as shown in fig. 1. Thereafter, the mouth piece 32 is turned by an angle of about 90° from its inactive to its active position. In the preferred embodiment, the mouth piece 32 is mounted to or formed as a part of the lid 31 and the lid 31 which is rigidly connected to or formed as a part of the upper part of the dispersion chamber 3. The movement of the mouth piece 32 will release the locking means of the piston 4 from its first locked position.

In the preferred embodiment, the dispersion chamber 3 is rotated by about 90° in a plane parallel to the horizontal as illustrated in the Figures, but the angle can be made less or more

than 90° simply by modifying the arrangement of the lever arms or the number of gear teeth in the mounting and activating means 6. This is because the turning movement of the manoeuvring means 71 to feed a dose to its release position determines the required movement of the mounting element 63. The mounting element 63 is turned by the movement of the lever arms 61, 62a and 62b or the gears 261, 262, 263 when the device is activated, i.e. when the dispersing chamber 3 and the mouth piece 32 are turned.

When the lid 31 and the mouth piece 32 are turned to activate the inhalation device, the movement of the dispersion chamber 3 and the piston 4 is transferred to the first lever 61 or gear 261 via the shaft 11. The first lever 61 turns and transfers this movement to the further levers 62a and 62b or the gear 261 transfers this movement to gears 262, 263 which then turn the mounting element 63 and the manoeuvring means 71 of the inhaler 7.

As described above the mounting and activating means 6 for the inhaler is arranged in such manner that the manoeuvring means 71 of the inhaler 7 is turned when the mouth piece 32 is turned to its active position. In this way a dose of the substance to be inhaled will be fed from the reservoir of the inhaler into the dosing unit and positioned for inhalation in the inhalation channel of the inhaler.

In the initial retracted position, the lugs 42 of the piston 4 are latched into the locked position in the bottom wall 35 of the dispersion chamber. When the dispersion chamber is moved in relation to the first chamber, the piston 4 will follow the dispersion chamber upwardly until an end position is reached. When the end position has been reached, the mouth piece is turned and the arrangement of the guiding means between the two chambers will unlock the lugs 42 such that the piston 4 is released. Due to the biasing forces of the spring 43, the piston is forced downwardly away from wall 35 inside the first chamber increasing instantly the volume of the suction chamber. A negative pressure or vacuum is thus created in the suction chamber. Through the stand pipe 91, air is drawn from the dispersion chamber down into the suction chamber and a negative pressure or vacuum is created in the dispersion chamber. As mentioned above, air inlets 75 are arranged in the

bottom wall of the housing 1. These air inlets are formed to guide air/gas in to the chamber in which the inhaler is housed. Due to a seal 73 provided around the inhaler, the only path for the air is through the inhalation channel of the inhaler. A dose of the powder has already been placed in the inhalation channel during the activation of the device. This dose will be lifted out of its position, mixed with the air in the air flow and will travel with the air flow up through the mouth piece 72 of the inhaler via the L-shaped connection means 8 into the dispersion chamber through the opening 34.

The stand pipe 9 is constructed in such a manner that the volume of air passing down to the suction chamber is less then the air volume of the dispersion chamber before air is entered from the inhaler. In this manner the amount of aerosolised substance which enters into the stand pipe is minimised.

As illustrated in Fig 10, in order to further improve the device, an insert 100 can be provided in said dispersion chamber 3 in order to provide a channelled region and to prevent powder particles which have collected on the bottom of the dispersion chamber from falling out of the dispersion chamber into the inhalation channel 33 of the lid or into the mouth piece 32. Preferably, the insert 100 has a funnel-form and is placed with its tip directed downwardly towards the bottom 35 of the dispersion chamber 3. However, any form producing a channelled region around the outlet 102 will have an equivalent effect, such as a curved cross section as illustrated in Fig 11a and a ridge as illustrated in Fig 11b. These channelled regions may be used with other dispersion chambers such as described above in conjunction with EP-A-0548152.

Possible modifications

The inhalation device according to the invention as described above could of course be modified within the scope of the appended claims.

Thus, although in the preferred embodiment, the mouth piece and the dispersing chamber are turned through an angle of about 90° when the device is activated for inhalation, by a

modification of the guiding means, the angle of rotation can be changed to any other desirable angle.

Although a breath-actuated dry-powder inhaler has been described above, any other inhaler could be used where a dose of a substance to be inhaled is placed in an inhalation channel for inhalation and in which air or gas is drawn through the inhalation channel in order to mix the dose with the inhalation flow and to transport it to a patient.

The device has been described for use with air drawn from the environment around the device. However, if necessary or required, a gas source could easily be connected to the air inlet of the device and gas could be drawn into the device instead of or together with outside ambient air.

It is also possible to modify the device so that the air contained in the chamber 2 under the piston 4 is used to equalize the negative pressure or vacuum created in the inhaler during the drawing of air from the inhaler into the dispersing chamber 3. In this case, air from the chamber 2 will be drawn through air inlets close to the inhaler and will pass through the inhaler in the same manner as described above. An advantage of this arrangement is that the increased pressure created in the air volume beneath the piston provides an extra force to release and transport the dose and the air up through the inhaler and further into the dispersion chamber.

In the described embodiment, the mounting and activating means consists of a lever mechanism comprising lever arms or a gear drive. However, other activating mechanisms for the manoeuvring means of the inhaler could be used, such as different types of drive mechanisms, e.g. drive belts and similar.

CLAIMS

1. An inhalation device for use with an inhaler, the inhaler being for providing a dose of a substance for inhalation, the device having:

a section for receiving the inhaler;

a dispersion chamber in fluid connection with said section; and

a suction chamber of variable internal volume and in fluid connection with said dispersion chamber; wherein

by increasing the internal volume of said suction chamber, a negative pressure is produced in said dispersion chamber, thereby drawing substance from the inhaler into the dispersion chamber for subsequent inhalation.

2. An inhalation device having:

an inhaler for providing a dose of a substance for inhalation;

a dispersion chamber in fluid connection with said inhaler; and

a suction chamber of variable internal volume and in fluid connection with said dispersion chamber; wherein

by increasing the internal volume of said suction chamber, a negative pressure is produced in said dispersion chamber, thereby drawing substance from the inhaler into the dispersion chamber for subsequent inhalation.

3. An inhalation device according to claim 1 or 2 having a first chamber and a piston movable within said first chamber, wherein said suction chamber is defined by said first chamber and said piston.

4. An inhalation device according to claim 3 wherein the dispersion chamber is mounted telescopically within said first chamber and is movable between a retracted position within said first chamber and an extended position.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

5. An inhalation device according to claim 4 wherein said dispersion chamber has a wall dividing it from said first chamber, said piston being releasably connected adjacent said wall and movable with said dispersion chamber when connected.

6. An inhalation device according to claim 5 having a releasing mechanism for releasing the connection with said piston and a biasing member for biasing said piston away from said wall wherein when said dispersion chamber is moved from the retracted position to the extended position, the piston moves with the dispersion chamber until the dispersion chamber reaches the extended position, whereupon the releasing mechanism operates to release the connection with the piston, such that the piston is biased away from the wall and the internal volume of said suction chamber is increased.

7. An inhalation device according to any preceding claim having an element for controlling the fluid flow from said dispersion chamber to said suction chamber.

8. An inhalation device according to claim 7, wherein said element is formed as a fluid regulating valve.

9. An inhalation device according to claim 7 or 8, wherein said element is formed as a stand pipe and a cone shaped restriction element on said piston protruding into the inside of said stand pipe, thereby regulating the fluid flow through the stand pipe when the piston moves from its first to its second position.

10. An inhalation device according to any preceding claim, wherein the inhaler includes a manoeuvring element for feeding a dose of the substance to an inhalation channel of the inhaler, the device further including a mounting and activating means comprising a mounting element for mounting the manoeuvring element and a lever arrangement being in movable connection with the mounting element wherein said lever arrangement is connected to the first and dispersion chambers.

This Sheet Has Been Replaced

THIS SHEET WAS BEEN REPLACED

11. An inhalation device according to claim 10, having a shaft which is connected to the lever arrangement and which is mounted on a bottom wall of said dispersion chamber and said piston, whereby a movement of the dispersion and first chambers in relation to the inhaler is transferred to the manoeuvring element via said shaft and said lever arrangement.

12. An inhalation device according to any one of claims 1 to 9 wherein the inhaler includes a manoeuvring element for feeding a dose of the substance to an inhalation channel of the inhaler, the device further including a mounting and activating means comprising a gear arrangement in moveable correction with the mounting element wherein said gear arrangement is connected to the first and dispersion chambers.

13. An inhalation device according to any preceding claim, having an insert provided in said dispersion chamber, said insert being funnel-shaped and provided with its tip directed away from an inhalation outlet of the dispersion chamber.

14. An inhalation device according to any preceding claim, wherein the substance is a pharmaceutically active substance.

15. An inhalation device according to any preceding claim, wherein the inhaler is a dry-powder inhaler.

16. An inhalation device according to any of the preceding claims, wherein the inhaler is a Turbuhaler®.

17. A method of preparing a substance in a dispersed state in a dispersion chamber by drawing the substance into the dispersion chamber from a dispenser, wherein a suction chamber of variable internal volume is provided in fluid connection with the dispersion chamber and the method includes the steps of:

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

increasing the internal volume of the suction chamber so as to produce a negative pressure in said dispersion chamber to thereby draw said substance from the dispenser into the dispersion chamber.

18. An inhalation device comprising:

a dispersion chamber for containing a substance dispersed in a gas;

a sprung device for creating a change in pressure so as to cause said dispersed substance to flow into said dispersion chamber; and

a flow regulating valve of variable restriction for restricting said flow of said dispersed substance into said dispersion chamber; wherein

the restriction of said flow regulating valve is arranged to vary in conjunction with operation of said sprung device so as to compensate for characteristics of the sprung device.

19. An inhalation device according to claim 18 wherein;

said flow regulating valve is located at an outlet of said dispersion chamber.

20. An inhalation device according to claim 18 or 19 wherein

during a single use of the sprung device, the force provided by the sprung device decreases and the restriction provided by said flow regulating valve is arranged to decrease simultaneously.

21. An inhalation device according to claim 18, 19 or 20 wherein the sprung device comprises a moveable piston and a spring for moving said piston.

22. An inhalation device according to any one of claims 18 to 21 wherein the flow regulating valve comprises an elongate pipe and an axially moveable member within said pipe, the relative cross sections of the pipe and the member being such that as the member is moved out of the pipe, the smallest cross sectional area between the pipe and the member increases in area.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

23. A method of preparing a substance in a dispersed state in a dispersion chamber by using a sprung device for creating a change in pressure so as to cause said dispersed substance to flow into said dispersion chamber, the method comprising;

varying a restriction offered to the flow into the dispersion chamber in conjunction with operation of said sprung device so as to compensate for characteristics of the sprung device.

24. An inhalation device for providing a substance dispersed in a gas for inhalation, the device comprising:

walls defining a dispersion chamber for containing said dispersed substance and defining an outlet in said dispersion chamber through which said dispersed substance may leave said dispersion chamber in a dispersed state; wherein

said walls also define at least one channelled region at least partly surrounding said outlet such that any substance on said walls cannot be caused to travel across the walls defining said channelled region and to pass through said outlet.

25. An inhalation device according to claim 24 wherein said walls defining said channelled region comprise a substantially conical section protruding inwardly of the dispersion chamber, said outlet being formed at the apex of said conical section.

26. A method of preparing a substance in a dispersed state in a dispersion chamber and of preventing the substance leaving an outlet of the dispersion chamber when not in a dispersed state, the method comprising:

providing walls in said dispersion chamber which define at least one channelled region at least partly surrounding said outlet.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

Fig.1.



31
33
5
32
93
91
81
8
1
3
9
11
37
92
72
34
7
35
36
2
43
44
73
73
42
71
21
IV
IV
4
6
61
63

Fig.2.




Fig.3.




Fig.4.




Fig.5.




Fig.6a.




Fig.6b.



Fig.6c.




Fig.7a.




Fig.7b.




Fig.7c.




Fig.7d.




Fig.7e.




Fig.7f.




Fig.8a.




Fig.8b.




Fig.9.




Fig.11a.




Fig.11b.





Fig.10.



CLAIMS

1. An inhalation device for use with an inhaler, the inhaler being for providing a dose of a substance for inhalation, the device having:

a section for receiving the inhaler;

a dispersion chamber in fluid connection with said section; and

a suction chamber of variable internal volume and in fluid connection with said dispersion chamber; wherein

by increasing the internal volume of said suction chamber, a negative pressure is produced in said dispersion chamber, thereby drawing substance from the inhaler into the dispersion chamber for subsequent inhalation.

2. An inhalation device having:

an inhaler for providing a dose of a substance for inhalation;

a dispersion chamber in fluid connection with said inhaler; and

a suction chamber of variable internal volume and in fluid connection with said dispersion chamber; wherein

by increasing the internal volume of said suction chamber, a negative pressure is produced in said dispersion chamber, thereby drawing substance from the inhaler into the dispersion chamber for subsequent inhalation.

3. An inhalation device according to claim 1 or 2 having a first chamber and a piston movable within said first chamber, wherein said suction chamber is defined by said first chamber and said piston.

4. An inhalation device according to claim 3 wherein the dispersion chamber is mounted telescopically within said first chamber and is movable between a retracted position within said first chamber and an extended position.

REPLACEMENT SHEET

27 MAR 1999

REPLACEMENT SHEETS SG
☐ Description : paged .... to paged .....
☑ Claim(s) : paged 16 to paged 19
☐ Drawing(s) : paged ..... to paged .....
☐ Abstract : paged ..... to paged .....
DATE OF RECEIPT 27/3/99

5. An inhalation device according to claim 4 wherein said dispersion chamber has a wall dividing it from said first chamber, said piston being releasably connected adjacent said wall and movable with said dispersion chamber when connected.

6. An inhalation device according to claim 5 having a releasing mechanism for releasing the connection with said piston and a biasing member for biasing said piston away from said wall wherein when said dispersion chamber is moved from the retracted position to the extended position, the piston moves with the dispersion chamber until the dispersion chamber reaches the extended position, whereupon the releasing mechanism operates to release the connection with the piston, such that the piston is biased away from the wall and the internal volume of said suction chamber is increased.

7. An inhalation device according to any preceding claim having an element for controlling the fluid flow from said dispersion chamber to said suction chamber.

8. An inhalation device according to claim 7, wherein said element is formed as a fluid regulating valve.

9. An inhalation device according to claim 7 or 8, wherein said element is formed as a stand pipe and a cone shaped restriction element on said piston protruding into the inside of said stand pipe, thereby regulating the fluid flow through the stand pipe when the piston moves from its first to its second position.

10. An inhalation device according to any preceding claim, wherein the inhaler includes a manoeuvring element for feeding a dose of the substance to an inhalation channel of the inhaler, the device further including a mounting and activating means comprising a mounting element for mounting the manoeuvring element and a lever arrangement being in movable connection with the mounting element wherein said lever arrangement is connected to the first and dispersion chambers.

REPLACEMENT SHEET

27 MAR 1999

11. An inhalation device according to claim 10, having a shaft which is connected to the lever arrangement and which is mounted on a bottom wall of said dispersion chamber and said piston, whereby a movement of the dispersion and first chambers in relation to the inhaler is transferred to the manoeuvring element via said shaft and said lever arrangement.

12. An inhalation device according to any one of claims 1 to 9 wherein the inhaler includes a manoeuvring element for feeding a dose of the substance to an inhalation channel of the inhaler, the device further including a mounting and activating means comprising a gear arrangement in moveable correction with the mounting element wherein said gear arrangement is connected to the first and dispersion chambers.

13. An inhalation device according to any preceding claim, having an insert provided in said dispersion chamber, said insert being funnel-shaped and provided with its tip directed away from an inhalation outlet of the dispersion chamber.

14. An inhalation device according to any preceding claim, wherein the substance is a pharmaceutically active substance.

15. An inhalation device according to any preceding claim, wherein the inhaler is a dry-powder inhaler.

16. An inhalation device according to any of the preceding claims, wherein the inhaler is a Turbuhaler®.

17. A method of preparing a substance in a dispersed state in a dispersion chamber by drawing the substance into the dispersion chamber from a dispenser, wherein a suction chamber of variable internal volume is provided in fluid connection with the dispersion chamber and the method includes the steps of:

REPLACEMENT SHEET

27 MAR 1999

REPLACEMENT SHEET

increasing the internal volume of the suction chamber so as to produce a negative pressure in said dispersion chamber to thereby draw said substance from the dispenser into the dispersion chamber.

REPLACEMENT SHEET

27 MAR 1999

9802236-1

IPOS copy

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61M 15/00 — A1

(11) International Publication Number: WO 97/11732

(43) International Publication Date: 3 April 1997 (03.04.97)

(21) International Application Number: PCT/SE96/01184

(22) International Filing Date: 23 September 1996 (23.09.96)

(30) Priority Data:
9503344-5 27 September 1995 (27.09.95) SE

(71) Applicant *(for all designated States except US)*: ASTRA AKTIEBOLAG [SE/SE]; S-151 85 Södertälje (SE).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: BERG, Elna [SE/SE]; Dalby nr 10, S-240 10 Dalby (SE). JEPPSSON, Magnus [SE/SE]; Holmgången 2, S-224 75 Lund (SE). MACANDREW, John, A. [GB/GB]; 10 Kings Road, St. Neots, Cambridgeshire PE19 1LD (GB). REVELL, William, J. [GB/GB]; Clover Cottage, Clare Road, Stoke by Clare, Sudbury, Suffolk CO10 2HJ (GB). ROBERTSON, Paul, A. [GB/GB]; 5 Engleric, Chrishall, Herts SG8 8QZ (GB).

(74) Agent: ASTRA AKTIEBOLAG; Patent Dept., S-151 85 Södertälje (SE).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: INHALATION DEVICE

(57) Abstract

An inhalation device for inhalation of a pharmaceutically active substance comprising means for generating a negative pressure or vacuum and means for housing an inhaler within said device, said device comprising a constant volume and a variable volume in fluid connection with each other, said negative pressure or vacuum being generated in the constant volume through the variation of the volume in the variable volume whereby the substance is moved from said inhaler and dispersed in said constant volume, a flow regulating valve for regulating the flow of substance to the constant volume and a channelled region surrounding an outlet in said contant volume to prevent substance leaving said outlet when not in a dispersed state.

