

04 JUN 2023

**COLLISION AVOIDANCE SYSTEM****BACKGROUND OF THE INVENTION****5 Field of the Invention**

The present invention relates generally to the field of avionics for collision avoidance systems (CAS). More specifically, the present invention relates generally to displays for use with airborne traffic alert and collision avoidance systems and transponders in formation flight.

10 Background of the Invention

Spurred by the collision of two airliners over the Grand Canyon in 1956, the airlines initiated a study of collision avoidance concepts. By the late 1980's, a system for airborne collision avoidance was developed with the cooperation of the airlines, the aviation industry, and the Federal Aviation Administration (FAA). The system, referred to
15 as Traffic Alert and Collision Avoidance System II (TCAS II) was mandated by Congress to be installed on most commercial aircraft by the early 1990's. A chronology of the development of airborne collision avoidance systems can be found in "Introduction to TCAS II," printed by the Federal Aviation Administration of the U.S. Department of Transportation, March 1990.

20 The development of an effective airborne CAS has been the goal of the aviation community for many years. Airborne collision avoidance systems provide protection from collisions with other aircraft and are independent of ground based air traffic control. As is well appreciated in the aviation industry, avoiding such collisions with other aircraft is a very important endeavor. Furthermore, collision avoidance is a problem for both military
25 and commercial aircraft alike. In addition, a large, simultaneous number of TCAS interrogations from close-in formation aircraft members generate significant radio frequency (RF) interference and could potentially degrade the effectiveness of maintaining precise position/separation criteria with respect to other aircraft and obstacles. Therefore, an additional collision avoidance mode for use in close formation flight with other aircraft
30 is highly desirable.

In addition the problems described above, it is desirable that aircraft, specifically

-1-

SUBSTITUTE SHEET

G00002

military aircraft, perform precision airdrops, rendezvous, air refueling, and air-land missions at night and in all weather conditions, including Instrument Meteorological Conditions (IMC) with a low probability of detection. Also, it is desirable that these aircraft be allowed to fly in formations including as few as 3 through as many as 250 aircraft to maintain formation position and separation at selectable ranges from 500 ft (ft; where 1 ft = 0.304 m) to 100 nautical miles (nm; where 1 nm = 1.85 km) at all Instrument Flight Rules (IFR) altitudes. Also, the CAS system is to be compatible (primarily because of cost issues) with current station keeping equipment (SKE) systems or they will not be able to fly IMC formation with SKE-equipped aircraft.

Referring to FIG. 1, there is shown a block diagram of a conventional TCAS system 100, comprising a TCAS interrogator subsystem 110 and a Mode-Select (Mode-S) transponder subsystem 160. The TCAS interrogator 110 comprises a TCAS directional antenna 111, a TCAS omni-directional antenna 112, and TCAS computer unit 120, which further includes receiver 121, transmitter 122, and processor 123. Also shown in FIG. 1 are aural annunciator 113, traffic advisory (TA) display 114, and resolution advisory (RA) displays 115. The Mode-S transponder 160 comprises a receiver-transmitter 161, a control panel 162, and transponder antennas 163 and 164. The TCAS interrogator 110 and Mode-S transponder 160 operate together to function as a collision avoidance system. Those skilled in the art understand that this is merely illustrative of a conventional TCAS.

In a TCAS system, both the interrogator 110 and transponder 160 are airborne and provide a means for communication between aircraft. The interrogator 110 initiates such communication by transmitting a query, for example at 1030 MHz. The transponder responds to the query by transmitting a reply, for example at 1060 MHz, which is received and processed by the interrogator. The reply received by the interrogator consists of a series of information pulses that may identify the aircraft, or contain altitude or other information. The reply can be a pulse position modulated (PPM) signal containing data formatted in either in an Air Traffic Control Radar Beacon System (ATCRBS) format or in one of several Mode-S formats.

A TCAS II equipped aircraft can monitor other aircraft within approximately a 20-nm radius of the TCAS II equipped aircraft. When an intruding aircraft is determined to be a threat, the TCAS II system alerts the pilot to the danger and gives the pilot bearing and distance to the intruding aircraft. If the threat is not resolved and a collision or near

H25478

04 JUN 2003 PCT/US99/30459

miss is probable, then the TCAS II system advises the pilot to take evasive action by, for example, climbing or descending to avoid a collision. There are methods known in the prior art for extending the range of TCAS, such as disclosed in Brettner et al, U.S. Patent 5,805,111.

5 Systems in addition to those described above have been developed to provide steering commands for aircraft flying in formation. For example, station-keeping equipment (SKE), used by the U.S. Air Force can support a formation of up to 16 aircraft.

Attempts have been made in the past to provide a TCAS system that is compatible with formation flight. One type of system is provided by Honeywell (former AlliedSignal
10 Aerospace) under the name Enhanced Traffic Alert Collision Avoidance System (ETCAS). The ETCAS provides both a TCAS mode for operation in civilian airspace and a limited formation search mode for military specific missions. The ETCAS formation search mode functions as an aircraft formation member identification and rendezvous system rather than a true intra-formation positioning collision avoidance system.

15 The ETCAS falls short of being a true intra-formation positioning collision avoidance system in several ways. First, once an aircraft joins a formation, the ETCAS does not itself or in conjunction with any other on-board system maintain aircraft position and separation within the formation. The ETCAS is simply a situational awareness tool that designates other intra-formation aircraft by receiving predetermined Mode 3/A codes
20 transmitted from transponders onboard said other intra-formation aircraft. The ETCAS does not interface with other aircraft systems, on board its host aircraft, to compensate for aircraft position errors within the formation. Second, the ETCAS does not provide a display that indicates, for each formation follower aircraft, a relative velocity (range-rate) between that follower aircraft and a formation leader aircraft. Hence, the pilot of a
25 follower aircraft has no relative velocity reference to maintain formation position with the leader aircraft, which is especially critical during turning maneuvers. Third, the ETCAS formation/search mode technique is wholly based upon active TCAS interrogations within the aircraft formation. These transponder interrogations and the resulting Mode-S transponder replies significantly increase radio frequency (RF) reception interference with
30 a large formation of aircraft and could degrade an ability to maintain precise aircraft position and separation within the formation. In addition, an increased composite level of RF severely inhibits a large formation of aircraft from covertly traversing airspace without

H25478

PCT/US99/30459

04 JUN 2003

being detected.

Drouilhet et al, U.S. Patent 5,570,095 discloses an Aircraft Dependent Surveillance -Broadcast (ADS-B) system in which aircraft in a predetermined airspace continuously transmits its own geographical position and altitude. This type of system is suitable for typical aircraft operating in civilian airspace, but is not suitable for aircraft that are flying in formation for the three reasons that follow.

First, it is desirable that the aircraft formation responds to external interrogations, for example TCAS, with a single response. The aircraft formation response represents the entire formation as a very large, for example 1 km^2 , virtual aircraft. A formation leader aircraft will determine the position of the virtual aircraft that represents the entire formation and report this position in response to external interrogations. The reported position will likely be the geometric center of the formation, but could also be some other location as well, for example the actual position of the leader aircraft.

Second, it is further desired that the both the quantity and radio frequency (RF) level of intraformation communication be kept to a minimum. This means that the RF level is attenuated for datalink between members of the formation and that only the formation leader aircraft is permitted to respond to external interrogations.

Third, formation station keeping is the responsibility of the formation leader aircraft. The follower aircraft within the formation display the relative velocity and relative altitude of other formation follower aircraft with respect to the leader aircraft. The leader aircraft can, for example, move other aircraft within a formation by calculating steering commands and incorporating these commands into the relative altitude and velocity values transmitted to each of the follower aircraft. Because the altitude and velocity values can additionally contain a steering component, successful intraformation collision avoidance relies on the cooperative effort of at least three aircraft including the leader aircraft and two follower aircraft that are dependent on the leader to maintain separation therebetween.

There is need for an intraformation collision avoidance system (IFCAS) that meets the formation flight requirements listed above. It would be advantageous if such IFCAS mode could be added as an additional mode to an existing TCAS system.

H25478

04 JUN 2003 PCT/US99/30459

SUMMARY OF THE INVENTION

The following summary of the invention is provided to facilitate an understanding of some of the innovative features unique to the present invention, and is not intended to be a full description. A full appreciation of the various aspects of the invention can only
5 be gained by taking the entire specification, claims, drawings, and abstract as a whole.

The present invention describes a system and method of maintaining aircraft position and safe separation of a large aircraft flying formation, such as those types of military formations to perform a strategic brigade airdrop, although it can be used for any aeronautical service involving the application of aircraft formation flying units. The
10 present invention involves the use of a new display format for use with a passive Traffic Alert and Collision Avoidance System (TCAS) and Mode-S data link transponder to provide distributed intra-formation collision avoidance and control among multiple formation aircraft.

In one embodiment, the present invention comprises a data link Mode-S
15 transponder, which generates and transmits Automatic Dependent Surveillance Broadcast (ADS-B) broadcast data. Such ADS-B broadcast data contains aircraft position information of the host aircraft. The present invention also includes a passive traffic alert and collision avoidance system (TCAS) computer in communication with the Mode-S transponder. The TCAS receives and processes broadcast data from another data link
20 transponder that is located onboard another aircraft (e.g., a follower aircraft within a formation cell) to determine relative aircraft position of the host aircraft with respect to the other aircraft.

In a further embodiment of the present invention, a data link Mode-S transponder is in communication with a TCAS computer. The TCAS computer receives and processes
25 the broadcast data from the transponder. The TCAS computer is also in communication with a flight mission computer, which receives the broadcast data from the TCAS computer and generates steering commands based on the broadcast data. The present invention includes a high-speed digital communication link that is operatively connected to the mission computer, which is used to transmit the steering commands to a
30 transponder-equipped follower aircraft where the steering commands are processed by the follower aircraft. The follower aircraft uses the steering commands to position itself with respect to the formation lead aircraft. This can be accomplished with either station

04 JUN 2003

H25478

PCT/US99/30459

keeping equipment or automatic flight controllers.

The present invention includes the steps of providing a transponder (on one or more aircraft), which generates and transmits ADS-B broadcast data including relative aircraft position, and providing a TCAS computer onboard a lead aircraft. The TCAS is in communication with the transponder and receives and processes ADS-B broadcast data from the transponder. The invention includes the step of (automatically) positioning and separating the follower aircraft with respect to one another while flying in formation based on the broadcast data from the lead aircraft using, for example, automatic flight or station keeping means. The invention further includes a mission computer in communication with the TCAS computer and the steps of: transmitting the broadcast data from the TCAS computer to the mission computer; processing the broadcast data; and selectively transmitting the processed broadcast data between the lead aircraft and the follower aircraft via a high speed data link. The step of processing further includes the step of calculating the follower aircraft range, range rate, relative altitude, altitude rate, and bearing from the broadcast (ADS-B) data received from the Mode-S transponder to determine whether a follower aircraft is in a correct formation position. The step of selectively transmitting is conducted, for example, using a unique flight identifier of the particular aircraft. The method also includes the steps of alerting the pilots of the follower aircraft when a non-formation intruder penetrates a predefined perimeter of aircraft flying in formation and displaying the range rate or relative velocity of each follower aircraft with respect to the formation lead aircraft. The method further includes the step of inhibiting air traffic control radar beacon systems (ATCRBS) messages from being sent by the follower aircraft Mode-S transponder.

The present invention is capable of supporting a flight formation of 250 aircraft through distributed control of multiple aircraft formation cell units. It uses a passive surveillance technique for maintaining formation aircraft position within 500-ft to 100-nm of one another at all Instrument Flight Rules (IFR) altitudes. Updated follower aircraft position information is broadcast periodically (e.g., 2 times per second). These follower aircraft periodic Mode-S transponder transmissions of ADS-B information are sent to and received by the TCAS of the formation lead aircraft. This extended ADS-B data transmission is also referred to herein as Global Positioning System (GPS) or Mode-S squitter. Formation aircraft positions, relative altitude and velocity of each follower

H25478

04 JUN 2003

PCT/US99/30459

aircraft with respect to the lead aircraft are presented on the Vertical Speed Indicator/Traffic Resolution Advisory (VSI/TRA) display (e.g., cathode ray tube or flat panel display) and processed in the aircraft mission computer's intra-formation positioning collision avoidance system (IFPCAS) data fusion center. The mission computer receives
5 data from the TCAS computer, processes the data to obtain, for example, range and range rate, and then the mission computer places the data in a format usable by external equipment such as the station keeping equipment. Steering commands are generated and disseminated to the various or individual formation aircraft. The steering commands are executed using on-board station keeping equipment (which can also be used to maintain
10 helicopter positioning) or autopilot means. The passive surveillance intra-formation collision avoidance technique of the present invention significantly reduces the range upon which a large aircraft formation can be detected and the resulting lower RF interference maintains uninterrupted position and separation correction updates.

The present invention overcomes several problems, including, but not limited to:
15 providing a means to position and separate aircraft in an extremely large flight formation (e.g., 100 aircraft) in night/instrument meteorological conditions utilizing ADS-B information and high frequency data links (and accompanying antennas) for disseminating intra-formation steering commands; utilizing the aircraft mission computer as a data fusion center for generating steering commands based upon assimilated ADS-B information
20 received from the TCAS; and reducing the amount of RF interference resulting from multiple simultaneous TCAS interrogations and Mode-S transponder replies. The present invention maintains safe separation between 2 to 100 aircraft, and up to 250 aircraft, in night and Instrument Meteorological Conditions (IMC). The present invention enables aircraft position/separation at selectable ranges from 500 ft to 100 nm at all Instrument
25 Flight Rules (IFR) altitudes.

The novel features of the present invention will become apparent to those of skill in the art upon examination of the following detailed description of the invention or can be learned by practice of the present invention. It should be understood, however, that the detailed description of the invention and the specific examples presented, while indicating
30 certain embodiments of the present invention, are provided for illustration purposes only because various changes and modifications within the spirit and scope of the invention will become apparent to those of skill in the art from the detailed description of the

invention and claims that follow.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying figures, in which like reference numerals refer to identical or functionally-similar elements throughout the separate views and which are incorporated in and form part of the specification, further illustrate the present invention and, together with the detailed description of the invention, serve to explain the principles of the present invention.

FIG. 1 (prior art) is a block diagram of a conventional TCAS system.

FIG. 2 is a diagram of the components of an exemplary aircraft formation.

FIG. 3 is a block diagram of an embodiment of the collision avoidance system for close formation flights in accordance with the present invention.

FIG. 4 is a block diagram of an alternate embodiment of the collision avoidance system for intra-formation positioning flights in accordance with the present invention.

FIG. 5 is a more detailed block diagram of the embodiment of FIG. 4 (the intra-formation collision avoidance system architecture) in accordance with the present invention.

FIG. 6 is an elevation of a TCAS VSI/TRA display with the relative velocity (range rate) of formation aircraft displayed in accordance with the present invention.

FIG. 7 is a flowchart of the methodology used to display information to the viewer in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is designed for use with a passive Collision Avoidance System (CAS). A passive Collision Avoidance System (CAS) is implemented by the present invention to maintain selectable separation between formation cells and follower aircraft within each cell using an integrated control system. The passive CAS is attained by the present invention using centralized control and decentralized execution of multiple aircraft formation cells. The present invention uses TCAS and Global Positioning System

H25478

04 JUN 2003

PCT/US99/30459

(GPS) Squitter data from a Mode-S transponder. The terms GPS squitter, Mode-S squitter, and ADS-B mean the same thing and are used interchangeably throughout the description of the present invention to describe extended data transmission.

Assembling a large number of formation aircraft (e.g., for a massive size military airdrop in IMC and night flying conditions) is a positioning /separation control problem that is implemented by the present invention in two parts:

1) Modification or augmentation of a conventional TCAS, e.g., L3 Communications (previous Honeywell) TCAS-2000 (product no. RT-951), to add an additional IFPCAS mode to permit close formation flight without unnecessary traffic advisories or resolution advisories; and

2) Use of data from a Mode-S transponder to process aircraft position, and an external high frequency (e.g., VHF, UHF) data link (transmitter and receiver), with accompanying antennas, to pass data, such as ADS-B and intra-formation steering commands, between aircraft.

Referring to FIG. 2, there is shown an exemplary aircraft formation with its members heading towards a drop zone 260 for which an Intra-Formation Positioning Collision Avoidance System (IFPCAS) is necessary. Adjacent aircraft flying in close proximity to one another could maintain a safe separation using passive TCAS detection and processing. A large formation (master cell) 200 can be split into smaller cells (210, 220, 230, 240) with a cell leader aircraft (225, 235, 245) responsible for maintaining aircraft separation among cell follower aircraft (212, 213, 222, 223, 232, 233, 242, 243). A cell can be defined as a smaller formation of approximately 2-50 aircraft. A large formation (up to 250 aircraft) 200 may contain many cells within it. A Master Formation Leader (MFL) aircraft 250 is responsible for maintaining separation between the multiple cells (210, 220, 230, 240) that make up the entire formation 200 (the MFL acts as a beacon for the formation followers).

The MFL 250 maintains cell separation using information that is periodically broadcast from each cell leader's transponder, for example, Global Positioning System (GPS) squitter data. The MFL 250 receives the data from each cell leader (225, 235, 245) aircraft. Each cell leader aircraft (225, 235, 245) can be identified by a unique Mode-S 24-bit address. Precise position location of formation cells and other multiple formations

can be accurately tracked using GPS squitter data. MFL 250 fuses the data of all cell positions; such data fusion is accomplished in the MFL's Flight Management System (FMS) IFPCAS data fusion center as shown and discussed with respect to FIG. 5. Individual cell steering commands are transmitted via Mode-S data link to cell leader
5 (225, 235, 245) aircraft as shown and discussed with respect to FIG. 4. Steering commands are directed to individual cell leaders by their unique Mode-S 24-bit address. MFL 250, cell leader aircraft (225, 235, 245), and cell follower aircraft (212, 213, 222, 223, 232, 233, 242, 243) can be identified by their Mode-S 24-bit address and/or Flight Identification that are assigned to each aircraft and transmitted as part of the existing
10 Mode-S message types.

Cell leaders (225, 235, 245) then process steering commands within their own FMS and disseminate steering commands, for example relative altitude and relative velocity values, to follower aircraft within their cell. Individual cell follower aircraft act upon the steering command if they are addressed to do so, for example via a station
15 keeping system digital datalink with the cell leader aircraft. It should be noted that every Mode-S message contains a cyclic redundancy check (24-bit error detection code) to prevent erroneous information from being received by the aircraft.

GPS squitter can also be used in a similar manner to enable multiple formations to inter-fly and maintain position/separation at selectable distances. In the multiple
20 formations scenario a Super Master Formation Leader (SMFL) receives ADS-B information from the MFLs. The SMFL processes the fused data and disseminates steering commands to formation element master leaders to maintain position and separation between multiple formations.

Distributed formation positioning control approach prevents single points of failure
25 and provides the flexibility of passing MFL 250 and cell leader (225, 235, 245) responsibilities to any formation aircraft.

Referring to FIG. 3, there is shown a graphical depiction of the passive surveillance system of the present invention that is used to attain close formation collision avoidance. Passive surveillance as used herein means that close formation collision
30 avoidance can be attained without active TCAS traffic advisory interrogations, as with conventional TCAS. Passive surveillance can be achieved through Mode-S transponder GPS squitter broadcast and subsequent TCAS reception and processing of that data to

display aircraft position.

FIG. 3 illustrates an exemplary embodiment of the present invention. Although only three aircraft systems are illustrated, it should be clear to those skilled in the art that multiple aircraft will have a similar relationship to that shown between the Cell Formation Leader Aircraft 225, Cell Follower Aircraft No. 1 (222) and Cell Follower Aircraft No. 2 (223). The operation of TCAS and each component shown are well known in the art and need not be described in detail. Certain traffic control system transponders, such as the Mode-S transponder, include unique aircraft identifiers so that each message from a target aircraft can be stamped with the identity of the target aircraft. ADS-B messages are broadcast from each Mode-S transponder (360, 361, and 362) at a predetermined interval, e.g., periodically one or two times per second, and contain the aircraft's geographic coordinates (latitude and longitude), magnetic heading, velocity, barometric altitude, and flight identifier, etc., of the respective aircraft. Such ADS-B data set is derived from each aircraft's GPS and Inertial Navigation System (330, 331, and 332), and Flight Management System (FMS) (not shown) via a bus interface, e.g., high-speed ARINC 429-bus interface, and provided to the Mode-S transponder. ADS-B data received by the TCAS-equipped aircraft is processed and displayed in the cockpit to better enable a flight crew to assess potential conflicts. The leader aircraft TCAS 351 is manipulated by software to receive the Mode-S squitter information and compute the positions of target proximity aircraft. Target range, range rate, relative altitude, altitude rate, and bearing are calculated from this ADS-B data received from the Mode-S transponders (360, 362) to determine where an aircraft is relative to the air space of the leader aircraft 225. In a formation, only the lead aircraft 225 is permitted to respond to any ground interrogations because of the radio frequency interference and inability of FAA Air Traffic Control to decipher multiple returns in a very small area. From an accuracy point of view, the present invention uses GPS/INS data that is broadcast by a follower aircraft (222, 223), which permits an exact calculation of position with no more than 10-m error in most cases instead of a relative positional calculation. The relative altitude, altitude rate, range, and relative velocity (range-rate), with respect to formation lead aircraft, are all critical to avoiding a collision in the present invention. Other parameters of the target aircraft are accounted for to derive intent and closure rate.

The TCAS 352 of the follower aircraft No. 2 (223) receives steering data, for

example relative altitude and relative velocity data, from the Mode-S transponder 361 of the leader aircraft 225 through the Mode-S transponder datalink at a predetermined frequency, for example, 1090 MHz. Similarly, the Mode-S transponder 362 of follower aircraft No. 2 (223) transmits ADS-B data to the TCAS 351 of the leader aircraft 225 through its Mode-S transponder datalink. Each TCAS (350, 351, and 352) is in communication with a corresponding Mode-S transponder (360, 361, and 362) through an aircraft data bus, for example an ARINC 429 digital data bus, providing altitude, which is derived, for example from each Air Data Computer (ADC) (340, 341, and 342). ADS-B data, such as latitude, longitude, velocity, intended flight path, are provided, for example, from a Global Navigation Satellite System/Inertial Navigation System (GNSS/INS) (330, 331, and 332) to each TCAS (350, 351, and 352) (through a Flight Management System (FMS), which is not shown) and to each Mode-S transponder (360, 361, and 362).

The IFPCAS display, which is presented, for example to an aircraft pilot, in follower aircraft No. 1 (222) is shown in Figure 6.

The ADS-B messages referenced herein are comprised of five "extended length" squitter messages: (1) Extended squitter airborne position; (2) Extended squitter airborne velocity; (3) Extended squitter surface position; (4) Extended squitter aircraft identification; and (5) Event-driven squitter. For formation flying, the present invention primarily uses message formats (1) and (2) for passive airborne implementations and are discussed in the following paragraphs. Additional information regarding these ADS-B messages can be found in AEEC (Airlines Electronic Engineering Committee) ARINC (Aeronautical Radio, Inc.), Circulation of Draft 2 of Project Paper 718A, "MARK 4 AIR TRAFFIC CONTROL TRANSPONDER (ATCRBS/MODE-S)," Sept. 12, 1997.

The extended squitter airborne position message is emitted only when the aircraft is airborne. The extended squitter airborne position message contains position information derived from the aircraft navigation aids (GPS and INS). The extended squitter for airborne position is transmitted as Mode-S Downlink Format Message 17 (DF 017), which is a format known to those skilled in the art. The message is emitted twice per second at random intervals that are uniformly distributed over the range 0.4 to 0.6 seconds relative to the previous extended squitter airborne position emission.

The extended squitter airborne velocity message is emitted only when the aircraft is airborne. The extended squitter airborne velocity message contains velocity information

04 JUN 2003

H25478

derived from aircraft navigation aids (GPS, INS). The extended squitter airborne velocity message is transmitted as Mode-S Downlink Format Message 17 (DF 017), which is a format known to those skilled in the art. The message is emitted twice per second at random intervals that are uniformly distributed over the range 0.4 to 0.6 seconds relative
5 to the previous extended squitter airborne velocity emission.

It is important to note that the TCAS units (350, 352) installed in the follower aircraft (222, 223) can operate in a passive mode, meaning that they do not actively interrogate other aircraft. Under conventional TCAS operations, the TCAS and Mode-S transponder share resolution advisory information, or sometimes called coordination
10 messages, when the TCAS is operating in the active interrogation mode. According to the present invention, the active interrogation of the TCAS is disabled during the IFCAS mode.

Broadcast Mode-S squitter data is not only important to tight formation collision avoidance, but also important to effectively controlling the relative position of cellular
15 formation units within the larger formation group. The intra-formation positioning system presented herein is based upon a distributed formation cell control scheme that utilizes Mode-S transponder ADS-B squitter, TCAS ADS-B information processing, mission computer target track processing, and the resident aircraft SKE. In this approach, a MFL 250 maintains cell positioning using the ADS-B information that is periodically broadcast
20 from the cell leader aircraft (225, 235, and 245) Mode-S transponder.

Referring to FIG. 4, there is shown an alternate embodiment of the present invention when operating in the IFPCAS mode. A mission computer (410, 411, and 413) and SKE (380, 381, and 383) communicate with a respective TCAS (350, 351, and 353) as has been described earlier with respect to FIG. 3. Suitable SKE include products
25 AN/APN-169C or AN/APN-240 available from Sierra Research, a division of Sierra Technologies Inc., although details of the SKE are not necessary for an understanding of the present invention. A higher level diagram of this system architecture is shown in FIG. 5.

Although only three aircraft are illustrated in FIG. 4, an extremely large formation
30 (e.g., 250 aircraft) consisting of multiple formation units would operate in a similar manner. A passive surveillance approach could be equally effective in enabling multiple formations to inter-fly and maintain formation position/separation at selectable distances

04-01-2001

PCT/US99/30459

04 JUN 2003

P DESCAMD

H25478

PCT/US99/30459

from 500 ft to 100 nm at all IFR altitudes. In this scenario, an MFL 250 will receive Formation Cell Leader ADS-B position information and generate steering commands that will be disseminated in a hierarchical manner as described above.

A Master Formation Leader (see, e.g., MFL of FIG. 2) communicates with a cell leader aircraft. The TCAS 353 provides the mission computer 413 a full set of ADS-B derived track data. The MFL mission computer 413 can select formation cell leaders by that aircraft's unique 24-bit Mode-S address. Cell aircraft position and separation information can be calculated by the MFL mission computer 413 with resultant guidance commands, for example relative velocity and relative altitude, disseminated to the cell formation leaders via a very high frequency (VHF) data link 390. Steering commands are forwarded from the VHF receive suite to the cell leader aircraft mission computer 411. Similarly, the cell leader aircraft mission computer 411 can provide aircraft guidance commands to an associated SKE 381 based on the data received from an associated TCAS 351. The cell follower aircraft can then execute the cell leader aircraft SKE commands, for example pitch, roll and thrust to maintain a desired position within the formation. The system architecture shown in FIG. 5 is illustrated with the IFPCAS Controller, Data Fusion, and Control Laws implemented in the mission computer 410 as software functions. Multi-function Displays (MFD) 550 can be used to display the formation CAS information. The MFD can display both Cell aircraft IFCAS targets as well as conventional TCAS targets.

It is important to note that the selection of formation members can be accomplished using the unique 24-bit Mode-S address that is broadcast at the tail end of each GPS squitter transmission. In addition, a secondary means of member selection can be attained using the Flight ID, which is also transmitted as part of the Mode-S extended length message.

Non-station keeping aircraft formations (e.g., tanker cell formations) can be handled in a similar manner. In fact, TCAS-equipped tankers can utilize Mode-S ADS-B information to rendezvous with specific formation aircraft using the selective 24-bit address or Flight ID transmitted in the Mode-S squitter message. Such non-station keeping aircraft could maintain position and separation within the formation unit by receiving Mode-S squitter ADS-B data from the MFL and/or cell leader aircraft and reconfiguring the aircraft's mission data to comply with the Mode-S squitter ADS-B data.

Similarly, rendezvous aircraft guidance commands could be generated by their mission computers using serviced aircraft's ADS-B track data. This is another example where the unique Mode-S address can be used to selectively track a specific formation member aircraft.

5 Referring to FIG. 5, there is shown an embodiment of the IFPCAS architecture in accordance with the present invention. The aircraft mission computer 410 is comprised of IFPCAS Controller 555 subject to IFPCAS Control Laws 560, FMS 565, Data Fusion 570, and Display Processing 575.

10 The Data Fusion element 570 interfaces with peripheral (digital) datalink equipment to collect data available from the TCAS 350, Mode-S Transponder 360, VHF Data Link Radio 520, SKE 380, and Zone Marker Receiver 510. The data collected is Automatic Dependent Surveillance (ADS) data, Station Keeping Equipment (SKE) data, and Traffic Alert and Collision Avoidance System (TCAS) and Mode-S data. ADS data is received from other aircraft within line of sight range of this aircraft as well as from Air
15 Traffic Control (ATC) ground stations. SKE data is received from other aircraft currently in formation with this aircraft. TCAS/Mode-S data is received from other aircraft within line of sight range of this aircraft as well as from ATC ground stations.

Because this data is obtained from multiple independent sources, it represents different views of the position and state of this aircraft relative to other adjacent aircraft.
20 The total set of data collected will contain duplicate data and possibly some contradictory data. Data fusion algorithms (details are not necessary for understanding the present invention) are used to correlate this total set of data into logical and consistent subsets of information that eliminate duplicate data and resolve contradictory data. Several subsets are involved: a subset for other follower aircraft currently in formation with this follower
25 aircraft; a subset for lead aircraft in adjacent or joining formations; and a subset for aircraft in the line of sight range of this aircraft, but not associated with any formation. Each subset of information will contain identification data, position data, intent data, threat priority data, and intra-formation data for each aircraft.

The IFPCAS Controller 555 interfaces with peripheral datalink equipment to
30 determine their current modes of operations. The IFPCAS Controller 555 element receives crew command inputs and data fusion information to determine which IFPCAS

functions to activate. During intra-formation operations, the IFPCAS Controller 555 responds to crew inputs and activates Control Laws 560 to fly the aircraft in formation using data fusion information. Additionally, the IFPCAS Controller 555 interfaces with the FMS 565 passing it control data for flight plan changes coordinated among other aircraft in the intra-formation. In addition, the IFPCAS Controller 555 responds to crew inputs to enable or minimize RF emissions by sending control data to the Mode-S Transponder 360 and TCAS 350. This will minimize the ability of enemy forces to detect this aircraft in or near war zones during military operations.

The IFPCAS Control Laws 560 are control laws that use the Data Fusion information and IFPCAS Controller 555 inputs to process control law algorithms that compute airspeed, altitude, heading, and throttle targets for the Automatic Flight Control System (AFCS) 530 in a manner apparent to those skilled in the art. Because the control laws of conventional TCAS are known by those skilled in the art, the control laws of the present invention are similarly implemented by those skilled in the art while also accounting for external equipment such as the SKE. The AFCS 530 is a conventional aircraft automatic flight control system that provides flight director, autopilot, and autothrottle control functions. The AFCS 530 receives airspeed, altitude, heading, and throttle targets from the IFPCAS Control Laws element 560 to control this aircraft within the intra-formation. These targets are used to keep the aircraft in formation with other aircraft and to maintain the crew-entered separation distances.

The Control Display Units (CDU) 540 are interfaces used by an operator to input flight parameters into the FMS 565. The FMS 565 is a conventional aircraft flight management system that provides flight plan routes, and lateral and vertical guidance along those routes. The FMS 565 receives control data from the IFPCAS Controller 555 to accomplish coordinated flight plan route changes among all aircraft within the intra-formation.

The Display Processing 575 element is a conventional display processing function that presents information to the flight crew on, for example, MFD 550. The Display Processing 575 element receives display data from the IFPCAS Controller 555 and Data Fusion 570 functions. This data is an integrated set of Cockpit Display of Traffic Information (CDTI) that provides a clear and concise presentation of the adjacent traffic for improved situational awareness.

H25478

Non-formation military and civilian aircraft that are capable of receiving TCAS ADS-B data can see formation aircraft targets on their VSI/TRA 600 (see FIG. 6). Because formation aircraft are not passing resolution advisories, it will be the responsibility of the non-formation aircraft to maneuver out of the way.

6 The TCAS 350 receives and processes the ADS-B information and displays relative aircraft position (range, bearing, and altitude) on the Vertical Speed Indicator/Traffic Resolution Alert (VSI/TRA) display 600. When the TCAS of the present invention is configured for IFPCAS mode, resolution advisories are inhibited because of the close proximity of aircraft within the cell. Of course, the prior art systems teach away
10 from this feature of the present invention because resolution advisory is desired in those other collision avoidance situations.

Zone marker receiver 510 emulates GPS squitter broadcasts from a Mode-S transponder 360, which are key to ensuring precision airdrops. The TCAS 350 could designate the zone marker with unique symbology as described herein. Zone marker
15 receiver 510 updates 100 nm out appear feasible. However, it will be dependent upon the RF transmit power levels that can be tolerated for various mission scenarios.

The L3 Communications TCAS-2000 (e.g., RT-951) and Mode-S Transponder (e.g., XS-950) can meet the unique intra-formation positional requirements described herein with some modifications to the TCAS-2000 unit. These changes will be discussed
20 in the following paragraphs.

A modified or augmented TCAS-2000 is a preferable TCAS (since it is the most recent product) but other TCAS systems can be adapted and used as well in a manner well known to those skilled in the art. The TCAS-2000 is a new Traffic Alert and Collision Avoidance System and is available from L3 Communications, the company that also
25 developed the TCAS II. Standard (i.e., before modification as described herein) TCAS 2000 features include: increased display range to 80 nm to meet Communication, Navigation, Surveillance/Air Traffic Management (CNS/ATM) requirements; variable display ranges (5, 10, 20, 40 and 80 nm); 50 aircraft tracks (24 within five nm); 1200 knots (kt; where 1 kt = 0.5144 m/s) closing speed; 10,000 feet per minute (fpm; where
30 1000 fpm = 5.07 m/s) vertical rate; normal escape maneuvers; enhanced escape maneuvers; escape maneuver coordination; and air/ground data link.

H25478

By way of illustration and not by limitation, an input/output (I/O) card 355 is added (in, for example, an existing spare card slot) in the TCAS-2000 computer in addition to its other components as shown in FIG. 4. This I/O card 355 provides the ADS-B data interface from the TCAS-2000 computer to the aircraft mission computer 410. In addition, the TCAS 350 derives its present position, altitude, and airspeed from GNS/INS. Such information is accommodated using this I/O card 355 to interface with the aircraft's GPS receiver and INS systems (330). The I/O card 355 accommodates an ARINC 429 interface to the GNSS/ INS 330 so the TCAS can establish its own geographical position and airspeed reference. The TCAS receives altitude data from the Mode-S Transponder via a high-speed ARINC 429 data bus. These parameters are necessary in order to precisely calculate exact range, range-rate, bearing and relative altitude of adjacent cell formation aircraft.

A modification to the TCAS-2000 Computer Processing Unit card (not shown) is needed to decrease the average filtered range error from approximately 72 ft to 50 ft. In addition, a modification to the Control Panel is needed to add the IFPCAS Mode-Selection option and to add the 0.5-nm range selection option.

A preferable Mode-S transponder is the L3 Communications Mode-Select (Mode-S) Data Link Transponder (product no. XS-950), which is a "full-feature" system implementing all currently defined Mode-S functions—but with built-in upgradeability for future growth. As will become apparent to those skilled in the art, other Mode-S transponders can be used in the present invention. Current Mode-S transponders are used in conjunction with TCAS and ATCRBS to identify and track aircraft position, including altitude. The Mode-S Data Link Transponder XS-950 product transmits and receives digital messages between aircraft and air traffic control. It meets all requirements for a Mode-S transponder as described in DO-181A, including Change 1. The unit also conforms to ARINC Characteristic 718 with interfaces for current air transport applications. The Mode-S transponder is capable of transmitting and receiving extended length Mode-S digital messages between aircraft and ground systems. The data link provides more efficient, positive, and confirmed communications than is possible with current voice systems.

Modifications to the conventional Mode-S transponder are required by the present invention to inhibit Air Traffic Control Radar Beacon System (ATCRBS) interrogation

replies while in the IFPCAS operational mode. To further reduce RF emission levels, the present invention further comprises an external RF power step attenuator, which requires a change to the TCAS RF board. The Mode-S RF power transmission level is 640 watts peak pulse, 250 watts minimum. An external attenuator controlled from the pilot's station
5 reduces emission levels for close proximity aircraft, contributes to reducing probability of detection, and reduces the chance of adjacent aircraft L-Band receiver desensitization. Only the formation cell leader (e.g., 225 in FIG. 2) will transmit at higher Mode-S squitter power levels to ensure positive formation positional control with the Master Formation Leader (250 in FIG. 2). No modification to the L3 Communications XS-950 Mode-S
10 transponder is required to broadcast GPS Squitter data because it is already Mode-S, ICAO Level 4 capable (i.e., transmits and receives 16-segment extended length (112) bit messages).

In addition to hardware modifications to the commercially-available TCAS 2000 (or other TCAS product), software modifications to it and to the Mode-S ADS-B systems
15 are contemplated for the present invention to reduce the number of unnecessary evasive maneuvers and allow close formation flying. The modifications include, for example, a GPS Squitter capability enhancement to the commercially available L3 Communications Mode-S transponder product no. XS-950. The IFPCAS mode will be added to the existing software. This unique TCAS mode of operation will provide pilot/operator situational
20 awareness when flying in a formation of multiple TCAS-equipped aircraft. Differences between the IFPCAS mode of the present invention and the conventional TCAS operation mode include, but are not limited to: TCAS Interrogation inhibited; VSI/TRA display of intruders with visual/aural indication of when an intruder penetrates a protected volume or meets some closure rate criteria within a protected volume; centered (or some positioning)
25 VSI/TRA display with approximately 0.5 nm selection range (see FIG. 6) appropriate sized range ring (e.g., 500 ft) on VSI/TRA display (see FIG. 6); intruder range quantization of a predetermined distance (e.g., 70 ft) and filtered to provide resolution of a predetermined distance (e.g., 50 ft); additional annunciation of relative velocity and formation member identification (see FIG. 6); shutoff interference limiting logic; changes
30 necessary to interface with a GNSS/INS; new data recorder parameters; and modify Mode-S Transponder software code to inhibit Air Traffic Control Radar Beacon System (ATCRBS) response by follower aircraft (only the MFL will have the transponder enabled). All of these changes are well within the skill of those skilled in the art and their

04 JUN 2003

PCT/US99/30459

H25478

implementation will be apparent to them.

Both TCAS-2000 GPS Squitter data processing and Mode-S extended length message ADS-B data transmission will be implemented as part of TCAS-2000 Change 7 software modification in accordance with the present invention as described above. The existing commercial TCAS-2000 system can be modified to operate in an IFPCAS mode while maintaining the normal TCAS mode of operation. Normal TCAS Traffic Advisory/Resolution Advisory (TA/RA) capability would be inhibited to prevent aircraft interrogations and resolution advisory operation.

Software in the transponder is completed and certified to DO-178B, the FAA requirement for software development and certification. Software updates can be completed on-board the aircraft by means of, for example, an ARINC 615 portable data loader, which has a data loader port located on the front connector. All of the foregoing software modifications are well within the skill of those skilled in the art and their implementation need not be discussed in detail.

Referring to FIG. 6, there is shown a Vertical Speed Indicator/Traffic Resolution Advisory (VSI/TRA) (or Traffic Advisory/Resolution Advisory) display 600 in accordance with the present invention. FIG. 6 illustrates an exemplary VSI/TRA display 600 with formation members (610, 620, 630) identified, such as formation cell aircraft (depicted as airplane icons) and lead formation aircraft (225) (depicted as an airplane icon inside a diamond). The VSI/TRA display can also show different symbology for formation tanker, non-formation aircraft, etc.

As shown in FIG. 6, the TCAS VSI/TRA display of the present invention not only shows the relative altitude 660 of own follower aircraft 630 (depicted as an airplane icon inside the dotted range ring 640) with the formation lead aircraft 225, but annunciates the relative velocity 650 (or range-rate) of own follower aircraft 630 with the formation lead 225. Own aircraft position is represented by the aircraft icon 630 at the bottom of the display headed toward the twelve o'clock position. The number (05) on top of the airplane icon 225 represents the relative velocity 650 of own aircraft 630 in, for example, nm/hr and the number below the formation lead aircraft (e.g., 660 pointing to 01) represents the relative altitude in, for example, thousand ft increments. The positive number 650 above the lead formation aircraft 225 indicates own aircraft is traveling 50 nm/hr faster than the lead aircraft. The positive number 660 below lead aircraft 225

H25478

PCT/US99/30459

indicates own aircraft is 100 ft above the lead aircraft. A negative number 652 indicates that the follower aircraft 620 is traveling at a lower velocity than the formation lead aircraft 225 while a positive number indicates that the follower aircraft 610 is traveling at a higher velocity than the formation lead aircraft 225. Similarly, a negative relative altitude 662 indicates follower aircraft 620 is 100 ft below the lead aircraft 225. This enhancement makes the TCAS a value-added instrument for the pilot flying in tight formation profiles. Relative velocity annunciation will be particularly useful for maintaining aircraft relative position within a formation during turning maneuvers. A conventional TCAS is aware of intruder range and range-rate but today it displays only color warnings when the intruder's relative velocity presents a threat. The TCAS display of the present invention operating in intra-formation mode displays formation cell aircraft relative velocity (650, 652, 654); relative velocity is displayed digitally along with the relative altitude data (660, 662, 664) on the TCAS display 600.

With instantaneous knowledge of the relative speed of each aircraft in a formation, any crew can immediately correct their speed to match the lead aircraft or communicate with an adjacent aircraft if it is flying off formation speed. Once speed is under better control, it becomes possible for all the aircraft in formation to fly coupled to their flight management system, thus ensuring each aircraft flies the same track. The TCAS display 600 of the present invention, which is augmented with relative velocity, should eliminate nearly all of the variation in range, significantly reduce crew workload and enhance safe effective large cell formations in IMC.

The method of the present invention follows the above description of the systems embodiments and is described in the Summary of the Invention section.

Referring to FIG. 7, there is shown a flowchart of the information processing to determine the manner in which information is displayed to the aircraft flight crew on the display 600. In step 704, the process of displaying TCAS formation members is begun. In step 706, the TCAS computer of the lead and follower aircraft receives Mode-S Squitter (ADS-B) message from an intruder to the protected volume. The VSI/TRA display provides pilots situational awareness of formation aircraft position and an audiovisual indication when an intruder penetrates a protected volume or meets some closure rate criteria within a protected volume. Intruder range quantization is filtered to provide resolution of, for example, 50 ft. The VSI/TRA display 600 includes appropriate-sized

H25478

PCT/US99/30459

range ring 640 of approximately 500 ft and centered in step 708, the intruder is identified by its unique 24-bit Mode-S address ID and stored for further processing. In step 710, the TCAS processor accesses a look-up table to determine whether the intruder is a formation member (FMBR) or formation leader (FLDR). In step 712, a decision is made as to whether the intruder is a formation member according to the Mode-S address ID. If the intruder is a FMBR, then certain bits, referred to herein as FMBR bits, in, for example, the ARINC 429 are set in step 714 and a TCAS-to-display data label is assigned. In step 720 the relative altitude, range, range rate, and bearing information are set in the ARINC 429 and a data label assigned. The intruder data label assigned in step 720 is then transmitted to the VSI/TRA display 600 in step 722. The information obtained in step 708 is also provided to step 716, which is a TCAS intruder database that can be arranged by an aircraft's Mode-S address ID. In step 716; the information is updated in the TCAS intruder database, specifically, the range, range rate, relative altitude, altitude rate, and the bearing of the intruder. The outputs of step 716 are provided to step 720.

Referring again to step 712, a decision is made as to whether the intruder is a formation member according to the Mode-S address ID. If the intruder is not a FMBR, then in step 718 the intruder is declared a FLDR. If the intruder is a FLDR, then the FLDR bits are set in the ARINC 429 in step 718 for processing in steps 720 and 722 as discussed earlier.

Although there are numerous advantages realized by the TCAS system described herein, there are two major advantages of using passive surveillance for close formation aircraft separation.

The first major advantage is that the positional accuracy is substantially equivalent to the longitude and latitude positional accuracy associated with the aircraft's GPS navigational source. A relative aircraft bearing within 2° root mean square (RMS) can be attained with the present invention. This is because TCAS calculates individual target cell position based upon ADS-B positional data transmitted from each aircraft. TCAS ADS-B operations enables processing of at least 50 targets. The number of targets displayed to the pilot will be based upon a prioritization scheme of number of aircraft within a specified horizontal range, bearing relative to the host aircraft, and relative altitude. The nominal aircraft target processing and display capability is a formation of 35 TCAS-equipped aircraft. The received TCAS ADS-B data could be transferred to the aircraft's

H25478

mission computer via ARINC 429 data bus interface for further processing and generation of SKE steering commands to maintain aircraft horizontal and vertical separation within the cell. Processed ADS-B information that results in aircraft horizontal and vertical positioning would be directly or indirectly coupled to the autopilot or SKE via the Flight Management Computer (FMC).

The second major advantage is that passive surveillance reduces RF emissions and contributes to minimizing probability of detection. TCAS interrogations are not required to establish the relative position of aircraft squittering ADS-B data. GPS squitter data is emitted at random intervals uniformly distributed over a range, for example, from 0.4 to 0.6 seconds. The L3 Communications XS-950 transponder contains ARINC 429 interfaces reserved for inputting longitude, latitude, airspeed, magnetic heading, intended flight path, and flight number identification. Most of these parameters are provided via Global Positioning System Navigation Satellite System (GNSS) and Flight Management System (FMS). Barometric altitude, however, would be derived by the on-board ADC 340 via the Mode-S transponder interface.

Other variations and modifications of the present invention will be apparent to those of skill in the art, and it is the intent of the appended claims that such variations and modifications be covered. For example, the antenna mounting technique taught in U.S. Pat. No. 5,805,111 could be implemented in the present invention to extend TCAS detection range. The particular values and configurations discussed above can be varied and are cited merely to illustrate a particular embodiment of the present invention and are not intended to limit the scope of the invention. It is contemplated that the use of the present invention can involve components having different characteristics as long as the principle, the display of traffic advisories, resolution advisories, proximate traffic, and other information obtained while using a passive TCAS and Mode-S transponder in communication is followed. The present invention applies to almost any CAS system and is not limited to use by TCAS. It is intended that the scope of the present invention be defined by the claims appended hereto.

CLAIMS

What is claimed is:

1. A close formation collision avoidance system for a host follower aircraft (222), the system comprising a first data link transponder (360), said transponder generating and transmitting broadcast data, the broadcast data comprising aircraft position information of the host follower aircraft; a traffic alert and collision avoidance system (TCAS) (350) in communication with said transponder for receiving and processing the broadcast data from a second data link transponder (360') located onboard a leader aircraft (225) to determine relative aircraft position of the host follower aircraft with respect to the leader aircraft; a display (600) for displaying the broadcast data to an operator of the host follower aircraft, the broadcast data comprising the relative locations of the leader aircraft and a plurality of intra-formation follower aircraft (223); further characterized by:

said display symbolically depicting each of the intra-formation follower aircraft as an icon (610, 620) with adjacent indicia comprising the relative velocity (654, 652) between said intra-formation follower aircraft and said leader aircraft.

2. The system of Claim 1, wherein said data link transponder is a mode-select data link transponder.
3. The system of Claim 1, wherein the broadcast data comprises automatic dependent surveillance broadcast (ADS-B) data.
4. The system of Claim 1, wherein the broadcast data comprises global positioning system (GPS) data.
5. The system of Claim 1, wherein the broadcast data comprises Mode-S squitter data.

- 1 6. The system of Claim 1, wherein said display alerts an operator of the host
2 follower aircraft when an intruder penetrates a predefined perimeter of an aircraft
3 formation comprising the leader aircraft and the plurality of intra-formation
4 follower aircraft.
- 1 7. The system of Claim 1, further having operational modes comprising:
- 2 (a) a first mode wherein TCAS interrogation from the host follower aircraft is
3 enabled; and
- 4 (b) a second mode wherein TCAS interrogation from the host follower aircraft
5 is disabled and wherein RF transmission output from the first data link
6 transponder is attenuated.
- 1 8. An intra-formation position and collision avoidance system for a formation
2 leader aircraft (225), a first follower aircraft (222), and a second follower aircraft
3 (223) wherein the first follower aircraft has equipment comprising a first data link
4 transponder (360) which generates and transmits first broadcast data, said first
5 broadcast data from the first follower aircraft comprising geographic position,
6 heading, velocity, and altitude of the first follower aircraft, a first traffic alert and
7 collision avoidance system (TCAS) (350); the second follower aircraft has
8 equipment comprising a second data link transponder (360'') which generates and
9 transmits second broadcast data, said second broadcast data from the second
10 follower aircraft comprising geographic position, heading, velocity, and altitude of
11 the second follower aircraft; and the leader aircraft has equipment comprising a
12 second traffic alert and collision avoidance system (TCAS) (350') for receiving and
13 processing the first and second broadcast data; further characterized by:
- 14 (a) said leader aircraft including a mission computer for computing steering
15 commands based on the first and second broadcast data to prevent collisions
16 between the first and second follower aircraft;
- 17 (b) said leader aircraft including a third data link transponder (360') for
18 transmitting third broadcast data comprising the steering commands to said first
19 follower aircraft and said second follower aircraft;

- 20 (c) said first follower aircraft including a display (600) for displaying said third
21 broadcast data from the leader aircraft to an operator of the first follower
22 aircraft; and
- 23 (d) said intra-formation position and collision avoidance system further having
24 operational modes comprising:
- 25 (i) a first mode wherein TCAS interrogation is enabled; and
- 26 (ii) a second mode wherein interrogation by the first traffic alert and
27 collision avoidance system is disabled and wherein RF transmission output
28 from the first data link transponder is attenuated.

1 9. The system of claim 8, wherein the first data link transponder is a mode-select
2 data link transponder.

1 10. The system of claim 8, wherein the first broadcast data comprises automatic
2 dependent surveillance broadcast (ADS-B) data.

1 11. The system of claim 8, wherein the first broadcast data comprises global
2 positioning system (GPS) data.

1 12. The system of claim 8, wherein the first broadcast data comprises Mode-S
2 squitter data.

1 13. The system of claim 8, wherein said display alerts an operator of the host
2 follower aircraft when an intruder penetrates a predefined perimeter of an aircraft
3 formation comprising the leader aircraft and the plurality of intra-formation
4 follower aircraft.