

DESCRIPTION
WIND POWER GENERATOR

Technical Field

[0001]

The present invention relates to a wind power generator, and more particularly, to a wind power generator that generates electric power by efficiently utilizing energy of natural wind.

Background Art

[0002]

Conventionally, various types of wind power generators have been proposed and embodied. Among these wind power generators, there has been a wind power generator that includes wind inlets arranged on the side surface of a wind tunnel at four positions at an interval of 90° to rotate a fan by wind introduced into the wind tunnel (see, e.g. Patent Literature 1).

Patent Literature 1: JP 2004-190506 A

Disclosure of the Invention

Problems to be Solved by the Invention

[0003]

However, the above-mentioned fan rotating type wind power generator has problems that it is not possible to efficiently introduce wind around the wind tunnel into the wind tunnel and that the wind introduced into the wind tunnel blows through from

the inside of the wind tunnel to the leeward side. Therefore, the energy of wind has not been effectively used. Further, conventionally, it has been attempted to collect wind by facing a trumpet-shaped opening toward the windward side. However, since the direction of the opening should be adjusted according to the wind direction, a complicated mechanism is required and thus it is difficult to increase in size.

[0004]

An object of the invention is to provide a wind power generator capable of efficiently generating electric power by effectively utilizing the energy of wind even if the wind is weak and regardless of a wind direction and easily increasing in size and power with a simple structure.

Means for Solving the Problems

[0005]

A wind power generator according to an aspect of the invention includes: a wind tunnel formed by a cylindrical member erected on the surface of a foundation in a vertical direction; a plurality of wind-collecting plates that extends from a circumferential wall of the cylindrical member in directions normal to the circumferential wall; a top plate that closes an upper end opening of the cylindrical member and upper end openings of spaces between adjacent wind-collecting plates; a plurality of wind inlets that is formed on the circumferential wall of the cylindrical member to introduce wind collected by the wind-collecting plates into the wind tunnel; back-flow

preventing means arranged at the wind inlets for allowing only the flow of wind blowing from outside of the cylindrical member into inside of the cylindrical member, while regulating the flow of wind blowing from the inside to the outside; a plurality of guide plates arranged between adjacent wind-collecting plates for guiding the wind collected by the wind-collecting plates downward; a turbine that is driven by wind blowing out from one end of the wind tunnel; and a power generator driven by the turbine.

[0006]

Further, it is preferable that the wind power generator according to the aspect of the invention further includes second back-flow preventing means arranged between outer portions of adjacent wind-collecting plates for allowing the flow of wind blowing into spaces between the wind-collecting plates from outside, while regulating the flow of wind blowing from the spaces between the wind-collecting plates to the outside. Furthermore, it is preferable that six of wind-collecting plates are provided on the cylindrical member at regular intervals in a circumferential direction. It is preferable that the wind power generator further includes surplus wind discharging units arranged in the wind tunnel for discharging surplus wind introduced into the wind tunnel. It is preferable that other than the turbine and the power generator, more than one turbine and power generator are provided in a flow direction of wind in one wind tunnel, and a rotary impeller of each of the turbines is configured in such manner that $1/2$ to $1/4$ of the rotary

impeller enters in the wind tunnel.

Effects of the Invention

[0007]

According to the wind power generator of the embodiment of the invention, wind is collected toward the wind tunnel by the plurality of wind-collecting plates, particularly, six wind-collecting plates and a plurality of guide plates. Accordingly, wind blowing in any direction can be introduced into the wind tunnel by the plurality of wind-collecting plates and guide plates positioned on the windward side while the wind is compressed. Further, since the back-flow preventing means are provided at the wind inlets, the wind introduced into the wind tunnel does not blow through to the leeward side. In addition, since the second back-flow preventing means are provided between adjacent wind-collecting plates, it is possible to efficiently introduce the wind, which has been introduced into spaces between the wind-collecting plates, into the wind tunnel. Further, since the surplus wind in the wind tunnel is discharged from the surplus wind discharging units, a large load is not applied to the turbine even during strong wind. Furthermore, since the plurality of turbines and power generators is provided in one wind tunnel in a flow direction of wind and the turbines are arranged in such a manner that about $1/2$ to $1/4$ of a rotary impeller of each of the turbines enters in the wind tunnel, power generation efficiency is improved. Basically, the wind power generator can be formed by erecting

the cylindrical member and the plurality of wind-collecting plates on the surface of a foundation, which is provided on the ground where turbines and power generators are provided, in a vertical direction. Accordingly, it is possible to appropriately set the height of the cylindrical member, the diameter of the wind tunnel, and the width of the wind-collecting plate according to conditions, such as the average wind speed at an installation place and the amount of necessary power to be generated and thus, a wind power generator and a wind power equipment suitable for various conditions at an installation place can be installed.

Brief Description of the Drawings

[0008]

Fig. 1 is a front view of a wind power generator according to an embodiment of the invention;

Fig. 2 is a cross-sectional view of the wind power generator;

Fig. 3 is a longitudinal sectional view of the central portion of the generator;

Fig. 4 is a sectional view taken along a line 4-4 of Fig. 3;

Fig. 5 is a front view of the central portion of the generator;

Fig. 6 is a longitudinal sectional view of an example where a plurality of turbines and power generators are arranged in one wind tunnel; and

Fig. 7 is a cross-sectional view of a portion where a turbine and a power generator of Fig. 6 are installed.

Best Mode for Carrying Out the Invention

[0009]

A wind power generator according to an embodiment of the invention will be described with reference to drawings. The wind power generator 10 includes a power generator chamber 11 arranged under the ground, and a wind-collecting means 12 arranged on the ground. The wind-collecting means 12 includes: a cylindrical member 14 that is erected on a foundation 13; six wind-collecting plates 15, lower ends of which are fixed to the foundation 13, bases of which are fixed to the circumferential wall of the cylindrical member 14, and which extend from the surface of the circumferential wall in directions normal to the circumferential wall; a top plate 16 that closes an upper end opening of the cylindrical member 14 and upper end openings between adjacent wind-collecting plates 15; wind inlets 17 that are formed on the wall of the cylindrical member 14; and a plurality of upper and lower guide plates 18 provided between adjacent wind-collecting plates 15.

[0010]

The cylindrical member 14 includes a wind tunnel 19, which reaches the power generator chamber 11, therein. The cylindrical member 14 is formed in the shape of a regular hexagon, the base of the wind-collecting plate 15 is fixed to each angular portion of the cylindrical member, and the wind inlet 17 is formed

on each side portion of the cylindrical member. The cylindrical member 14 may be separately formed of a plurality of pieces in a circumferential direction and height direction according to the height and diameter thereof, and may be assembled at a place where the wind power generator is installed. Further, the cylindrical member 14 may be formed to have the same diameter in the height direction as a whole, or may be formed in a gentle conical shape in which the lower portion has a larger diameter and the upper portion has a smaller diameter, according to the strength of the cylindrical member 14 or the pressure state in the wind tunnel 19 and the like.

[0011]

If the direction of the wind is substantially constant throughout the year, two or three wind-collecting plates 15 may be used. However, it is most preferable that six wind-collecting plates be used to efficiently collect wind in all directions. That is, if six wind-collecting plates 15 are arranged around the cylindrical member 14 at regular intervals, it is possible to collect wind to the center and to introduce the wind into the wind tunnel 19 by at least two adjacent wind-collecting plates 15 regardless of the direction from which the wind blows. Meanwhile, seven or more wind-collecting plates 15 may be provided. However, the wind-collecting effect is not improved enough correspondingly to the increase of the cost of the generator, this is not economical. According to the height and width, the wind-collecting plates 15 may also be separately formed of a plurality of pieces in a height direction and width

direction and may be assembled.

[0012]

The side view of the guide plate 18 is curved in an arc shape, in which the end side of the wind-collecting plate 15 is substantially parallel to the horizontal direction and the base side of the wind-collecting plate 15 is substantially parallel to the vertical direction. A gap between the upper and lower guide plates 18 may be set according to a distance between the base and outer end of the wind-collecting plate 15. Further, with the guide plates 18, adjacent wind-collecting plates 15 are connected to each other, thereby reinforcing the wind-collecting plates 15.

[0013]

The wind collected by the wind-collecting plates 15 and the guide plate 18 arranged as described above, is converged into an apex of a triangle in plan view, the lowermost portion of which is surrounded by the foundation 13, the uppermost portion of which is surrounded by the top plate 16, and which is further surrounded by the upper and lower guide plates 18. Accordingly, due to the guide plates 18, the wind blows into the wind tunnel 19 from the wind inlets 17 while the pressure of the wind is increased and the flow direction of the wind is changed into downward.

[0014]

The wind inlet 17 is formed by punching out a wall plate of the cylindrical member 14 in a quadrangular shape, and each of the wall plates 21 provided with a first back-flow preventing

means 20, which allows the flow of wind blowing into the inside of the cylindrical member 14 while regulating the flow of the wind blowing from the inside of the cylindrical member to the outside, is arranged between the bases of adjacent wind-collecting plates 15 on the outside of the wind inlets 17.

[0015]

The first back-flow preventing means 20 is formed by attaching a swing flap 24 with a hinge 23 at upper portion of the opening on the inside of the opening 22 formed in the wall plates 21. When wind pressure is applied to the flap from the outside, the lower portion of the flap 24 is opened about the hinge 23 toward the wind inlet 17 so as to allow the flow of the wind that flows into the inside of the cylindrical member 14 from the outside. Further, when wind pressure is not applied to the flap from the outside, the flap closes the opening 22 due to its own weight, thereby regulating the flow of the wind that blows from the inside of the cylindrical member to the outside.

[0016]

In addition, a second back-flow preventing means 25, which allows the flow of the wind blowing from the outside into spaces between the wind-collecting plates 15, while regulating the flow of the wind blowing from the spaces between the wind-collecting plates 15 to the outside, is arranged at the outer ends of adjacent wind-collecting plates 15. Like the back-flow preventing means 20 that is arranged at the base side of the wind-collecting plates 15, the second back-flow preventing

means 25 is formed by attaching a swing flap 29 on the inside of an opening 27 with a hinge 28 at upper portion of opening 27 formed in the wall plate 26 covering the spaces between the outer ends of the wind-collecting plate 15. When wind pressure is applied to the flap from the outside, the lower portion of the flap 29 is also opened about the hinge 28 toward the inside so as to allow the flow of the wind that blows into the space between the wind-collecting plates 15 from the outside. Further, when wind pressure is not applied to the flap from the outside, the flap closes the opening 27 due to its own weight, thereby regulating the flow of the wind that blows from the inside to the outside.

[0017]

Accordingly, the flaps 24 and 29 of the back-flow preventing means 20 and 25, which are positioned on the windward side, are automatically opened by the wind pressure, and the flaps of the back-flow preventing means 20 and 25, which are positioned on sides other than the windward side, are automatically closed. By further providing rubber sealants between the peripheral portions of the openings 22 and 27 and the flaps 24 and 29 respectively, adhesion can be improved and thus, secured closed state can be achieved. Meanwhile, the structure of the back-flow preventing means 20 and 25 is not limited thereto.

[0018]

The back-flow preventing means 20 and 25 formed as described above opens the lower portions of the openings 22 and

27 so as to make the wind that flows into the spaces between the wind-collecting plates 15 through the openings 27, and the wind that flows into the wind tunnel 19 through the openings 22 flow downward. In particular, it is possible to efficiently make the wind flow toward the power generator chamber 11 provided on the lower side of the wind tunnel 19 due to a synergistic effect of the guide plates 18 and the back-flow preventing means 20. Further, it is possible to prevent the wind, which is introduced into the spaces between the wind-collecting plates 15 and the wind tunnel 19, from blowing to the outside by the back-flow preventing means 20 and 25. Accordingly, it is possible to effectively use the introduced wind to generate electric power.

[0019]

The size (flow rate) or the number of the wind inlets 17 or the back-flow preventing means 20 and 25 is set according to the amount of the wind that is collected by the wind-collecting plates 15. If the width of the wind-collecting plate 15 is small, the number of the wind inlets may be set to be small or the size of the wind inlet 17 may be set to be small. If the width of the wind-collecting plate 15 is large, the number of the wind inlets may be set to be large and the size of the wind inlet 17 or the back-flow preventing means 20 and 25 may be set to be large.

[0020]

The power generator chamber 11, which is provided under the ground, is provided with an underground wind tunnel 30 that

communicates with the wind tunnel 19. In the underground wind tunnel 30, turbines 31 that are rotationally driven by the wind flowing through the underground wind tunnel 30, power generators 32 that are driven by the turbines 31, and other power transmission equipments are provided. The turbine 31 and the power generator 32 may be selected so as to correspond to the pressure and amount of wind that is supplied to the underground wind tunnel 30 from the wind tunnel 19, and may be selected in accordance with the intended use of electric power at a place where the wind power generator 10 is installed. Further, the wind, which has driven the turbines 31, is discharged to the atmosphere from the end of the underground wind tunnel 30.

[0021]

Furthermore, if surplus wind discharging units, which release pressure to the outside from the inside of the wind tunnel 19 when the pressure in the wind tunnel 19 exceeds a predetermined pressure, are provided at the upper and lower ends of the wind tunnel 19, respectively, it is possible to discharge the surplus wind that is introduced into the wind tunnel 19 during strong wind, thereby preventing the overload of the turbine 31. As the surplus wind discharging unit, vents may be formed on the top plate 16 and flap-shaped members for opening and closing the vents may be provided.

[0022]

The operating pressure of the surplus wind discharging units may be set to the same pressure. However, considering the flow of the wind in the wind tunnel 19, it is preferable

that the operating pressure of the lower surplus wind discharging unit is set to be lower. Further, the discharge flow rates of the surplus wind discharging units may also be set to the same flow rate. However, considering the strong wind such as a typhoon, the discharge flow rate of the upper surplus wind discharging unit, the operating pressure of which is set to be higher, is set to a larger flow rate so that only the lower surplus wind discharging unit, the operating pressure of which is set to be lower, can be operated in a normal variation range of wind power. Accordingly, a small amount of surplus wind is discharged without disturbing the flow of the wind in the wind tunnel 19. During the strong wind such as a typhoon, the upper surplus wind discharging unit, the operating pressure of which is set to be higher, can be also operated, whereby a large amount of surplus wind is discharged. As a result, it is possible to reliably protect devices such as turbines 31.

[0023]

A plurality of surplus wind discharging units may be provided toward a plurality of directions so as to set the discharge direction toward the leeward side. In addition, a self-adjusting surplus wind discharging unit, which automatically adjusts a discharge flow rate according to the electric power generating state of the power generator 32, may be provided. Further, it is preferable to provide a drain, which discharges moisture entering the wind tunnel 19, at the bottom of the underground wind tunnel 30 and the wind tunnel 19.

[0024]

Furthermore, in order to prevent foreign materials from entering the wind tunnel 19 through the wind inlet 17, it is preferable to provide screens on the outside of the wind inlets 17 or the outside of back-flow preventing means 20 and 25. The screens may be provided by holding general wire meshes or the like on frames and fixing the frames to adjacent wind-collecting plates 15 or the wall plates 21 and 26, for example.

[0025]

As described above, the cylindrical member 14, a plurality of (particularly, six) wind-collecting plates 15, and the plurality of guide plates 18 are combined with one another as the wind-collecting means 12 of the wind power generator 10, and thus, it is possible to effectively collect wind blowing in various directions so as to utilize the wind for the purpose of electric power generation and possible to obtain sufficient output of electric power generation even during weak wind. In addition, it may be possible to stably supply necessary electric power by selecting the height and diameter according to the conditions at the installation place. Furthermore, in relatively small-sized wind power generator, a baseplate alternative to the foundation 13 may be integrated with the wind-collecting means 12 to form a unit and further, the units may be stacked and used.

[0026]

A plurality of turbines 31 and power generators 32 may be provided in one underground wind tunnel 30 arranged at predetermined intervals in the flow direction of wind, and the number of operating power generators 32 may be increased or

decreased according to wind speed. For example, as shown in Fig. 6, five turbines 31a, 31b, 31c, 31d, and 31e may be provided in the underground wind tunnel 30, and power generators 32a, 32b, 32c, 32d, and 32e, which are driven by the turbines 31a to 31e, respectively, may be provided. The wind introduced into the underground wind tunnel 30 rotationally drives the turbines 31a to 31e. The power generators 32a to 32e are driven by the turbines 31a to 31e, respectively, to generate electric power. The wind, which has rotationally driven the turbines 31a to 31e, is discharged from the end of the underground wind tunnel 30.

[0027]

In addition, when the plurality of turbines 31 and the power generators 32 are provided as described above, the turbines 31 are arranged in such a manner that about $1/2$ to $1/4$ of an impeller 33 of each of the turbines 31 enters in the underground wind tunnel 30 as shown in Fig. 7. Accordingly, the wind in the underground wind tunnel 30 can pass without decreasing wind speed, and thus can rotationally drive the plurality of turbines 31.

[0028]

Regarding to the cylindrical member 14, the wind-collecting plates 15, the guide plates 18, and the like, appropriate material and an appropriate manufacturing method may be used according to conditions, such as the size of the entire wind power generator or predicted maximum wind speed and in general, a metal material, which is excellent in corrosion resistance, such as stainless steel or an aluminum alloy is

preferable and a structure, in which corrosion-resistant steel sheets or plates made of FRP or the like are attached to the metal framework, may be adopted.

[0029]

The width of the wind-collecting plate 15 may be determined according to various conditions at the place where the wind power generator is installed. Further, a ratio between the height and diameter (a diameter of a circle passing through the ends of the wind-collecting plates 15) of the wind power generator may also be arbitrarily selected. For example, if height is not regulated, the height may be increased up to 100 m, 200 m or more and the width of the wind-collecting plate 15 may be set to be small. If an installation area is sufficient, the height may be suppressed to be small and the diameter of the wind-collecting plate 15 may be increased up to 100 m or more. In general, it is preferable that the wind-collecting plate be formed as high as possible so as to effectively collect wind in the upper air where the wind is more stable comparing to the surface of the earth. The wind-collecting plate installed at a rooftop of a skyscraper or the like can have sufficient wind collecting efficiency even with the height or diameter between several meters and about 10 m.

[0030]

Since the wind-collecting plates 15 are provided in six directions around the cylindrical member 14, the wind power generator 10 as a building may have sufficient strength against strong wind or an earthquake if the height of the cylindrical

member 14 and the width of the wind-collecting plate 15 are appropriately set. Further, reinforcing members may be provided at appropriate positions if necessary, and appropriate flexible structure may be employed for quake resistance.

[0031]

In addition, an observatory 41 may be provided on the top plate 16, and a hall 42 may be provided at the bottom of the wind power generator. Further, elevators moving up and down between the hall 42 and the observatory 41 may be provided along the cylindrical member 14 or the wind-collecting plates 15. In addition to the observatory 41, a heliport, a signal tower, a radio relay station, a meteorological station, an astrophysical observatory, and the like may be provided on the top of the wind power generator 10. Further, for the maintenance and check of the back-flow preventing means 20 and 25 and the like, ladders (steps) may be formed at the cylindrical member 14 or the wind-collecting plates 15. In addition, the outer surfaces of the wind-collecting plates 15 and the back-flow preventing means 25 may be used for advertisements. In addition, the wind-collecting plates 15 and the back-flow preventing means 25 may be colored or patterned according to a surrounding scene, or may be illuminated at night.

CLAIMS

1. A wind power generator comprising:

a wind tunnel formed by a cylindrical member erected on the surface of a foundation in a vertical direction;

a plurality of wind-collecting plates that extends from a circumferential wall of the cylindrical member in directions normal to the circumferential wall;

a top plate that closes an upper end opening of the cylindrical member and upper end openings of spaces between adjacent wind-collecting plates;

a plurality of wind inlets that is formed on the circumferential wall of the cylindrical member to introduce wind collected by the wind-collecting plates into the wind tunnel;

back-flow preventing means arranged at the wind inlets for allowing only the flow of wind blowing into inside of the cylindrical member from outside of the cylindrical member, while regulating the flow of wind blowing from the inside to the outside;

a plurality of guide plates arranged between adjacent wind-collecting plates for guiding the wind collected by the wind-collecting plates downward;

a turbine that is driven by wind blowing out from one end of the wind tunnel; and

a power generator driven by the turbine.

2. The wind power generator according to claim 1, further

comprising:

second back-flow preventing means arranged between outer portions of adjacent wind-collecting plates for allowing the flow of wind blowing into spaces between the wind-collecting plates from outside, while regulating the flow of wind blowing from the spaces between the wind-collecting plates to the outside.

3. The wind power generator according to claim 1,

wherein six of the wind-collecting plates are provided on the cylindrical member at regular intervals in a circumferential direction.

4. The wind power generator according to claim 1, further comprising:

surplus wind discharging units arranged in the wind tunnel for discharging surplus wind introduced into the wind tunnel.

5. The wind power generator according to claim 1,

wherein other than the turbine and the power generator, more than one turbine and power generator are provided and arranged in a flow direction of wind in one wind tunnel, and

a rotary impeller of each of the turbines is configured in such manner that $1/2$ to $1/4$ of the rotary impeller enters in the wind tunnel.