[ABSTRACT]

~~The present invention provides an~~ An application container (1) of the present invention includes~~provided with~~: an ~~inside~~ inner plug member (20) ~~that is attached to~~mounted on a mouth ~~part~~ portion (10) of a container main body (2) and ~~has~~ formed with a communication hole (21) and a~~n ejection~~ discharge hole (22); ~~formed therein;~~ a holder (30) that ~~has an~~includes an ~~accommodation~~ accommodating ~~part~~ portion (31) and a plug body (35) and ~~has a~~ is formed with a communication path (40) ~~formed~~ between the holder (30) and the ~~inside~~ inner plug member (20); an application member (50) ~~that is arranged inside~~disposed in the ~~accommodation~~ accommodating ~~part~~ portion (31); a biasing member (60) ~~that~~ configured to bias~~es~~ the holder (30) upward with respect to the ~~inside~~ inner plug member (20); an over-cap (4) ~~that is attached to~~mounted on the mouth ~~part~~ portion (10) of the container main body (2); and a seal ~~part~~ portion (80) ~~that intercepts~~ configured to block communication between the communication path (40) and ~~the~~ an outside, in a state ~~in which~~where the over-cap (4) is ~~detached~~ removed from the mouth ~~part~~ portion (10) and the plug body (35) closes the communication hole (21).

[FIG. 1]