



(51) International Patent Classification:
F41A 9/68 (2006.01)

(21) International Application Number:

PCT/US2011/030051

(22) International Filing Date:

25 March 2011 (25.03.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/317,386 25 March 2010 (25.03.2010) US

(71) Applicant (for all designated States except US):
ARMWEST, LLC [US/US]; 955 W. Rosser Street,
Prescott, Arizona 86305 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SULLIVAN, Leroy
James [US/US]; 955 West Rosser Street, Prescott, Ari-
zona 86305 (US).

(74) Agent: CARTE, Norman E.; Haynes and Boone, LLP,
2323 Victory Avenue, Suite 700, Dallas, Texas 75219
(US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

[Continued on next page]

(54) Title: HIGH CAPACITY MAGAZINE




FIG. 1

(57) Abstract: A box magazine for a firearm may have a housing with two substantially different widths. A wider region may accommodate four columns of cartridges and may have tapered surfaces at one end that lead into a narrower region which may accommodate an interlocked and staggered double column of cartridges. Cartridges in the wider region may be separated into two staggered double columns by a free standing dividing wall and may be advanced by inner and outer contoured followers that may be nested together to form a single follower assembly surrounding the freestanding wall and that may be driven by the outer follower's spring. An inner follower spring may remain nested within the outer follower such that the two followers coordinate the advance of the two separated double columns of cartridges toward tapered surfaces that merge the two double columns into two single columns proximate the top of the dividing wall.



SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG). **Published:**

— *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*