

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶ :
H04Q 7/22

A2

(11) International Publication Number: WO 96/19085

(43) International Publication Date: 20 June 1996 (20.06.96)

(21) International Application Number: PCT/SE95/01432

(22) International Filing Date: 29 November 1995 (29.11.95)


(30) Priority Data:
355,282 12 December 1994 (12.12.94) US(71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON
[SE/SE]; S-126 25 Stockholm (SE).(72) Inventor: ÅSTRÖM, Bo, Arne, Valdemar; Telefonvägen 31,
S-126 37 Hägersten (SE).(74) Agents: BOHLIN, Björn et al.; Telefonaktiebolaget LM Ericsson,
Patent Dept., S-126 25 Stockholm (SE).

(81) Designated States: AL, AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: FLOW CONTROL METHOD FOR SHORT MESSAGE SERVICE-BUSY SUBSCRIBER



(57) Abstract

A flow control system and method in a global system for mobile communication (GSM) mobile telephone system for short message service (SMS). The SMS enables short text messages to be sent to and from mobile stations. The system and method is directed to a control for a service for messages sent to MSs (MT-SMs) and in particular to the case when several SCs send MT-SMs to the same mobile station subscriber. When several SCs send MT-SMs to the same subscriber, the first SC that establishes a short message dialog is allowed to be fully completed. While the short message dialog for this SC is established, any other SC attempting to send MT-SMs are detected and stored in a waiting list. After the initial short message dialog is completed, the same radio connection is maintained and each of the short messages corresponding to the SC addresses stored in the waiting list are sent by a first in-first to send principle. More generally, the system and method controls messages sent by SMS during a busy condition which enable a better utilization of the network and the network entity resources.