

DESICCANT ENHANCED EVAPORATIVE COOLING SYSTEMS AND METHODS

BACKGROUND

[0001] There are many applications for which controlling the environmental conditions within an enclosed space is important - for example, cooling data centers. A data center usually consists of computers and associated components operating 24 hours a day, 7 days a week. The electrical components in data centers produce a lot of heat, which needs to be removed from the space. Air-conditioning systems in data centers can consume as much as 40% of the total energy.

[0002] Comfort cooling of residential, commercial and institutional buildings is predominantly done using vapor-compression cooling equipment. Many process applications, such as data centers, also use mechanical cooling for primary or supplemental cooling. In most of these applications, the required cooling temperature is moderate (for example, 50°F - 85°F; 10°C - 30°C). Mechanical cooling equipment can produce high cooling capacities, operate reliably and can have acceptable cost due to mass production of compressors, exchangers and other components. However, these systems require significant amounts of high grade electrical energy to operate. For example, about 15% of the total annual US domestic electricity production is consumed by air conditioning units. Moreover, about one-third of the peak demand in hot summer months is driven by air conditioning units, leading to issues with power grid loading and stability. The production of electricity remains carbon intensive, so electricity driven cooling systems can contribute significantly to emissions and global warming.

[0003] Thermoelectric power production requires vast amounts of water for cooling, and the US average water consumption (evaporated water) for combined thermoelectric and hydroelectric power production is about 2 gallons/kWh. The water consumed to produce the electricity required by an EER 11 air conditioner is about equivalent to the water consumed by a good efficiency evaporative cooling system producing an equivalent amount of cooling. However, evaporative cooling systems consume far less electricity. Vapor-compression also typically requires synthetic refrigerants operating at high pressures. The deployment of large quantities of refrigerants in air conditioning and refrigeration systems has resulted in safety, health and environmental concerns. Modern high efficiency refrigerants, such as HFCs, can have high global warming potential and are being phased out. There is currently no direct replacement refrigerant option that has all the desired properties in terms of efficiency, stability, flammability, toxicity, and environmental impact.

[0004] Evaporative cooling systems are used successfully in many applications, especially in dry climates. Direct evaporative coolers (DEC) can be simple in design and efficient, compared to, for example, vapor compression systems. However, conventional DEC's can have some drawbacks. The supply air temperature coming out of the cooler may be challenging to control and is dependent on the outdoor air temperature and humidity level. The supply air may be excessively humid. These systems need careful maintenance to ensure that bacteria, algae, fungi and other contaminants do not proliferate in the water system and transfer into the supply air stream. Since these systems utilize direct contact between the evaporating liquid water and supply air, carryover of contaminants into the air stream can occur, which can, in turn, lead to reduced indoor air quality, odors and "sick building syndrome." Also, buildup of mineral deposits in the unit and on the evaporative pads can reduce performance and require maintenance.

[0005] Indirect evaporative coolers address the humidity problem but typically operate at lower wet bulb efficiencies. State-of-the-art dew-point evaporative coolers can deliver lower cooling temperatures than conventional direct or indirect evaporative systems and can maintain cooling power to higher outdoor wet bulb temperatures. However, all evaporative cooling technologies lose cooling performance as the working air humidity rises and cannot be used in humid climates without supplemental (usually vapor compression) cooling equipment. The water usage efficiency of evaporative cooling systems also varies widely depending on the system design and control characteristics. The water usage of evaporative coolers can be a problem, or at least a perceived problem. For example, large scale data centers may consume large quantities of potable water. Moreover, for those locations in which evaporative cooling works best (dry climates), the water demand may not be sustainable.

[0006] Absorption chillers are increasingly being adopted for comfort and process cooling, especially when waste heat is available. These systems have been successfully commercialized for larger scale applications and can be a good alternative to mechanical cooling in integrated building designs where the required technical and maintenance support is available. Single-effect absorptions chillers have a COP less than one, so significant quantities of heat are required to drive the system. Current absorption chiller designs are intended to replace electric chillers and deliver comparable cooling temperatures (40°F - 50°F; 4.4°C - 10°C). This requires the use of specialized materials (alloy metals), vacuum vessels, multiple heat exchangers, relatively high grade heat input for the generator, control methods to prevent crystallization, etc. Higher efficiency double and triple effect designs are increasingly complex and expensive. The complexity, cost and maintenance requirements of absorption systems may limit their

widespread acceptance as an alternative to mechanical cooling, especially in light commercial and residential applications.

[0007] There remains a need for alternative cooling technologies for comfort conditioning applications, which can largely replace mechanical cooling. The growing awareness of environmental impacts, electricity consumption and increasing regulatory pressure on refrigerants are pressing challenges for current HVAC cooling equipment. There is a need for a commercially viable design which meets requirements for capital and installation costs, operating costs, performance, reliability, size/weight restrictions, etc., while avoiding the creation of any new resource utilization problems, such as excessive water or gas consumption. The design should have good cooling performance and compactness, make use of low cost materials, and avoid the use of any environmentally harmful or toxic substances. From a thermodynamic perspective, the system should operate near atmospheric pressures with low grade heat input, employ moderate temperature changes and exchange fluxes to minimize irreversibility in the system and improve second law efficiency. Comfort conditioning may only require low grade cooling, and an exergy analysis shows how wasteful it is to use precious high grade energy sources such as electricity to drive cooling equipment.

SUMMARY

[0007a] An aspect of the present disclosure provides a system for conditioning air for an enclosed space, the system comprising:

a process plenum having a plenum inlet and outlet, the process plenum configured to direct air in an air flow path from the plenum inlet to the plenum outlet, air received at the plenum inlet being hot process air and air exiting the plenum outlet being conditioned supply air for the enclosed space;

a liquid-to-air membrane energy exchanger (LAMEE) arranged inside the process plenum, the LAMEE comprising a desiccant flow path separated from the air flow path by a membrane, the LAMEE configured to circulate a desiccant through the desiccant flow path and remove water from the air in the air flow path, a moisture content of the air at a LAMEE outlet being lower than a moisture content of the air at a LAMEE inlet; and

a direct evaporative cooler (DEC) arranged inside the process plenum downstream of the LAMEE, the DEC configured to operate adiabatically and evaporatively cool the air, a temperature of the air at a DEC outlet being lower than a temperature of the air at a DEC inlet.

[0007b] Another aspect of the present disclosure provides a system for conditioning air for an enclosed space, the system comprising:

a process plenum configured to direct air from a process inlet to a process outlet, the process inlet receiving air at a first temperature and the process outlet supplying air to the space at a second temperature that is lower than the first temperature;

a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the process plenum, the LAMEE1 configured to use a liquid desiccant flowing through the LAMEE1 to reduce the humidity of the air, a first concentration of water in the liquid desiccant at a fluid inlet of the LAMEE1 being lower than a second concentration of water in the liquid desiccant at a fluid outlet of the LAMEE1; and

a second LAMEE (LAMEE2) arranged inside the process plenum downstream of the LAMEE1, the LAMEE2 configured to operate adiabatically and use water flowing there through to evaporatively cool the air, a temperature of the air at an air outlet of the LAMEE2 being lower than a temperature of the air at an air inlet of the LAMEE2.

[0007c] Another aspect of the present disclosure provides a method of conditioning air for an enclosed space, the method comprising:

directing air through a process plenum having a plenum inlet and outlet, the air entering the plenum inlet at a first temperature;

directing the air through a liquid-to-air energy exchanger (LAMEE) arranged inside the plenum, a first moisture content of the air being higher at a LAMEE inlet compared to a second moisture content of the air at a LAMEE outlet;

directing a desiccant through the LAMEE, the desiccant and air separated by a membrane of the LAMEE, the LAMEE configured to remove water from the air using the desiccant, a first concentration of water in the desiccant being lower at a LAMEE inlet compared to a second concentration of water in the desiccant at a LAMEE outlet, the desiccant at the LAMEE outlet being a dilute desiccant;

directing the air through a direct evaporative cooler (DEC) arranged inside the process plenum downstream of the LAMEE, the DEC operating adiabatically to cool the air; and

delivering the air to the enclosed space, the air exiting the plenum outlet at a second temperature lower than the first temperature.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different letter suffixes may represent different instances of similar components, sub-components of a larger logical or

physical system, or the like. The drawings illustrate generally, by way of example, but not by way of limitation, various examples described in the present disclosure.

[0009] FIG. 1 schematically depicts an example conditioning system with a single working air stream, a desiccant dryer LAMEE and a direct evaporative cooler (DEC).

[0010] FIG. 2 is a psychometric chart for a modeled conditioning system similar to the conditioning system of FIG. 1.

[0011] FIG. 3 schematically depicts another example conditioning system that uses outdoor air in combination with process air and includes a desiccant dryer LAMEE, a DEC and a pre-cooler disposed between the desiccant dryer LAMEE and DEC.

[0012] FIG. 4 is a psychometric chart for a modeled conditioning system similar to the conditioning system of FIG. 2.

[0013] FIG. 5 schematically depicts an example regeneration system for use in a conditioning system.

[0014] FIG. 6 schematically depicts another example regeneration system for use in a conditioning system.

[0015] FIG. 7 is a flowchart depicting a method of operating a conditioning system in accordance with this disclosure.

OVERVIEW

[0016] The inventor(s) recognize, among other things, an opportunity for improved performance in providing cooling to an enclosed space through design of a conditioning system using a first Liquid-to-Air Membrane Energy Exchanger (LAMEE) as a dehumidifier to dry the air in an air stream passing through the first LAMEE, thus lowering the enthalpy and dew point of the air, and then passing the air through a second LAMEE (or another type of direct evaporative cooler (DEC)) to evaporatively cool the air. The inventor(s) also recognize an opportunity to use the water removed from the air stream by the first LAMEE as a source of water supply for evaporative coolers in the system, including, for example, the second LAMEE/DEC, to reduce or eliminate the need for an external water supply.

[0017] Examples according to the present application can include systems for conditioning air for an enclosed space. A conditioning system can include a process plenum configured to direct air from a plenum inlet to a plenum outlet. A LAMEE can be arranged inside the process plenum and a DEC can be arranged inside the process plenum downstream of the LAMEE. The LAMEE can function as a pre-dryer and can be configured to circulate a desiccant through a desiccant flow path to remove at least one of water and heat from the air passing through the LAMEE. A membrane in the LAMEE can separate the desiccant from the air. Essentially all of the energy removed from the air in the LAMEE can be transferred to the desiccant. The DEC downstream of the LAMEE can be used to cool the air prior to delivering the air to the enclosed space.

[0018] In an example, the DEC can be a direct-contact DEC such that the evaporative fluid (water) in the DEC directly contacts the air for evaporative cooling. In an example, the DEC can be a non-contact DEC, in which case the evaporative fluid does not directly contact the air. An example of a non-contact DEC is a LAMEE functioning as an evaporative cooler. In such an example, the dryer LAMEE can be a first LAMEE and the DEC can be a second LAMEE.

[0019] In an example, the air passing through the plenum can be hot process air from the enclosed space. Once it exits the plenum, the air can be delivered to the enclosed space as conditioned air. In an example, the air passing through the plenum can be outdoor air that is conditioned inside the plenum such that the air can then be delivered to the enclosed space. In

an example, the air passing through the plenum can be a combination of hot process air and outdoor air. In an example, the enclosed space can be a data center.

[0020] In an example, the conditioning system can include a regenerator to regenerate at least a portion of a dilute desiccant exiting the LAMEE, prior to recirculating the desiccant through the LAMEE. The regenerator can remove at least a portion of the water from the desiccant such that the regenerator can output a concentrated desiccant stream and a distilled water stream. In an example, the distilled water can be used as make up water for the DEC. The system can operate effectively with only a portion of the dilute desiccant from the LAMEE being regenerated.

[0021] Examples according to the present application can include a system for conditioning air for an enclosed space and the system can include a first LAMEE arranged inside a process plenum and a second LAMEE arranged inside the process plenum downstream of the first LAMEE. The first LAMEE can be configured to reduce the humidity of an air stream flowing there through and the second LAMEE can be configured to cool the air stream. In an example, the system can include a pre-cooler arranged inside the plenum between the first LAMEE and the second LAMEE.

[0022] In an example, the conditioning system can receive a mixture of hot process air from the enclosed space and outdoor air. In an example, the system can further comprise an exhaust plenum in fluid connection with the process plenum. A portion of the air in the process plenum can be diverted to the process plenum downstream of the first LAMEE. The air in the exhaust plenum can be used to provide cooling to water from an evaporative cooler in the process plenum, such as the pre-cooler arranged between the first and second LAMEEs. In an example, the exhaust plenum can include a third LAMEE, also referred to herein as an exhaust LAMEE.

[0023] In an example, the conditioning system can be used for commercial or residential applications. In an example, the enclosed space can be a residential home. In an example, the enclosed space can be a data center.

[0024] Examples according to the present application can include a method of conditioning air for an enclosed space and the method can include directing air through a LAMEE arranged inside a plenum and directing desiccant through the LAMEE. The LAMEE can be configured such that the desiccant can remove at least one of moisture and heat from the air. The air exiting the LAMEE can have a reduced moisture content relative to the air at an inlet of the LAMEE. The method can further include directing the air through a DEC arranged inside the plenum downstream of the LAMEE. The DEC can cool the air such that the air can be delivered to the enclosed space as reduced temperature or reduced humidity air.

[0025] In an example, the method can include regenerating at least a portion of the desiccant exiting the LAMEE. In an example, the method can include using the water recovered from the desiccant as make up water for operation of one or more evaporative coolers in the conditioning system.

[0026] This overview is intended to provide an overview of subject matter of the present patent application. It is not intended to provide an exclusive or exhaustive explanation of the invention. The detailed description is included to provide further information about the present patent application.

DETAILED DESCRIPTION

[0027] The present application relates to systems and methods for conditioning air for an enclosed space, and includes using a liquid to air membrane energy exchanger (LAMEE) as a desiccant dryer in combination with a direct evaporative cooler (DEC) located downstream of the desiccant dryer LAMEE. The desiccant dryer LAMEE can circulate a liquid desiccant, such as, for example, lithium chloride. The liquid desiccant and the LAMEE are described in further detail below. In an example, the DEC can be a LAMEE that operates as an evaporative cooler. The evaporative cooler LAMEE is an example of a non-contact DEC, as described below, since the evaporative fluid (water) and air are separated by a membrane. In an example, the DEC can be a direct contact DEC in which the water directly contacts the air.

[0028] In an example, the desiccant dryer LAMEE and DEC can be included in a system configured to condition hot process air (return air) from an enclosed space and return the process air to the enclosed space as cold, or reduced temperature process air (supply air). The desiccant dryer LAMEE can remove moisture from the hot process air, prior to passing the process air through the DEC. Dehumidification of the process air upstream of the DEC can facilitate efficient operation of the overall system and enable the DEC to cool the process air to lower temperatures. In another example, the desiccant dryer LAMEE and DEC can condition outdoor air and deliver the conditioned air to an enclosed space. In yet another example, the desiccant dryer LAMEE and DEC can condition a combination of process air and outdoor (makeup) air for delivery to an enclosed space. The system can be used to control or condition both a temperature and a humidity of the air stream being provided to the enclosed space.

[0029] A liquid to air membrane energy exchanger (LAMEE) can be used as part of a conditioning system to transfer heat and moisture between a liquid and an air stream, both flowing through the LAMEE, in order to condition the temperature and humidity of the air or to reduce a temperature of the liquid. In an example, the membrane in the LAMEE can be a non-porous film having selective permeability for water, but not for other constituents that may be

present in the liquid. Many different types of liquids can be used in combination with the non-porous membrane, including, for example, water, liquid desiccants, glycols. In an example, the membrane in the LAMEE can be semi-permeable or vapor permeable, and generally anything in a gas phase can pass through the membrane and generally anything in a liquid phase cannot pass through the membrane. In an example, the membrane in the LAMEE can be micro-porous such that one or more gases can pass through the membrane. In an example, the membrane can be a selectively-permeable membrane such that some constituents, but not others, can pass through the membrane. It is recognized that the LAMEEs included in the conditioning systems disclosed herein can use any type of membrane suitable for use with an evaporative cooler LAMEE or a desiccant dryer LAMEE.

[0030] In an example, the LAMEE can use a flexible polymer membrane, which is vapor permeable, to separate air and water. Relative to other systems/devices, the water flow rate and air flow rate through the LAMEE may not be limited by concerns such as droplet carryover at high face velocities. In addition, the LAMEE can operate with water flow rates that enable the transport of thermal energy into the cooler similar to a cooling tower, and the elevated inlet water temperatures can boost the evaporative cooling power of the LAMEE.

[0031] The desiccant dryer LAMEE can circulate any type of liquid desiccant suitable for removing moisture from the air. In an example, the cooling fluid is a liquid desiccant that is a high concentration salt solution. The presence of salt can sanitize the cooling fluid to prevent microbial growth. In addition, the desiccant salt can affect the vapor pressure of the solution and allow the cooling fluid to either release or absorb moisture from the air. Examples of salt-based desiccants usable herein include lithium chloride, magnesium chloride, calcium chloride, lithium bromide, lithium iodide, potassium fluoride, zinc bromide, zinc iodide, calcium bromide, sodium iodide and sodium bromide. In an example, the liquid desiccant can include an acetate salt, such as, but not limited to, an aqueous potassium acetate and an aqueous sodium acetate.

[0032] In an example, the liquid desiccant can include a glycol or glycol-water solution. Glycols can be unsuitable for use in a direct contact exchanger because the glycol can evaporate into the air stream. A glycol based liquid desiccant can be used here with a non-porous membrane since the membrane can prevent the transfer of the glycol into the air. In an example, the liquid desiccant can include glycols, or glycol-based solutions, such as triethylene glycol and propylene glycol, which are non-toxic, compatible with most metals and comparatively low in cost. Glycols can be strongly hygroscopic at higher concentrations. For example, a 95% solution of triethylene glycol has a comparable drying/dehumidification potential to lithium chloride near saturation. Triethylene glycol and tripropylene glycol can have low vapor pressures, but can be expensive. Less expensive and higher vapor pressure

glycols, such as ethylene glycol, diethylene glycol, propylene glycol and dipropylene glycol, can be used herein.

[0033] Other examples of liquid desiccants usable in the desiccant dryer LAMEE described herein include, but are not limited to, hygroscopic polyol based solutions, sulfuric acid and phosphoric acid. Glycerol is an example of a hygroscopic polyol usable herein. It is recognized that mixtures of desiccants can be used as the liquid desiccant in the desiccant dryer LAMEEs described herein. In addition to the desiccants listed above, the liquid desiccant can include, but is not limited to, an acetate salt solution, a halide salt solution, a hygroscopic polyol based solution, a glycol based solution, a sulfuric acid solution, a phosphoric acid solution, and any combinations thereof.

[0034] In an example, the conditioning system can include a regeneration system configured to increase a concentration of the liquid desiccant exiting the desiccant dryer LAMEE, prior to recirculating the liquid desiccant through the desiccant dryer LAMEE. The present application discloses systems and methods for recovering the water from the air stream (which is absorbed by the liquid desiccant in the desiccant dryer LAMEE) and using the recovered water as make up water for one or more cooling devices in the system, including, for example, the DEC. The systems and methods disclosed herein can eliminate or markedly reduce an external water consumption of the DEC.

[0035] In an example, a LAMEE can circulate an evaporative cooling fluid through the LAMEE and the LAMEE can operate as an evaporative cooler, using the cooling potential in both air and the cooling fluid (for example, water) to reject heat. As described above, the DEC located downstream of the desiccant dryer LAMEE can be an evaporative cooler LAMEE. In an example in which the LAMEE is an evaporative cooler, as air flows through the LAMEE, water, or both the air and the water, can be cooled to temperatures approaching the inlet air wet bulb (WB) temperature. Due to the evaporative cooling process in the LAMEE, a temperature of the water at the outlet of the LAMEE can be less than a temperature of the water at the inlet, or the temperature of the water may not be changed, but the air may be cooled. In an example, the cooling fluid in the LAMEE can be water or predominantly water. Other types of evaporative cooling fluids, including those listed above, can be used in combination with water or as an alternative to water.

[0036] A LAMEE can offer advantages over conventional cooling systems, such as cooling towers, for example. The membrane separation layer in the LAMEE can reduce maintenance, can eliminate the requirement for chemical treatments, and can reduce the potential for contaminant transfer to the liquid loop. The use of LAMEEs along with an upstream and/or downstream cooling coil (or other LAHX) can result in a lower temperature of the water leaving

the LAMEE and a higher cooling potential. Various configurations of conditioning systems having one or more LAMEEs are described herein and can boost performance in many climates.

[0037] FIG. 1 depicts an example conditioning system 100, which can be configured to condition air for delivery to an enclosed space, such as, for example, a data center. The conditioning system 100 can be used in commercial and industrial applications, as well as residential applications. The conditioning system 100 can be used for cooling air that is hot because of surrounding equipment and conditions in the enclosed space. The conditioning system 100 can be used for comfort cooling in residential and commercial applications. The conditioning system 100 can receive hot process air from the enclosed space and condition the process air such that it can be returned to the enclosed space as reduced-temperature or reduced-humidity supply air. The conditioning system 100 can receive outdoor air and condition the outdoor air prior to delivering the outdoor air to the enclosed space. In other examples, the conditioning system 100 can receive a mix or combination of outdoor air and process air.

[0038] In an example in which the conditioning system receives process air from the enclosed space, the conditioning system 100 can sometimes be referred to as a 100% recirculation system, which generally means that the air within the enclosed space recirculates through the conditioning system 100 in a continuous cycle of being cooled by the system 100 to a target supply air temperature, supplied to the space, heated by elements in the space (for example, computers, servers, and other electronics), and returned to the system 100 for cooling. Although not shown or described in detail, in such an example, the conditioning system 100 can include a make-up air unit or system, to continuously or periodically refresh the air within the space to satisfy ventilation requirements.

[0039] The conditioning system 100 can include a system cabinet 102 that can house a process plenum 104. A desiccant dryer LAMEE 106 and a direct evaporative cooler (DEC) 108 can be arranged inside the process plenum 104. A fan 110 can be arranged inside the process plenum 104 upstream of the desiccant dryer LAMEE 106 or in some other location. The process plenum 104 can include a plenum inlet 112, a plenum outlet 114, and a bypass inlet 116. Associated and generally collocated with each of inlet 112, outlet 114 and bypass inlet 116 can be dampers 118, 120 and 122, respectively.

[0040] The DEC 108 can be any type of direct evaporative cooler suitable for use inside the process plenum 104 to cool the air stream passing there through. Direct evaporative coolers can be defined for purposes herein as direct-contact DEC's and non-contact DEC's. In an example, the DEC 108 can be a LAMEE, also referred to herein as an evaporative cooler LAMEE. The evaporative cooler LAMEE is a non-contact DEC because the membrane in the LAMEE

separates and (maintains separation) between the evaporative fluid (water) and the air. In such an example in which the DEC 108 is a LAMEE, the desiccant dryer LAMEE 106 can also be referred to herein as a first LAMEE 106 and the evaporative cooler LAMEE 108 can also be referred to herein as a second LAMEE 108. In other examples, the DEC 108 can include, but is not limited to, a wetted media or spray atomizer system, both of which are examples of direct-contact DEC's since the evaporative fluid (water) directly contacts the air to cool the air.

[0041] Inlet air can enter the process plenum 104 at a first temperature through the plenum inlet 112. In an example, the air entering the process plenum 104 has been heated in the enclosed space and requires cooling to a target supply air temperature, which, in an example, can generally be determined based on the amount and characteristics of equipment housed in the enclosed space, for example, computing, networking, data storage and other equipment. In another example, the air entering the process plenum 104 can be outdoor air. In yet another example, the air entering the process plenum 104 can be a mixture of outdoor air and process air from the enclosed space.

[0042] In an example, the target supply air temperature can be based on a comfort cooling set point in a residential or commercial application. Air exiting the process plenum 104 at the plenum outlet 114 can be at a second temperature lower than the first temperature and can be supplied to the enclosed space as cooled process air (supply air). The second temperature can be at or within an acceptable tolerance of the target supply air temperature. As described below, the moisture content of the air at the outlet 114 can be controlled or maintained. In an example, a moisture content of the air at the inlet 112 can be about equal to a moisture content of the air at the outlet 114. In another example, the moisture content of the air at the inlet 112 can be less than or greater than the moisture content of the air at the outlet 114.

[0043] The system 100 can include a first desiccant circuit 124 configured to circulate a liquid desiccant through the desiccant dryer LAMEE 106. A desiccant tank or a first tank 126 can be part of the first desiccant circuit 124 and can receive the desiccant exiting the LAMEE 106 at a LAMEE outlet 128. A liquid to air heat exchanger (LAHX) or a liquid to liquid heat exchanger (LLHX) 132 can be part of the first desiccant circuit 124 and can cool the desiccant prior to passing the desiccant into the LAMEE 106 at a LAMEE inlet 134 for continued circulation through the LAMEE 106.

[0044] The system 100 can include a second desiccant circuit 166 for regeneration of the liquid desiccant. As shown in FIG. 1, the liquid desiccant in the desiccant circuit 124 exiting the tank 126 can be transported or delivered to at least one of the heat exchanger 132 (via the circuit 124) and a regeneration system (via the second desiccant circuit 166). In an example, a modulating valve 168 can control a distribution of the liquid desiccant to the heat exchanger

132 and to regeneration. A regeneration system for the liquid desiccant is described further below and shown in FIGS. 3 and 5. As shown in FIG. 1, the liquid desiccant in the second desiccant circuit 166 can be returned to the tank 126 (as concentrated desiccant) from the regeneration system.

[0045] The system 100 can be designed such that only a portion of the desiccant is regenerated. Thus, in an example, the system 100 can continue operating efficiently without requiring all of the desiccant to flow through the regenerator. As shown in FIG. 1, the valve 168 can direct all or a portion of the desiccant from the tank 126 directly back to the LAMEE 106. This is a result in part to the mixing in the tank 126 of concentrated desiccant from the regeneration system with dilute desiccant from the LAMEE 106. This is also a result of the design of the LAMEE 106 which operates at high flow rates of liquid desiccant through the LAMEE 106. Because the flow rate of liquid desiccant through the LAMEE 106 is high, a concentration decrease of the desiccant in the desiccant stream between the inlet 134 and the outlet 128 of the LAMEE 106 is small, compared to if the flow rate was low. As such, in an example, only a minor portion of the desiccant from the tank 126 can be diverted for regeneration.

[0046] The LAMEE 106 is configured such that the desiccant removes at least one of water and heat from the air stream. It is recognized that if the desiccant only removes water from the air (i.e. the air remains at a generally constant temperature between the LAMEE inlet and outlet), a temperature of the desiccant at an outlet of the LAMEE 106 can still be higher than a temperature of the desiccant at an inlet of the LAMEE 106. The temperature increase of the desiccant is due to the latent heat of condensation of the moisture from the air.

[0047] The design of the LAMEE 106 allows for the desiccant to not only remove water from the air stream, but the desiccant can also remove heat from the air stream. The LAMEE 106 can be configured such that essentially all of the energy removed from the air stream is transferred to the desiccant stream. In other words, an energy reduction of the air in the air stream between the LAMEE inlet and outlet can be about equal to an energy gain of the liquid desiccant in the desiccant stream between the LAMEE inlet and outlet. It is recognized that there may be some loss inherent in the system and 100% of the energy removed from the air stream may not be transferred to the desiccant stream. For purposes herein, the term “essentially all of the energy” or “all of the energy” recognizes and accounts for such losses in the system. Similarly, for purposes herein, “about equal” in reference to the energy reduction of the air relative to the energy gain of the desiccant recognizes and accounts for the system not being 100% efficient and having some loss. The LAMEE 106 can be configured such that a single fluid (the desiccant) can be used to remove heat and water from the air. Thus the LAMEE 106

can be a two-fluid design – the first fluid is the air stream and the second fluid is the desiccant. Additional fluids are not included for reducing the energy of the air, and the single desiccant stream in the LAMEE 106 can sufficiently remove heat and water from the air stream passing there through. The heat from the air stream can primarily be latent heat, although some sensible heat can also be removed from the air by the desiccant. Because the flow rate of liquid desiccant through the LAMEE 106 is high, a temperature increase of the desiccant stream between the inlet 134 and the outlet 128 of the LAMEE 106 is small, compared to if the flow rate was low.

[0048] The system 100 can include a first water circuit 130 configured to circulate a cooling fluid (such as water) through the DEC 108. A cooling fluid tank or a second tank 136 can receive the cooling fluid exiting the DEC 108 at an outlet 138. The cooling fluid can be recirculated from the tank 136 back to an inlet 140 of the DEC 108. The tank 136 can include a water supply; a portion of the water supply can be water recovered from the liquid desiccant during regeneration. Thus the water recovered in regeneration can be used as make up water for operation of the DEC 108. This is described below and shown in FIGS. 3 and 5.

[0049] The DEC 108 can be configured to adiabatically cool the air flowing through the DEC 108. A cooling potential of the DEC 108 may be limited by a humidity level of the air stream. The LAMEE 106, located upstream of the DEC 108, can reduce the humidity of the air stream such that dry air, as compared to the air's moisture content at the plenum inlet 112, enters the DEC 108. Dehumidification of the air upstream of the DEC 108 can allow for reaching lower air temperatures in the DEC 108 and thus can provide the ability to efficiently supply the air to the enclosed space at the set point temperature.

[0050] The desiccant dryer LAMEE 106 may be similar in construction to an evaporative cooler LAMEE. In an example, the desiccant dryer LAMEE 106 can circulate a liquid desiccant which can be a different composition than the cooling fluid used within an evaporative cooler LAMEE. In an example, the liquid desiccant can be a lithium chloride solution (or another liquid desiccant solution known in the art), while the cooling fluid in an evaporative cooler LAMEE can be pure water or predominately water. In an example, the liquid desiccant can be naturally-occurring, non-toxic, environmentally benign, low cost and an abundantly available substance. The liquid desiccant can absorb both heat and moisture from the air stream passing through the desiccant dryer LAMEE 106.

[0051] The liquid desiccant can be discharged from the LAMEE 106 at the LAMEE outlet 128 and into the desiccant tank 126. After the liquid desiccant exits the LAMEE outlet 128, the liquid desiccant can be diluted due to absorbed moisture from the air, which reduces the concentration of the desiccant and thereby reduces the drying ability of the LAMEE 106. The

conditioning system 100 can include a regeneration system to concentrate the liquid desiccant, prior to recirculating the desiccant. The desiccant can be transported from the tank 126, via a pump 142, to the regeneration system described below and shown in FIGS. 3 and 5. The regeneration system can control the concentration of the liquid desiccant entering the LAMEE 106 at the LAMEE inlet 134. A concentration of the desiccant at the inlet 134 can impact a capacity of the liquid desiccant to decrease the humidity of the air passing through the LAMEE 106.

[0052] The LAHX or LLHX 132 can be configured to cool the liquid desiccant prior to recirculating the liquid desiccant through the LAMEE 106. In an example, the liquid desiccant can be transported from the tank 126 to the LAHX or LLHX 132, which is described further below. The desiccant can then be delivered to the LAMEE inlet 134 at a reduced temperature, relative to the temperature of the liquid desiccant in the tank 126. The LAHX or LLHX 132 can include any type of heat exchanger or combination of heat exchangers suitable for cooling the liquid desiccant. In an example, the LAHX or LLHX 132 can include a liquid to air heat exchanger that uses the outdoor air to provide cooling to the liquid desiccant. In another example, the LAHX or LLHX 132 can include a liquid to liquid heat exchanger that uses another cooling fluid to cool the desiccant. Such cooling fluid can be cooled in a dry cooler, a cooling tower or any other type of evaporative cooler or hybrid cooler, or a combination thereof.

[0053] In an example, the conditioning system 100 can operate with the liquid desiccant in the first desiccant circuit 124 at higher temperatures, as compared to if water cooling were used as an alternative to the desiccant dryer LAMEE 106. In water cooling applications, such as a chilled water coil, water circulating through the circuit 124 would need to be at lower temperatures to achieve comparable results. (For example, a chilled water coil operates at a temperature colder than the dew point temperature of the air passing through the coil; such water temperature can be markedly colder than an operating temperature of the liquid desiccant in the first desiccant circuit 124.) In an example, a set point temperature of the desiccant entering the LAMEE 106 at the inlet 134 can be higher than an outdoor ambient dry bulb temperature. As such, in an example, heat can be released from the desiccant using an air cooler for the LAHX 132. In another example, the set point temperature of the desiccant entering the LAMEE 106 can be higher than an outdoor ambient wet bulb temperature, and the heat can be released from the desiccant using an evaporative assisted cooler for the LAHX 132.

[0054] Because the liquid desiccant in the circuit 124 can circulate at markedly higher temperatures (compared to water cooling), it can be easy to reject the heat from the desiccant to ambient air using “free cooling” methods, which can include direct sensible air cooling or evaporatively-assisted air cooling using only ambient air. Because conventional chilled water

systems have to run at lower temperatures by comparison, those systems typically require mechanical cooling equipment, at least during portions of the year when ambient conditions are high.

[0055] A primary function of the LAMEE 106 is to lower the moisture content, as well as the enthalpy, of the air passing through the LAMEE 106. As such, a moisture level of the air exiting the LAMEE 106 can be significant lower than a moisture level of the air entering the LAMEE. Similarly, an enthalpy of the air exiting the LAMEE 106 can be significantly lower than an enthalpy of the air entering the LAMEE 106. In an example, a temperature of the air exiting the LAMEE 106 can be about equal to or lower than a temperature of the air entering the LAMEE 106. In another example, a temperature of the air exiting the LAMEE 106 can be higher than a temperature of the air entering the LAMEE 106.

[0056] The air can flow through the DEC 108, which as an evaporative cooler can adiabatically cool the air using evaporation. Thus the process air exiting the DEC 108 can be at a lower temperature than the air entering the DEC 108. After exiting the DEC 108, the air can be directed to the outlet 114 of the process plenum 104 and can be delivered to the enclosed space as supply air. In an example, in which the DEC 108 is a LAMEE functioning as an evaporative cooler, the LAMEE 108 can adiabatically cool the air in a similar manner described above.

[0057] In an example, the system 100 can be controlled such that a moisture content of the air exiting the DEC 108 can be about equal to a moisture content of the air entering the process plenum 104 at the inlet 112. In another example, the moisture content of the air exiting the DEC 108 can be lower or higher than the moisture content of the air at the inlet 112.

[0058] In an example, the conditioning system 100 can utilize the bypass damper 122 to bypass the desiccant dryer LAMEE 106. The bypass damper 122 can be open (and the damper 118 can be closed), for example, when the inlet air entering the plenum 104 is dry or cold. In an example, the dampers 118 and 122 can be modulated to mix the air streams (i.e. some inlet air going through LAMEE 106 and some inlet air bypassing the LAMEE 106) to achieve desired conditions. Although not shown in FIG. 1, the conditioning system 100 can include other components (such as one or more fans) to direct the air into and through the process plenum 104 downstream of the LAMEE 106.

[0059] The design of the conditioning system 100 can facilitate cooling the air to the discharge set point temperature over a large range of humidity levels. The conditioning system 100 can replace vapor-compression cooling equipment in comfort cooling applications (residential or commercial) or in process cooling applications, like a data center. The conditioning system 100 can facilitate DX-free (direct expansion free) cooling in a wide range of climates.

[0060] The conditioning system 100 can achieve cooling comparable to an absorption chiller. However, in contrast to an absorption chiller, the conditioning system 100 can operate at or near atmospheric pressure and does not require sealed chambers under vacuum. This can eliminate the need for special materials and complexity resulting from operating the system 100, or components thereof, under vacuum. As compared to a DX system, which may require high operating pressures (for example, 400 psi), the conditioning system 100 can advantageously operate at or near atmospheric pressure.

[0061] The conditioning system 100 can directly cool the air stream and thus can be configured with a single working air stream. This can result in a compact system with a lower footprint and reduced costs. The conditioning system 100 can utilize moisture from the air and thus can operate effectively when there is moisture in the air.

[0062] The design of the conditioning system 100, using the desiccant dryer LAMEE 106, can facilitate collection of a significant amount of water from the air. Such water is contained within the dilute desiccant exiting the LAMEE 106 at the outlet 128. As described under the regeneration system of FIG. 5, the water can be separated from the desiccant and transported to other parts of the system 100. In an example, the water can be transported to the tank 136 for use by the DEC 108. The design of the conditioning system 100 can markedly reduce or eliminate external water consumption of the DEC 108 and of the system 100 overall.

[0063] The conditioning system 100 can include the fan (or fan array) 110 to drive the air into and through the process plenum 104. Example conditioning system 100 and other example systems in accordance with this disclosure can include more or fewer fans than what is shown in FIG. 1. Moreover, the fans can be located in different locations within the system 100 relative to what is shown in FIG. 1. For example, the fan 110 can be configured as a single fan or multiple fans, including a fan array, such as, for example, FANWALL® Systems provided by Nortek Air Solutions. Although not shown in the figures, example conditioning systems in accordance with this disclosure can include one or more filters disposed in the process plenum 104.

[0064] In the example of FIG. 1, the fan 110 can be arranged inside the process plenum 104 upstream of the LAMEE 106. In this position, some heat generated by the fan 110 can be removed. In other examples, the fan 110 can be located at different positions within/along the process plenum 104.

[0065] The conditioning system 100 can include a system controller 150, which can include hardware, software, and combinations thereof to implement the functions attributed to the controller herein. The system controller 150 can be an analog, digital, or combination analog and digital controller including a number of components. As examples, the controller 150 can

include ICB(s), PCB(s), processor(s), data storage devices, switches, relays, etcetera. Examples of processors can include any one or more of a microprocessor, a controller, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or equivalent discrete or integrated logic circuitry. Storage devices, in some examples, are described as a computer-readable storage medium. In some examples, storage devices include a temporary memory, meaning that a primary purpose of one or more storage devices is not long-term storage. Storage devices are, in some examples, described as a volatile memory, meaning that storage devices do not maintain stored contents when the computer is turned off. Examples of volatile memories include random access memories (RAM), dynamic random access memories (DRAM), static random access memories (SRAM), and other forms of volatile memories known in the art. The data storage devices can be used to store program instructions for execution by processor(s) of the controller 150. The storage devices, for example, are used by software, applications, algorithms, as examples, running on and/or executed by the controller 150. The storage devices can include short-term and/or long-term memory, and can be volatile and/or non-volatile. Examples of non-volatile storage elements include magnetic hard discs, optical discs, floppy discs, flash memories, or forms of electrically programmable memories (EPROM) or electrically erasable and programmable (EEPROM) memories.

[0066] The system controller 150 can be configured to communicate with conditioning system 100 and components thereof via various wired or wireless communications technologies and components using various public and/or proprietary standards and/or protocols. For example, a power and/or communications network of some kind may be employed to facilitate communication and control between the controller 150 and the conditioning system 100. In one example, the system controller 150 may communicate with the conditioning system 100 via a private or public local area network (LAN), which can include wired and/or wireless elements functioning in accordance with one or more standards and/or via one or more transport mediums. In one example, the system 100 can be configured to use wireless communications according to one of the 802.11 or Bluetooth specification sets, or another standard or proprietary wireless communication protocol. Data transmitted to and from components of the system 100, including the controller 150, can be formatted in accordance with a variety of different communications protocols. For example, all or a portion of the communications can be via a packet-based, Internet Protocol (IP) network that communicates data in Transmission Control Protocol/Internet Protocol (TCP/IP) packets, over, for example, Category 5, Ethernet cables.

[0067] The system controller 150 can include one or more programs, circuits, algorithms or other mechanisms for controlling the operation of the conditioning system 100. For example, the system controller 150 can be configured to modulate the speed of the fan 110 and/or control actuation of one or more of the dampers 118, 120 and 122. The system controller 150 can also be configured to operate the system 100 in a bypass mode in which the LAMEE 106 can be off and the air can still pass there through; alternatively, the damper 118 can be closed and the damper 122 can be open to direct the air into the plenum 104 downstream of the LAMEE 106.

[0068] FIG. 2 is a psychrometric chart for a theoretical system substantially similar to example conditioning system 100 of FIG. 1. In the example represented by FIG. 2, the inlet air is a hot process air stream from an enclosed space. The psychrometric chart illustrates the conditions of a modeled conditioning system, and in particular, conditions of the working fluid(s) thereof at different components of the system and/or at different points during operation. The various components of the modeled system are designated below using the reference labels of the system 100 of FIG. 1. The chart depicted in FIG. 2 was created using various numerical, analytical, algorithmic, etc. methods, tools, etc. to estimate the physical characteristics of a system in accordance with this disclosure when operated under certain initial conditions.

[0069] The example modeled system is operated at ambient conditions including an outdoor air dry bulb temperature of 32.2 degrees Celsius, an outdoor air wet bulb temperature of 29.4 degrees Celsius and a relative humidity of 81.6%. The altitude of the modeled system is sea level (0 meters), the barometric pressure is 760 mm Hg, and the atmospheric pressure is 101.325 kPa. The target temperature for the air being delivered to the enclosed space (from outlet 114) is about 28 degrees Celsius. The liquid desiccant employed in the LAMEE 106 is a lithium chloride solution with a salt concentration of 38% (at the LAMEE inlet 134) and a target fluid inlet temperature of 36.7 degrees Celsius (at the LAMEE inlet 134). The DEC 108 in the modeled system is an evaporative cooler LAMEE.

[0070] The characteristic values associated with the chart of FIG. 2 are as follows:

[0071] 1. Hot Air Return (HAR) – Conditions of Inlet Air at Plenum Inlet 112

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
14,159	41.667	27.847	35.4	18.10	0.917	88.463	23.250	1.1097	21.4012	19.729

[0072] 2. Fan 110 – Conditions of Air at outlet of Fan 110

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
14,159	42.500	28.036	33.8	18.10	0.920	89.328	23.250	1.1068	21.4012	19.677

Energy Change of Air (Sensible Heating) across Fan 110

Start Point Name	Total Heating (kW)	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Moisture Difference (kg/hr)	Sensible Heat Ratio	Enthalpy/Humidity Ratio (kJ/kg / g/kg)
HAR	14.7	14,711	14,711	0	0.0	1.000	N/A

[0073] 3. Desiccant Dryer LAMEE 106 (PreDry) – Conditions of Air at outlet of LAMEE 106

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
14,159	39.100	24.503	30.2	13.40	0.903	73.701	18.483	1.1219	15.9606	14.835

Energy Change of Air across Desiccant Dryer LAMEE 106

Start Point Name	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Moisture Difference (kg/hr)	Sensible Heat Ratio	Enthalpy/Humidity Ratio (kJ/kg / g/kg)
FAN	-265,741	-59,538	-206,203	-287.8	0.224	N/A

[0074] 4. Evaporative Cooler LAMEE 108 – Conditions of Air at outlet of LAMEE 108

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
14,159	28.200	24.572	74.6	18.10	0.878	74.478	23.250	1.1593	21.4012	20.611

Energy change of Air across LAMEE 108

Start Point Name	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Moisture Difference (kg/hr)	Sensible Heat Ratio	Enthalpy/Humidity Ratio (kJ/kg / g/kg)
Desiccant LAMEE	13,207	-192,498	205,705	287.8	-14.576	N/A

[0075] 5. Net Cooling of Conditioning System

Start Point Name	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Moisture Difference (kg/hr)	Sensible Heat Ratio	Enthalpy/Humidity Ratio (kJ/kg / g/kg)
HAR	-237,833	-237,833	0	0.0	1.000	N/A

[0076] Referring to the psychrometric chart of FIG. 2, the hot return air (HAR), or hot process air, enters the conditioning system at a plenum inlet 112 at a dry bulb temperature of 41.7 degrees Celsius, a wet bulb temperature of 27.8 degrees Celsius and a relative humidity of 35.4%. A moisture content or humidity ratio of the HAR is 18.1 g/kg. After passing through a fan 110, a dry bulb temperature of the process air is 42.5 degrees Celsius and a humidity ratio remains at 18.1 g/kg. As illustrated by the chart of FIG. 2, the fan 110 results in a slight increase in the dry bulb temperature of the process air, and consequently a minor gain in the sensible energy of the process air.

[0077] After passing through a desiccant dryer LAMEE 106 (pre-dry), a dry bulb temperature of the process air is reduced from 42.5 degrees Celsius to 39.1 degrees Celsius. The humidity ratio is reduced from 18.1 g/kg to 13.4 g/kg, indicating that a significant amount of water has been removed from the process air passing through the desiccant dryer LAMEE 106. As illustrated by the chart of FIG. 2 and the values above, the desiccant dryer LAMEE can significantly decrease the enthalpy of the process air. The total energy of the process air is reduced by 265,741 Watts (W), and the reduction is predominately a reduction in latent energy.

[0078] Although not included in the values above, the temperature of the liquid desiccant at an inlet of the desiccant dryer LAMEE 106 is 36.7 degrees Celsius and the temperature of the desiccant at the outlet of the LAMEE 106 is 39.3 degrees Celsius. As such, the liquid desiccant can absorb a significant amount of water from the process air running the desiccant at a relatively high temperature (36.7) and without significantly increasing a temperature of the liquid desiccant as it flows through the LAMEE 106. The desiccant can be run at higher temperatures, as compared, for example, to water temperatures required in a cooling coil; moreover, this facilitates an easier rejection of the heat from the desiccant during cooling in the LAHX or LLHX. For example, a conventional chilled water system can require water at entering temperatures of about 24-26 degrees Celsius to cool the process air down to 28 degrees Celsius. It is not possible to produce chilled water at these temperatures with “free cooling” methods when the outdoor air is 32.2 degrees Celsius dry bulb and 29.4 degrees Celsius. Such systems would require mechanical cooling.

[0079] After passing through an evaporative cooler LAMEE 108, a dry bulb temperature of the process air is reduced from 39.1 degrees Celsius to 28.2 degrees Celsius. A wet bulb

temperature of the process air remains essentially unchanged (24.5 degrees Celsius to 24.6 degrees Celsius). The net change in enthalpy is negligible - there is an increase in latent energy that is negated by a decrease in sensible energy.

[0080] After passing through the evaporative cooler LAMEE 108, the humidity ratio is increased from 13.4 g/kg to 18.1 g/kg as moisture from the cooling fluid in the evaporative cooler LAMEE 108 is added back to the process air. In the modeled conditioning system, there is not a net change in moisture between the plenum inlet and outlet. The moisture loss in the desiccant dryer LAMEE is 288 kg/hr and the moisture gain in the evaporative cooler LAMEE is 288 kg/hr.

[0081] The net cooling provided by the conditioning system is 237,833 Watts (W) of sensible cooling. This is defined as the cooling provided to the air stream passing between the inlet 112 and the outlet 114 of the conditioning system and is labeled in FIG. 2 as "Net Change".

[0082] It is recognized that in other examples or under other conditions, the conditioning system can be configured to have a net change in moisture of the process air. For example, if the enclosed space is experiencing increased humidity levels over time, the conditioning system can be configured to supply the process air back to the enclosed space at a moisture content less than the moisture content of the hot return air. Similarly, the conditioning system can be configured to supply the process air back to the enclosed space at a moisture content more than the moisture content of the hot return air.

[0083] FIG. 3 depicts an example conditioning system 200, which can share many of the components and functions of the conditioning system 100 of FIG. 1. For example, the conditioning system 200 can include the system cabinet 102, the process plenum 104, the desiccant dryer LAMEE 106, the DEC 108, the fan 110, the first desiccant circuit 124, the first water circuit 130, the first tank 126 (and the pump 142), the second tank 136, the LAHX or LLHX 132, and the system controller 150. As provided above, the DEC 108 can be an evaporative cooler LAMEE. The process plenum 104 can include the inlet 112 and the outlet 114, as well as the bypass inlet 116. Associated and generally collocated with each of the inlet 112, outlet 114 and the bypass inlet 116 can be the dampers 118, 120 and 122, respectively.

[0084] In addition to the components in common with the conditioning system 100, the conditioning system 200 can include an LAHX 244 arranged inside the process plenum 104 between the desiccant dryer LAMEE 106 and the DEC 108, an exhaust plenum 246 in fluid connection with the process plenum 104, an exhaust LAMEE 248 arranged inside the exhaust plenum 246, and a regenerator 252. As described above, the conditioning system 200 can be suitable for residential applications as well as commercial or industrial applications, including,

but not limited to, data centers, and can be designed to deliver the supply air at low temperatures and low to moderate humidity.

[0085] The conditioning system 200 can be designed to receive hot return air from an enclosed space. The conditioning system 200 can also be designed to receive outdoor air. The return air and outdoor air can mix together at the inlet 112 or inside the plenum 104 near the inlet 112 to form a mixed air stream. In FIG. 3, the hot return air (process air) and the outdoor air are shown being introduced into the plenum 104 at the plenum inlet 112 with one set of dampers 118. However, it is recognized that the process air and outdoor air may be introduced by way of separate dampers for the process air and the outdoor air. In an example, an amount of outdoor air introduced into the plenum 104 can be less than the amount of process air introduced into the plenum 104. In an example, the amount of outdoor air can be less than half of the amount of process air. In other examples, the conditioning system 200 can be designed to essentially only receive return air or essentially only receive outdoor air.

[0086] The addition of outdoor air into the plenum 104 can provide replenishment or make up air to the enclosed space and can eliminate or reduce the need for separate ventilation and make-up air units. As further described below, the outdoor air can be used to reject heat from the system 200 to the outside. In an example described further below, an exhaust air stream can provide additional cooling to other components within the conditioning system 200.

[0087] After entering the plenum 104, the mixed air stream can pass through the fan 110 and through the desiccant dryer LAMEE 106, as similarly described above under FIG. 1. Next, the mixed air stream can pass through the LAHX 244. The mixed air stream can be delivered to the LAHX 244 as relatively hot but relatively dry air. The LAHX 244 can function as a pre-cooler to reduce a dry bulb and wet bulb temperature of the mixed air prior to directing the air through the DEC 108.

[0088] In an example, the LAHX 244 can be a cooling coil that utilizes a cooling fluid (such as water) such that the mixed air stream can reject heat to the cooling fluid as the mixed air stream passes through the LAHX 244. It is recognized that other types of liquid to air heat exchangers that use a cooling fluid to reduce a temperature of air passing there through can be used as the LAHX 244.

[0089] The LAHX 244 can be included in a second water circuit 254 that can circulate the cooling fluid (water) for the LAHX 244. The cooling fluid can enter the LAHX 244 at an inlet 256 and at a first temperature. The cooling fluid can exit the LAHX 244 at an outlet 258 and at a second temperature that is higher than the first temperature. The cooling fluid can then be cooled in the exhaust LAMEE 248, which is described further below. The reduced temperature cooling fluid can be discharged to a third tank 260, where the cooling fluid can be stored. The

cooling fluid can be transported from the third tank 260 back to the inlet 256 of the LAHX 244 via a pump 262.

[0090] As further described below, in an example, the second water circuit 254 can use water from the regenerator 252, which can be transported to the tank 260. Thus the recovered water from regeneration can be used to provide at least a portion of the water circulating through the LAHX 244.

[0091] The second water circuit 254 as described above and shown in FIG. 3 is one example of a fluid circuit for the cooling fluid for LAHX 244. It is recognized that other components and methods can be used to reduce the temperature of the cooling fluid for the LAHX 244 prior to recirculating the cooling fluid through the LAHX 244.

[0092] It is recognized that the LAHX 244 can optionally be included in the conditioning system 100 of FIG. 1 and can be located between the desiccant dryer LAMEE 106 and the DEC 108. Similar to its function in the conditioning system 200, the LAHX 244 can be included in the system 100 to provide pre-cooling to the air stream exiting the LAMEE 106, before passing the air stream through the DEC 108. In such a design that excludes the exhaust plenum 246, the LAHX 244 can use another type of cooling device, as an alternative to the exhaust LAMEE 248, to cool the water exiting the LAHX 244 prior to recirculating the water back through the LAHX 244.

[0093] In an example, the LAHX 244 can be excluded, depending, for example, on the type of application that the system 200 is intended for. For example, if the supply air can be delivered at moderate temperatures rather than at cool temperatures, the LAHX can be excluded. In other examples, the LAHX 244 can be included in the system 200 but can be turned off or bypassed under some conditions.

[0094] The mixed air stream can exit the LAHX 244 at a reduced temperature relative to a temperature at an inlet of the LAXH 244. In an example, the mixed air stream can be split into exhaust air and process air. The exhaust air can be discharged through the exhaust plenum 246, which can be fluidly connected to the process plenum 104. The process air can continue through the plenum 104 and pass through the DEC 108 before being supplied back to the enclosed space through the outlet 114 as cooled process air.

[0095] The DEC 108 can operate as described above under FIG. 1. Given the addition of LAHX 244 upstream of the DEC 108, the process air entering the DEC 108 can be at a lower dry bulb and wet bulb temperature. The DEC 108 can be controlled depending on the temperature or humidity set points for the enclosed space. A ratio of latent to sensible cooling can be controlled and varied in the DEC 108. The DEC 108 can be turned on or off, or its capacity can be staged depending, at least in part, on the required amount of sensible to latent cooling

required. The first water circuit 130 for the DEC 108 can include the tank 136, as described above, and water can be delivered back to the DEC 108 via a pump 264. The first water circuit 130 can use water from the regenerator 252, as described below.

[0096] In an example, the amount of air delivered to the exhaust plenum 246 (from the mixed air stream) can be about equal to the amount of outdoor air input into the process plenum 104 at the inlet 112. In another example, the amount of exhaust air delivered to the exhaust plenum 246 can be more or less than the amount of outdoor air input into the process plenum 104. Having just exited the LAHX 244, the exhaust air can be cool and can be suitable for providing air cooling.

[0097] In an example, the exhaust air can pass through the exhaust LAMEE 248 arranged inside the exhaust plenum 246. The exhaust LAMEE 248 can be an evaporative cooler and the exhaust air can reduce a temperature of the water (in the second water circuit 254) passing there through. Moisture can be released into the exhaust air, which can then be discharged to the outside at an exhaust plenum outlet 247 through dampers 249. The exhaust air can thus provide cooling to the cooling fluid used in the LAHX 244. In an example, other types of evaporative coolers can be used for cooling the water in the second water circuit 254.

[0098] The regenerator 252 can be part of a second desiccant circuit 266 that can be in fluid connection with the first desiccant circuit 124. The regenerator 252 and the second desiccant circuit 266 can be part of a regeneration system that can be configured to regenerate the liquid desiccant before the desiccant is recirculated back to the desiccant dryer LAMEE 106. The regenerator 252 can receive a second portion of the liquid desiccant in the first desiccant circuit 124 that can be transported from the tank 126. A first portion of the liquid desiccant in the first desiccant circuit 124 can be transported to the LAHX or LLHX 132. The desiccant from the tank 126 can pass through a modulating valve 268 that can be controlled based on, at least in part, the latent or sensible cooling load of the system 200 or a condition of the hot return air and outdoor air. The modulating valve 268 can thus control the distribution of desiccant to the LAMEE 106 and to the regenerator 252. Other means can be used in addition to or as an alternative to the valve 268 to control a flow of desiccant from the tank 126 to the regenerator 252. As an example, a second pump can be included in the system 200 to pump desiccant to the regenerator 252 such that the pump 142 can only pump desiccant to the LAMEE 106; the operation of the second pump can control how much, if any, desiccant is transported to the regenerator 252. In another example, the tank 126 can be configured such that overflow of desiccant in the tank 126 can be directed to the regenerator 252.

[0099] As described above in reference to FIG. 1, because the LAMEE 106 can operate at high flow rates for the desiccant through the LAMEE 106, the reduction in concentration of the

desiccant in the desiccant stream exiting the LAMEE 106, relative to the concentration at the inlet of the LAMEE 106, can be small. As such, a small portion of the desiccant from the tank 126 can be diverted to the regenerator 252 via the modulating valve 268. In an example, between about 1 and about 25 percent of the desiccant exiting the tank 126 can be diverted to the regenerator; consequently, about 75 to about 99 percent of the desiccant exiting the tank 126 can be recirculated back to the LAMEE 106. Due to the mixing in the tank 126 of concentrated desiccant from the regenerator 252, the desiccant leaving the tank 126 can be at a higher concentration than the concentration of the desiccant exiting the LAMEE 106.

[00100] The regenerator 252 can be configured to receive the liquid desiccant at an inlet 270 and separate the water and desiccant into a concentrated desiccant stream, which exits the regenerator 252 at an outlet 272, and a water stream, which exits the regenerator 252 at an outlet 274. The regenerator 252 can include an energy input to facilitate such separation of water and desiccant. The concentrated desiccant stream can be transported back to the desiccant tank 126 where it can mix with other desiccant in the tank 126, including the dilute desiccant exiting the LAMEE 106. The water can be transported from the regenerator 252 via a water line 275 to at least one of the tank 136 (via a line 275a) and the tank 260 (via a line 275b) for use in the DEC 108 and the LAHX 244/LAMEE 248, respectively. The water provides cooling to the air in the LAHX 244. The increased-temperature water can then pass through the LAMEE 248, which acts as an evaporative cooler to reduce a temperature of the water prior to recirculating the water through the LAHX 244. Thus the LAHX 244/LAMEE 248 can use water from the regenerator 252 as make up water due to water consumption through evaporation in the LAMEE 248. Depending on a volume of water available for separation from the liquid desiccant, the water exiting the regenerator 252 can reduce or eliminate an external water supply for one or both of the DEC 108 and the LAHX 244/LAMEE 248. As shown in FIG. 3, the system 200 can be configured for connection to an external water supply such that one or both of the tanks 136 and 260 can receive external water as needed for operation of the DEC 108 and LAHX 244/LAMEE 248, respectfully.

[00101] Additional details about the regenerator 252 and the modulating valve 268 are provided below in reference to FIG. 5.

[00102] As provided above under FIG. 1, the conditioning system 200 can include the bypass inlet such that the desiccant dryer LAMEE can be bypassed in some conditions.

[00103] The system controller 150 can be structured and operate in association with the conditioning system 200 in a manner similar to that described with reference to the conditioning system 100 of FIG. 1. For example, the controller 150 can be communicatively connected to the system 200, can control operation of components thereof, and can control the

components to maintain a low humidity level or low temperature of the supply air. Such control can be based on variable sensible and latent loads in the enclosed space. The controller 150 can respond to changing outdoor air conditions or changing requirements for ventilation to the enclosed space. In an example, the system controller 150 can control or vary an amount of outdoor air added to the plenum 104. In an example, the system controller 150 can operate the modulating valve 268 to control or vary an amount of desiccant passing to the regenerator 252.

[00104] Although not shown in FIG. 3, the conditioning system 200 can include an air to air heat exchanger for the outside air prior to directing the outside air into the inlet 112. In an example, the exhaust air from the exhaust LAMEE 248 can be used to pre-cool the outdoor air designated for intake before the outdoor air enters the plenum 104 or after the outdoor air enters the plenum 104, but before it mixes with the return air.

[00105] FIG. 4 is a psychometric chart for a theoretical system substantially similar to example conditioning system 200 of FIG. 3. The psychometric chart illustrates the conditions of a modeled conditioning system, and in particular, conditions of the working fluid(s) thereof at different components of the system and/or at different points during operation. The various components of the modeled system are designated below using the reference labels of the system 200 of FIG. 3. The chart depicted in FIG. 4 was created using various numerical, analytical, algorithmic, etc. methods, tools, etc. to estimate the physical characteristics of a system in accordance with this disclosure when operated under certain initial conditions.

[00106] The example modeled system is operated at ambient conditions including an outdoor air dry bulb temperature of 35.0 degrees Celsius, an outdoor air wet bulb temperature of 23.9 degrees Celsius and a relative humidity of 39.8%. The altitude of the modeled system is sea level (0 meters), the barometric pressure is 760 mm Hg, and the atmospheric pressure is 101.325 kPa. The target temperature for the air being delivered to the enclosed space is about 15 degrees Celsius. The air is delivered at about 88.8% relative humidity; however, as the cold air moves into the enclosed space, it heats up and the relative humidity decreases. The return air from the enclosed space is 26.7 degrees Celsius and 51.1% relative humidity (and thus the relative humidity the occupants of the space would experience.)

[00107] The liquid desiccant employed in the LAMEE 106 is a lithium chloride solution with a salt concentration of 38% (at the LAMEE inlet 134) and a target fluid inlet temperature of 27 degrees Celsius (at the LAMEE inlet 134). The DEC 108 in the modeled system is an evaporative cooler LAMEE.

[00108] The characteristic values associated with the chart of FIG. 4 are as follows:

[00109] 1. Outdoor Air (OA) at Plenum Inlet 112

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
236	35.000	23.889	39.8	14.14	0.892	71.378	19.328	1.1364	16.8252	15.844

[00110] 2. Return Air (RA) at Plenum Inlet 112

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
566	26.667	19.444	51.1	11.23	0.864	55.354	15.744	1.1699	13.4183	12.988

[00111] 3. Mixed Air Stream

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
802	29.127	20.836	47.6	12.08	0.873	60.067	16.878	1.1598	14.4236	13.847

[00112] 4. Desiccant Dryer LAMEE 106 (PreDry) – Conditions of Air at outlet of LAMEE 106

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
802	28.200	16.405	28.7	6.84	0.863	45.727	8.339	1.1670	8.2345	7.928

Energy Change of Air across Desiccant Dryer LAMEE 106

Start Point Name	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Moisture Difference (kg/hr)	Sensible Heat Ratio	Enthalpy/Humidity Ratio (kJ/kg / g/kg)
Mixed RA	-13,819	-909	-12,910	-18.2	0.066	N/A

[00113] 5. LAHX 244 (PreCool) – Conditions of Air at outlet of LAHX 244

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/jg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
802	21.400	13.888	43.1	6.84	0.843	38.807	8.339	1.1940	8.2345	8.111

Energy Change of Air across LAHX 244

Start Point Name	Total Cooling (kW)	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Moisture Difference (kg/hr)	Sensible Heat Ratio	Enthalpy/Humidity Ratio (kJ/kg / g/kg)
PreDry	-6.7	-6,664	-6,664	0	0.0	1.000	N/A

[00114] 6. DEC 108 (Evap) – Conditions of Air at outlet of DEC 108

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/kg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
566	15.000	13.888	88.8	9.48	0.828	38.962	13.167	1.2186	11.3576	11.439

Energy Change of Air across DEC 108

Start Point Name	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Cooling Effectiveness (%)	Evaporation Rate - Mass (kg/hr)	Evaporation Rate - Volume (L/hr)	Sensible Heat Ratio
PreCool	149	-6,304	6,453	85.2	9.1	9.1	-42.3

[00115] 7. Supply Air (SA) at Plenum Outlet 114

Energy change of the air stream from plenum inlet to outlet (Net Cooling)

Start Point Name	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Moisture Difference (kg/hr)	Sensible Heat Ratio	Enthalpy/Humidity Ratio (kJ/kg / g/kg)
RA	-11,128	-8,114	-3,014	-4.3	0.729	N/A

[00116] 8. Exhaust LAMEE 248 (Evap Exhaust) – Conditions of Air at outlet of Exhaust LAMEE 248

Air Flow (Standard) (L/s)	Dry Bulb (°C)	Wet Bulb (°C)	Relative Humidity (%)	Humidity Ratio (g/kg)	Specific Volume (cu.m/kg)	Enthalpy (kJ/kg)	Dew Point (°C)	Density (kg/cu.m)	Vapor Pressure (mm Hg)	Absolute Humidity (g/cu.m)
236	23.680	21.568	83.3	15.40	0.861	62.912	20.672	1.179	18.286	17.879

Energy Change of Air across LAMEE 248

Start Point Name	Total Energy (W)	Sensible Energy (W)	Latent Energy (W)	Moisture Difference (kg/hr)	Sensible Heat Ratio	Enthalpy/Humidity Ratio (kJ/kg / g/kg)
PreCool Exh	6,832	668	6,165	8.7	0.098	N/A

[00117] Referring to the psychometric chart of FIG. 4, the return air (RA) enters the conditioning system at a plenum inlet 112 at a dry bulb temperature of 26.7 degrees, a wet bulb temperature of 19.4 degrees Celsius and a relative humidity of 51.1%; the outdoor air (OA) enters the conditioning system at a dry bulb temperature of 35 degrees Celsius, a wet bulb temperature of 23.9 degrees Celsius, and a relative humidity of 39.8%. The flow rate of the return air is 566 L/s and the flow rate of the outdoor air is 236 L/s; thus the flow of return air is more than two times greater than the flow rate of outdoor air.

[00118] The outdoor and return air mix at or downstream of the plenum inlet 112 and the mixed air stream has a dry bulb temperature of 29.1 degrees Celsius, a wet bulb temperature of 20.8 degrees Celsius and a relative humidity of 47.6% with a humidity ratio of 12.1 g/kg. As shown in the psychometric chart, there is an increase in enthalpy of the mixed air stream, relative to the return air, and a decrease in enthalpy relative to the outdoor air.

[00119] After passing through a desiccant dryer LAMEE 106 (pre-dry), a dry bulb temperature of the mixed air is reduced from 29.1 degrees Celsius to 28.2 degrees Celsius, whereas the wet bulb temperature is reduced from 20.8 degrees Celsius to 16.4 degrees Celsius. The humidity ratio is reduced from 12.1 g/kg to 6.8 g/kg. There is a significant reduction in enthalpy of the mixed air. More specifically, there is a significant reduction in latent energy. Although not included in the values above, a temperature of the desiccant at the inlet of the LAMEE 106 is 27 degrees Celsius and a temperature of the desiccant at the outlet of the LAMEE 106 is 29.1 degrees Celsius.

[00120] After passing through a LAHX 244 (pre-cool), a dry bulb temperature of the mixed air is reduced from 28.2 degrees Celsius to 21.4 degrees Celsius, whereas a wet bulb temperature is reduced from 16.4 degrees Celsius to 13.9 degrees Celsius. The humidity ratio is unchanged at 6.8 g/kg. The total energy reduction of the mixed air at 6,664 W is a reduction that is essentially all sensible energy.

[00121] Next the mixed air is split into a process air stream and an exhaust air stream. A flow rate of the process air is 566 L/s, which is the same flow rate as the return air entering the plenum inlet 112. The process air stream passes through a DEC 108 (Evap) to evaporatively cool the process air. After passing through the DEC 108, the process air has a dry bulb temperature reduced from 21.4 degrees Celsius to 15.0 degrees Celsius and a wet bulb temperature that is essentially unchanged. Through evaporative cooling, moisture is added to the process air in the DEC 108 such that the humidity ratio is increased from 6.8 g/kg to 9.5 g/kg. The net enthalpy is essentially unchanged after passing through the DEC 108. A reduction in sensible energy is equal to 6,304 W and an increase in latent energy is equal to 6,453 W.

[00122] The process air exiting the DEC 108 becomes the supply air (SA) for the enclosed space. Section 7 of the tables above shows the conditions of the supply air for delivery to the enclosed space, as well as the net change in energy between the return air (RA) and the supply air (SA), which is also shown by a line labeled "Net Change" in FIG. 4. There is a total energy reduction, or net cooling, of 11,128 W, which includes a sensible energy reduction of 8,114 W and a latent energy reduction of 3,014 W. (This amount of cooling is generally equivalent to about 3 tons of refrigeration, which is a common peak cooling capacity for a conventional residential air conditioner.) The return air is at a humidity level of 11.2 g/kg, compared to a reduced humidity level of the supply air at 9.5 g/kg. The conditioning system is removing 4.3 kg/hr of water from the air, so there is a relatively high level of latent cooling as well as sensible cooling.

[00123] The exhaust air stream at the outlet of the LAHX 244 (section 5) is split into separate exhaust and process air streams. The exhaust air passes through an exhaust LAMEE 248 that also circulates a cooling fluid for evaporative cooling. The cooling fluid is the water from the LAHX 244. The cooling fluid is primarily cooled by evaporation in the LAMEE 248. The temperature of the water entering the LAMEE 248 is at 26.1 degrees Celsius and a dry bulb temperature of the exhaust air entering the LAMEE 248 is 21.4 degrees Celsius. The temperature of the water exiting the LAMEE 248 is at 19.7 degrees Celsius and is delivered to a tank 260 to store the reduced-temperature water until it is recirculated back through the LAHX 244. A dry bulb temperature of the air exiting the LAMEE 248 is 23.7 degrees Celsius and the

humidity ratio is increased to 15.4 g/kg. The exhaust air is outlet to the outside via dampers 249. FIG. 4 shows the significant increase in enthalpy of the exhaust air as the heat from the water is rejected to the exhaust air in the LAMEE 248 (Evap Exhaust). A majority of the enthalpy increase to the air is latent heat.

[00124] The combination of the LAHX 244 and DEC 108 downstream of the desiccant dryer LAMEE 106 can allow the system 200 to adjust to the required sensible and latent loads. The system 200 can have humidity control in addition to temperature control. Thus the supply air returned to the enclosed space can be at comfortable conditions. Because the system 200 can deliver the supply air at low humidity levels, in some examples, a higher temperature may still feel comfortable since humidity is moderate. The system 200 can be suitable for residential applications or commercial applications in which low to moderate temperatures and moderate humidity can be desirable.

[00125] The combination of the desiccant dryer 106 with the LAHX 244 and DEC 108 can facilitate operation of the system 200 with little to no water input. In an example, the desiccant dryer 106 can remove enough water from the air stream such that the regenerator 252 can supply sufficient water for operation of the LAHX 244 and the DEC 108, without requiring water from an external water supply to be added to the tanks 136 and 260 for make up water for the DEC 108. This is described further below.

[00126] FIG. 5 depicts an example regeneration system 11, which can be part of a conditioning system 10 for conditioning air for delivery to an enclosed space. The conditioning system 10 can include a desiccant dryer LAMEE 6 arranged in a plenum 4 and a DEC 8 arranged in the plenum 4 downstream of the LAMEE 6. The conditioning system 10 can also include the same or similar components to the conditioning system 100 of FIG. 1 or the conditioning system 200 of FIG. 3. The plenum 4 can be configured to receive an air stream through a plenum inlet 12 and release the air stream through a plenum outlet 14. Associated and generally collocated with the inlet 12 and outlet 14 can be dampers 18 and 20, respectively. Although not shown in FIG. 5, a fan can be arranged inside the plenum 4 upstream of the desiccant dryer LAMEE 6 or in some other location.

[00127] The conditioning system 10 can circulate a liquid desiccant through the LAMEE 6 to reduce a humidity level of the air stream entering the plenum 4, prior to passing the air stream through the DEC 8. After circulating through the LAMEE 6, the liquid desiccant can be diluted due to absorbed moisture from the air. A reduction in the concentration of the desiccant can thereby reduce the drying ability of the LAMEE 6. The regeneration system 11, which can include a regenerator 52, can be configured to regenerate the liquid desiccant prior to recirculating the liquid desiccant back through the LAMEE 6.

[00128] After the liquid desiccant exits the LAMEE 6 at a LAMEE outlet 28, the liquid desiccant can be discharged into a desiccant tank 26 configured for storage of the liquid desiccant. The desiccant can be transported from the desiccant tank 26, via a pump 42, to the regenerator 52 and a LAHX or LLHX 32. The LAHX or LLHX 32 can be configured to reduce a temperature of the desiccant prior to passing the desiccant into the LAMEE 6 at a LAMEE inlet 34. The LAHX or LLHX 32 and the regenerator 52, in combination, can thus decrease a temperature and increase a concentration of the liquid desiccant prior to circulating the desiccant through the LAMEE 6. Both capabilities can be important in order for the desiccant to effectively remove moisture from the air stream passing through the LAMEE 6. A modulating valve 68 can control and vary a distribution of the desiccant from the tank 26 to the regenerator 52 and the LAHX or LLHX 32, as described further below.

[00129] The regeneration system 11 can include a portion of a first desiccant circuit 24 and a second desiccant circuit 66 in fluid connection with the first desiccant circuit 24. The first desiccant circuit 24 can be similar to the first desiccant circuit 124 of the system 200 of FIG. 3. The LAHX or LLHX 32 can be part of the first desiccant circuit 24. The second desiccant circuit 66 can be similar to the second desiccant circuit 266 of the system 200 of FIG. 3. The tank 26 can be part of the first desiccant circuit 24 and the second desiccant circuit 66. The regenerator 52 can be part of the second desiccant circuit 66 and can be similar to the regenerator 252 of FIG. 3.

[00130] The desiccant exiting the tank 26 can be transported to the regenerator 52 via the second desiccant circuit 66 and enter the regenerator 52 at an inlet 70. The regenerator 52 can separate the water from the desiccant such that a first exit stream 71 exiting the regenerator 52 at a first outlet 72 can be concentrated desiccant and a second exit stream 73 exiting the regenerator 52 at a second outlet 74 can be distilled water. (Concentration levels C1-C3 of the desiccant are described below.) The first exit stream 71 can be part of the second desiccant circuit 66. In an example, the first exit stream 71 can be transported back to the tank 26 via a pump 76.

[00131] The second exit stream 73 (distilled water) can be transported to a tank 36 for the DEC 8, via a pump 78, and used in a first water circuit 30 for the DEC 8. Thus the water in the air stream passing through the plenum 4 can be absorbed by the desiccant in the desiccant dryer LAMEE 6, separated from the desiccant in the regenerator 52, and then used as make up water for the DEC 8. The DEC 8 can still be connected to an external water supply – this is shown in FIG. 5 as external water supply to the tank 36. External water can be provided to the DEC 8 as needed; however the use by the DEC 8 of the recovered water from the desiccant can result in a significant reduction or elimination of water for operation of the DEC 8. In other

examples, the water in the second exit stream 73 can be used by more than one cooling unit in a conditioning system – see, for example, the conditioning system 200 of FIG. 3.

[00132] The dilute desiccant exiting the LAMEE 6 at the LAMEE outlet 28 can have a first desiccant concentration C1. The dilute desiccant can be mixed with existing desiccant in the tank 26 such that a concentration of desiccant in the tank 26 can be at a second concentration C2 that is greater than the first concentration C1. In an example, a difference in concentration between the first concentration C1 and the second concentration C2 can be small. The desiccant at the second concentration C2 can be regenerated in the regenerator 52 such that a third concentration C3 of the desiccant in the first exit stream 71 can be markedly greater than the second concentration C2. The concentrated desiccant in the first exit stream 71 (at the third concentration C3) can then be mixed with the dilute desiccant exiting the tank 26 (at the first concentration C1), and with the desiccant already in the tank 26, to increase the second concentration C2 of the mixed desiccant. As such, the second concentration C2 in the tank 26 can depend on the concentrations C1 and C3, and the volume/flow rate of each, as well as the volume of desiccant in the tank 26.

[00133] FIG. 5 shows an exemplary design for the regeneration system 11 in which the dilute desiccant exiting the LAMEE 6 can be mixed with the concentrated desiccant from the regenerator 52, and a portion of the desiccant exiting the tank 26 can be circulated back through the LAMEE 6 and a portion can be regenerated. The valve 68 can control a distribution of the desiccant exiting the tank 26 to the LAMEE 6 and to the regeneration system 11. In other examples, the conditioning system 10 can be configured such that all or a portion of the dilute desiccant exiting the LAMEE 6 can be transported directly to the regenerator 52, rather than mixing the dilute desiccant in the tank 26 with the concentrated desiccant coming back from the regenerator 52. This is shown in FIG. 6 and described below.

[00134] A dehumidification capacity of the LAMEE 6 can depend on a flow rate, a temperature, and a concentration of the liquid desiccant passing through the LAMEE 6. In an example, the conditioning system 10 can operate with a set point temperature and a set point concentration of the liquid desiccant at the LAMEE inlet 34; the flow rate of the desiccant through the LAMEE 6 can be generally constant. The load on the LAMEE 6 can vary as the conditions of the air stream passing through the plenum 4 vary. If the air stream increases in humidity, the load on the LAMEE 6 can increase. As a result, the liquid desiccant exiting the LAMEE 6 at the outlet 28 can require more regeneration, relative to if the LAMEE 6 receives a low humidity air stream. The regeneration system 11 can be configured such that as additional regeneration of the desiccant is required, the flow rate of liquid desiccant to the regenerator 52 can be increased via the modulating valve 68. In an example, the modulating valve 68 can be

controlled by a system controller 50 that is similar to the system controller 150 described above.

[00135] An increase in the flow rate of liquid desiccant to the regenerator 52 can result in an increase in the flow rate of concentrated liquid desiccant back to the tank 26 at the concentration C3. The increased amount of concentrated liquid desiccant can mix with the liquid desiccant in the tank 26 to increase the concentration C2 of the liquid desiccant that is transported back to the LAMEE 6 (after passing through the LAHX or LLHX 32). The flow rate of desiccant to the regenerator 52 can be controlled such that the concentration C2 can be at or near the set point concentration for the LAMEE 6 at the LAMEE inlet 34. In an example, the concentration C2 can vary (up or down) depending, at least in part, on the load of the system (i.e. the outdoor air conditions).

[00136] As an alternative or in addition to using a regeneration system, the concentration of the liquid desiccant in the first desiccant circuit 24 can be increased by introducing a concentrated desiccant into the desiccant tank 26. This can be done intermittently as needed or throughout operation of the system 10.

[00137] In an example, the flow of liquid desiccant to the LAHX or LLHX 32 can be relatively constant and the flow of liquid desiccant through the modulating valve 68 can be variable. It is recognized that in other examples the flow of liquid desiccant to the LAHX or LLHX 32 can also be variable.

[00138] The regenerator 52 can include any type of device capable of separating liquid water from the liquid desiccant. For example, the regenerator 52 can include, but is not limited to, vacuum multi-effect membrane distillation (VMEMD), electro-dialysis, reverse osmosis filtration, a gas boiler with condenser, a vacuum assisted generator, multi-stage flash, membrane distillation, and combinations thereof. The type of energy input to the regenerator 52 can include, for example, electrical power, mechanical power, or heat. The type of energy input depends on the technology used for regeneration of the liquid desiccant. Although the regenerator 52 is shown as a single unit in FIG. 5, the regenerator 52 can represent more than one unit operation. For example, the regeneration system 11 can include a heat recovery unit upstream of the regeneration or separation unit.

[00139] The LAHX or LLHX 32 can include any type of device suitable for cooling the liquid desiccant. For example, the LAHX or LLHX 32 can include, but is not limited to, a polymer fluid cooler (with evaporative cooling capability), a plate exchanger, and combinations thereof. In an example, the LAHX or LLHX 32 can provide air cooling to the liquid desiccant, using the outdoor air outside of the conditioning system 10. In another example, the LAHX or LLHX 32 can provide liquid cooling to the liquid desiccant using another cooling fluid. In an example, the

LAHX or LLHX 32 can be located external to the process plenum 4 or the other components of the conditioning system 10. In an example, the LAHX or LLHX 32 can be supplemented with an evaporative cooler for use as needed, depending on outdoor air conditions. For example, the LAHX can be supplemented with evaporative cooling sprays such that the tubes can be sprayed with water to enhance the cooling. In an example, an evaporative cooler LAHX 32 can use water recovered from the regeneration system 11 as make up water for the LAHX 32.

[00140] The design of the regeneration system 11 in combination with the desiccant dryer LAMEE 6 can facilitate operation of the conditioning system 10 with little to no external water consumption. The LAMEE 6 can remove the water from the air stream and use that water (which is separated from the desiccant for regeneration of the desiccant) as the make up water supply for one or more evaporative coolers in the conditioning system 10. The recovered water can be stored in the tank 36 and can be used as needed. Operation of evaporative coolers, like the DEC 8, can commonly require a significant amount of water. The conditioning system 10 having the regeneration system 11 can eliminate or markedly decrease the external water needed to operate the system 10. In an example, the system 10 can be generally water neutral. In an example, the system 10 can include an external water supply as back up in the event that additional water is needed.

[00141] In an example, the LAHX or LLHX 32 may require make up water in an example in which the LAHX or LLHX 32 includes evaporative cooling for use as needed. The evaporative cooling can be utilized when the outdoor air is at high dry bulb temperatures and air cooling of the liquid desiccant is not sufficient to meet a set point temperature for the desiccant delivered to the LAMEE 6. It is recognized that the recovered water from the regenerator system 11 can be sufficient in some cases to provide the make up water requirements for the DEC 8, as well as an evaporative cooler LAHX 32.

[00142] The design of the regeneration system 11 in combination with the desiccant dryer LAMEE 6 can also improve operation of the DEC 8 since water can be collected directly from the atmosphere. As such, the water recovered from the liquid desiccant in the regenerator 52 can be high quality water, which can be ideal for many cooling applications, including evaporative coolers. Such high quality water can increase the lifespan of the media in the DEC 8 and can decrease required maintenance on the cooler. In contrast, if the water supplied to the DEC 8 is potable water from wells or surface water sources, in some cases, mineral build up or scaling can occur, which may require the system 10 to include management of mineral concentrations or other water treatment units. In summary, the design described herein can reduce or eliminate overall water consumption of the conditioning system 10, as well as improve operation of the evaporative cooler 8.

[00143] FIG. 6 shows an example conditioning system 300 that can be similar to the conditioning systems 10, 100 and 200 but can include an alternative design for the fluid circuits for regeneration. Only a portion of the system 300 is shown in FIG. 6 for simplicity and it is recognized that additional components can be included. For example, only a portion of a system cabinet 302 and plenum 304 is shown in FIG. 6, but it is recognized that the plenum 304 can include some or all of the additional components shown and described above in reference to FIGS. 1, 3 and 5.

[00144] The desiccant dryer LAMEE 306 can operate similar to the desiccant dryer LAMEEs described above. The dilute desiccant exiting the desiccant dryer LAMEE 306 at an outlet 328 can be split into two flow paths – a first flow path to a tank 326 or a second flow path directly to a regenerator 352 (via a desiccant circuit 366). The regenerator 352 can operate similar to the regenerators described above. The desiccant entering the regenerator 352 at an inlet 370 can be at a first concentration C1. The concentrated desiccant exiting the regenerator 352 at an outlet 372 can be at a third concentration C3 and can be transported to the tank 326 for mixing with the desiccant already in the tank 326. As such, the desiccant in the tank 326 can be at a second concentration C2 that is greater than the first concentration C1 and less than the third concentration C3.

[00145] In contrast to the designs shown in FIGS. 1, 3 and 5, instead of the dilute desiccant (at the concentration C1) mixing with the desiccant in the tank and then flowing to the regenerator (at the second concentration C2), the dilute desiccant exiting the LAMEE 306 in FIG. 6 is transported directly to the regenerator 352 at the first concentration C1 (via a pump 367). All of the desiccant exiting the tank 326 at the second concentration C2 is circulated through the heat exchanger 332 and back through the LAMEE 306, rather than selectively directing a portion of the desiccant at the second concentration C2 to the regenerator 352. Thus in the design of FIG. 6 the split of the desiccant flow path is at the outlet 328 of the LAMEE 306, rather than at an outlet of the tank 326.

[00146] The pump 367 is shown in the desiccant circuit 366 and is an example of a device for regulating or controlling a flow of the dilute desiccant to the regenerator 352. As described above in reference to the other example conditioning systems, in an example, generally during operation of the system only a portion of the dilute desiccant exiting the LAMEE 306 is sent to the regenerator 352. The amount of desiccant transported to the regenerator 352 can be variable and a percentage of the desiccant at the outlet 328 can be directed to the regenerator and a remaining percentage of the desiccant at the outlet 328 can be directed to the tank 326. Such percentages can depend in part on a load of the conditioning system 300.

[00147] FIG. 7 illustrates an example method 700 for conditioning air for delivery to an enclosed space according to the example systems described above. The method 700 can include at 702 directing air through a desiccant dryer LAMEE arranged in a process plenum and at 704 directing a concentrated desiccant into and through the LAMEE to remove moisture from the air. The air can be outdoor air, hot supply air from the enclosed space, or a combination thereof. The method 700 can include at 706 regenerating the diluted desiccant exiting the LAMEE before recirculating the desiccant back through the LAMEE. The method 700 can include at 708 directing the air through a DEC arranged in the process plenum downstream of the LAMEE and at 710 delivering the conditioned air to the enclosed space at a reduced temperature.

[00148] It is recognized that the method 700 for conditioning the air can include other steps not included in FIG. 7. Such other steps can include, but are not limited to, directing air through a pre-cooler arranged in the process plenum downstream of the LAMEE and upstream of the DEC, utilizing water removed from the desiccant in the regenerating steam as make up water for the DEC or other components in the system. In an example, directing air through the LAMEE in 702 can include mixing process air with outdoor air upstream of the LAMEE to create a mixed air stream that passes through the process plenum. In an example, the method 700 can include removing a portion of the air in the mixed stream, at a location downstream of a pre-cooler and upstream of the DEC, to create an exhaust air stream and utilizing the exhaust air stream to cool the cooling fluid circulating through the pre-cooler.

[00149] The above detailed description includes references to the accompanying drawings, which form a part of the detailed description. The drawings show, by way of illustration, specific embodiments in which the invention can be practiced. These embodiments are also referred to herein as “examples.” Such examples can include elements in addition to those shown or described. However, the present inventors also contemplate examples in which only those elements shown or described are provided. Moreover, the present inventors also contemplate examples using any combination or permutation of those elements shown or described (or one or more aspects thereof), either with respect to a particular example (or one or more aspects thereof), or with respect to other examples (or one or more aspects thereof) shown or described herein.

[00150] All publications, patents, and patent documents referred to in this document are incorporated by reference herein in their entirety, as though individually incorporated by reference. In the event of inconsistent usages between this document and those documents so incorporated by reference, the usage in the incorporated reference(s) should be considered supplementary to that of this document; for irreconcilable inconsistencies, the usage in this document controls.

[00151] In this document, the terms “a” or “an” are used, as is common in patent documents, to include one or more than one, independent of any other instances or usages of “at least one” or “one or more.” In this document, the term “or” is used to refer to a nonexclusive or, such that “A or B” includes “A but not B,” “B but not A,” and “A and B,” unless otherwise indicated. In this document, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Also, in the following claims, the terms “including” and “comprising” are open-ended, that is, a system, device, article, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects.

[00152] Method examples described herein can be machine or computer-implemented at least in part. Some examples can include a computer-readable medium or machine-readable medium encoded with instructions operable to configure an electronic device to perform methods as described in the above examples. An implementation of such methods can include code, such as microcode, assembly language code, a higher-level language code, or the like. Such code can include computer readable instructions for performing various methods. The code may form portions of computer program products. Further, the code can be tangibly stored on one or more volatile or non-volatile tangible computer-readable media, such as during execution or at other times. Examples of these tangible computer-readable media can include, but are not limited to, hard disks, removable magnetic disks, removable optical disks (e.g., compact disks and digital video disks), magnetic cassettes, memory cards or sticks, random access memories (RAMs), read only memories (ROMs), and the like.

[00153] Examples, as described herein, may include, or may operate on, logic or a number of components, modules, or mechanisms. Modules may be hardware, software, or firmware communicatively coupled to one or more processors in order to carry out the operations described herein. Modules may hardware modules, and as such modules may be considered tangible entities capable of performing specified operations and may be configured or arranged in a certain manner. In an example, circuits may be arranged (e.g., internally or with respect to external entities such as other circuits) in a specified manner as a module. In an example, the whole or part of one or more computer systems (e.g., a standalone, client or server computer system) or one or more hardware processors may be configured by firmware or software (e.g., instructions, an application portion, or an application) as a module that operates to perform specified operations. In an example, the software may reside on a machine-readable medium. In an example, the software, when executed by the underlying hardware of the module, causes

the hardware to perform the specified operations. Accordingly, the term hardware module is understood to encompass a tangible entity, be that an entity that is physically constructed, specifically configured (e.g., hardwired), or temporarily (e.g., transitorily) configured (e.g., programmed) to operate in a specified manner or to perform part or all of any operation described herein. Considering examples in which modules are temporarily configured, each of the modules need not be instantiated at any one moment in time. For example, where the modules comprise a general-purpose hardware processor configured using software; the general-purpose hardware processor may be configured as respective different modules at different times. Software may accordingly configure a hardware processor, for example, to constitute a particular module at one instance of time and to constitute a different module at a different instance of time. Modules may also be software or firmware modules, which operate to perform the methodologies described herein.

[00154] The above description is intended to be illustrative, and not restrictive. For example, the above-described examples (or one or more aspects thereof) may be used in combination with each other. Other embodiments can be used, such as by one of ordinary skill in the art upon reviewing the above description. Also, in the above Detailed Description, various features may be grouped together to streamline the disclosure. This should not be interpreted as intending that an unclaimed disclosed feature is essential to any claim. Rather, inventive subject matter may lie in less than all features of a particular disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment, and it is contemplated that such embodiments can be combined with each other in various combinations or permutations. The scope of the invention should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

[00155] The present application provides for the following exemplary embodiments or examples, the numbering of which is not to be construed as designating levels of importance:

[00156] Example 1 provides a system for conditioning air for an enclosed space. The system can include a process plenum having a plenum inlet and outlet, the process plenum configured to direct air in an air flow path from the plenum inlet to the plenum outlet. The system can further include a liquid-to-air membrane energy exchanger (LAMEE) arranged inside the process plenum, the LAMEE comprising a desiccant flow path separated from the air flow path by a membrane, the LAMEE configured to circulate a desiccant through the desiccant flow path and remove water from the air in the air flow path. A moisture content of the air at a LAMEE outlet can be lower than a moisture content of the air at a LAMEE inlet. The system can further include a direct evaporative cooler (DEC) arranged inside the process plenum downstream of

the LAMEE, the DEC configured to evaporatively cool the air. A temperature of the air at a DEC outlet can be lower than a temperature of the air at a DEC inlet.

[00157] Example 2 provides the system of Example 1 optionally configured such that the LAMEE is a first liquid-to-air membrane energy exchanger (LAMEE1) and the DEC is a second liquid-to-air membrane energy exchanger (LAMEE2).

[00158] Example 3 provides the system of Example 2 optionally configured such that water removed from the air by the desiccant in the LAMEE1 is transported to the LAMEE2 and used to supply at least a portion of the make up water required for operation of the LAMEE2.

[00159] Example 4 provides the system of Example 1 optionally configured such that the DEC is a direct-contact DEC.

[00160] Example 5 provides the system of Example 4 optionally configured such that the direct-contact DEC includes at least one of wetted-media and a spray atomizer.

[00161] Example 6 provides the system of any of Examples 1-5 optionally further comprising a heat exchanger configured to cool the desiccant prior to recirculating the desiccant through the desiccant flow path of the LAMEE.

[00162] Example 7 provides the system of Example 6 optionally configured such that the heat exchanger is external to the process plenum.

[00163] Example 8 provides the system of Example 6 or 7 optionally configured such that the heat exchanger is a polymer fluid cooler.

[00164] Example 9 provides the system of any of Examples 6-8 optionally configured such that the heat exchanger is a liquid to air heat exchanger (LAHX) that uses outdoor air to cool the desiccant.

[00165] Example 10 provides the system of Example 6 or 7 optionally configured such that the heat exchanger is a liquid to liquid heat exchanger (LLHX).

[00166] Example 11 provides the system of any of Examples 1-10 optionally further comprising a regeneration system configured to increase a concentration of at least a portion of the desiccant exiting the LAMEE.

[00167] Example 12 provides the system of Example 11 optionally configured such that the regeneration system comprises a regeneration unit in fluid connection with the LAMEE. The regeneration unit is configured to receive a desiccant stream and separate water from the desiccant. A first output stream of the regeneration unit is concentrated desiccant and a second output stream of the regeneration unit is distilled water.

[00168] Example 13 provides the system of Example 12 optionally configured such that the second output stream is used as make up water for operation of the DEC.

[00169] Example 14 provides the system of Example 12 or 13 optionally configured such that the first output stream is transported to a desiccant tank configured to receive the first output stream and the desiccant exiting the LAMEE.

[00170] Example 15 provides the system of Example 14 optionally configured such that a desiccant output stream exiting the desiccant tank is transported to at least one of the regeneration unit and a heat exchanger configured to reduce a temperature of the desiccant before the desiccant circulates through the LAMEE.

[00171] Example 16 provides the system of Example 15 optionally further comprising a modulating valve configured to control a distribution of desiccant from the desiccant tank to the heat exchanger and the regeneration unit.

[00172] Example 17 provides the system of any of Examples 1-16 optionally configured such that the LAMEE is configured such that the desiccant circulating through the desiccant flow path removes heat from the air to reduce a temperature of the air.

[00173] Example 18 provides the system of any of Examples 1-17 optionally configured such that the process plenum is configured to receive hot process air from an enclosed space and condition the process air such that reduced-temperature air can be returned to the enclosed space.

[00174] Example 19 provides the system of any of Examples 1-17 optionally configured such that the process plenum is configured to receive outdoor air and condition the outdoor air such that reduced-temperature air can be delivered to the enclosed space.

[00175] Example 20 provides the system of any of Examples 1-17 optionally configured such that the process plenum is configured to receive outdoor air that mixes with process air in the air flow path, and wherein the process air is from the enclosed space.

[00176] Example 21 provides the system of any of Examples 1-20 optionally further comprising a pre-cooler arranged between the LAMEE and the DEC and configured to reduce a temperature of the air passing through the pre-cooler.

[00177] Example 22 provides the system of any of Examples 1-21 optionally configured such that the system operates at or near atmospheric pressure.

[00178] Example 23 provides a system for conditioning air for an enclosed space and the system can include a process plenum configured to direct air from a process inlet to a process outlet, the process inlet receiving air at a first temperature and the process outlet supplying air to the space at a second temperature that is lower than the first temperature. The system can further include a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the process plenum, the LAMEE1 configured to use a liquid desiccant flowing through the LAMEE1 to reduce the humidity of the air, a first concentration of water in the liquid desiccant at a fluid

inlet of the LAMEE1 being lower than a second concentration of water in the liquid desiccant at a fluid outlet of the LAMEE1. The system can further include a second LAMEE (LAMEE2) arranged inside the process plenum downstream of the LAMEE1, the LAMEE2 configured to use water flowing there through to evaporatively cool the air, a temperature of the air at an air outlet of the LAMEE2 being lower than a temperature of the air at an air inlet of the LAMEE2.

[00179] Example 24 provides the system of Example 23 optionally configured such that at least a portion of the water flowing through the LAMEE2 is water removed from the air by the liquid desiccant in the LAMEE1.

[00180] Example 25 provides the system of Example 24 optionally configured such that a quantity of the water removed from the air by the liquid desiccant in the LAMEE1 is sufficient as the make-up water for operation of the LAMEE2.

[00181] Example 26 provides the system of any of Examples 23-25 optionally configured such that the LAMEE1 is configured to use the liquid desiccant flowing through the LAMEE1 to remove heat from the air, a temperature of the desiccant at a desiccant outlet of the LAMEE1 being higher than a temperature of the desiccant at a desiccant inlet of the LAMEE1.

[00182] Example 27 provides the system of any of Examples 23-26 optionally further comprising a regenerator system in fluid connection with a desiccant flow path through the LAMEE1, the regenerator system configured to increase a concentration of the liquid desiccant at the fluid inlet of the LAMEE1 relative to the fluid outlet of the LAMEE1.

[00183] Example 28 provides the system of Example 27 optionally configured such that the regenerator system comprises a regeneration unit configured to receive a desiccant stream at an inlet of the regeneration unit and separate the desiccant and water in the desiccant stream, wherein a first outlet of the regeneration unit includes a concentrated desiccant stream and a second outlet of the regeneration unit includes a distilled water stream.

[00184] Example 29 provides the system of Example 28 optionally configured such that the distilled water stream is in fluid connection with the LAMEE2.

[00185] Example 30 provides the system of Example 28 or 29 optionally configured such that the concentrated desiccant stream is transported to a desiccant storage tank configured to receive the desiccant exiting the LAMEE1, and the concentrated desiccant stream mixes with the desiccant exiting the LAMEE1.

[00186] Example 31 provides the system of Example 30 optionally configured such that a desiccant output stream exiting the desiccant storage tank is delivered to at least one of the LAMEE1 and the regeneration unit.

[00187] Example 32 provides the system of Example 31 optionally configured such that a modulating valve in the desiccant stream controls a distribution of the desiccant in the desiccant output stream to the LAMEE1 and to the regeneration unit.

[00188] Example 33 provides the system of any of Examples 23-32 optionally further comprising a make-up air unit configured to provide replenishment air to the enclosed space.

[00189] Example 34 provides the system of any of Examples 23-33 optionally further comprising a liquid-to-air heat exchanger LAHX arranged between the LAMEE1 and the LAMEE2, the LAHX configured to reduce a temperature of the air flowing there through.

[00190] Example 35 provides the system of Example 34 optionally configured such that a first portion of the air exiting the LAHX is configured to flow through the LAMEE2 and a second portion of the air exiting the LAHX is configured to flow through a third liquid-to-air membrane energy exchanger (LAMEE3) arranged inside an exhaust plenum in fluid connection with the process plenum.

[00191] Example 36 provides the system of Example 35 optionally configured such that a volume of air in the second portion is less than a volume of air in the first portion.

[00192] Example 37 provides the system of Example 35 or 36 optionally configured such that a cooling liquid circulating through the LAHX is in fluid connection with the LAMEE3, wherein the cooling liquid exits the LAHX and passes through the LAMEE3, and wherein the air from the exhaust plenum cools the cooling liquid in the LAMEE prior to recirculating the cooling liquid through the LAHX.

[00193] Example 38 provides the system of any of Examples 23-37 optionally configured such that the process plenum receives outdoor air at the process inlet, and the outdoor air mixes with process air from the enclosed space prior to passing through the LAMEE1.

[00194] Example 39 provides the system of any of Examples 23-38 optionally further comprising a heat exchanger configured to cool the liquid desiccant prior to flowing the liquid desiccant through the LAMEE1, wherein the heat exchanger is a liquid-to-air heat exchanger or a liquid-to-liquid heat exchanger.

[00195] Example 40 provides the system of Example 39 optionally configured such that the heat exchanger is located external to the process plenum.

[00196] Example 41 provides a method of conditioning air for an enclosed space. The method can include directing air through a process plenum having a plenum inlet and outlet, directing the air through a liquid-to-air energy exchanger (LAMEE) arranged inside the plenum, and directing a desiccant through the LAMEE. The desiccant and air are separated by a membrane of the LAMEE, the LAMEE configured to remove water from the air using the desiccant, a first concentration of water in the desiccant being lower at a LAMEE inlet compared

to a second concentration of water in the desiccant at a LAMEE outlet. A first moisture content of the air is higher at a LAMEE inlet compared to a second moisture content of the air at a LAMEE outlet. The method can further include directing the air through a direct evaporative cooler (DEC) arranged inside the process plenum downstream of the LAMEE, to cool the air, and delivering the air to the enclosed space. The air enters the plenum inlet at a first temperature and exits the plenum outlet at a second temperature lower than the first temperature.

[00197] Example 42 provides the method of Example 41 optionally configured such that the LAMEE is configured to remove heat from the air using the desiccant as the desiccant and the air are directed through the LAMEE, and wherein a temperature of the desiccant at the LAMEE outlet is higher than a temperature of the desiccant at the LAMEE inlet.

[00198] Example 43 provides the method of Example 41 or 42 optionally configured such that directing the air through a DEC comprises directing the air through an evaporative cooler LAMEE configured to adiabatically cool the air.

[00199] Example 44 provides the method of Example 41 or 42 optionally configured such that directing the air through a DEC comprises directing the air through a direct-contact DEC configured to cool the air through direct contact of an evaporative fluid with the air.

[00200] Example 45 provides the method of any of Examples 41-44 optionally further comprising directing the air through a pre-cooler arranged inside the process plenum downstream of the LAMEE and upstream of the DEC.

[00201] Example 46 provides the method of Example 45 optionally configured such that the pre-cooler is a cooling coil. The method can optionally further comprise directing a portion of the air exiting the pre-cooler into an exhaust plenum and through a second LAMEE arranged inside the exhaust plenum, and directing water exiting the cooling coil through the second LAMEE. The second LAMEE can be configured to cool the water using the air, the water at an outlet of the second LAMEE at a reduced temperature relative to the water at an inlet of the second LAMEE. The method can optionally further comprise recirculating the water to the cooling coil.

[00202] Example 47 provides the method of any of Examples 41-46 optionally further comprising regenerating at least a portion of the desiccant exiting the LAMEE.

[00203] Example 48 provides the method of Example 47 optionally configured such that regenerating at least a portion of the desiccant comprises transporting the dilute desiccant exiting the LAMEE to a desiccant storage tank, and transporting a portion of the desiccant from the desiccant storage tank to a regeneration unit.

[00204] Example 49 provides the method of Example 48 optionally further comprising separating at least a portion of the water from the desiccant by directing the desiccant through

the regeneration unit, wherein a first output stream of the regeneration unit is concentrated desiccant and a second output stream of the regeneration unit is distilled water.

[00205] Example 50 provides the method of Example 49 optionally further comprising transporting at least a portion of the distilled water in the second output stream to the DEC to provide at least a portion of make-up water for operation of the DEC.

[00206] Example 51 provides the method of Example 49 or 50 optionally further comprising transporting a portion of the distilled water in the second output stream to a fluid circuit that includes a pre-cooler and an exhaust cooler and utilizing the distilled water as make-up water in the fluid circuit. The pre-cooler is arranged inside the process plenum downstream of the LAMEE and upstream of the DEC, and the exhaust cooler is an evaporative cooler configured to cool increased-temperature water exiting the pre-cooler.

[00207] Example 52 provides the method of any of Examples 49-51 optionally further comprising transporting the concentrated desiccant in the first output stream to the desiccant storage tank and mixing the concentrated desiccant with the dilute desiccant from the LAMEE. A concentration of the desiccant inside the desiccant storage tank has a desiccant concentration higher than the dilute desiccant and lower than the concentrated desiccant.

[00208] Example 53 provides the method of Example 48 optionally further comprising transporting a portion of the desiccant from the desiccant storage tank to the LAMEE for recirculation of the desiccant through the LAMEE.

[00209] Example 54 provides the method of Example 53 optionally further comprising directing the desiccant through a heat exchanger upstream of the LAMEE to cool the desiccant prior to recirculation of the desiccant through the LAMEE.

[00210] Example 55 provides the method of Example 53 or 54 optionally further comprising controlling a volume distribution of desiccant transported from the desiccant storage tank to the LAMEE and to the regeneration unit.

[00211] Example 56 provides the method of Example 55 optionally configured such that controlling the volume distribution of desiccant to the LAMEE and to the regeneration unit comprises using a modulating valve located in a desiccant output stream of the desiccant storage tank.

[00212] Example 57 provides a system or method of any one or any combination of Examples 1-56, which can be optionally configured such that all steps or elements recited are available to use or select from.

[00213] Various aspects of the disclosure have been described. These and other aspects are within the scope of the following claims.

CLAIMS

What is claimed is:

1. A system for conditioning air for an enclosed space, the system comprising:
a process plenum having a plenum inlet and outlet, the process plenum configured to direct air in an air flow path from the plenum inlet to the plenum outlet, air received at the plenum inlet being hot process air and air exiting the plenum outlet being conditioned supply air for the enclosed space;
a liquid-to-air membrane energy exchanger (LAMEE) arranged inside the process plenum, the LAMEE comprising a desiccant flow path separated from the air flow path by a membrane, the LAMEE configured to circulate a desiccant through the desiccant flow path and remove water from the air in the air flow path, a moisture content of the air at a LAMEE outlet being lower than a moisture content of the air at a LAMEE inlet; and
a direct evaporative cooler (DEC) arranged inside the process plenum downstream of the LAMEE, the DEC configured to operate adiabatically and evaporatively cool the air, a temperature of the air at a DEC outlet being lower than a temperature of the air at a DEC inlet.
2. The system of claim 1 wherein the LAMEE is a first liquid-to-air membrane energy exchanger (LAMEE1) and the DEC is a second liquid-to-air membrane energy exchanger (LAMEE2).
3. The system of claim 2 wherein water removed from the air by the desiccant in the LAMEE1 is transported to the LAMEE2 and used to supply at least a portion of the make up water required for operation of the LAMEE2.
4. The system of claim 1 wherein the DEC is a direct-contact DEC.
5. The system of claim 4 wherein the direct-contact DEC includes at least one of wetted-media and a spray atomizer.
6. The system of claim 1 further comprising a heat exchanger configured to cool the desiccant prior to recirculating the desiccant through the desiccant flow path of the LAMEE.
7. The system of claim 6 wherein the heat exchanger is external to the process plenum.

8. The system of claim 6 wherein the heat exchanger is a polymer fluid cooler.
9. The system of claim 6 wherein the heat exchanger is a liquid to air heat exchanger (LAHX) that uses outdoor air to cool the desiccant.
10. The system of claim 6 wherein the heat exchanger is a liquid to liquid heat exchanger (LLHX).
11. The system of claim 1 further comprising:
a regeneration system configured to increase a concentration of at least a portion of the desiccant exiting the LAMEE.
12. The system of claim 11 wherein the regeneration system comprises a regeneration unit in fluid connection with the LAMEE, wherein the regeneration unit is configured to receive a desiccant stream and separate water from the desiccant, and wherein a first output stream of the regeneration unit is concentrated desiccant and a second output stream of the regeneration unit is distilled water.
13. The system of claim 12 wherein the second output stream is used as make up water for operation of the DEC.
14. The system of claim 12 wherein the first output stream is transported to a desiccant tank configured to receive the first output stream and the desiccant exiting the LAMEE.
15. The system of claim 14 wherein a desiccant output stream exiting the desiccant tank is transported to at least one of the regeneration unit and a heat exchanger configured to reduce a temperature of the desiccant before the desiccant circulates through the LAMEE.
16. The system of claim 15 further comprising a modulating valve configured to control a distribution of desiccant from the desiccant tank to the heat exchanger and the regeneration unit.
17. The system of claim 1 wherein the LAMEE is configured such that the desiccant circulating through the desiccant flow path removes heat from the air to reduce a temperature of the air.

18. The system of claim 1 wherein the process plenum is configured to receive hot process air from an enclosed space and condition the process air such that reduced-temperature air can be returned to the enclosed space.
19. The system of claim 1 wherein the process plenum is configured to receive outdoor air and condition the outdoor air such that reduced-temperature air can be delivered to the enclosed space.
20. The system of claim 1 wherein the process plenum is configured to receive outdoor air that mixes with process air in the air flow path, and wherein the process air is from the enclosed space.
21. The system of claim 1 further comprising a pre-cooler arranged between the LAMEE and the DEC and configured to reduce a temperature of the air passing through the pre-cooler.
22. The system of claim 1 wherein the system operates at or near atmospheric pressure.
23. A system for conditioning air for an enclosed space, the system comprising:
a process plenum configured to direct air from a process inlet to a process outlet, the process inlet receiving air at a first temperature and the process outlet supplying air to the space at a second temperature that is lower than the first temperature;
a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the process plenum, the LAMEE1 configured to use a liquid desiccant flowing through the LAMEE1 to reduce the humidity of the air, a first concentration of water in the liquid desiccant at a fluid inlet of the LAMEE1 being lower than a second concentration of water in the liquid desiccant at a fluid outlet of the LAMEE1; and
a second LAMEE (LAMEE2) arranged inside the process plenum downstream of the LAMEE1, the LAMEE2 configured to operate adiabatically and use water flowing there through to evaporatively cool the air, a temperature of the air at an air outlet of the LAMEE2 being lower than a temperature of the air at an air inlet of the LAMEE2.
24. The system of claim 23 wherein at least a portion of the water flowing through the LAMEE2 is water removed from the air by the liquid desiccant in the LAMEE1.

25. The system of claim 24 wherein a quantity of the water removed from the air by the liquid desiccant in the LAMEE1 is sufficient as the make-up water for operation of the LAMEE2.
26. The system of claim 23 wherein the LAMEE1 is configured to use the liquid desiccant flowing through the LAMEE1 to remove heat from the air, a temperature of the desiccant at a desiccant outlet of the LAMEE1 being higher than a temperature of the desiccant at a desiccant inlet of the LAMEE1.
27. The system of claim 23 further comprising a regenerator system in fluid connection with a desiccant flow path through the LAMEE1, the regenerator system configured to increase a concentration of the liquid desiccant at the fluid inlet of the LAMEE1 relative to the fluid outlet of the LAMEE1.
28. The system of claim 27 wherein the regenerator system comprises:
a regeneration unit configured to receive a desiccant stream at an inlet of the regeneration unit and separate the desiccant and water in the desiccant stream, wherein a first outlet of the regeneration unit includes a concentrated desiccant stream and a second outlet of the regeneration unit includes a distilled water stream.
29. The system of claim 28 wherein the distilled water stream is in fluid connection with the LAMEE2.
30. The system of claim 28 wherein the concentrated desiccant stream is transported to a desiccant storage tank configured to receive the desiccant exiting the LAMEE1, and the concentrated desiccant stream mixes with the desiccant exiting the LAMEE1.
31. The system of claim 30 wherein a desiccant output stream exiting the desiccant storage tank is delivered to at least one of the LAMEE1 and the regeneration unit.
32. The system of claim 31 wherein a modulating valve in the desiccant stream controls a distribution of the desiccant in the desiccant output stream to the LAMEE1 and to the regeneration unit.

33. The system of claim 23 further comprising:
a make-up air unit configured to provide replenishment air to the enclosed space.
34. The system of claim 23 further comprising a liquid-to-air heat exchanger LAHX arranged between the LAMEE1 and the LAMEE2, the LAHX configured to reduce a temperature of the air flowing there through.
35. The system of claim 34 wherein a first portion of the air exiting the LAHX is configured to flow through the LAMEE2 and a second portion of the air exiting the LAHX is configured to flow through a third liquid-to-air membrane energy exchanger (LAMEE3) arranged inside an exhaust plenum in fluid connection with the process plenum.
36. The system of claim 35 wherein a volume of air in the second portion is less than a volume of air in the first portion.
37. The system of claim 35 wherein a cooling liquid circulating through the LAHX is in fluid connection with the LAMEE3, wherein the cooling liquid exits the LAHX and passes through the LAMEE3, and wherein the air from the exhaust plenum cools the cooling liquid in the LAMEE3 prior to recirculating the cooling liquid through the LAHX.
38. The system of claim 23 wherein the process plenum receives outdoor air at the process inlet, and the outdoor air mixes with process air from the enclosed space prior to passing through the LAMEE1.
39. The system of claim 23 further comprising:
a heat exchanger configured to cool the liquid desiccant prior to flowing the liquid desiccant through the LAMEE1, wherein the heat exchanger is a liquid-to-air heat exchanger or a liquid-to-liquid heat exchanger.
40. The system of claim 39 wherein the heat exchanger is located external to the process plenum.
41. A method of conditioning air for an enclosed space, the method comprising:

directing air through a process plenum having a plenum inlet and outlet, the air entering the plenum inlet at a first temperature;

directing the air through a liquid-to-air energy exchanger (LAMEE) arranged inside the plenum, a first moisture content of the air being higher at a LAMEE inlet compared to a second moisture content of the air at a LAMEE outlet;

directing a desiccant through the LAMEE, the desiccant and air separated by a membrane of the LAMEE, the LAMEE configured to remove water from the air using the desiccant, a first concentration of water in the desiccant being lower at a LAMEE inlet compared to a second concentration of water in the desiccant at a LAMEE outlet, the desiccant at the LAMEE outlet being a dilute desiccant;

directing the air through a direct evaporative cooler (DEC) arranged inside the process plenum downstream of the LAMEE, the DEC operating adiabatically to cool the air; and

delivering the air to the enclosed space, the air exiting the plenum outlet at a second temperature lower than the first temperature.

42. The method of claim 41 wherein the LAMEE is configured to remove heat from the air using the desiccant as the desiccant and the air are directed through the LAMEE, and wherein a temperature of the desiccant at the LAMEE outlet is higher than a temperature of the desiccant at the LAMEE inlet.

43. The method of claim 41 wherein directing the air through a DEC comprises:
directing the air through a direct-contact DEC configured to cool the air through direct contact of an evaporative fluid with the air.

44. The method of claim 41 further comprising:
directing the air through a pre-cooler arranged inside the process plenum downstream of the LAMEE and upstream of the DEC.

45. The method of claim 44 wherein the pre-cooler is a cooling coil and the method further comprises:

directing a portion of the air exiting the pre-cooler into an exhaust plenum and through a second LAMEE arranged inside the exhaust plenum;

directing water exiting the cooling coil through the second LAMEE, the second LAMEE configured to cool the water using the air, the water at an outlet of the second LAMEE at a reduced temperature relative to the water at an inlet of the second LAMEE; and

recirculating the water to the cooling coil.

46. The method of claim 41 further comprising regenerating at least a portion of the desiccant exiting the LAMEE.

47. The method of claim 46 wherein regenerating at least a portion of the desiccant comprises:

transporting the dilute desiccant exiting the LAMEE to a desiccant storage tank; and
transporting a portion of the desiccant from the desiccant storage tank to a regeneration unit.

48. The method of claim 47 further comprising:

separating at least a portion of the water from the desiccant by directing the desiccant through the regeneration unit, wherein a first output stream of the regeneration unit is concentrated desiccant and a second output stream of the regeneration unit is distilled water.

49. The method of claim 48 further comprising:

transporting at least a portion of the distilled water in the second output stream to the DEC to provide at least a portion of make-up water for operation of the DEC.

50. The method of claim 48 further comprising:

transporting a portion of the distilled water in the second output stream to a fluid circuit that includes a pre-cooler and an exhaust cooler; and

utilizing the distilled water as make-up water in the fluid circuit, wherein the pre-cooler is arranged inside the process plenum downstream of the LAMEE and upstream of the DEC, and the exhaust cooler is an evaporative cooler configured to cool increased-temperature water exiting the pre-cooler.

51. The method of claim 48 further comprising:

transporting the concentrated desiccant in the first output stream to the desiccant storage tank; and

mixing the concentrated desiccant with the dilute desiccant from the LAMEE, wherein a concentration of the desiccant inside the desiccant storage tank has a desiccant concentration higher than the dilute desiccant and lower than the concentrated desiccant.

52. The method of claim 47 further comprising:
transporting a portion of the desiccant from the desiccant storage tank to the LAMEE for recirculation of the desiccant through the LAMEE.
53. The method of claim 52 further comprising:
directing the desiccant through a heat exchanger upstream of the LAMEE to cool the desiccant prior to recirculation of the desiccant through the LAMEE.
54. The method of claim 52 further comprising:
controlling a volume distribution of desiccant transported from the desiccant storage tank to the LAMEE and to the regeneration unit.
55. The method of claim 54 wherein controlling the volume distribution of desiccant to the LAMEE and to the regeneration unit comprises using a modulating valve located in a desiccant output stream of the desiccant storage tank.