includes second connection bands attached to the bracket assembly, and each of the second connection bands has an exposed free end; the free end of each of the second connection bands is detachably connected to the second end portion of one of the first connection bands.

[0006] Further, each of the second connection bands is attached to a surface of the bracket assembly facing an outer bottom portion of the box body portion, and the free end of each of the second connection bands passes through between the bracket assembly and the box body portion and is exposed. Or, the bracket assembly has hollow channels, and each of the second connection bands extends in one of the hollow channels and is exposed from an end of the one of the hollow channels. Or, the bracket assembly is formed with second guide grooves, each of the second connection bands includes a second guide rod embedded in the each of the second connection band, and each of the second guide rods is adapted to be accommodated in one of the second guide grooves.

[0007] Further, the bracket assembly includes a first frame, a second frame and a connection frame. The first frame is close to an upper periphery of the box body portion. The second frame is located below the first frame. The connection frame is connected between the first frame and the second frame. A contour of the first frame and a contour of the connection frame correspond to a contour of the box body portion. Each of the second connection bands is attached to a surface of the connection frame facing the outer bottom portion of the box body portion through a fastener, and the free end of each of the second connection bands is exposed at an end of the connection frame. Or, the connection frame is formed with the hollow channels, and the free end of each of the second connection bands is exposed from an end of the connection frame. Or, the connection frame is formed with the second guide grooves.

[0008] Further, the carrier includes an accommodation body, and the accommodation body includes the box body portion. The accommodation body has a top opening, and the canopy portion is covered on the accommodation body to cover the top opening. A frame at a bottom of the canopy portion includes two opposite first side edges and two opposite second side edges, and the two second side edges are located between the two first side edges. The accommodation body includes two opposite first side surfaces and two opposite second side surfaces, and the two second side surfaces are located between the two first side surfaces. At least one of the connection enhancement members is arranged between each of the first side edges and the first side surface corresponding to the each of the first side edges, and at least one of the connection enhancement members is arranged between each of the second side edges and the second side surface corresponding to the each of the second side edges.

[0009] Further, the carrier includes an accommodation body, and the accommodation body includes the box body portion. The accommodation body has a top opening, and the canopy portion is covered on the accommodation body to cover the top opening. The canopy portion includes two half canopies oppositely arranged, the two half canopies are a first half canopy and a second half canopy respectively, and an edge of the first half canopy and an edge of the second half canopy opposite to each other are detachably connected through at least one connection assembly. Or, the canopy portion includes a fixed canopy and a movable canopy, and the fixed canopy is non-detachably connected to the accommodation body. A bottom of the movable canopy is detachably connected to the accommodation body through at least one of the connection enhancement members, and/or, an edge of the movable canopy and an edge of the fixed canopy opposite to