

Title: Attachment device for a slide channel or guide rail

Description

The invention relates to an attachment device for a slide channel or guide rail, which are used in particular for door closers. The sliding block of a door closer is guided for example in a slide channel of this species. As the sliding block is connected to the arm of the door closer, the slide channel is substantially C-shaped, i.e. it has a lateral opening in which the arm of the door closer engages with the associated sliding block. The slide channel itself is attached to a door or to a frame. An attachment device disposed on the face side of the slide channel serves for this purpose in a known manner, which device has a clamping piece engaging into the slide channel and, outside the profile of the slide channel, a connecting plate integrally connected to the clamping piece. The connecting plate has a bore by means of which the connecting plate and thus the slide channel can be connected to the door or to the frame. In prior art devices, the blocking between the clamping piece, which engages on the face side in the slide channel, and the slide channel is realized by a clamping screw penetrating the clamping piece, which screw allows to achieve interlocking between the clamping piece and the slide channel. On the one hand, this requires a threaded bore in the clamping piece, which for visual reasons needs

in addition to be countersunk; on the other hand, there is the risk that the attachment bolt, which is detectable from the outside, may unintentionally self-disengage.

It is an object of the invention to improve an attachment
5 device of the species mentioned above in that an expensive and visually unattractive screw connection between the clamping piece and the slide channel or guide rail can be eliminated. In an advantageous further development of the invention, the attachment device is to
10 be formed in that a technically simple and visually appealing cover for the attachment device and thus for the termination on the face side of the profile of the slide channel or guide rail is achieved.

The invention solves of the given problem with the teaching
15 according to claim 1.

Therefore, on at least one outside wall, the clamping piece has a tothing, which abuts against an inside wall of the profile of the slide channel or guide rail by means of a press fit, and which, in an advantageous embodiment of
20 the invention, at two diametrically opposite outside walls abuts against two opposite inside walls of the profile.

According to the above technical teaching, the clamping piece, which is integrally formed with the connecting plate, can be non-positively pressed into the slide channel or

guide rail on the face side without requiring a screw connection between the clamping piece and the guide rail.

Further advantageous embodiments of the invention are the subject matter of the dependent claims.

- 5 The clamping piece's toothing is preferably formed as an inclined toothing, the inclination of the teeth being such that pressing the clamping piece into the profile requires less expenditure of energy than the principally possible release of the clamping piece from the profile, which accordingly
10 requires a higher expenditure of energy. Thus, a reliable blocking of the clamping piece in the profile is guaranteed.

The connecting plate, which is integrally formed with the clamping piece, has a stop face, which, with the clamping piece being completely inserted into the profile, abuts
15 against an end surface of the profile and thus blocks the position of the clamping piece in the profile.

Moreover, the connecting plate is formed such that a surface of the connecting plate abutting against the sub-construction extends flush with an outside wall of the profile
20 oriented towards the sub-construction.

In a particularly advantageous embodiment of the invention, the connecting plate has locking components for clampingly connecting a cover cap, which overlaps the connecting plate and covers the profile on the face side,

the connecting plate having projections and/or recesses at the opposite lateral surface thereof extending orthogonally in relation to the surfaces adjoining the sub-construction, whereby, projections, which are disposed in advantageous manner on the opposite lateral surfaces of the connecting plate, form the complementary locking components for the recesses disposed at the cover cap. Thus, the connecting plate does not only serve as an attachment for the slide channel or guide rail at a sub-construction, but furthermore it has the complementary locking components for a cover cap, which forms a covering for both the connecting plate and for the entire covering on the face side of the profile of the slide channel or guide rail.

The bore, in a way which is known per se, is formed as an oblong hole in the connecting plate, in order to be able to compensate for important tolerances when connecting the slide channel or guide rail to a sub-construction.

Generally the slide channels or guide rails consist of an aluminium alloy, however, principally they may be produced from any optional material. As a sufficient frictional connection is required between the toothing of the clamping piece and the profile of the slide channel or guide rail, the choice of material of the attachment device, i.e. particularly of the clamping piece, needs to match the material of the slide channel or guide rail. As a result, the embodiment of the invention may require the use of

appropriate plastic material, aluminium material or zinc-die cast for the attachment device.

In the following, the invention will be described in more detail, reference being made to one possible exemplary
5 embodiment, in which

Figure 1: shows a view on the end surface of the attachment device in a slide channel.

Figure 2: shows the section according to line II-II in Figure 1.

10 Figure 3: shows a lateral view of the attachment device according to Figure 1.

Figure 4: shows a plane view according to Figure 3.

Figure 5: shows a perspective illustration of the attachment device.

15 Figure 6: shows the slide channel including the attachment device and the cover cap in a perspective exploded view.

Figure 7: shows the section VII-VII through the cover cap according to Figure 6.

20 Figure 8: shows the detail X in an illustration, which is enlarged in relation to Figure 7.

According to the illustrated drawings, an attachment device 2 is disposed in the area of a termination 6 on the face side of a profile 4 of a slide channel 1. The attachment device 2 substantially consists of a clamping piece 5 and of a
5 connecting plate 8, which is provided with a bore 7. As particularly illustrated in Figure 2, the clamping piece 5, on two diametrically opposite sides, has a toothing 11, which is formed as an inclined toothing and, in the exemplary embodiment according to Figure 2 in the plane of the
10 illustration, abuts against an upper inside wall 10 and against a lower inside wall 13 of the profile 4. The toothing 11 is formed respectively on diametrically opposite outside walls 12 of the clamping piece 5. If the clamping piece 5 is inserted into the profile 4, a stop face 15 of the connecting
15 plate 8, which plate is integrally formed with the clamping piece 5, abuts against an end surface 14 of the slide channel 1 and thus blocks the clamping piece 5 in its intended position. A surface 16 of the connecting plate 8 oriented towards the sub-construction 3 extends flush with
20 an outside wall 17 of the profile 4 oriented towards the sub-construction 3.

As can be seen particularly in Figure 5, projections 20 are formed on opposite lateral surfaces 19 of the connecting plate 8, which are overlapped by recesses 21 (see Figures
25 7 and 8) of a cover cap 18, such that the recesses 21 of

the cover cap 18 form complementary locking components for the projections 20 of the connecting plate 8.

List of reference numerals

	1	slide channel
	2	attachment device
	3	sub-construction
5	4	profile
	5	clamping piece
	6	termination on the face side
	7	bore
	8	connecting plate
10	9	outside wall
	10	inside wall
	11	toothing
	12	outside wall
	13	inside wall
15	14	end surface
	15	stop face
	16	surface
	17	outside wall
	18	cover cap
20	19	lateral surfaces
	20	projections
	21	recesses
	X	detail

Patent claims

1. An attachment device (2) for a slide channel or guide rail (1), in particular a slide channel or guide rail for a door closer, consisting of a clamping piece (5), which is detachably inserted in a profile (4) of the slide channel or guide rail (1) on the face side and interlocked with the profile (4), and of a connecting plate (8), which is integrally formed with the clamping piece (5), is located outside the face side termination (6) of the profile (4), and has a bore (7) for the connection to a sub-construction (3), characterized in that the clamping piece (5), on at least one outside wall (9), has a tothing (11), which abuts against an inside wall (10) of the profile (4) of the slide channel or guide rail (1) by means of a press fit.
5
10
15
2. An attachment device according to claim 1, characterized in that the clamping piece (5) has toothings (11) on two diametrically opposite outside walls (9, 12), which abut against two opposite inside walls (10, 13) of the profile (4).
20
3. An attachment device according to claim 1 or 2, characterized in that the tothing (11) is formed as an inclined tothing.

4. An attachment device according to one of the claims 1 to 3, characterized in that the connecting plate (8) has a stop face (15) abutting against an end surface (14) of the profile (4).
- 5 5. An attachment device according to one of the claims 1 to 4, characterized in that a surface (16) of the connecting plate (8) abutting against the sub-construction (3) extends flush with an outside wall (17) of the profile (4) oriented towards the
10 sub-construction (3).
6. An attachment device according to one of the claims 1 to 5, characterized in that the connecting plate (8) has locking components for clampingly connecting a cover cap (18), which overlaps the
15 connecting plate (8) and covers the profile (4) on the face side.
7. An attachment device according to claim 6, characterized in that the connecting plate (8) has projections (20) and/or recesses on its opposite
20 lateral surfaces (19) extending orthogonally to the surface (16), which abuts against the sub-construction (3).
8. An attachment device according to claim 7, characterized in that projections (20), which are
25 disposed on the opposite lateral surfaces (19) of

the connecting plate (8), form the complementary locking components for recesses (21) disposed at the cover cap (18).

- 5 9. An attachment device according to one of the claims 1 to 8, characterized in that the bore (7) in the connecting plate (8) is formed as an oblong hole.
- 10 10. An attachment device according to one of the claims 1 to 9, characterized in that the attachment device (2) is made from plastic material.
11. An attachment device according to one of the claims 1 to 9, characterized in that the attachment device (2) is made from an aluminium material.
- 15 12. An attachment device according to one of the claims 1 to 9, characterized in that the attachment device (2) is made from zinc die casting.