

RADIO FREQUENCY MAGNETIC FIELD UNIT

Cross-Reference to Related Applications

- 5 This application claims priority under 35 U.S.C. 119(e) from U.S. Provisional Application Serial No. 60/222,144, filed July 31, 2000, which is incorporated by reference herein.

Field

- This invention relates to radio frequency magnetic field units suitable for
10 use in connection with an imaging and/or spectroscopy system.

Background

- Radio frequency magnetic field units, such as volume coils, are used in connection with imaging and/or spectroscopy systems, such as but not limited to magnetic resonance imaging systems, nuclear magnetic resonance imaging
15 systems, functional magnetic resonance imaging systems, and electron spin resonance systems.

- A problem with many cylindrical form volume coils is that they provide limited access to the coil volume. These cylindrical form volume coils can be accessed only through the ends of the cylinders or between the radio frequency
20 (RF) current carrying rungs or loops. The "between the rung" or lateral access is further limited when the coil is shielded. A Faraday shield on a birdcage for example, completely screens the lateral walls of the coil cylinder with typically a copper clad, etched circuit board material. The result is a "copper can."
 Similarly, the transverse electromagnetic (TEM) coil circuits are composed of a
25 cylindrical symmetrical array of conductor rungs in parallel resonance with and enclosed by a copper resonant cavity. The limited access provided by end access or "between the rung" access to the coil volume affects a subject confined to the coil volume and physicians or technicians treating or interacting with the subject. Some subjects are claustrophobic and cannot tolerate confinement in a volume
30 coil, while some medical procedures, such as brain surgery, require access to the subject during imaging. For these and other reasons there is a need for the present invention.

Brief Description of the Drawings

FIG. 1A is an illustration of some embodiments of an apparatus including a radio frequency magnetic field unit according to the teachings of the present invention;

5 FIG. 1B is an illustration of some embodiments of an imaging unit including a radio frequency magnetic field unit according to the teachings of the present invention;

FIG. 2A is an illustration of some embodiments of an alternative embodiment of an apparatus including a radio frequency magnetic field unit
10 according to the teachings of the present invention;

FIG. 2B is an illustration of some alternative embodiments of an imaging unit including a radio frequency magnetic field unit according to the teachings of the present invention;

FIG. 2C is an illustration of some embodiments of the apparatus
15 including the radio frequency magnetic field unit shown in FIG. 2A configured for use in a clinical setting;

FIG. 3A-3D are illustrations of some embodiments of the structure of a volume coil according to the teachings of the present invention; and

FIG. 4 is an illustration of one embodiment of a current element suitable
20 for use in connection with the radio frequency magnetic field units of the present invention.

Description

In the following detailed description of the invention, reference is made to the accompanying drawings which form a part hereof, and in which are
25 shown, by way of illustration, specific embodiments of the invention which may be practiced. In the drawings, like numerals describe substantially similar components throughout the several views. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention. Other embodiments may be utilized and structural, logical, and electrical changes may
30 be made without departing from the scope of the present invention. The following detailed description is not to be taken in a limiting sense, and the

scope of the present invention is defined only by the appended claims, along with the full scope of equivalents to which such claims are entitled.

Radio frequency magnetic field units that include an aperture that is substantially unobstructed and located in a radio frequency magnetic field unit and radio frequency magnetic field units that include side apertures are described. When a radio frequency magnetic field unit that includes a first aperture that is substantially unobstructed is used in connection with an imaging system, the medical benefits associated with the use of an imaging system can be extended to claustrophobic subjects. When a radio frequency magnetic field unit that includes side apertures is used in connection with an imaging system, the medical benefits associated with the use of an imaging system can be extended to subjects that have difficulty fitting into a standard radio frequency magnetic field unit. Methods for transforming a radio frequency magnetic field unit that lacks an aperture that is substantially unobstructed into a radio frequency magnetic field unit that has an aperture that is substantially unobstructed, and methods for transforming a radio frequency magnetic field unit that lacks side apertures into a radio frequency magnetic field unit that has side apertures are also described.

In addition, including an aperture in a radio frequency magnetic field unit, such as a coil, allows parts of the anatomy to project from the coil (e.g. nose, or arms). This allows the rest of the coil to be much smaller and fit much closer to a subject. Small, close fitting coils improve image signal efficiency which results in images of higher resolution being acquired in less time using less power.

FIG. 1A is an illustration of some embodiments of an apparatus 100 comprising a radio frequency magnetic field unit 102 according to the teachings of the present invention. The radio frequency magnetic field unit 102 includes a first aperture 104 and a second aperture 106.

The radio frequency magnetic field unit 102 generates a desired magnetic field 108. The desired magnetic field 108 is not limited to a magnetic field having a particular magnitude and direction. Preferably, the desired magnetic field 108 has a magnitude and direction suitable for use in imaging an object,

such as a human head, in an imaging system, such as but not limited to a magnetic resonance imaging system, a magnetic resonance spectroscopy system, a functional magnetic resonance imaging system, or an electron spin resonance system.

- 5 The radio frequency magnetic field unit 102 is not limited to a particular type of radio frequency magnetic field unit. In one embodiment, the radio frequency magnetic field unit 102 is a TEM cavity resonator. A TEM cavity resonator includes one or more current elements having controllable elements, such as inductors and capacitors, that are varied to tune the transmission line
10 resonator. In some embodiments, TEM cavity resonators include two open ends. In alternative embodiments, TEM cavity resonators include one open end and one closed end.

 The radio frequency magnetic field unit 102 is not limited to a particular number of current elements (shown in FIG. 4). Current elements 110-115 shown
15 in FIG. 1A are illustrations only and no attempt is being made to depict the detailed components of the current elements. In some embodiments, the radio frequency magnetic field unit 102 includes current elements 110-115. The current elements 110-115 are preferably arranged such that none of the elements 110-115 obstruct the second aperture 106, but the current elements 110-115 are
20 not limited to a particular arrangement. In some embodiments, the current elements 110-115 are asymmetrically arranged, physically disconnected from one another and reactively coupled. In alternative embodiments, the current elements 110-115 are arranged to "enclose" a substantially cylindrical volume. In some embodiments, each of the current elements 110-115 is a resonant current
25 element inductively coupled to at least one other current element. In alternative embodiments, each of the current elements 110-115 is a resonant current element capacitively coupled to at least one of the current elements 110-115. When used in connection with an imaging system (shown in FIG. 1B), the magnetic field unit 102 is tuned to a frequency suitable to image a particular object or subject.

- 30 The radio frequency magnetic field unit 102 is not limited to a particular shape or volume. Preferably, the shape and volume of the radio frequency magnetic field unit 102 approximate the shape and volume of the object or

subject to be imaged. In one embodiment, the radio frequency magnetic field unit 102 has a substantially cylindrical shape, including a diameter and a length sufficient to receive a human head. In an alternative embodiment, the radio frequency magnetic field unit 102 has a substantially cylindrical shape that includes a longitudinal axis 116 and a surface 118 that is substantially parallel to the longitudinal axis 116. The surface 118 need not be continuous. The current elements 110-115 are arranged substantially parallel to the longitudinal axis.

The first aperture 104 provides a port for introducing an object or subject into the radio frequency magnetic field unit 102. For example, a human head (not shown) can be introduced into the radio frequency magnetic field unit 102 at the first aperture 104. The head is preferably oriented within the radio frequency magnetic field unit 102 such that the eyes are directed toward the second aperture 106. With this orientation, the subject avoids the claustrophobic effects often experienced by subjects introduced into a radio frequency magnetic field unit that lacks a second aperture that is substantially unobstructed. The first aperture 104 is not limited to a particular alignment with respect to the radio frequency magnetic field unit 102. In one embodiment, the first aperture 104 has a center of mass point 120 that is substantially aligned with the longitudinal axis 116. Such an alignment permits easy introduction of the subject into the radio frequency magnetic field unit 102. The first aperture 104 is formed at an end of the radio frequency magnetic field unit 102. An end of the radio frequency magnetic field unit 102 is located at an end of the current elements 110-115.

The first aperture 104 is preferably contiguous to the second aperture 106. A contiguous second aperture 106 permits relatively easy introduction of a subject into the radio frequency magnetic field unit 102 and reduces the likelihood that the subject will experience claustrophobic effects during imaging by providing a contiguous open space that includes the first aperture 104 and the second aperture 106. The second aperture 106 also allows a subject to see outside the radio frequency magnetic field unit 102 and allows a physician or technician access to the eyes, nose and mouth of the subject.

The second aperture 106 comprises an area 122 including an unobstructed area 124 and a potentially obstructed area 126. An area is

unobstructed, if the area is substantially transparent. An area is obstructed, if the area is not substantially transparent. Preferably, the area 122 does not include an obstructed area. The area 122 is not limited to a particular size.

5 The second aperture 106 has a center of mass point 130 (not drawn to scale) and a first aperture axis 132. In one embodiment, the first aperture axis 132 passes through the center of mass point 130, intersects the longitudinal access 116 and is substantially perpendicular to the longitudinal access 116. In one embodiment, the second aperture 106 subtends an arc 134 having an arc length 136 of between about 0° and about 90° as traced out by the first aperture
10 axis 132 rotating about the longitudinal axis 118. The second aperture 106 subtending an arc 134 having an arc length 136 of greater than 0° and about 90° reduces claustrophobic effects in a human subject. However, an arc length 136 of greater than about 90° increases the difficulty in generating the desired magnetic field 108.

15 The second aperture 106 permits the manufacture of a radio frequency magnetic field unit 102 that closely fits the head of a human subject having a large nose. A radio frequency magnetic field unit that lacks the second aperture 106 must be sized to accommodate the large nose of a subject and therefore cannot be designed to closely fit the head of a human subject having a large
20 nose. Since a close fitting radio frequency magnetic field unit produces higher quality images than a larger loosely fitting radio frequency magnetic field unit, the radio frequency magnetic field unit 102 including the second aperture 106 produces higher quality images than a radio frequency magnetic field unit that lacks the second aperture 106.

25 An imaging unit 139 can be mounted on the radio frequency magnetic field unit 102 to provide a communication link to the second aperture 106. The imaging unit 139 is located with respect to the second aperture 106 such that the imaging unit 139 provides a communication link to a subject whose head is positioned in the radio frequency magnetic field unit 102. The imaging unit 139
30 is not limited to a particular type of imaging unit. In one embodiment, the imaging unit 139 comprises a mirror. In an alternative embodiment, the imaging

unit 139 comprises a prism. In still another alternative embodiment, the imaging unit 139 comprises a projection system.

In some embodiments, one or more apertures 144 and 145 are formed on a side of the radio frequency magnetic field unit 102 to permit access to a subject's ears. These apertures can be formed by removing a current element from a radio frequency magnetic field unit. In other embodiments, an auditory communication device 146 is attached to one or more of the one or more apertures 144 and 145 to communicate with a subject or provide auditory protection for the subject. The communication device 146 is preferably capable of providing active or passive auditory protection.

A radio frequency magnetic field unit lacking a second aperture can be transformed into the radio frequency magnetic field unit 102 that includes the second aperture 106. In one embodiment of a method to transform a radio frequency magnetic field unit lacking a second aperture into the radio frequency magnetic field unit 102 that includes the second aperture 106, one current element is removed from the radio frequency magnetic field unit lacking a second aperture to form the radio frequency magnetic field unit 102 that includes the second aperture 106. Removing one current element from a radio frequency magnetic field unit lacking a second aperture creates a void in the radio frequency magnetic field unit lacking a second aperture. This void provides an area in which to form the second aperture 106. After removing a current element from the radio frequency magnetic field unit lacking a second aperture, currents to produce the desired magnetic field 108 are calculated for the remaining current elements. In an alternative embodiment, two or more adjacent current elements are removed from a radio frequency magnetic field unit lacking a second aperture to form the radio frequency magnetic field unit 102 that includes the second aperture 106. Removing two or more adjacent current elements from the radio frequency magnetic field unit lacking a second aperture creates a void in the radio frequency magnetic field unit lacking a second aperture. This void provides an area in which to form the second aperture 106 of the radio frequency magnetic field unit 102. After removing two or more current elements from the radio frequency magnetic field unit lacking a second aperture, currents

to produce the desired magnetic field 108 are calculated for the remaining electronic circuits.

FIG. 1B is an illustration of some embodiments of an imaging unit 140 including a radio frequency magnetic field unit 102 according to the teachings of the present invention. The imaging unit 140 includes a static field magnetic field unit 142 and the radio frequency magnetic field unit 102 located within the static field magnetic field unit 142. Preferably, the static field magnetic field unit 142 produces a magnetic field having a high magnetic field strength. A high magnetic field strength enables the production of high resolution images by the imaging unit 140. However, the radio frequency magnetic field unit 102 is not limited to use in connection with a particular static magnetic field or a static field magnetic field unit that produces a particular magnetic field strength. The radio frequency magnetic field unit 102 is suitable for use in connection with any static field magnet used in connection with an imaging unit.

FIG. 2A is an illustration of some embodiments of an apparatus 200 comprising a radio frequency magnetic field unit 202 according to the teachings of the present invention. The radio frequency magnetic field unit 202 includes a pair of end apertures 204 and 205, a first side aperture 206 and a second side aperture 208.

The radio frequency magnetic field unit 202 generates a desired magnetic field 210. The desired magnetic field 210 is not limited to a magnetic field having a particular magnitude and direction. Preferably, the desired magnetic field 210 has a magnitude and direction suitable for use in imaging an object, such as a human body, in an imaging system, such as but not limited to a magnetic resonance imaging system, a functional magnetic resonance imaging system or an electron spin resonance system.

The radio frequency magnetic field unit 202 is not limited to a particular type of radio frequency magnetic field unit. In one embodiment, the radio frequency magnetic field unit 202 is a TEM cavity resonator. A TEM cavity resonator includes one or more current elements having controllable elements that are varied to tune the transmission line resonator. In one embodiment, the radio frequency magnetic field unit 202 comprises a first group of current

elements 212 and a second group of current elements 214. In one embodiment, the first group of current elements 212 include at least one current element, such as current elements 216-218, and the second group of current elements 214 include at least one current element, such as current elements 220-222. The first
5 group of current elements 212 and the second group of current elements 214 are preferably arranged such that none of the current elements 216-218 or the current elements 220-222 obstruct the first side aperture 206 or the second side aperture 208. In one embodiment, the first group of current elements 212 are separated from the second group of current elements 214 by a separation distance 228 of
10 between about 15 centimeters and about 30 centimeters which is the area available to form the first side aperture 206 and the second side aperture 208. A separation distance of less than about 15 centimeters is insufficient to permit extremities, such as arms or legs, or excess body mass, of a subject to fit into the first side aperture 206 and the second side aperture 208. A separation distance
15 228 of greater than about 30 centimeters results in the radio frequency magnetic field unit 202 having a volume significantly greater than necessary to receive a human body. When used in connection with an imaging system (shown in FIG. 2B), the magnetic field unit 202 is tuned to a frequency suitable to image a particular object or subject.

20 The first side aperture 206 and the second side aperture 208 permit the extremities or excess body mass of a subject (not shown) to be positioned outside the radio frequency magnetic field unit 202 when the subject is located inside the radio frequency magnetic field unit 202. The first side aperture 206 and the second side aperture 208 are substantially parallel to the first group of
25 current elements 212 and the second group of current elements 214. The first side aperture 206 and the second side aperture 208 are preferably free of physical obstructions. A physical obstruction is a structure that prevents the extremities or excess body mass of a subject from extending into and through the first side aperture 206 or the second side aperture 208. The first side aperture 206 and the
30 second side aperture 208 also permit the radio frequency magnetic field unit 202 to receive subjects larger than an inside diameter 230 of the radio frequency magnetic field unit 202 without increasing the inside diameter 230 of the radio

frequency magnetic field unit 202. For many subjects, the first side aperture 206 and the second side aperture 208, by allowing extremities or excess body mass to extend outside the radio frequency magnetic field unit 202, increase the subject's comfort when positioned inside the radio frequency magnetic field unit 202. A

5 comfortable subject tends to move less during imaging, and therefore fewer imaging retakes are required and higher quality images are obtained when the subject is imaged. In addition, the smaller, closer coil improves image quality significantly for body coils. The smaller sized coil can be made to resonate efficiently at the high frequencies required for high field strength imaging.

10 The radio frequency magnetic field unit 202 is not limited to a particular shape or volume. Preferably, the shape and volume of the radio frequency magnetic field unit 202 approximate the shape and volume of the object or subject to be imaged. For example, a substantially cylindrical radio frequency magnetic field unit having a length 232 of about 100 centimeters and the
15 diameter 230 of about 60 centimeters has a shape that approximates the shape of a human body. In one embodiment, the radio frequency magnetic field unit 202 has a substantially cylindrical shape, including a diameter and a length sufficient to receive an adult human body.

In an alternative embodiment, the radio frequency magnetic field unit
20 202 has a substantially cylindrical shape that includes a longitudinal axis 234 and surfaces 236 and 238 that are preferably curved and substantially parallel to the longitudinal axis 234. The surfaces 234 and 236 need not be continuous. The first group of current elements 212 including the at least three current elements 216-218 and the second group of current elements 214 including the at
25 least three current elements 220-222 are arranged to "enclose" a substantially cylindrical volume.

The end aperture 204 provides a port for introducing an object or subject into the radio frequency magnetic field unit 202. For example, a human body (not shown) can be introduced into the radio frequency magnetic field unit 202 at
30 the end aperture 204. The end aperture 204 is not limited to a particular alignment with respect to the radio frequency magnetic field unit 202. In one embodiment, the end aperture 204 includes a center of mass point 240 that is

substantially aligned with the longitudinal axis 234.

In one embodiment, the first side aperture 206 and the second side aperture 208 are contiguous to end aperture 204. A contiguous relationship between the first side aperture 206, the second side aperture 208 and the end aperture 204 permits easy introduction of a subject into the radio frequency magnetic field unit 202. The first side aperture 206 has a width or separation distance 228 and the second side aperture 208 has a width or separation distance 244. The width or separation distance 228 is preferably about equal to the width or separation distance 244.

10 In some embodiments, the radio frequency magnetic field unit 202 includes a top-half 247 and a bottom-half 248, the top-half 247 capable of being mechanically attached and detached to the bottom-half 248 at the first side aperture 206 or the second side aperture 208. In one embodiment, an attachment device 249, such as a hinge or flexible bracket, attaches the top-half 247 to the
15 bottom half 248.

A radio frequency magnetic field unit lacking a first side aperture and a second side aperture can be transformed into the radio frequency magnetic field unit 202 including the first side aperture 206 and the second side aperture 208. In one embodiment of a method to transform a radio frequency magnetic field
20 unit lacking a first side aperture and a second side aperture into a radio frequency magnetic field unit 202 that includes the first side aperture 206 and the second side aperture 208, two non-adjacent current elements are removed from the radio frequency magnetic field unit lacking a first side aperture and a second side aperture. Preferably, the two non-adjacent current elements are located opposite
25 from one another. Removing two non-adjacent current elements from the radio frequency magnetic field unit that lacks a first side aperture and a second side aperture creates two voids in the radio frequency magnetic field unit. These voids provide areas in which to form the first side aperture 206 and the second side aperture 208. After removing two non-adjacent current elements from the
30 radio frequency magnetic field unit lacking a first side aperture and a second side aperture, currents to produce the desired magnetic field 210 are calculated for the remaining current elements.

FIG. 2B is an illustration of some embodiments of an imaging unit 250 including the radio frequency magnetic field unit 202 according to the teachings of the present invention. The imaging unit 250 includes a static-field magnetic field unit 252 and the radio frequency magnetic field unit 202 located within the static-field magnetic field unit 252. Preferably, the static-field magnetic field unit 252 produces a magnetic field having a high magnetic field strength. A high magnetic field strength enables the production of high resolution images by the imaging unit 250. However, the radio frequency magnetic field unit 202 is not limited to use in connection with a static-field magnetic field unit or a static-field magnetic field unit that produces a particular magnetic field strength. The radio frequency magnetic field unit 202 is suitable for use in connection with any static-field magnetic field unit used in connection with an imaging unit.

FIG. 2C is an illustration of some embodiments of the apparatus including the radio frequency magnetic field unit 202 shown in FIG. 2A configured for use in a clinical setting. As can be seen in FIG. 2C, a subject easily and comfortably fits into a close fitting radio frequency magnetic field unit 202 which makes radio frequency magnetic field unit 202 particularly well suited for use in heart, lung and breast imaging applications.

Although the embodiments described above were directed to radio frequency magnetic field units for use in connection with imaging a human head and body, the radio frequency magnetic field units 102 and 202 are not limited to use in connection with imaging a human head and body. The radio frequency magnetic field units 102 and 202 are suitable for use in connection with imaging a wide range of subjects including but not limited to human extremities, such as arms, legs, joints, hands and feet, non-human subjects, such as dogs, cats, mice, rats, horses, and primates and the extremities of those non-human subjects.

FIG. 3A-3D are illustrations of some embodiments of the structure of a volume coil 300 according to the teachings of the present invention. The volume coil 300 includes a cavity wall 301, which is not shaded so that the underlying structure of the volume coil 300 can be seen. The volume coil 300 shown in FIG. 3A-3D includes current elements 302-308. The volume coil 300 shown in FIG. 3A includes a radio frequency conductive front end ring 310 and a radio

frequency conductive backplane 312. The radio frequency conductive front end ring 310 and the radio frequency conductive backplane 312 are coupled to the current elements 302-308.

The volume coil 300 shown in FIG. 3B includes a radio frequency
5 conductive front end ring 314 having a gap 316 and a radio frequency conductive backplane 318 truncated to the current elements 302 and 308. The radio frequency conductive front end ring 314 and the radio frequency conductive backplane 318 are coupled to the current elements 302-308.

The volume coil 300 shown in FIG. 3C includes a radio frequency
10 conductive front end ring 310 and a radio frequency conductive back end ring 319. The radio frequency conductive front end ring 310 and the radio frequency conductive back end ring 319 are coupled to the current elements 302-308.

The volume coil 300 shown in FIG. 3D includes a radio frequency
15 conductive front end ring 314 having a gap 316 and a radio frequency conductive back end ring 320 having a gap 322. The radio frequency conductive front end ring 314 and the radio frequency conductive back ring 320 are coupled to the current elements 302-308.

As can be seen in FIGs. 3A-3D, the volume coil 300 includes an aperture 324 formed between the current elements 302 and 308. Also, as can be seen in
20 FIG. 3A-3D, the aperture 324 is formed by removing a current element 326 (shown by a dashed line) from a regular or symmetrical arrangement of current elements that includes current elements 302-308 and current element 326 (shown by a dashed line). In an alternative embodiment, the current element 326 is removed from the top 328 of the volume coil 300. In another alternative
25 embodiment, the current element 326 is displaced (rather than removed) to form an the aperture 324.

Each of the end rings 310, 314, 319 and 320 comprise an open end 330 of the volume coil 300 and each of the backplanes 312 and 318 comprise a closed end 332 of the volume coil 300.

30 The volume coil 300 includes an impedance. In one embodiment, an adjustable impedance is included in each of the current elements 302-308. The adjustable impedance, in one embodiment, is a capacitance. The adjustable

impedance, in an alternative embodiment, is an inductance.

In one embodiment, the cavity wall 301 comprises return elements of the current elements 302-308. In an alternative embodiment, the cavity wall 301 comprises a slotted shield. As can be seen in FIG. 3A-3D, the cavity wall 301
5 includes an aperture in line with the missing or displaced current element 326.

The volume coil 300 is suitable for use in imaging a wide range of objects and subjects including but not limited to heads, ankles, feet, and other extremities.

Each of the radio frequency magnetic field units 102 and 202 and the
10 volume coils 300 described above is suitable for use as a double tuned coil, a multiply tuned coil, a circularly polarized coil, a coil doubly tuned by the Vaughan method and an actively detuned coil. A double tuned coil is driven at two frequencies. A multiply tuned coil is driven at multiple frequencies. A circularly polarized coil is driven to impart a circularly polarized radio frequency
15 magnetic field. The Vaughan method of doubly detuning a coil is described in U.S. Patent 5,557,247 titled "High Frequency Volume coils for Nuclear magnetic Resonance Applications" which is hereby incorporated herein by reference. Each of the radio frequency magnetic field units 102 and 202 and the volume coil 300 are capable of being actively detuned/retuned for use with a
20 local receiving coil by adjusting the current elements included in the coil. The current elements are adjusted by changing the impedance of the current elements.

FIG. 4 is an illustration of one embodiment of a current element 400 suitable for use in connection with the radio frequency magnetic field units of
25 the present invention. The current element 400 includes a shield or cavity wall section 402 resonant with a conductor 404. The cavity wall section 402 is formed from a conductive material and the conductor 404 is formed from a conductive material. In one embodiment, the cavity wall section 402 is formed from a conductive mesh. A plurality of current elements 400 can be arranged to
30 form an "enclosure." In one embodiment, a plurality of current elements 400 are arranged to form a cylindrical enclosure (not shown). In a cylindrical enclosure, the shield or cavity wall section 402 is oriented to the outside of the enclosure

and the conductor 404 is oriented to the inside of the enclosure. Current elements, such as current element 400, are further described in U.S. Patent 5,557,247 which is hereby incorporated by reference herein.

Although specific embodiments have been described and illustrated
5 herein, it will be appreciated by those skilled in the art, having the benefit of the present disclosure, that any arrangement which is intended to achieve the same purpose may be substituted for a specific embodiment shown. This application is intended to cover any adaptations or variations of the present invention. Therefore, it is intended that this invention be limited only by the claims and the
10 equivalents thereof.

What is claimed is:

1. An apparatus comprising: a volume coil including a plurality of current elements, the volume coil for magnetic resonance having an aperture formed by
5 removal or displacement of one or more current elements from a regular or symmetric pattern or arrangement of current elements wherein each current element includes a transmission line segment having a first current path and a parallel return current path for the first current path, wherein, for each current element of the plurality of current elements the first current path is resonant with the parallel
10 current return path.
2. The apparatus of claim 1, wherein the remaining pattern or arrangement of current elements is capable of producing a desired field and the desired field is restored, compensated or otherwise effected by adjustment of currents in the
15 plurality of current elements.
3. The apparatus of claim 2, wherein the volume coil includes a top and one or more of the regular or symmetric pattern or arrangement of current elements is removed from the top for improved access from the top and the desired field is
20 restored.
4. The apparatus of claim 3, wherein the volume coil capable of being used in head imaging.
- 25 5. The apparatus of claim 2, wherein the volume coil includes an open end and a closed end, the closed end being closed by a conductive plane.
6. The apparatus of claim 5, wherein the volume coil is capable of being used in head imaging.
30
7. The apparatus of claim 2, wherein the volume coil includes two open ends.

8. The apparatus of claim 7, wherein the volume coil is capable of being used in head imaging.
- 5 9. The apparatus of claim 2, wherein the volume coil is capable of being used in head imaging.
10. The apparatus of claim 2, wherein the volume coil is capable of being used in extremity imaging.
- 10 11. The apparatus of claim 2, wherein the volume coil is capable of being used in foot and ankle imaging.
12. The apparatus of claim 2, wherein the volume coil includes an impedance
15 and the impedance is adjusted to control current in the plurality of current elements.
13. The apparatus as in 12, wherein the impedance is adjusted by adjusting a capacitance.
- 20 14. The apparatus as in 12, wherein the impedance is adjusted by adjusting an inductance.
15. The apparatus of claim 2, further comprising a radio frequency conductive front end ring coupled to the plurality of current elements and a radio frequency
25 conductive back plane coupled to the plurality of current elements.
16. The apparatus of claim 2, further comprising a radio frequency conductive front end ring including a gap, the radio frequency conductive front end ring coupled to the plurality of current elements and a radio frequency conductive back
30 plane coupled to the plurality of current elements.

17. The apparatus of claim 2, further comprising a radio frequency conductive front end ring coupled to the plurality of current elements and a radio frequency conductive back end ring coupled to the plurality of current elements.
- 5 18. The apparatus of claim 2, further comprising a radio frequency conductive front end ring including a gap and a radio frequency conductive back end ring including a gap, the radio frequency conductive front end ring and the radio frequency conductive back end ring coupled to the plurality of radio frequency current elements.
- 10 19. The apparatus of claim 2, further comprising a slotted shield or cavity wall coupled to the plurality of radio frequency current elements.
20. The apparatus of claim 2, further comprising means to actively detune/retune
15 the volume coil for use with a local receiver coil.
21. A apparatus of claim 2, wherein the volume coil is double tuned or multiple tuned.
- 20 22. The apparatus of claim 2, wherein the volume coil is double tuned by the Vaughan method.
23. The apparatus of claim 2, further comprising a mirror or prism mounted over the window or aperture.
- 25 24. The apparatus of claim 2, further comprising a window or aperture in shield or cavity in approximate line with missing or displaced element or elements.
25. The apparatus of claim 24, wherein the volume coil includes an open end
30 and a closed end, the closed end being closed by a conductive plane.

26. The apparatus of claim 25, wherein the volume coil capable of being used in head imaging.
27. The apparatus of claim 24, wherein the volume coil includes two open ends.
- 5 28. The apparatus of claim 27, wherein the volume coil is capable of being used in head imaging.
29. The apparatus of claim 24, wherein includes a top and one or more of the regular or symmetric pattern or arrangement of current elements is removed from the top for improved access from the top.
- 10 30. The apparatus of claim 29, wherein the volume coil is capable of being used in head imaging.
- 15 31. The apparatus of claim 24, wherein the volume coil is capable of being used in body imaging.
32. The apparatus of claim 24, wherein the volume coil is capable of being used in extremity imaging.
- 20 33. The apparatus of claim 24, wherein the volume coil is capable of being used in foot and ankle imaging.
- 25 34. The apparatus of claim 24, wherein the volume coil includes an impedance and the impedance is adjusted to control current in the plurality of current elements.
35. The apparatus of claim 24, wherein the impedance is adjusted by adjusting a capacitance.
- 30

36. The apparatus of claim 24, wherein the impedance is adjusted by adjusting an inductance.
37. The apparatus of claim 24, further comprising a radio frequency conductive front end ring coupled to the plurality of current elements and a radio frequency
5 conductive back plane coupled to the plurality of current elements.
38. The apparatus of claim 24, further comprising an open front end ring coupled to the plurality of current elements and a radio frequency conductive back plane coupled to the plurality of current elements.
- 10 39. The apparatus of claim 24, further comprising a radio frequency conductive front end ring coupled to the plurality of current elements and radio frequency conductive back end ring coupled to the plurality of current elements.
- 15 40. A apparatus of claim 24, further comprising a front end ring including a gap coupled to the plurality of current elements and a back end ring including a gap coupled to the plurality of current elements.
41. The apparatus of claim 24, further comprising a slotted shield or cavity wall.
- 20 42. The apparatus of claim 24, further comprising a mirror or prism mounted over the window or aperture.
43. An apparatus comprising: a radio frequency magnetic field unit for magnetic
25 resonance including a plurality of current elements that are asymmetrically arranged, wherein at least one current element includes a transmission line segment having a first current path and a parallel return current path for the first current path and at least one current element is physically disconnected from another current element and at least two current elements are reactively coupled.
- 30

44. The apparatus of claim 43, wherein two or more current elements is are physically disconnected on one or more ends.
45. The apparatus of claim 43, wherein the plurality of current elements are
5 asymmetrically arranged about a substantially cylindrical form.
46. The apparatus of claim 45, wherein each of the plurality of current elements comprises a resonant current element.
- 10 47. The apparatus of claim 46, further comprising a static-field magnetic field unit having a bore, the radio frequency magnetic field unit inserted in the bore to form an imaging unit.
48. The apparatus of claim 43, wherein each of the plurality of current elements
15 is inductively coupled to at least one of the plurality of current elements.
49. The apparatus of claim 43, wherein the each of the plurality of current elements is capacitively coupled to at least one of the plurality of current elements.
- 20 50. An apparatus comprising: a radio frequency magnetic field unit for magnetic resonance having a plurality of current elements wherein each current element includes a transmission line segment having a first current path and a parallel return current path for the first current path, the radio frequency magnetic field unit adapted to generate a desired magnetic field, the radio frequency magnetic field unit
25 having a first aperture formed at an end of the radio frequency magnetic field unit and a second aperture that is substantially unobstructed, wherein the first aperture is contiguous to the second aperture.
51. The apparatus of claim 50, wherein the second aperture has an arc having an
30 arc length of between about 0° and about 90°.

52. The apparatus of claim 51, further comprising a static-field magnetic field unit having a bore, the radio frequency magnetic field unit inserted in the bore to form an imaging unit.

5 53. The apparatus of claim 50, further comprising one or more apertures formed on a side of the radio frequency magnetic field unit to permit access to a subject's ears.

54. The apparatus of claim 53, further comprising an auditory communication
10 device to communicate through the one or more apertures.

55. The apparatus of claim 54, wherein the communication device provides active or passive auditory protection.

15 56. An apparatus comprising: a radio frequency magnetic field unit for magnetic resonance having a plurality of current elements wherein each current element includes a transmission line segment having a first current path and a parallel return current path for the first current path, the radio frequency magnetic field unit having a first side aperture, a second side aperture and a pair of end apertures, the first side
20 aperture and the second side aperture contiguous with each of the pair of end apertures.

57. The apparatus of claim 56, wherein the radio frequency magnetic field unit comprises a substantially cylindrical volume having a curved arrangement of current
25 elements with the first side aperture and the second side aperture located along the curved arrangement and the first side aperture located substantially opposite from the second side aperture.

58. The apparatus of claim 57, wherein the first side aperture has a first width
30 and the second side aperture has a second width that is about equal to the first width.

59. The apparatus of claim 58, further comprising a static-field magnetic field unit having a bore, the radio frequency magnetic field unit inserted in the bore to form an imaging unit.

5 60. The apparatus of claim 56, wherein the radio frequency magnetic field unit includes a top-half and a bottom-half, the top-half capable of being mechanically attached and detached to the bottom-half at the first side aperture or the second side aperture.

10 61. A method comprising: removing one current element of a plurality of current elements from a first radio frequency magnetic field unit to form a second radio frequency magnetic field unit for magnetic resonance having an aperture, wherein each current element includes a transmission line segment having a first current path and a parallel return current path for the first current path.

15

62. The method of claim 61, further comprising:
calculating and implementing a set of currents for each current element to generate a desired magnetic field in the second radio frequency magnetic field unit.

20 63. A method comprising: removing two or more adjacent current elements of a plurality of current elements from a first radio frequency magnetic field unit to form a second radio magnetic field unit for magnetic resonance and having an aperture, wherein each current element includes a transmission line segment having a first current path and a parallel return current path for the first current path.

25

64. The method of claim 63, further comprising:
calculating and implementing a set of currents for each current element to generate a desired magnetic field in the second radio frequency magnetic field unit.

30 65. A method comprising: removing two oppositely positioned current elements circuits from a first radio frequency magnetic field unit to form a second radio

frequency magnetic field unit for magnetic resonance and having a first aperture and a second aperture wherein each current element circuit includes a transmission line element having a first current path and a parallel return current path for the first current path.

5

66. A transverse electromagnetic coil cavity including current elements, the transverse electromagnetic coil for magnetic resonance and having windows or apertures cut between current elements to allow access through the current elements wherein each current element includes a transmission line segment having a first
10 current path and a parallel return current path for the first current path.

67. A radio frequency coil comprising:

a plurality of magnetic resonance current elements including a first current element, a second current element and a third current element, each current element
15 having an inner conductor and a outer conductor separated by a dielectric, each inner conductor for carrying a current and each outer conductor for providing a return path for the current, the current elements arranged in a parallel alignment and enclosing a volume and the current element unequally spaced from each other and at least one current element having an individually adjustable impedance.

20

68. The coil of claim 67 wherein a field generated within the volume is a function of the current in each current element.

69. The coil of claim 67 wherein at least one outer conductor includes a slotted
25 shield.

70. The coil of claim 67 wherein the current elements are asymmetrically arranged.

30 71. The coil of claim 67 wherein the volume is cylindrical.

72. The coil of claim 67 wherein at least two of the current elements are reactively coupled.

73. The coil of claim 67 wherein the outer conductor of at least one current
5 element includes a mesh.

74. The coil of claim 67 wherein the current in the first current element is
controllable independent of the current in the second current element.
10

75. The coil of claim 67 further including a radio frequency conductive
backplane affixed to at least one of the current elements.

76. The coil of claim 67 further including an auditory communication device
15 disposed proximate a current element.

77. The coil of claim 67 further including an imaging unit disposed proximate
two adjacent current elements.

20 78. The coil of claim 77 wherein the imaging unit includes a mirror.

79. The coil of claim 77 wherein the imaging unit includes a prism.

80. An apparatus comprising:
25 a plurality of magnetic resonance current elements, each current element
having a shield and an inner conductor separated by a dielectric and at least one
current element individually controllable; and
wherein the current elements are arranged to define a surface about a volume
with the inner conductors disposed towards an interior of the volume and the shields
30 disposed towards an exterior of the volume, the volume having a first side aperture
devoid of a current element, the volume having an axis and wherein a current path

through each current element of the plurality of current elements is aligned substantially coaxially with the axis.

81. The apparatus of claim 80 further including a second side aperture in the
5 volume, the second side aperture devoid of a current element.

82. The apparatus of claim 80 further including an auditory communication device coupled to a current element wherein the auditory communication device is adapted for active auditory protection.
10

83. The apparatus of claim 80 further including an auditory communication device coupled to a current element wherein the auditory communication device is adapted for passive auditory protection.

15 84. The apparatus of claim 80 wherein the first side aperture subtends an arc of less than about 90 degrees.

85. The apparatus of claim 80 further including a radio frequency conductive first backplane coupled to at least one current element.
20

86. The apparatus of claim 85 wherein the first backplane includes a first end aperture.

87. The apparatus of claim 86 wherein the first end aperture is contiguous with
25 the first side aperture.

88. The apparatus of claim 87 further including a radio frequency conductive second backplane coupled to at least one current element.

30 89. The apparatus of claim 88 wherein the second backplane includes a second end aperture.

90. The apparatus of claim 89 wherein the second end aperture is contiguous with the first side aperture.
- 5 91. The apparatus of claim 90 further including a second side aperture in the volume, the second side aperture devoid of a current element, and wherein the second side aperture is contiguous with the first end aperture and contiguous with the second end aperture.
- 10 92. The apparatus of claim 80 wherein the plurality of current elements are adapted for head imaging.
93. The apparatus of claim 80 wherein the plurality of current elements are adapted for extremity imaging.
- 15 94. The apparatus of claim 80 wherein the plurality of current elements are adapted for foot and ankle imaging.
95. The apparatus of claim 80 wherein the plurality of current elements are adapted for body imaging.
- 20 96. The apparatus of claim 80 wherein a field generated within the interior is a function of the controllable element.
- 25 97. The apparatus of claim 80 wherein the controllable element includes an adjustable impedance.
98. The apparatus of claim 80 wherein the controllable element includes a PIN diode.
- 30

99. The apparatus of claim 97 wherein the adjustable impedance includes an inductance.

100. The apparatus of claim 97 wherein the adjustable impedance includes a capacitance.

101. The apparatus of claim 80 wherein at least two current elements are reactively coupled.

102. The apparatus of claim 80 further including an imaging unit disposed proximate two adjacent current elements.

103. The apparatus of claim 102 wherein the imaging unit includes a mirror.

104. The apparatus of claim 102 wherein the imaging unit includes a prism.

105. The apparatus of claim 80 wherein the current elements are asymmetrically arranged about the volume.

106. The apparatus of claim 80 wherein the current elements are doubly tuned.

107. The apparatus of claim 80 wherein the current elements are tuned to multiple frequencies.

108. The apparatus of claim 80 wherein the current elements generate a circularly polarized field.

109. The apparatus of claim 80 wherein the current elements are actively detunable.

30

110. A method comprising:
from a radio frequency volume coil having a plurality of magnetic resonance
current elements, each current element having a pair of adjacent conductors
separated by a dielectric and having an individually adjustable impedance, removing
5 one or more current elements to yield a plurality of remaining current elements;
calculating a current for each remaining current element, and selecting an
impedance for each remaining current element.
111. The method of claim 110 wherein calculating a current includes selecting a
10 resonant frequency for tuning.
112. The method of claim 110 wherein removing one or more current elements
includes removing two adjacent current elements.
- 15 113. The method of claim 110 further including adjusting a reactive component
of at least one remaining current element.
114. The method of claim 110 further including applying an excitation signal to
the plurality of remaining current elements.
20
115. An apparatus comprising:
a plurality of magnetic resonance current elements, each current element
having a shield and an inner conductor separated by a dielectric; and
a radio frequency conductive first backplane coupled to at least one current
25 element; and
wherein the current elements are arranged to define a surface about a volume
with the inner conductors disposed towards an interior of the volume and the shields
disposed towards an exterior of the volume, the volume having a first side aperture
devoid of a current element, the volume having an axis and wherein a current path
30 through each current element of the plurality of current elements is aligned

substantially coaxially with the axis, and wherein the first backplane includes a first end aperture.

5 116. The apparatus of claim 115 wherein the first end aperture is contiguous with the first side aperture.

117. The apparatus of claim 116 further including a radio frequency conductive second backplane coupled to at least one current element.

10 118. The apparatus of claim 117 wherein the second backplane includes a second end aperture.

119. The apparatus of claim 118 wherein the second end aperture is contiguous with the first side aperture.

15

120. The apparatus of claim 119 further including a second side aperture in the volume, the second side aperture devoid of a current element, and wherein the second side aperture is contiguous with the first end aperture and contiguous with the second end aperture.

20