

FLUID NOZZLE SPRAY AND FIRE EXTINGUISHER

FIELD OF THE ART

The invention relates to fluid spraying techniques and can be used in fire
5 extinguishing systems as a part of technological equipment, for burning fuel at heat
power stations and the transport as well as for moistening the environments. The
invention as a fire extinguisher can be employed as a member of stationary and mobile
systems for fire fighting at different sites: in rooms of the hospitals, libraries, museums;
on board a ship, an aircraft, etc.

10

PRIOR STATE OF THE ART

Known in the art are different types of fluid nozzle sprays having an application,
including that in fire fighting systems.

Thus, for instance, from a description to Author's Certificate SU 1220703 A
(B05 B1/14, publ. 30.03.86) a fluid nozzle spray is known, the structure of which
15 comprises spraying nozzles of head-striking action. The said nozzles are built in the
form of through pairwise head-directed channels. These channels are inclined to the axis
of symmetry of the nozzle spray body. The angle between the axes of symmetry of the
channels is selected within 30° to 150° range. This structural spray embodiment allows
to decrease energy supply for both fluid dispersion and spraying in the environment
20 space.

The most close analogue of a fluid nozzle spray patented is a device described in
Patent RU 2111033 C1 (A626 31/02, publ. 20.05.98). The known nozzle spray contains
injectors placed in rows along the external surface of the body. Each injector is formed
by two co-axial channels of the same cross-section provided for head liquid supply and a
25 nozzle formed by a partial intersection of external conical passage and co-axial channel
surface. The inlet orifice of the said nozzle is formed by intersection of internal surfaces
of cylindrical channels and conical surfaces forming a nozzle. The nozzle spray of the
said structure allows to create a uniform-in-volume flow of finely dispersed spray drops
30 to 150µm in size. However, the said technical solution is aimed at generating a finely
30 dispersed flow of drops in the environment volume but not a directed flow of drops of a
preferred size with a particular cross-section, which is necessary, for instance, for

effective fire extinguishing. The said requirement is of great importance while employing a fluid nozzle spray as a fire extinguisher structural member.

Besides, known are different types of fire extinguisher fitted with fluid nozzle sprays. These fire extinguishers include, e.g., a device disclosed in the description to
5 Author's Certificate SU 1657204 A1 (A62C 35/00, publ. 11.05.89). The said fire extinguisher comprises a fluid nozzle spray for fire fighting made in the shape of an exhaust branch pipe of a siphon pipe, a vessel with liquid, a liquid expulsion system and a pressurized gas bottle connected with a gas vessel cavity, and a siphon pipe, through which the liquid passes to the nozzle spray. The present technical solution is aimed at
10 fire fighting efficiency increase on account of maintaining a desired pressure providing an ejection of the overall fire extinguishing substance mass. However, this device lacks any means of generating a directed finely dispersed gas-and-drop flow of a desired cross-section and means necessary to control the liquid supply for fire fighting.

The most closely analog device to the fire extinguisher patented is the one
15 described in Application DE 2635531 A1 (A6 2C 31/02, publ. 09.02.78). The said fire extinguisher includes a fluid nozzle spray in the shape of a mouthpiece, a vessel with liquid for fire extinguishing, a liquid expulsion system and a pressurized gas bottle, pipes connecting a liquid vessel cavity and a nozzle spray, and regulators to control liquid supply to the nozzle spray. The above technical solution, though it is aimed at fire
20 fighting efficiency increase (on account of simultaneous supply of foam-forming fluid and powder to the fire site), however it does not concern the improvement of the system spraying fluid into the environmental space.

SUMMARY OF THE INVENTION

25 The invention patented is aimed at developing a device enable to generate gas-and-drop flows of a preferred dimensional configuration that can be used for effective fire fighting with portable means of fire extinguishing - fire extinguishers applied. Achievement of the said technical result is connected with uniformity and, accordingly, intensity rate increase of fluid spraying over the total surface of a particular area.

30 A problem solved by the invention and aimed at obtaining a desired technical result consists in developing a finely dispersed gas-and-drop flow with a cross-section in the shape of an ellipse, with a special means applied. The above shape of a directed drop flow cross-section allows to effectively spray the fluid with certain intensity over

large and small areas with a step-by-step nozzle spray displacement along the fire site surface.

Achievement of the said technical result is provided by the fact that in the fluid nozzle spray built in the shape of a body with two co-axial channels of the same cross-section designed for head liquid supply and a nozzle, the inlet orifice of which is formed by intersection of internal channel surfaces and the nozzle forming surface according to the present invention the nozzle is of a conical diffuser shape oriented transverse to the channels. The diffuser inlet orifice shall not exceeding the total area of channel cross-sections.

10 The said aggregate of essential features provides the ability to generate a finely dispersed gas-and-drop flow with an elliptical cross-section with the aid of nozzle spray.

In a preferred version of a nozzle spray structural design an angle between the axis of symmetry of the channels and axis of symmetry of a conical surface forming a diffuser is 89° to 91° . In this case a symmetrical finely-dispersed drop distribution of gas-and-drop flow over the area of its cross-section is achieved.

15 From a technological viewpoint it is preferred to build channels of a cylindrical shape.

The most uniform drop distribution in the flow generated is achieved in case of angle selection with a diffuser-forming cone vertex of 30° to 90° .

20 It is preferred to form a nozzle spray diffuser with a conical orifice made in the body. In this case a nozzle spray construction technology is simplified.

The above technical result is achieved with the aid of a fire extinguisher containing a fluid nozzle spray, a liquid vessel for fire extinguishing, a liquid expulsion system, a pipeline connecting a liquid vessel cavity and a nozzle spray and, at least, one valve or a regulator to control liquid supply to the nozzle spray, in which according to the present invention a fluid nozzle spray is built in the shape of a body with two co-axial channels of the same cross-section designed for liquid head supply. The nozzle spray must have a nozzle, the inlet orifice of which is formed by intersection of internal channel surfaces and nozzle-forming surface. The nozzle is of a conical diffuser shape and it is oriented transverse to the channels. The diffuser inlet orifice shall not exceeding a total cross-section area of the channels.

The said aggregate of essential features, which characterize a fire extinguisher structure, provide a finely dispersed gas-and-drop flow with an elliptical cross-section with the aid of a fire extinguisher.

In preferred embodiments of the said fire extinguisher an angle between the axis
5 of symmetry of the nozzle spray and the axis of symmetry of a conical diffuser-forming surface can be 89° to 91° . The nozzle spray channels can be of a cylindrical shape. An angle at nozzle spray diffuser-forming cone vertex can be 30° to 90° . A nozzle spray diffuser can be formed by a conical orifice made in the body.

It is preferred for the fire extinguisher liquid expulsion siphon pipe to be placed in
10 the vessel cavity to connect a liquid cavity with a fluid nozzle spray.

The most suitable liquid for fire extinguishing is water with a foam-forming agent. To increase effectiveness of liquid expulsion from a vessel some volatile liquids can be added to the water, preferably carbon dioxide - CO_2 and/or liquefied gases - SF_6 .

A liquid expulsion system can be fitted with an elastic separation diaphragm
15 separating a gas cavity of the vessel from its liquid cavity. This structure enables to exclude interaction of cavity pressurization gas and the liquid expelled.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention patented is described with reference to a specific embodiment
20 illustrated in the accompanying drawings, wherein:

Fig.1 is a schematic view of fire extinguisher and a nozzle spray connected to it;

Fig.2 is a transverse section of a nozzle spray in the inlet orifice of the diffuser scaled-up (two-fold scale-up).

PREFERRED EMBODIMENTS OF THE INVENTION

A fluid nozzle spray illustrated in Figs.1 and 2 comprises the body 1, in which two
co-axial cylindrical channels 2 are built designed for liquid head supply. A spray nozzle
is built in the shape of the conical diffuser 3 formed by a conical orifice in the body 1
and oriented transverse to the channels 2. An angle between the axis of symmetry of co-
30 axial cylindrical channels 2 and the axis of symmetry of a conical surface forming
diffuser 3 is 90° (with account of technological error $\pm 30'$). An angle at cone vertex
forming the diffuser 3 is 40° .

The inlet nozzle orifice (of the diffuser 3) is formed by intersection of internal channel surfaces and a conical surface forming a nozzle. The inlet orifice area of the diffuser 3 is 0,7 from a total cross-section area of the channels 2.

A fire extinguisher fitted with a nozzle spray of the said structure also includes the vessel 4 with fire extinguishing liquid, which can be preferably water and foam-forming agent. The vessel 4 consists of liquid 5 and gas 6 cavities. The liquid expulsion system contains the siphon pipe 7, which, via the control valve 8 comprising the spring-loaded closure 9 and the control lever 10, is connected with flexible pipeline 11. The body 1 of the nozzle spray is installed in the branch pipe 12, the cavity of which is connected with the liquid cavity 5 of the vessel 4 via the siphon pipe 7, the valve 8 and the flexible pipeline 11.

Liquid composition filling the vessel 4 can include a liquid volatile additive, for instance, liquefied carbon dioxide (CO_2) or elegas (SF_6) to increase the liquid expulsion effectiveness from the vessel 4. To exclude pressurized gas of the vessel 4 and liquid interaction an elastic diaphragm can be additionally installed (not shown in the drawing).

The fluid nozzle spray and the fire extinguisher fitted with the said nozzle spray (see Figs.1 and 2) function in the following manner.

By the co-axial channels 2 the liquid is supplied under pressure of ~ 1 MPa (operating pressure range 0,3 to 3 MPa) in the form of the two head flows, which collide in the inlet orifice area of the diffuser 3. During interaction of head flows running out of a diffuser inlet orifice, the cross-section area of which is less than a total area of the feeding channels 2, a liquid flow cavitation takes place. In the course of fluid running out of the diffuser 3 a finely dispersed gas-and-drop flow with an elliptical cross-section is formed. As a result of experiments conducted it was determined that at the distance of 2 m from the nozzle spray exit section a gas-and-drop flow of an ellipse-shape cross-section with the greatest transverse dimension of 2,3 m and the least transverse dimension of 0,5 m is generated. Dispersivity of drops sprayed within the range of elliptical cross-section was 100 μm to 130 μm .

In the same manner the nozzle spray functions as a structural member of a fire extinguisher. A liquid vessel for fire extinguishing (with water) is filled preliminarily with gas up to a desired storage pressure (up to 3 MPa), the vessel may be filled with liquefied carbondioxide or elegas as an additive.

The fire extinguisher functions in the following manner. In pressing the lever 10 the closure element 9 is released from the valve seat and the liquid under the excessive pressure developed by pressurized gas in the gas cavity 6 is expelled from the liquid cavity 5 of the vessel 4 through the siphon pipe 7 and the flexible pipeline 11. Then the liquid passes into the co-axial channels 2, in which head flows of the same rate are generated colliding in the area of the nozzle inlet orifice (of the diffuser 3). As a result of head liquid flow collision the atomizing of drops takes place at the orifice edges and a gas-and-drop flow with an elliptical form of its cross-section is generated. This shape of the flow elongated in its transverse cross-section allows to spray the fluid over rather a large fire site area with a step-by-step nozzle spray displacement along the surface of the fire site. The fluid nozzle spray displacement possibility along the fire site surface of a large area is determined by a length of the flexible pipeline 11 and the total fire extinguisher mass.

A preferred duration and intensity of gas-and-drop flow supply is controlled by the lever 10 of the valve 8 built in the vessel 4. To increase liquid expulsion effectiveness the volatile liquids can be utilized, preferably liquefied carbon dioxide (CO_2) and elegend (SF_6) used as such. These substances are added to the liquid (water) for fire extinguishing. At pressure decrease less than the saturated vapor pressure of volatile additives in the vessel 4 during a process of liquid expulsion their vaporization takes place resulting in automatic pressure maintenance at the level preferred in the gas cavity 6 and liquid ejection via the nozzle spray does not become lower than the acceptable level.

To exclude pressurization gas and expulsion liquid interaction, including chemical interaction and liquid saturation with gas, the liquid cavity 5 is separated from the gas cavity 6 by a hermetic separation diaphragm made of an elastic material (not shown in the drawing). Though this embodiment of liquid expulsion system makes the fire extinguisher structure more complex, however, in this case its operation reliability increases. In the simplest version of embodiment, when water is used as liquid for fire extinguishing with inert gas utilized as pressurization gas, there is no necessity to use a separation diaphragm.

To stop a fire extinguisher operation one must release the lever 10 of the valve 8. The closure component 9 under the force of a compressed spring is displaced to a valve

seat and shuts its passage cross-section, thus cutting off the fluid supply via the nozzle spray.

Fire fighting efficiency with the help of a fire extinguisher built according to the present invention is ensured on account of ability to generate a gas-and-drop flow with its elliptical cross-section and uniform intensity and dispersity of drops along the flow cross-section. This elongated (approaching rectangular) shape of the flow cross-section allows to more effectively, in comparison with a round shape of the flow cross-section commonly applied, distribute the dispersed fluid over the fire site, the area of which considerably exceeds the gas-and-drop flow cross-section area. The solution of the problem enables to lower the liquid consumption, the capacity of which is determined by the vessel 4 volume, for fire site extinguishing.

As a result of experiments conducted it was established that generation of gas-and-drop flow with an elliptical cross-section and uniform intensity and dispersity is ensured on account of employing a spray nozzle in the form of a conical diffuser oriented transverse to feeding co-axial channels. The area of the diffuser inlet orifice formed by intersection of internal channel surfaces and diffuser-forming surface should not exceed a total cross-section area of the channels. These conditions determine the ability of achieving a desired technical result.

INDUSTRIAL APPLICATION

The invention may be used in different fields of engineering where it is required to generate spraying fluid flows both in closed and open space. A nozzle spray may be used in fire extinguishing systems, as a part of technological equipment, for burning fuel at heat power stations and the transport, moistening the environment as well as spraying different chemicals over agricultural lands and in industrial premises. The fire extinguisher fitted with a fluid nozzle spray according to the invention may find its application as a standard equipment for fire extinguishing at different objects: in the rooms of hospitals, libraries, museums, on board a ship, an aircraft and other sites of importance.

Through a group of inventions patented is described at the example of a preferred embodiment, a specialist in this field of engineering acknowledges that structural improvements and other embodiments can take place without deviation from the invention subject characterized by the claims defining the invention.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A fluid nozzle spray made in the form of a body (1) with two co-axial channels (2) of the same cross-section designed for head liquid supply and a nozzle, the inlet orifice of which is formed by intersection of internal channel surfaces and a nozzle-forming surface, characterized by the fact that the nozzle has a shape of a conical diffuser (3) oriented transverse to the channels (2), the diffuser (3) inlet orifice area not exceeding a total cross-section area of the channels (2).

2. The nozzle spray of claim 1, characterized by the fact that the angle between the axis of symmetry of the channels (2) and the axis of symmetry of a conical surface forming the diffuser (3) is 89° to 91° .

3. The nozzle spray of claims 1 and 2, characterized by the fact that the channels (2) are of a cylindrical shape.

4. The nozzle spray of any said claims, characterized by the fact that the angle at the diffuser (3) -forming cone vertex is 30° to 90° .

5. The nozzle spray of any said claims, characterized by the fact that the diffuser (3) is formed by a conical orifice made in the body (1).

6. The fire extinguisher comprising a fluid nozzle spray, a vessel (4) containing liquid for fire extinguishing, a liquid expulsion system, a pipeline (11) connecting a liquid vessel cavity (5) with a nozzle spray and at least one valve or a regulator (8) to control the liquid supply to the nozzle spray, characterized by the fact that the fluid nozzle spray is made in the form of a body (1) with two co-axial channels (2) of the same cross-section designed for head liquid supply and a nozzle, the inlet orifice of which is formed by intersection of internal surfaces of the channels and a nozzle-forming surface, the nozzle having a shape of a conical diffuser (3) and oriented transverse to the channels (2) with the diffuser (3) inlet orifice area not exceeding a total cross-section area of the channels (2).

7. The fire extinguisher of claim 6, characterized by the fact that the angle between the axis of symmetry of the channels (2) and the axis of symmetry of a conical surface forming the diffuser (3) is 89° to 91° .

8. The fire extinguisher of claim 6, characterized by the fact that the nozzle spray channels (2) have a cylindrical shape.

9. The fire extinguisher of claim 6, characterized by the fact that the angle at the vertex of the cone forming a nozzle spray diffuser (3) is 30° to 90°.

10. The fire extinguisher of claim 6, characterized by the fact that the nozzle spray diffuser (3) is formed by a conical orifice made in the body.

5 11. The fire extinguisher of claim 6, characterized by the fact that the liquid expulsion system has a siphon pipe (7) installed in the vessel cavity.

12. The fire extinguisher of claim 6, characterized by the fact that the liquid for fire extinguishing is water with a foam-forming agent.

10 13. The fire extinguisher of claim 6, characterized by the fact that the liquid for fire extinguishing includes a volatile fluid.

14. The fire extinguisher of claim 6, characterized by the fact that the liquid for fire extinguishing includes a volatile fluid, liquefied carbon dioxide CO₂ and/or liquefied gas SF₆ used as such.

15 15. The fire extinguisher of claim 6, characterized by the fact that a liquid expulsion system is fitted with an elastic separation diaphragm separating a gas cavity from its liquid cavity.