

1

Security document with holographic foil and printed machine-readable markings

5 Technical Field

The invention relates to a security document, such as a banknote or an identification document, with holographic foil and printed machine-readable markings.
10 The invention also relates to methods for manufacturing such a security document as well as for checking its authenticity.

15 Background Art

It has been known to provide security documents with a foil element comprising a security feature formed by a diffractive structure, such as a surface or volume hologram or grating. Such foils cannot be forged
20 by conventional printing or copying techniques, thereby rendering the documents more secure.

EP 2 009 516 A2 discloses a volume hologram transfer foil and a volume hologram laminate.

EP 1 985 462 A1 discloses an information recording patch that allows authentication of a security
25 document.

JP 2007-136907 A discloses a printed article on which forgery can be detected.

WO 2005/070693 A1 discloses a security document with a diffractive structure.
30

JP 2003-226085 A discloses printed matter with a light reflective substrate material.

JP 2008-096625 A discloses a hologram transfer foil.

35 US 2004/0234816 A1 discloses a magnetic card comprising a substrate.

JP 2007/072188 A discloses a black hologram with allegedly improved security properties.

However, such documents may be tampered with if it is possible to remove the foil element without damaging it. Even though a removal of the foil element can be detected by verification devices, such devices need to be equipped with dedicated sensors for sensing the presence of the foil element, which renders such equipment more expensive.

10

Disclosure of the Invention

Hence, it is a general object of the invention to provide a security document with a foil element comprising a security feature, such as a diffractive structure, that has improved counterfeit security.

This object is achieved by the security document of claim 1. That document comprises a substrate, such as a paper or plastic substrate, and a foil element. The foil element comprises the security feature and has a top surface facing away from the substrate and a bottom surface attached to the substrate. In addition, the security document comprises machine-readable markings arranged between the bottom surface and the substrate, i.e. below the foil element. These machine-readable markings intersect at least partially with the foil element, i.e. they cover at least part of the same surface region of the security document as the foil element. This makes it possible to more readily detect the presence of the foil element when the document's authenticity has to be verified by a machine, in particular by a conventional machine equipped for detecting conventional printed security markings. There is no need to equip the machine with means for detecting the security feature of the foil element.

35

Furthermore, at least part of the machine readable markings are printed onto the substrate. The ad-

hesion of the markings to the substrate is weaker than the adhesion of the markings to the foil element, i.e. when the foil element is removed from the substrate by mechanical force, a major part (more than 50%) of the markings printed to the substrate should be lifted off together with the foil element. This, again, allows to easily detect the removal of the foil element.

In a further aspect, the invention also relates to a method for manufacturing such a security document. This method comprises the step of printing at least part of said markings to said substrate and to at least one of said top surface and said bottom surface.

In a first advantageous embodiment, at least part of the machine readable markings are printed onto the top surface of the foil element, thus that they are missing from the security document when the foil element is removed.

In a second advantageous embodiment, at least part of the machine readable markings are printed onto the bottom surface of the foil element. In that case, again, the markings will likely remain attached at least partially to the foil element if the foil element is removed from the substrate.

The invention also relates to a method for automatically verifying the authenticity of the security document. This method comprises the step of checking for a presence of the markings by means of a sensor device. If the markings are at least in part missing, it can be assumed that the document is not authentic or at least damaged.

Brief Description of the Drawings

The invention will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings, wherein:

Fig. 1 shows a top view of a security document and

Fig. 2 shows a sectional view of a security document with a substrate and a foil element.

Modes for Carrying Out the Invention

Definitions:

The term "security document" encompasses any type of document that contains a security feature that makes it difficult to reproduce. Examples for security documents of this type are banknotes, passports, checks, stock certificates, tickets, credit cards, ID cards, good certificates, stamps, vouchers, shares, driving licenses,

residence permits, birth certificates, or insurance certificates. The present invention is, however, of particular advantage when applied to banknotes.

The term "diffractive structure" as used
5 herein and in the claims is to designate a periodic structure with a periodicity in the order of the wavelength of visible light, in particular between 0.1 μm and 10 μm . Such periodic structures give rise to diffractive interference effects. As known to the skilled person, the
10 structure may e.g. be a surface structure, such as e.g. known from surface gratings, surface holograms or kinegrams, or it may be a structure in the volume of the foil element, in particular an absorptive or refractive grating, such as it is e.g. known from volume holograms.

15 The terms "top", "above", "below", "bottom" etc. refer to a direction extending perpendicularly to the substrate of the document, with the foil element being, by definition, above the substrate. Hence, the surface of the foil element that faces away from the sub-
20 strate is called the "top surface" of the foil element, while the surface of the foil element that faces the substrate is called its "bottom surface".

Security document:

25 The security document shown in Fig. 1 comprises a flexible or rigid substrate 1 of paper or plastics, or a combination of such materials, such as in a multilayer structure, onto which graphical elements, for example in the shape of security designs 2, illustrations
30 3 and indications of value 4, are printed in known manner. In addition the document possesses a security feature 5, the design of which is described in the following.

As shown in Fig. 2, security feature 5 com-
35 prises a foil element 6 having a top surface 7 and a bottom surface 8. It is attached to the top surface 9 of substrate 1, e.g. by means of an adhesive layer 11.

A security feature in the form of a diffractive structure, such as a volume hologram 12, is arranged in foil element 6. As mentioned above, other diffractive structures can be provided in foil element 6 alternatively to or in addition to volume hologram 12.

Even though Fig. 2 shows foil element 6 as consisting of a single layer, foil element 6 can also comprise several layers, such as protective layers, partially metalized layers or carrier layers. Adhesive layer 11 can also be part of foil element 6.

Advantageously, foil element 6 has a thickness of no more than 100 μm , in particular no more than 25 μm , which renders it difficult to remove, in particular without damaging it.

As shown in Figs. 1 and 2, security markings 4, 14, 15 can be printed above and/or below foil element 6. As mentioned above, the security markings can be printed:

- Onto top surface 7 of foil element 6, such as shown for security markings 14: This location has the advantage that the security markings 14 are readily accessible for detection and are certain to be removed from the security device when a counterfeiter tries to remove foil element 6.

- Onto bottom surface 8 of foil element 6, such as shown for security markings 15: This design has the advantage that the markings are protected from mechanical damage by means of foil element 6, and still they typically adhere more strongly to foil element 6 than to substrate such that they are certain to be removed from the security device when a counterfeiter tries to remove foil element 6. If adhesive layer 11 is part of foil element 6, printing can also take place onto the bottom surface of adhesive layer 11, in which case the location of the markings corresponds to those of markings 4 in Fig. 2.

- Onto substrate 1, again such as shown for security marking 4: In this case the adhesion of the markings to substrate 1 should be weaker than their adhesion to foil element 6. This can e.g. be achieved by appropriately selecting the ink for the security markings as well as the material of adhesive layer 11. If adhesive layer 11 bonds sufficiently well to the security markings as well as to foil element 6, a major part of adhesive layer 11 and of the markings will be removed from substrate 1 when foil element 6 is lifted off by force. For example, both the ink for the markings 4 and the material for adhesive layer 11 can comprise a resin that cross-links upon illumination with UV light.

The security markings should be machine readable, i.e. they should be readily detectable by means of automated sensor devices. For easy and reliable detection, the security markings can e.g. use combination of the following techniques:

- The markings can comprise a magnetic ink. Magnetic inks are known by the skilled person. In particular, magnetic inks may comprise inks that have a high magnetic remanence ("hard" magnetic inks), e.g. of at least 1000 Gauss, or inks that have a low magnetic remanence but a high magnetic permeability μ ("soft" magnetic inks), e.g. of at least 2, in particular much higher than 2.

- The markings can comprise a fluorescent ink. Upon illumination with light of a first given wavelength λ_1 , such dyes emit light of a second, typically longer wavelength λ_2 .

- The markings can comprise an infrared absorbing dye, i.e. a dye showing strong absorptive bands in the infrared spectral range.

- The markings can comprise an electrically conductive layer, such as printed by an electrically conductive ink. Such layers can be detected electrically, i.e. using conductivity measurements. In a particularly

advantageous embodiment, the security document can comprise a resonant circuit, with the conductive layer of the markings forming at least part of the resonant circuit. Such resonant circuits can be detected using RF measurements. Examples for manufacturing resonant circuits using printing techniques are disclosed in WO 03/096268. Fig. 1 shows, by way of example, an illustration of such a circuit at reference number 18.

- The markings can also comprise liquid crystal pigments with polarization-dependent optical properties.

- The markings can also comprise so-called taggings, such as optical up-converters or down-converters.

Advantageously, at least part of the markings are invisible to the naked eye. For example, markings 15 can be such that, in the visible spectral range, they do not differ from other markings in their surroundings, while they show a strong absorptive band in the infrared spectral range.

However, other markings, such as markings 4, can be readily visible to the human observer.

In a further advantageous aspect, at least part of the markings are machine detectable through foil element 6, i.e. a suitable sensor is able to detect them from the top side of the security document, by probing the markings through foil element 6. For example, if markings 15 comprise a magnetic dye and foil element 6 is of a polymeric material, an inductive sensor is readily able to detect the markings through foil element 6.

The markings can form any desired pattern, such as patterns readable to the human eye (for example a printed number), or they can form codes typically read by a machine only (such as a bar code).

Manufacturing:

The security document shown in Figs. 1 or 2 can e.g. be manufactured by using the following steps:

In a first printing step, e.g. using offset print, ink is applied to substrate 1. Typically, such a
5 step applies background colors and patterns and at least part of the visually perceptible elements of the final document.

The first step can also comprise the printing of security markings, such as the markings 4, onto sub-
10 strate 1, at a location that intersects with the later applied foil element 6. If the markings 4 printed onto substrate 1 are to comprise dyes that are difficult to apply by means of offset print, other printing techniques can be used for applying them, such as screen printing or
15 intaglio printing. However, in that case, because dyes applied with screen printing or intaglio printing are likely to weaken the adhesive force between foil element 6 and substrate 1, the area covered by such markings should be much smaller than the area covered by foil ele-
20 ment 6 as a whole.

In a next step, foil element 6 is applied to substrate 1. Before doing so, markings (such as markings 15) may be printed to bottom surface 8 of foil element 6.

An advantageous method for applying foil ele-
25 ment 6 to substrate 1 is a transfer method, where foil element 6 delivered as a laminate with its top surface 7 connected to a carrier layer. Then, bottom surface 8 of foil element 6 is mounted to substrate 1, e.g. using adhesive layer 11, whereupon the carrier layer can be re-
30 moved. This technique allows for the application of even very thin foil elements 6.

Adhesive layer 11 can e.g. be a hot-melt layer and/or a UV-curable resin layer. In the first case, heat is applied for applying foil element 6 to substrate
35 1, in the second case UV-radiation is used for curing adhesive layer 11. Typical adhesives can e.g. comprise at least one component from the group comprising polyure-

thane, acrylates, polyvinyl-alcohols, polyvinyl-acetates oder polyvinyl-pyrrolidones.

After applying foil element 6, any security markings (such as markings 14) to be printed onto its top surface 7 can be applied, using any printing technique, such as offset printing, screen printing or intaglio printing.

Finally and optionally, a varnish layer can be applied over at least part of the security document, in particular for protecting any markings printed onto top surface 7 of foil element 6.

Notes:

In the example above, the security feature of foil element 6 has been formed by a diffractive structure. It must be noted, though, that the security feature can be formed by other techniques. For example, the security feature may comprise any optically variable device (OVD), such as a thin-film element with UV-fluorescence, or an optical light guide, see e.g. WO 2006/056089.

The authenticity of the security document can be verified by checking for the presence of the markings 4, 14, 15 in the region of foil element 6 by means of a suitable sensor device, as indicated by reference numeral 17 of Fig. 2. If at least part of the markings is missing, it can be assumed that the document has been tampered with.

As mentioned above, the markings 4 and 15 situated between substrate 1 and foil element 6 can be checked by performing a measurement through the foil element 6. Alternatively, a detection can also take place by measuring through substrate 1 if substrate 1 allows the passage of the required signals.

One advantage of the present technique is the fact that it uses conventional printing technology for improving the security of a diffractive foil element, thus that it can be implemented easily. Still, it allows

to reliably detect a removal of foil element 6 using conventional authentication devices.

While there are shown and described presently preferred embodiments of the invention, it is to be distinctly understood that the invention is not limited thereto but may be otherwise variously embodied and practiced within the scope of the following claims.

Claims

1. A security document comprising
a substrate (1),
5 a foil element (6) comprising a security feature (12), wherein said foil element (6) has a top surface (7) facing away from said substrate (1) and a bottom surface (8) attached to said substrate (1),
printed machine-readable markings (4, 14, 15)
10 between said bottom surface (8) and said substrate (1),
wherein said markings (4, 14, 15) intersect at least partially with said foil element (6),
wherein at least part of said markings (4, 14, 15) are printed onto said substrate (1), and
15 wherein, for said part of said markings (4, 14, 15) printed onto said substrate, an adhesion of said markings (4, 14, 15) to said substrate (1) is weaker than an adhesion of said markings (4, 14, 15) to said foil element (6).
- 20 2. The security document of claim 1 wherein said foil element (6) comprises an adhesive layer (11) and wherein at least part of said markings (4, 14, 15) is printed onto a bottom surface of said adhesive layer
25 (11).
- 30 3. The security document of any of the preceding claims wherein at least part of said markings (4, 14, 15) are printed onto said bottom surface (8).
- 35 4. The security document of any of the preceding claims wherein at least part of said markings (4, 14, 15) are machine detectable through said foil element (6).

5. The security document of any of the preceding claims wherein at least part of said markings (4, 14, 15) comprises a magnetic dye.

5 6. The security document of any of the preceding claims wherein at least part of said markings (4, 14, 15) comprises a fluorescent ink.

10 7. The security document of any of the preceding claims wherein at least part of said markings (4, 14, 15) is invisible to the naked eye.

15 8. The security document of any of the preceding claims wherein at least part of said markings (4, 14, 15) comprises an electrically conductive layer, and in particular wherein said security document comprises a resonant circuit and wherein said conductive layer forms at least part of said resonant circuit (18).

20 9. The security document of any of the preceding claims wherein at least part of said markings (4, 14, 15) comprises an infrared absorbing dye.

25 10. The security document of any of the preceding claims wherein said security feature comprises an optically variable device, such as a diffractive structure or an optical thin-film element, or an optical waveguide.

30 11. A method for manufacturing the security document of any of the preceding claims comprising the step of printing at least part of said markings (4, 14, 15) onto said substrate (1) and onto at least one of said top surface (7) and said bottom surface (8).

35 12. The method of claim 11 wherein at least part of said markings (4, 14, 15) is printed onto said

bottom surface (8) prior to attaching said foil element (6) to said substrate (1).

13. The method of claim 12 wherein said foil
5 element (6) comprises an adhesive layer (11) and wherein
at least part of said markings (4, 14, 15) is printed on-
to a bottom surface of said adhesive layer (11).

14. A method for automatically verifying the
10 authenticity of the security document of any of the
claims 1 to 10 comprising the step of checking for a
presence of said markings (4, 14, 15) in the region of
said foil element (6) by means of a sensor device (17).

15 15. The method of claim 14 comprising the
step of checking for said markings (4, 14, 15) arranged
between said foil element (6) and said substrate (1) by
performing a measurement through said foil element (6).