



(51) International Patent Classification:

E21B 21/08 (2006.01) *G01F 1/84* (2006.01)
E21B 47/10 (2012.01) *G01F 15/12* (2006.01)

(21) International Application Number:

PCT/EP2011/065834

(22) International Filing Date:

13 September 2011 (13.09.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

1015408.6 15 September 2010 (15.09.2010) GB

(71) Applicant (for all designated States except US): **MAN-AGED PRESSURE OPERATIONS PTE. LIMITED** [SG/SG]; 1 Maritime Square, #12-04A, Harbour Front Centre, 099253 (SG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LEUCHTENBERG, Christian** [DE/SG]; Apt 06#103, Block 42A, Caribbean Apartments, Keppel Bay Drive, Singapore 098656 (SG).


(74) Agent: **FORRESTERS**; Chamberlain House, Paradise Place, Birmingham, West Midlands B3 3HP (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

[Continued on next page]

(54) Title: DRILLING APPARATUS



(57) Abstract: A drilling system including a drill string which extends into a borehole, and a well closure system which contains fluid in the annular space in the borehole around the drill string, the well closure system having a side bore whereby controlled flow of fluid out of the annular space in the borehole around the drill string is permitted, the side bore being connected to fluid return line which extends from the side bore to a fluid reservoir, there being provided in the fluid return line a valve which is operable to restrict flow of fluid along the fluid return line to variable extent, and a flow meter operable to measure the rate of flow of fluid along the fluid return line, the flow meter being located between the valve and the side bore, wherein a filter is provided between the flow meter and the side bore, the filter including a plurality of apertures which have a smaller cross-sectional area than the smallest fluid flow lines in the flow meter.

FIG 1



SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG). **Published:**

— *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*