

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number  
**WO 2004/033810 A2**

(51) International Patent Classification<sup>7</sup>: **E04B 1/21**,  
E04C 3/34, 3/44

(21) International Application Number:  
PCT/US2003/031929

(22) International Filing Date: 8 October 2003 (08.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/417,065 8 October 2002 (08.10.2002) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *without international search report and to be republished upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(71) Applicant and  
(72) Inventor: **POWELL, David, W.** [US/US]; 8108 Texas  
Plume Road, Austin, TX 78759 (US).

(74) Agent: **YEAGER, Rick, B.**; Rick B. Yeager, Attorney,  
10805 Mellow Lane, Austin, TX 78759 (US).

(54) Title: METHOD AND APPARATUS FOR PRECAST AND FRAMED BLOCK ELEMENT CONSTRUCTION

(57) Abstract: Precast planar construction blocks are cast on-site or received and assembled in free-standing modules. A variety of shapes of spaced apart paired blocks form free-standing modules which apply building load over a large footprint. Biaxial sleeve connectors and threaded rods facilitate connection between blocks. The free-standing modules are connected with other structural elements to form a complete primary structure. The primary structure can then be enclosed using manufactured blocks to establish perimeter walls and roofs.



**WO 2004/033810 A2**