

219633

SYNERGISTIC ACID BLEND EXTRACTION AID AND METHOD FOR ITS USE

Field of the Invention

[0001] The present invention relates to extraction aids, and the use of them in oil production and refinery desalting processes. More particularly, it relates to extraction aids used to remove contaminants, particularly metals and amines, from crude oils during production and processing.

Background of the Invention

[0002] Liquid hydrocarbon mediums, such as crude oils and crude fractions, including naphtha, gasoline, kerosene, jet fuel, fuel oil, gas oil and vacuum residuals, often contain contaminants that can be deleterious to processing or product quality. The contaminants can contribute to corrosion, heat exchanger fouling, furnace cooking, catalyst deactivation and product degradation in refinery and other processes. The contaminants are broadly classified as salts, bottom sediment and water, solids and metals. The amounts of these impurities vary depending upon the particular crude and to its processing.

[0003] Desalting or dewatering is a process that is used to remove contaminants, primarily water and inorganic salts, from crude oils prior transportation and refining. The initial dewatering step is typically performed in the field using a device such as a Free Water Knockout (FWKO) to separate the produced water from the oil. Generally, produced oil contains water at amounts far above the typical pipeline specification of 0.5% and the objective of the FWKO is to remove water to below the pipeline specification. The desalting step in a refinery is provided by adding and mixing with the crude a few volume percentages of fresh water to contact brine left in the crude oil as an emulsion and allow this brine to be removed. Desalting provides benefits to the processing or refining of crude oils, including, reducing crude unit corrosion; reducing

219633

crude preheat system fouling; reducing the potential for distillation column damage; reducing energy costs; and reducing downstream process and product contamination.

[0004] In crude oil desalting, an emulsion of water in oil is intentionally formed with the water admitted being on the order of about four (4) to about ten (10) percent by volume based on the crude oil. Water is added to the crude and mixed intimately to transfer the impurities in the crude to the water phase. Separation of the phases occurs due to coalescence of the small water droplets into progressively larger droplets and eventual gravitational separation of the oil and underlying water phase.

[0005] In US patent no. 4,778,589, a process is disclosed for the removal of metal contaminants, particularly calcium, from hydrocarbonaceous feedstocks. The process comprises mixing the feedstock with an aqueous solution of a metals sequestering agent, particularly hydroxycarboxylic acids, and more particularly, citric acid, or salts or mixtures thereof, and separating the aqueous solution containing the metals from the demetalated feedstock.

[0006] US patent no. 5,078,858, discloses and claims methods for extracting iron species, such as iron naphthenate and iron sulfides from a liquid hydrocarbon, such as crude oil. A chelant selected from the group consisting of oxalic or citric acid is added directly to the liquid hydrocarbon and mixed therewith. The wash water is added to form a water in oil emulsion, the emulsion is resolved, and the iron laden aqueous phase is separated.

[0007] In US patent application publication no. US 2004/0045875 A1, it was found that metals and/or amines can be removed or transferred from a hydrocarbon phase to a water phase in an emulsion breaking process by using a composition that contains water-soluble hydroxyacids. The composition may also include at least one mineral acid to reduce the pH of the desalter wash water. A solvent may be optionally included in the composition. The process permits transfer of metals and/or amines into the aqueous phase with little or no hydrocarbon phase under-carry into the aqueous pHs.

[0008] Accordingly, a need still exists for a process that would show an improvement over the extraction of the contaminants in the crude oils such that the contaminants are not partitioned into the crude in the desalting process, using

219633

components that are water soluble, do not result in acids in the crude unit overhead that can raise neutralizer demand, are stable at high temperatures and that are easy to implement.

Summary of the Invention

[0009] An extraction aid has been found which provides for enhanced contaminate removal, such as metals and amines, from crude oils that uses components that are desirable in production and desalting processes as the components are water soluble, have low toxicity, are highly biodegradable and exhibit high thermal stability.

[0010] According to one embodiment of the invention, an extraction aid that provides enhanced extraction properties is comprised of a blend of acids, particularly water-soluble acids. More specifically, a combination of two acids chosen from the group consisting of acetic acid, sulfuric acid, glycolic acid, citric acid and methanesulfonic acid.

[0011] An alternate embodiment showing synergistic effects in extraction is comprised of methanesulfonic acid (MSA) and citric acid, the combination of that has been found to perform better than the use of a single acid, such as citric acid.

[0012] In a further alternative embodiment of the invention, it was found by exploration, that the synergistic effect of the combination of methanesulfonic acid and citric acid was evident when methanesulfonic acid is present at levels of from about 5 to about 50% by volume of the extraction aid. Synergistic effects appear to be at a maximum at when methanesulfonic acid is present in the extraction aid at a level of between about 10 and about 20% by volume.

[0013] The various features of novelty that characterize the invention are pointed out with particularity in the claims annexed to and forming a part of this disclosure. For a better understanding of the invention, its operating advantages and benefits obtained by its uses, reference is made to the accompanying drawings and descriptive matter. The accompanying drawings are intended to show examples of the invention. The drawings are not intended as showing the limits of all of the ways the invention can be made and

219633

used. Changes to and substitutions of the various components of the invention can of course be made. The invention resides as well in sub-combinations and sub-systems of the elements described, and in methods of using them.

Brief Description of the Drawings

- [0014]** Figure 1 is a graphic display of enhanced amine extraction vs. untreated waste water according to an embodiment of the present invention.
- [0015]** Figure 2 is a graph displaying synergy from the combined acid extraction aid according to an embodiment of the present invention.
- [0016]** Figure 3 is a graph displaying enhanced amine extraction vs. a citric acid extraction aid according to an embodiment of the present invention.

Detailed Description of the Invention

[0017] Approximating language, as used herein throughout the specification and claims, may be applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “about”, is not limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value. Range limitations may be combined and/or interchanged, and such ranges are identified and include all the sub-ranges included herein unless context or language indicates otherwise. Other than in the operating examples or where otherwise indicated, all numbers or expressions referring to quantities of ingredients, reaction conditions and the like, used in the specification and the claims, are to be understood as modified in all instances by the term “about”.

[0018] As used herein, the terms “comprises,” “comprising,” “includes,” “including,” “has,” “having” or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, method, article or apparatus that comprises

219633

a list of elements is not necessarily limited to only those elements, but may include other elements not expressly listed or inherent to such process, method article or apparatus.

[0019] According to one embodiment of the invention, an extraction aid, that provides enhanced extraction properties, for removing contaminants from crude oil during the desalting process in oil refining is comprised of a blend of acids, particularly water soluble acids. It has been found that the addition of a combination of acids to a crude oil can significantly reduce the amount of calcium and other metals and the amount of amines in the hydrocarbon when it is run through a desalter in a refinery. The combination of acids has been found to reduce the contaminants, particularly metal and amine contaminants, in the hydrocarbon at a higher level than a single acid alone when used as an extraction aid.

[0020] Various chemical species that enter a refinery with crude oil can be deleterious to either processing or product quality. One such group or chemical entity is the family of amines. Depending on relative boiling points, certain alkyl amines for instance, can remain in the crude oil after desalting and distill up the atmospheric tower. HCl salts of these amines can lead to deposition and to very aggressive under-deposit corrosion or molten salt corrosion. Rates of greater than 1000 mpy (mils per year penetration of corrosion) have been identified. This becomes particularly problematic if the salt point of the amine HCl salt is located in the tower top or draw lines, ahead of the water dew point. The sources of amines are many and include amines from an acid gas scrubbing unit, blowdown or leaks. It is also possible that amines enter the crude tower by virtue of coming from the desalter wash water and partitioning into the crude in the desalter. Amines which are present and demonstrate these characteristics, and which are significantly reduced by the addition of the extraction aid are known in the industry, and include but are not limited to, ethanolamine, diethanolamine, triethanolamine, N-methylethanolamine, N,N-dimethylethanolamine, morpholine, N-methyl morpholine, ethylenediamine, methoxypropylamine, N-ethyl morpholine, N-methyl ethanolamine, N-methyldiethanolamine, dibutylamine, and combinations thereof.

[0021] Another chemical species that are not desirable in the processing of crude oils and lead to problems are metals. It is intended that metals referred to in this

219633

invention included, but are not limited to, those Groups IA, IIA, VB, VIII, IIB and IVA of the Periodic Table (CAS version). In another, non limiting embodiment, the metals include, but are not limited to calcium, iron, zinc, silicon, nickel, sodium, potassium, vanadium and combinations thereof. Metals that are not extracted from the oil in the desalter, for instance, iron, may end up in the bottoms of the atmospheric distillation and in the coke made from these bottoms. This results in coke, which is off specification for metals. Residual calcium can cause coker furnace fouling, drive residual fuel off specification for metal content or act as a catalyst poison in FCC feeds.

[0022] The desalting process in general is used as a means to remove undesirable species from crude oil.. Water washing alone can extract some contaminants, including some metals and amines. Acids in general can assist with the removal of contaminants, particularly amines, by protonating the amines and making them more soluble in water. The beneficial effect of the acids is pronounced with the use of hydrophilic amines. An extraction aid that provides enhanced extraction properties is comprised of a blend of acids, particularly water-soluble acids. More specifically, a combination of two acids chosen from the group consisting of acetic acid, sulfuric acid, glycolic acid, citric acid and methanesulfonic acid.

[0023] Acids that are water soluble are preferred, particularly citric acid, which not only exhibits water solubility but is also not soluble in hydrocarbons, and therefore does not result in acids remaining or entering the crude unit overhead. Such an action would result in the need to raise the amount of neutralizer. Citric acid ($C_6H_8O_7$) is a weak organic acid, with a water solubility of 133 g/100 ml (20°C), and is not soluble in hydrocarbons, and is environmentally benign, and is therefore a preferred acid.

[0024] Methanesulfonic acid (CH_3SO_2OH), is a member of the sulfonic acid family, and is an organic acid. It is water soluble, but not soluble in hydrocarbons, exhibits stability at high temperatures and is biodegradeable.

[0025] By combining two acids to create an extraction aid, synergistic effects are exhibited on the extraction of contaminants from crude oils, particularly with respect to the extraction of metals, such as but not limited to iron and zinc, and/or amines. The synergistic value of the combined acids varies according to the composition of the

219633

extraction aid. Synergistic effects are exhibited in extraction aids that are comprised of from about 5 to about 50% by volume of methanesulfonic acid, with the second acid comprising citric acid. One embodiment of the invention comprises an extraction aid comprising methanesulfonic acid and citric acid, wherein the methanesulfonic acid comprises from about 10 to about 20% by volume methanesulfonic acid.

[0026] Synergistic effects are seen with the combined acid extraction aid when compared to wash water alone, or a single acid extraction aid, such as citric acid. In an embodiment wherein methanesulfonic acid and citric acid are combined in an extraction aid, extraction enhancements are seen from up to about 70% over untreated wash water. The average extraction enhancement in such an embodiment is from about 20 to about 40% over untreated wash water. These synergistic effect is seen over a variety of crude oils, which exhibit a variety of contaminants, including various amines. Examples of such crude oils include, but are not limited to Syncrude PZ, Maya, Arab Medium and Heidrun. The synergistic effect also varies in relation to different amines, such as dibutylamine (DBA), dimethylethanoamine(DMEA), morpholine (MORPH), diethanolamineand (DEA), and monoethanolamine(MEA)..

[0027] Synergistic effects are also exhibited by the use of an extraction aid comprised of methanesulfonic acid and citric acid, over the use of an extraction aid comprised of only one acid, such as citric acid. This is particularly true with respect to the extraction of amines, and even more so with respect to polar amines.

Example

[0028] Desalter simulations were performed using five industry relevant amines, DBA, DMEA, MORPH, DEA and MEA, in several crude oils of varying properties, in particular the crudes were Syncrude PZ, Maya, Arab Medium and Heidrun. The crudes wer dosed with 200 ppm of the amines, a laboratory desalter simulation was conducted with treated and untreated wash water. The process used 4-8% wash water at from 240 to 300°F, with added shear. The results are displayed in the following chart.

Sample	DBA ppm	DMAE ppm	MORPH ppm	DEA ppm	MEA ppm
Syncrude – tap water	135	80	80	59	40
Syncrude – pH 5 with citric acid	104	65	68	66	26
Syncrude – pH 5 citric acid/MSA (4:1)	124	66	70	14	7
Heidrun – tap water	100	80	75	48	26
Heidrun – pH 5 with citric acid	129	70	64	23	8
Heidrun – pH 5 citric acid/MSA (4:1)	115	70	68	47	22
Maya – tap water	119	70	80	30	18
Maya – pH 5 with citric acid	128	90	98	40	34
Maya – repeat at pH 5 (citric)	124	37	45	19	16
Maya – pH 5 citric acid/MSA (4:1)	144	47	49	13	6
Arab Med – tap water	148	90	95	37	27
Arab Med - pH 5 with citric acid	176	100	77	20	15
Arab Med - pH 5 citric acid/MSA (4:1)	162	69	58	16	7

219633

[0029] The percentage of amine extraction enhancement over untreated wash water is shown in accompanying Fig. 1, while Fig. 3 shows the enhanced extraction over an extraction aid with a single acid, specifically citric acid. Fig. 2 displays the synergy of the combined acids according to the present invention. While the present invention has been described with references to preferred embodiments, various changes or substitutions may be made on these embodiments by those ordinarily skilled in the art pertinent to the present invention without departing from the technical scope of the present invention. Therefore, the technical scope of the present invention encompasses not only those embodiments described above, but all that fall within the scope of the appended claims.

219633

What is claimed is:

1. An extraction aid for the removal of contaminants in crude oil during a refining process, wherein the extraction aid comprises a combination of water soluble acids.
2. The extraction aid of claim 1 wherein the extraction is conducted in a desalter process.
3. The extraction aid of claim 1 wherein the water soluble acids are chosen from the group consisting of acetic acid, sulfuric acid, glycolic acid, citric acid and methanesulfonic acid.
4. The extraction aid of claim 1 wherein the combination of water soluble acids is comprise of two acids.
5. The extraction aid of claim 1 wherein one of the water soluble acids is methanesulfonic acid.
6. The extraction aid of claim 1 wherein the combination of water soluble acids consists of methansulfonic acid and citric acid.
7. The extraction aid of claim 6 wherein the methansulfonic acid is present in an amount of from about 5 to about 50% by volume of the aid.
8. The extraction aid of claim 6 wherein the methansulfonic acid is present in an amount of from about 10 to about 20% by volume of the aid.
9. The extraction aid of claim 1 wherein the contaminants extracted comprise metals and/or amines.
10. An extraction aid for enhanced removal of contaminants during the desalting process in a refinery, wherein the extraction aid is comprised of water-soluble acids.
11. The extraction aid of claim 10 wherein the water soluble acids are chosen from the group consisting of acetic acid, sulfuric acid, glycolic acid, citric acid and methanesulfonic acid.
12. The extraction aid of claim 10 wherein the extraction aid consists of methansulfonic acid and citric acid.

219633

13. A process for the removal of contaminants in a crude oil refinery wherein the extraction aid for the desalting process is comprised of a combination of water soluble acids.

14. The process of claim 14 wherein water soluble acids are chosen from the group consisting of acetic acid, sulfuric acid, glycolic acid, citric acid and methanesulfonic acid.

15. The process of claim 15 wherein the extraction aid consists of methanesulfonic acid and citric acid.