

Description

This invention relates generally to heat transfer and more particularly to an improved heat exchanger for transferring heat between two fluids.

Heat exchangers comprising a tube bundle enclosed in a case or housing, generally identified as shell-and-tube type heat exchangers, are well known. Traditionally, shell-and-tube heat exchangers have been constructed of metallic materials. In particular, the tube bundle has conventionally been formed of a plurality of elongated metal tubes that are brazed in a predetermined pattern to a pair of end walls and one or more internal baffle plates. Such brazed assemblies are not only costly, but are also prone to both thermal and vibration-induced mechanical fatigue cracking and subsequent leakage between the fluid chambers at the brazed joints and at the contact points between the tubes and the internal baffle plates. Further, the brazing process tends to anneal the metal tubes, thereby reducing the yield strength of the tubes. In high pressure applications, annealed tubes may collapse, resulting in failure of the heat exchanger.

In an attempt to avoid the above-described inherent problems associated with brazed or soldered heat exchangers, various mechanical sealing arrangements have been proposed. One such example is the tube bundle heat exchanger described in US-A-4,328,862. This patent discloses an elastic sealing means for a heat exchanger wherein a pair of pressure plates exert a force in the longitudinal direction of the tube bundle to expand the elastic sealing means in a transverse, or radial, direction thus confining the elastic sealing means in all directions. However, this construction still presents a number of problems. First, the requirement for a pair of apertured pressure plates limits the number of tubes that may be enclosed within the shell. As the number of tubes in the tube bundle increases, the number of apertures provided in the pressure plates through which the tubes pass, must also increase. Typically, a 152 mm (6 in.) diameter heat exchanger may contain about 600 tubes having a 4.78 mm (.188 in. diameter). Forming 600 clearance holes in each of the pressure plates would not only be extremely costly and time consuming but would also significantly weaken the plate. If the thickness of the pressure plates were increased to add strength, the cost and difficulty of forming the required number of clearance holes would also increase. Further, the pressure plate would be structurally weaker towards the center of the plate and would be unable to apply a uniform, equal compression force across the complete elastic medium interface surface.

An additional deficiency in the prior art is that as the axially applied compressive pressure increases, the sealing surface contact area between the elastic medium and the tubes and shell wall also decreases. Further, if the clamping bolts are overly tightened, the confined elastic medium may easily collapse some of the tubes, especially

the relatively small diameter tubes found in high efficiency, high density heat exchangers. This attribute is further worsened by the tendency of maintenance personnel to tighten the clamping bolts if leakage is detected.

FR-A-1089816 discloses a heat exchanger (hereinafter referred to as of the kind described) including a rigid peripheral shell and a plurality of tubes disposed within the shell and, at at least one end of the shell, extending through apertures in an elastomeric end plate; the periphery of the end plate being sealed to the shell and the part of the end plate defining the apertures being axially unconstrained and sealing resiliently against the tubes by virtue of the free-state transverse area of each of the apertures being smaller than the transverse area of the respective tubes.

In this construction, the periphery of the end plate is gripped between two flanged parts of the shell to seal the end plate to the shell but this does not contribute to the sealing between the end plate and tubes.

GB-A-1477839 discloses somewhat similar constructions of heat exchanger and, in Figure 6, an arrangement in which the elastomeric end plate is radially compressed by a clamp which surrounds the shell. However the shell must consequently be flexible where as the invention refers to a rigid shell and it is acknowledged that the arrangement is only suitable for pressures up to 206 kPa (30 psi).

In addition to the problems outlined above with respect to brazed and soldered end plate constructions, it has been found that tube fractures may also occur at the surface contact points between the tubes and one or more internal baffle plates. For ease in assembly, it is generally accepted practice to form tube-receiving apertures in the baffle plate to the same or a slightly larger diameter than the external diameter of the tubes. During operation of the heat exchanger, it has been found that the tubes are often subjected to severe vibration both from external sources and from internal fluid pressure pulses. Initially, the lateral displacement or movement of the tubes during various vibrational modes is limited by the close-fitting baffle plates. However, after repeated forced contact either the tubes or the plate, or both, may wear or deform and the clearance between the tube and baffle aperture becomes greater, thereby permitting increased movement of the tube within the baffle. This action not only leads to early mechanical or fatigue failure of the tube but also permits fluid to pass through the enlarged aperture thereby decreasing the flow-directing function of the baffle.

According to the invention, a heat exchanger of the kind described is characterised in that the outer periphery of the end plate is axially unconstrained and seals resiliently against the inner surface of the shell by virtue of the surface circumscribing a transverse area which is smaller than the transverse area of the end plate; and in that the compressive forces experienced by the end plate from the tubes and the shell in the plane

of the end plate are such as to cause expansion of the end plate in the direction along the tubes throughout substantially its whole area of between 5 and 50% of the thickness of the uncompressed end plate.

This construction provides a rugged, economical, and efficient heat exchanger end wall assembly, avoiding the requirement for costly and design-limiting pressure plates. Further, it eliminates the need for adjustable exterior clamping members where improper operation may be an inadvertent cause of damage to the heat exchanger tubes. Still further, as a result of applying the compressive force only in the direction transverse to the tubes, the sealing surface contact area between the elastomeric end plate and each of the tubes and, also the shell wall, increases in response to an increase in the compressive force.

The heat exchanger may include at least one baffle plate disposed inwardly of the shell normal to the tubes and preferably constructed of a vibration energy absorbing material having a hardness less than the hardness of the tubes.

This overcomes the problem of vibration-induced internal tube damage by providing a vibration-damping baffle plate constructed, e.g. of a non-metallic material that is considerably softer than the material of the tubes. Further, the baffle plates provide an effective non-absorbing support between each of the tubes and each of the plates. The elastomeric end plates and the non-metallic baffle plates then cooperate to provide a resilient, vibration energy absorbing support for each of the tubes in the tube bundle.

The baffle plate per se is subject of a divisional European patent application published under number EP-A-171 090.

An example of a heat exchanger constructed in accordance with the invention is illustrated in the accompanying drawings, in which:—

Figure 1 is a partially sectioned, elevation; and, Figure 2 is an end view.

As illustrated, a heat exchanger 10 includes a conventional shell 12 having an inner wall 14 and a plurality of longitudinally extending tubes 16 disposed within the shell 12. In the example shown in Figure 1, the heat exchanger 10 is of the single pass type and has a pair of elastomeric end plates 18 forming part of an end plate assembly 19 at each end of the shell 12 with each of the tubes 16 extending through a respective aperture 20 formed through each of the end plates 18. In heat exchangers of the double-pass type, one end of the heat exchanger may have a solid end wall and the opposite end have an apertured elastomeric end plate assembly 19 constructed according to the present invention. The heat exchanger 10 also includes a plurality of non-metallic internal baffle plates 28 disposed inwardly of the shell 12 at predetermined spaced positions along the normal to the longitudinal axis X of the tubes 16.

Preferably, the elastomeric end plate 18 is constructed of a natural or synthetic resin material having a hardness of from about 45

durometer to about 80 durometer as measured in the Shore A scale. It is necessary that the hardness of the end plate 18 be sufficient to support the tubes 16 in a sealed relationship with respect to the internal chamber defined by the shell 12 and yet not be adversely axially deflected by high pressure pulses that may be transmitted by fluid in the shell chamber. Also, the hardness should not be so high that the transverse compressive stress required for sealing the tube and chamber is not greater than the transverse crush strength of the tubes 16. In addition, the end plate material should have good resistance to the effects of both high and low temperatures and in particular should be resistant to temperature induced deterioration within the thermal operating range of the heat exchanger 10. Further, the end plate material should have good resistance to the deleterious effects of the particular fluids that may be passed through the heat exchanger 10. While by no means being an all-inclusive list, materials having these properties include some compounds of natural rubber, synthetic rubber, thermoset elastomers and thermoplastic elastomers. Examples of suitable thermoset elastomers include butyl rubber, chlorosulfonated polyethylene, chloroprene (neoprene), chlorinated polyethylene, nitrile butadiene, epichlorohydrin, polyacrylate rubber, silicone, urethane, fluorosilicone and fluorocarbon. Polyurethane, copolyester and polyolefin are examples of suitable thermoplastic elastomers.

The baffle plates 28 are preferably constructed of a non-metallic, vibration-energy absorbing material having a hardness substantially less than the hardness of the tubes 16, such as an asbestos filled neoprene rubber having a durometer hardness of about 80 on the Shore D scale. Other suitable materials include but are not limited to the compounds listed above with respect to the end plate 18. Combinations of the listed compounds and various metallic, mineral or organic fiber fillers are particularly useful.

A means 22 for compressing the elastomeric end plate 18 includes a continuous surface 24 on the inner wall 14 of the shell 12. The surface 24 circumscribes a transverse area that is somewhat smaller than the unconfined or free-state transverse area of the end plate 18. After the end plate is installed in the shell 12, the inner wall 14 will urge the outer periphery of the end plate 18 radially inwardly and maintain a compressive stress about the circumference of the end plate 18. Further, the means 22 for compressing the elastomeric end plate 18 includes in combination with the inner wall 14 of the shell 12, an external surface area 26 on each of the tubes 16. The free-state transverse area of each of the apertures 20 is somewhat smaller than the transverse or cross-sectional area of each of tubes 16 so that the external surface area 26 on each of the tubes 16 will urge a portion of the end plate 18 immediately surrounding, or circumscribing, each of the tubes 16 in a direction radially outwardly and maintain a stress on the end plate 18 in a

transverse direction with respect to the longitudinal orientation of the tubes 16.

In the preferred embodiment of the present invention, the shell 12 of the heat exchanger 10 is constructed of a ferrous metal composition, has a length of about 762 mm (30.0 in.) and an inner wall 14 diameter of 164.64 mm (6.482 in.). The tubes 16 are copper, have a length of 759 mm (29.88 in.), an outer diameter of 4.78 mm (.188 in.) and an inner diameter of 4.17 mm (.164 in.). The tubes 16 are carefully arranged in offset parallel rows inside the shell to provide a large number of tubes and consequently a large heat transfer surface area. The example heat exchanger 10 of the present invention contains 579 of the tubes 16, providing a tube/cross-section area ratio of about 2.7 tubes/cm². High tube density heat exchangers in this general size group typically range from about 1 to about 3 tubes/cm².

In the present example, the end plates 18 are constructed of a neoprene rubber composition having a Shore A durometer hardness of 60. The end plate has an unconfined, or free-state, axial thickness, i.e., a dimension measured in the longitudinal direction of the apertures 20 of 23.6 mm (0.93 in.), and a transverse diameter of 172.03 mm (6.773 in.). Each of the apertures 20 have a free-state diameter of 4.22 mm (.166 in.).

Upon assembly of the end plate 18 in the end of the shell 12 and insertion of the tubes 16 through apertures 20 provided in the end plate 18, as shown in Fig. 1, the outer circumference of the end plate 18 is reduced from the free-state diameter of 172.03 mm to the diameter of the inner wall 14; i.e., 164.64 mm. The end plate 18 is therefore radially compressed by the fixed surface of the inner wall 14 of the shell 12 to a dimension 4.4% less than the unconfined or free-state dimension of the end plate 18, thereby providing and maintaining a radial compressive stress on the periphery of the end plate 18. To achieve the required compressive stress, the end plate 18 should be compressed by the inner wall 14 of the shell 12 to a predetermined dimension at least sufficient to provide an adequate fluid seal between the end plate 18 and the inner wall 14.

Further, the end plate 18 is stressed in the transverse direction by insertion of the tubes 16, or alternatively, by expansion of the tubes 16 after insertion of the tubes 16 through the apertures 20 in the end plate. As listed above, the outer diameter of the tubes 16 is 4.78 mm and the free-state diameter of the apertures 20 is 4.22 mm. The apertures are therefore expanded about 12% in a direction radially outwardly from each of the tubes 16 to establish and maintain a radial stress in the end plate 18 about each of the tubes 16. It is recommended that the apertures 20 be sized so that there is at least an interference fit between a tube 16 and a corresponding aperture 20, and preferably that the diameter of the aperture 20 be expanded by placement of the tube to provide a compressive stress to assure sufficient

retention of the tube in the end plate and a fluid seal between the external surface area 26 of the tubes 16 and the end plate 18.

In the example presented above, the end wall is sufficiently stressed in the transverse direction by the inner wall 14 of the shell 12 and the external surfaces 26 of the tubes 16 to axially expand i.e., expand in the longitudinal direction of the tubes 16, the end plate 18 from the free state dimension of 23.6 mm (0.93 in.) to 31.8 mm (1.25 in.). The end plate 18 is therefore axially expanded to a dimension about 34% greater than the unconfined or free-state axial dimension of the end plate. It is easily seen that since the end plate 18 is unrestrained in the axial direction, the amount of elongation, or expansion, in the axial direction is a function of the combined material properties and the transverse compressive stresses provided by the inner wall 14 and tube external surface areas 26. Preferably the end plate 18 should be sufficiently transversely compressed to expand the plate 18 to a predetermined axial dimension in a range of from about 5% to about 50% greater than the axial dimension of the end plate 18 when measured in an unconfirmed, or free state. Also, it can be easily seen that for a given elastomeric material, the axial elongation of the end plate 18, and consequently the contact area between the end plate 18 and each of the tubes 16 will increase in response to increasing the radial stress on the end plate.

The baffle plates 28 provide support and alignment for the tubes 16 which pass through apertures formed in each of the baffle plates. Further, as is well known in the art, baffle plates form a series of partial dams or flow-directing walls within the shell to provide improved circulation and heat transfer between fluid passing through the shell chamber and fluid passing through the tubes. Conventionally, baffle plates are constructed of a metal and are mechanically positioned within the shell 12 to prevent movement of the baffle plates during operation of the heat exchanger. In the preferred embodiment of the present invention, the baffle plates 28 are constructed of an asbestos-filled neoprene—a non-metallic, vibration-energy absorbing, sheet material, having a Shore D durometer hardness of about 80 and a thickness of 3 mm (.120 in.). The baffle plates 28 can be adhesively bonded to the external surface of at least some of the copper tubes 16 with nitrile phenolic adhesive to establish an initial position for assembly purposes. The plurality of openings formed in each of the baffle plates 28 for passage of the heat exchanger tubes 16, each have a dimension substantially the same as the outer diameter of the tubes 16. It has been found that with somewhat resilient materials, such as the asbestos-filled neoprene composition of the preferred embodiment, the openings in the baffle plate 28 tend to diminish in cross-sectional area after forming. This characteristic, in combination with the greater thickness of the baffle plate serves to

13

support a sufficient length of the tube to avoid the sharp edges and deleterious wear attributable to the thin metal plates of the prior art constructions. Further, it has been found that the asbestos-filled neoprene composition of the preferred embodiment tends to swell slightly in the presence of oil, thereby increasing the mechanical support and decreasing the amount of leakage about each of the tubes 16 and accordingly improving the heat transfer performance when oil is the fluid medium circulated through the outer chamber of the heat exchanger 10.

Heat exchangers 10 having the end wall and baffle plate assemblies of the present invention have been found to be particularly suitable for use in vehicular applications. The high vibration, cyclic pressure and heat load requirements of vehicle engine, transmission and hydraulic accessory systems have only marginally been satisfied by conventional brazed-assembly metallic heat exchangers.

In one test, a heat exchanger 10 constructed according to the present invention has been installed in the implement hydraulic circuit of a large track-type tractor. The heat exchanger has successfully accumulated over 600 operating hours at the time of the filing of this application for patent. In this particular example, SAE 10 oil at a typical temperature of about 93°C and at inlet pressure of about 350 kPa passes through the shell chamber and about the external surfaces of the tubes. Coolant having a conventional mixture of water and anti-freeze passes through the tubes 16 at a normal operating temperature of about 82°C and at an inlet pressure of about 90 kPa. In addition to the above test, heat exchangers of the present invention have been bench tested wherein a pressure of 2100 kPa (305 psi) has been cyclicly applied for an extended time period to the internal shell chamber without failure or leakage of the end wall assembly 19.

The heat exchanger of the present invention is believed suitable for a large number of applications whereif the performance requirements are severe and where heat exchangers of prior art constructions have been inadequate or prone to high failure rates.

Claims

1. A heat exchanger (10) including a rigid peripheral shell (12) and a plurality of tubes (16) disposed within the shell and, at at least one end of the shell, extending through apertures (20) in an elastomeric end plate (18); the periphery of the end plate being sealed to the shell, and the part of the end plate (18) defining the apertures (20) being axially unconstrained and sealing resiliently against the tubes by virtue of the free-state transverse area of each of the apertures (20) being smaller than the transverse area of the respective tubes; characterised in that the outer periphery of the end plate is axially unconstrained and seals resiliently against the inner surface (24) of the shell by virtue of the surface (24) circumscribing a

transverse area which is smaller than the free-state transverse area of the end plate (18); and in that the compressive forces experienced by the end plate from the tubes and the shell in the plane the end plate are such as to cause expansion of the end plate in the direction along the tubes throughout substantially its whole area of between 5 and 50% of the thickness of the uncompressed end plate.

2. A heat exchanger (10) according to claim 1, wherein the end plate is constructed of a material selected from the group including compounds of natural rubber, synthetic rubber, thermoset elastomers and thermoplastic elastomers.

3. A heat exchanger (10) according to claim 2, wherein the end plate (18) is constructed of a neoprene rubber composition.

4. A heat exchanger (10) according to any one of the preceding claims, wherein the elastomeric end plate (18) has a hardness of between 45 and 80 durometer as measured as measured on the Shore A scale.

5. A heat exchanger (10) according to claim 4, wherein the end plate has a hardness of substantially 60 durometer as measured on the Shore A scale.

6. A heat exchanger (10) according to any one of the preceding claims, wherein the ratio of the number of tubes (16) to the area of the end plate (18) is in a range from 1 to 3 tubes/cm².

7. A heat exchanger according to any of the preceding claims, wherein the tubes are constructed of copper.

8. A heat exchanger (10) according to any one of the preceding claims including at least one baffle plate (28) disposed inwardly of the shell (12) normal to the tubes.

9. A heat exchanger according to claim 8, wherein the baffle plate (28) is constructed of a vibration energy absorbing material having a hardness less than the hardness of the tubes (16).

10. A heat exchanger according to claim 9, wherein the baffle plate (28) is constructed of a reinforced natural or synthetic resin.

11. A heat exchanger according to any one of claims 8 to 10, wherein the baffle plate has a hardness of substantially 80 durometer as measured on the Shore D scale.

Patentansprüche

1. Ein Wärmeaustauscher (10) mit einem starren Umfangsmantel (12) und einer Vielzahl von Rohren (16), angeordnet innerhalb des Mantels, und wobei mindestens ein Ende des Mantels sich durch Öffnungen (20) in einer elastomeren Endplatte (18), erstreckt, wobei der Umfang der Endplatte mit dem Mantel abdichtend verbunden ist und der Teil der Endplatte (18) der die Öffnungen (20) bildet axial nicht eingeschränkt ist und elastisch gegenüber den Rohren abdichtet, und zwar basierend darauf, daß im freien Zustand die Querschnittsfläche jeder der Öffnungen (20) kleiner ist als die Querschnittsfläche der entsprechenden Rohre, dadurch gekennzeichnet, daß der Außenumfang der Endplatte axial nicht einge-

support a sufficient length of the tube to avoid the sharp edges and deleterious wear attributable to the thin metal plates of the prior art constructions. Further, it has been found that the asbestos-filled neoprene composition of the preferred embodiment tends to swell slightly in the presence of oil, thereby increasing the mechanical support and decreasing the amount of leakage about each of the tubes 16 and accordingly improving the heat transfer performance when oil is the fluid medium circulated through the outer chamber of the heat exchanger 10.

Heat exchangers 10 having the end wall and baffle plate assemblies of the present invention have been found to be particularly suitable for use in vehicular applications. The high vibration, cyclic pressure and heat load requirements of vehicle engine, transmission and hydraulic accessory systems have only marginally been satisfied by conventional brazed-assembly metallic heat exchangers.

In one test, a heat exchanger 10 constructed according to the present invention has been installed in the implement hydraulic circuit of a large track-type tractor. The heat exchanger has successfully accumulated over 600 operating hours at the time of the filing of this application for patent. In this particular example, SAE 10 oil at a typical temperature of about 93°C and at inlet pressure of about 350 kPa passes through the shell chamber and about the external surfaces of the tubes. Coolant having a conventional mixture of water and anti-freeze passes through the tubes 16 at a normal operating temperature of about 82°C and at an inlet pressure of about 90 kPa. In addition to the above test, heat exchangers of the present invention have been bench tested wherein a pressure of 2100 kPa (305 psi) has been cyclicly applied for an extended time period to the internal shell chamber without failure or leakage of the end wall assembly 19.

The heat exchanger of the present invention is believed suitable for a large number of applications whereif the performance requirements are severe and where heat exchangers of prior art constructions have been inadequate or prone to high failure rates.

Claims

1. A heat exchanger (10) including a rigid peripheral shell (12) and a plurality of tubes (16) disposed within the shell and, at at least one end of the shell, extending through apertures (20) in an elastomeric end plate (18); the periphery of the end plate being sealed to the shell, and the part of the end plate (18) defining the apertures (20) being axially unconstrained and sealing resiliently against the tubes by virtue of the free-state transverse area of each of the apertures (20) being smaller than the transverse area of the respective tubes; characterised in that the outer periphery of the end plate is axially unconstrained and seals resiliently against the inner surface (24) of the shell by virtue of the surface (24) circumscribing a

transverse area which is smaller than the free-stage transverse area of the end plate (18); and in that the compressive forces experienced by the end plate from the tubes and the shell in the plane the end plate are such as to cause expansion of the end plate in the direction along the tubes throughout substantially its whole area of between 5 and 50% of the thickness of the uncompressed end plate.

2. A heat exchanger (10) according to claim 1, wherein the end plate is constructed of a material selected from the group including compounds of natural rubber, synthetic rubber, thermoset elastomers and thermoplastic elastomers.

3. A heat exchanger (10) according to claim 2, wherein the end plate (18) is constructed of a neoprene rubber composition.

4. A heat exchanger (10) according to any one of the preceding claims, wherein the elastomeric end plate (18) has a hardness of between 45 and 80 durometer as measured as measured on the Shore A scale.

5. A heat exchanger (10) according to claim 4, wherein the end plate has a hardness of substantially 60 durometer as measured on the Shore A scale.

6. A heat exchanger (10) according to any one of the preceding claims, wherein the ratio of the number of tubes (16) to the area of the end plate (18) is in a range from 1 to 3 tubes/cm².

7. A heat exchanger according to any of the preceding claims, wherein the tubes are constructed of copper.

8. A heat exchanger (10) according to any one of the preceding claims including at least one baffle plate (28) disposed inwardly of the shell (12) normal to the tubes.

9. A heat exchanger according to claim 8, wherein the baffle plate (28) is constructed of a vibration energy absorbing material having a hardness less than the hardness of the tubes (16).

10. A heat exchanger according to claim 9, wherein the baffle plate (28) is constructed of a reinforced natural or synthetic resin.

11. A heat exchanger according to any one of claims 8 to 10, wherein the baffle plate has a hardness of substantially 80 durometer as measured on the Shore D scale.

Patentansprüche

1. Ein Wärmeaustauscher (10) mit einem starren Umfangsmantel (12) und einer Vielzahl von Rohren (16), angeordnet innerhalb des Mantels, und wobei mindestens ein Ende des Mantels sich durch Öffnungen (20) in einer elastomeren Endplatte (18), erstreckt, wobei der Umfang der Endplatte mit dem Mantel abdichtend verbunden ist und der Teil der Endplatte (18) der die Öffnungen (20) bildet axial nicht eingeschränkt ist und elastisch gegenüber den Rohren abdichtet, und zwar basierend darauf, daß im freien Zustand die Querschnittsfläche jeder der Öffnungen (20) kleiner ist als die Querschnittsfläche der entsprechenden Rohre, dadurch gekennzeichnet, daß der Außenumfang der Endplatte axial nicht einge-



14

schränkt ist und elastisch gegen die Innenoberfläche (24) des Mantels abdichtet, und zwar basierend darauf, daß die Oberfläche (24) eine Querschnittsfläche umschreibt, die kleiner ist als die im freien Zustand eingenommene Querschnittsfläche der Endplatte (18), und ferner dadurch gekennzeichnet, daß die von der Endplatte aufgenommenen Druckkräfte von den Rohren und dem Mantel in der Ebene der Endplatte derart sind, daß eine Ausdehnung der Endplatte in Richtung längs den Rohren hervorgerufen wird, und zwar über im wesentlichen deren gesamte Fläche hinweg, und zwar zwischen 5 und 50% der Dicke der nicht zusammengedrückten Endplatte.

2. Wärmeaustauscher (10) nach Anspruch 1, wobei die Endplatte aus einem Material aufgebaut ist, welches aus der folgenden Gruppe ausgewählt ist: Verbindungen aus natürlichem Gummi, synthetischem Gummi, unter Wärme aushärtenden Elastomeren und thermoplastischen Elastomeren.

3. Wärmeaustauscher (10) nach Anspruch 2, wobei die Endplatte (18) aus einer Neoprengummi-Zusammensetzung aufgebaut ist.

4. Wärmeaustauscher (10) nach einem der vorhergehenden Ansprüche, wobei die Elastomer-Endplatte (18) eine Härte zwischen 45 und 80 Durometer, gemessen auf der Shore-A-Skala aufweist.

5. Wärmeaustauscher (10) nach Anspruch 4, wobei die Endplatte eine Härte von im wesentlichen 60 Durometer, gemessen auf der Shore-A-Skala aufweist.

6. Wärmeaustauscher (10) nach einem der vorhergehenden Ansprüche, wobei das Verhältnis aus der Zahl der Rohre (16) zur Fläche der Endplatte (18) im Bereich von 1 bis 3 Rohren/cm² liegt.

7. Wärmeaustauscher (10) nach einem der vorhergehenden Ansprüche, wobei die Rohre aus Kupfer aufgebaut sind.

8. Wärmeaustauscher (10) nach einem der vorhergehenden Ansprüche, mit mindestens einer Prallplatte (28), angeordnet nach innen gegenüber dem Mantel (12), senkrecht zu den Rohren.

9. Wärmeaustauscher nach Anspruch 8, wobei die Prallplatte (28) aus einem Schwingungsenergie absorbierenden Material aufgebaut ist und eine Härte von weniger als der Härte der Rohre (16) aufweist.

10. Wärmeaustauscher nach Anspruch 8, wobei die Prallplatte (28) aus einem verstärkten natürlichen oder synthetischem Harz aufgebaut ist.

11. Wärmeaustauscher nach einem der Ansprüche 8 bis 10, wobei die Prallplatte eine Härte von im wesentlichen 80 Durometer, gemessen auf der Shore-D-Skala, aufweist.

Revendications

1. Echangeur de chaleur (10) comportant une coque périphérique rigide (12) et une multiplicité de tubes (16) disposés à l'intérieur de la coque, et s'étendant, au moins au niveau d'une extrémité de la coque, à travers des ouvertures (20) ména-

gées dans une plaque d'extrémité élastique (18), le pourtour de la plaque d'extrémité étant scellé à la coque, et la partie de la plaque d'extrémité (18) délimitant les ouvertures (20) n'étant pas contrainte axialement et s'appliquant élastiquement d'une manière étanche contre les tubes par le fait que la section transversale au repos de chacune des ouvertures (20) est inférieure à la section transversale des tubes respectifs, caractérisé en ce que le pourtour extérieur de la plaque d'extrémité n'est pas contraint axialement et s'applique élastiquement de façon étanche contre la surface intérieure (24) de la coque par le fait que la surface (24) circonscrit une aire transversale qui est inférieure à l'aire transversale au repos de la plaque d'extrémité (18), et en ce que les forces de compression, qui sont appliquées à la plaque d'extrémité par les tubes et la coque, dans le plan de la plaque d'extrémité, sont telles qu'elles entraînent une dilatation de la plaque d'extrémité, comprise entre 5 et 50% de l'épaisseur de la plaque d'extrémité non comprimée, suivant la direction longitudinal des tubes, et ce sensiblement sur toute la surface de la plaque.

2. Echangeur de chaleur (10) selon la revendication 1, dans lequel la plaque d'extrémité est réalisée en un matériau choisi dans le groupe comprenant des composés de caoutchouc naturel, de caoutchouc synthétique, d'élastomères thermodurcissables et d'élastomères thermoplastiques.

3. Echangeur de chaleur (10) selon la revendication 2, dans lequel la plaque d'extrémité (18) est réalisée en une composition de caoutchouc au néoprène.

4. Echangeur de chaleur (10) selon l'une quelconque des revendications précédentes, dans lequel la plaque d'extrémité élastique (18) possède une dureté comprise entre 45 et 80, telle que mesurée sur l'échelle Shore A.

5. Echangeur de chaleur (10) selon la revendication 4, dans lequel la plaque d'extrémité possède une dureté égale sensiblement à 60, telle que mesurée sur l'échelle Shore A.

6. Echangeur de chaleur (10) selon l'une quelconque des revendications précédentes, dans lequel le rapport du nombre des tubes (16) à la surface de la plaque d'extrémité (18) se situe dans une plage de 1 à 3 tubes/cm².

7. Echangeur de chaleur selon l'une quelconque des revendications précédentes, dans lequel les tubes sont réalisés en cuivre.

8. Echangeur de chaleur (10), selon l'une quelconque des revendications précédentes, renfermant au moins une chicane (28) disposée à l'intérieur de la coque (12), perpendiculairement aux tubes.

9. Echangeur de chaleur selon la revendication 8, dans lequel la chicane (28) est réalisée en un matériau absorbant l'énergie de vibration et présentant une dureté inférieure à la dureté des tubes (16).

10. Echangeur de chaleur selon la revendication 9, dans lequel la chicane (28) est réalisée en une résine naturelle ou synthétique, renforcée.



11. Echangeur de chaleur selon l'une quelconque des revendications 8 à 10, dans lequel la

chicane possède une dureté égale sensiblement à 80, telle que mesurée sur l'échelle Shore D.

15

5

10

15

20

25

30

35

40

45

50

55

60

65

7



* C L M S *