



- (51) **International Patent Classification:**
A61M 5/32 (2006.01)
- (21) **International Application Number:**
PCT/US2014/067925
- (22) **International Filing Date:**
1 December 2014 (01.12.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/910,373 1 December 2013 (01.12.2013) US
- (71) **Applicant:** BECTON, DICKINSON AND COMPANY [US/US]; Alan W. Fiedler, MC110, 1 Becton Drive, Franklin Lakes, New Jersey 07417 (US).
- (72) **Inventors:** CRONENBERG, Richard; 108 Kohout Drive, Mahwah, New Jersey 07430 (US). RAJ, Abhijitsing; 17 Stockton Court, Morris Plains, New Jersey 07950 (US). CHARVIN, Matthieu; 14 avenue Albert 1er de Belgique, F-38000 Grenoble (FR). BOOTH, David; 50A Beacon Hill Road, West Milford, New Jersey 07480 (US).
- (74) **Agents:** BUSH, Michael, A. et al.; Roylance, Abrams, Berdo & Goodman LLP, 1300 19th Street N.W., Suite 600, Washington, District of Columbia 20036 (US).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(88) **Date of publication of the international search report:**
17 September 2015

(54) **Title:** MEDICAMENT DEVICE




FIG. 12

(57) **Abstract:** A method for creating a sterile connection with a fluid in a container. The container has a sealing member sealing a first end of the container, and a barrier sealing a chamber in fluid communication with the sealing member. The method includes providing a valve sleeve assembly that includes a flexible sleeve having a barrier portion at an end of the flexible sleeve, a hollow first penetrator disposed within the flexible sleeve, and a hollow second penetrator at least partially disposed within the first penetrator. An interior of the flexible sleeve is sterile. The method also includes piercing the barrier portion and the barrier with the first penetrator, and displacing the second penetrator relative to the first penetrator and the sealing member to pierce the sealing member and establish the sterile connection with an interior of the container.

