

SPECIFICATION

COMBUSTION APPARATUS

FIELD OF THE INVENTION

The present invention relates to combustion apparatus for use as boilers wherein refuse-derived fuel (hereinafter referred to as "RDF") is used as the fuel or incinerators for burning municipal waste.

BACKGROUND ART

FIG. 4 shows a combustion apparatus conventionally utilized as a boiler wherein RDF is used as its fuel.

With reference to FIG. 4, the combustion apparatus comprises a fluidized-bed furnace 1, a cyclone 2 (dust collector) disposed downstream from the furnace 1 for separating a free-flowing medium and a combustion residue discharged from the furnace 1 from combustion gases and collecting these solids, and a medium-residue return channel 3 provided between the cyclone 2 and the fluidized-bed furnace 1 for returning the free-flowing medium and the combustion residue collected by the cyclone 2 to the furnace 1 therethrough.

The fluidized-bed furnace 1 forms a fluidized bed from sand or like free-flowing medium with primary air

and secondary air sent from an air preheater. A multiplicity of water tubes (not shown) for a boiler are arranged within the furnace 1 to cover the inner peripheral surface thereof. These water tubes communicate at their upper ends with a steam drum 6 via an unillustrated header. RDF is supplied from an unillustrated scale conveyor to a hopper 7 in portions of predetermined quantity and placed into the fluidized-bed furnace 1 from the hopper 7. Noncombustibles and free-flowing medium are drawn off from the lower end of the furnace 1 and separated by a separator 8 disposed below the furnace 1, and the noncombustibles are discharged from the system, while the medium is returned to the furnace 1 by a conveyor 9 and an elevator 10.

15 The medium-residue return channel 3 is bifurcated into two branches at an intermediate portion thereof. One of the branches, 3a, is provided at intermediate portions thereof with a flow control valve 11 and a heat recovery unit 12 which are arranged in this order downstream from the cyclone 2. A superheater 13 for the boiler is disposed in the heat recovery unit 12. Medium transport air is forced into the heat recovery unit 12. The forward end of the other branch 3b is opened to the fluidized-bed furnace 1 at a position above the position

where the hopper 7 is opened to the furnace. The free-flowing medium transported by the conveyor 9 and the elevator 10 is admitted into the branch 3b at an intermediate portion thereof.

5 A heat recovery column 14 is disposed downstream from the cyclone 2. This column 14 has in its interior a first flue 15 for passing combustion gases, discharged from the cyclone 2, from above downward therethrough, and a second flue 16 in communication with the lower end
10 of the first flue 15 for passing the combustion gases from below upward therethrough. The inner peripheral surface of the first flue 15 is covered with a multiplicity of boiler water tubes (not shown), the upper ends of which also communicate with the steam drum
15 6 via an unillustrated header. Arranged within the second flue 16 are a boiler economizer 17 for passing therethrough water forwarded from a deaerator, and two superheaters 18, 19 connected in series with the superheater 13 in the heat recovery unit 12 for passing
20 steam sent from the steam drum 6. A water injector 20 for adjusting the temperature and pressure of the steam by injecting water is disposed between the two superheaters 18, 19 within the second flue 16, also between the lower superheater 19 in the flue 16 and the

superheater 13 in the heat recovery unit 12.

A temperature reduction column 21 and a bag filter 22 are arranged downstream from the heat recovery column 14. The combustion gases passing through the heat recovery column 14 are further reduced in temperature by the heat reduction column 21. The bag filter 22 serves to collect hydrogen chloride, sulfur oxides, soot and dust from the combustion gases. Slaked lime or like neutralizing agent and a reaction assisting agent are added to the combustion gases at a position upstream from the filter. After passing through the bag filter 22, the combustion gases are released into the atmosphere through a stack.

Fly ash is discharged from the lower ends of the heat recovery column 14, temperature reduction column 21 and bag filter 22 and sent to a fly ash treating unit (not shown).

With the combustion apparatus thus constructed, RDF is sent into the fluidized-bed furnace 1 by the hopper 7. In the furnace 1, the free-flowing medium is formed into a fluidized bed with primary air and secondary air, and RDF is burned in the fluidized bed. The unburned combustibles are almost completely burned until the combustion gases and the medium enter the cyclone 2 from

the upper end of the furnace 1. The medium and combustion residue discharged from the furnace 1 are separated from the combustion gases and trapped in the cyclone 2, passed through the two branches 3a, 3b of the return channel 3 and returned to the furnace 1. While passing through the branch 3a having the heat recovery unit 12, the medium and the residue have their heat transferred to steam flowing through the superheater 13, whereby the steam is superheated. The temperature of the furnace 1 can be lowered by adjusting the amount of medium transport air to be forced in and the opening degree of the flow control valve 11 and thereby increasing the quantities of medium and residue to be passed through the branch 3a having the heat recovery unit 12. Conversely, the temperature of the furnace 1 can be raised by reducing the quantities of medium and residue to be passed through the branch 3a having the heat recovery unit 12.

The combustion gases flowing out of the cyclone 2 enter the heat recovery column 14, flow down the first flue 15 first and consequently have their heat transferred to boiler water in the water tubes providing the wall of the flue, whereby the boiler water in the water tubes is heated and evaporated, and the

temperature of the combustion gases is lowered. The combustion gases then flow upward through the second flue 16 and have their heat transferred to the boiler water in the water tubes constituting the wall of the flue, to the steam in the two superheaters 19, 18 and to the water in the economizer 17, whereby the boiler water in the water tubes is heated and evaporated, the steam is superheated, and the water in the economizer 17 is preheated to result in a drop in the temperature of the combustion gases.

The combustion gases subsequently flow into the temperature reduction column 21 and have their temperature further reduced. Slaked lime or like neutralizing agent and a reaction assisting agent are thereafter added to the combustion gases, and the resulting mixture is led into the bag filter 22, in which hydrogen chloride, sulfur oxides, soot and dust are removed. The gases separated off are then released into the atmosphere.

On the other hand, the water sent from the deaerator and preheated during passage through the economizer 17 is admitted into the steam drum 6 and thereafter further heated within the water tubes of the fluidized-bed furnace 1 and the heat recovery column 14 constituting a

boiler water circulation circuit to become a steam-water mixture, which is then sent to the steam drum 6 again.

The steam is separated off in the steam drum 6, passed through the three superheaters 18, 19, 13 in succession
5 and superheated with the heat of the combustion gases during passage through the super heaters 18, 19 and with the heat of the free-flowing medium during passage through the superheater 13. The superheated steam is sent to a steam turbine.

10 However, the conventional combustion apparatus has the problem that almost complete combustion of RDF in the fluidized furnace 1 increases the internal temperature of the furnace 1 to a considerably high level and necessitates supply of secondary air at a high
15 rate to result in the presence of a large amount of oxygen, consequently producing large quantities of NO_x with the nitrogen contained in RDF and the nitrogen afforded by the air. Further since the combustion gases flowing into the cyclone 2 have a considerably high
20 temperature, for example, of at least about 800° C, the apparatus has another problem that the ash resulting from incineration and contained in the gases is partly melted and adheres to the cyclone 2 to entail an impaired medium separation efficiency. Another problem

is also encountered in that the molten ash adheres to the free-flowing medium, causing faulty fluidization in the furnace 1. An attempt to reduce the temperature of the furnace 1 to preclude these problems will entail the
5 problem of giving rise to incomplete combustion to produce increased amounts of unburned combustibles.

An object of the present invention is to overcome the foregoing problems and to provide a combustion apparatus which is diminished in the quantities of NO_x
10 produced, further permitting a cyclone or like dust collector to achieve an improved efficiency in separating off a free-flowing medium and assuring a fluidized-bed furnace of effective fluidization.

DISCLOSURE OF THE INVENTION

15 The present invention provides a combustion apparatus comprising a fluidized-bed furnace, a dust collector disposed downstream from the furnace for separating a free-flowing medium and a combustion residue discharged from the furnace from combustion
20 gases and collecting the medium and the residue, a medium-residue return channel provided between the dust collector and the fluidized-bed furnace for returning the free-flowing medium and the combustion residue collected by the dust collector to the furnace

therethrough, and a secondary combustion furnace disposed downstream from the dust collector for completely burning unburned combustibles in the combustion gases egressing from the dust collector by
5 introducing air into the combustion furnace.

When the apparatus is thus constructed, the portion of combustibles left incompletely burned in the fluidized-bed furnace and contained in the combustion gases from the dust collector can be completely burned
10 in the secondary combustion furnace in the presence of air introduced therein. This makes it possible to give a relatively low internal temperature to the fluidized-bed furnace and to reduce the rate of supply of oxygen, consequently permitting formation of smaller quantities
15 of NO_x than in the conventional apparatus. Since the fuel is not completely burned in the fluidized-bed furnace, the combustion gases flowing into the dust collector have a relatively low temperature, preventing incineration ash from melting in the dust collector and
20 consequently enabling the dust collector to separate the free-flowing medium from the combustion gases with a higher efficiency than in the conventional apparatus. Because molten incineration ash is unlikely to adhere to the medium, faulty fluidization within the fluidized-bed

furnace is avoidable. The unburned combustibles contained in the combustion gases from the dust collector can further be burned completely in the secondary combustion furnace.

5 The combustion apparatus of the present invention may further comprise a heat recovery unit disposed at an intermediate portion of the medium-residue return channel for recovering heat from the free-flowing medium and combustion residue trapped in the dust collector.

10 Heat can then be recovered from the heated medium and combustion residue for effective use.

Preferably, the heat recovery unit is, for example, a superheater for a boiler.

In this case, the free-flowing medium and combustion
15 residue in the fluidized-bed furnace flow into the dust collector along with the combustion gases, and the residue is retained in the collector for a sufficient period of time before it is returned as separated from the gases to the fluidized-bed furnace, whereby the
20 residue is dechlorinated. This precludes high-temperature corrosion of the superheater due to the presence of chlorine.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram showing the overall construction

of a combustion apparatus of the invention for use as a boiler wherein RDF is used as the fuel;

FIG. 2 is a fragmentary diagram in horizontal section showing a modified dust collector as a
5 substitute for a cyclone;

FIG. 3 is a diagram showing the overall construction of a combustion apparatus of the invention for use as an incinerator for burning municipal waste; and

FIG. 4 is a diagram showing the overall construction
10 of a conventional combustion apparatus for use as a boiler wherein RDF is used as the fuel.

BEST MODE OF CARRYING OUT THE INVENTION

The best mode of carrying out the invention will be described below with reference to the drawings.

15 FIG. 1 shows the overall construction of a combustion apparatus of the invention for use as a boiler wherein RDF is used as the fuel. In FIGS. 1 and 4, like parts are designated by like reference numerals and will not be described repeatedly.

20 The fluidized-bed furnace 1 of the combustion apparatus shown in FIG. 1 does not have as large a space as in the apparatus of FIG. 4 but is basically the same as that of FIG. 4 in construction. However, the combustion apparatus comprises a secondary combustion

furnace 31 disposed downstream from the cyclone 2 and upstream from the heat recovery column 14. The secondary combustion furnace 31 is supplied with tertiary air and completely burns the unburned combustibles in the combustion gases delivered from the fluidized-bed furnace 1 via the cyclone 2. With the exception of this feature, the apparatus is the same as the one shown in FIG. 4.

RDF is placed by the hopper 7 into the fluidized-bed furnace 1 of the combustion apparatus thus constructed and burned in the fluidized bed within the furnace 1 as is the case with the apparatus of FIG. 4.

The fuel is burned in the furnace 1 at a smaller rate of supply of secondary air than when it is completely burned therein, i.e., at a lower oxygen concentration, and is not completely burned, so that the temperature of combustion is lower, consequently reducing the quantities of NO_x to be produced, especially NO_x responsible to the nitrogen contained in the RDF.

Combustion gases containing unburned combustibles and the free-flowing medium containing a combustion residue flow into the cyclone 2 from the upper end of the fluidized-bed furnace 1. As in the apparatus of

FIG. 4, the medium and combustion residue are separated off and trapped in the cyclone 2 and returned to the furnace 1 through the two branches 3a, 3b of the medium-residue return channel 3. The steam flowing through the superheater 13 is superheated while the medium and residue pass through the branch 3a.

The period of time from the charging of RDF into the furnace 1 until the medium and combustion residue are separated off in the cyclone 2, and the internal temperature of the furnace 1 and the cyclone 2 are so determined that the chlorine contained in the combustion residue of the RDF is thermally removed. More specifically, the time is 1 to 2 seconds, and the temperature is 650 to 800° C. Accordingly, even if the steam flowing through the superheater 13 in the heat recovery unit 12 of the branch 3a has a high temperature, for example, of not lower than 500° C, the corrosion of the superheater 13 at high temperatures can be precluded. As a result, the steam to be sent to a steam turbine can be set at a temperature of at least 500° C, enabling the steam turbine generating plant to achieve a remarkably improved efficiency.

On the other hand, since incineration ash starts to melt at about 800° C, the condition described above

obviates the likelihood of molten incineration ash adhering to the interior of the cyclone 2, consequently precluding an impairment in the efficiency of separating the medium and combustion residue from the combustion
5 gases. Further because molten incineration ash is unlikely to adhere to the free-flowing medium, faulty fluidization is avoidable.

The combustion gases egressing from the cyclone 2 flow into the secondary combustion furnace 31, into
10 which tertiary air is introduced to completely burn the unburned combustibles in the gases. In this case, the combustion gases have a temperature of about 850 to about 900° C and are retained in the furnace for about 2 seconds. This temperature range is low for the
15 formation of NOx from the nitrogen in air, thus serving to inhibit NOx.

The resulting combustion gases flow out of the secondary combustion furnace 31, pass along the heat transfer surfaces of the boiler as in the apparatus of
20 FIG. 4, have their temperature reduced in the temperature reduction column 21, and then flow into the bag filter 22, in which hydrogen chloride, sulfur oxides, soot and dust are removed. The gases are thereafter released into the atmosphere via a stack.

On the other hand, the superheated steam to be fed to the steam turbine is obtained by the same process as in the apparatus of FIG. 4.

FIG. 2 is a plan view of a modified dust collector 5 which is to be disposed downstream from the fluidized-bed furnace 1 for separating the free-flowing medium and combustion residue discharged from the furnace 1 from the combustion gases and trapping these solids.

With reference to FIG. 2, the dust collector 35 10 comprises a multiplicity of medium collision plates 36 provided inside an unillustrated housing in a staggered arrangement when seen from above. Each plate 36 for the free-flowing medium and combustion residue to collide with is channel-shaped and has an open side 15 facing toward the upstream side with respect to the flow of combustion gases when seen from above. The plate is left open at its upper and lower ends.

In the case of this dust collector 35, the medium and residue striking against the collision plates 36 20 flow down the plates 36 and are discharged from the lower end of the housing.

FIG. 3 shows the overall construction of a combustion apparatus of the invention for use as an incinerator for burning municipal waste. In FIGS. 3 and

1, like parts are designated by like reference numerals and will not be described repeatedly.

In the case of the combustion apparatus of FIG. 3, the heat recovery column included in the apparatus of FIG. 1 is not disposed between the secondary combustion furnace 31 and the temperature reduction column 21. Further the heat recovery unit 12 of the branch 3a of the medium-residue return channel 3 has a steam generator or like heat exchanger 40 for heat recovery in place of the boiler superheater. The apparatus has none of the components needed for the boiler, i.e., no water tubes along the inner periphery of the fluidized-bed furnace 1, and no steam drum. With the exception of these features, the apparatus has the same construction as the one shown in FIG. 1.

With the combustion apparatus thus constructed, municipal waste placed into the fluidized-bed furnace 1 by the hopper 7 is burned, and the free-flowing medium and combustion residue separated from the combustion gases and trapped in the cyclone 2 are returned to the furnace 1, in the same manner as in the apparatus of FIG. 1.

INDUSTRIAL APPLICABILITY

The combustion apparatus of the invention is

suitable for use as a boiler wherein RDF is used as the fuel, or as an incinerator for burning municipal waste.

THIS SHEET HAS BEEN
REPLACED

18

CLAIMS



1. A combustion apparatus comprising a fluidized-bed
furnace, a dust collector disposed downstream from the
furnace for separating a free-flowing medium and a
5 combustion residue discharged from the furnace from
combustion gases and collecting the medium and the
residue, a medium-residue return channel provided
between the dust collector and the fluidized-bed furnace
for returning the free-flowing medium and the combustion
10 residue collected by the dust collector to the furnace
therethrough, and a secondary combustion furnace
disposed downstream from the dust collector for
completely burning unburned combustibles in the
combustion gases egressing from the dust collector by
15 introducing air into the combustion furnace.

2. A combustion apparatus according to claim 1
wherein a heat recovery unit is disposed at an
intermediate portion of the medium-residue return
channel for recovering heat from the free-flowing medium
20 and the combustion residue collected by the dust
collector.

3. A combustion apparatus according to claim 2
wherein the heat recovery unit is a superheater for a
boiler.

This Sheet Has Been Replaced

