



Apparatus and method for operating a flight simulator
with a special impression of reality

5 The invention relates to a method and an apparatus for
operating a flight simulator with a special impression
of reality.

10 DE 10 2008 023 955 B4 describes a method for simulating
events and processes of aircraft, land vehicles or
watercraft and a simulation system. This invention is
based on the object of actuating a simulation device in
real time even though the data which is necessary for
actuation is made available merely by a non-real-time
simulation program, wherein a latency time which is
15 caused by a data manager is to be compensated.

In this context, the time which is actually required by
processes in the real world is understood to be the
real time. The term real time does not mean a specific
speed or processing power of the program or of the
20 controller but instead defines only the time frame
within which the system must react. The term latency
time means a time period between an action and the
occurrence of the expected reaction, that is to say a
delay time. In this patent, protection is essentially
25 given to the fact that if data is not received in good
time the data gap which occurs is replaced by data from
empirical values or data from preceding simulation
programs and this data is then transmitted to the
movement controller of the real time simulation device
30 [0046]. Details on the specific improvement of the
mechanical configuration of a flight simulator are not
available here.

DE 600 20 466 T2 describes what is referred to as a
35 parallel robot with four degrees of freedom which
solves the problem of shifting a movable plate with
four degrees of freedom at high speed and with a high
acceleration and of positioning the moveable plate with



a high degree of rigidity and accuracy. The term parallel robot is used here to refer to a robot in which a multiplicity of actuators are arranged in parallel, wherein such a robot can be applied, for example, in a travel simulator for a motor vehicle. With respect to the prior art, this document specifies parallel robots which have six degrees of freedom and which are used, for example, in flight simulators such as are disclosed in US 5 333 514 and US 5 715 729. In order to solve the problem proposed in DE 600 20 466 T2, a parallel robot is described which is composed essentially of a specific arrangement of a parallel linkage (3), a moving platform (4), coupling parts (42) and kinematic elements (33). A particular application of such a robot in a flight simulator is not mentioned here.

WO 96/26 512 A (translation of the corresponding European patent available as DE 696 23 410 T2) discloses an improved flight simulator which is based on the problem of more precisely simulating the real movement which a pilot senses when maneuvering an aircraft. This is based on a movement simulator having a supporting device (102) and a pitching movement strut (114) with a pitching movement axis, wherein the pitching movement strut (114) is rotatably connected to the support device, and wherein the movement simulator comprises the following:

a rolling movement strut (134) with a rolling movement axis which is perpendicular to the pitching movement axis and is rotatably connected to the pitching movement strut (114), and a participant cabin (160) having a center of gravity, wherein the participant cabin (160) is held by the rolling movement strut in such a way that the center of gravity of the participant cabin is separated from the pitching movement axis.

In order to solve the above problem, in the case of this flight simulator protection was given to the fact that the rolling movement strut (134) is rotatably connected to the pitching movement strut (114) in such a way that the rolling movement strut (134) can rotate completely about the pitching movement strut (114) in a plane perpendicular to the pitching movement axis. Apart from the fact that this feature only contains details which relate to an effect to be achieved, without details on the specific embodiment, the flight simulator described here appears worthy of improvement.

The apparatus according to the invention and the corresponding method are therefore based on the object of presenting an apparatus and a method with which the operation of a simulator can be achieved with a special impression of reality for learning how to control a vehicle, in particular an aircraft, moving in three-dimensional reality. In addition, for the instructor who is accompanying the learning process there is also to be the possibility of being able to monitor objectively the learning progress and the degree of loading of a trainee.

This object is achieved with an apparatus as claimed in claim 1 and a method as claimed in claim 6.

The apparatus according to the invention will be described in more detail below. In particular, in this context, in the drawing:

- Fig. 1 shows a side view of a simulator according to the invention,
- Fig. 2 shows a side view of the projection conditions, and
- Fig. 3 shows a representation of the implemented additional simulation devices and

systems for detecting the human reactions.

5 The underlying idea of the present invention is, on the one hand, to simulate, by means of a special 6-axis robot which can be moved in two dimensions, the conditions in a vehicle cabin, specifically of an aircraft, such as actually occur in reality. On the other hand, the trainee is to be provided with a real
10 simulation of the expected difficulties by means of a realistic representation of the surroundings which are to be expected during operation. The instructor is, in turn, to be supplied all the time with a realistic impression of the physical and psychic loading and/or
15 the load-bearing capability of a trainee by means of data representing the physical state of the trainee.

The side view of a simulator according to the invention shown in fig. 1 makes the main novelties of the
20 inventive concept apparent. A 6-axis robot 1 is, on the one hand, connected here directly via an adaptor plate 3 to a vehicle cockpit 4, to the entry 2 and, on the other hand, securely to a device 6 for translatory lateral movement. The lateral movements which are
25 possible with this device 6 are characterized by means of the customary arrow symbols. The travel movements of a device 5 for translatory longitudinal movement, on which device 5 the device 6 is installed, are illustrated by means of the double arrow shown. This
30 combination of the devices 6 and 5 permits accelerated movements of the aircraft cabin 4 in the longitudinal direction and in the lateral direction simultaneously, independently of the movements of the robot 1. The longitudinal direction is defined here by the longitu-
35 dinal orientation of the aircraft, that is to say of the aircraft cabin 4. Since the simulation of the conditions in an aircraft such as, for example, a passenger plane, is expected to involve the greatest

demands being made of the simulator, this case will be considered in more detail below.

The center of gravity of a passenger plane, or of any other aircraft with aerofoils, is approximately in the region of the center of these aerofoils. The center of gravity is the point at which the entire weight of such an aircraft can be imagined as being combined and about which the entire plane can, as it were, rotate. However, the pilot's seat is generally located at a distance from the center of gravity of the plane, both shifted forward in the direction of flight and moved upward in relation to the center of gravity of the plane. This means that, for example when a plane starts, the pilot not only experiences the normal movement of the center of gravity of his plane but also experiences an additional torque which arises substantially from the distance between the pilot's seat and the center of gravity of the plane.

In the example of fig. 1, this corresponds approximately to the distance between the center of the device 5 for a translatory longitudinal movement and the seat 4 in the aircraft cockpit of the flight simulator. Therefore, in order to simulate a starting process it is possible with the simulator according to the invention to move the vehicle cockpit 4 in the longitudinal direction by means of the device 5 for translatory longitudinal movement. The 6-axis robot 1 carries out the normal combined lifting movement and pivoting movement of a starting vehicle here. For this purposes, the device 5 can be moved with natural acceleration in the translatory mode. As a result of the fact that the device 6 for translatory lateral movement is movably installed on the device 5 for translatory longitudinal movement, combined accelerated movements of the two devices are possible both individually and jointly.

In order to use the device 6 for translatory lateral movement, reference is made to the following example:

If in this case of a normal starting process it is also to be stimulated that during the starting process the aircraft is affected by shearing winds, a hazardous form of side winds, this can be simulated in conditions close to reality by means of the additional use of the device 6 for translatory lateral movement. In this context it is self-evident that such a simulation by means of the devices 5 and 6 for translatory longitudinal movement and respectively for translatory lateral movement can only take place for as long as the travel path of the respective device is configured. However, in practice the travel path of the device 5 for translatory longitudinal movement is made longer than that of the device 6 for translatory lateral movement. This also corresponds to the real requirements here since shearing winds usually occur briefly and in the manner of gusts.

In particular the unexpected occurrence of shearing winds when aircraft start or land easily gives rise to accidents and it is to be simulated by means of the inventive simulator in conditions close to reality.

Fig. 2 outlines in a side view the projection conditions of the simulated external view in the vehicle cockpit 4.

The reference 15 represents here a possible OLED view which can be adapted, as a flexible screen, to the contours of the respective vehicle cockpit 4. OLED stands here for "organic light emitting diode" and denotes a low-viscosity illuminating component made of organic semi-conducting materials which differs from the inorganic light-emitting diodes in that, on the one hand, the power density and the lighting density are lower and, on the other hand, no monocrystalline materials are necessary. The OLED technology is excellently well suited for screens and displays. A further field of use is large-area spatial illumination.

An alternative possible way of representing the simulated external view is that this external view is projected by means of projectors onto projection surfaces which are located outside the vehicle cockpit

5 4.

See in this respect:

http://en.wikipedia.org/wiki/Cave_Automatic_Virtual_Environment.

In the side view shown, the projection surface 9 of the front portion, the projection surface 8 of the right-hand side portion and the projection surface 7 of the ceiling portion can be seen in this case. These projection surfaces can be connected to the vehicle cabin 4 or installed in the simulation space. In the latter case, these projection surfaces must, of course, be correspondingly large in the spatial dimensions. There are suitable projection methods for this purpose which permit a scene to be represented with a depth character on straight, abutting projection surfaces with joint edges which run in a linear fashion, wherein these joint edges which run in a linear fashion can be made invisible for representing a total image with relatively low computational complexity. This making invisible is carried out by means of "calculating out" by computer the relatively precisely defined abutment edges of the projection areas used.

For the use of the flight simulator according to the invention for training helicopter pilots, it is also possible in one particular refinement to provide a further projection surface which maps the ground area. In this case, the aircraft cockpit 4 is equipped with an additional transparent floor panel.

Fig. 3 shows a representation of the implemented additional simulation devices and systems for detecting the human reactions. For this purpose of simulating a fire which has broken out onboard, a central smoke generator 12 is provided with a controllable smoke distribution 11. With this system it is possible for

the operator of the simulation system to produce smoke of a defined type and intensity at certain locations of the aircraft cockpit 4 which are important for practical use. In addition, in a particular form of the
5 embodiment it is possible to subject the entire vehicle cockpit 4, in a defined way which occurs under practical everyday conditions, to shaking movements such as are caused, for example, by propulsion unit damage which is becoming apparent. In order to be able
10 to simulate the occurrence of such damage situations in even more realistic fashion, in this embodiment additional acoustic backgrounds are also provided to the flight trainee by means of a complex loudspeaker system. For reasons of clarity, corresponding devices
15 have not been represented separately. The system 14 for illuminating the cabin can be changed in a directly controlled manner or in a programmed manner with respect to the color and the intensity (flickering light) in accordance with the simulated realities.

20 The reactions of a flight trainee can be detected with the detector device 16 for detecting a movement of persons and/or for detecting the physiognomy and/or recorded for later evaluation of the human reactions (maneuver criticism).

25 The measuring device 10 for measuring the resistance of the skin of a flight trainee serves a comparable purpose. The resistance of the skin can be most easily measured in the region of the control knob or some other control unit. The surface of an emergency switch,
30 which is possibly present, is also suitable for this purpose.

The sensor 17 serves to detect the actually realised movements of the vehicle cockpit 4. The output signals
35 of the sensor 17 serve to record the entire profile of a training unit of the respectively operated simulation program.

The operator control panel used can be quickly adapted to the respectively simulated aircraft type or vehicle type by means of the module system 13 using easy-to-exchange slide-units.

5

It is apparent that the flight simulator according to the invention is also suitable for use in military projects since a considerable experience potential of a fighter pilot is important particularly in this area
10 for the purposes of preparing for hazardous deployment. Such experience potential can be obtained cost-effectively by training with a flight simulator with a special impression of reality without endangering human
lives.

15

The control of the complex movement processes and the signal processing of the sensors used requires a special control program.

List of reference numbers

	1	6-Axis robot
	2	Entry
5	3	Adaptor plate
	4	Vehicle cockpit, aircraft cockpit
	5	Device for translatory longitudinal movement
	6	Device for translatory lateral movement
	7	Projection surface of the ceiling portion
10	8	Projection surface of the right-hand side portion
	9	Projection surface of the front portion
	10	Measuring device for measuring the resistance of the skin
15	11	Smoke distribution
	12	Smoke producer
	13	Module system for changing over the operator control panel
	14	System for illuminating the cabin
20	15	OLED display
	16	Detector device for detecting movement of persons and/or for detecting the physiognomy
	17	Sensor for detecting the cockpit movement

Patent claims

Claim 1:

- 5 An apparatus for operating a simulator with a special impression of reality for learning how to control a vehicle, in particular an aircraft, moving in three-dimensional reality,
- 10 characterized in that said apparatus has the following features:
- 15 a) a vehicle cab (4) modeled on the vehicle to be simulated and having real operator control elements is connected, on the one hand, to a 6-axis industrial robot (1) and, on the other hand, to the ground via a device (6) for translatory lateral movement which is movably mounted at a right angle on a device (5) for translatory
20 longitudinal movement,
 - b) a display modeled on the contours of the vehicle cab (4) serves to transmit a simulated external view on the basis of OLED technology,
 - 25 c) for the purposes of simulating hazardous situations which occur in practice, controllable systems for artificially producing smoke (12), shaking movements, sound generation and light phenomena (14)
30 are provided,
 - d) for detecting human stress reactions, controllable systems for sensing the resistance (10) of the skin and for detecting movements of persons and physiognomy (16) are provided,
 - 35 e) a sensor (17) for detecting the actual movements of the vehicle cab,

f) a system for externally operating and controlling the simulator, which system also registers the reactions of a flight trainer.

5

Claim 2:

The apparatus for operating a simulator as claimed in claim 1,

characterized

10

in that in order to transmit a simulated external view, instead of the OLED technology according to feature b) a display is used which is projected by means of projectors onto projection surfaces which are located outside the aircraft cockpit (4).

15

Claim 3:

The apparatus as claimed in one of the preceding claims,

20

characterized

in that the operator control panel of the aircraft cabin (4) which is used can be quickly adapted to the respectively simulated aircraft type, in an easily exchangeable fashion, by means of the module system (13).

25

Claim 4:

The apparatus as claimed in one of the preceding claims,

30

characterized

in that for the purpose of training, in particular helicopter pilots, a further projection surface which maps the ground area is also provided, and in that the aircraft cockpit 4 is equipped with a transparent floor panel.

35

Claim 5:

The apparatus as claimed in one of the preceding claims,
characterized

in that for the purpose of training in the
military field for simulating hazardous situations which occur in practice, parameters which are relevant in terms of military technology, of an acoustic, optical and mechanical nature, are provided in the training program.

Claim 6:

A method for operating a simulator with a special impression of reality for learning how to control a vehicle, in particular an aircraft, moving in three-dimensional reality,

characterized in that it has the following features:

a) a vehicle cab (4) modeled on the vehicle to be simulated and having real operator control elements can be moved by means of an external operator control unit by means of a 6-axis industrial robot (1) which can be moved in two orthogonal directions on the ground,

b) a simulated external view is conveyed to the flight trainer by means of a display using OLED technology instead of the normally transparent aircraft cockpit,

c) for the purposes of simulating hazardous situations which occur in practice, controllable systems for artificially producing smoke (12), shaking movements, sound generation and light phenomena (14) are provided,

d) for detecting human stress reactions, controllable systems for sensing the

resistance (10) of the skin and detecting movements of persons and the physiognomy (16) are provided, and

- 5 e) the operator control panel used can be quickly adapted to the respectively simulated aircraft type by means of a module system (13).

Claim 7

- 10 The method as claimed in claim 1, characterized in that in order to convey a simulated external view, instead of the OLED technology according to feature b) a display is used
15 which is projected by means of projectors onto projection surfaces which are located outside the aircraft cockpit (4).

Claim 8:

- 20 A computer program having a program code for implementing the method steps as claimed in one of claims 6 and 7 when the program is running in a computer.

25 Claim 9:

A machine-readable carrier having the program code of a computer program for implementing the method as claimed in one of claims 6 and 7 when the program is running in a computer.