(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
5 December 2002 (05.12.2002)

PCT

(10) International Publication Number
WO 02/096999 A1

(51) International Patent Classification[7]: C09G 1/02, C09K 3/14, H01L 21/306, 21/3105

(21) International Application Number: PCT/JP02/05066

(22) International Filing Date: 24 May 2002 (24.05.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2001-157937 25 May 2001 (25.05.2001) JP

(71) Applicant *(for all designated States except US)*: **EKC TECHNOLOGY K.K.** [JP/JP]; R & D Business Park Bldg. D-3, 3-2-1, Sakado, Takatsu-ku, Kawasaki-shi, Kanagawa 213-0012 (JP).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: **NOJO, Haruki** [JP/JP]; 440, Kurami, Samukawa-machi, Kouza-gun, Kanagawa 253-0101 (JP). **YOSHIDA, Akitoshi** [JP/JP]; 991-176, Yahagi-cho, Chuo-ku, Chiba-shi, Chiba 260-0851 (JP). **BERAR, Pascal** [FR/JP]; D705, 3-6-4, Hisamoto, Takatsu-ku, Kawasaki-shi, Kanagawa 213-0011 (JP).

(74) Agents: **KOBAYASHI, Hiroshi** et al.; Fukuoka Bldg. 9th Fl., 8-7, Yaesu 2-chome, Chuo-ku, Tokyo 104-0028 (JP).

(81) Designated States *(national)*: CN, KR, SG, US.

(84) Designated States *(regional)*: European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

**Published:**
— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

WO 02/096999 A1

(54) Title: CERIUM OXIDE SLURRY, AND METHOD OF MANUFACTURING SUBSTRATE

(57) Abstract: A problem to be solved is to provide a slurry that is capable of flattening an uneven film on a substrate with good precision, and that has good stability, not separating into two layers, solidifying through flocculated settling or undergoing changes in viscosity. This problem is solved by adding poly ammonium acrylates having different degrees of neutralization to one another as surfactants to a cerium oxide slurry containing cerium oxide particles, and suitably adjusting the total amount of polyacrylates added.