

A SCALABLE NON-BLOCKING SWITCHING NETWORK FOR PROGRAMMABLE LOGIC

TECHNICAL FIELD

[0001] Embodiments of this invention relate to switching networks and, in particular to switching networks used with programmable logic circuits.

BACKGROUND

[0002] A programmable logic circuit, also referred to as field programmable gate array (FPGA) is an off the shelf integrated logic circuit which can be programmed by the user to perform logic functions. Circuit designers define the desired logic functions and the circuit is programmed to process the signals accordingly. Depending on logic density requirements and production volumes, programmable logic circuits are superior alternatives in terms of cost and time to market. A typical programmable logic circuit is composed of logic cells where each of the logic cells can be programmed to perform logic functions on its input variables. Additionally, interconnect resources are provided throughout the programmable logic circuit which can be programmed to conduct signals from outputs of logic cells to inputs of logic cells according to user specification.

[0003] As technology progresses to allow for larger and more sophisticated programmable logic circuits, both the number of logic cells and the required interconnect resources increases in the circuit. Competing with the increased number of logic cells and interconnect resources is the need to keep the circuit size small. One way to minimize the required circuit size is to minimize the interconnect resources while maintaining a certain level of connectivity. Therefore, it can be seen that as the functionality implemented on the chip increases, the interconnection resources required to connect a large number of signals can be quickly exhausted. The trade-offs are either to provide for a lower

utilization of logic cells in a circuit while keeping the circuit size small or to provide more routing resources that can increase the circuit size dramatically.

[0004] There has been a progression of increasingly complex connection styles over the last forty years in the field of programmable logic circuits. L.M. Spandorfer in 1965 describes possible implementation of a programmable logic circuit using neighborhood interconnection, and connections through multiple conductors using switches in a Clos network. R.G. Shoup in his PhD thesis of 1970 describes both the use of a neighborhood interconnect and the use of a bus for longer distance interconnect.

[0005] Freeman in the U.S. 4,870,302 of 1989 describes a commercial implementation of a FPGA using neighborhood interconnects, short (length one, called single) distance interconnects, and global lines for signals such as clocks. The short distance interconnects interact with the inputs and outputs of logic cells where each input is connected through switches to every short wire neighboring to a logic cell and horizontal and vertical short wires connect through a switch box in a junction. El Gamal et al. in U.S. 4,758,745 introduces segmented routing where inputs and outputs of logic cells interact with routing segments of different lengths in one dimension.

[0006] Peterson et al. in U.S. 5,260,610 and Cliff et al. in U.S. 5,260,611 introduce a local set of conductors interfacing with a set of logic elements where every input of the logic elements is connected, through switches, to every local conductor in the set; additional chip length conductors are introduced both horizontally and vertically where the horizontal conductor can connect to the vertical conductors and the horizontal conductors connect to multiple local conductors. In U.S. 4,870,302, U.S. 4,758,745, U.S. 5,260,610, and U.S. 5,260,611, the input conductor of a logic cell has full connections to the set of local conductors (e.g. for n -inputs and k -local conductors, there is $n \times k$ switches connecting the inputs to the local conductors. A multiplexer (MUX) scheme may also be used so that the number of transistors is reduced.). In U.S. 4,870,302, U.S. 4,758,745, U.S. 5,260,610, and U.S. 5,260,611, the general interconnect

resources are limited to one or two different lengths (i.e. singles of U.S. 4,870,302, local and chip length in U.S. 5,260,610 and U.S. 5,260,611) or limited in one dimension (i.e. different lengths horizontally in U.S. 4,758,745, local vertically in U.S. 5,260,610 and U.S. 5,260,611).

[0007] Camarota et al. in U.S. 5,144,166 and Kean in U.S. 5,469,003 introduce a routing scheme with more than two different lengths in both dimensions with limitations in the reach of those conductors. While U.S. 5,144,166 allows each wire to be selectively driven by more than one possible driving source, U.S. 5,469,003 is limited to be unidirectional in that each wire is hardwired to a MUX output. The connectivity provided in both U.S. 5,144,166 and U.S. 5,469,003 are very low, based on the premises that either connections are neighborhood or relatively local, or logic cells itself can be used as interconnection resources instead of performing logic functions. Ting in U.S. 5,457,410, U.S. 6,507,217, U.S. 6,051,991, U.S. 6,597,196 describe a multiple level architecture where multiple lengths of conductors interconnect through switches in a hierarchy of logic cells.

[0008] Young et al. in U.S. 2001/0007428 and U.S. 5,914,616 describe an architecture with multiple lengths of wires in two dimensions (three in each dimension) where for short local connections, a near cross-bar scheme is used where a set of logic cells outputs are multiplexed to a reduced set of output ports which then interface to other interconnect resources. The longer wires generally fan-in into shorter length wires in a respective dimension. Reddy et al. in U.S. 6,417,694 discloses another architecture where inter-super-region, inter-region, and local conductors are used. A cross-bar scheme is used at the lowest level (using MUXs) for the local wires to have universal access to the inputs of the logic elements. Reddy et al. in U.S. 5,883,526 discloses various schemes having circuit reduction techniques in the local cross-bar.

[0009] At the base level of circuit hierarchy, four-input Look Up Table (LUT) logic cells are commonly used. There are two advantages in using a LUT as the base logic cell. One advantage is that the circuit allows any four-input, one

output Boolean functions with programmable controls. Another advantage is that the four inputs are exchangeable and logically equivalent. Hence it does not matter which signal connecting to which input pin of the LUT for the LUT to function correctly as long as those four signals connect to the four inputs of the LUT.

[0010] A common problem to be solved in any programmable logic circuit is that of interconnectivity, namely, how to connect a first set of conductors carrying signals to multiple sets of conductors to receive those signals where the logic cells originating the signals and the logic cells receiving the signals are spread over a wide area in an integrated circuit (i.e., M outputs of M logic cells where each output connects to inputs of multiple number of logic cells). A highly desirable but in most cases impractical solution is to use a cross bar switch where every conductor of the first set is connectable to every conductor in the multiple sets of conductors directly through a switch. Prior solutions in one degree or another try to divide the connectivity problem into multiple pieces using a divide and conquer strategy where local clusters of logic cells are interconnected and extended to other clusters of logic, either through extensions of local connections or using longer distance connections. These prior interconnect schemes are ad hoc and mostly based on empirical experiences. A desired routing model or interconnect architecture should guarantee full connectability for a large number of inputs and outputs (through programmable interconnect conductors) connecting to multiple sets of conductors over a large part of the circuit all the time.

[0011] Complicated software is necessary to track interconnect resources while algorithms are used to improve interconnectability during the place and route stage implementing a custom design using the programmable logic circuit. Thus, it is desirable to have a new interconnect scheme for programmable logic circuits where the routability or interconnectability may be guaranteed in a more global scale while the cost of interconnections remains low in terms of required switches and the software efforts in determining a place and route for custom design implementation are simplified.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The objectives, features, and advantages of the present invention will be apparent from the following detailed description in which:

[0013] **FIG. 1** illustrates an embodiment of a circuit with four four-input logic cells and two flip flops using a scalable non-blocking switching network (SN).

[0014] **FIG. 2** illustrates one embodiment of a circuit using a stage-0 scalable non-blocking switching network (0-SN) with eleven M conductors accessing four sets of four N conductors.

[0015] **FIG. 3** illustrates one embodiment of a circuit using two stage-0 scalable non-blocking switching networks with each 0-SN having five M conductors accessing four sets of two N conductors.

[0016] **FIG. 4** illustrates one embodiment of a circuit using a stage-1 scalable non-blocking switching network (1-SN) with eleven M conductors accessing four sets of four N conductors through N sets of four intermediate conductors.

[0017] **FIG. 5** illustrates one embodiment of a circuit using a stage-1 scalable non-blocking switching network with twelve M conductors accessing four sets of four N conductors through fewer intermediate conductors.

[0018] **FIG. 6** illustrates one embodiment of a circuit using a stage-1 scalable non-blocking switching network with twelve M conductors accessing four sets of four N conductors with stronger connectivity property.

[0019] **FIG. 7** illustrates one embodiment of a reduced stage-1 scalable non-blocking switching network with fewer switches.

[0020] **FIG. 8** illustrates one embodiment of a larger size stage-1 scalable non-blocking switching network.

[0021] **FIG. 9** illustrates one embodiment of a stage-1 scalable non-blocking switching network with sixteen M conductors.

[0022] **FIG. 10** is a block diagram illustrating one embodiment of a stage-2 scalable non-blocking switching network (2-SN) and a circuit with four logic

circuits of **FIG. 1**, each using the scalable non-blocking switching network of **FIG. 9**.

[0023] **FIG. 11A** illustrates a block diagram embodiment of the stage-2 scalable non-blocking switching network of **FIG. 10**.

[0024] **FIG. 11B** illustrates one embodiment of the first part of the stage-2 scalable non-blocking switching network of **FIG. 11A**.

[0025] **FIG. 12** illustrates one embodiment of a stage-1 scalable non-blocking switching network implementing the second part of the 2-SN of **FIG. 11A**.

DETAILED DESCRIPTION

[0026] An innovative scalable non-blocking switching network (SN) which uses switches and includes intermediate stage(s) of conductors connecting a first plurality of conductors to multiple sets of conductors where each conductor of the first plurality of conductors is capable of connecting to one conductor from each of the multiple sets of conductors through the SN, is first described. The scalable non-blocking switching network can be applied in a wide range of applications, when used, either in a single stage, or used hierarchically in multiple stages, to provide a large switch network used in switching, routers, and programmable logic circuits. A scalable non-blocking switching network is used to connect a first set of conductors, through the SN, to multiple sets of conductors whereby the conductors in each of the multiple sets are equivalent or exchangeable, for example, the conductors of one of the multiple sets are the inputs of a logic cell (which can be the inputs of a LUT or inputs to a hierarchy of logic cells). The scalable non-blocking switching network in this present invention allows any subset of a first set of conductors to connect, through the SN, to conductors of a second multiple sets of conductors, so that each conductor of the subset can connect to one conductor from each set of the multiple sets of conductors.

[0027] In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent to one skilled in the art that embodiments of

the present invention may be practiced without these specific details. In other instances, well-known structures and circuits are shown in block diagram form in order to avoid unnecessarily obscuring the present invention. For purpose of description, unless otherwise specified, the terms program controlled switch and switch are interchangeable in the context of this description: the terms program configured logic cell, logic cell, cell, Look Up Table (LUT), programmable logic cell are interchangeable in the context of this description; the terms conductor, signal, pin, port, line are interchangeable in the context of this description. It should also be noted that the present invention describes embodiments which use program control means to set the states of switches utilized, this control means can be one time, such as fuse/anti-fuse technologies, or re-programmable, such as SRAM (which is volatile), FLASH (which is non-volatile), Ferro-electric (which is non-volatile), etc. Hence the present invention pertains to a variety of processes, including, but not limited to, static random access memory (SRAM), dynamic random access memory (DRAM), fuse/anti-fuse, erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM) such as FLASH, and Ferro-electric processes.

[0028] The concept of scalable non-blocking switching networks utilized in a programmable logic circuit described herein can be generally applied to allow unrestricted connections between a plurality of conductors to multiple sets of conductors, as long as the connection requirements do not exceed the available conductors.

[0029] When a program controlled switch is used to interconnect one conductor to another conductor, a driver circuit may be coupled to the switch to improve the speed of the signal traversing those conductors. Additionally, if multiple conductors (signals) fan-in to a conductor through program controlled switches, it is possible to use a MUX scheme, if desired, to either reduce loading on the conductor or to reduce circuit size, or both, depending on the process technology used. In the case where a MUX is used, the multiple switches are converted into a new switch mechanism where, the number of effective states are

the same as the number of switches, connectivity is enabled by choosing the particular state (corresponding to the switch if multiple switches were used) in connecting two conductors and the states are determined by programmable control.

[0030] Various types of scalable non-blocking switching networks are described including, but not limited to: stage-0 scalable non-blocking switching network (0-SN), stage-1 scalable non-blocking switching network (1-SN), stage-2 scalable non-blocking switching network (2-SN) and extensions to multi-stage scalable non-blocking switching networks and the use of those scalable non-blocking switching networks hierarchically in providing interconnectivity to programmable logic circuits.

[0031] **FIG. 1** shows an embodiment of a cluster (CLST4) circuit **100** including a scalable non-blocking switching network **200** and including k number of four-input logic cells (where $k=4$ in this embodiment) **10**, **20**, **30** and **40** and two Flip-Flops **50** and **60**. Each of the logic cells **10-40** has four inputs **101-104** ($N0[0-3]$) for cell **10**, four inputs **105-108** ($N1[0-3]$) for cell **20**, four inputs **109-112** ($N2[0-3]$) for cell **30** and four inputs **113-116** ($N3[0-3]$) for cell **40**, with four conductors **121-124** as the four outputs for cells **10-40** respectively. Switches **151-156** and **159, 160** are used to control whether a logic cell output drives a Flip-Flop or the logic cell outputs to circuit **100** outputs **125-128** directly. The Flip-Flops **50, 60** output to circuit **100** outputs **125-128** using switches **157, 158, 161** and **162**. Additionally, conductor **131** can drive conductor **101** of cell **10** through switch **141** and conductor **105** of cell **20** through switch **142**. Similarly, conductor **132** can drive cells **30** and **40** through switches **143** and **144**, respectively. Cell **20** can drive a neighboring CLST4 circuit (not shown in **FIG. 1**) through output **122** using switches **145** to conductor **133**. Output **124** of cell **40** drives out to conductor **134** through switch **146** in **FIG. 1**. Three other signals **135-137** are used to control the Flip-Flops as SET, CLOCK, and CLEAR, respectively. Additionally, **FIG. 1** has $(X+1)$ conductors **180** ($M[0-X]$) fanning in

to drive the sixteen inputs **101-116** using a switch network **MTX 200**. The conductors $M[0-X]$ **180** are called M conductors where M is equal to the number of conductors $(X+1)$ in the embodiment of **FIG. 1**. The input conductors $N_i[0-3]$ for $i=[0-(k-1)]$ **101-116** are called the N_i conductors where N_i is equal to the number of inputs which is four in the embodiment of **FIG. 1**. For purpose of illustration, the size $N_i = N = 4$ is shown in **FIG. 1**. Alternatively, each N_i can have a different size without changing the connectivity property described herein.

[0032] **FIG. 2** shows an embodiment where **MTX 200** of **FIG. 1** is represented by a stage-0 scalable non-blocking switching network (0-SN) **300**; each N conductor **101-116** is connectable to $(M-N+1)$ conductors of the M conductors (e.g., conductors **180** of **FIG. 1**) **201-211** ($M[0-10]$), the number of switches shown in **FIG. 2** for each input conductor of conductors **101-116** is thus $(M-N+1) = 8$ for the 0-SN **300** of **FIG. 2**. The switch network 0-SN **300** allows any subset of M conductors **201-211** to drive one input conductor of each of the logic cells **10-40** using the switches of **300** without any blocking as long as the number of connections do not exceed the available interconnect resources (i.e., the number of M conductors driving the inputs of any of the logic cells can not exceed the number of inputs of the logic cell). The scheme of **FIG. 2** is an improvement over a cross bar connection where instead of a full switch matrix comprising $M \times (k \times N) = 11 \times (4 \times 4) = 176$ switches, the number of switches is $(M-N+1) \times (k \times N) = 128$. The 0-SN **300** in **FIG. 2** allows the above stated connectivity by assuming the four inputs for each of the logic cells as exchangeable or logically equivalent (i.e., conductors **101-104** of cell **10** of **FIG. 1** are equivalent or exchangeable) so it is only necessary to connect a particular M conductor (i.e. $M[4]$ conductor **205**) to any input pin of a given logic cell (i.e., conductor **101** out of conductors **101-104** of cell **10** of **FIG. 1** using switch **222**) if the connection requirement is to connect the particular M conductor to the given logic cell.

[0033] Depending on technology used in the programmable circuits, some area minimization can be accomplished. For example, using a SRAM memory cell with six transistors as the program control for each switch implemented using a passgate, the eight switches 221-228 of FIG. 2 per input line 101 will require fifty six transistors. Instead, an eight input MUX using three memory bits can be used to control eight states to effectively replace the eight SRAM bits and eight switches. In the MUX scheme, three bits, fourteen passgates and perhaps one inverter (to regenerate the signal) uses thirty four transistors which is a large reduction from the fifty six transistors used with eight SRAM memory cells as the program control for each switch. The loading on conductor 101 will be reduced using the MUX implementation while there are additional delays due to the eight to one MUX.

[0034] FIG. 3 shows an embodiment where MTX 200 of FIG. 1 is represented by using two stage-0 scalable non-blocking switching networks 330 and 320 with $M = M_a + M_b = 10$ conductors 301-310 composed of subgroups $M_a = [A0-A4] = 5$ 301-305 conductors and $M_b = [B0-B4] = 5$ 306-310 conductors. Each $N_a = 2$ for the upper two input conductors of each of the four logic cells (composed of conductors 101-102 for cell 10, conductors 105-106 for cell 20, conductors 109-110 for cell 30 and conductors 113-114 for cell 40) and $N_b = 2$ for the lower two input conductors for each of the $k = \text{four}$ logic cells (composed of conductors 103-104 for cell 10, conductors 107-108 for cell 20, conductors 111-112 for cell 30 and conductors 115-116 for cell 40). A full sized stage-0 scalable non-blocking switching network of FIG. 3 would have $(M - N + 1) = 10 - 4 + 1 = 7$ program controlled switches per input conductor. Instead, in the embodiment of FIG. 3, the number of input switches is only four because of the separate M_a conductors and M_b conductors (with $M_a = M_b = 5$) and the number N is broken into two parts (with $N_a = N_b = 2$). As such, the number of program controlled switches per input conductor in network 330 is $M_a - N_a + 1 = 5 - 2 + 1 = 4$ and the use of program controlled switches per input conductor in network 320 is $M_b - N_b + 1 = 5 - 2 + 1 = 4$. While it

is true that the Ma 301-305 conductors connecting to the upper two inputs of the four logic cells using network 330 maintain the connectivity illustrated in FIG. 2 (and similar for Mb conductors 306-310 to the lower two inputs of the four logic cells using network 320), it is not true that any arbitrary use of [A0-A4], [B0-B4] to fan-in to the four logic cells is so. This constraint prevents arbitrary assignments of M conductors connecting to the N conductors through the two 0-SNs 320 and 330 of FIG. 3. However, the stage-0 scalable non-blocking switching networks 320 and 330 together can be an economic implementation to provide good connectivity for a programmable logic circuit while the software efforts in book-keeping and tracking the allowable M conductors usage are more complex than the scheme of FIG. 2. FIG. 3 allows at least eight M conductors out of ten to be arbitrarily connected to the inputs of the four logic cells, where each one conductor connecting to one input to each of the four logic cells using networks 320 and 330; the constraint here is that the ten conductors can not be arbitrarily assigned as in the FIG. 2 case.

[0035] In embodiments of the present invention, a first group of conductors is connected to multiple groups of equivalent conductors using a switch network. Thus far a 0-SN has been presented, where there are $(M-N+1) \times N \times k$ switches to provide unrestricted connections between a first set of M conductors to multiple k sets of N conductors where any subset of M conductors can connect to one conductor to each of the k sets of N conductors using the 0-SN without any blockage.

[0036] FIG. 4 illustrates an alternative embodiment scheme where the number of switches used in the switch network can be greatly reduced without changing the connectivity property of the 0-SN. FIG. 4 shows an embodiment where MTX 200 of FIG. 1 is represented by using a stage-1 scalable non-blocking switching network (1-SN). The 1-SN 400 connects a M conductor of conductors 401-411 to a N conductor of conductors 101-116 using two switches of the 1-SN 400 plus one intermediate conductor. Instead of directly connecting

the M conductors 201-211 to the k sets of N conductors 101-116 through the network 300 of FIG. 2 where 128 switches are used, the 1-SN 400 in FIG. 4 connects a M conductor 407 (M[6]) to a N conductor 109 by first connecting to an intermediate I conductor 454 through switch 437 and then to the N conductor 109 through switch 441 of sub-network 450. Similarly, the same M conductor 407 can connect to N conductors 101, 105, and 113 through the same intermediate conductor 454 through switches 442, 443 and 444, respectively. The 1-SN 400 of FIG. 4 has ninety six switches which is a 25% reduction in the number of switches compared with the 0-SN 300 of FIG. 2. It is possible to reduce the number of switches required in a 0-SN by creating a scalable non-blocking switching network with intermediate stage(s) of interconnect where each of the M conductors can connect, arbitrarily, to a conductor from each of k sets of N conductors. The scalable non-blocking switching network is capable of connecting a M conductor to more than one conductor from each of k sets of N conductors; however, logically it is not necessary to connect to more than one conductor in each of the N conductors.

[0037] FIG. 4 illustrates a 1-SN 400 with N sets of intermediate conductors I_i for $i=[1-N]$, where there are eleven M conductors 401-411, four sets of N conductors, 101-104, 105-108, 109-112 and 113-116, and k is four. The first intermediate conductors I_1 , for example, are the four conductors 451-454 that associate with the first input for each of the N conductors, thus conductors 101, 105, 109 and 113. Similarly, conductors 461-464 are the I_4 conductors associated with conductors 104, 108, 112, and 116. The $(M-N+1)$ switches for each conductor of the N conductors in a 0-SN are distributed amongst the corresponding I_i conductors in FIG. 4. For example, the eight switches 431-438 coupling the M conductors 401-408 are distributed to the I_1 conductors 451-454 where each of the I_1 conductors couples to $[(M-N+1)/I_1]$ switches, which is two. In the example of FIG. 4, the number of intermediate conductors in each of the I_i

conductors is four. Generally, different I_i need not be a uniform number (as described below). The 1-SN 400 of FIG. 4 has $[(M-N+1) \times N + \sum_{i=1-N} (I_i \times k)] = 32+64 = 96$ switches where I_i is the number of intermediate conductors in each of N sets of I_i intermediate conductors. The 1-SN 400 of FIG. 4 allows the same connectivity property as the respective 0-SN 300 of FIG. 2, connecting any conductor of the M conductors to one conductor of each k sets of N conductors through two switches and one intermediate conductor in 1-SN 400.

[0038] In the 1-SN 400 of FIG. 4, any N -tuple of M conductors have the appropriate choice of switches to different N sets of I_i conductors. For example, conductors 401, 404, 405, and 410 are the four-tuple ($N=4$) of M conductors where conductor 401 connects to conductor 451 (of the I_1 conductors) through switch 431; conductor 404 connects to conductor 466 (of the I_2 conductors) through switch 446; conductor 405 connects to conductor 467 (of the I_3 conductors) through switch 447; and conductor 410 connects to conductor 464 (of the I_4 conductors) through switch 427. Any subset of the N -tuple of M conductors has the same property connecting to the intermediate conductors. Additionally, each intermediate conductor of I_i conductors is connectable to one N conductor in each of the k sets of N conductors. For example, any conductor of conductors 451-454 is connectable, through the switches in sub-network 450, to conductors 101, 105, 109 and 113. Similarly, any conductor of conductors 461-464 is connectable to conductors 104, 108, 112 and 116 through switches in sub-network 420.

[0039] FIG. 5 illustrates an alternative embodiment of a 1-SN representing the MTX 200 of FIG. 1. In 1-SN 500 there are twelve M conductors 501-512, four sets of N conductors 101-116, and N sets of intermediate I_1 conductors 521-523, I_2 conductors 524-526, I_3 conductors 527-529, and I_4 conductors 530-532 where $M = I_1+I_2+I_3+I_4$ or $I_i = M/N = 3$. The number of switches in FIG. 5 is

$[(M-N+1) \times N + \sum_{i=1}^N (I_i \times k)] = 36+48 = 84$. A corresponding 0-SN would have one hundred and forty four switches and a cross bar would have one hundred and ninety two switches. The connectivity property of the 1-SN 500 of FIG. 5 is the same as those discussed earlier with respect to 1-SN 400 of FIG. 4 with fewer intermediate conductors and switches. The illustrations in FIG. 4 and FIG. 5 have the first set of intermediate I_1 conductors (conductors 451-454 of FIG. 4 and conductors 521-523 of FIG. 5) connecting to conductors 101, 105, 109, 113, which are the first input of each of the four logic cells 10-40 of FIG. 1, through switches of sub-network 450 of FIG. 4 and switches of sub-network of 540 of FIG. 5, respectively. An equally effective alternative is to connect each set of I_i conductors to any one conductor (instead of the i^{th} one) from each of the four logic cells as long as each of the four inputs of a particular logic cell in this example are covered by a different set of I_i conductors.

[0040] FIG. 6 illustrates an embodiment of a different version of a stage-1 scalable non-blocking switching network having a stronger connectivity property than the 1-SN 500 of FIG. 5. While requiring more switches, the twelve M conductors, 601-612 ($M[0]$ - $M[11]$) of 1-SN 600 are connectable to all the conductors in each of the N sets of I_i intermediate conductors 621-623, 624-626, 627-629, 630-632. This is in contrast to the coupling to $(M-N+1)$ conductors of the M conductors in FIG. 4 and FIG. 5. In 1-SN 600, conductors 601-612 are connectable to I_1 conductors 621-623 through the switches in sub-network 620. Conductors 601-612 are connectable to I_2 conductors 624-626 through the switches in sub-network 640. Conductors 601-612 are connectable to I_3 conductors 627-629 through the switches in sub-network 650. Conductors 601-612 are connectable to I_4 conductors 630-632 through the switches in sub-network 660. The twelve M conductors 601-612 in FIG. 6 have a stronger connectivity property compared to the 1-SN 500 of FIG. 5 where one conductor

of M/I_i conductors can be program selected to connect to a specific N conductors of any of the k sets. As an example, in the embodiment of **FIG. 6**, any of N -tuples conductors **601-604**, **605-608**, **609-612** (of M conductors) can connect to any specific input conductor of any of the four ($k=4$) sets of N conductors using the 1-SN, but the conductors within each four-tuples are mutually exclusive to the specific input conductor. The number of switches required in this 1-SN **600** of **FIG. 6** is $[M \times N + \sum_{i=[1-N]} (I_i \times k)] = 48+48 = 96$ switches.

[0041] The difference between a 0-SN and a 1-SN in terms of switches required is the difference between $[(M-N+1) \times N \times k]$ and $[(M-N+1) \times N + \sum_{i=[1-N]} (I_i \times k)]$ in the case of **Fig. 5** where $(M-N+1)$ of the M conductors are connectable through the 1-SN to the I_i conductors in each of the N sets of I_i conductors. The difference between a 0-SN and a 1-SN in terms of switches required is the difference between $[M \times N \times k]$ and $[M \times N + \sum_{i=[1-N]} (I_i \times k)]$ in the case of **FIG. 6**. If we simplify each $I_i = k$, then M is at least $[k+N+1/(k-1)]$ for the case of **FIG. 5** and M is at least $[k+1+1/(k-1)]$, it is worthwhile to note that the scheme of **FIG. 5** still works for M to be less than the number(s) above. Additionally, in order for the scheme of a 1-SN to work, the number of switches per intermediate conductor $[(M-N+1)/I_i]$ may not be greater than N without loosing the non-blocking characteristics of the SN. The number, $[(M-N+1)/I_i]$, may not be an integer, in the case, an integer number P_i is used by rounding the number $(M-N+1)/I_i$ up or down while the sum $\sum_{i=[1-N]} P_i = (M-N+1)$. Similarly, for the case of **FIG. 6**, M is used instead of $(M-N+1)$ so P_i would be the integer rounding up or down (M/I_i) , while the sum $\sum_{i=[1-N]} P_i = M$. Furthermore, in the examples of **FIG. 4** and **FIG. 5**, the number of intermediate conductors $\sum_{i=[1-N]} I_i$ is bounded to be at least M and if $k \times N$ is greater than M , the sum $\sum_{i=[1-N]} I_i$ can either be M or $k \times N$ or some number in between; while each individual I_i is bounded by M/N , k or some number in between and since M/N may not be

integer divisible, I_i is an integer by rounding up or down M/N , hence we can see that individual I_i may not be uniform among all i for $i=[1-N]$.

[0042] **FIG. 7** illustrates an embodiment where the number of switches in the embodiment of **FIG. 6** is reduced without much change to the connectivity property of the 1-SN. **FIG. 7** represents the reduction where conductor 601 is shorted to conductor 621, conductor 602 is shorted to conductor 624, conductor 603 is shorted to conductor 627, and conductor 604 is shorted to conductor 630 in **FIG. 6**; where the sixteen switches in sub-network 670 of **FIG. 6** are deleted and the number of switches is eighty in **FIG. 7** instead of ninety six in **FIG. 6**. The 1-SN 700 minus sub-networks 710, 720, 730 and 740 in **FIG. 7** with M conductors 605-612, has the same stronger connectivity property of the 1-SN 600 described in **FIG. 6** and is a 1-SN with $M=8$. It is possible to further reduce the number of switches, for example, by shorting more M conductors to the intermediate conductors, but the connectivity property would be much reduced and the software efforts in determining a connection pattern would become increasingly more complex.

[0043] **FIG. 8** illustrates an embodiment of a 1-SN with $M=48$, $k=4$, $N=16$ and $I_i=3$ for $i=[1-16]$. Because there are 720 switches in 1-SN 800, a 0-SN would require 2112 switches and a cross bar would require 3072 switches. Each of the $N(=16)$ sets of I_i intermediate conductors, for example, I_{16} , has three conductors (inside sub-network 810) where the I_{16} conductors couple to $(M-N+1) = 33$ M conductors in **FIG. 8**, each of the intermediate conductors couples to eleven M conductors through the eleven switches in sub-network 811. By introducing an intermediate conductor and an extra switch in the connection path, the 1-SN 800 provides a large reduction in number of switches required compared to that of a 0-SN.

[0044] In the various embodiments examples have been used where M is less than $k \times N$ and M conductors are the conductors carrying fan-in signals while the

k sets of N conductors are the conductors to receive those fan-in signals. This need not be the case. We can simply have a SN where M is larger than $k \times N$. Alternatively, we can consider, for example, the conductors 101-104, 105-108, 109-112 and 113-116 in FIG. 6 as sixteen outputs from four clusters of logic cells and using the 1-SN for the purpose of output reduction from sixteen to twelve where any subset of twelve outputs out of sixteen outputs can be selected using the 1-SN. Additionally, the conductors 101-104, 105-108, 109-112 and 113-116 in the various figures need not be either inputs or outputs of logic cells but may be a plurality of equivalent conductors where connection to any of the conductor in one plurality of equivalent conductors is sufficient as opposed to connection to a particular conductor in the plurality of equivalent conductors.

[0045] In designing interconnection architecture for programmable logic circuits, it may be important to provide reasonable connectivity and adequate interconnection resources based on engineering trade-offs such a circuit size, speed and ease of software to place and route a customer specified design. There is a ratio R between the M conductors and the k sets of N conductors where $R = M/(k \times N)$; if R is too small, the connectivity is more limited than a larger R. The circuit in FIG. 6, for example, has $R = 0.75$. We shall call R the expansion exponent in building up the hierarchy of circuits using scalable non-blocking switching networks. A commonly used expansion exponent, for the design of a programmable logic circuits using the scalable non-blocking switching networks, is in the range between 0.5 and 1.0 and the choice is dependent on factors such as engineering design trade-offs (i.e., logic utilization, circuit area minimization, ease of software place and route, etc.), technology used (i.e., SRAM, anti-fuse, etc.), etc. It is sometimes advantageous to exceed the range in parts of the circuits, for example, in an output reduction where a large number of outputs are reduced to a lesser number using a SN.

[0046] The previous discussion dealt with using 0-SN and 1-SN which can be used to build up a circuit hierarchy for the interconnect of programmable logic cells whereby each level of hierarchy contains several programmable logic

circuits with associated 0-SN and/or 1-SN to connect to various conductors throughout the circuits using the various scalable non-blocking switching networks. The previously described schemes allow connection to an arbitrary signal at any level of circuit hierarchy to reach an input of any of the logic cells within the hierarchy using the 0-SNs and the 1-SNs as long as interconnect resources and logic capacities remain available.

[0047] Below is described a scheme in building up a programmable logic circuit using stage-1 and stage-2 scalable non-blocking switching networks hierarchically. **FIG. 9** illustrates an embodiment of the MTX circuit **200** in the CLST4 circuit **100** in **FIG. 1** using a stage-1 scalable non-blocking switching network with sixteen M conductors **901-916**, four sets of N conductors **101-104**, **105-108**, **109-112**, **113-116** where $N=4$, and N sets of I_i conductors **931-934**, **935-938**, **939-942**, **943-946**, for $i=[1-N]$ where each $I_i = M/N = 4$; the expansion exponent R is 1.0 in the embodiment of **FIG. 9**.

[0048] By construction in building a programmable circuit, for example, using a 1-SN **900** of **FIG. 9**, any subset of the M conductors **901-916** can be individually connected through the 1-SN **900** to one conductor in each of the k sets of N conductors. Those M conductors themselves then become logically equivalent. For any signal originating somewhere outside the CLST4 circuit **100** of **FIG. 1** to connect up to four inputs from each of the four logic cells **10-40** (one from conductors **101-104**, one from conductors **105-108**, one from conductors **109-112**, and one from conductors **113-116**) of **FIG. 1**; it is only necessary to connect to one of the M conductors. Thus, those M conductors **901-916** can be treated hierarchically as the N conductors (where $N=16$) where multiple new k sets of those new N conductors each having a circuit including four logic cells and two Flip Flops together with the 1-SN are to be selectively connected through a new switch network such as a SN by a new set of M conductors. This process can be repeated till a desired circuit size is reached while the desired circuit allows unrestricted connectivity as discussed above.

[0049] FIG. 10 illustrates a block diagram embodiment of a next level of circuit hierarchy CLST16 1000 using four sets of CLST4 100 of FIG. 1 (CLST4 1010, CLST4 1020, CLST4 1030, CLST4 1040 of FIG. 10) where circuit MTX 200 is implemented using the 1-SN 900 of FIG. 9 and a stage-2 scalable non-blocking switching network of circuit MTX16 1050 with sixty four M conductors having forty eight conductors 1055 (M[0-47]) and sixteen conductors 1056 (OW[0-7], OE[0-7]) and four sets of N conductors 1060, 1070, 1080, 1090 where each of the N conductors has sixteen conductors which correspond to the sixteen M conductors 901-916 of FIG. 9. In FIG. 10, sixteen conductors 1056 of the sixty four M conductors 1055 and 1056 directly connect to the four outputs 1065, 1075, 1085, 1095 of the four CLST4 100 circuits 1010, 1020, 1030, 1040. The sixteen conductors 1056 (OW[0-7], OE[0-7]) having four sets of four conductors and each of the four conductors corresponds to the four outputs 125-128 (O[0-3]) of the CLST4 100 circuit of FIG. 1. The expansion exponent R is again 1.0 in this circuit 1000.

[0050] The use of scalable non-blocking switching networks in this next level of circuit hierarchy, connecting large number of conductors to multiple sets of conductors, is illustrated in FIG. 11A. FIG. 11A illustrates an embodiment, in block diagram form, of circuit MTX16 1050 of FIG. 10 where the sixty four M conductors 1101 (M[0-47], OW[0-7], OE[0-7]) correspond to conductors 1055 and 1056 of FIG. 10. The first stage of intermediate conductors is composed of N_0 (where $N_0=4$) sets of sixteen I_{0i} conductors (where $I_{0i} = M/N_0 = 16$ for $i = [1-N_0]$) 1150, 1160, 1170, and 1180. The M conductors 1101 interface to the first four sets of intermediate stage I_{0i} conductors 1150, 1160, 1170, 1180 using the switches of sub-networks 1110, 1120, 1130 and 1140. FIG. 11B illustrates a scheme where conductors 1101 connects to conductors 1160 through sub-network 1120. The connection scheme where conductors 1101 connect to conductors 1150 through sub-network 1110, and to conductors 1170 through sub-network 1130, and to conductors 1180 through sub-network 1140 are the same as sub-

network 1120 of FIG. 11B. The number of switches used between the M conductors 1101 to the four sets of first stage intermediate conductors 1150, 1160, 1170, 1180 in this embodiment is $M \times N_0 = 256$. As described in relation to FIG. 5, an alternative implementation is to have $(M - N_0 + 1) \times N_0$ switches instead.

[0051] FIG. 12 illustrates an embodiment of circuit TA1 1165 where conductors 1160 is the second N_0 set of I_{0i} conductors, where $i=2$ and $I_{0i} = 16$; intermediate conductors 1201-1216 (which correspond to conductors 1160 of FIG. 11A) interface to sixteen conductors 1241-1256 (which correspond to conductors 1161-1164 of FIG. 11A). Sub-networks 1155, 1175, 1185 of FIG. 11A are the same circuit as sub-network 1165 to interconnect conductors 1150, 1170, 1180 to conductors 1151-1154, 1171-1174, 1181-1184 of FIG. 11A, respectively.

[0052] In FIG. 12, the circuit TA1 is a 1-SN 1165 of FIG. 11A where M conductors 1201-1216 are the sixteen intermediate I_{02} conductors 1160 ($I_{1_1}[0-15]$) of FIG. 11A; sixteen intermediate conductors 1221-1236 are composed of $N_1 (=4)$ sets of I_{12j} ($I_{12j} = M/N_1 = 4$) conductors for $i=2, j = [1-N_1]$: conductors 1221-1224, 1225-1228, 1229-1232, 1233-1236. The I_{12j} conductors connects to the four sets of destination conductors 1241-1244, 1245-1248, 1249-1252, 1253-1256 for $j = [1-N_1]$, respectively. The 1-SN 1165 of FIG. 12 uses the same 1-SN 900 of FIG. 9. However, the 1-SN 1165 is one of four (sub-networks 1155, 1165, 1175, 1185) in a second part of a stage-2 scalable non-blocking switching network (2-SN) 1050 of FIG. 11A where the conductors 1151-1154, 1161-1164, 1171-1174, 1181-1184 of the 2-SN are the M conductors 1060, 1070, 1080, 1090 of the CLST4 circuits 1010, 1020, 1030, 1040, respectively of FIG. 10. Each of the CLST4 circuits 1010, 1020, 1030, 1040 corresponds to the CLST4 circuit 100 of FIG. 1 along with the 1-SN 900 of FIG. 9.

[0053] The TA1 circuit 1165 of FIG. 12 connects conductors 1201-1216 selectively to conductors 1241-1256; 1241, 1245, 1249, 1253 that are conductors

1161 (N0[4-7]) of FIG. 11A which correspond to four of the sixteen M conductors 1060 (C0[4-7] of C0[0-15]) of CLST4 1010 of FIG. 10. Similarly, conductors 1242, 1246, 1250, 1254 are conductors 1162 (N1[4-7]) of FIG. 11A which correspond to four of the sixteen M conductors 1080 (C1[4-7] of C1[0-15]) of CLST4 1030 of FIG. 10. Conductors 1243, 1247, 1251, 1255 are conductors 1163 (N2[4-7]) of FIG. 11A which correspond to four of the sixteen M conductors 1070 (C2[4-7] of C2[0-15]) of CLST4 1020 of FIG. 10. Conductors 1244, 1248, 1252, 1256 are conductors 1164 (N3[4-7]) of FIG. 11A which correspond to four of the sixteen M conductors 1090 (C3[4-7] of C3[0-15]) of CLST4 1040 of FIG. 10.

[0054] In a 1-SN implementation of the MTX 1050 circuit of FIG. 11A, $M=64$, $k=4$, and $N=16$, and in the 2-SN implementation, the number of sets of each stage of intermediate conductors $N0=4$ and $N1=4$ where the product $N0 \times N1$ is equal to N . The number of switches in the 2-SN 1050 of FIG. 10 using a stronger connectivity SN discussed in FIG. 6 and FIG. 9 is $M \times N0 + \sum_{i=[1-N0]} [(I0_i \times N1) + \sum_{j=[1-N1]} (I1_{ij} \times (I0_i / N1))]$ where $I0_i = M/N0$ for $i=[1-N0]$, and $I1_{ij} = I0_i / N1$ for $i=[1-N0]$, $j=[1-N1]$ in network 1050 so $I0_i = 16$, $I1_{ij} = 4$ and the 2-SN of 1050 has 768 switches. A 1-SN implementation would require 1280 switches, and a full cross bar switch would require 4096 switches. In the case where each $I0_i$ conductors interface to $(M-N0+1)$ instead of M of the M conductors, and for each $I1_{ij}$ conductors interface to $(I0_i - N1 + 1)$ instead of $I0_i$ of the $I0_i$ conductors, the number of switches would be $(M-N0+1) \times N0 + \sum_{i=[1-N0]} [(I0_i - N1 + 1) \times N1 + \sum_{j=[1-N1]} (I1_{ij} \times (I0_i / N1))]$. In the FIG. 10 case, we have $N=N0 \times N1$, $I0_i = M/N0$, $I1_{ij} = M/N = k$, thus the number of switches in this case for the 2-SN is $[M \times (N0 + N1 + k)]$.

[0055] As discussed earlier, each of the N conductors of the k sets of N conductors in the different SNs does not need to be of uniform size. A SN can be constructed with different sized N_i 's where the maximum sized N_i is used as the

uniform sized new N and virtual conductors and switches can be added to the smaller sized N_i making the N_i appear to be of size N . Since the interconnection specification will not require the smaller sized N_i to have more connections than N_i , there is no change in the connectivity property of the SN. As an example, in **FIG. 1** instead of four sets of N conductors 101-104, 105-108, 109-112, 113-116 as inputs for logic cells 10-40, respectively, logic cell 10 of **FIG. 1** has only three inputs 101-103. In SN of **FIG. 6** with M conductors 601-612, switches in **FIG. 6** and intermediate conductors 621-632 stay the same, with the exception that the three switches in sub-network 680 and conductor 104 are “virtual” and can be taken out of the SN in **FIG. 6**.

[0056] Multiple stages of scalable non-blocking switching networks can be built using the schemes described above, for example, the MTX 1050 of **FIG. 10** can be implemented as a stage-3 scalable non-blocking switching network using $N_0=2$, $N_1=2$ and $N_2=4$ with first intermediate I_{0i} conductors $I_{0i} = M/N_0$, $I_{1ij} = I_{0i}/N_1$ and $I_{2ijk} = I_{1ij}/N_2$ for $i = [1-N_0]$, $j = [1-N_1]$ and $k = [1-N_2]$, where $N_0 \times N_1 \times N_2 = N = 16$ which is the number of inputs for each of the four CLST4 circuits 1010, 1020, 1030, 1040 of **FIG. 10**. Similarly, SN 1050 can be implemented as a stage-4 SN where $N_0=2$, $N_1=2$, $N_2=2$ and $N_3=2$ with four intermediate stages of conductors connecting the M conductors to the N conductors. The 2-SN implementation over the 1-SN implementation in SN 1050 of **FIG. 10** has a reduction in the number of switches by the difference between $N \times M = 16M$ and $(N_0+N_1) \times M = (4+4) \times M = 8M$; the 3-SN and 4-SN where $(N_0+N_1+N_2) = (2+2+4) = 8$ and $(N_0+N_1+N_2+N_3) = (2+2+2+2) = 8$, respectively, has no improvement over the 2-SN where $(N_0+N_1) = (4+4) = 8$. As such, it may make sense only when the sum of N_i , the number of sets of the intermediate conductors for each stage, add up to be less than the previous stage multi-stage SN. Thus, it can be seen that for $N=64$, a 3-SN using $N_0=N_1=N_2=4$ where $(N_0+N_1+N_2) = 12$ would be very effective in switch reduction over a 2-SN

using $N_0=N_1=8$ with $(N_0+N_1) = 16$ and similarly for the 2-SN over 1-SN where $N=64$.

[0057] Thus we have described two levels of circuit hierarchy using scalable non-blocking switching networks where sixty four M conductors fan in to connect, through a 2-SN and then a 1-SN, to sixteen four-input logic cells. Sixteen of the sixty four M conductors are directly connected to the sixteen outputs of each of the four CLST4 (125-128 of 100 in FIG. 1) circuits, providing unrestricted connections from any output to all sixteen logic cells. The first level of circuit hierarchy includes the circuit CLST4 100 of FIG. 1 with MTX 200 implemented as the 1-SN 900 of FIG. 9 where CLST4 100 has four four-input logic cells 10-40 and two flip-flops 50, 60 as shown in FIG. 1. The next higher second level of circuit hierarchy is the CLST16 1000 circuits of FIG. 10 having four CLST4 100 circuits with a 2-SN MTX16 1050 as shown in FIG. 10, where the network 1050 implementation is illustrated in FIG. 11A, FIG. 11B and FIG. 12. In CLST16 1000, each of sixteen outputs 1065, 1075, 1085, 1095 (connecting directly to conductors 1056) has unrestricted connectivity to every logic cell in the CLST16 1000 circuit and the other 48 M conductors 1055 of FIG. 10 can be treated as the N conductors of the CLST16 1000 in building up the next level of circuit hierarchy. The sixteen outputs 125-128 of CLST4 100 in FIG. 1 for each of the four CLST4 circuits 1010, 1020, 1030, 1040 of FIG. 10 are directly wired to sixteen M conductors 1056, whose outputs can further connect, through a SN, to the next third level of circuit hierarchy using CLST16 1000 circuits as building blocks and the forty-eight other M conductors are the equivalent pins or input conductors for the CLST 1000 circuits to provide continued high connectivity in the programmable logic circuit.

[0058] The CLST 1000 circuit of FIG. 10 is illustrated using a 2-SN cascading four 1-SNs with sixty four M conductors 1055, 1056 and sixteen four-input logic cells organized in four groups 1010, 1020, 1030, 1040 using a total of 1280 switches amongst the various SNs: SN 1050 of FIG. 10 and SN 200 of

FIG. 1 for each group **1010-1040** of **FIG. 10**. The CLST 1000 circuit of **FIG. 10** can have an alternative implementation using a 1-SN with sixty four M conductors, k(e.g., 16) plurality of N(e.g., 4) conductors using the methods discussed in **FIG. 9**. The number of switches is $M \times (N+k) = 1280$ using the analysis discussed herein. It turns out, in this case, both the 1-SN implementation and the embodiment of **FIG. 10** has the same number of switches.

[0059] The decision in determining which implementation is more suitable will depend on engineering considerations such as: whether a four-input MUX implementation with more intermediate stages of conductors in the **FIG. 10** embodiment or sixteen-input MUX and less number of intermediate stages of conductors in the 1-SN implementation is more preferable using SRAM technology, whether one style is more suitable in layout implementation, etc. It is important to note, based on the above analysis, that it is preferable to have a reasonable sized base array of logic cells connecting through a SN so the overhead, in total switch count, in stitching up several base arrays of logic cells using another SN in the next level of circuit hierarchy does not exceed implementing a larger sized base array of logic cells. In most programmable logic circuits, a base logic cell (of a logic cell array with a SN) usually has either three inputs or four inputs, and it is reasonable to see, from the illustrated examples discussed above, the number of logic cells, k, in the base logic array should not be a small number, or rather, depending upon the size of N, $k \times N$ should be of reasonable size (e.g., the CLST4 100 circuit of **FIG. 1**) for a SN to be used efficiently as the interconnect network.

[0060] Using numerous embodiments and illustrations, a detailed description in building various scalable non-blocking switching networks is provided and used in various combinations to provide interconnect, both for inputs and outputs, for programmable logic circuits. Depending on technology and engineering considerations, variations in implementation of the scalable non-blocking switching networks may be used, including, but not exclusive of, the use of MUXs to reduce number of memory controls, switch reductions, etc.

CLAIMS

What is claimed is:

1. An integrated circuit, comprising:
 - a first plurality of M number of conductors;
 - a second plurality of k sets of N number of conductors (k x N number of conductors); and
 - a switching network (SN), wherein M is at least k + N, where k is at least two and N is at least two;
 wherein the SN comprises:
 - a plurality of switches;
 - a third plurality of I₀ number of conductors, including N₀ sets of I_{0i} number of conductors for i = [1-N₀], wherein N₀ is at least two, N is at least N₀, I₀ is at least equal to M and between M and (k x N) when M is less than (k x N);
 - any two conductors of the first plurality of M number of conductors to selectively couple to at least two different conductors selected each from at least two different I_{0p} number of conductors and I_{0q} number of conductors, respectively, for p, q = [1-N₀] through the plurality of switches without requiring traversal of another conductor;
 - a first conductor of said at least two different conductors to selectively couple to a first set of at most (k x (M/N₀)) number of conductors through the SN, wherein the first set of at most (k x (M/N₀)) number of conductors has at most (M/N₀) number of conductors from each of the k sets of N number of conductors; and
 - a second conductor of the at least two different conductors to selectively couple to a second set of at most (k x (M/N₀)) number of conductors through the SN, wherein the second set of at most (k x (M/N₀)) number of conductors has at most (M/N₀) number of conductors,

different from the first set of at most $(k \times (M/N_0))$ number of conductors, from each of the k sets of N number of conductors.

2. The integrated circuit of claim 1, each conductor of the I_{0i} number of conductors to selectively couple k number of conductors through the SN without requiring traversal of another conductor.
3. The integrated circuit of claim 2, wherein the I_{0i} number is at most a larger of $(k \times N/N_0)$ number and (M/N_0) number, and wherein the plurality of switches is at least $[(M-N+1) \times N + M \times k]$ number of switches and at most $M \times (k + N)$ number of switches.
4. The integrated circuit of claim 2, further comprising k number of programmable logic cells, each of the k number of programmable logic cells having N number of input conductors, wherein each of the k number of conductors corresponds to one conductor of the N number of input conductors of the k number of programmable logic cells.
5. The integrated circuit of claim 1, where M is equals $R \times (k \times N)$, wherein R is at least 0.5 and at most 1.0.
6. The integrated of claim 1, further comprising:

a fourth plurality of I_{1i} number of conductors to selectively couple the I_{0i} number of conductors, wherein the I_{1i} number of conductors comprise N_1 groups of I_{1ij} number of conductors for $j = [1-N_1]$ where N_1 is at least two, wherein

any two conductors of the I_{0i} number of conductors to selectively couple to two different conductors of the I_{1i} number of conductors through the plurality of switches without requiring traversal of another conductor, wherein a third

conductor of the two different conductors is from I_{1ir} number of conductors and a fourth conductor of the two different conductors is from I_{1is} number of conductors and the number r is different from the number s for $r, s = [1-N1]$;

the third conductor to selectively couple a third set of at most $(k \times (M/(N0 \times N1)))$ number of conductors from the k sets of N number of conductors through the SN, wherein the third set of at most $(k \times (M/(N0 \times N1)))$ number of conductors has at most $(M/(N0 \times N1))$ number of conductors from each of the k sets of N number of conductors; and

the fourth conductor to selectively couple a fourth set of at most $(k \times (M/(N0 \times N1)))$ number of conductors from the k sets of N number of conductors through the SN, wherein the fourth set of at most $(k \times (M/(N0 \times N1)))$ number of conductors has at most $(M/(N0 \times N1))$ number of conductors, different from the third set of at most $(k \times (M/(N0 \times N1)))$ number of conductors, from each of the k sets of N number of conductors.

7. The integrated circuit of claim 6, wherein each conductor of the I_{1ij} number of conductors selectively couples k number of conductors through the SN without requiring traversal of another conductor.

8. The integrated circuit of claim 7, further comprising k number of programmable logic cells, each of the k number of programmable logic cells having N input conductors, wherein each of the k number of conductors corresponds to one conductor of said N number of input conductors of the k number of programmable logic cells.

9. The integrated circuit of claim 7, wherein the I_{1ij} number is at most the larger of $(k \times N/(N0 \times N1))$ number and $(M/(N0 \times N1))$ number and the plurality of switches are comprised of at most $[M \times (N0 + N1 + k)]$ number of switches.

10. The integrated circuit of claim 1, wherein each of the plurality of switches is comprised of at least a program controlled passgate.
11. The integrated circuit of claim 1, wherein each of the plurality of switches is comprised of at least a program controlled drivers/receivers.
12. The integrated circuit of claim 1, wherein the plurality of switches are comprised of at least one of program controlled passgates and program controlled drivers/receivers.
13. The integrated circuit of claim 1, wherein one of the plurality of switches has a program controlled on state and off state.
14. The integrated circuit of claim 1, wherein the integrated circuit is implemented using process technology incorporating memory devices.
15. The integrated circuit of claim 1, wherein the integrated circuit is implemented using process technology incorporating non-volatile memory devices.
16. The integrated circuit of claim 1, wherein the integrated circuit is implemented using process technology incorporating fuse devices.
17. The integrated circuit of claim 1, wherein the integrated circuit is implemented using process technology incorporating anti-fuse devices.
18. The integrated circuit of claim 1, wherein the integrated circuit is implemented using process technology incorporating Ferro-electric devices.

19. The integrated circuit of claim 1, wherein M is determined by $R \times (k \times N)$, where R is at least 0.5 and at most 1.0.

20. A method of connectivity in an integrated circuit comprising a first plurality of M number of conductors, a second plurality of k sets of N number of conductors ($k \times N$ number of conductors), and a switching network (SN) wherein M is at least $k + N$, where k is at least two and N is at least two, wherein the SN comprises a plurality of switches and a third plurality of I_0 number of conductors, including N_0 sets of I_{0i} number of conductors for $i = [1-N_0]$, wherein N_0 is at least two, N is at least N_0 , I_0 is at least equal to M and between M and $(k \times N)$ when M is less than $(k \times N)$, wherein the method comprises:

selectively coupling any two conductors of the first plurality of M number of conductors to at least two different conductors selected each from at least two different I_{0p} number of conductors and I_{0q} number of conductors, respectively, for $p, q = [1-N_0]$ through the plurality of switches without requiring traversal of another conductor;

selectively coupling a first conductor of said at least two different conductors to a first set of at most $(k \times (M/N_0))$ number of conductors through the SN, wherein the first set of at most $(k \times (M/N_0))$ number of conductors has at most (M/N_0) number of conductors from each of the k sets of N number of conductors; and

selectively coupling a second conductor of the at least two different conductors to a second set of at most $(k \times (M/N_0))$ number of conductors through the SN, wherein the second set of at most $(k \times (M/N_0))$ number of conductors has at most (M/N_0) number of conductors, different from the first set of at most $(k \times (M/N_0))$ number of conductors, from each of the k sets of N number of conductors.

21. The method of claim 20, further comprising selectively coupling each conductor of the $I0_i$ number of conductors to k number of conductors through the SN without requiring traversal of another conductor.

22. The method of claim 21, wherein the $I0_i$ number of conductors is at most a larger of $(k \times N/N0)$ number and $(M/N0)$ number, and wherein the plurality of switches is at least $[(M-N+1) \times N + M \times k]$ number of switches and at most $M \times (k + N)$ number of switches.

23. The method of claim 21, further comprising k number of programmable logic cells, each of the k number of programmable logic cells having N number of input conductors, wherein each of the k number of conductors corresponds to one conductor of the N number of input conductors of the k number of programmable logic cells.

24. The method of claim 20, where M equals $R \times (k \times N)$, wherein R is at least 0.5 and at most 1.0.

25. The method of claim 20, further comprising:
 selectively coupling a fourth plurality of $I1_i$ number of conductors to the $I0_i$ number of conductors, wherein the $I1_i$ number of conductors comprise $N1$ groups of $I1_{ij}$ number of conductors for $j = [1-N1]$ where $N1$ is at least two;
 selectively coupling any two conductors of the $I0_i$ number of conductors to two different conductors of the $I1_i$ number of conductors through the plurality of switches without requiring traversal of another conductor, wherein a third conductor of the two different conductors is from $I1_{ir}$ number of conductors and a fourth conductor of the two different conductors is from $I1_{is}$ number of conductors and the r is different from the s for $r, s = [1-N1]$;

selectively coupling the third conductor to a third set of at most $(k \times (M/(N_0 \times N_1)))$ number of conductors from the k sets of N number of conductors through the SN , wherein the third set of at most $(k \times (M/(N_0 \times N_1)))$ number of conductors has at most $(M/(N_0 \times N_1))$ number of conductors from each of the k sets of N number of conductors; and

selectively coupling the fourth conductor to a fourth set of at most $(k \times (M/(N_0 \times N_1)))$ number of conductors from the k sets of N number of conductors through the SN , wherein the fourth set of at most $(k \times (M/(N_0 \times N_1)))$ number of conductors has at most $(M/(N_0 \times N_1))$ number of conductors, different from the third set of at most $(k \times (M/(N_0 \times N_1)))$ number of conductors, from each of the k sets of N number of conductors.

26. The method of claim 25, further comprising selectively coupling each conductor of the I_{1ij} number of conductors to k number of conductors without requiring traversal of another conductor.

27. The method of claim 26, further comprising k number of programmable logic cells, each of the k number of programmable logic cells having N number of input conductors, wherein each of the k number of conductors corresponds to one conductor of the N number of input conductors of the k number of programmable logic cells.

28. The method of claim 26, wherein the I_{1ij} number is at most the larger of $(k \times N/(N_0 \times N_1))$ number and $(M/(N_0 \times N_1))$ number and the plurality of switches comprises at most $[M \times (N_0 + N_1 + k)]$ number of switches.