

(51) International Patent Classification:  
*G06F 19/00* (2011.01)(21) International Application Number:  
PCT/US2013/070398(22) International Filing Date:  
15 November 2013 (15.11.2013)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant: **LANDMARK GRAPHICS CORPORATION** [US/US]; 2107 City West Boulevard, Building 2, Houston, Texas 77042 (US).(72) Inventors: **FILIPPOV, Andrey**; 1715 Mossy Stone Dr., Houston, Texas 77077 (US). **LU, Jianxin**; 4810 Palmetto St., Bellaire, TX 77401 (US). **KHORIAKOV, Vitaly**; 22 Royal Birch RI NW, Calgary, Alberta T3G 5K2 (CA).(74) Agents: **RAJ, Vinu** et al.; Haynes and Boone, LLP, 2323 Victory Avenue, Suite 700, Dallas, Texas 75219 (US).


AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, — with international search report (Art. 21(3))

(54) Title: OPTIMIZING FLOW CONTROL DEVICE PROPERTIES FOR A LIQUID INJECTION WELL USING A COUPLED WELLBORE-RESERVOIR MODEL



(57) Abstract: The disclosed embodiments include a method, apparatus, and computer program product for determining optimal flow control device (FCD) properties that would yield to a prescribed shape of the injection flow rate profile. For example, in one embodiment, a computer implemented method is configured to perform the steps of: determining a reference location along a production length of the injection well; determining a reference value equal to the injection flow rate profile at the reference location along the production length of the injection well; defining a target injection profile using the reference value; determining a pressure distribution along the production length of the injection well based on the target injection profile; determining a FCD distribution profile using the target injection profile and the pressure distribution; and determining FCD properties that yields the target injection profile based on the FCD distribution profile.

