(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
8 March 2007 (08.03.2007)

PCT

(10) International Publication Number
WO 2007/027473 A3

(51) International Patent Classification:
H01L 21/8238 (2006.01) *H01L 27/092* (2006.01)
H01L 21/265 (2006.01)

(21) International Application Number:
PCT/US2006/032743

(22) International Filing Date: 23 August 2006 (23.08.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
102005041225.4 31 August 2005 (31.08.2005) DE
11/420,091 24 May 2006 (24.05.2006) US

(71) Applicant *(for all designated States except US)*: **ADVANCED MICRO DEVICES, INC.** [US/US]; One AMD Place, Mail Stop 68, P.O. Box 3453, Sunnyvale, CA 94088-3453 (US).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: **HOENTSCHEL, Jan** [DE/DE]; Mittelweg 33c, 01844 Neustadt In Sachsen (DE). **WEI, Andy** [US/DE]; Alaun Str 23, 01099 Dresden (DE). **KAMMLER, Thorsten** [DE/DE]; Buchenstr 12c, 01458 Ottendorf-Okrilla (DE). **RAAB, Michael** [DE/DE]; Mittlere Berg Str 57, 01445 Radebeul (DE).


(74) Agent: **DRAKE, Paul, S.**; Advanced Micro Devices, Inc., 5204 East Ben White Boulevard, Mail Stop 562, Austin, TX 78741 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: TECHNIQUE FOR FORMING RECESSED STRAINED DRAIN/SOURCE IN NMOS AND PMOS TRANSISTORS



(57) Abstract: By forming a strained semiconductor layer (117, 217) in a PMOS transistor (110, 210), a corresponding compressively strained channel region (11 IA) may be achieved, while, on the other hand, a corresponding strain in the NMOS transistor (120, 220) may be relaxed. Due to the reduced junction resistance caused by the reduced band gap of silicon/germanium in the NMOS transistor (120, 220), an overall performance gain is accomplished, wherein, particularly in partially depleted SOI devices, the deleterious floating body effect is also reduced, due to the increased leakage currents generated by the silicon/germanium layer (117, 127, 217, 227) in the PMOS (110, 210) and NMOS transistor (120, 220).

WO 2007/027473 A3

Published:
— *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:
19 April 2007

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.