【CLAIMS】

【Claim 1】

A method for decoding image data, the method ~~of removing blocking artifacts,~~ comprising:

~~determining a boundary strength for each 4-sample edge lying on 8x8 sample grid;~~

~~determining whether deblocking filtering is performed on the 4-sample edge or not if the boundary strength is not equal to zero;~~

~~selecting a deblocking filter if the deblocking filtering is performed on the 4-sample edge; and~~

~~filtering the 4-sample edge using the selected filter.~~generating a prediction block based on prediction mode;

generating a quantization block by inversely scanning quantization coefficient information;

generating a transform block by inversely quantizing the quantization block using a quantization parameter;

generating a residual block by inversely transforming the transform block;

generating a reconstructed block by using the prediction block and the residual block;

determining a boundary strength per each 4-sample edge which is a boundary of a transform unit or a prediction unit, and lies on 8x8 sample grid;

determining whether to apply deblocking filtering on the 4-sample edge when the boundary strength of the 4-sample edge is not zero;

selecting a deblocking filter which is applied to the 4-sample edge when it is determined to apply deblocking filtering on the 4-sample edge; and

filtering the 4-sample edge by using the selected deblocking filter,

wherein, in the operation of determining the boundary strength, the boundary strength is not determined for a 4-sample edge which does not lie on the 8x8 sample grid,

wherein the quantization parameter is derived by using residual quantization parameter and quantization parameter predictor,

wherein the quantization parameter predictor is an average of two available quantization parameters among a left quantization parameter, an above quantization parameter, and a previous quantization parameter, and

wherein the previous quantization parameter is set as the quantization parameter predictor when both of the left quantization parameter and the above quantization parameter are unavailable.

【Claim 2】

The method of claim 1, wherein the boundary strength is set ~~equal~~ to zero ~~if~~ when the 4-sample edge is neither a boundary of a transform unit nor a boundary of a prediction unit~~not a transform unit edge and the 4-sample edge is not a prediction unit edge~~.

【Claim 3】

The method of claim 1, wherein the boundary strength of the 4-sample edge is ~~set equal to~~ 0, 1, or 2.

【Claim 4】

The method of claim 1, wherein ~~vertical~~ 4-sample horizontal edges are filtered after 4-sample vertical edges are filtered~~first and then horizontal 4-sample edges are filtered~~.

【Claim 5】

The method of claim ~~4~~2, wherein, for a sample p0 and sample q0 which are located on each side of the 4-sample edge, the boundary strength is set to 2 when a prediction unit including the sample p0 or a prediction unit including the sample q0

is intra coded~~ the boundary strength is set equal to 2 if a prediction unit containing the sample p0 or a prediction unit containing the sample q0 is intra-coded~~.

【Claim 6】

The method of claim 5, wherein the boundary strength is set to 0 or 1 when the prediction unit including the sample p0 and the prediction unit including q0 are inter coded~~equal to 1 or 0 if a prediction unit containing the sample p0 and a prediction unit containing the sample q0 are inter-coded~~.

【Claim 7】

The method of claim 1, wherein the average of the two quantization parameter is rounded off.