

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
8 November 2001 (08.11.2001)

PCT

(10) International Publication Number
WO 01/84102 A1

- (51) International Patent Classification⁷: G01M 3/26, (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (21) International Application Number: PCT/AU01/00504
- (22) International Filing Date: 3 May 2001 (03.05.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: PQ 7266 3 May 2000 (03.05.2000) AU
- (71) Applicant (*for all designated States except US*): **STRUCTURAL MONITORING SYSTEMS LTD** [AU/AU]; Level 1, 16 Ord Street, WEST PERTH, Western Australia 6005 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **DAVEY, Kenneth, John** [AU/AU]; 15 Mann Way, BASSENDEAN, Western Australia 6054 (AU).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: SYSTEM AND METHOD FOR THE DETECTION AND PROPAGATION MEASUREMENT OF FLAWS IN A COMPONENT OR STRUCTURE



(57) Abstract: A system 10 for continuously monitoring the integrity of a structure 14 includes a sensor pad 16 having a surface 18. The surface 18 is provided with a set of first channels 22 and interspersed second channels 24. Surface 18 is sealed onto the surface 12 of structure 14 so that the channels 22, 24 together with surface 12 form respective sets of first and second cavities 26 and 28. The first cavities 26 are placed in fluid communication with a vacuum source 101 via a third channel 30. The second cavities 28 are vented to the atmosphere via a fourth channel 34, through hole 35, and conduit 36. A high impedance 102 is placed in series between the vacuum source 101 and the first cavities 26. A differential pressure transducer 103 is connected across the high impedance 102 and monitors for change in vacuum condition between the vacuum source 101 and the vacuum in the cavities 26. If a fault 40 were to develop in structure 14 opening onto surface 12 and propagate to form a fluid communication path between one of the cavities 26 and adjacent cavity 28 there will be a change in the vacuum condition of the cavity 26 which will be detected by the transducer 103.

WO 01/84102 A1

G00002