

ELECTRO-MAGNETIC CHECK VALVE

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Patent Application Serial No. 61/663, 868 filed June 25, 2012, the contents of which are incorporated herein by reference thereto

BACKGROUND OF THE INVENTION

[0002] The invention relates generally to transport refrigeration systems and, more particularly, to an air exchange valve of a transport refrigeration system.

[0003] A transport refrigeration system is used to control an environment in an enclosed area, such as the insulated box on trailers, trucks, containers. The refrigeration system absorbs heat from the enclosed area and releases the heat outside of the box into the environment. Perishable items that are commonly transported in such refrigeration systems respire over time, converting oxygen into carbon dioxide. If the concentration of oxygen is too low, or the concentration of carbon dioxide is too high, the cargo may be damaged. Fresh air exchanges avoid such a result by drawing fresh air into the system and forcing the carbon dioxide out an exhaust. The amount of fresh air drawn into the refrigeration system must be limited because the air may dry out the perishable items, and because power from the system must be used to cool the air.

BRIEF DESCRIPTION OF THE INVENTION

[0004] According to one embodiment of the invention, a valve for use in an air exchange panel of a transportation refrigeration system is provided including a valve cap configured and arranged to be positioned adjacent the air exchange panel and movable between a first position and a second position. The valve cap includes a magnetic portion. A resilient flexible member is coupled to the valve cap and is configured and arranged to be coupled to the air exchange panel. The resilient flexible member biases the valve cap into a first position. An electromagnet is positioned inside the air exchange panel, opposite the valve cap. A controller is coupled to the electromagnet to selectively apply power to move the valve cap between the first position and the second position.

[0005] According to another embodiment of the invention, a transportation refrigeration system is provided including a container having a wall. A sensor detects a state inside the

container. An air exchange panel is located with the wall of the container and includes an air intake duct. An air exchange valve is mounted to the air exchange panel adjacent the air intake duct and includes a valve cap movable between a first position and a second position. A resilient flexible member is coupled to the valve cap and biases the valve cap to a first position. The air exchange valve also includes an electromagnet located with the air exchange panel, opposite the valve cap. A controller is coupled to the electromagnet to selectively apply power to the electromagnet to move the valve cap between the first position and the second position in response to a signal from the sensor.

[0006] According to yet another embodiment of the invention, a method for operating a transportation refrigeration system having a container configured to store cargo is provided including detecting an oxygen level within the container. Power is applied to an electromagnet if the oxygen level is greater than or equal to a threshold. The oxygen level within the container is again detected. Power is removed from the electromagnet if the oxygen level is below the threshold. The valve cap is biased into a first position by a resilient flexible member.

[0007] These and other advantages and features will become more apparent from the following description taken in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWING

[0008] The subject matter, which is regarded as the invention, is particularly pointed out and distinctly claimed in the claims at the conclusion of the specification. The foregoing and other features, and advantages of the invention are apparent from the following detailed description taken in conjunction with the accompanying drawings in which:

[0009] FIG. 1 is a cross-section of a portion of a transportation refrigeration system;

[0010] FIG. 2 is a perspective view of an open air exchange valve;

[0011] FIG. 3 is a perspective view of a closed air exchange valve;

[0012] FIG. 4 is a perspective view of an air exchange panel;

[0013] FIG. 5 is a perspective view of an air exchange panel; and

[0014] FIG. 6 is a cross-section of another air exchange valve.

DETAILED DESCRIPTION OF THE INVENTION

[0015] Referring to FIG. 1, a simplified schematic diagram of a portion of an exemplary transport refrigeration system 10 is illustrated. The system 10 includes a container 12 for storing cargo, such as perishable goods for example. At least one wall 14 of the container 12

includes an air exchange panel 20. The air exchange panel 20 includes at least one air intake duct 22, at least one air exhaust duct 24, an air exchange valve 100 and a sensor 26. The air intake duct 24 receives oxygen-rich air external to the system, such as from the atmosphere for example. The carbon dioxide-rich air within the container 12 flows through the air exhaust duct 24 and is discharged outside the container 12. In one embodiment, the sensor 26 is configured to detect the amount of oxygen in the container 12 and based on the oxygen level detected to selectively operate the air exchange valve 100. More specifically, if the sensed oxygen level is below a predetermined value, a controller 28 in communication with the sensor 26 will open the air exchange valve 100, so that oxygen-rich air will flow through the air intake duct 22 and into the container 12. It will be appreciated that alternatively, the sensor 26 may be configured to sense the amount of carbon-dioxide in the container 12.

[0016] The air exchange valve 100 is mounted to the air exchange panel 20 adjacent the air intake duct 22 and is movable between a closed position, in which the air flow through the air intake duct 22 is inhibited, and an open position, in which the airflow through the air intake duct 22 is allowed. The air exchange valve 100 is electrically coupled through a controller 28 to the sensor 26. During normal operation of the system, when the sensor 26 determines that the oxygen in the container 12 is at an acceptable level, the valve 100 is held in the closed position, and flow through the air intake duct 22 is prohibited or substantially inhibited. If, however, the sensor 26 determines that the oxygen level is low, the valve 100 is opened, allowing oxygen-rich air to flow through the air intake duct 22 and into the container 12.

[0017] Referring now to FIGS. 2 and 3, an air exchange valve 100 is illustrated. The air exchange valve 100 includes a valve cap 102 mounted to a resilient flexible member 110, the valve cap 102 being movable between an open position and a closed position. The valve cap 102 may be made from a magnetic material or from an iron based steel. The valve cap 102 is sized such that when the valve cap 102 is in a closed position, the valve cap 102 inhibits air flow through the air intake ducts 22 of the air exchange panel 20. In one embodiment, a portion 112 of the resilient flexible member 110 is coupled to a first surface 104 of the valve cap 102, such as at the center of the first surface 104 for example. Alternate connections between the resilient flexible member 110 and the cap 102 are within the scope of the invention. In one embodiment, the resilient flexible member 110 is made from a sheet metal having a grain structure such that the resilient flexible member 110 has an increased flexibility in a direction parallel to the grain and an increased stiffness in a direction normal to the grain. The resilient flexible member 110 biases the valve cap 102 into an open

position. In one embodiment, when the valve cap 102 is in an open position (see FIG. 2), the resilient flexible member 110 is located within a plane and the first surface 104 of the valve cap 102 coupled to the resilient flexible member 110 is parallel to and abuts that plane.

When the valve cap 102 is in a closed position, shown in FIG. 3, the portion 112 of the resilient flexible member 110 coupled to the valve cap 102 extends out of the plane in the direction of the air exchange panel 20.

[0018] The valve cap 102 may additionally include at least one sealing mechanism 108 (FIG. 5) for engagement with a portion of an air exchange panel 20. The sealing mechanism 108 may be connected to or may be integrally formed with a second surface 106 (FIG. 5), opposite the first surface 104, of the valve cap 102. In one embodiment, the sealing mechanism 108 is a generally v-shaped peak that extends from the second surface 106 of the valve cap 102 to engage a gasket on the air exchange panel 20 to seal a respective air intake duct 22. The resilient flexible member 110 includes a first flange 114 having a first hole 116 and a second flange 120 having a second hole 122. The first flange 114 and the second flange 120 are coplanar and located on opposing sides of the resilient flexible member 110. A first spacer 118 is mounted to the first flange 114 adjacent the first hole 116 and a second spacer 124 is mounted to the second flange 120 adjacent the second hole 122. The first and second spacers 118, 124 extend perpendicular to the plane of the resilient flexible member 110 in the direction of the air exchange panel 20. The spacers 118, 124 may be used to couple a portion of the resilient flexible member 110 to the air exchange panel 20 at a fixed distance.

[0019] FIGS. 4 and 5 are cross-sectional views of the air exchange panel 20 when the air exchange valve 100 is in an open position and a closed position. Housed within the air exchange panel 20, is an electromagnet 150. In one embodiment, the electromagnet 150 includes an iron core and a wire 152 wrapped around the iron core. The wire 152 of the electromagnet 150 is coupled to the controller 28 so that power may be selectively applied to the wire 152. At least one air intake duct 22 is disposed adjacent the electromagnet 150. The air intake duct 22 extends through the air exchange panel 20 and into the container 12. The air exchange valve 100 is mounted to an exterior surface 21 of the air exchange panel 20 using a plurality of fasteners, such as screws for example. A fastener may extend through the hole 116, 122 in the flanges 114, 120 of the resilient flexible member 110 and the adjacent spacer 118, 124 respectively into the air exchange panel 20. The spacers 118, 124 define a space between the plane of the resilient flexible member 110 and the air exchange panel 20 so that the valve cap 102 may move between an open position and a closed position.

[0020] During operation of the transport refrigeration system 10, the air exchange valve 100 is biased into the open position by the resilient flexible member 110, as shown in FIG. 4. When the valve cap 102 is open, air may flow through the air intake ducts 22 of the air exchange panel 20. The pressure differential between the atmosphere and the inside of the container 12 draws the air through the open air intake ducts 22 and into the container 12.

[0021] If the sensor 26 detects that the oxygen level inside the container 12 has reached an acceptable level, the sensor 26 generates and sends a signal to the controller 28 coupled to the electromagnet 150. The controller 28 closes the valve 100 by applying power to the wire 152. When power is applied, the electromagnet 150 generates a magnetic field that attracts the valve cap 102, such that the sealing mechanisms 108 of the valve cap 102 create a seal about the air intake duct 22. The valve 100 will remain closed as long as the controller continues to power the electromagnet 150. When the sensor 26 determines that the oxygen level in the container 12 is too low, the sensor 26 generates and sends another signal to the controller 28. The controller 28, in turn, stops supplying electricity to the wire 152 of the electromagnet 150, thereby eliminating the magnetic field that attracts the valve cap 102. Because the electromagnet 150 no longer attracts the valve cap 102, the resilient flexible member 110 is able to bias the valve cap 102 into the open position. The sealing mechanisms 108 again separate from the surface 21 of the air exchange panel 20 to allow air to flow through the air intake ducts 22 and into the container 12.

[0022] In an alternate embodiment, illustrated in FIG. 6, the air exchange valve 200 pivots relative to the surface 21 the air exchange panel 20, rather than moving parallel to the air exchange panel 20 as described above. A first end 204 of the valve cap 202 may be mounted to the air exchange panel 20 with a resilient flexible member 210 and at least one fastener 220. Fixed to the first end 204, adjacent the fastener 220, is a stiffener plate 212 that securely clamps the valve cap 202 in a closed position. Mounted near the free end 206 of the valve cap 202 is a magnetic material 214, such as an iron core or permanent magnet for example. The magnetic material 214 is located opposite the electromagnet 150 of the air exchange panel, such that when the electromagnet 150 generates a magnetic field, the magnetic material 214 is attracted to the electromagnet 150. During normal operation, the valve cap 202 is biased into an open position by the flexible resilient member 210. When power is applied to the electromagnet 150, the magnetic material 214 is attracted to the magnetic field of the electromagnet 150 and the valve cap 202 is held in a closed position. When power is removed from the electromagnet 150, the magnetic force attracting the permanent magnet 214 is eliminated, and the resilient flexible member 210 biases the valve

cap 202 to an open position. A stop 230 may be disposed adjacent the free end 206 of the valve cap 202 to limit the angular movement of the valve cap 202 relative to the air exchange panel 20. Though it is desirable to provide a valve 202 that is open in the event of a power failure, it is within the scope of the invention to apply power to the electromagnet 150 to open the valve 200 rather than to close it.

[0023] While the invention has been described in detail in connection with only a limited number of embodiments, it should be readily understood that the invention is not limited to such disclosed embodiments. Rather, the invention can be modified to incorporate any number of variations, alterations, substitutions or equivalent arrangements not heretofore described, but which are commensurate with the spirit and scope of the invention. Additionally, while various embodiments of the invention have been described, it is to be understood that aspects of the invention may include only some of the described embodiments. Accordingly, the invention is not to be seen as limited by the foregoing description, but is only limited by the scope of the appended claims.

CLAIMS:

1. An electromagnetic check valve for use in an air exchange panel of a transportation refrigeration system, comprising:
 - a valve cap positioned adjacent the air exchange panel and movable between a first position and a second position, the valve cap including a magnetic portion;
 - a resilient flexible member, separate from and coupled to the valve cap, the resilient flexible member being connected to the air exchange panel to bias the valve cap into a first position;
 - an electromagnet positioned inside the air exchange panel opposite the valve cap, and
 - a controller that selectively applies power to the electromagnet to move the valve cap between the first position and the second position wherein the resilient flexible member includes a plurality of grains such that the resilient flexible member has an increased flexibility parallel to the plurality of grains and an increased stiffness normal to the plurality of grains.
2. The electro-magnetic check valve according to claim 1, wherein the valve cap is made of an iron based steel.
3. The electro-magnetic check valve according to claim 1, wherein the valve cap includes a permanent magnet.
4. The electro-magnetic check valve according to claim 1, wherein the resilient flexible member is located within a plane when the valve cap is in the first position.
5. The electro-magnetic check valve according to claim 1, wherein the resilient flexible member extends from a plane in the direction of the electromagnet when the valve cap is in the second position.
6. A transportation refrigeration system comprising:
 - a container having a wall;
 - a sensor for detecting a state within the container;
 - an air exchange panel disposed within the wall of the container including an air intake duct;

an air exchange valve mounted to the air exchange panel adjacent the air intake duct including:

- a valve cap movable between a first position and a second position, the valve cap being formed from a magnetic portion;
- a resilient flexible member coupled to the valve cap to bias the valve cap into a first position;
- an electromagnet disposed within the air exchange panel opposite the valve cap; and
- a controller for selectively applying power to the electromagnet to move the valve cap between a first position and a second position in response to a signal from the sensor;

wherein the resilient flexible member includes a plurality of grains such that the resilient flexible member has an increased flexibility parallel to the plurality of grains and an increased stiffness normal to the plurality of grains.

7. The transportation refrigeration system according to claim 6, wherein the valve cap is made of an iron based steel.

8. The transportation refrigeration system according to claim 6, wherein the valve cap includes a permanent magnet.

9. The transportation refrigeration system according to claim 6, wherein the resilient flexible member is located within a plane when the valve cap is in the first position.

10. The transportation refrigeration system according to claim 6, wherein the resilient flexible member extends from a plane in the direction of the electromagnet when the valve cap is in the second position.

11. The transportation refrigeration system according to claim 6, wherein the sensor detects an amount of oxygen within the container.

12. The transportation refrigeration system according to claim 6, wherein the sensor detects an amount of carbon dioxide within the container.

13. A method for operating a transportation refrigeration system having a container configured to store cargo, comprising:

detecting an oxygen level within the container;

applying power to an electromagnet if the oxygen level is greater than or equal to a threshold;

detecting the oxygen level within the container;

removing power from the electromagnet if the oxygen level is below the threshold;

and

biasing a valve cap and resilient flexible member to a first position to allow a flow of oxygen into the container, the valve cap being formed from a magnetic material;

wherein the resilient flexible member includes a plurality of grains such that the resilient flexible member has an increased flexibility parallel to the plurality of grains and an increased stiffness normal to the plurality of grains.

14. The method according to claim 13, wherein the oxygen level is detected by a sensor within the container.

15. The method according to claim 13, wherein a controller is coupled to both the sensor and the electromagnet.

16. The method according to claim 15, wherein the controller applies power to and removes power from the electromagnet in response to a signal from the sensor.

17. The method according to claim 13, wherein the resilient flexible member is coupled to the valve cap.




FIG. 1

2/6






FIG. 2

3/6





5/6




FIG. 5




FIG. 6