

GENERATING A CUSTOM RESERVOIR FROM MULTIPLE COMPARTMENTS REPRESENTING ONE OR MORE GEOLOGICAL STRUCTURES

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The priority of U.S. Provisional Patent Application No. 61/866,927, filed August 16, 2013, is hereby claimed and the specification thereof is incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

[0002] Not applicable.

FIELD OF THE DISCLOSURE

[0003] The present disclosure generally relates to systems and methods for generating a custom reservoir from multiple compartments representing one or more geological structures. More particularly, the present disclosure relates to generating a custom reservoir from multiple compartments representing one or more geological structures by performing custom reservoir generation on each compartment to generate one or more combined compartments.

BACKGROUND

[0004] Compartments are on-the-fly auto-detected sealed spaces in the framework bound by framework objects (surfaces, faults, geoshells, fluid contacts) and/or the framework limits. Compartments provide visual control for highly accurate volumetric calculations; they provide thickness grids and visualize complex geologic structures. Conventional compartments technology started modeling sealed spaces (volume-based modeling), but does not provide the level of functionality and updatability such as the geologic grouping of compartments and associated tools. In addition, the framework to geocellular model workflow is very linear and static and most capabilities are inherent to the geocellular models and not to the framework.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The present disclosure is described below with references to the accompanying drawings in which like elements are referenced with like reference numerals, and in which:

[0006] **FIG. 1** is a graphical user interface illustrating various different compartments (stratigraphic layer, fault block, fluid layer, combined), user specified properties and inherent properties in an exemplary table loaded in step **2104** of **FIG. 21**.

[0007] **FIGS. 2A-2B** are a flow diagram illustrating one embodiment of a method **200** for implementing the present disclosure.

[0008] **FIG. 3** is a flow diagram illustrating one embodiment of a method **300** for implementing step **206** in **FIG. 2**.

[0009] **FIGS. 4A-4B** are a flow diagram illustrating one embodiment of a method **400** for implementing step **208** in **FIG. 2**.

[0010] **FIG. 5** is a schematic diagram illustrating the intrusion of a geoshell body scanned in step **704** of **FIG. 7**.

[0011] **FIG. 6** is a display illustrating an exemplary three-dimensional geoshell volume compartment.

[0012] **FIG. 7** is a flow diagram illustrating one embodiment of a method **700** for implementing step **212** in **FIG. 2**.

[0013] **FIG. 8** is a schematic diagram illustrating a group of cached bodies for a stratigraphic layer in relation to a geoshell body returned in step **1022** of **FIG. 10**.

[0014] **FIG. 9** is a display illustrating an exemplary three-dimensional stratigraphic layer compartment.

[0015] **FIGS. 10A-10B** are a flow diagram illustrating one embodiment of a method

1000 for implementing step **214** in **FIG. 2**.

[0016] **FIG. 11** is a schematic diagram illustrating three groups of cached bodies for three respective fault blocks in relation to a geoshell body returned in step **1322** of **FIG. 13**.

[0017] **FIG. 12** is a display illustrating an exemplary three-dimensional fault block compartment.

[0018] **FIGS. 13A-13B** are a flow diagram illustrating one embodiment of a method **1300** for implementing step **218** in **FIG. 2**.

[0019] **FIG. 14** is a schematic diagram illustrating two groups of cached bodies for two respective fluid layers in relation to a geoshell body returned in step **2024** of **FIG. 20**.

[0020] **FIG. 15** is a display illustrating an exemplary three-dimensional fluid layer compartment.

[0021] **FIG. 16** is a display illustrating multiple groups of cached bodies for respective fluid reservoirs returned in step **2038** of **FIG. 20**.

[0022] **FIG. 17** is another display illustrating multiple groups of cached bodies for respective fluid reservoirs returned in step **2038** of **FIG. 20**.

[0023] **FIG. 18** is another display illustrating multiple groups of cached bodies for respective fluid reservoirs returned in step **2038** of **FIG. 20**.

[0024] **FIG. 19** is another display illustrating multiple groups of cached bodies for respective fluid reservoirs returned in step **2038** of **FIG. 20**.

[0025] **FIGS. 20A-20D** are a flow diagram illustrating one embodiment of a method **2000** for implementing step **224** in **FIG. 2**.

[0026] **FIGS. 21A-21C** are a flow diagram illustrating one embodiment of a method **2100** for implementing step **238** in **FIG. 2**.

[0027] **FIG. 22** is a Venn Diagram illustrating the various combinations from the group of union, intersect some and intersect all.

[0028] **FIGS. 23A-23B** are a flow diagram illustrating one embodiment of a method **2300** for implementing step **240** in **FIG. 2**.

[0029] **FIG. 24** is a flow diagram illustrating one embodiment of a method **2400** for implementing step **244** in **FIG. 2**.

[0030] **FIG. 25** is a block diagram illustrating one embodiment of a computer system for implementing the present disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0031] The present disclosure overcomes one or more deficiencies in the prior art by providing systems and methods for generating a custom reservoir from multiple compartments representing one or more geological structures by performing custom reservoir generation on each compartment to generate one or more combined compartments.

[0032] In one embodiment, the present disclosure includes a method for generating a custom reservoir from multiple compartments representing one or more geological structures, which comprises: i) selecting two or more compartments from the multiple compartments; ii) selecting one of union, intersect some and intersect all as a combination type; and iii) combining the two or more compartments based on the selected combination type into a combined compartment representing a custom reservoir using a computer processor, wherein union is a combination of the selected compartments, intersect some is a combination of a section of each selected compartment that intersects another selected compartment, and intersect all is a combination of only a section of each selected compartment that intersects each of the other selected compartments.

[0033] In another embodiment, the present disclosure includes a non-transitory program carrier device tangibly carrying computer-executable instructions for generating a custom reservoir from multiple compartments representing one or more geological structures, the instructions being executable to implement: i) selecting two or more compartments from the multiple compartments; ii) selecting one of union, intersect some and intersect all as a combination type; and iii) combining the two or more compartments based on the selected combination type into a combined compartment representing a custom reservoir, wherein union is a combination of the selected compartments, intersect some is a combination of a section of each selected compartment that intersects another selected compartment, and intersect all is a combination of only a section of each selected compartment that intersects each of the other selected compartments.

[0034] In yet another embodiment, the present disclosure includes a non-transitory program carrier device tangibly carrying computer-executable instructions for generating a custom reservoir from multiple compartments representing one or more geological structures, the instructions being executable to implement: i) selecting two or more compartments from the multiple compartments; lii) selecting intersect some as a combination type; and iii) combining the two or more compartments based on the selected combination type into a combined compartment representing a custom reservoir, wherein intersect some is a combination of a section of each selected compartment that intersects another selected compartment.

[0035] The subject matter of the present disclosure is described with specificity; however, the description itself is not intended to limit the scope of the disclosure. The subject matter thus, might also be embodied in other ways, to include different steps or combinations of steps similar to the ones described herein, in conjunction with other present or future

technologies. Moreover, although the term “step” may be used herein to describe different elements of methods employed, the term should not be interpreted as implying any particular order among or between various steps herein disclosed unless otherwise expressly limited by the description to a particular order. While the present disclosure may be applied in the oil and gas industry, it is not limited thereto and may also be applied in other industries to achieve similar results.

Method Description

[0036] The present disclosure describes compartment geogrouping, which models not only the framework objects but also the sealed spaces (compartments) in between. Compartment geogrouping automatically groups compartments into different categories without user interaction. When compartments are auto-detected, they are immediately grouped into stratigraphic layers, fault blocks, fluid layers and geoshells. Fluid layers are unique in that they have fluid layer type logic and support for blocking fluid flow across faults, surfaces and/or fluid contacts. In addition, custom reservoirs can be generated by merging or intersecting other compartments. Filter tools help identify the compartment(s) of interest. Compartment geogrouping advances the basic compartment technology. It offers geologically coherent combinations of sealed spaces, which are automatically detected and updated when bounding objects change. This significantly facilitates modeling complex frameworks as well as serving as basis for highly accurate property and volumetric analysis.

[0037] This disclosure includes features that support complex geological workflows such as intrusion isolation, seamless stratigraphic layer and fault block detection, advanced fluid contact interpretation with integrated fluid layer detection, pre-defined custom reservoir generation and management, and filter tools for reservoir selection. This disclosure also

includes dynamic and iterative updatability to optimize performance and make the tools more accessible. This generates a near real-time three-dimensional sealed model with inherently higher accuracy than cellular or subsampled alternatives. When compartments are auto-detected, they are immediately grouped into stratigraphic layers, fault blocks, fluid layers and geoshell volumes. The geogrouping engine keeps track of each framework object by referencing its sealing segments as individual patches. Each compartment can therefore, be assembled from its complete or a partial collection of its patches. This allows different geogrouping types to be assembled from different patch collections so interior seams (internal boundaries) or non-sealing edges can vanish from the final compartment. It also allows compartments to be merged or split automatically into overlapping regions. Geogrouping technology thus, can automatically assemble all of the individual patches into geological units on the fly.

[0038] Referring now to **FIGS. 2A-2B**, a flow diagram of one embodiment of a method **200** for implementing the present disclosure is illustrated.

[0039] In step **202**, current data comprising a plurality of source data points in a common coordinate system with predefined units is loaded into a conventional 3D modeling engine, operating in a system with predefined units, from a database.

[0040] In step **204**, the method **200** determines if the current data loaded in step **202** includes non-standard data. If the current data does not include non-standard data, then the method **200** proceeds to step **208**. Otherwise, the method **200** proceeds to step **206**.

[0041] In step **206**, generic geology adaptation is performed on the current data from step **202** to transform it into a recognizable geological structure such as, for example, a gridded

surface. One embodiment of a method for performing this step is described further in reference to **FIG. 3**.

[0042] In step **208**, Volume of Interest (VOI) based model sealing is performed using the current data from step **202** or the geological structure from step **206** to extrapolate the current data or the geological structure against the VOI to produce a cached body. In this manner arbitrary extents may be used within the model. Each cached body includes a top patch, a side patch and bottom patch, (each of which may be associated with a surface, a fault or a fluid contact), a center of mass and a volume. One embodiment of a method for performing this step is described further in reference to **FIGS. 4A-4B**.

[0043] In step **210**, the method **200** determines if geoshells are present in the cached bodies from step **208**. If geoshells are not present, then the method **200** proceeds to step **214**. Otherwise, the method **200** proceeds to step **212**.

[0044] In step **212**, an intrusion analysis is performed on the cached bodies from step **208** to isolate and extract any intrusive bodies. One embodiment of a method for performing this step is described further in reference to **FIG. 7**.

[0045] In step **214**, a stratigraphic analysis is performed on the cached bodies from step **208** or step **212** to extract stratigraphic layers from the cached bodies. One embodiment of a method for performing this step is described further in reference to **FIGS. 10A-10B**.

[0046] In step **216**, the method **200** determines if faults are present in the cached bodies from step **214**. If faults are not present, then the method **200** proceeds to step **220**. Otherwise, the method **200** proceeds to step **218**.

[0047] In step **218**, a fault block analysis is performed on the cached bodies from step **208** to extract fault blocks from the cached bodies. One embodiment of a method for performing

this step is described further in reference to **FIGS. 13A-13B**.

[0048] In step **220**, the method **200** determines if fluids are present in the cached bodies from step **214** or step **218**. If fluids are not present, then the method **200** proceeds to step **238**. Otherwise, the method **200** proceeds to step **224**.

[0049] In step **224**, a fluid fill analysis is performed on the group of cached bodies from step **214** and/or step **218** using advanced fluid fill analysis algorithms to extract fluid reservoirs from the geological structure represented by the group of cached bodies. One embodiment of a method for performing this step is described further in reference to **FIGS. 20A-20D**.

[0050] In step **238**, property matching is performed on the group of cached bodies from step **214**, step **218** and/or step **224** to convert each cached body to a respective compartment represented by a triangulated mesh of the bounding cached body with properties such as color and lithology. One embodiment of a method for performing this step is described further in reference to **FIGS. 21A-21C**.

[0051] In step **240**, custom reservoir generation is performed on each compartment from step **238** to generate one or more combined compartments. This allows intersection and union algorithms to sit on top of other compartments, which allows combined compartments to be generated automatically. One embodiment of a method for performing this step is described further in reference to **FIGS. 23A-23B**.

[0052] In step **242**, the compartments from step **238** and/or the combined compartments from step **240** may be displayed. In **FIGS. 6, 9, 12** and **15**, various exemplary displays illustrate the different compartments that may be displayed. In **FIG. 6**, the display **600** illustrates an exemplary three-dimensional geoshell volume compartment. In **FIG. 9**, the display **900** illustrates an exemplary three-dimensional stratigraphic layer compartment. In **FIG. 12**, the

display **1200** illustrates an exemplary three-dimensional fault block compartment. In **FIG. 15**, the display **1500** illustrates an exemplary three-dimensional fluid layer compartment.

[0053] In step **244**, one or more dynamic interactions are performed on the current data loaded in step **202**, the predefined polygon AOI and the predefined minimum/ maximum depths from the VOI based model sealing performed in step **208** and/or the fluid contact flag and the sealing state from the fluid fill analysis performed in step **224** to dynamically update the compartments from step **238** and/or the combined compartments from step **240**. One embodiment of a method for performing this step is described further in reference to **FIG. 24**.

Generic Geology Adaptation

[0054] Referring now to **FIG. 3**, a flow diagram of one embodiment of a method **300** for implementing step **206** in **FIG. 2** is illustrated. The method **300** performs a generic geology adaptation on the current data from step **202** to transform it into a recognizable geological structure such as, for example, a gridded surface. When combined with the fluid fill analysis from step **224**, gas and oil filled reservoirs may be interpreted with a higher degree of accuracy. When combined with the fluid fill analysis from step **224** and the custom reservoir generation from step **240**, the differences between measurement techniques, min and max cases, or fluid level variation through time may be evaluated. Typically, fluid contacts can only be represented as a flat plane or a predefined grid. The method **300**, however, allows any current data source such as, for example, hand digitized polylines to be transformed into fluid contacts in the 3D modeling engine as one example of a recognizable geological structure.

[0055] In step **302**, the current plurality of source data points loaded in step **202** is mapped to a common point cloud in the coordinate system of the current plurality of source data points using the 3D modeling engine and techniques well known in the art. In this

manner, a common point collection is mapped to a common point cloud.

[0056] In step **304**, a sorted point cloud collection with a footprint representing a boundary is created by sorting points in the common point cloud from step **302** according to a distance of each of the current plurality of source data points from an origin, first by a length of a z-vector in the z-axis and then by a length of an x-y vector across the x and y axes, using techniques well known in the art.

[0057] In step **308**, a new point cloud is created by reducing the footprint of the sorted point cloud collection created in step **304** using the 3D modeling engine and techniques well known in the art.

[0058] In step **310**, units for points in the new point cloud from step **308** are translated into the predefined units used by the system in which the 3D modeling engine operates using techniques well known in the art.

[0059] In step **312**, a recognizable geological structure is generated such as, for example, a gridded surface by gridding the points in the translated new point cloud from step **310** using the 3D modeling engine and techniques well known in the art. Each geological structure is returned to step **206** in **FIG. 2**.

VOI Based Model Sealing

[0060] Referring now to **FIGS. 4A-4B**, a flow diagram of one embodiment of a method **400** for implementing step **208** in **FIG. 2** is illustrated. The method **400** performs Volume of Interest (VOI) based model sealing using the current data from step **202** or the geological structure from step **206** to extrapolate the current data or the geological structure against the VOI to produce a cached body. In this manner, arbitrary extents may be used within the model that are different than the extents of the structural framework. Thus, the model may be used to

restrict the compartment generation to a desired trap when working in a trap within a larger basin. The method **400** provides a performance improvement and a varying level of resolution. Further, the model generated by method **400** can also be extended vertically to allow deeper estimates. Typically, a model is always generated based on the hulled extents of all surfaces and an internal padding value. The method **400**, however, uses a well-known algorithm for sealed model constraints to specify a full volume of interest or automatically calculate a smarter default for any unspecified information.

[0061] In step **402**, the method **400** determines if there is a predefined polygon area of interest (AOI). If there is a predefined polygon AOI, then the method **400** proceeds to step **406**. Otherwise, the method **400** proceeds to step **404**.

[0062] In step **404**, a polygon AOI is detected from hulled surfaces using techniques well known in the art.

[0063] In step **406**, a polygon AOI is set in the 3D modeling engine using a predefined polygon AOI or the polygon AOI detected in step **404**.

[0064] In step **408**, the method **400** determines if there are any predefined minimum/maximum depths of surfaces and/or faults. If there are predefined minimum/maximum depths of surfaces and/or faults, then the method **400** proceeds to step **412**. Otherwise, the method **400** proceeds to step **410**.

[0065] In step **410**, the minimum/maximum depths of surfaces/faults are detected. The minimum/maximum depths are detected by direct accumulation of modeled surface and fault extents. Modeled objects are queried in a loop and the minimum/maximum depths are stored. In this manner, the upper most and lower most compartments will properly seal.

[0066] In step **412**, minimum/maximum depths of the surfaces/faults are set in the 3D

modeling engine using predefined minimum/maximum depths of surfaces/faults or the minimum/maximum depths of surfaces and/or faults detected in step **410**.

[0067] In step **414**, topology patches are extracted from the 3D modeling engine using the polygon AOI set in step **406**, the minimum/maximum depths set in step **412** and techniques well known in the art. Each topology patch represents a triangulated mesh patch.

[0068] In step **416**, the topology patches extracted in step **414** are extrapolated or trimmed using the current data from step **202** or the geological structure from step **206**, and techniques well known in the art. If a patch is smaller than the polygon AOI, then conventional extrapolation is performed with zero dip. In this step, however, an average dip is used near the point of extrapolation providing a result with more consistency in parallel bedding. In cases where the patch is smaller, the triangulated mesh may be trimmed to the polygon AOI using techniques well known in the art.

[0069] In step **418**, the extrapolated or trimmed patches from step **416** are sealed and cleaned using techniques well known in the art. In this manner, each extrapolated or trimmed patch is sealed against the other extrapolated or trimmed patches and any overlap is trimmed to the bounding edge.

[0070] In step **420**, each sealed patch from step **418** is cached by body. In other words, each sealed patch is grouped as a solid body with the extrapolated or trimmed patches from step **416**. Each cached body includes a center of mass and volume. Each patch contains a symbolic link back to the bounding topology structure, which allows query by structure. The structure also allows navigation by top, side, or bottom structure query, i.e. what body is below. Each cached body is returned to step **208** in **FIG. 2**.

Intrusion Analysis

[0071] Referring now to **FIG. 7**, a flow diagram of one embodiment of a method **700** for implementing step **212** in **FIG. 2** is illustrated. The method **700** performs an intrusion analysis on the cached bodies from step **208** to isolate and extract any intrusive bodies (e.g. geoshells). Geoshells are data objects used to represent uncharacteristic complex geometries such as salt bodies. Geoshells are separated as a compartment group called geoshell volumes, which are automatically subtracted from volumetric calculations of stratigraphic layers, fault blocks, and fluid layers because they typically represent different properties from the surrounding rock. The method **700** may be performed immediately after each sealed patch is cached by body in step **208**. No additional access to the topology engine is required from this point forward. In conventional applications, all intrusions are seamed combinations of stratigraphic layers that require manual disassembly and reassembly. The method **700**, however, automatically extracts and groups intrusions without seams.

[0072] In step **704**, each cached body from step **208** is scanned for isolated geoshell bodies. In this manner, the bodies will be queried for any objects that contain an intrusion (geoshell) and will identify each body that contains only an intrusion. Since a geoshell represents an intrusion, it will inherently not have seams from other structures. There could, however, still be multiple patches and internal seams from the same intrusion or other intrusions. In **FIG. 5**, a schematic diagram **500** illustrates the intrusion of a geoshell body **502**.

[0073] In step **706**, matched patches are grouped together in an intermediate object for the cached bodies from step **208** that contain an intrusion identified in step **704**.

[0074] In step **708**, shared internal patches are removed from each group of matched patches from step **706**. All shared internal patches (e.g. duplicated or common but not an

external edge) are removed from the group of matched patches using techniques well known in the art.

[0075] In step **710**, each group of matched patches remaining after step **708** is cached as a single group.

[0076] In step **712**, the isolated geoshell bodies scanned in step **704** are removed from each group of matched patches in step **710**. Because an intrusion is not part of the surrounding stratigraphy, the isolated geoshell bodies are removed from each group of matched patches. This ensures no other geological analysis will process them.

[0077] In step **714**, a compartment is generated by linking each group of matched patches from step **712** to a respective compartment that is cached as a respective body. Each compartment includes a center of mass and a volume. Each cached body is returned to step **212** in **FIG. 2**.

Stratigraphic Analysis

[0078] Referring now to **FIGS. 10A-10B**, a flow diagram of one embodiment of a method **1000** for implementing step **214** in **FIG. 2** is illustrated. The method **1000** performs a stratigraphic analysis on the cached bodies from step **208** or step **212** to extract stratigraphic layers from the cached bodies. In case of surfaces with different areal extents, the compartment boundaries are extrapolated to the extents of the largest surface. A stratigraphic layer is always created above the topmost surface and below the bottommost surface, which represent arbitrary extensions into unknown rock layers. Stratigraphic layers automatically adjust to changes of the surface sources (e.g. horizons, picks) and changes to the framework model (e.g. surface AOI, algorithms etc.). In conventional applications, all stratigraphic layers are seamed of several bodies sorted by all bounding structure names and are auto-grouped in a system that creates

challenges to recognition. The method **1000**, however, automatically extracts stratigraphic layers and groups them without seams or intrusions for simple identification.

[0079] In step **1002**, each cached body from step **208** or step **212** is loaded. Thus, each cached body includes a top patch, a center of mass and a volume.

[0080] In step **1004**, a surface flag is assigned to each respective one of the cached bodies loaded in step **1002**. Each surface flag is designated or set to empty.

[0081] In step **1006**, a surface flag is selected from step **1004** that is assigned to one of the cached bodies loaded in **1002** with a top patch that is a surface.

[0082] In step **1012**, the surface flag selected in step **1006** is converted from empty to a top-surface representing a top-surface flagged body.

[0083] In step **1014**, one of the cached bodies loaded in step **1002** that is below the top-surface flagged body from step **1012** is selected.

[0084] In step **1016**, the cached body selected in step **1014** is identified to determine if it is a continuation of the top-surface flagged body from step **1012**.

[0085] In step **1018**, the method **1000** determines if there are any bodies in the cached bodies loaded in step **1002** that are below the top-surface flagged body from step **1012**. If there are bodies in the cached bodies loaded in step **1002** that are below the top-surface flagged body from step **1012**, then the method **1000** returns to step **1014**. Otherwise, the method **1000** proceeds to step **1020**.

[0086] In step **1020**, the method **1000** determines if there are any remaining surface flags from step **1004** that are assigned to one of the cached bodies loaded in step **1002** with a top patch that is a surface and a surface flag that has not been converted from empty to a top surface representing a top-surface flagged body. If there are any surface flags from step **1004** that are

assigned to one of the cached bodies loaded in step **1002** with a top patch that is a surface and a surface flag that has not been converted from empty to a top surface representing a top-surface flagged body, then the method **1000** returns to step **1006**. Otherwise, the method **1000** proceeds to step **1022**.

[0087] In step **1022**, each top-surface flagged body from step **1012** and each respective body identified in step **1016** as a continuation of the top-surface flagged body from step **1012** are separated into a group of cached bodies. The group of cached bodies is returned to step **214** in **FIG. 2**. In **FIG. 8**, a schematic diagram **800** illustrates a group of cached bodies for a stratigraphic layer **802** in relation to the geoshell body **502** in **FIG. 5**.

Fault Block Analysis

[0088] Referring now to **FIGS. 13A-13B**, a flow diagram of one embodiment of a method **1300** for implementing step **218** in **FIG. 2** is illustrated. The method **1300** performs a fault block analysis on the cached bodies from step **208** or step **212** to extract fault blocks from the cached bodies. In many models, surfaces may be much larger than faults. Faults can be extrapolated using fault networking and a smaller compartment attribute-of-interest polygon can be specified to ensure faults can seal enough of the solid model to properly detect fault blocks. Fault blocks automatically adjust to changes of the fault sources (e.g. seismic faults, fault picks) and changes to the framework model (e.g. fault networking, fault sealing). In conventional applications, fault blocks cannot be generated due to the limitations resolved by volume-of-interest model sealing. The method **1300**, however, enables fault blocks to be automatically extracted and grouped without seams. The faults may be structurally sealing and completely isolate a 3D space within two surfaces in order to be extracted. The resulting collection of individual compartments becomes a fault block. Geoshell volumes are removed against the fault

blocks for the purpose of volumetric calculations.

[0089] In step **1302**, the cached bodies from step **208** or step **212** are loaded. Thus, each cached body includes a side patch, a center of mass and a volume.

[0090] In step **1304**, a fault flag is assigned to each respective one of the cached bodies loaded in step **1302**. Each fault flag is designated or set to empty.

[0091] In step **1306**, a fault flag is selected from step **1304** that is assigned to one of the cached bodies loaded in **1302** with a top patch that is a fault.

[0092] In step **1312**, the fault flag selected in step **1306** is converted from empty to a fault representing a fault-flagged body.

[0093] In step **1314**, one of the cached bodies loaded in step **1302** that is below the fault-flagged body from step **1312** is selected.

[0094] In step **1316**, the cached body selected in step **1314** is identified to determine if it is a continuation of the fault-flagged body from step **1312**.

[0095] In step **1318**, the method **1300** determines if there are any bodies in the cached bodies loaded in step **1302** that are below the fault-flagged body from step **1312**. If there are bodies in the cached bodies loaded in step **1302** that are below the fault-flagged body from step **1312**, then the method **1300** returns to step **1314**. Otherwise, the method **1300** proceeds to step **1320**.

[0096] In step **1320**, the method **1300** determines if there are any remaining fault flags from step **1304** that are assigned to one of the cached bodies loaded in step **1302** with a top patch that is a fault and a fault flag that has not been converted from empty to a fault representing a fault-flagged body. If there are any fault flags from step **1304** that are assigned to one of the cached bodies loaded in step **1302** with a top patch that is a fault and a fault flag that

has not been converted from empty to a fault representing a fault-flagged body, then the method **1300** returns to step **1306**. Otherwise, the method **1300** proceeds to step **1322**.

[0097] In step **1322**, each fault-flagged body from step **1312** and each respective body identified in step **1316** as a continuation of the fault-flagged body from step **1312** are separated into a group of cached bodies. The group of cached bodies is returned to step **218** in **FIG. 2**. In **FIG. 11**, a schematic diagram **1100** illustrates three groups of cached bodies for three respective fault blocks **1104**, **1106**, and **1008** in relation to the geoshell body **502** in **FIG. 5**.

Fluid Fill Analysis

[0098] Referring now to **FIGS. 20A-20D**, a flow diagram of one embodiment of a method **2000** for implementing step **224** in **FIG. 2** is illustrated. The method **2000** performs a fluid fill analysis on the group of cached bodies from step **214** and/or step **218** using advanced fluid fill analysis algorithms to extract fluid reservoirs from the geological structure represented by the cached bodies. Fluid Layers are created between fluid contacts and other fluid contacts or framework surfaces. Fluid layers are a particular compartment type defined by a fluid property such as oil, gas, water or a generic fluid. They may also be subdivided by sealing faults. In conventional applications, fluid compartments are manually grouped by individually turning them on in a view and then dragging and dropping them into a new grouping. This creates a slow, frustrating, seamed grouping with no fluid properties. The method **2000**, however, enables fluid layers to be automatically detected, filled, and grouped by fluid type.

[0099] In step **2004**, the group of cached bodies from step **214** and/or step **218** is loaded. Thus, each cached body in either group includes a top patch, a center of mass and a volume.

[00100] In step **2008**, any cached bodies in the group of cached bodies loaded in step

2004 that are duplicated are removed.

[00101] In step **2010**, a fluid contact flag is assigned to each respective one of the cached bodies remaining after step **2008**. Each fluid contact flag is designated or set to empty.

[00102] In step **2012**, a fluid contact flag is selected from step **2010** that is assigned to one of the cached bodies remaining after step **2008** with a top-patch that is a fluid contact.

[00103] In step **2014**, the fluid contact flag selected in step **2012** is converted from empty to a fluid contact representing a top-fluid contact flagged body.

[00104] In step **2016**, one of the cached bodies remaining after step **2008** that is in the same fault block or stratigraphic layer as the top-fluid contact flagged body from step **2014** is selected.

[00105] In step **2018**, the cached body selected in step **2016** is identified to determine if it is a continuation of the top-fluid contact flagged body from step **2014**.

[00106] In step **2020**, the method **2000** determines if there are any bodies in the cached bodies remaining after step **2008** that are in the same fault block or stratigraphic layer as the top-fluid contact flagged body from step **2014**. If there are bodies in the cached bodies remaining after step **2008** that are in the same fault block or stratigraphic layer as the top-fluid contact flagged body from step **2014**, then the method **2000** returns to step **2016**. Otherwise, the method **2000** proceeds to step **2022**.

[00107] In step **2022**, the method **2000** determines if there are any remaining fluid contact flags from step **2010** that are assigned to one of the cached bodies remaining after step **2008** with a top-patch that is a fluid contact and a fluid contact flag that has not been converted from empty to a fluid contact representing a top-fluid contact flagged body. If there are any fluid contact flags from step **2010** that are assigned to one of the cached bodies remaining after step

2008 with a top-patch that is a fluid contact and a fluid contact flag that has not been converted from empty to a fluid contact representing a top-fluid contact flagged body, then the method **2000** returns to step **2012**. Otherwise, the method **2000** proceeds to step **2024**.

[00108] In step **2024**, each top-fluid contact flagged body from step **2014** and each respective body identified in step **2018** as a continuation of the top-fluid contact flagged body from step **2014** are separated into a group of cached bodies. In **FIG. 14**, a schematic diagram **1400** illustrates two groups of cached bodies for respective fluid layers **1404** and **1406** in relation to the geoshell body **502** in **FIG. 5**.

[00109] In step **2026**, a reservoir flag is assigned to each respective one of the bodies in the group of cached bodies from step **2024**. Each reservoir flag is designated or set to empty.

[00110] In step **2028**, a reservoir flag is selected from step **2026** that is assigned to one of the bodies in the group of cached bodies from step **2024**.

[00111] In step **2030**, the reservoir flag selected in step **2028** is converted from empty to a fluid type based on the fluid contact flag from step **2010** and a unique identifier (e.g. oil 17) representing a fluid-reservoir flagged body.

[00112] In step **2032**, a body in the group of cached bodies from step **2024** that has the same fluid contact as the fluid-reservoir flagged body from step **2030** is selected.

[00113] In step **2034**, the method **2000** determines if there is a shared patch between the body assigned to the reservoir flag selected in step **2028** and the body selected in step **2032** that seals against fluid flow using the client interface and/or the video interface described in reference to **FIG. 25**. If there is not a shared patch between the body assigned to the reservoir flag selected in step **2028** and the body selected in step **2032** that seals against fluid flow, then the method **2000** returns to step **2032**. Otherwise, the method **2000** proceeds to step **2035**.

[00114] In step **2035**, the body selected in step **2032** is identified to determine if it is a continuation of the fluid-reservoir flagged body from step **2030**.

[00115] In step **2036**, the method **2000** determines if there are any remaining reservoir flags from step **2026** that are assigned to one of the bodies in the group of cached bodies from step **2024** that have not been converted from empty to a fluid type and a unique identifier representing a fluid-reservoir flagged body. If there are any reservoir flags from step **2026** that are assigned to one of the bodies in the group of cached bodies from step **2024** that have not been converted from empty to a fluid type and a unique identifier representing a fluid-reservoir flagged body, then the method **2000** returns to step **2028**. Otherwise, the method proceeds to step **2038**.

[00116] In step **2038**, each fluid-reservoir flagged body from step **2030** and each respective body identified in step **2035** as a continuation of the fluid-reservoir flagged body from step **2030** are separated into a group of cached bodies. The group of cached bodies is returned to step **224** in **FIG. 2**. In **FIGS. 16-19**, various exemplary displays **1600**, **1700**, **1800** and **1900** illustrate multiple groups of cached bodies for respective fluid reservoirs with different sealing states.

Property Matching

[00117] Referring now to **FIGS. 21A-21C**, a flow diagram of one embodiment of a method **2100** for implementing step **238** in **FIG. 2** is illustrated. The method **2100** performs property matching on the group of cached bodies from step **214**, step **218** and/or step **224** to convert each cached body to a respective compartment represented by a triangulated mesh of the bounding cached body with properties such as color and lithology. This facilitates finding specific compartments when a large number of compartments are present. One or more

boundary objects such as surfaces, faults, fluid contacts and geoshells may be selected and all compartments that share those objects as boundaries are identified. Multiple selections mean that any of the selected boundaries may be matched. Since all compartments are a combination of patches from the framework structure, any compartment can be quickly scanned for common structural boundaries. This provides a near instant filtering method even with thousands of compartments in complex frameworks. In conventional applications, all compartments are generated with a random color and names that represent a string amalgamation of all the structural boundaries surrounding the compartment that can change each model build or new session load. The method **2100**, however, provides the ability to set custom names and properties such as color or lithology, and provides that compartments return with the same properties each time the model is loaded to a new session.

[00118] In step **2102**, the group of cached bodies from step **214**, step **218** and/or step **224** is loaded.

[00119] In step **2103**, the method **2100** determines if there is a table of properties for different compartments. If there is no table of properties for different compartments, then the method **2100** proceeds to step **2117**. Otherwise, the method **2100** proceeds to step **2104**.

[00120] In step **2104**, a table of properties for different compartments is loaded. The table includes user specified properties like color, name or lithology and inherent properties like patches, center of mass and volume for each compartment. In **FIG. 1**, a graphical user interface **100** illustrates various different compartments (stratigraphic layer, fault block, fluid layer, combined), user specified properties and inherent properties in an exemplary table.

[00121] In step **2108**, the method **2100** determines if one or more properties in the table from step **2104** match a cached body from a group of cached bodies loaded in step **2102**. If one

or more properties in the table from step **2104** do not match a cached body from a group of cached bodies loaded in step **2102**, then the method **2100** proceeds to step **2112**. Otherwise, the method **2100** proceeds to step **2109**. A match is determined by comparing the inherent properties (e.g. patches, center of mass, volume) in the table and the inherent properties of each cached body from a group of cached bodies loaded in step **2102** for identical values (i.e. an exact match).

[00122] In step **2109**, the one or more properties in the table from step **2104** that match (i.e. have identical inherent properties) a respective body in a group of cached bodies loaded in step **2102** are associated with the respective body.

[00123] In step **2110**, the method **2100** determines if there are any remaining cached bodies from a group of cached bodies loaded in step **2102** that do not match one or more properties in the table from step **2104**. If there are cached bodies from a group of cached bodies loaded in step **2102** that do not match one or more properties in the table from step **2104**, then the method **2100** proceeds to step **2112**. Otherwise, the method **2100** proceeds to step **2118**. A match is determined by comparing the inherent properties (e.g. patches, center of mass, volume) in the table and the inherent properties of each cached body from a group of cached bodies loaded in step **2102** for identical values (i.e. an exact match).

[00124] In step **2112**, the method **2100** determines if one or more properties in the table from step **2104** relate to any remaining cached bodies from a group of cached bodies loaded in step **2102**. If one or more properties in the table from step **2104** do not relate to any remaining cached bodies from a group of cached bodies loaded in step **2102**, then the method **2100** proceeds to step **2116**. Otherwise, the method **2100** proceeds to step **2113**. One or more properties in the table from step **2104** relate to a respective cached body from a group of cached

bodies loaded in step **2102** if the inherent properties (e.g. patches, center of mass, volume) in the table and the inherent properties of a respective cached body have corresponding values within a predefined tolerance.

[00125] In step **2113**, the one or more properties in the table from step **2104** that relate to a respective body in a group of cached bodies loaded in step **2102** are associated with the respective body.

[00126] In step **2114**, the method **2100** determines if there are any remaining cached bodies from a group of cached bodies loaded in step **2102** that do not relate to one or more properties in the table from step **2104**. If there are cached bodies from a group of cached bodies loaded in step **2102** that do not relate to one or more properties in the table from step **2104**, then the method proceeds to step **2116**. Otherwise, the method **2100** proceeds to step **2118**.

[00127] In step **2116**, default properties are created in the table from step **2104** for the remaining cached bodies from a group of cached bodies loaded in step **2102** that do not relate to one or more properties in the table from step **2104**. The method **2100** then proceeds to step **2118**.

[00128] In step **2117**, a table is created for different compartments with default properties for each cached body in a group of cached bodies loaded in step **2102**. The default properties include user specified properties like color, name or lithology and inherent properties like patches, center of mass and volume for each compartment.

[00129] In step **2118**, a compartment is created for each row of properties in the table from step **2104** or step **2117**, wherein each row of properties represents one or more continuous bodies. Each compartment is returned to step **238** in **FIG. 2**.

Custom Reservoir Generation

[00130] Referring now to **FIGS. 23A-23B**, a flow diagram of one embodiment of a method **2300** for implementing step **240** in **FIG. 2** is illustrated. The method **2300** performs custom reservoir generation on each compartment from step **238** to generate one or more combined compartments. Since each compartment is composed of patches, those patches can be reassembled into new compartments on the fly. By analyzing the interior of bounding patches, connected compartments may be either grouped or isolated. Once a new set of sealed patches is assembled, the interior seams will be removed. The final result is a merge or intersection between any set of compartments, which forms a combined compartment. All volumes and properties will honor the new bounding edges. In conventional applications, all compartments are isolated as individual bodies that are manually assembled into meaningful geological units. The method **2300**, however, automatically generates most standard geological units. This automatic generation provides an advantage, even in those situations where a subset or merging of these units may be more useful.

[00131] In step **2302**, each compartment from step **238** is loaded.

[00132] In step **2304**, two or more compartments loaded in step **2302** are selected.

[00133] In step **2306**, a combination type from the group of union, intersect some, intersect all is selected. A union is the combination of all selected compartments. Intersect some is the combination of the section of each selected compartment that intersects another selected compartment. Intersect all is the combination of only the section of each selected compartment that intersects each of the other selected compartments. In **FIG. 22**, a Venn Diagram illustrates the various combinations from the group of union (**2202**), intersect some (**2204**) and intersect all (**2206**).

[00134] In step **2308**, the method **2300** determines if the combination type selected in step **2306** is union using the client interface and/or the video interface described in reference to **FIG. 25**. If the combination type selected in step **2306** is not a union, then the method **2300** proceeds to step **2312**. Otherwise, the method **2300** proceeds to step **2310**.

[00135] In step **2310**, the compartments selected in step **2304** are combined into a combined compartment that is returned to step **240** in **FIG. 2**.

[00136] In step **2312**, the method **2300** determines if the combination type selected in step **2306** is intersect some using the client interface and/or the video interface described in reference to **FIG. 25**. If the combination type selected in step **2306** is not intersect some, then the method **2300** proceeds to step **2316**. Otherwise, the method **2300** proceeds to step **2314**.

[00137] In step **2314**, each section of each compartment selected in step **2304** that intersects another compartment selected in step **2304** is combined into a combined compartment that is returned to step **240** in **FIG. 2**. Unlike the example in **FIG. 22**, multiple intersections may be non-contiguous depending on the position of the selected compartments.

[00138] In step **2316**, only the section of each compartment selected in step **2304** that intersects each of the other compartments selected in step **2304** is combined into a combined compartment that is returned to step **240** in **FIG. 2**.

Dynamic Interactions

[00139] Referring now to **FIG. 24**, a flow diagram of one embodiment of a method **2400** for implementing step **244** in **FIG. 2** is illustrated. The method **2400** performs one or more dynamic interactions on the current data loaded in step **202**, the predefined polygon AOI and the predefined minimum/maximum depths from the VOI based model sealing performed in step **208** and/or the fluid contact flag and the sealing state from the fluid fill analysis performed in

step **224** to dynamically update the compartments from step **238** and/or the combined compartments from step **240**. Compartments are automatically synchronized with updates and there is no need to redetect compartments after framework changes. Since the compartments can now incrementally update, performance is improved. Even disabling compartments will keep the state preserved so enabling compartments will still only need an incremental update. As a result, compartments may be active more frequently and more analysis tools may be used. In conventional applications, compartments are often required to be manually redetected any time they updated the model, changed properties, or grouped compartments. In addition, visibility states are often required to be constantly toggled to parse names and figure out which compartment is needed. The method **2400**, however, enables all aspects of dynamic updatability for compartments. In other words, sealed geological units are always visible that update with each change to the model. There is no additional interaction required and the compartments can be used for quality control and better comprehend the complex, three-dimensional structure of a geological model.

[00140] In step **2402**, each compartment from step **238** and each combined compartment from step **240** is loaded.

[00141] In step **2404**, the method **2400** determines if there is any more current data than the current data loaded in step **202**. If there is more current data than the current data loaded in step **202**, then the method **2400** returns to step **202** to load the more current data. Otherwise, the method **2400** proceeds to step **2406**.

[00142] In step **2406**, the method **2400** determines if the predefined polygon AOI referred to in step **402** or the predefined minimum/maximum depths referred to in step **408** have changed. If the predefined polygon AOI referred to in step **402** or the predefined

minimum/maximum depths referred to in step **408** have changed, then the method **2400** returns to step **406** to set the polygon AOI using a new predefined polygon AOI or step **412** to set the minimum/maximum depths using new predefined minimum/maximum depths. Otherwise, the method **2400** proceeds to step **2408**.

[00143] In step **2408**, the method **2400** determines if the fluid contact flag referred to in step **2012** or the sealing state referred to in step **2034** have changed. If the fluid contact flag referred to in step **2012** or the sealing state referred to in step **2034** have changed, then the method **2400** returns to step **2010** to select a fluid contact flag using a new fluid contact flag or step **2034** to determine if there is a shared patch using a new sealing state. Otherwise, the method **2400** returns to step **2404**.

System Description

[00144] The present disclosure may be implemented through a computer-executable program of instructions, such as program modules, generally referred to as software applications or application programs executed by a computer. The software may include, for example, routines, programs, objects, components, data structures, etc., that perform particular tasks or implement particular abstract data types. The software forms an interface to allow a computer to react according to a source of input. DecisionSpace® Geosciences, which is a commercial software application marketed by Landmark Graphics Corporation, may be used as an interface application to implement the present disclosure. The software may also cooperate with other code segments to initiate a variety of tasks in response to data received in conjunction with the source of the received data. Other code segments may provide optimization components including, but not limited to, neural networks, earth modeling, history-matching, optimization, visualization, data management, reservoir simulation and economics. The software may be

stored and/or carried on any variety of memory such as CD-ROM, magnetic disk, bubble memory and semiconductor memory (*e.g.*, various types of RAM or ROM). Furthermore, the software and its results may be transmitted over a variety of carrier media such as optical fiber, metallic wire, and/or through any of a variety of networks, such as the Internet.

[00145] Moreover, those skilled in the art will appreciate that the disclosure may be practiced with a variety of computer-system configurations, including hand-held devices, multiprocessor systems, microprocessor-based or programmable-consumer electronics, minicomputers, mainframe computers, and the like. Any number of computer-systems and computer networks are acceptable for use with the present disclosure. The disclosure may be practiced in distributed-computing environments where tasks are performed by remote-processing devices that are linked through a communications network. In a distributed-computing environment, program modules may be located in both local and remote computer-storage media including memory storage devices. The present disclosure may therefore, be implemented in connection with various hardware, software or a combination thereof, in a computer system or other processing system.

[00146] Referring now to **FIG. 25**, a block diagram illustrates one embodiment of a system for implementing the present disclosure on a computer. The system includes a computing unit, sometimes referred to as a computing system, which contains memory, application programs, a client interface, a video interface, and a processing unit. The computing unit is only one example of a suitable computing environment and is not intended to suggest any limitation as to the scope of use or functionality of the disclosure.

[00147] The memory primarily stores the application programs, which may also be described as program modules containing computer-executable instructions, executed by the

computing unit for implementing the present disclosure described herein and illustrated in **FIGS. 1-24**. The memory therefore, includes a compartment geogrouping module, which enables steps **204, 206, 210-240** and **244** in **FIG. 2**. The component geogrouping module may integrate functionality from the remaining application programs illustrated in **FIG. 25**. In particular, DecisionSpace® Geosciences may be used as an interface application to perform step **242** in **FIG. 2** and a 3D modeling engine may be used to perform step **208** in **FIG. 2**. Step **202** in **FIG. 2** may be performed using the 3D modeling engine and a database. Although DecisionSpace® Geosciences may be used as an interface application, other interface applications may be used, instead, or the compartment geogrouping module may be used as a stand-alone application.

[00148] Although the computing unit is shown as having a generalized memory, the computing unit typically includes a variety of computer readable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. The computing system memory may include computer storage media in the form of volatile and/or nonvolatile memory such as a read only memory (ROM) and random access memory (RAM). A basic input/output system (BIOS), containing the basic routines that help to transfer information between elements within the computing unit, such as during start-up, is typically stored in ROM. The RAM typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by the processing unit. By way of example, and not limitation, the computing unit includes an operating system, application programs, other program modules, and program data.

[00149] The components shown in the memory may also be included in other removable/non-removable, volatile/nonvolatile computer storage media or they may be

implemented in the computing unit through an application program interface (“API”) or cloud computing, which may reside on a separate computing unit connected through a computer system or network. For example only, a hard disk drive may read from or write to non-removable, nonvolatile magnetic media, a magnetic disk drive may read from or write to a removable, nonvolatile magnetic disk, and an optical disk drive may read from or write to a removable, nonvolatile optical disk such as a CD ROM or other optical media. Other removable/non-removable, volatile/nonvolatile computer storage media that can be used in the exemplary operating environment may include, but are not limited to, magnetic tape cassettes, flash memory cards, digital versatile disks, digital video tape, solid state RAM, solid state ROM, and the like. The drives and their associated computer storage media discussed above provide storage of computer readable instructions, data structures, program modules and other data for the computing unit.

[00150] A client may enter commands and information into the computing unit through the client interface, which may be input devices such as a keyboard and pointing device, commonly referred to as a mouse, trackball or touch pad. Input devices may include a microphone, joystick, satellite dish, scanner, voice recognition or gesture recognition, or the like. These and other input devices are often connected to the processing unit through the client interface that is coupled to a system bus, but may be connected by other interface and bus structures, such as a parallel port or a universal serial bus (USB).

[00151] A monitor or other type of display device may be connected to the system bus via an interface, such as a video interface. A graphical user interface (“GUI”) may also be used with the video interface to receive instructions from the client interface and transmit instructions to the processing unit. In addition to the monitor, computers may also include other peripheral

output devices such as speakers and printer, which may be connected through an output peripheral interface.

[00152] Although many other internal components of the computing unit are not shown, those of ordinary skill in the art will appreciate that such components and their interconnection are well known.

[00153] While the present disclosure has been described in connection with presently preferred embodiments, it will be understood by those skilled in the art that it is not intended to limit the disclosure to those embodiments. It is therefore, contemplated that various alternative embodiments and modifications may be made to the disclosed embodiments without departing from the spirit and scope of the disclosure defined by the appended claims and equivalents thereof.

CLAIMS

1. A method for generating a custom reservoir from multiple compartments representing one or more geological structures, which comprises:

selecting two or more compartments from the multiple compartments;

selecting one of union, intersect some and intersect all as a combination type; and

combining the two or more compartments based on the selected combination type into a combined compartment representing a custom reservoir using a computer processor, wherein union is a combination of the selected compartments, intersect some is a combination of a section of each selected compartment that intersects another selected compartment, and intersect all is a combination of only a section of each selected compartment that intersects each of the other selected compartments.

2. The method of claim 1, further comprising:

selecting intersect some as the combination type; and

combining each section of each selected compartment that intersects another selected compartment into the combined compartment.

3. The method of claim 1, further comprising:

selecting intersect all as the combination type; and

combining only a section of each selected compartment that intersects each of the other selected compartments into the combined compartment.

4. The method of claim 1, wherein the selected compartments represent different geological structures.

5. The method of claim 4, wherein the selected compartments represent at least one geoshell volume compartment and at least one stratigraphic layer compartment.

6. The method of claim 4, wherein the selected compartments represent at least one fault block compartment and at least one fluid layer compartment.

7. The method of claim 1, further comprising:

selecting union as the combination type; and

combining each selected compartment into the combined compartment.

8. A non-transitory program carrier device tangibly carrying computer-executable instructions for generating a custom reservoir from multiple compartments representing one or more geological structures, the instructions being executable to implement:

selecting two or more compartments from the multiple compartments;

selecting one of union, intersect some and intersect all as a combination type; and

combining the two or more compartments based on the selected combination type into a combined compartment representing a custom reservoir, wherein union is a combination of the selected compartments, intersect some is a combination of a section of each selected compartment that intersects another selected compartment, and intersect all

is a combination of only a section of each selected compartment that intersects each of the other selected compartments.

9. The program carrier device of claim 8, further comprising:

selecting intersect some as the combination type; and

combining each section of each selected compartment that intersects another selected compartment into the combined compartment.

10. The program carrier device of claim 8, further comprising:

selecting intersect all as the combination type; and

combining only a section of each selected compartment that intersects each of the other selected compartments into the combined compartment.

11. The program carrier device of claim 8, wherein the selected compartments represent different geological structures.

12. The program carrier device of claim 11, wherein the selected compartments represent at least one geoshell volume compartment and at least one stratigraphic layer compartment.

13. The program carrier device of claim 11, wherein the selected compartments represent at least one fault block compartment and at least one fluid layer compartment.

14. The program carrier device of claim 8, further comprising:

selecting union as the combination type; and

combining each selected compartment into the combined compartment.

15. A non-transitory program carrier device tangibly carrying computer-executable instructions for generating a custom reservoir from multiple compartments representing one or more geological structures, the instructions being executable to implement:

selecting two or more compartments from the multiple compartments;

selecting intersect some as a combination type; and

combining the two or more compartments based on the selected combination type into a combined compartment representing a custom reservoir, wherein intersect some is a combination of a section of each selected compartment that intersects another selected compartment.

16. The program carrier device of claim 15, further comprising:

selecting intersect all as the combination type, wherein intersect all is a combination of only a section of each selected compartment that intersects each of the other selected compartments; and

combining only a section of each selected compartment that intersects each of the other selected compartments into the combined compartment.

17. The program carrier device of claim 15, wherein the selected compartments represent different geological structures.

18. The program carrier device of claim 17, wherein the selected compartments represent at least one geoshell volume compartment and at least one stratigraphic layer compartment.

19. The program carrier device of claim 17, wherein the selected compartments represent at least one fault block compartment and at least one fluid layer compartment.

20. The program carrier device of claim 15, further comprising:

selecting union as the combination type, wherein union is a combination of the selected compartments; and

combining each selected compartment into the combined compartment.