



CARD PROCESSING DEVICE

Field of the Invention

This invention is directed to a card processing device including a reader and writer for data on magnetic cards.

5

Background of the Invention

To accurately process data on a card (i.e. to read and write magnetically encoded data on the card) while that card is being conveyed along a course, one must produce clock signals to serve as a reference for the timing of processing operations based on the displacement of the card as it is conveyed.

Existing card processing devices have an encoder provided either on the rotating shaft of the motor which generates the force to convey the card, or on a rotating member of the mechanism which transmits the motor's rotation to the card. The motor is controlled for constant velocity based on pulse signals outputted by this encoder. These signals are also used as clock signals for the reading and writing of data.

An existing card processing device is pictured in Fig. 21. This device has three sets of paired conveyor rollers 201(a-c). The route the card follows is located between these pairs of rollers. Magnetic head 202, which is mounted on the shaft of the central pair of rollers 201a processes the data on the card. During data processing, conveyance force is applied to the card only by rollers 201a, as it is crucial to prevent changes in the speed of the card that might occur as forward rollers 201b stop supplying conveying force and rear rollers 201c begin supply conveying force.

Existing card processing devices do not detect the



displacement of the card along the route of conveyance in a way which is directly dependent on the movement of the card. The dimensional accuracy of the gears, cogged belts and pulleys constituting the transmission mechanism have an effect on the detection signal produced by the encoder, as would the stretching or slipping of the belts over time. The linear relationship between the rotational velocity of the encoder and the velocity at which a card is conveyed can be affected, and the device would no longer be able to generate a clock signal in good enough conformity with the true displacement of the card to allow it to serve as a reference to perform processing.

Because the existing card processing devices have three sets of rollers, their construction tends to be complicated, and such devices cannot easily be made smaller, nor can their cost be reduced.

Summary of the Invention

An object of the present invention is to provide an improved card processing device including a reader and write for magnetic cards.

Another object of the present invention is to provide a card processing device that is more accurate and simple in construction by providing means to detect a reference signal for processing data on a card in a way which is directly dependent on the movement of the card being conveyed.

A further object of the present invention is to provide a card processing device which can process data on the card according to the true relative displacement of the card and the processor, even when the relative speeds of the card and the processor may vary.

An even further object of the present invention is to provide a card processing device in which the card is conveyed and the data can be processed according to the true displacement of the card with respect to the processor.



Another further object of the present invention is to provide a card processing device in which the data on the card can be processed accurately even if the card reverses its direction while it is being conveyed.

5 Another object of the present invention is to provide a card processing device in which the data on the card can be processed according to the true relative displacement of the card and the data reader, even though the relative speeds of the card and the reader may vary.

10 A further object of the present invention is to provide a conveyor-type card processing device in which the data can be read off the card according to the true displacement of the card with respect to the data reader.

An even further object of the present invention is to
15 provide a card processing device in which the data can be read off the card accurately even if the card reverses its direction while it is being conveyed.

Another object of the present invention is to provide a card processing device in which non-uniformity in the
20 rotation of the mechanism which transmits the drive force for the conveyance of the card can be minimized.

A further object of the present invention is to provide a card processing device in which the route along which the card is conveyed has fewer rollers providing a
25 design that simplifies the device and reduces its cost.

An even further object of the present invention is to provide a card processing device in which a card which has been deformed by excessive conveying force can be conveyed normally.

30 Another object of the present invention is to provide a card processing device in which the conveyor rollers can apply considerable force to the card, and the structure of the conveyor can be simplified and designed to assure that conveying force is supplied in a stable manner.

35 A further object of the present invention is to provide a card processing device in which displacement can



be detected normally even if a card is substantially deformed.

5 An even further object of the present invention is to provide a card processing device such that even before a card has passed the detector device, that device outputs a signal which is matched to the rotation of the drive source.

10 Another object of the present invention is to eliminate a separate detector device used to control the drive source in the prior art devices to reduce both the size of the card processor and its cost.

15 A further object of the present invention is to provide a card processing device in which a detection signal employed in processing is used in place of a separate control signal for the image reader which reads images off the surface of the card, thus allowing the elimination of the detection device dedicated to the image reader to reduce both the size of the card processor and its cost.

20 An even further object of the present invention is to provide a card processing device in which the existing drive source can be used when it is mounted in a device with a drive mechanism which is also used for other functions to reduce both the size of the card processor and its cost.

25 Another object of the present invention is to provide a card processing device in which the processor moves relative to the card to allow the data on the card to be processed according to the true displacement of the processor.

30 A further object of the present invention is to provide a card processing device in which a lead screw is used both to guide the movement of the processor and to transmit the drive force to allow the size of the card processor to be reduced.

35 An even further object of the present invention is to



provide a card processing device in which the displacement of the processor is detected accurately by a simple structure.

5 Another object of the present invention is to provide a card processing device in which the data reader moves relative to the card to allow the data to be read in perfect conformity to the displacement of the data reader.

10 A further object of the present invention is to provide a card processing device in which a lead screw is used both to guide the movement of the data reader and to transmit the drive force to allow the size of the card processor to be reduced.

15 An even further object of the present invention is to provide a card processing device in which the displacement of the data reader is detected accurately by a simple structure.

20 Another object of the present invention is to provide a card processing device in which the inertial moment is minimized with respect to the detector rollers to improve the accuracy of detection and allow the size of the card processor to be reduced.

25 The present invention is directed to a card processing device with a processor which moves along with the card and processes data on that card as it is moving. This device is distinguished by the fact that it has a detection device which detects the displacement of the processor relative to the aforesaid card in a way which is directly dependent on the movement of either the card or the processor, and a converter device which converts the signal from the
30 detection device to a reference signal for the processing of the aforesaid data.

35 The card processing device includes a conveyor device providing a route along which the card is conveyed for defining the processor. The detection device detects the displacement of the card in a way which is directly dependent on the movement of that card.



The card processing device detects the displacement of the card, and also detects the direction in which the card is moving. This card processing device also includes a device to stop the processing. If the detection device
5 detects that the direction of the card's movement has been reversed, this device stops the processing of the data on the card.

The card processing device includes a data reader, which moves along with the card and reads the data written
10 on the card as it is conveyed along its path. This device is distinguished by the fact that it has a device which detects the displacement of the data reader relative to the card in a way which is directly dependent on the movement of either the card or the data reader; and a device which
15 corrects the data read by the data reader based on signals from the detector device.

The conveyor device defines a route along which the card is conveyed relative to the aforesaid data reader, and the detector device detects the displacement of the card in
20 a way which is directly dependent on the movement of that card.

The detector device detects both the displacement of the card and the direction in which the card is moving, and includes a device to stop the reading of data. If the
25 detector device detects that the direction of the card's movement has been reversed, this device stops the processor from reading the data on the card.

In the detector device, a portion of the mechanism transmitting drive power to the conveyor device defining
30 the conveyor route includes worm gears.

The conveyor device is constructed of two pairs of rollers with one or both pairs of rollers supplied with drive power. The space between the two pairs of rollers is shorter than the route along which the card is conveyed.

35 The two pairs of rollers which define the conveyor device are positioned in such a way that they face both the



processor and the portion of the card on which data is recorded.

5 The upper and lower rollers defining the two pairs of rollers exert elastic force radially. These rollers oppose one another above and below the route of the card, and are separated by a space whose vertical dimension is less than the thickness of the card. Drive force is supplied to both of these pairs of rollers.

10 The detector device includes rollers whose peripheral surfaces come in contact with the card. These rollers which are components of the detector device are positioned above and below the route of the card so as to squeeze the card between them. This detector device has a roller to propel the card forward which is supplied with drive force
15 from the same drive source as are the conveyor rollers which constitute the route along which the card is conveyed. It also has an elastic member which supplies force to the pressure roller in the direction which will cause it to make contact with the detector roller, and a
20 stop to constrain the movement of the pressure roller to within a specified range as it is displaced away from the detector roller.

The signal from the device which detects the displacement of the card is used as a reference signal to
25 control the drive source.

The card processing device includes an image reader which reads images off the surface of the card. The signal from the detector device is used as a reference signal to control the image reader.

30 The card processing device includes an input power transmission device to accept the supply of drive force from the exterior of the device to convey the card on the route.

35 The card processing device includes a device which moves the processor with respect to the card. The detector device detects the displacement of the processor directly



based on its current position.

The device to move the processor includes a female screw fixed to the processor and a male screw of a length which at least surpasses that of the range of movement of the processor, and which by engaging with the female screw supplies rotary force to it.

The device for detecting the displacement of the processor includes an array of elements to be detected, which is formed in the space traversed by the processor and a detector element, which is fixed to the processor, and which outputs a detection signal at the moment the position of the processor corresponds to that of each element to be detected.

The carding processing device includes a device which moves the data reader with respect to the card, and the detector device detects the displacement of the data reader directly based on its current position.

The device to move the data reader includes a lead screw mechanism with a female screw fixed to the data reader and a male screw of a length which at least surpasses that of the range of movement of the data reader, and which by engaging with the female screw supplies rotary force to it.

The device to move the data reader includes elements to be detected, which are provided at equal intervals along the path traversed by the data reader, and a detector element which is fixed to the data reader, which outputs a detection signal at the moment the position of the data reader corresponds to that of each element to be detected.

The device to move the data reader includes an input power transmission device to accept the supply of drive force from the exterior of the device to move the processor or the data reader.

The device to detect the displacement of the card includes elements, which generate signals related to displacement. These elements includes features for detec-



tion, which are provided at regular intervals on the peripheral surface, coaxial with the detector roller.


The features to be detected in the element to generate signals related to displacement are defined by reflective surfaces or non-reflective surfaces. Luminous elements and photodetector elements are provided on the peripheral surface of the element to generate signals related to displacement. These elements are oriented so that their angles of incidence and reflection are identical. The non-reflective surfaces can be defined by slits.

The features to be detected by the element to generate signals related to displacement are defined by two different colors of reflected light.

In the card processing device, relative movement is detected in a way which is directly dependent on the movement of the card or processor as they move relative to each other. The detection signal outputted by the detector is converted by the converter device to a reference signal to be used in processing the data on the card. Thus the reference signal for processing is created directly based on the movement of the card. Such a signal is not affected by the accuracy of the transmission mechanism or its operating condition.

The displacement of the card is detected in a way which is directly dependent on the movement of the card while it is being conveyed, and the detection signal outputted by the detector is converted by the converter device to a reference signal to be used in processing the data on the card. Thus, the reference signal for processing is created directly based on the movement of the card. Such a signal is not affected by the accuracy of the transmission mechanism or its operating condition.

The processing of the data on the card is stopped by a device for that purpose if the detector device detects the fact that the card has reversed its direction of travel. This scheme prevents data from being overwritten.



during the write-in process in a region of the card which already has data written on it. It insures that data will be written in properly.


5 The relative displacement is detected in a way which is directly dependent on the movement of the card or data reader, which are moving relative to one another. Thus, even if the speed of the card varies, the data read from the card can easily be corrected to usable data.

10 The displacement of the card is detected in a way which is directly dependent on the movement of that card as it is being conveyed, and the detection signal output by the detector is converted by the converter device to a reference signal which can be used in processing the data. Since the reference signal used to correct the data which
15 have been read is based directly on the movement of the card, it will not be affected by the accuracy of the transmission mechanism or its operating condition.

The data which have been read off the card is erased by a device for that purpose if the card reverses its
20 direction while data is being read. This scheme allows the accuracy of data-reading to be maintained even if the direction of the card is reversed by a faulty conveyor.

The drive force is supplied to the conveyor device defining course along which the card is conveyed through a
25 transmission mechanism which includes a worm gear. Generally, the reduction ratio of the worm and worm toothed wheel in a worm gear is substantially greater than that of a combination of flat gears. The rotational velocity output by a worm toothed wheel varies by 5 to 10%. This
30 degree of speed variation can be corrected by signal processing performed by the converter or correction device.

The course along which the card is conveyed consists of two sets of paired rollers. Data processing is performed on the card while it is between these two sets of
35 rollers. This scheme obviates the need for a separate set of rollers to convey the card independently during



processing, thus reducing the number of rollers needed.

The width of the conveyor rollers is made to be identical to that of the portion of the card used to store data and the rollers can supply substantial conveying force to the card. With this scheme, even deformed cards will not get hung up on the conveyor course. No rotational force will be transmitted onto the surface of the card, and the data on the card will be processed accurately.

Substantial pressure is exerted on the card by the elastic force of the peripheral surfaces of the conveyor rollers. Because drive force is supplied to both the upper and lower rollers, the force by which the card is conveyed is quite large. There is thus no need for elastic members or mechanisms such as levers to augment the force of the conveyor rollers in the direction in which they make contact with the card.

The pressure roller comes in contact with the detector roller which detects the displacement of the card even before a card has gone past the detector roller. Drive force is supplied to this pressure roller by the same drive source as serves the conveyor rollers. Thus, the detector roller detects the rotation of the drive source through the pressure roller even before a card has passed as far as the detector roller.

The detection signal output by the detection roller is used as a reference signal to control the drive source. This obviates the need for a device to generate a separate reference signal for the drive source.

The conveying force supplied from the exterior can be received through an input power transmission device, thus obviating the need for a built-in drive source.

The displacement of the card is detected directly by the processor as it moves with respect to the card, and the detection signal output by the detector is converted by the converter device to a reference signal which can be used in processing the data. Since the reference signal used to



process the data on the card is based directly on the movement of the processor, it will not be affected by the accuracy of the transmission mechanism or its operating condition.

5 The drive force is furnished to the processor by a lead gear mechanism which also guides the movement of the processor. Thus, two separate components need not be furnished to serve the functions of guiding the processor and transmitting drive force to it.

0 The device to detect the displacement of the processor includes a detector element which is fixed to the processor and elements to be detected, which are furnished along the course travelled by the processor. In this way the displacement of the processor can be detected accurately by
15 a simple structure.

 The displacement of the card is detected directly by the data reader, which is moving with respect to the card, and the data which is read off the card is corrected by an error correction device with the help of the detection
20 signal outputted by the detector. With this scheme, correction of the data which has been read is based on the movement of the data reader, so it is not affected by the accuracy of the transmission mechanism or its operating condition.

25 The drive force is furnished to the data reader by a lead gear mechanism which also guides its movement. Thus, two separate components need not be furnished to serve the functions of guiding the data reader and transmitting drive force to it.

30 The device to detect the displacement of the data reader includes a detector element which is fixed to the data reader and an array of elements to be detected, which are furnished along
the course travelled by the processor. In this way the
35 displacement of the data reader can be detected accurately by a simple structure.



The conveying force supplied from the exterior for the processor or data reader can be received through an input power transmission device, thus obviating the need for a built-in drive source.

5 There is no need to have an encoder coaxial with, but spatially removed from the detector roller. The moment of inertia of the detector roller is kept small and any variation of the speed of the detector roller can be minimized resulting in improved accuracy of detection. The
10 features to be detected are simple to produce.

Brief Description of the Drawings

Fig. 1 is a lateral cross-sectional and plan view of the essential components of a card processing device which is one preferred embodiment of this invention.

15 Fig. 2 is a lateral view of the encoder in the card processing device and a view showing how the slits are arranged.

Fig. 3 is a block diagram of the control unit for the card processing device.

20 Fig. 4 is a flow chart of processes occurring in the control unit of the card processing device described above during the write-in operation.

Fig. 5 shows a timing chart for input and output signals for the same control unit during the write-in operation and a diagram of how the slits function during movement detection.

Fig. 6 is a flow chart of the processing performed in the card processing device during the read-out operation.

Fig. 7 is a timing chart for input and output signals
30 for the same control unit during the read-out operation.

Fig. 8 is a timing chart showing the status of the signal processing during correction of read-out data in a card processing device which is another preferred embodiment of this invention.




Fig. 9 is a timing chart for the process used by the control unit of the same card processing device to erase data read off the card.

5 Fig. 10 shows a timing chart giving the status of each signal when data is being erased and a diagram of how the slits function during movement detection.

0 Fig. 11 is a detailed view of a data processing device which is one preferred embodiment of this invention as seen from the rear, from overhead, from the front, and from the right side.

Fig. 12 are plan views showing how a card is conveyed in that same card processing device and in an existing device.

5 Fig. 13 are lateral views showing how a card is conveyed in that same card processing device and in an existing device.

Fig. 14 shows the compressive force applied to the card by the pressure roller in the same card processing device.

0 Fig. 15 is a detailed plan view showing the configuration of a preferred embodiment of a card processing device which is a preferred embodiment of the invention.

5 Fig. 16 shows essential aspects of the configuration of the host device in which that same card processing device is housed.

Fig. 17 is a plan view of the main components of a card processing device which is a preferred embodiment of the invention.

10 Fig. 18 is a plan view showing the essential configuration of a card processing device which is a preferred embodiment of the invention.

15 Fig. 19 is a plan view showing the essential configuration of a card processing device which is a preferred embodiment of the invention.

Fig. 20 shows how the sensor which detects the card is



mounted in the card processing device which embodies this invention.

Fig. 21 is a lateral cross-sectional view of an existing card processing device.


5 Detailed Description of Preferred Embodiments

Fig. 1 shows a lateral cross-sectional and a plan view of the essential components of a card processing device which is a preferred embodiment of this invention.

Card 1 is conveyed in the direction indicated by arrow
10 A on the conveyor course including drive rollers 3a and 3b and their corresponding driven rollers, 4a and 4b. Detector roller 6 and pressure roller 7 oppose each other on conveyor course 2 between the locations in which drive rollers 3a and 3b are installed. The rotation of drive
15 rollers 3a and 3b conveys card 1 from a position between drive roller 3a and driven roller 4a to a position between pressure roller 7 and detector roller 6, and then to a position between drive roller 3b and driven roller 4b. Rotational force is transmitted to drive rollers 3a and 3b
20 from a motor (not pictured) by way of a power transmission mechanism.

Reading head 11 and writing head 12 are positioned on conveyor course 2 so that they are facing magnetic strip 1a on card 1. Magnetically encoded data are read from or
25 written onto the card by reading head 11 and writing head 12 via magnetic strip 1a. Encoder 5 is fixed onto the shaft of detector roller 6 so that it rotates along with detector roller 6. Detector roller 6 comes in contact with the bottom of card 1 as it moves along conveyor course 2,
30 and is rotated by the movement of card 1 along course 2. Encoder 5, which is fixed to the shaft of roller 6, is therefore also rotated by the movement of card 1.

Fig. 2 shows a lateral view of the encoder in the aforesaid card processing device and an enlargement of the
35 rows of slits in that encoder. Rows of concentric slits 5a



and 5b are formed at regular intervals near the perimeter of disk-shaped encoder 5. The slits in rows 5a and 5b are all of virtually the same width, and the spaces between them are of the same width as the slits. Photointerrupters S_1 and S_2 face rows 5a and 5b, respectively. Each photointerrupter is activated when a slit in the corresponding row is apposed to it. The slits in inner row 5b face photointerrupter S_2 half a pitch later than the slits in inner (sic) row 5a face photointerrupter S_1 .

With the configuration described above, a card 1 which is inserted into course 2 will be conveyed along that course in direction A by the rotation of drive rollers 3a and 3b. The movement of card 1 will cause detector roller 6, which comes in contact with the bottom of the card to rotate as well, and encoder 5, which is mounted on the same shaft as roller 6 will rotate with it. The rotation of encoder 5 will be detected by photointerrupters S_1 and S_2 , thus the displacement of card 1 is detected.

Fig. 3 is a block diagram of the control unit for the card processing device described above. In this control unit, reading head 11, writing head 12, photointerrupters S_1 and S_2 and motor driver 29 are connected to CPU 21, which has a ROM 22 and a RAM 23 via interfaces 24 through 27. The program which defines the operation of CPU 21 is prewritten into ROM 22. CPU 21 controls all input and output devices according to this program. Data to be input or output are stored in a specified memory area in RAM 23.

The magnetically encoded data which reading head 11 has read off magnetic stripe 1a on card 1 are inputted into CPU 21. CPU 21 stores the magnetically encoded data in RAM 23. CPU 21 supplies the data which is to be written onto card 1 to writing head 12 via interface 25. The data detected by photointerrupters S_1 and S_2 are inputted into CPU 21 by interfaces 26 and 27. CPU 21 detects the insertion of card 1 into course 2 by means of a sensor (not pictured), and it outputs drive data for motor M to motor



driver 29 through interface circuit 28.

CPU 21 supplies the detection signal from photointerrupter S_1 to writing head 12 as a clock signal for the writing of data. When data is to be written onto card 1, CPU 21 outputs previously stored data into writing head 12, and head 12 writes the data onto card 1 using the detection signal from photointerrupter S_1 as a clock signal. When data recorded on card 1 is to be read, CPU 21 supplies a read-out signal to reading head 11. This signal is derived from the detection signal from photointerrupter S_1 .

Fig. 4 is a flow chart of processes occurring in the control unit of the card processing device described above during the write-in operation. To begin the write-in process, CPU 21 outputs to writing head 12 the write-in data which it has organized (n1). It waits for photointerrupters S_1 and S_2 to go on one after the other. The signal from photointerrupter S_2 is supplied to writing head 12 as a clock signal (n2 to n4). In this way writing head 12 begins to write data onto card 1.

Whenever the transport of card 1 is interrupted (n5 to n7), CPU 21 renders a judgment as to whether photointerrupter S_1 is activated while photointerrupter S_2 is off. If card 1 has completed its travel, this fact can be ascertained either from the detection signals from photointerrupters S_1 and S_2 indicating that the rotation of encoder 5 has stopped, or from a detection signal from a sensor (not pictured) mounted at the end of course 2.

If photointerrupter S_1 is on when photointerrupter S_2 is off, CPU 21 will conclude that there is something wrong with the way card 1 is being transported, and it will output a WRITE-IN PROHIBITED signal to writing head 12 (n5 and n6 → n8). This causes head 12 to suspend the writing of data on card 1. CPU 21 continues to output this WRITE-IN PROHIBITED signal until photointerrupter S_2 is on at the same time that photointerrupter S_1 is on (n9 to n11). The aforesaid processing of steps n5 and n6 → n8 corresponds to



the device to stop the processing which is a part of this invention.

As is shown in Fig. 5 (A), as long as card 1 is being conveyed normally along course 2 during write-in, output pulses from photointerrupter S_1 are supplied to writing head 12 as a clock signal for writing data.

If during the write-in process card 1 temporarily reverses its direction on course 2 due to a faulty conveyor, as shown by the dotted line in Figure 5 (B), the detection pulse from photointerrupter S_1 will still be high when that from photointerrupter S_2 is falling. The processes in steps $n5$ and $n6 \rightarrow n8$ discussed above will cause a WRITE-IN PROHIBITED signal to be output. This signal will be output continuously until the output signal from photointerrupter S_2 rises at a time when that from photointerrupter S_1 is already high. In this way, the fact that card 1 has reversed its direction can be detected based on the output pulses from photointerrupters S_1 and S_2 . Since the operation of writing head 12 is interrupted under these circumstances, data is prevented from being overwritten on the portion of magnetic strip 1a where data have already been written in the normal fashion.

Fig. 6 is a flow chart of the processing performed in the aforesaid card processing device during the read-out operation. To read data, CPU 21 supplies output pulses from photointerrupter S_1 to reading head 11 as a clock signal by which to read out data (n 21). CPU 21 stores both the data read out by reading head 11 and the output pulses from photointerrupter S_2 in RAM 23 (n22 and n23). When card 1 reaches the end of the course and the read-out of data is completed (n 24), correction pulses are created based on the read-out data and the output pulses from photointerrupter S_2 which were stored in RAM 23 (n 25), and the read-out data are corrected (n 26).

If, for example, as is shown in Fig. 7, the speed of card 1 on course 2 varies, the status of the card's



ment will be stored in RAM 23 in the form of the output as from photointerrupter S_2 . The data which have been using the output pulses from photointerrupter S_1 as a clock signal will likewise be stored in RAM 23. For both on and the off times of the read-out data, CPU 21 obtains the ratio of times before and after, with respect to the corresponding on or off transitions of the output pulse, before and after correction at $t_a : t_b = T_a : T_b$. The output pulse and the read-out data are corrected so that the on and off periods of the output pulse from photointerrupter S_2 all have fixed duration T_0 . In this way data read by head 11 can easily be corrected to read-out data with normal timing relationships which would have been obtained had card 1 travelled at a steady speed.

As is shown in Fig. 8, the slope of the speed during photointerrupter S_2 's on and off periods is obtained from the lengths t_1 and t_2 of the previous and subsequent periods. The quantities of data D_1 and D_2 collected before the rise point and after the fall point of the read-out data in this period are obtained by calculating the areas. The length of each of photointerrupter S_2 's on or off period is made to be of a fixed duration T_0 . These periods are divided by the ratio of the aforesaid quantities of data D_1 and D_2 ($D_1 : D_2 = T_1 : T_2$) to yield the rise and fall points of the corrected read-out data. Treating the read-out data in this way by matching the state of card 1's travel yields a highly accurate correction.

Fig. 9 is a timing chart for the process used in the aforesaid card processing device to erase data read off the card after it has reversed its direction during read-out. CPU 21 stores all the data written on card 1 in RAM 23. It then compares the output pulses from photointerrupters S_1 and S_2 , which are likewise stored in RAM 23 (n 31). In this comparison, it checks all data as to whether photointerrupter S_1 was on at the rise time of the output pulse from photointerrupter S_2 .



If there occurred an incident such that photointerrupter S_1 was on when the output pulse from photointerrupter S_2 began to rise, the point at which the output pulse from photointerrupter S_2 began to rise will be stored as the starting point E_1 from which the read-out data should be erased (n 34). The next time at which the pulse from photointerrupter S_2 rises, while photointerrupter S_1 is on will be stored as the ending point E_2 for the erasing of the data (n 35). Thus, the data read out between the stored starting and ending points E_1 and E_2 will be erased (n 36). Steps n 32 and n 34 through n 36 correspond to the device to erase data which is a part of this invention.

If card 1 changes direction on course 2 while data is being read, encoder 5 reverses its direction of rotation as shown by the dotted line in Fig. 10 (B). In the erasure process described earlier, CPU 21 erases the portion of the data read by head 11 which has been overwritten. Thus, the data will be read off the card accurately at all times regardless of the direction of travel of card 1.

Figs. 11 (A) through (D) are views showing the configuration of a data processing device which is a preferred embodiment of this invention from the rear, top, front and right sides. Card processing device 30 includes a front frame 47 and rear frame 48 and paired conveyor rollers 34 and 35 and 44 and 45, which are pivotally supported between frames 47 and 48. The two sets of rollers 34, 35 and 44, 45, constitute the course on which card 51 is conveyed. The space between rollers 34-35 and 44-45 is not as long as the entire path of card 51's travel. Magnetic head 38, which reads and writes data on the card, is installed in this space.

This configuration obviates the need for separate rollers which would convey card 51 only while its data is being processed by magnetic head 38. Simplifying the design of the device allows it to be reduced both in size and cost.




The rotation of motor 31 is transmitted to conveyor rollers 34, 35, 44 and 45 through timing pulleys 49 and cogged belts 50. Worm 32 is mounted on the rotating shaft of motor 31. Rotation is transmitted to timing pulley 49 through worm toothed wheel 33, which engages with worm 32.

This configuration allows any variations of the rotational velocity of motor 31, which is transmitted to timing pulley 49 to be minimized, which in turn minimizes nonuniformity in the rotation of conveyor rollers 34, 35, 44 and 45.

Conveyor rollers 34 and 44 and magnetic head 38 are positioned so as to make contact with the magnetic strip on card 51. In other words, rollers 34 and 44 and head 38 are arrayed in a straight line along the path traversed by card 51.

With this configuration, conveyor rollers 34, 35, 44 and 44 are the same width as the magnetic strip on card 51. Sufficient conveying force is used to insure that the card cannot move to a position where the embossed portion of card 51 can come in contact with the rollers, as shown in Fig. 12 (A). Thus, even a mutilated card 51 like the one shown in Fig. 12 (B) will be conveyed normally. This arrangement prevents a problem which occurred with previous card processing devices, namely that frictional resistance would sometimes cause a card to rotate horizontally when it is in contact with magnetic head 38 with the result that the magnetic strip moved away from the head.

Conveyor rollers 34, 35, 44 and 45 are rubber rollers which are composed of a material which gives them substantial elastic force in a radial direction. When card 51 is not between them, upper rollers 34 and 44 are in contact with lower rollers 35 and 45, respectively. When card 51 is being conveyed, the perimeter surfaces of rollers 34, 35, 44 and 45 are elastically deformed in a radial direction by the portion of card 51 with which they are in contact.



It is known that generally speaking, the lower the hardness of an elastic substance, the greater the coefficient of friction will be. It is also known that when pressure is exerted on contacting rollers by springs or other elastic components, the greater the pressure, the larger will be the deviation in rotational position between the rollers.

In this embodiment, conveyor rollers 34, 35, 44 and 45 are sufficiently elastic along their radial directions that substantial conveying force is conferred to card 51, so that there is no need for additional components to exert pressure on the upper and lower rollers. This scheme minimizes deviations in rotational position between rollers. Since it simplifies the configuration of the device, it reduces both its size and its cost.

Detector roller 37 and pressure roller 39 are mounted in the same location as magnetic head 38 along the path of card 51. Detector roller 37 and pressure roller 38 come in contact with the front and the back of card 51, respectively. An optical chopper including two photointerrupters and encoder 46 is mounted on the same shaft as detector roller 37. The photointerrupters detect the slits which are provided at regular intervals on the encoder wheel, which rotates along with detector roller 37.

Pressure roller 39 is pivotally supported at one end of lever 40, which is anchored at its midpoint in such a way that it can swing back and forth. Rotational force which is identical to that of conveyor roller 35 is supplied to roller 39 through belt 36. On the other end of lever 40 is spring 41, which exerts elastic force downward, causing pressure roller 39 to come in contact with detector roller 37. Stop 42 comes in contact with the top of the same end of lever 40. This scheme limits the travel of pressure roller 39 away from detector roller 37 to within a specified range.

With this configuration, as shown in Fig. 13 (A), the



elastic force of spring 41 transmitted through pressure roller 39 causes card 51 to exert pressure on detector roller 37. The displacement of card 51 can then be detected by roller 37.

It is conceivable that a card 51 which was bent excessively, as shown in Fig. 13 (B), would resist the elastic force of spring 41 and push pressure roller 39 downward so that detector roller 37 did not make contact with card 51. If in anticipation of this circumstance the elastic force of spring 41 were augmented somewhat, the mechanical components such as lever 40 would also have to be upgraded sufficiently to counterbalance the force of the spring, and the size of the device might have to be increased.

The use of stop 42 limits the downward movement of pressure roller 39, which cannot move downward beyond its specified range even if a substantially bent card 51 is being conveyed through the processing device. Thus, detector roller 37 will under all circumstances make contact with card 51. As is shown in Fig. 14, if the degree of deformation of card 51 is such that lever 40 does not come in contact with stop 42, the elastic force of spring 41 will press card 51 against detector roller 37. If card 51 is so deformed that lever 40 comes in contact with stop 42, the combination of the elastic force exerted by spring 41 and elastic force exerted radially by pressure roller 39 will press card 51 against detector roller 37.

Since this scheme does not require that spring 41 have a very substantial elastic force, the structural components on the periphery of pressure roller 39 can be small.

Even when no card is being conveyed, pressure roller 39 remains in contact with detector roller 37. Since the rotation of motor 31 is transmitted to pressure roller 39, detector roller 37 will detect that rotation when no card is being conveyed. Thus, the detection signal from encoder 46, which is mounted on the same shaft as detector roller 37 can be applied to control the drive of motor 31. With



this scheme, there is no need for a separate device to detect the rotation of motor 31.

As is shown in Fig. 11, card processing device 30 may have an image reader 43 to read images off the surface of card 51. In this case, the detection signal from encoder 46 can be used as a reference clock signal to control image reader 43.

Fig. 15 is a plan view showing the configuration of a preferred embodiment of a card processing device suitable to be built into a host device. In place of motor 31, which was pictured in Fig. 11, this device has power transmission unit 61, which consists of a pulley or gear coaxial with timing pulley 49. Power transmission unit 61 transmits the rotation of the motor in the host device to the interior of card processing device 30, which is an ATM or the like. In this case signal processing unit 62 in card processing device 30 is connected to the control unit in the host device through an interface (not pictured). Data is read off or written onto the card via magnetic head 38.

Such a scheme is pictured in Fig. 16. ATM 71 supplies conveying force to card processing device 30 through motor 77, which is furnished to convey cards through imprinting unit 72 and issuing unit 73. The control of the processing can be simplified if it is performed by the control unit for ATM 71. This scheme obviates the need for a small DC motor whose only use is to drive card processing device 30. It thus enhances the service life of the device and simplifies maintenance inspections.

Fig. 17 is a plan view of the main components of a card processing device which is another preferred embodiment of this invention. Card processing device 80 has a magnetic head 84 which scans magnetic strip 52 on card 51. Magnetic head 84 engages with guide 81, which runs parallel to magnetic stripe 52. The rotation of motor 86 is transmitted through belt 85. Magnetic head 84, which



detects the magnetic strip on card 51, is provided with a photointerrupter 82 and encoding slit 83, which runs parallel to guide 81.

5 With this configuration, the displacement of magnetic head 84 with respect to card 51 can be detected by means of the output from photointerrupter 82. As shown in Fig. 18, a male screw thread is formed on guide 81, and a lead screw mechanism with a female screw which engages with this male screw is also furnished with guide 81. In this way the
10 lead screw serves both to guide the movement of the magnetic head and to transmit drive force to it, thus simplifying the configuration of the device.

When card processing device 80 is built into a host device such as an ATM, drive force may be transmitted to
15 magnetic head 84 by the motor in the host device.

Fig. 19 shows plan and frontal views of a card processing device which is a preferred embodiment of the invention. The card processing device 90 pictured in Fig. 19 has a tubular protruding drum 93 on the side of and
20 coaxial with detector roller 37, which is also pictured in the configuration shown in Fig. 11. The peripheral surface of protruding drum 93 is fashioned into a reflective surface, on which indentations 94 are provided at regular intervals. Facing these indentations 94 are luminous
25 element 100 and photodetector element 102, which are positioned so that their angles of incidence and reflection are identical. The light emitted by luminous element 100 passes through lens 95 and is reflected by the reflective surface of protruding drum 93. It then passes through lens
30 96 and strikes photodetector element 102. Thus, luminous element 100, photodetector element 102, and indentations 94 comprise the encoder which detects the rotation of detector roller 37.

Indentations 94, which constitute the encoder to
35 detect the rotation of detector roller 37, are provided on a portion of that same roller. This scheme provides a



reduced moment of inertia for detector roller 37 as compared with the scheme shown in Fig. 11, in which encoder 16 is coaxial with but physically removed from detector roller 37, and it allows roller 37 to rotate more easily. Since the encoder components can be placed within the boundaries of the course travelled by card 51, this scheme allows the size of the device to be reduced.

In place of indentations 94, slits may be provided at regular intervals on the peripheral surface of protruding drum 93, or strips of a dark color may be used to create the same effect.

In the card processing device there are sensors which indicate the card's progress or detect its position along the course. These sensors are generally composed of a luminous element and a photodetector element. As is shown in Fig. 20, luminous element 111 and photodetector element 112 are placed so that the optical axis between them is oblique with respect to the surface of the course. This arrangement increases the proportion of the light emitted by luminous element 111 which is reflected by the surface of card 51. Further, refraction within card 51 of any transmitted light shifts the optical axis. Therefore, the quantity of light emitted by element 111 and the detection level of element 112 need not be fine-tuned. Even a transparent card 51 can be detected accurately. With this arrangement, there will be no danger that card 51 will fail to be detected because wear and tear has reduced the quantity of light which element 111 emits or because of dust spots on element 112, and the service life of element 111 will be extended.

With the invention described above, the reference signals to time processing can be created directly based on the movement of the card. The processing of the card is simplified, and its accuracy is not dependent on the accuracy of the transmission mechanism or its operating



condition.

With the invention, the reference signal for processing can be created directly based on the movement of the card.

With the invention, the processing of the data on the card can be stopped by a device for that purpose if the detector device detects the fact that the card has reversed its direction of travel. This scheme prevents data from being overwritten during the write-in process in a region of the card which already has data written on it. It insures that data will be written in properly.

With the invention, even if the speed of the card varies, the data read from the card can easily be corrected to a usable condition.

With the invention, the reference signal used to correct the data which has been read is based directly on the movement of the card. Thus, it will not be affected by the accuracy of the transmission mechanism or its operating condition.

With the invention, the accuracy of data-reading can be maintained even if the direction of the card is reversed in the midst of its travel by a fault in the conveyor process.

With the invention, any variations in speed due to variations in the drive force transmitted to the conveyor device can be kept within a level which can be corrected by signal processing performed in the aforesaid converter device or correction device.

With the invention, there is no need for a separate set of rollers to convey the card independently during processing, thus reducing the number of rollers needed.

With the invention, even deformed cards will not get hung up within the conveyor course. No rotational force will be transmitted onto the surface of such cards, and the data on these cards can be processed accurately.

With the invention, substantial pressure can be



exerted on the card by the elastic force of the peripheral surfaces of the conveyor rollers. Drive force is supplied to both upper and lower rollers. There is no need for elastic members or mechanisms such as levers to augment the force of the conveyor rollers in the direction along which they make contact with the card.

With the invention, the detector roller can detect the rotation of the drive source even before a card has reached it.

With the invention, the detection signal output by the detector roller can be used as a reference signal to control the drive source. This obviates the need for a separate device to generate a reference signal for the drive source.

With the invention, the detection signal output by the detection roller can be used as a reference signal to control an image reader which reads images off the surface of the card. This obviates the need for a separate device to generate a reference signal for the image reader.

With the invention, conveying force supplied from the exterior can be received through an input power transmission device, thus obviating the need for a built-in drive source.

With the invention, the reference signal used to process the data on the card can be based directly on the movement of the processor, so its accuracy will not be dependent on the accuracy of the transmission mechanism or its operating condition. Card data can be processed easily and accurately.

With the invention, two separate components need not be furnished to serve the functions of guiding the processor and transmitting drive force to it. The scheme used simplifies the configuration of the device and allows it to be made smaller.

With the invention, the device to detect the displacement of the processor consists of a detector element which



is fixed to the processor, as well as an array of elements to be detected, which is furnished along the course travelled by the processor. In this way the displacement of the processor can be detected accurately by a simple structure.

With the invention, correction of the data which has been read is based on the movement of the data reader, so its accuracy is not affected by the accuracy of the transmission mechanism or its operating condition. Data can be read off the card easily and accurately.

With the invention, two separate components need not be furnished to serve the functions of guiding the data reader and transmitting drive force to it. This simplifies the configuration of the device and allows it to be made smaller.

With the invention, the displacement of the data reader can be detected accurately by a simple structure.

With the invention, conveying force supplied from the exterior of the processor or data reader can be received through an input power transmission device, thus obviating the need for a built-in drive source. This allows the device to be made smaller.

With the invention, there is no need to have an encoder coaxial with, but spatially removed from the detector roller. The moment of inertia of the detector roller can be kept small and the variability of the speed of the detector roller can be minimized, resulting in improved accuracy of detection.

With the invention, the features to be detected are simple to produce.

This device has a detector roller 6, which comes in contact with the bottom of card 1 as it is conveyed along course 2 by drive rollers 3a and 3b, and an encoder 5, which is mounted on the shaft of detector roller 6. It also has two photointerrupters which detect the rows of slits provided in encoder 5. When card 1 moves, detector

This Sheet Has Been Replaced



30

roller 6 rotates, and encoder 5 rotates along with it. The rotation of encoder 5 is detected by the photointerrupters.



WE CLAIM:

1. A card processing device for processing data on a card, comprising:

a processor configured to move along with the card and process data on the card as it is moving;

a detection device which detects the displacement of the processor relative to the card in a manner which is directly dependant on the movement of either the card or the processor; and

a converter device which converts the signal from the detection device to a reference signal for the processing of the data.

2. A device according to Claim 1, including a conveyor device defining a route along which the card is conveyed relative to said processor.

3. A device according to Claim 2, wherein said detection device also detects the direction in which the card is moving, and including a device to stop processing of the data on the card in the event said detection device detects that the direction of the card's movement has been reversed.

4. A device according to Claim 1, wherein said processor includes a data reader which moves along with the card and reads the data written on the card as it is conveyed along its path wherein the device detects the displacement of the data reader relative to the card in a way which is directly dependent on the movement of either the card or the data reader, and including a device which corrects the data read by the data reader based on signals from said detector device.



5. A device according to Claim 4, including a conveyor device defining a route along which the card is conveyed relative to the said data reader, and such that the said detector device detects the displacement of the card in a way which is directly dependent on the movement of the card.
6. A device according to Claim 5, wherein said detector device detects both the displacement of the card and the direction in which the card is moving, and including a device to stop the reading of data in the event said detector device detects that the direction of the card's movement has been reversed.
7. A device according to Claim 2, wherein said conveyor device includes a drive comprising worm gears.
8. A device according to Claim 5, wherein said conveyor device includes a drive comprising worm gears.
9. A device according to Claim 2, wherein said conveyor device comprises two pairs of set apart drive rollers with a space between said two pairs of rollers being shorter than the route along which the card is conveyed.
10. A device according to Claim 5, wherein said conveyor device comprises two pairs of set apart drive rollers with a space between said two pairs of rollers being shorter than the route along which the card is conveyed.
11. A device according to Claim 7, wherein said conveyor device comprises two pairs of set apart drive rollers with a space between said two pairs of rollers being shorter than the route along which the card is conveyed.
12. A device according to Claim 9, wherein said two pairs



of rollers defining said conveyor device are positioned in such a manner that they face both the processor and a portion of the card on which data is recorded.

5 13. A device according to Claim 12, wherein said two pairs of rollers are each defined by an upper roller and a lower roller that are constructed to exert elastic force radially, said upper roller and said lower roller oppose one another above and below the route of the card, and are separated by a space whose vertical dimension is less than
10 the thickness of the card.

14. A device according to Claim 2 or 5, wherein said detector device includes rollers whose peripheral surfaces come in contact with the card and are positioned above and below the route of the card so as to squeeze the card
15 between a pair of said rollers of said detector device, said rollers of said detector device are driven by a same drive as said rollers of said conveyor device and are provided with elastic members to supply force to a pressure roller in a direction which will cause it to make contact
20 with a detector roller, and a stop to constrain the movement of said pressure roller to within a specified range as it is displaced away from said detector roller.

25 15. A device according to Claim 14, wherein a signal from detection device which detects the displacement of the card is used as a reference signal to control said drive.

16. A device according to Claim 1, including an image reader which reads images off a surface of the card, wherein a signal from said detector device is used as a reference signal to control said image reader.

30 17. A device according Claim 1, including an input power transmission device to accept a supply of drive force from



an a drive source exterior of the device to convey the card on the route.

18. A device according to Claim 1, including a device for moving said processor relative to the card, and said detector device detects the displacement of said processor directly based on its current position.


19. A device according to Claim 18, said device for moving said processor includes a lead screw mechanism comprising a female screw fixed to said processor and a male screw of a length which at least surpasses that of a range of movement of said processor, said male screw engages with said female screw to supply rotary force to said female screw.

20. A device according to Claim 19, wherein said detection device comprises an array of elements to be detected, said array of elements are provided in a space traversed by said processor, and including a detector element fixed to said processor, said detector element outputs a detection signal at a moment when the position of said processor corresponds to each position of said detector element.

21. A device according to Claim 4, including a device for moving said data reader with respect to the card, and wherein said detector device detects the displacement of said data reader directly based on its current position.

22. A device according to Claim 21, wherein said device for moving said data reader comprises a lead screw mechanism comprising a female screw fixed to said data reader and a male screw of a length which at least surpasses that of the range of movement of the said data reader, said male screw of said data reader engages with said female screw of said data reader to supply rotary





force to female screw of said data reader.

23. A device according to Claim 22, wherein said device to move said data reader comprises elements to be detected, which are provided at equal intervals along a path
5 traversed by said data reader, and a detector element fixed to said data reader, said detector element of said data reader outputs a detection signal at a moment when a position of said data reader corresponds to that of each detector element of said data reader being detected.

10 24. A device according to Claim 23, wherein said device to move said data reader includes an input power transmission device to accept a supply of drive force from a drive exterior of the device to move said processor or said data reader.

15 25. A device according to Claim 14, wherein said device to detect a displacement of the card includes elements which generate signals related to displacement of the card, said elements of said device to detect displacement of the card comprising features for detection which are provided at
20 regular intervals on a peripheral surface coaxial with said detector roller.

25 26. A device according to Claim 25, wherein said features to be detected to generate signals related to displacement are composed of reflective surfaces and non-reflective surfaces, luminous elements and photodetector elements
provided on a peripheral surface of said elements to generate signals related to displacement, said elements to generate signals are oriented so that their angles of incidence and reflection are identical.

30 27. A device according to Claim 26, wherein said non-reflective surfaces are slits.



28. A device according to Claim 27, wherein said features to be detected by said element to generate signals related to displacement comprises two different colors of reflected light.

This Sheet Has Been Replaced



* C L M S *