HYDRAULIC ACTUATOR

FIELD OF THE INVENTION

The present invention relates to well completion equipment, and more specifically to mechanisms for actuating downhole well tools that require pressurized hydraulic fluid to operate.

BACKGROUND OF THE INVENTION

It is well known that many downhole devices require power to operate, or shift from position to position in accordance with the device's intended purpose. A surface controlled subsurface safety valve (SCSSV) requires hydraulic and/or electrical energy from a source located at the surface. Setting a packer that is sealably attached to a string of production tubing requires either a tubing plug together with application of pressure on the tubing, or a separate and retrievable "setting tool" to actuate and set the packer in the tubing. Sliding sleeves or sliding "side door" devices may also require hydraulic activation. It will become apparent to anyone of normal skill in the art that many downhole devices requiring power for actuation can be adapted to utilize this invention. Such devices may comprise: packers, such as those disclosed in U.S. Pat. Nos. 5,273,109, 5,311,938, 5,433,269, and 5,449,040; perforating equipment, such as disclosed in U.S. Pat. Nos. 5,449,039, 5,513,703, and 5,505,261; locking or unlocking devices, such as those disclosed in U.S. Pat. Nos. 5,353,877 and 5,492,173; valves, such as those disclosed in U.S. Pat. Nos. 5,394,951 and 5,503,229; gravel packs, such as those disclosed in U.S. Pat. Nos. 5,531,273 and 5,597,040; flow control devices or well remediation tools, such as those disclosed in U.S. Pat. Nos. 4,429,747, and 4,434,854; and plugs or expansion joints, of the type well known to those in the art.

Each of these well known devices has a method of actuation, or actuation mechanism that is integral and specific to the tool. Consequently, in the past, most of these well known devices have required an independent source of power. There is a need for a device that can provide one or more sources of pressurized hydraulic fluid into the downhole environment, enabling actuation of

any number of downhole tools. The device should be adaptable for various downhole tasks in various downhole tools, and be simple to allow for redress in the field. It should also be adaptable for permanent installation in the completion, thereby allowing multiple functions to be performed on multiple tools located therein, all controlled by an operator at a control panel on the earth's surface.

BRIEF DESCRIPTION OF THE INVENTION

A full understanding of the present invention will be obtained from the detailed description of the preferred embodiment presented herein below, and the accompanying drawings, which are given by way of illustration only and are not intended to be limitative of the present invention, and wherein:

Fig. 1 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention.

Fig. 2 is a cross-sectional view of the seating element and seal nut of an embodiment of the hydraulic distributor.

Fig. 3 is a perspective view of an embodiment of the indexer sleeve of the present invention in its lowermost position.

Fig. 3A is a diagrammatic sketch of the receptacles of the indexer sleeve of the present invention.

Fig. 4 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention in its first position under no pressure.

Fig. 5 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention in its first position under an initial pressure.

Fig. 6 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention in its first position under an elevated pressure.

Fig. 7 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention in its first position with the elevated pressure bled off.

Fig. 8 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention in its first position with the initial pressure bled off.

Fig. 9 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention transitioning to its second position under no pressure.

Fig. 10 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention in its second position under an initial pressure.

Fig. 11 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention in its second position under an elevated pressure.

Fig. 12 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention in its second position with the elevated pressure bled off.

Fig. 13 is a cross-sectional view of an embodiment of the hydraulic distributor of the present invention transitioning to its first position with the initial pressure bled off.

Fig. 14 is a sectional view of an embodiment of the present invention in which hydraulic fluid pressure is distributed to upper and lower pistons.

Fig. 15 is a diagrammatic sketch of an embodiment of the present invention wherein the hydraulic distributor further comprises a ratchet assembly.

Fig. 15A is a perspective view an embodiment of the present invention wherein the ratchet assembly further comprises a mechanical override.

Fig. 15B is a perspective view of the proximal components of an embodiment of the mechanical override.

Fig. 15C is a perspective view of the distal components of an embodiment of the mechanical override.

Figs. 15D and 15E show an embodiment of the present invention used to control a subsurface safety valve. Fig. 15D provides a perspective view wherein the ratchet assembly is shown in a cut-away cross sectional view, and Fig. 15E provides a cross-section taken along line 15E in Fig. 15D.

Fig. 15F is a perspective view of an embodiment of an internal brake.

Fig. 16 is a diagrammatic sketch of an embodiment of the present invention wherein the hydraulic distributor is used to control a sliding sleeve valve.

Figs. 17A – 17D are fragmentary elevational views, in quarter section, of an embodiment of the present invention wherein the hydraulic is used to control a safety valve.

Figs. 18A and 18B are longitudinal sectional views, with portions in side elevation, of an embodiment of the present invention wherein the hydraulic distributor is used to control a subsea control valve apparatus.

Figs. 19A – 19D are elevational views, of an embodiment of the present invention wherein the hydraulic is used to control a variable orifice gas lift valve.

Fig. 20 is a diagrammatic sketch of an embodiment of the present invention wherein the hydraulic distributor is used to control a hydraulically actuated lock pin assembly.

Fig. 21 is a cross-sectional view of an embodiment of the present invention wherein the hydraulic distributor is used to control a resettable packer.

Figs. 22A – 22D are continuations of each other and are elevational views, in quarter section, of an embodiment of the present invention wherein the hydraulic distributor is used to control a safety valve.

Figs. 23A – 23B are sectional views of an embodiment of the present invention wherein the hydraulic distributor is used to control a formation isolation valve.

Figs. 24A – 24C are continuations of each other and form an elevational view in cross section of an embodiment of the present invention wherein the hydraulic distributor is used to advantage to control an emergency disconnect tool.

Fig. 25 is a diagrammatic sketch of a series of hydraulic distributors used to control a plurality of tools from a single control line.

Fig. 25A is a diagrammatic sketch of a series of hydraulic distributors used to control a plurality of tools from a single control line.

Fig. 25B is a diagrammatic sketch of a series of hydraulic distributors used to control a single tool from a single control line.

Fig. 25C is a diagrammatic sketch of a series of hydraulic distributors used to control a plurality of tools from a single control line.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the subject matter of the present invention, the invention is principally described as being used in oil well applications. Such applications are intended for illustration purposes only and are not intended to limit the scope of the present invention. The present invention can also be used to advantage in operations within gas wells, water wells, injection wells, control wells, and other applications requiring remote hydraulic control. All such applications are intended to fall within the purview of the present invention. However, for purposes of illustration, the present invention will be described as being used for oil well applications.

Additionally, in the following detailed description of the subject matter of the present invention, the invention is principally described as being used to supply hydraulic devices with hydraulic fluid pressure from a main control line. Such hydraulic devices include, but are not limited to, hydraulic tools, hydraulic actuators, and hydraulic distributors, for example. All such applications are intended to fall within the purview of the present invention.

In describing the present invention and its operation, it is important to note that directional terms such as "up", "down", "upper", "lower", are used to facilitate discussion of the example. However, the present invention can be used to advantage in any axially orientation. However, for purposes of illustration, certain directional terms relating to the orientation on the drawing page will be used.Fig. 1 is a cross-sectional view of an embodiment of the hydraulic distributor **1** of the present invention. The main body **10** of the hydraulic distributor **1** serves as its chassis and comprises a flow control housing **12** and an actuator housing **52** that are in coupled communication to channel the hydraulic fluid pressure from the main control line **18**. It should be noted that although in this embodiment of the present invention the main body **10** is a unitary component having two housings

12, **52**, in alternate embodiments within the scope of the present invention, the main body **10** can be comprised of other configurations such as, for example, separate, but affixed housings **12**, **52**.

Hydraulic fluid pressure from the main control line **18** is received by an inlet port **14** in the flow control housing **12**. In this embodiment of the hydraulic distributor **1**, the inlet port **14** has a series of inlet threads **16** for sealingly engaging the nozzle of the main control line. However, there are a multiplicity of ways in which the main control line can engage the inlet port **14** of the flow control housing **12** such as flanged connections, quick-connect fittings, welded connections, and the like. All such ways are intended to fall within the purview of the present invention. The flow entering the inlet port **14** is distributed to a plurality of outlet ports **20a**, **20b**. The outlet ports **20a**, **20b** provide the conduit for supplying hydraulic fluid pressure to hydraulic devices.

In an embodiment of the present invention, each outlet port **20a**, **20b** houses a seating element **22** that controls the flow therethrough the outlet ports **20a**, **20b**. Each seating element **22**, in this embodiment, is maintained within the outlet ports **20a**, **20b** by a seal nut **32**.

It should be noted that in alternate embodiments, the seating element **22** is maintained within the outlet ports **20a**, **20b** by means such as welds, solders, threaded connections, or the like. In still further alternate embodiments, the seating element **22** is integral with the outlet ports **20a**, **20b**.

As best described with reference to Fig. 2, each seating element **22** provides a seating surface **24** that is a mating surface for a spring-controlled actuation ball **38** (discussed below) to redirect fluid communication. When the actuation ball **38** is in mating contact with the seating surface **24**, fluid is prevented from entering and traveling through the internal conduit **26** that extends therethrough the seating element **22**. Conversely, when the actuation ball **38** is not in mating contact with the seating surface **24**, fluid may flow through the internal conduit **26**. In an alternate embodiment, the seating surface **24** is energized by a spring, for example, to further secure the mating engagement with the actuation balls **38**.

At the distal end of the internal conduit **26** is a tool interface port **28** that provides the interface to supply fluid flow from the internal conduit **26** to the hydraulic devices. The tool interface port **28** is provided with internal threads **30** for engagement with the attached hydraulic devices. However, alternate connections for engagement may be utilized depending upon the type of hydraulic device. Such connections include, but are not limited to, flanged connections, quick-connect fittings, welded connections, and the like. All such ways are intended to remain within the purview of the present invention.

Referring back to Fig. 1, the flow control housing **12** is further defined by a control chamber **34**. The control chamber **34** is an internal channel within the flow control housing **12** that extends from the inlet port **14** to the outlet ports **20a, 20b** and extends from the inlet port **14** to the actuator housing **52**. Housed within the control chamber **34** is a supply alternator **36**. The supply alternator **36** controls the distribution of the hydraulic fluid pressure from the inlet port **14** to the appropriate outlet port **26a, 26b**.

In the embodiment of Fig. 1, the supply alternator **36** is comprised of a ball housing **40** that houses a plurality of actuation balls **38**, ball springs **44** and spring spacer **46**. The ball housing **40** is oriented within the control chamber **34** such that it is axially aligned with the longitudinal axis of the seating elements **22**. The ball housing **40** has a retaining shoulder **42** at each distal end of the ball housing **40**. Intermediate within the ball housing **40** is the spring spacer **46** that acts as a base for the opposing ball springs **44** that bias the actuation balls **38** towards each retaining shoulder **42**. The retaining shoulders **42** prevent further outward movement of the actuation balls **38**.

A plurality of control screws **48** are affixed to and extend therefrom the ball housing **40** in a direction perpendicular to the axial orientation of the ball housing **40**. To maintain the spacing and orientation of the control screws **48**, a control screw spacer **50** is provided from which the control screws **48** extend therefrom. The control screws **48** extend from the ball housing **40** and are affixed to a shuttle sleeve **60** (discussed below) housed within the actuator housing **52**. Although shown as screws, the "control screws **48**" may be any member capable

of connecting the ball housing **40** to the shuttle sleeve **60**. For example, the "control screws **48**" can be an arm, an integrally formed connector, or any other connection.

The actuator housing **52** has a locking end **76**, an indexing end **112**, and defines an internal bore **54**. The internal bore **54** is defined by the interior walls **56** of the actuator housing **52** and extends therethrough the actuator housing **52**. The internal bore **54** is further defined by a bore shoulder **58**.

A shuttle sleeve **60** having a lock end **62** and an index end **70** resides within the internal bore **54** such that the shuttle sleeve **60** can travel axially therethrough. The lock end **62** of the shuttle sleeve **60** provides a shuttle sleeve spring **64** within a shuttle spring housing **66**. The lock end **62** further provides a locking profile **68** that is defined by a series of recesses **69a**, **69b**. The index end **70** provides a base surface **72** that abuts the bore shoulder **58** to limit the travel of the shuttle sleeve **60** towards the indexing end **112** of the actuator housing **52**.

The shuttle sleeve **60** further provides a control screw receptacle **74** for fixed engagement with the control screws **48** originating in the supply alternator. Because of the substantially rigid fixation, movement of the shuttle sleeve **60** controls the movement of the supply alternator **36**.

A lock piston housing **78** is affixed to the locking end **76** of the actuator housing **52**. The lock piston housing **78** has a lock piston chamber **80** defined by opposing interior walls **82** and a chamber base **84**. In an alternate embodiment, a spacer (such as stack of washers) is located on the chamber base **84**.

A lock piston **88** is located and maneuverable within the lock piston chamber **80**. The lock piston **88** is comprised of a piston rod **90**, a flange **92**, and a control rod **94**. The lock piston further comprises a piston shaft **90a** that enables external manipulation of the lock piston **88** (as will be discussed below). A lock piston seal **110** maintains the fluid pressure within the lock piston chamber **80**. It should be noted that the lock piston seal **110** shown in Fig. 1 is exemplary of one embodiment of the present inventionAny number of seal arrangements could be utilized to advantage in the present invention. To fall within the purview

of the present invention it is only necessary that the seal arrangement act to prevent loss of fluid within the actuator housing **52**.

The control rod **94** of the lock piston **88** extends from the flange **92** opposite the piston rod **90**. The control rod **94** has a tapered detent **96** utilized to manipulate a plurality of locking balls **108** as will be discussed below. The distal end of the control rod **94** extends within the lock end **62** of the shuttle sleeve **60**.

A lock spring **98** located within the lock piston chamber **80** is utilized to bias the lock piston rod **90** away from the chamber base **84**. The lock spring **98** applies biasing force against the flange **92** of the lock piston rod **90**. The stroke of the lock piston rod **90** away from the chamber base **84** is limited, and defined by, the location of a fixed cage **100**. The fixed cage **100** having a limiting shoulder **102** is affixed to the interior walls **82** of the lock piston chamber **80**. The limiting shoulder **102** resists movement of the piston rod **90** resulting from the bias of the lock spring **98** when the flange **92** abuts the limiting shoulder **102**. Thus, the stroke of the lock piston rod **90** is controlled by the location of the fixed cage **100**.

The fixed cage **100** further has a lock ball housing **104**. The lock ball housing **104** extends within the lock end **62** of the shuttle sleeve **60** and receives of the control rod **94** of the lock piston **88** therethrough. The lock ball housing **104** defines a plurality of receptacles **106** for the receipt of the lock balls **108**. The lock ball housing **104** provides the base for the shuttle sleeve spring **64** located within the shuttle sleeve spring housing **66**.

As will be discussed further below, the relational positions of the control rod **94**, the lock ball housing **104**, and the lock balls **108** control whether the shuttle sleeve **60** is engaged by the fixed cage **100** thereby preventing axial movement by the shuttle sleeve **60**. As shown in Fig. 1, the shuttle sleeve **60** is in an unlocked position in which the lock balls **108** are not engaging the recesses **69a**, **69b** of the shuttle sleeve **60**, but are rather residing within the tapered detent **96** of the control rod **94**. However, it should be understood that downward (with respect to the drawing page) axial movement of the control rod **94** will result in the lock balls **108** being forced out of the tapered detent **96** of the control rod **94** and into engagement with one of the recesses **69a**, **69b** of the shuttle sleeve

60, thereby preventing the shuttle sleeve **60** from further axial movement. Upon an upward movement by the control rod **94**, the lock balls **108** release from engagement with the shuttle sleeve **60** and again reside in the tapered detent **96** of the control rod **94**.

An indexer piston housing **114** is affixed to the indexing end **112** of the actuator housing **52**. The index piston housing **114** has an indexer piston chamber **116** defined by opposing interior walls **118** and a chamber base **120**. In an alternate embodiment, a spacer (such as a stack of washers) is located on the chamber base **120**.

An indexer piston **122** is located and maneuverable within the indexer piston chamber **116**. The indexer piston **122** is comprised of a piston rod **124**, a flange **126**, and a control rod **128**. An indexer piston seal maintains the fluid pressure within the indexer piston chamber **116**. As discussed above with reference to the lock piston seal **110**, it should be noted that the indexer piston seal **152** shown in Fig. 1 is exemplary of one embodiment of the present invention. Any number of seal arrangements could be utilized to advantage in the present invention. To fall within the purview of the present invention it is only necessary that the seal arrangement act to prevent loss of fluid within the actuator housing.

The control rod **128** of the indexer piston **122** extends from the flange **126** opposite the piston rod **124**. The control rod **128** is utilized to manipulate the shuttle sleeve **60**, as will be discussed below. The control rod **128** extends within the indexing end **112** of the actuator housing **52**.

An indexer spring **130** located within the indexer piston chamber **116** is utilized to bias the indexer piston rod **124** away from the chamber base **120**. The indexer spring **130** applies biasing force against the flange **126** of the indexer piston rod **124**. The stroke of the indexer piston rod **124** resulting from the spring bias is limited, and defined by, the location of an indexer sleeve **134** with relation to an indexer pin **132**.

The indexer sleeve **134** is housed within thrust bearings **150** and is affixed to the indexer piston **122** such that axial movement of the indexer piston **122**

results in axial movement of the indexer sleeve **134** and vice versa. The axial displacement of the indexer sleeve **134** is limited by the indexer pin **132** that is rigidly affixed to the interior wall **118** of the indexer piston chamber **116**.

The axial displacement of the indexer sleeve **134** is best described with reference to Figs. 3, which is a perspective view of an embodiment of the indexer sleeve **134** of the present invention in its uppermost position, and Fig. 3A which is a diagrammatic sketch displaying the relational positions of the receptacles of the indexer sleeve. As shown in Fig. 3, the indexer sleeve **134** is comprised of an upper thrust surface **136**, a lower thrust surface **138**, one or more upper stops **140**, one or more lower receptacles **144**, and one or more intermediate receptacles **146**.

In Fig. 3, the indexer pin **132** is located in a lower receptacle **144**. In this position, the indexer pin **132** prevents the indexer sleeve **134** from upward movement resulting from a force applied to the lower thrust surface **138**. However, upon application of force to the upper thrust surface **136** the indexer sleeve **134** is able to move downward toward its lowermost position. As the indexer sleeve **134** moves downward, the indexer pin **132** is forced into engagement with the tapered surface **142** of an upper stop **140** which forces the indexer sleeve **134** to rotate. The downward travel and rotation of the indexer sleeve **134** continues until the upper stop **140** is engaged by the indexer pin **132**. At this point, the indexer sleeve **134** has rotated such that the indexer pin **132** is in axial alignment with the tapered surface **148** of an intermediate receptacle **146**.

With the indexer sleeve in its lowermost position in which the indexer pin **132** is engaged by an upper stop **140**, a force applied to the lower thrust surface **138** results in the indexer sleeve **134** moving upward toward its uppermost position. As the indexer sleeve **134** moves upward, the tapered surface **148** of an intermediate receptacle **146** engages the indexer pin **132**. With continued upward movement, the indexer pin **132** forces the indexer sleeve **134** to rotate as it moves upward. The upward travel and rotation of the indexer sleeve **134** continues until the intermediate receptacle **146** is engaged by the indexer pin

132. At this point, the indexer sleeve **134** is prevented from returning to its uppermost position and is maintained in its intermediate position by the interaction between the indexer pin **132** and the intermediate receptacle **146**. Further, the indexer sleeve **134** has rotated such that the indexer pin **132** is in axial alignment with the tapered surface **142** of an upper stop **140**.

Alternate applications of force to the upper thrust surface **136** and the lower thrust surface **138** will continue to cause the indexer sleeve **134** to rotate and oscillate between a lowermost, uppermost, and intermediate position.

It should be noted that the positions of travel of the indexer sleeve **134** of this embodiment of the present invention are only demonstrative for a particular application. By altering the receptacle and slot arrangements of the indexer sleeve **134**, the indexer sleeve **134** can be oscillated between any number of intermediate positions, or no intermediate positions at all (a simple 2 position indexer sleeve **12**). All such embodiments fall within the purview of the present invention.

It should further be noted that in an alternate embodiment, the indexer pin **132** could be located on the control rod **128** with the positional receptacles of the indexer sleeve **134** held stationary within the indexer piston housing **114**. Again, such embodiments are intended to fall within the purview of the present invention.

Figs. 4 – 9 illustrate the various stages of operation of the hydraulic distributor **1** as it is switched from its first position to its second. Fig. 4 illustrates a cross-sectional view of an embodiment of the hydraulic distributor **1** in its upper position under no pressure. The indexer sleeve **134** in Fig. 4 is in an uppermost position with the indexer pin **132** engaged by a lower receptacle **144**. The bias of the indexer spring **130** resists downward movement of the indexer sleeve **134** with the upper movement limited by the interaction between the indexer pin **132** and the lower receptacle **144**. Under these conditions, the control rod **128** of the indexer piston **122** contacts the base surface **72** of the shuttle sleeve **60** and forces the shuttle sleeve **60** into its upper position and prevents the shuttle sleeve **60** from downward movement.

Under no pressure, the coefficient of the lock spring **98** is not overcome and so the lock spring **98** continues to maintain the lock piston **88** in its lowermost position in which the flange **92** abuts the fixed cage **100**. With the lock piston **88** in its lowermost position, the lock balls **108** remain within the tapered detent **96** of the control rod **94** and the shuttle sleeve **60** is not fixed to the fixed cage **100**. However, the downward movement of the shuttle sleeve **60** is restricted by the control rod **128** of the indexer piston **122** as discussed above. Thus, the shuttle sleeve **60** is locked in its upper position.

With the shuttle sleeve **60** in its upper position, the control screws **48**, which are affixed to the shuttle sleeve **60**, are forced into an upper position within the control chamber **34**. Consequently, the supply alternator **36** is forced into its upper position in which the upper actuation ball **38** matingly engages the seating surface **24** of the upper seating element **22**. Such engagement is secured by the force supplied by the compression of the upper ball spring **44**. The lower actuation ball **38** is maintained within the ball housing **40** by the lower retaining shoulder **42**.

The application of an initial pressure to the hydraulic distributor **1** is illustrated in Fig. 5. Under initial pressure, the hydraulic distributor **1** remains in its first position. It should be understood that for purposes of illustration, the term "initial pressure" refers to a pressure sufficient to overcome the spring coefficient of the lock spring **98**, but insufficient to overcome the spring coefficient of the indexer spring **130**. The coefficients are solely dependent upon the type of application for which the hydraulic distributor **1** is utilized.

As shown in Fig. 5, the hydraulic distributor **1** remains in its first position in which the shuttle sleeve **60** remains in its uppermost position with the indexer pin **132** engaged by a lower receptacle **144**. The control rod **128** of the indexer piston **122** maintains the shuttle sleeve **60** in its upper position and resists downward movement of the shuttle sleeve **60**.

Under initial pressure conditions, the coefficient of the lock spring **98** is overcome such that the flange **92** applies a force to the lock spring **98** sufficient to compress the lock spring **98** and enable the piston rod **90** to move upward

(indicated by the arrow) toward the chamber base **84** of the lock piston chamber **80**. The piston rod **90** continues to compress the lock spring **98** until movement of the piston rod **90** is resisted by the chamber base **84**. In the embodiment shown in Fig. 5, to protect the surface of the chamber base **84**, and to adjust the load of the lock spring **98**, a spacer **86** is provided.

As the piston rod **90**, and thus control rod **94**, moves upward, the lock balls **108** are forced out of the tapered detent **96** and into engagement with the first recess **69a** of the locking profile **68** of the shuttle sleeve **60**. The shuttle sleeve **60** is consequently fixedly engaged to the fixed cage **100** and prevented from downward movement regardless of the position of the control rod **128** of the indexer piston **122**.

With the shuttle sleeve **60** remaining in its upper position, the supply alternator **36** is maintained in its upper position in which the upper actuation ball **38** matingly engages the seating surface **24** of the upper seating element **22**. The initial pressure is restricted from flow into the upper internal conduit **26** of the upper seating element **22** but is free to flow through the lower internal conduit **26** of the lower seating element **22**. Thus, the initial pressure can be used to supply hydraulic fluid pressure to a hydraulic device attached to the lower seating element **22**.

It should be understood that the term "restricted" as used herein to describe the control of flow through the upper and lower internal conduits **26** refers to a condition wherein the flow is totally or substantially prevented from entering the conduits **26**. As long as a portion of the flow is prevented from entering the conduits **26**, the flow is considered to be restricted.

Fig. 6 displays a cross-sectional view of hydraulic distributor **1** as the initial pressure is increased to an elevated pressure. Under this elevated pressure, the hydraulic distributor **1** still remains in its first position. It should be understood that for purposes of illustration, the term "elevated pressure" refers to a pressure sufficient to overcome the spring coefficient of the lock spring **98**, and sufficient to overcome the spring coefficient of the indexer spring **130**. Again, these

coefficients are solely dependent upon the type of application for which the hydraulic distributor **1** is utilized.

As indicated by the arrows in Fig. 6, the coefficient of the indexer spring **130** is overcome such that the flange **126** of the indexer piston **122** applies a force to the indexer spring **130** sufficient to compress the indexer spring **130** and enable the piston rod **124** to move downward toward the chamber base **120**. The action of the piston rod **124** forces the indexer sleeve **134** downward toward its lowermost position. As the indexer sleeve **134** moves downward, the indexer pin **132** engages the tapered surface **142** of an upper stop **140** which forces the indexer sleeve **134** to rotate. The downward travel and rotation of the indexer sleeve **134** continues until the upper stop **140** is engaged by the indexer pin **132**. At this point, the indexer sleeve **134** has rotated such that the indexer pin **132** is in axial alignment with the tapered surface **148** of an intermediate receptacle **146**.

With the upper stop **140** engaged by the indexer pin **132**, the indexer sleeve **134** is in its lowest position. Consequently, the control rod **128** is also in its lowest position in which the control rod **128** does not extend above the bore shoulder **58**. Thus, the control rod **128** of the indexer piston **122** no longer resists downward movement of the shuttle sleeve **60**. However, because the lock piston **88** remains in its upper position with the lock balls **108** of the fixed cage **100** engaged with the recess **69a** of the shuttle sleeve **60**, the shuttle sleeve **60** is maintained in its upper position.

Once again, with the shuttle sleeve **60** remaining in its upper position, the supply alternator **36** is maintained in its upper position in which the elevated pressure is restricted from flow into the internal conduit **26** of the upper seating element **22** but is free to flow through the internal conduit **26** of the lower seating element **22**. Thus, the elevated pressure can be used to supply hydraulic fluid pressure to a hydraulic device attached to the lower seating element **22**.

Fig. 7 illustrates the hydraulic distributor **1** with the elevated pressure bled off back to the initial pressure. With the elevated pressure bled off, the hydraulic distributor **1**, still remains in its first position.

As indicated by the arrows in Fig. 7, the coefficient of the indexer spring **130** now overcomes the applied pressure such that the indexer spring **130** applies force to the flange **126** of the indexer piston **122** sufficient to force the indexer piston **122** upwards. As the indexer piston **122** moves upwards, the indexer sleeve **134** moves upward toward its uppermost position. As the indexer sleeve **134** moves upward, the tapered surface **148** of an intermediate receptacle engages the indexer pin **132**. With continued upward movement, the indexer pin **132** forces the indexer sleeve **134** to rotate as it moves upward. The upward travel and rotation of the indexer sleeve **134** continues until the intermediate receptacle **146** is engaged by the indexer pin **132**. At this point, the indexer sleeve **134** is prevented from returning to its uppermost position and is maintained in its intermediate position by the interaction between the indexer pin **132** and the intermediate receptacle **146**. Further, the indexer sleeve **134** has rotated such that the indexer pin **132** is in axial alignment with the tapered surface **142** of an upper stop **140**. With the indexer sleeve **134** in an intermediate position, the control rod **128** extends up to the bore shoulder **58**.

Once again, the lock piston **88** remains in its upper position with the lock balls **108** of the fixed cage **100** engaged with the recess **69a** of the shuttle sleeve **60**, and the shuttle sleeve **60** is maintained in its upper position. Thus, the supply alternator **36** is maintained in its upper position in which the bled off pressure is restricted from flow into the internal conduit **26** of the upper seating element **22** but is free to flow through the internal conduit **26** of the lower seating element **22**.

Fig. 8 illustrates the hydraulic distributor **1** with the pressure further bled off to a pressure lower than the initial pressure. The hydraulic distributor **1** continues to remain in its first position.

As indicated by the arrows in Fig. 8, the coefficient of the lock spring **98** is no longer overcome and lock spring **98** applies a downward force to the flange **92** such that the piston rod **90** moves downward until the flange **92** abuts and is resisted by the fixed cage **100**. As the piston rod **90**, and thus the control rod **94**, moves downward, the lock balls **108** are once again received in the tapered detent **96** of the control rod **94** and are removed from engagement with the first

recess **69a** of the locking profile **68** of the shuttle sleeve **60**. The shuttle sleeve **60** is no longer fixedly engaged to the fixed cage **100**. However, the applied pressure maintains the shuttle sleeve **60** in its upward position.

Fig. 9 illustrates the subsequent bleeding off of the pressure applied to the hydraulic distributor **1** to a predetermined release pressure. Under the release pressure, the hydraulic distributor **1**, as indicated by the arrows, moves to its second position.

As stated above with reference to Fig. 8, the shuttle sleeve **60** is no longer held in an upper position by engagement of the lock balls **108** of the fixed cage **100**. Thus, once all of the pressure is bled to a predetermined release pressure, the shuttle sleeve **60** is forced to its lower position by action of the shuttle sleeve spring **64**, that has a coefficient sufficiently low to be overcome by minimal pressures but able to overcome a no-pressure state. As indicated above, the downward movement of the shuttle sleeve **60** is no longer impeded by the control rod **128** of the indexer piston **122**, as it is held in an intermediate position by the engagement of the indexer sleeve **134** by the indexer pin **132**.

As the shuttle sleeve **60** moves into its lower position, the control screws **48**, which are affixed to the shuttle sleeve **60**, are forced into a lower position within the control chamber **34**. Consequently, the supply alternator **36** is forced into its lower position in which the lower actuation ball **38** matingly engages the seating surface **24** of the lower seating element **22**. Such engagement is secured by the force supplied by the compression of the lower ball spring **44**. The upper ball **38** is maintained within the ball housing **40** by the upper retaining shoulder **42**.

As has been discussed, the shuttle sleeve spring **64** has a sufficiently low coefficient that the switching of the shuttle sleeve **60** from its upper position to its lower position does not occur until nearly all of the pressure has been bled off. In essence, the action of the shuttle sleeve spring **64** acts to impart a time delay on the switching of the hydraulic distributor **1** from its first position to its second position. This time delay avoids problems associated with prematurely bleeding off the pressure as the supply alternator **36** is toggled from its upper position to

its lower position. In addition to affecting the operation of the hydraulic distributor **1**, premature bleeding off of the pressure affects the instantaneous delivery of power to the hydraulic devices.

Figs. 10 – 13 illustrate the various stages of the hydraulic distributor **1** of the present invention as it moves from its second position to its first position. To begin, Fig. 10 provides a cross-sectional view of the hydraulic distributor **1** in its second position under an initial pressure. As discussed above, an intermediate receptacle **146** of the indexer sleeve **134** is engaged by the indexer pin **132**. The indexer sleeve **134** is maintained in this position by the bias of the indexer spring **130**. As discussed above, force applied to the lower thrust surface **138** is resisted by the interaction between the indexer pin **132** and the intermediate receptacle **146**. In this position, the control rod **128** of the indexer piston **122** does not force the shuttle sleeve **60** away from the bore shoulder **58** and away from its lower position.

Under initial pressure, the hydraulic distributor **1** remains in its second position. Again it should be understood that for purposes of illustration, the term "initial pressure" refers to a pressure sufficient to overcome the spring coefficient of the lock spring **98**, but insufficient to overcome the spring coefficient of the indexer spring **130**.

Under these initial pressure conditions, the coefficient of the lock spring **98** is overcome such that the flange **92** applies a force to the lock spring **98** sufficient to compress the lock spring **98** and enable the piston rod **90** to move upward (indicated by the arrow) toward the chamber base **84** of the lock piston chamber **80**. The piston rod **90** continues to compress the spring until its shoulder **87b** abuts the chamber base **84** preventing further movement. In the embodiment shown in Fig. 10, to protect the surface of the chamber base **84**, and to adjust the load of the lock spring **98**, a spacer **121** is provided. As the piston rod **90**, and thus control rod **94**, moves upward, the lock balls **108** are forced out of the tapered detent **96** and into engagement with the second recess **69b** of the locking profile **68** of the shuttle sleeve **60**. The shuttle sleeve **60** is

consequently fixedly engaged to the fixed cage **100** and prevented from upward movement.

With the shuttle sleeve **60** fixed in its lower position, the supply alternator **36** is maintained in its lower position in which the lower actuation ball **38** matingly engages the seating surface **24** of the lower seating element **22**. The initial pressure is restricted from flow into the lower internal conduit **26** of the lower seating element **22** but is free to flow through the internal conduit **26** of the upper seating element **22**. Thus, the initial pressure can be used to supply hydraulic fluid pressure to a hydraulic device attached to the upper seating element **22**.

Fig. 11 displays a cross-sectional view of hydraulic distributor **1** as the initial pressure is increased to an elevated pressure. Under this elevated pressure, the hydraulic distributor **1** still remains in its second position. As above, it should be understood that for purposes of illustration, the term "elevated pressure" refers to a pressure sufficient to overcome the spring coefficient of the lock spring **98**, and sufficient to overcome the spring coefficient of the indexer spring **130**.

As indicated by the arrows in Fig. 11, the coefficient of the indexer spring **130** is overcome such that the flange **126** of the indexer piston **122** applies a force to the indexer spring **130** sufficient to compress the indexer spring **130** and enable the piston rod **124** to move downward toward the chamber base **120**. The action of the piston rod **124** forces the indexer sleeve **134** downward toward its lowermost position. As the indexer sleeve **134** moves downward, the indexer pin **132** engages the tapered surface **142** of an upper stop **140** which forces the indexer sleeve **134** to rotate. The downward travel and rotation of the indexer sleeve **134** continues until an upper stop **140** is engaged by the indexer pin **132**. At this point, the indexer sleeve **134** has rotated such that the indexer pin **132** is in axial alignment with the tapered surface **145** of a lower receptacle **144**.

The shuttle sleeve **60** continues to be maintained in its lower position by the lock balls **108** engaging the second recess **69b** of the shuttle sleeve. Thus, the supply alternator **36** is maintained in its lower position in which the elevated pressure is restricted from flow into the internal conduit **26** of the lower seating

element **22** but is free to flow through the internal conduit **26** of the upper seating element **22**. Thus, the elevated pressure can be used to supply hydraulic fluid pressure to a hydraulic device attached to the upper seating element **22**.

Fig. 12 illustrates the hydraulic distributor **1** with the elevated pressure bled off back to the initial pressure. With the elevated pressure bled off, the hydraulic distributor **1**, still remains in its second position. As indicated by the arrows in Fig. 12, the coefficient of the indexer spring **130** now overcomes the applied pressure such that the indexer spring **130** applies force to the flange **126** of the indexer piston **122** sufficient to force the indexer piston **122**, and thus the indexer sleeve **134**, to move upwards. As the indexer sleeve **134** moves upwards, the tapered surface **145** of a lower receptacle **144** engages the indexer pin **132**. With continued upward movement, the indexer pin **132** forces the indexer sleeve **134** to rotate as it moves upward. The upward travel and rotation of the indexer sleeve **134** continues until the control rod **128** of the indexer piston **122** comes into contact with the base surface **72** of the shuttle sleeve **60**. Because the shuttle sleeve **60** is locked in its lower position by the lock balls **108** of the fixed cage **100**, additional upward movement of the indexer piston **122**, and thus indexer sleeve **134**, is prevented.

With the shuttle sleeve **60** remaining in its lower position, the supply alternator **36** is also maintained in its lower position in which the bled off pressure is restricted from flow into the internal conduit **26** of the lower seating element **22** but is free to flow through the internal conduit **26** of the upper seating element **22**.

Fig. 13 illustrates the hydraulic distributor **1** with all of the pressure bled off such that the hydraulic distributor **1** returns to its first position. As indicated by the arrows in Fig. 13, the coefficient of the lock spring **98** is no longer overcome and the lock spring **98** applies a downward force to the flange **92** such that the piston rod **90** moves downward until the flange **92** abuts and is resisted by the fixed cage **100**. As the piston rod **90**, and thus the control rod **94**, moves downward, the lock balls **108** are once again received in the tapered detent **96** of the control rod **94** and are removed from engagement with the second recess **69b** of the locking profile **68** of the shuttle sleeve **60**. The shuttle sleeve **60** is no longer

fixedly engaged to the fixed cage **100**. Now the upward movement of the indexer piston **122** is no longer resisted and the indexer sleeve **134** continues its upward movement until the indexer pin **132** is engaged by the most receptacle **144**. At the same time, the control rod **128** forces the shuttle sleeve **60** into and maintains the shuttle sleeve **60** in its upper position.

As the shuttle sleeve **60** moves into its upper position, the control screws **48**, which are affixed to the shuttle sleeve **60**, are forced into an upper position within the control chamber **34**. Consequently, the supply alternator **36** is forced into its upper position in which the upper actuation ball **38** matingly engages the seating surface **24** of the upper seating element **22**. Such engagement is secured by the force supplied by the compression of the upper ball spring **44**. The lower actuation ball **38** is now maintained within the ball housing **40** by the upper retaining shoulder **42**.

Fig. 14 provides a sectional view of an embodiment of the present invention in which the outlet ports **20a**, **20b** of the hydraulic distributor **1** distribute hydraulic fluid pressure to upper and lower pistons **160a**, **160b**. (Again, it should be emphasized that the directional terms such as "up", "down", "upper", "lower", are used to facilitate discussion of the example and are not intended to limit the scope of the present invention.) The upper and lower pistons **160a**, **160b** can be used to advantage to control the actuation of various downhole well equipment and tools. In an alternate embodiment, the upper and lower pistons **160a**, **160b** are replaced by hydraulic control lines. It should be noted that in this embodiment, the inlet port **14** of the hydraulic distributor **1** is located in the actuator housing **52**.

Fig. 15 is a diagrammatic sketch of an embodiment of the present invention wherein the hydraulic distributor **1** further comprises a ratchet assembly **210**. The ratchet assembly **210** is comprised of an upper piston **226a**, a lower piston **226b**, and a driving rod **240**. The action of the pistons **226a**, **226b** is used to incrementally advance or retrieve the driving rod **240** to activate or maneuver downhole tools, devices and equipment. It should be understood that the ratchet

assembly **210** of the present invention can be used to manipulate and maneuver a plurality of pistons **226a**, **226b** and a plurality of driving rods **240**.

The pistons **226a**, **226b** of the present invention are actuated by hydraulic fluid pressure supplied by the hydraulic distributor **1**. Upper and lower piston springs **229a**, **229b** act to return the pistons **226a**, **226b** to their initial position once the pressure is bled off. Each of the pistons **226a**, **226b** has a control arm **228a**, **228b** and a pawl **230a**, **230b** having engagement teeth **232a**, **232b** attached thereto. In an embodiment of the present invention, the pawls **230a**, **230b** are attached to the control arms **228a**, **228b** by pins **236a**, **236b**, for example, such that the pawls **230a**, **230b** have some rotational flexibility, but are substantially rigid in the axial direction of the control arms **228a**, **228b**. Engagement springs **234a**, **234b** bias the pawls **230a**, **230b** such that the engagement teeth **232a**, **232b** are forced to rotate away from the control arms **228a**, **228b**.

It should be noted that the pawls **230a**, **230b** described with reference to the embodiment of the present invention illustrated in Fig. 15 are illustrative and not intended as limiting on the scope of the present invention. Any number of pawls, collet fingers, latching mechanisms, or the like, can be used to advantage to cooperate with the pistons **226a**, **226b** and driving rod **240** of the present invention.

A biasing surface **238a**, **238b** is located approximate each of the pistons **226a**, **226b**. Upon retraction of the pistons **226a** **226b**, the pawls **230a**, **230b** contact the biasing surface **238a**, **238b** which imparts a force upon the pawls **230a**, **230b** sufficient to overcome the bias of the engagement springs **234a**, **234b** and force the engagement teeth **232a**, **232b** to rotate toward the control arms **228a**, **228b**.

The driving rod **240** has a plurality of upper ratchet detents **242a** and lower ratchet detents **242b** with each ratchet detent **242a**, **242b** having a tapered release **243a**, **243b**. The ratchet detents **242a**, **242b** are oriented such that the upper detents **242a** can be cooperatively engaged by the upper engagement teeth **232a** on the upper pawl **230a**, and likewise, such that the lower detents

242b can be cooperatively engaged by the lower engagement teeth **232b** on the lower pawl **230b**. The cooperative engagement enables the driving rod **240** to be incrementally advanced or retrieved. The spacing and number of ratchet detents **242a, 242b** is dependent upon the application for which the present invention is being used.

In an embodiment of the present invention, the hydraulic distributor **1**, and the ratchet assembly **210** are housed within an assembly frame **212** that is affixed to pipe tubing **244**, for example. The assembly frame **212** has a hydraulic module **220** that houses the hydraulic distributor **1** and the upper and lower pistons **226a, 226b**. The assembly frame **212** also has opposing spring modules **221** that, in combination with the hydraulic module **220**, form a compression chamber **214** filled with a fluid such as oil. The control arms **228a, 228b** of the pistons **226a, 226b** extend therein the compression chamber **214**, and the piston springs **239a, 239b** are housed within the compression chamber **214**. The driving rod **240** is maneuverable within the compression chamber **214** and the lower end of the driving rod **240** extends therethrough the compression chamber **214** such that the device coupling **246** located at the distal end of the driving rod **240** can be used to advantage to control downhole tools, devices, and equipment.

A compensating piston **218** is located within the assembly frame **212** that acts to maintain the fluid pressure within the compression chamber **214** equal to the external bore pressure. Maintaining equal internal and external pressure provides several advantages. One such advantage is to maintain the fluid seals **216** that act to keep the compression chamber **214** free from contaminants, such as sand, that tend to degrade the components of the ratchet assembly **210**. An additional advantage of using the compensating piston **218** to maintain equal internal and external pressure is to prevent the piston effect of the rod **240**. If, for example, the external bore pressure is higher than the internal pressure of the compression chamber **214**, absent a high enough countering force supplied by the lower piston **226b**, the driving rod **240** will be forced upwards which could act to prematurely activate or deactivate a downhole device or tool. Likewise, an internal pressure of the compression chamber **214** greater than the external bore

pressure acts to force the driving rod **240** downwards. Thus, to maintain control over the maneuvering of the driving rod **240** it is necessary to maintain equal internal and external pressures.

In operation, hydraulic fluid pressure is supplied by the main control line **18** to the hydraulic distributor **1**. In the sketch shown in Fig. 15, the hydraulic distributor **1** is in its second position in which hydraulic fluid flow travels through the second flow line **18b** to actuate the lower piston **226b** and force the pawl **238b** downward. As discussed above, the engagement teeth **232b** are biased away from the control arm **228b** and engage a lower ratchet detent **242b** of the driving rod **240**. Thus, downward movement of the control arm **228b** acts to force the driving rod **240** downward.

Under continued hydraulic pressure, the control arm **228b** of the lower piston **226b** continues to move downward until it reaches its maximum stroke. At this point, if it is desired to advance the driving rod **240** further, the pressure through the supply line **18b** is bled off until the lower piston spring **233b** forces the piston **226b** back to its retracted position. As the piston **226b** and control arm **228b** are forced back toward its retracted position, the engagement teeth **232b** are guided out of engagement with the lower ratchet detent **242b** of the driving rod **240** by its tapered release **243b**. Subsequent supply of hydraulic pressure through the supply line **18b** acts to again force the lower piston **226b** and pawl **238b** downward. Because the engagement spring **234b** keeps the engagement teeth **232b** in contact with the profile of the driving rod **240**, the engagement teeth **232b** are forced into engagement with another ratchet detent **242b** of the driving rod. The newly engaged ratchet detent **242b** is displaced on the driving rod **240** above the first ratchet detent **242b** at a distance approximating the stroke of the piston **226b**. Under continued hydraulic pressure, the control arm **228b**, and therefore driving rod **240**, are forced downward until the piston **226b** reaches its maximum stroke. Cycling the above sequence of events acts to maneuver the driving rod **240** through its full displacement.

While the driving rod **240** is being forced downward, there is no hydraulic fluid pressure supplied by the hydraulic distributor **1** to the upper piston **226a**. As

such, the upper piston spring **239a** forces the upper piston **226a** into its fully retracted position. As the control arm **238a** is retracted by the piston **226a**, the pawl **230a** contacts the biasing surface **238a**. Because the force supplied by the upper piston spring **239a** is greater than the force supplied by the engagement spring **234b**, the engagement teeth **232a** are forced out of contact with the driving rod **240**. Thus, the driving rod **240** can be maneuvered downward without any frictional resistance provided by the upper pawl **230a**.

To reverse the process and move the driving rod **240** upwards, the hydraulic fluid pressure supplied by the main control line **18** is varied to exceed predetermined switching parameters of the hydraulic distributor **1** to switch the hydraulic distributor **1** to its second position. In its second position, the hydraulic distributor supplies hydraulic fluid pressure to the first supply line **18a**. The upper piston **226a** is now actuated and as it is forced upward, the engagement spring **234a** forces the engagement teeth **232a** of the pawl **230a** into engagement with the ratchet detents **242a** of the driving rod **240**. As above, repeated supply and bleeding off of the hydraulic fluid pressure to the upper piston **226a** acts to incrementally advance the driving rod **240** in an upward direction.

Because the driving rod **240** is advanced and retrieved by the actions of the pistons **226a**, **226b**, directional movement in both directions is controlled by positive pressure supplied from the hydraulic distributor **1**. Thus, neither direction of movement of the driving rod **240** is controlled by a spring. As a consequence, the ratchet assembly **210** enables more powerful movement of the driving rod **240** in both directions. This enables the ratchet assembly **210** to be used to advantage on tools, devices, and equipment requiring equal activation and deactivation forces. Further, such activation and deactivation is achieved from a single control line **18**. The use of the small strokes to advance or retrieve the driving rod **240** offers many advantages. One such advantage is to enable incremental movement of the driving rod **240**. Such incremental movement offers advantages to various downhole tools, devices, and equipment. For example, if the ratchet assembly **210** is used to control a valve, the incremental movement enables the valve to be opened or closed at varying rates of speed. Additionally,

the valve can be maintained in many intermediate positions in which the valve is partially opened or closed.

Another advantage of the small strokes that may be, but not required to be, utilized by the ratchet assembly **210** of the present invention is that a long stroke of the pistons **226a, 226b** is achieved by the use of many smaller strokes. Using smaller strokes enables the use of relatively compact but powerful mechanical piston springs **239a, 239b**. This avoids the problems associated with using longer mechanical springs (i.e., loss of resistivity) for pistons having a longer stroke.

Another advantage of the ratchet assembly **210** is that it can be used to force the driving rod **240** forward and backward without having to cycle through the complete stroke of the pistons **226a, 226b** like that required with the use of conventional j-slot designs.

In an embodiment shown in Figs. 15A – 15C, a mechanical override is provided. The mechanical override acts to mechanically switch the hydraulic distributor **1** from its first position to its second position, or from its second position to its first position. The mechanical override is activated when the engagement teeth **232a, 232b** of the pawls **230a, 230b** have been displaced beyond the last ratchet detents **242aa, 242bb** of the driving rods **240** in either direction.

In the embodiment shown in Figs. 15A – 15C, the ratchet assembly **210** is used to control two driving rods **240**. The mechanical override is provided with a proximal override **248** that is activated when the engagement teeth **232a** of the pawls **230a** have been displaced beyond the last ratchet detents **242aa** of the proximal end of the driving rods **240**. The mechanical override is further provided with a distal override **254** that is activated when the engagement teeth **232b** of the pawls **230b** have been displaced beyond the last ratchet detents **242bb** of the distal end of the driving rods **240**. It is important to note that although the mechanical override is described with reference to the embodiment shown in Figs. 15A – 15C in which two driving rods **240** are controlled, the mechanical override is not so limited. The mechanical override of the present invention has

equal applicability to ratchet assemblies **210** used to control any number of driving rods **240**.

The proximal override **248** is best described with reference to Figs. 15A and 15B. The proximal override **248** has a proximal lifter **249** having a proximal lifter notch **249a**. Under normal operating conditions, with the engagement teeth **232a** of the pawls **230a** engaged in the ratchet detents **242a** of the driving rods **240**, the pawls **230a** are maneuverable by the piston **228a** without interference from the proximal lifter notch **249a**. However, because the last ratchet detents **242aa** of the driving rods **240** are not cut as deep as the other ratchet detents **242a**, once the pawls **230a** engage the last ratchet detents **242aa**, the proximal lifter notch **249a** engages the pawls **230a**. Thus, as indicated by the arrows in Fig. 15B, further outward movement by the piston **228a**, results in displacement of the proximal lifter **249**.

Affixed to the proximal lifter **249** is a lifter arm **250** having a lifting fork **250a** for engagement and displacement of a distribution trigger **252**. Outward displacement by the proximal lifter **249** results in displacement of the lifter arm **250**, and consequently, outward displacement of the distribution trigger **252** (as indicated by the arrows in Fig. 15B). Because the distribution trigger **252** is affixed to the piston shaft **90a** (shown in Fig. 1), outward displacement of the distribution trigger **252** activates the lock piston **90** to mechanically switch the hydraulic distributor **1**. Once the hydraulic distributor **1** is switched, the pawls **230b** can be used to displace the driving rods **240** in the opposite direction, or can be used to bring the pawls **230a** back into engagement with the driving rods **240**.

The distal override **254** is best described with reference to Figs. 15A and 15C. The distal override **254** has a distal lifter **255** having a distal lifter notch **255a** and a distal lifter base **255b**. Under normal operating conditions, with the engagement teeth **232b** of the pawls **230b** engaged in the ratchet detents **242b**, the pawls **230b** are maneuverable by the piston **228b** without interference from the distal lifter notch **255a**. However, because the last ratchet detents **242bb** of the driving rod **240b** are not cut as deep as the other ratchet detents **242b**, once

the pawls **230b** engage the last ratchet detents **242bb**, the distal lifter notch **255a** engages the pawls **230b**. Thus, as indicated by the arrows in Fig. 15B, further outward movement by the piston **228b**, results in displacement of the distal lifter **255**.

Affixed to the base **255b** of the distal lifter **249** is a rocker **256** that rotates about a hinge pin **257**. The rocker **256** is in engagement with the distribution trigger **252**. Outward displacement by the distal lifter **255** results in inward displacement of the distal lifter base **255b**, and consequently, outward displacement of the distribution trigger **252** (as indicated by the arrows in Fig. 15B). Because the distribution trigger **252** is affixed to the piston shaft **90a** (shown in Fig. 1), outward displacement of the distribution trigger **252** activates the lock piston **90** to mechanically switch the hydraulic distributor **1**. Once the hydraulic distributor **1** is switched, the pawls **230a** can be used to displace the driving rods **240** in the opposite direction, or can be used to bring the pawls **230b** back into engagement with the driving rods **240**.

In this manner, the mechanical override acts to mechanically switch the hydraulic distributor **1** when the last ratchet detents **242aa**, **242bb** have been reached. This enables the controller to know the limit to which the driving rod **240** can be displaced, and eliminates the need to use excessive pressure to switch the hydraulic distributor **1**. Depending upon the application, excessive pressures may not be possible.

An embodiment of the present invention shown in Figs. 15D and 15E shows the ratchet assembly **210** used to advantage to control a subsurface safety valve **260**. The safety valve **260** has a choke **262** in communication with a flow regulator **264**. The flow regulator **264** has multiple intermediate conduits **265** through which flow is enabled. Thus, incremental movement of the choke **262** over the conduits **265** enables precise flow regulation and control. It should be noted that in the embodiment shown in Figs. 15D and 15E, the ratchet assembly **210** and the hydraulic distributor **1** are mounted in the wall of a well tool such that the wall of the well tool houses both components and acts as the assembly frame

212. It should be further noted that in an alternate embodiment, the components are mounted eccentrically in the well tool wall.

In the embodiment shown in Figs. 15D and 15E, the ratchet assembly **210** is comprised of two sets of pistons **226a**, **226b** used to manipulate two driving rods **240**. Again, the number of pistons **226a**, **226b** and driving rods **240** can be altered and still remain within the purview of the invention. The driving rods **240** are affixed to the choke **262** of the safety valve **260** by the device coupling **246**. As discussed above, by alternating the hydraulic fluid pressure from the main control line **18**, the hydraulic distributor **1** is used to manipulate the pistons **226a**, **226b** of the ratchet assembly **210**, which, in turn, manipulate the driving rods **240**. Downward movement of the driving rods **240** acts to force the choke **262** downward to incrementally close the valve **260**, and upward movement of the driving rods **240** acts to force the choke **262** upward to incrementally open the valve **260**. Thus, the pressure cycles can shift the safety valve **260** to the fully open position, multiple intermediate positions, and the fully closed position. In this manner, incremental opening and closing of the safety valve **260** can be accomplished by varying the flow supplied to a single control line **18**.

It should be noted that the illustrated embodiment of the choke **262** of the safety valve **260** has an internal brake **263** (shown in Fig. 15F) which acts to prevent undesired upward or downward movement of the choke **262**. Such brakes, known in the art, are used to advantage in the present invention to ensure that the driving rods **240**, which are affixed to the choke **262** are not able to displace when the hydraulic pressure is released. Although not required, such brakes are particularly advantageous in the present invention wherein it is necessary to bleed off hydraulic pressure to incrementally advance the ratchet assembly **210**. The embodiment of an internal brake **263** shown in Fig. 15F is comprised of a series of semi-rigid fingers **263a** that engage and grip notches cut into the choke **262** to prevent movement of the choke **262** until activation of the driving rod **240**. The fingers **263a** flex enough to enable the choke **262** to displace under force supplied by the driving rod **240**, but grip securely upon release of such force. In another embodiment, the internal brake **263** can be

applied directly to the driving rod **240**.It should be understood that, although in the above discussed embodiments of the present invention the ratchet assembly **210** is manipulated by the hydraulic distributor **1**, in an alternate embodiment the ratchet assembly is manipulated independently of the hydraulic distributor **1**. For example, the ratchet assembly **210** can be manipulated by hydraulic fluid pressure supplied by a plurality of control lines in direct communication with the pistons **226a**, **226b**, or by other known methods.

Figs. 16 is a diagrammatic sketch of an embodiment of the present invention wherein the hydraulic distributor **1** is used to advantage to control a sliding sleeve valve **300** such as that disclosed in U.S. Pat. No. 4,524,831 to Pringle. The sliding sleeve valve **300** is moved to an open position by applying pressure to a hydraulic inlet **302** and returned to its closed position by bleeding off the pressure. A spring may also be provided to facilitate the closing of the valve.

In Fig. 16, a hydraulic distributor **1** receives flow from a main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the hydraulic inlet **302** through the first supply line **18a**. The hydraulic fluid pressure entering the hydraulic inlet **302** actuates the sliding sleeve valve **300** and it is moved to an open position. Bleeding off the pressure from the main control line **18** acts to return the sliding sleeve valve **300** to its closed position. In this manner, repeated opening and closing of the sliding sleeve valve **300** can be accomplished.

An additional hydraulic device **201** can also be actuated by the hydraulic distributor **1**. As discussed earlier in describing the operation of the hydraulic distributor **1**, by varying the pressure supplied by the main control line **18** to exceed predetermined switching parameters, the hydraulic distributor **1** can be switched from its first position to its second position. In its second position, the hydraulic distributor **1** prevents flow to the first supply line **18a** while enabling hydraulic fluid pressure to the second supply line **18b**. In its second position, the

hydraulic distributor **1** facilitates hydraulic fluid pressure to an additional hydraulic device **201**.

Thus, by varying the hydraulic fluid pressure supplied by the main control line **18**, the hydraulic distributor **1** can be used to advantage to supply hydraulic fluid pressure to one or more hydraulic devices. The hydraulic distributor **1** only switches position upon exceeding predetermined pressure values, therefore, the flow to one or the other device can be varied without premature switching of the position of the distributor **1**. In this way, individual devices can be oscillated between pressure states and one or more devices can be remotely controlled by a single control line **18**.

It should be noted that for discussion purposes, the hydraulic distributor **1** is shown in Fig. 16 as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributor **1** as being external to the sliding sleeve valve **300**. The hydraulic distributor **1** can also be provided on or in a wall of the sliding sleeve valve **300** or be provided on or in a wall of a tool string to which the sliding sleeve valve **300** is a part of, for example.

Figs. 17A – 17D are fragmentary elevational views, in quarter section, of an embodiment of the present invention wherein the hydraulic distributor **1** (shown as a diagrammatic sketch) is used to advantage to control a safety valve **310** such as that disclosed in U.S. Pat. No. 4,621,695 to Pringle. The safety valve **310** is moved to an open position by applying hydraulic pressure to a first hydraulic inlet **311** that is in communication with the upper surface of the piston **312**. The safety valve **310** is returned to its closed position by applying a greater hydraulic pressure to a second hydraulic inlet **312** that is in communication with the lower surface of the piston **312**.

A hydraulic distributor **1** (shown in Fig. 17A) receives flow from a main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the first hydraulic inlet **311** through the first supply line **18a**. The hydraulic fluid pressure entering

the hydraulic inlet **311** forces the piston **312** downward which acts to open the safety valve **310**.

The second supply line **18b** of the hydraulic distributor **1** is in communication with the second hydraulic inlet **313**. Thus, varying the flow from the main control line **18** to switch the hydraulic distributor **1** from its first position to its second position, acts to supply hydraulic fluid pressure to the second hydraulic inlet **313** which forces the piston **312** upward and moves the safety valve **310** to a closed position. In this manner, repeated opening and closing of the sliding safety valve **310** can be accomplished by varying the flow supplied to a single control line **18**.

It should be noted that for discussion purposes, the hydraulic distributor **1** is shown in Figs. 17A as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributor **1** as being external to the safety valve **310**. The hydraulic distributor **1** can also be provided on or in a wall of the safety valve **310** or be provided on or in a wall of a tool string to which the safety valve **310** is a part of, for example.Figs. 18A and 18B are longitudinal sectional views, with portions in side elevation, of an embodiment of the present invention wherein the hydraulic distributor **1** (shown as a diagrammatic sketch) is used to advantage to control a subsea control valve apparatus **320** such as that disclosed in U.S. Pat. No. 3,967,647 to Young. The subsea control valve apparatus **320** receives hydraulic fluid pressure from three hydraulic inlets **320A**, **320B**, and **320C**. Hydraulic fluid pressure received by the first hydraulic inlet **320A** acts to force the outer piston assembly **321** and the inner piston assembly **322** downward causing corresponding downward movement of the valve cage **323** which rotates the ball valve element **324** to an open position. To rotate the ball valve element **324** to a closed position, the pressure to the first hydraulic inlet **320A** is bled off and the ball valve closure spring **325** shifts the valve cage **323** upwards.

Hydraulic fluid pressure received by the second hydraulic inlet **320B** is used for an emergency shut in. In the event that a wireline tool is suspended in the well for perforating or the like, and an emergency condition dictates that the

well be shut in before there is time to retrieve the wireline tool, hydraulic fluid pressure is directed to the second hydraulic inlet **320B**. The flow forces the inner piston assembly **322** upwards which acts to force the valve cage **323** upwards. The combination of the hydraulic force and the force of the return spring **325** is adequate to cause the ball valve element **324** to cut wireline or cable.

Hydraulic fluid pressure received by the third hydraulic inlet **320C** is used to release the control unit **326** from the valve assembly **327**. The control unit **326** can be retrieved to the surface leaving the valve section **327** within the blowout preventer stack.

The embodiment of the present invention shown in Fig. 18A, utilizes two hydraulic distributors **1**, **2** to supply hydraulic fluid pressure to the three hydraulic inlets **320A**, **320B**, **320C** from a single control line **18**. The first hydraulic distributor **1** receives flow from the main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the first hydraulic inlet **320A** through the first supply line **18a**. The hydraulic fluid pressure entering the first hydraulic inlet **320A** forces the outer piston assembly **321** and the inner piston assembly **322** downward causing corresponding downward movement of the valve cage **323** which rotates the ball valve element **324** to an open position. To rotate the ball valve element **324** to a closed position, the pressure supplied to the first hydraulic inlet **320A** is reduced and the ball valve closure spring **325** shifts the valve cage **323** upwards. In this manner, repeated opening and closing of the ball valve element **324** can be accomplished.

If an emergency condition dictates that the well be shut in, the pressure supplied by the main control line **18** can be varied to exceed predetermined switching parameters which act to switch the first hydraulic distributor **1** to its second position. In its second position, the hydraulic distributor **1** prevents flow to the first supply line **18a** while enabling hydraulic fluid pressure to the second supply line **18b**. In its second position, the hydraulic distributor **1** facilitates hydraulic fluid pressure to the second hydraulic distributor **2**. Assuming the

second hydraulic distributor **2** is in its first position, hydraulic fluid pressure is supplied to the second hydraulic inlet **320B** which acts to force the valve cage **323** upwards with adequate force to cause the ball valve element **324** to cut the wireline or cable.

Additionally, by varying the hydraulic fluid pressure supplied by the main control line **18** to a pressure value that does not exceed the predetermined switching parameters of the first hydraulic distributor **1**, but does exceed the predetermined switching parameters of the second hydraulic distributor **2**, the hydraulic fluid pressure can be provided by the second hydraulic distributor **2** to the third hydraulic inlet **320C**. As discussed above, supplying hydraulic fluid pressure to the third hydraulic inlet **320C** acts to release the control unit **326** from the valve assembly **327**.

Thus, by varying the hydraulic fluid pressure supplied by the main control line **18**, the first hydraulic distributor **1** can be used to open and close the ball valve element **324**, and also used to control a second hydraulic distributor **2** that provides hydraulic fluid pressure to additional hydraulic inlets **320B**, **320C**. In this way, the subsea control valve apparatus **320** can be oscillated between pressure states by a single control line **18**.

It should be noted that in an alternate embodiment, tags and sensors are used to advantage on each hydraulic distributor. The sensors transmit information to the control surface by electrical lines, fiber optic lines, or the like. The transmitted information details the present position of each distributor and the pressure it is being subjected to. The information provided by the sensors ensures efficient manipulation of the hydraulic distributors from the single control line.

It should be noted that for discussion purposes, the hydraulic distributors **1**, **2** are shown in Fig. 18A as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributors **1**, **2** as being external to the subsea control valve **320**. The hydraulic distributors **1**, **2** can also be provided on or in a wall of the subsea control valve **320** or be provided on or in a wall of a tool string to which the subsea control valve **310** is a part of, for example.

Figs. 19A and 19B are elevational views, of an embodiment of the present invention wherein the hydraulic distributor **1** (shown as a diagrammatic sketch) is used to advantage to control a variable orifice gas lift valve **330** such as that disclosed in U.S. Pat. No. 5,971,004 to Pringle. The hydraulically operated gas lift valve **330** is comprised of a lower hydraulic actuating piston **331** operatively connected to a moveable piston **332**, which is operatively connected to a variable orifice valve **333** and an upper hydraulic actuating piston **334**. A spring **335** biases the moveable piston **332** thereby biasing the variable orifice valve **333** to a closed position. Hydraulic inlets **336a** and **336b** supply hydraulic pressure to the lower and upper hydraulic actuating pistons **331**, **334** to move the pistons **331**, **334** upward thereby opening the variable orifice valve **333**.

A hydraulic distributor **1** (shown in Fig. 19A) receives flow from a main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the first hydraulic inlet **336a** through the first supply line **18a**. The hydraulic fluid pressure entering the hydraulic inlet **336a** forces the lower hydraulic actuating piston **331** upward which acts to open the variable orifice valve **333**.

The second supply line **18b** of the hydraulic distributor **1** is in communication with the second hydraulic inlet **336b**. Thus, varying the flow from the main control line **18** to switch the hydraulic distributor **1** from its first position to its second position, acts to supply hydraulic fluid pressure to the second hydraulic inlet **336b** which forces the upper hydraulic actuating piston **334** upward to open the variable orifice valve **333**.

By use of two independent pistons **331**, **334** with varying strokes, the variable orifice valve **333** can be fully opened or opened to an intermediate position to control the fluid flow therethrough. By using the hydraulic distributor **1** to control the flow to one or the other hydraulic inlets **336a**, **336b**, the full opening, partial opening, and closing of the variable orifice valve **333** can be accomplished by varying the flow supplied to a single control line **18**.

It should be noted that for discussion purposes, the hydraulic distributor **1** is shown in Figs. 19A and 19B as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributor **1** as being external to the gas lift valve **330**. The hydraulic distributor **1** can also be provided on or in a wall of the gas lift valve **330** or be provided on or in a wall of a tool string to which the gas lift valve **330** is a part of, for example.

Fig. 20 is a diagrammatic sketch of an embodiment of the present invention wherein the hydraulic distributor **1** is used to advantage to control a hydraulically actuated lock pin assembly **340** such as that disclosed in U.S. Pat. No. 4,770,250 to Bridges et al. The lock pin assembly **340** is for locking a pipe hanger **341** to a wellhead **342**. Application of hydraulic fluid pressure to a hydraulic inlet **343** forces a piston **344** inward which, in turn, forces a lock pin **345** to wedge tightly against the pipe hanger **341** to provide a lock down force. The lock down force is relieved by bleeding off the pressure supplied to the hydraulic inlet **343** and lock pin **345** is returned to its initial position by the bias of a spring **346**.

In Fig. 20, a hydraulic distributor **1** receives flow from a main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the hydraulic inlet **343** through the first supply line **18a**. The hydraulic fluid pressure entering the hydraulic inlet **343** actuates the piston **344** which, in turn, forces the lock pin **345** to wedge tightly against the pipe hanger **341**. Bleeding off the pressure from the main control line **18**, in combination with the bias of the spring **346**, acts to return the lock pin **345** to its initial position. In this manner, repeated locking and releasing of the pipe hanger **341** can be accomplished.

An additional hydraulic device **201** can also be actuated by the hydraulic distributor **1**. As discussed earlier, by varying the pressure supplied by the main control line **18** to exceed predetermined switching parameters, the hydraulic distributor **1** can be switched from its first position to its second position. In its second position, the hydraulic distributor **1** prevents flow to the first supply line

18a while enabling hydraulic fluid pressure to the second supply line **18b**. In its second position, the hydraulic distributor **1** facilitates hydraulic fluid pressure to an additional hydraulic device **201**.

Thus, by varying the hydraulic fluid pressure supplied by the main control line **18**, the hydraulic distributor **1** can be used to advantage to supply hydraulic fluid pressure to one or more hydraulic devices. The hydraulic distributor **1** only switches position upon exceeding predetermined switching pressure values, therefore, the flow to one or the other device can be varied without premature switching of the position of the distributor **1**. In this way, individual devices can be oscillated between pressure states and one or more devices can be remotely controlled by a single control line **18**.

It should be noted that for discussion purposes, the hydraulic distributor **1** is shown in Fig. 20 as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributor **1** as being external to the lock pin assembly **340**. The hydraulic distributor **1** can also be provided on or in a wall of the lock pin assembly **340** or be provided on or in a wall of a tool string to which the lock pin assembly **340** is a part of, for example.

Fig. 21 is a cross-sectional view of an of an embodiment of the present invention wherein the hydraulic distributor **1** (shown as a diagrammatic sketch) is used to advantage to control a resettable packer **350** such as that disclosed in U.S. Pat. No. 6,012,518 to Pringle. The resettable packer **350** receives hydraulic fluid pressure from three hydraulic inlets **350A**, **350B**, and **350C**. Hydraulic fluid pressure received by the first hydraulic inlet **350A** enables movement of a double acting piston **351**, which drives a wedge **352** under a set of slips **353** thereby setting the packer **350**. Hydraulic fluid pressure received by the second hydraulic inlet **350B** enables the reverse movement of the double acting piston **351**, which removes the wedge **352** from under the slips **353** thereby unsetting the packer **350**. Finally, hydraulic fluid pressure received by the third hydraulic inlet **350C** enables movement of a ratcheted piston **354** axially downward, coacting with the double acting piston **351**, which drives the wedge **352** under the slips **353** thereby permanently setting the packer **350**.

The embodiment of the present invention shown in Fig. 21, utilizes two hydraulic distributors **1**, **2** to supply hydraulic fluid pressure to the three hydraulic inlets **350A**, **350B**, **350C** from a single control line **18**. The first hydraulic distributor **1** receives flow from the main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the first hydraulic inlet **350A** through the first supply line **18a**. The hydraulic fluid pressure entering the first hydraulic inlet **350A** enables movement of a double acting piston **351**, which drives the wedge **352** under the set of slips **353** thereby setting the packer **350**.

To unset the packer **350**, the hydraulic fluid pressure supplied by the main control line **18** can be varied to exceed predetermined switching parameters which act to switch the first hydraulic distributor **1** to its second position. In its second position, the hydraulic distributor **1** prevents flow to the first supply line **18a** while enabling hydraulic fluid pressure to the second supply line **18b**. In its second position, the hydraulic distributor **1** facilitates hydraulic fluid pressure to the second hydraulic distributor **2**. Assuming the second hydraulic distributor **2** is in its first position, hydraulic fluid pressure is supplied to the second hydraulic inlet **350B** which enables the reverse movement of the double acting piston **351**, which removes the wedge **352** from under the slips **353** thereby unsetting the packer **350**.

Additionally, by varying the hydraulic fluid pressure supplied by the main control line **18** to a pressure value that does not exceed the predetermined switching parameters of the first hydraulic distributor **1**, but does exceed the predetermined switching parameters of the second hydraulic distributor **2**, the hydraulic fluid pressure can be provided by the second hydraulic distributor **2** to the third hydraulic inlet **350C**. As discussed above, supplying hydraulic fluid pressure to the third hydraulic inlet **350C** acts to permanently set the packer **350**.

Thus, by varying the hydraulic fluid pressure supplied by the main control line **18**, the first and second hydraulic distributors **1**, **2** can be used to set and

unset the packer **350**, as well as permanently set the packer **350**. In this way, the resettable packer **350** can be set and reset by a single control line **18**.

It should be noted that for discussion purposes, the hydraulic distributor **1** is shown in Fig. 21 as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributor **1** as being external to the resettable packer **350**. The hydraulic distributor **1** can also be provided on or in a wall of the resettable packer **350** or be provided on or in a wall of a tool string to which the resettable packer **350** is a part of, for example.

Figs. 22A – 22D are continuations of each other and are elevational views, in quarter section, of an embodiment of the present invention wherein the hydraulic distributor **1** (shown as a diagrammatic sketch) is used to advantage to control a safety valve **360** such as that disclosed in U.S. Pat. No. 4,660,646 to Blizzard. The safety valve **360** is comprised of an actuating piston **361** maneuverable by hydraulic fluid pressure supplied to hydraulic inlet ports **362A**, **362B**. Application of hydraulic fluid pressure to the first hydraulic inlet port **362A** forces the piston **361** downward, which acts to open the flapper valve **363**. Application of hydraulic fluid pressure to the second hydraulic inlet port **362B** forces the piston **361** upward, which acts to close the flapper valve **363**.

A hydraulic distributor **1** (shown in Fig. 22A) receives flow from a main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the first hydraulic inlet **362A** through the first supply line **18a**. The hydraulic fluid pressure entering the first hydraulic inlet **362A** forces the actuating piston **361** downward, which acts to open the flapper valve **363**. Varying the flow from the main control line **18** to switch the hydraulic distributor **1** from its first position to its second position, acts to supply hydraulic fluid pressure to the second hydraulic inlet **362B** which forces the actuating piston **361** upward to open the flapper valve **363**. In this manner, the safety valve **360** can be opened and closed by hydraulic fluid pressure supplied by a single control line **18**.

It should be noted that for discussion purposes, the hydraulic distributor **1** is shown in Fig. 22A as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributor **1** as being external to the safety valve **360**. The hydraulic distributor **1** can also be provided on or in a wall of the safety valve **360** or be provided on or in a wall of a tool string to which the safety valve **360** is a part of, for example.

Figs. 23A – 23B are sectional views of an embodiment of the present invention wherein the hydraulic distributor **1** (shown as a diagrammatic sketch) is used to advantage to control a formation isolation valve (FIV) **370** such as that disclosed in U.S. Pat. No. 6,085,845 to Patel et al. Fig. 23A illustrates the FIV valve in its open position and Fig. 23B illustrates the FIV valve in its closed position. The FIV valve **370** is comprised of an actuating piston **371** maneuverable by fluid pressure supplied to a fluid inlet port **372**. Although the fluid utilized by the '845 patent is gas, hydraulic fluid pressure can also be used to advantage. Application of hydraulic fluid pressure to the fluid inlet port **372** forces the piston **371** downward, which acts to open the valve element **373**. Bleeding off the pressure supplied to the fluid inlet port **372** enables the piston **371** to return to its upper position in which the valve element **373** is closed.

In Fig. 23A, a hydraulic distributor **1** receives flow from a main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the fluid inlet port **372** through the first supply line **18a**. The hydraulic fluid pressure entering the hydraulic inlet **372** forces the actuating piston **371** downward and the valve element **373** is opened.

In Fig. 23B, the pressure supplied by the main control line **18** is varied to exceed a predetermined switching parameter, and the hydraulic distributor **1** is switched from its first position to its second position. In its second position, the hydraulic distributor **1** prevents flow to the first supply line **18a** while enabling hydraulic fluid pressure to the second supply line **18b**. The fluid pressure supplied to the fluid inlet port **372** is thus bled off and the actuating piston **371**

returns to its upper position in which the valve element **373** is closed. At the same time, the hydraulic distributor **1** can now supply hydraulic fluid pressure to an additional hydraulic device **201**.

Thus, by varying the hydraulic fluid pressure supplied by the main control line **18**, the hydraulic distributor **1** can be used open and close the FIV valve **370**, and can be used to control an additional hydraulic device **201**. All such controls are performed by varying hydraulic fluid pressure supplied by a single control line **18**.

It should be noted that for discussion purposes, the hydraulic distributor **1** is shown in Figs. 23A and 23B as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributor **1** as being external to the formation isolation valve **370**. The hydraulic distributor **1** can also be provided on or in a wall of the formation isolation valve **370** or be provided on or in a wall of a tool string to which the formation isolation valve **370** is a part of, for example.

Figs. 24A – 24C are continuations of each other and form an elevational view in cross section of an embodiment of the present invention wherein the hydraulic distributor **1** (shown as a diagrammatic sketch) is used to advantage to control an emergency disconnect tool **380** such as that disclosed in U.S. Pat. No. 5,323,853 to Leismer et al. The emergency disconnect tool **380** can be used to disconnect a tool from a drilling assembly by hydraulic or electrical actuation. The hydraulic actuation is performed by supplying hydraulic fluid pressure to the inlet port **381** sufficient to overcome a rupture disk **382**. Rupture of the disk **382** allows the hydraulic fluid to move the piston **383** thereby moving the sleeve **384** upwardly, shearing the C-ring **385**, moving the locking shoulder **386** from behind the dogs **387**, and the aligning recess **388** with the dogs **387**, thereby releasing the tool parts **388A**, **388B**.

A hydraulic distributor **1** (shown in Fig. 24A) receives flow from a main control line **18**. Assuming the hydraulic distributor **1** is in its first position in which the hydraulic fluid pressure is able to flow to a first supply line **18a** and prevented from flowing to a second supply line **18b**, the flow is carried to the fluid inlet port **381** through the first supply line **18a**. The hydraulic fluid pressure entering the

inlet port **381** ruptures the rupture disk **382** allowing the hydraulic fluid to move the piston **383** thereby moving the sleeve **384** upwardly, shearing the C-ring **385**, moving the locking shoulder **386** from behind the dogs **387**, and aligning the recess **388** with the dogs **387**, thereby releasing the tool parts **388A** and **388B**.

As discussed earlier, by varying the hydraulic fluid pressure supplied by the main control line **18**, the hydraulic distributor **1** can be switched to a second position in which an additional hydraulic device **201** is controlled. Thus, the hydraulic distributor **1** can be used to actuate the emergency disconnect tool **380** and control an additional hydraulic device **201** by varying hydraulic fluid pressure supplied by a single control line **18**.

It should be noted that for discussion purposes, the hydraulic distributor **1** is shown in Fig. 24A as a diagrammatic sketch. The sketch is not intended to limit the location of the hydraulic distributor **1** as being external to the emergency disconnect tool **380**. The hydraulic distributor **1** can also be provided on or in a wall of the emergency disconnect tool **380** or be provided on or in a wall of a tool string to which the emergency disconnect tool **380** is a part of, for example.

The above embodiments of the present invention are exemplary of the applications of the present invention and are not limiting on the scope of the present invention. The present invention can be used to advantage to provide any number of hydraulic devices, tools and actuators with hydraulic fluid pressure supplied by a single control line. For example, Fig. 25 provides a diagrammatic sketch further demonstrating the hydraulic distributor **1** of the present invention used to advantage to control multiple tools and multiple other hydraulic distributors from a single control line.

As shown in Fig. 25, flow from a pump is carried through a main control line **18** to a first distributor **1**. Depending upon the pressure of the hydraulic fluid pressure and the position of the shuttle sleeve **60** within the first hydraulic distributor **1**, the flow is directed through one of the outlet ports **20a**, **20b** to a second distributor **2** or a third distributor **3**. If the flow from the main control line **18** is directed from the first distributor **1** to the second distributor **2**, then depending upon the pressure of the hydraulic fluid pressure and the position of

the shuttle sleeve **60** within the second hydraulic distributor **2**, the flow is distributed to a first hydraulic device **201** or a second hydraulic device **202**. Likewise, if the flow from the main control line **18** is directed from the first distributor **1** to the third distributor **3**, then depending upon the hydraulic fluid pressure and the position of the shuttle sleeve **60** within the third hydraulic distributor **3**, the flow is distributed to a third hydraulic device **203** or a fourth hydraulic device **204**. In this way, several tools and distributors can be operated by altering the hydraulic fluid pressure through a single control line **18**.

Likewise, Figs. 25A, 25B, and 25C display additional exemplary configurations whereby the present invention is utilized to control additional distributors and tools. In Fig. 25A, the first distributor **1** is used control a first hydraulic device **201** and a second distributor **2** that controls a second device **202** and a third device **203**. In Fig. 25B, a first distributor **1** is used to control a second distributor **2** and a third distributor **3** that are used in combination to control a single hydraulic device **201**. Fig. 25C illustrates a first distributor **1** used to control a second distributor **2** that control a first hydraulic device **201**, and used to control a third distributor **3** that controls a second hydraulic device **202** and a third hydraulic device **203**. It should be noted that the above configurations are illustrative and exemplary and not intended to limit the scope of the present invention. The hydraulic distributor **1** of the present invention can be used in any number of configurations to control any number of other distributors and other tools.

The invention being thus described, it will be obvious that the same may be varied in many ways. As one example, in an illustrated embodiment of the hydraulic distributor **1** of the present invention, the shuttle sleeve **60** is biased towards its upper position by a shuttle sleeve spring **62** and maneuvered to its lower position by the same. However, other means such as gas charges, or hydraulic actuators can be used to advantage to accomplish the same. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following non-limiting claims.

We claim:

1. A hydraulic distributor, comprising:

(a) an inlet connected to a hydraulic control line supplying hydraulic fluid pressure,

(b) at least one primary outlet and at least one secondary outlet, and

(c) a valve having a first position in which the hydraulic fluid pressure is restricted from the at least one primary outlet, and having a second position in which the hydraulic fluid pressure is restricted from the at least one secondary outlet, the valve maneuverable between its first position and its second position by the hydraulic fluid pressure.

2. The hydraulic distributor of claim 1, wherein the hydraulic fluid pressure controls one or more hydraulic devices.

3. The hydraulic distributor of claim 2, wherein the one or more hydraulic devices are selected from sleeve valves, ball valves, packers, formation isolation valves, gas lift valves, locks, sliding sleeves, and hydraulic distributors.

4. The hydraulic distributor of claim 2, wherein the hydraulic distributor is provided in a wall of the one or more hydraulic devices.

5. The hydraulic distributor of claim 2, wherein the hydraulic devices are part of a tool string.

6. The hydraulic distributor of claim 5, wherein the hydraulic distributor is provided in a wall of the tool string.

7. The hydraulic distributor of claim 1, wherein the valve is moved between its first and second positions by a mandrel.

8. The hydraulic distributor of claim 7, wherein the mandrel is manipulated by hydraulic pressure.

9. The hydraulic distributor of claim 7, wherein the mandrel is manipulated mechanically.

10. The hydraulic distributor of claim 7, further comprising an indexer assembly moveable through a plurality of positions to manipulate the mandrel.

11. The hydraulic distributor of claim 7, further comprising a lock assembly to fixedly engage the mandrel.

12. A hydraulic distributor, comprising:

(a) an inlet port adapted for receipt of hydraulic pressure,

(b) one or more first outlet ports and one or more second outlet ports,

(c) a valve, and

(d) a mandrel having a first position and a second position, the mandrel affixed to the valve such that, with the mandrel in its first position, the valve restricts the hydraulic pressure to the one or more first outlet ports and with the mandrel in its second position, the valve restricts the hydraulic pressure to the one or more second outlet ports, the mandrel moveable between its first position and its second position by the hydraulic pressure.

13. The hydraulic distributor of claim 12, wherein the hydraulic pressure controls one or more hydraulic devices.

14. The hydraulic distributor of claim 13, wherein the one or more hydraulic devices are selected from sleeve valves, ball valves, packers, formation isolation valves, gas lift valves, locks, sliding sleeves, and hydraulic distributors.

15. The hydraulic distributor of claim 13, wherein the hydraulic distributor is provided in a wall of the one or more hydraulic devices.

16. The hydraulic distributor of claim 13, wherein the hydraulic devices are part of a tool string.

17. The hydraulic distributor of claim 16, wherein the hydraulic distributor is provided in a wall of the tool string.

18. The hydraulic distributor of claim 12, wherein the mandrel is manipulated mechanically.

19. The hydraulic distributor of claim 12, further having a lock assembly hydraulically activated to fixedly engage the mandrel.

20. The hydraulic distributor of claim 12, further having an indexing assembly for manipulating the mandrel.

21. A hydraulic distributor, comprising:

(a) a housing defining an inlet and a plurality of outlets,

(b) a valve moveably positioned in the housing adapted to selectively close the plurality of outlets, and

(c) a pressure responsive indexer connected to the valve adapted to control the position of the valve.

22. The hydraulic distributor of claim 21, wherein the pressure responsive indexer has a mandrel affixed to the valve.

23. The hydraulic distributor of claim 22, wherein the pressure responsive indexer has a lock assembly to fixedly engage the mandrel.

24. The hydraulic distributor of claim 22, wherein the pressure responsive indexer has an indexer assembly to manipulate the mandrel.

25. The hydraulic distributor of claim 22, wherein the pressure responsive indexer is activated mechanically.

26. A hydraulic distributor, comprising:

(a) a housing defining an inlet connected to a hydraulic control line and at least one outlet, the inlet adapted for receipt of pressurized fluid from the hydraulic control line;

(b) a valve moveably positioned in the housing adapted to selectively close the at least one outlet to selectively control the flow of pressurized fluid from the inlet to the at least one outlet; and

(c) an indexer connected to the valve adapted to control the position of the valve in response to the pressurized fluid.

27. The hydraulic distributor of claim 26, wherein the at least one outlet is in communication with the one or more hydraulic devices.

28. The hydraulic distributor of claim 27, wherein the one or more hydraulic devices are selected from sleeve valves, ball valves, packers, formation isolation valves, gas lift valves, locks, sliding sleeves, and hydraulic distributors.

29. The hydraulic distributor of claim 27, wherein the hydraulic distributor is provided in a wall of the one or more hydraulic devices.

30. The hydraulic distributor of claim 27, wherein the hydraulic devices are part of a tool string.

31. The hydraulic distributor of claim 30, wherein the hydraulic distributor is provided in a wall of the tool string.

32. The hydraulic distributor of claim 26, wherein the valve is moveably positioned by a mandrel.

33. The hydraulic distributor of claim 32, wherein the mandrel is manipulated by hydraulic pressure.

34. The hydraulic distributor of claim 32, wherein the mandrel is manipulated mechanically.

35. The hydraulic distributor of claim 32, further comprising an indexer assembly moveable through a plurality of positions to manipulate the mandrel.

36. The hydraulic distributor of claim 32, further comprising a lock assembly to fixedly engage the mandrel.

37. A method of distributing a hydraulic fluid, comprising:

(a) providing a pressure responsive toggle valve having an inlet and a plurality of outlets;

(b) changing the pressure supplied to the inlet to shift the toggle valve to selectively close at least one of the plurality of outlets.

38. A method of providing hydraulic fluid pressure from a single source to a plurality of hydraulic devices , the method comprising:

(a) providing a hydraulic distributor having an inlet port and one or more first outlet ports and one or more second outlet ports,

(b) supplying hydraulic fluid pressure to the inlet port sufficient to activate the hydraulic distributor to prevent the flow of hydraulic fluid pressure to the one or more first outlet ports,

(c) varying the hydraulic fluid pressure supplied to the inlet port to activate the hydraulic distributor to prevent the flow of hydraulic fluid pressure to the one or more second outlet ports.

39. A system for distributing a hydraulic fluid, comprising:

(a) a hydraulic control line;

(b) a distributor having an inlet in fluid communication with the hydraulic control line;

(c) the distributor comprising at least two outlets and a valve moveable in the distributor to control the flow from the inlet to the at least two outlets;

(d) the valve shiftable in response to pressure supplied to the inlet.

40. The system of claim 39, wherein the valve is mechanically shiftable.

41. A system for distributing a hydraulic fluid, comprising:

(a) a hydraulic control line;

(b) a first distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the hydraulic control line;

(c) a second distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the at least one first outlet of the first distributor, the at least one first outlet in communication with a first hydraulic device, and the at least one second outlet in communication with a second hydraulic device; and

(d) a third distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the at least one second outlet of the first distributor, the at least one first outlet in communication with a third hydraulic device, and the at least one second outlet in communication with a fourth hydraulic device.

42. A system for distributing a hydraulic fluid, comprising:

(a) a hydraulic control line;

(b) a first distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the hydraulic control line, and the at least one first outlet in communication with a first hydraulic device; and

(c) a second distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the at least one second outlet of the first distributor, the at least one first outlet in communication with a second hydraulic device, and the at least one second outlet in communication with a third hydraulic device.

43. A system for distributing a hydraulic fluid, comprising:

(a) a hydraulic control line;

(b) a first distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the hydraulic control line;

(c) a second distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the at least one first outlet of the first distributor, the at least one first outlet in communication with a hydraulic device, and the at least one second outlet in communication with the hydraulic device; and

(d) a third distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the at least one second outlet of the first distributor, the at least one first outlet in communication with the hydraulic device, and the at least one second outlet in communication with the hydraulic device.

44. A system for distributing a hydraulic fluid, comprising:

(a) a hydraulic control line;

(b) a first distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the hydraulic control line;

(c) a second distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the at least one first outlet of the first distributor, the at least one first outlet in communication with a first hydraulic device, and the at least one second outlet in communication with the first hydraulic device; and

(d) a third distributor having at least one inlet, at least one first outlet, and at least one second outlet, the at least one inlet in communication with the at least one second outlet of the first distributor, the at least one first outlet in communication with a second hydraulic device, and the at least one second outlet in communication with a third hydraulic device.