

A POWER TRAIN FOR AN AMPHIBIAN

5 The present invention relates to a power train particularly
suitable for use in an amphibian capable of travel on land and
water. More particularly, the power train is suitable for use in
a high speed amphibian with at least one retractable wheel and
which is capable of planing on water. The present invention also
relates to an amphibian having such a power train.

10

Power trains for use in amphibians are known in the art.
These generally fall in into one of two categories. The first
are power trains for use in displacement only amphibians which
have limited and slow on-water performance. These are generally
15 automotive power trains modified to provide drive to a marine
propulsion means. The second category are power trains for use
in planing amphibians which suffer from limited on-land
performance. These are generally marine power trains modified to
provide drive to a wheel or track.

20

More recently, however, the applicant has developed power
trains for use in a new class of high speed amphibians having at
least one retractable wheel and which are capable of planing on
water. Furthermore, these high speed amphibians provide for good
25 road handling when the amphibian is operated on land or off-road
(e.g. in four wheel drive).

There remains, however, a need to improve on these prior
art power trains by providing increased flexibility in the
30 delivery of drive and power to the retractable land propulsion
means (e.g. wheels, track drives, etc.) for use of the amphibian
on land, and to the marine propulsion means (e.g. jet drives,
propellers, etc.) for use of the amphibian on water. The need to
retract wheels and/or wheel suspension assemblies or track drives
35 presents significant problems in terms of packaging, weight
distribution and also in terms of how the resulting power
transmission pathways can be realised.

The present invention provides a power train which can

deliver power to any one or more of at least one, two, three or four (or more) retractable wheel assemblies (i.e. can operate in 1, 2, 3 or 4 (or more) wheel drive), and can deliver power to any one or more of at least one or two (or more) marine propulsion means (e.g. jet drives). Furthermore, the power train according to the present invention provides this capability with at least one or two (or more) prime movers so as to enable selective and controllable engagement and delivery of power from the or each prime mover to a multitude of combinations of the individual or pluralities of retractable wheel and/or track drive assemblies and jet drives or other marine propulsion means available for use. This has the very important effect of providing for redundancy capability in the event of component failures in the power train. In addition, it provides unique drive options in the case of particular conditions experienced (e.g. in a four wheel amphibian, left hand 2 wheel drive - front and rear - where ground is particularly soft or slippery on, say, the right hand side) and also of optimising and efficiently delivering power matched to the torque curve of the prime mover(s). While it is routine to have two prime movers in boats of over 10m in length, a power train according to the present invention has not hitherto been thought possible in an amphibian due to the complexities of delivering power around such a complicated array of individual components, including the land and marine propulsion means (e.g. wheels/track drives and jet drives). A particular problem is in respect of how to achieve the required transmission.

Accordingly, in a first aspect, the present invention provides a power train for an amphibian, the power train comprising:

- a first prime mover;
- a first land propulsion means; and
- a first marine propulsion means, wherein:
 - the first prime mover is arranged to selectively drive the first land propulsion means, or the first marine propulsion means, or both, characterised in that the power train further comprises:
 - a second prime mover, wherein:

the second prime mover is arranged to selectively drive the first land propulsion means, or the first marine propulsion means, or both, either in place of the first prime mover or in addition thereto.

5

In a further aspect, the present invention provides a power train for an amphibian, the power train comprising:

a first prime mover;

a first speed change transmission;

10

a first land propulsion means; and

a first marine propulsion means, wherein:

the first prime mover is arranged to selectively drive the first land propulsion means, or the first marine propulsion means, or both, optionally through the first speed change transmission, characterised in that the power train further comprises:

15

a second prime mover;

a second speed change transmission;

a second land propulsion means; and

20

a second marine propulsion means, wherein:

the second prime mover is arranged to selectively drive the first and/or second land propulsion means, or the first and/or second marine propulsion means, or any combination thereof, optionally through the second and/or first speed change transmission, and

25

the first prime mover is additionally arranged to selectively drive the second land propulsion means, the second marine propulsion means, or both, optionally through the first and/or second speed change transmission.

30

In a further aspect, the present invention provides a power train for an amphibian, the power train comprising:

a first prime mover;

a first speed change transmission;

35

a first land propulsion means; and

a first marine propulsion means, wherein:

the first prime mover is arranged to selectively drive the first land propulsion means, or the first marine propulsion

means, or both, through the first speed change transmission,
characterised in that the power train further comprises:

- a second prime mover;
- a second speed change transmission;
- 5 a second land propulsion means; and
- a second marine propulsion means, wherein:

the second prime mover is arranged to selectively drive the
second land propulsion means, or a second marine propulsion
means, or both, through the second speed change transmission.

10

In a further aspect, the present invention provides a power
train for an amphibian, the power train comprising:

- a first prime mover;
- a first land propulsion means; and
- 15 a first marine propulsion means, wherein:

the first prime mover is arranged to selectively drive the
first land propulsion means, or the first marine propulsion
means, or both, characterised in that the power train further
comprises:

20

- a second marine propulsion means, wherein:

the first prime mover is arranged to selectively drive the
second marine propulsion means either in place of the first
marine propulsion means or in addition thereto.

25

In a further aspect, the present invention provides an
amphibian comprising the power train as set forth herein.

Preferred embodiments of the present invention will now be
described by way of example only with reference to the
30 accompanying drawings, in which:

Figure 1 is a schematic plan view from above of a power
train according to the present invention;

Figure 2 is a schematic perspective view from above and to
one side of the arranged components of the power train of Figure
35 1 (wheels shown indicatively only by dotted lines); and

Figure 3 is a further schematic plan view from above of a
power train according to the present invention, particularly as
illustrated in Figure 2, located in a hull of an amphibian

(certain components omitted for clarity).

Referring first to Figures 1 and 2, power train 10 can be seen to comprise:

- 5 two prime movers, port engine 20 and starboard engine 40;
- two variable speed transmissions, port variable speed transmission 22 and starboard variable speed transmission 42;
- two power take offs, port power take off 24 and starboard power take off 44;
- 10 two marine propulsion units, port water jet drive 27 and starboard water jet drive 47;
- two marine propulsion drive shafts, port water jet drive shaft 28 and starboard water jet drive shaft 48;
- two land propulsion drive shafts, front land propulsion drive shaft 30 and rear land propulsion drive shaft 50;
- 15 two differentials, front differential 32 and rear differential 52;
- four half (axle) shafts, port and starboard front half shafts 34, 35 and port and starboard rear half shafts 54, 55; and
- 20 four wheels, port and starboard front wheels 36, 37 and port and starboard rear wheels 56, 57.

Port variable speed transmission 22 comprises an input shaft 21 driven by port engine 20, and an output shaft 23 which provides drive to the input or input shaft 25 of port power take off 24 and on through to port water jet drive shaft 28. Port variable speed transmission 22 may comprise a manual, sequential shift, semiautomatic, or automatic gearbox, or a continuously variable transmission (CVT). Port power take off 24, located between port variable speed transmission 22 and port water jet drive shaft 28, transfers drive from the input or input shaft 25 to the output or output shaft 26. Port power take off 24 may be of any suitable type, for example, a belt drive, chain drive or gear drive. The ratio of drive between input or input shaft 25 and output or output shaft 26 of port power take off 24 may be 1:1 or may be another ratio selected to suit the particular arrangement or operating conditions. In this latter case, the change in ratio provided by the port power take off 24 may be

variable and selectable, e.g. by way of a continuously variable transmission (CVT) or by way of another variable speed change transmission. Indeed, this may obviate the need for port variable speed transmission 22. The output or output shaft 26 of
5 port power take off 24 provides drive to front land propulsion drive shaft 30 which runs forward in the amphibian towards the bow to front differential 32. In turn, front differential 32 provides drive to port front half shaft 34 and starboard front half shaft 35, and on to respective port front wheel 36 and
10 starboard front wheel 37. Port water jet drive shaft 28 takes drive from port variable speed transmission 22 and on to port water jet 27 (directly as shown, or indirectly via other components and/or drive shafts).

15 Starboard variable speed transmission 42 comprises an input shaft 41 driven by starboard engine 40, and an output shaft 43 which provides drive to the input or input shaft 45 of starboard power take off 44 and on through to starboard water jet drive shaft 48. Similarly, starboard variable speed transmission 42
20 may comprise a manual, sequential shift, semiautomatic, or automatic gearbox, or a continuously variable transmission (CVT). Starboard power take off 44, located between starboard variable speed transmission 42 and starboard water jet drive shaft 48, transfers drive from the input or input shaft 45 to the output or
25 output shaft 46. Similarly, starboard power take off 44 may be of any suitable type, for example, a belt drive, chain drive or gear drive. Again, the ratio of drive between input shaft 45 and output shaft 46 of starboard power take off 44 may be 1:1 or may be another ratio selected to suit the particular arrangement or
30 operating conditions. In this latter case, the change in ratio of starboard power take off 44 may be variable and selectable, e.g. by way of a continuously variable transmission (CVT) or by way of another variable speed change transmission. Indeed, again, this may obviate the need for starboard variable speed
35 transmission 42. The output or output shaft 46 of starboard power take off 44 provides drive to rear land propulsion drive shaft 50 which runs rearward in the amphibian to rear differential 52. In turn, rear differential 52 provides drive to

port rear half shaft 54 and starboard rear half shaft 55, and on to respective port rear wheel 56 and starboard rear wheel 57. Starboard water jet drive shaft 48 takes drive from starboard variable speed transmission 42 and on to starboard water jet 47 (directly as shown, or indirectly via other components and/or drive shafts).

Decouplers and/or constant velocity joints (not shown) may be provided at any suitable point in the power train, and in any number, as required. For example, decouplers may be provided in the drive line between any/some/all of wheels 36, 37, 56, 57 and its associated driving half shaft 34, 35, 54, 55, between any/some/all of driving half shaft 34, 35, 54, 55 and respective front and/or rear differentials 32, 52, between front differential 32 and front land propulsion drive shaft 30 and/or front land propulsion drive shaft 30 and port power take off 24, between rear differential 52 and rear land propulsion drive shaft 50 and/or rear land propulsion drive shaft 50 and starboard power take off 44, between either/each port and starboard power take off 24, 44 and respective port and starboard water jet drive shafts 28, 48 (if connected, or if drive passes therethrough), between either/each port and starboard water jet drive shafts 28, 48 and respective water jets 27, 47, and/or between output or output shaft 26 of port power take off 24 and output or output shaft 46 of starboard power take off 44. This enables drive from the engines to the wheels and water jets to be selectively coupled and decoupled at will. However, such decouplers are not essential and can be omitted, or selected ones can be omitted. Where present, any suitable decoupler and associated actuation/control system may be employed. Constant velocity joints may be provided as necessary to provide tolerance for angular differences between components in the power train 10. In addition, constant velocity joints may be beneficially employed in wheel retraction for use of the amphibian on water in high speed planing mode and/or for steering.

In the preferred embodiment shown in the Figures, the marine propulsion units are water jets 27, 47, but screw

propellers or any other suitable marine propulsion means, system or combination may be employed.

5 The front and rear differentials 32, 52 transmit drive to
the respective front and rear wheels 36, 37, 56, 57 of the
10 amphibian via half (axle) shafts 34, 35, 54, 55 in a conventional
automotive manner, optionally via decouplers as discussed above.
However, an important distinction over known automotive four
wheel drive power trains is that no differential is required
15 between the front and rear axles, either when idling or when
driven. Optionally, however, a differential may be provided
between the front and rear axles.

15 In use, the power train 10 according to the present
invention is extremely flexible and versatile. It can be
operated in numerous different ways, these being selected by the
amphibian's control systems and/or by or with inputs from the
driver. In land mode (including ingress to and egress from the
water), the amphibian may be driven in one, two, three or four
20 wheel drive, and with various combinations of the individual
wheels and engines selected to provide drive. The marine
propulsion means may optionally be driven in land mode. In
marine mode, either one or both water jets may be used to provide
marine propulsion, and either one or both engines selected to
25 provide drive. By way of example only, the following table
indicates a number of the modes/options available in the
particular configuration shown in Figure 1:

	Mode	Wheel	Water Jet	Engine
L	Land			
1	1 wheel drive	Front port 36	Optional	Port 20
2	1 wheel drive	Front stbd 37	Optional	Port 20
3	1 wheel drive	Rear port 56	Optional	Stbd 40
4	1 wheel drive	Rear stbd 57	Optional	Stbd 40
5	2 wheel drive	Front port 36	Optional	Port 20
		Front stbd 37		

6	2 wheel drive	Rear port 56	Optional	Stbd 40
		Rear stbd 57		
7	2 wheel drive	Front port 36	Optional	Port 20
		Rear port 56		Stbd 40
8	2 wheel drive	Front stbd 37	Optional	Port 20
		Rear stbd 57		Stbd 40
9	2 wheel drive	Front port 36	Optional	Port 20
		Rear stbd 57		Stbd 40
10	2 wheel drive	Front stbd 37	Optional	Port 20
		Rear port 56		Stbd 40
11	4 wheel drive	Front port 36	Optional	Port 20
		Front stbd 37	Optional	Port 20
		Rear port 56	Optional	Stbd 40
		Rear stbd 57	Optional	Stbd 40
12	Ingress/Egress	Front port 36	Port 27	Port 20
		Front stbd 37		
13	Ingress/Egress	Rear port 56	Stbd 47	Stbd 40
		Rear stbd 57		
14	Ingress/Egress	Any, some, all	Port 27	Port 20
			and/or Stbd 47	Stbd 40
M	Marine			
15	Displacement	Optional	Port 27	Port 20
16	Displacement	Optional	Stbd 47	Stbd 40
17	Displacement	Optional	Port 27	Port 20
			Stbd 47	Stbd 40
18	Planing	None	Port 27	Port 20
19	Planing	None	Stbd 47	Stbd 40
20	Planing	None	Port 27	Port 20
			Stbd 47	Stbd 40

Of course, further modes/options are available with other configurations. The flexibility and versatility of the power train 10 according to the present invention is thus readily appreciated from the above. In particular, it will be

appreciated that on land, drive can be selected to suit the terrain or any particular obstacles encountered. For example, engine use can be balanced, or redundancy catered for, either on land in two wheel drive by using modes 5 to 10, or when on water
5 by using modes 15 to 20. Where the torque curve of the engines is relatively flat above a threshold (e.g. with diesel engines), the speed change transmissions provide for fuel efficient use of the engines. For example, mode 20 permits sufficient power to get up onto the plane with high revs (say 3800rpm, for example)
10 before easing back the throttles to, say, half revs (say 1900rpm, for example) when on the plane with suitable gear ratio selection using the speed change transmissions, thereby dramatically improving fuel efficiency.

15 The position of the port and starboard engines 20, 40 and other components in the power train 10 are ideally suited for a high speed amphibian, because the weight of these components is towards or biased towards the rear of the amphibian, a requirement for optimum marine performance. In addition, their
20 alignment generally in line with the longitudinal axis of the hull 100 of the amphibian (see Figure 3), either north-south or south north, assists in the simplicity and packaging of the power train 10 in the hull 100. However, the engines 20, 40 and other components need not be packaged in this way, as alternative
25 configurations are equally possible. For example, the engines may be arranged transversely side by side or one in-front/ahead of the other, with suitable arrangement of the other components.

Figure 3 shows a preferred hull 100 of an amphibian in
30 which a power train 10 according to the present invention (and particularly illustrated in Figure 2) is located. In Figure 3, exhaust system components 80 are also shown.

Retractable wheel and suspension assemblies (not shown) as
35 described in the applicant's patents and published patent applications are particularly suitable for use with the power train 10 of the present invention.

Whilst not shown, it will be appreciated from the foregoing that it is possible also to provide additional power transmission pathways by connecting the port and starboard components of the power train, for example, by inserting a differential, coupling or other connection between, say, the respective outputs or output shafts 26, 46 of the port and starboard power take offs 24, 44. In such a configuration, by way of example, port engine 20 may additionally or alternatively be used to provide drive to the output or output shaft 46 of starboard power take off 44 so as to provide drive to rear land propulsion drive shaft 50 and rear differential 52. In turn, rear differential 52 provides drive to port rear half shaft 54 and starboard rear half shaft 55, and on to respective port rear wheel 56 and starboard rear wheel 57. Furthermore, power from port engine 20 may additionally or alternatively be used to provide drive via starboard power take off 44 (or other driveline pathways) and on via the starboard water jet drive shaft 48 to the starboard water jet 47. Similarly, starboard engine 40 may additionally or alternatively be used to provide drive to the output or output shaft 26 of starboard power take off 24 so as to provide drive to forward land propulsion drive shaft 30 and front differential 32. In turn, front differential 32 provides drive to port front half shaft 34 and starboard front half shaft 35, and on to respective port front wheel 36 and starboard front wheel 37. Furthermore, power from starboard engine 40 may additionally or alternatively be used to provide drive via port power take off 24 (or other driveline pathways) and on via the port water jet drive shaft 28 to the port water jet 27.

Whilst the port and starboard power take offs 24, 44 are shown positioned after (behind) the port and starboard speed change transmissions 22, 42, these port and starboard power take offs 24, 44 may be positioned at other locations in the power train, as appropriate. For example, port and starboard power take offs 24, 44 may be located ("sandwiched") between the port and starboard engines 20, 40 and the port and starboard speed change transmissions 22, 42, or may be located ahead (in front) of the port and starboard engines 20, 40. Furthermore, drive may

be taken from the port and starboard engines 20, 40, port and starboard speed change transmissions 22, 42, and/or port and starboard power take offs 24, 44 in any suitable or beneficial way or re-configuration of these components. For example, port and starboard speed change transmissions 22, 42 may be dispensed with entirely. Port and starboard power take offs 24, 44 may then, or alternatively, be positioned after (behind) the port and starboard engines 20, 40. While decouplers have been described, components in the power train may be provided or supplied with integral decouplers, disconnects or locks (e.g. diff-locks) which can be used as appropriate. Furthermore, drive shafts may be single entities or formed from combinations of shorter drive shafts and/or stub shafts.

In view of all of the foregoing, the flexibility and versatility of the power train 10 according to the present invention is thus readily appreciated, as are the numerous different power train configurations and thus modes/options available in use. In a simple form, the present invention provides for:

i) a single prime mover, at least two land propulsion means (wheels and/or track drives) and at least two marine propulsion means (providing for redundancy in the land and marine propulsion means and/or optimisation of either or both in use).

The present invention also provides for:

ii) at least two prime movers, at least two land propulsion means (wheels and/or track drives) and a single marine propulsion means (providing for redundancy in the prime mover and land propulsion means and/or optimisation of either or both in use).

In its preferred form, the present invention provides for:

iii) at least two prime movers, at least two land propulsion means (wheels and/or track drives) and at least two marine propulsion means (providing for redundancy in the prime mover, land and marine propulsion means and/or optimisation of any or all in use).

Speed change transmissions, power take offs, drive shafts, differentials, decouplers and/or constant velocity joints (not shown) may be optionally be provided at any suitable point in the

power train configurations of i), ii) and iii), and in any number, as required.

5 Whilst wheels have been described throughout as the land propulsion means, track drives or individual track drives (i.e. to replace a single wheel) may be used as an alternative or in combination with wheels.

10 Furthermore, port and starboard engines 20, 40 may instead comprise electric, hydraulic, or hybrid engines. A stealth mode may be incorporated where the prime mover limits noise and heat emissions. For example, the port and starboard engines 20, 40 may incorporate motor generators which act as alternators to charge batteries, which charge is then used to power the vehicle
15 for periods of time in a stealth mode.

20 Each feature disclosed in this specification (including the accompanying claims, abstract and drawings), may be replaced by alternative features serving the same, equivalent or similar purpose, unless expressly stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is one example only of a generic series of equivalent or similar features. In addition, all of the features disclosed in this specification (including the accompanying claims, abstract and drawings),
25 and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive. Accordingly, while different embodiments of the present invention have been described above, any one or more or all of the features described, illustrated and/or claimed in the appended claims may
30 be used in isolation or in various combinations in any embodiment. As such, any one or more feature may be removed, substituted and/or added to any of the feature combinations described, illustrated and/or claimed. For the avoidance of
35 doubt, any one or more of the features of any embodiment may be combined and/or used separately in a different embodiment with any other feature or features from any of the embodiments.

Whereas the present invention has been described in
relation to what is presently considered to be the most practical
and preferred embodiments, it is to be understood that the
invention is not limited to the disclosed arrangements but rather
5 is intended to cover various modifications and equivalent
constructions included within the scope of the appended claims.

10

15

CLAIMS

1. A power train for an amphibian, the power train comprising:
5 a first prime mover;
a first land propulsion means; and
a first marine propulsion means, wherein:
the first prime mover is arranged to selectively drive the
first land propulsion means, or the first marine propulsion
10 means, or both, characterised in that the power train further
comprises:
a second prime mover, wherein:
the second prime mover is arranged to selectively drive the
first land propulsion means, or the first marine propulsion
15 means, or both, either in place of the first prime mover or in
addition thereto.
2. A power train as claimed in claim 1, the power train
further comprising a second land propulsion means, wherein the
20 second prime mover is arranged to selectively drive the second
land propulsion means, and the first prime mover is arranged to
selectively drive the second land propulsion means, either in
place of the second prime mover or in addition thereto.
- 25 3. A power train as claimed in claim 1 or claim 2, the power
train further comprising a second marine propulsion means,
wherein the second prime mover is arranged to selectively drive
the second marine propulsion means, and the first prime mover is
arranged to selectively drive the second marine propulsion means,
30 either in place of the second prime mover or in addition thereto.
4. A power train as claimed in any one of the preceding
claims, the power train further comprising a first and/or a
second speed transmission, and wherein the first and/or second
35 prime mover is arranged to selectively drive any one or more of
the first land propulsion means and the first marine propulsion
means through the first and/or second speed transmission.

5. A power train as claimed in claim 3, the power train further comprising a first and/or a second speed transmission, and wherein the first and/or second prime mover is arranged to selectively drive any one or more of the first and/or second land
5 propulsion means and the first and/or second marine propulsion means through the first and/or second speed transmission.

6. A power train for an amphibian, the power train comprising:
a first prime mover;
10 a first speed change transmission;
a first land propulsion means; and
a first marine propulsion means, wherein:
the first prime mover is arranged to selectively drive the first land propulsion means, or the first marine propulsion
15 means, or both, optionally through the first speed change transmission, characterised in that the power train further comprises:
a second prime mover;
a second speed change transmission;
20 a second land propulsion means; and
a second marine propulsion means, wherein:
the second prime mover is arranged to selectively drive the first and/or second land propulsion means, or the first and/or second marine propulsion means, or any combination thereof,
25 optionally through the second and/or first speed change transmission, and
the first prime mover is additionally arranged to selectively drive the second land propulsion means, the second marine propulsion means, or both, optionally through the first
30 and/or second speed change transmission.

7. A power train as claimed in any one of the preceding claims, the power train further comprising a first power take off coupled to receive drive from the first prime mover and/or the
35 first speed change transmission.

8. A power train as claimed in any one of the preceding claims, the power train further comprising a second power take

off coupled to receive drive from the second primer mover and/or the second speed change transmission.

5 9. A power train as claimed in claim 7 or claim 8, wherein the first power take off is arranged to drive the first land propulsion means through a first land propulsion drive shaft and a first differential.

10 10. A power train as claimed in any one of claims 7 to 9, wherein the second power take off is arranged to drive the second land propulsion means through a second land propulsion drive shaft and a second differential.

15 11. A power train as claimed in any one of claim 7 to 10, wherein the first speed change transmission is arranged to drive the first marine propulsion means directly or through the first power take off and then a first marine propulsion drive shaft.

20 12. A power train as claimed in any one of claim 8 to 11, wherein the second speed change transmission is arranged to drive the second marine propulsion means directly or through the second power take off and then a second marine propulsion drive shaft.

25 13. A power train as claimed in any one of the preceding claims, wherein the first land propulsion means comprises a front set of wheels or track drives and the second land propulsion means comprises a rear set of wheels or track drives.

30 14. A power train as claimed in claim 13, wherein the front set of wheels or track drives comprises at least one port and one starboard wheel or track drive and the rear set of wheels or track drives comprises at least one port and one starboard wheel or track drive.

35 15. A power train as claimed in any one of the preceding claims, further comprising one or more decouplers arranged to selectively decouple the first prime mover from one or more of either the first land propulsion means and/or the first marine

propulsion means.

16. A power train as claimed in any one of the preceding claims, further comprising one or more decouplers arranged to
5 selectively decouple the second prime mover from one or more of either the second land propulsion means and/or the second marine propulsion means.

17. A power train as claimed in any one of the preceding
10 claims, further comprising one or more decouplers arranged to selectively decouple any one or more of the components in the power train.

18. A power train as claimed in any one of claims 15 to 17,
15 further comprising control means to selectively activate and deactivate any one or more of the decouplers in the power train.

19. A power train as claimed in any one of the preceding claims wherein first refers to port and second refers to starboard.
20

20. A power train as claimed in any one of the preceding claims wherein first refers to starboard and second refers to port.

21. A power train as claimed in any one of the preceding
25 claims, wherein either one or both of the first prime mover and the second prime mover comprise an internal combustion engine, an electric motor, a hydraulic motor, a hybrid engine, a motor generator and/or any combination thereof.

22. A power train as claimed in any one of the preceding
30 claims, wherein either one or both of the first marine propulsion means and the second marine propulsion means comprise either a water jet, or a propeller.

23. A power train according to any one of the preceding claims,
35 wherein the first and/or second speed transmission comprises a manual, sequential shift, semiautomatic, or automatic gearbox, or a continuously variable transmission (CVT).

24. A power train according to any one of the preceding claims, wherein the land mode includes entry of the amphibian into the water and egress of the amphibian from the water.

5

25. A power train according to any one of the preceding claims, further comprising control means and wherein the control means comprises electronic processing means and/or electrical, mechanical, hydraulic or electromechanical actuation devices, or any combination thereof.

10

26. A power train according to any one of the preceding claims, wherein any one or both of the first and/or second prime movers comprises any one or a combination of the following:

15

a spark ignition internal combustion engine;
a compression ignition internal combustion engine;
an electric motor;
a hydraulic motor;
a motor generator; and/ or
a hybrid engine; and/or
any combination thereof.

20

27. A power train for an amphibian, the power train comprising:
a first prime mover;
a first speed change transmission;
a first land propulsion means; and
a first marine propulsion means, wherein:

25

the first prime mover is arranged to selectively drive the first land propulsion means, or the first marine propulsion means, or both, through the first speed change transmission, characterised in that the power train further comprises:

30

a second prime mover;
a second speed change transmission;
a second land propulsion means; and
a second marine propulsion means, wherein:

35

the second prime mover is arranged to selectively drive the second land propulsion means, or a second marine propulsion means, or both, through the second speed change transmission.

28. A power train for an amphibian, the power train comprising:
a first prime mover;
a first land propulsion means; and
5 a first marine propulsion means, wherein:
the first prime mover is arranged to selectively drive the
first land propulsion means, or the first marine propulsion
means, or both, characterised in that the power train further
comprises:
10 a second marine propulsion means, wherein:
the first prime mover is arranged to selectively drive the
second marine propulsion means either in place of the first
marine propulsion means or in addition thereto.
- 15 29. A power train as claimed in claim 28, the power train
further comprising a second prime mover, wherein the second prime
mover is arranged to selectively drive the first land propulsion
means, the first marine propulsion means and the second marine
propulsion means, either separately or in any combination
20 thereof.
30. A power train as claimed in claim 28 or claim 29, the power
train further comprising a second land propulsion means, wherein
the first prime mover is arranged to selectively drive the second
25 marine propulsion means.
31. A power train as claimed in claim 29 or claim 30, the power
train further comprising a second land propulsion means, wherein
the first prime mover is arranged to selectively drive the second
30 marine propulsion means, and the first prime mover is arranged to
selectively drive the second marine propulsion means, either in
place of the second prime mover or in addition thereto.
32. A power train as claimed in any one of claims 28 to 31, the
35 power train further comprising a first and/or a second speed
transmission, and wherein the first and/or second prime mover is
arranged to selectively drive any one or more of the first land
propulsion means and the first marine propulsion means through

the first and/or second speed transmission.

33. A power train as claimed in any one of claims 28 to 32, the power train further comprising a first and/or a second speed
5 transmission, and wherein the first and/or second prime mover is arranged to selectively drive any one or more of the first and/or second land propulsion means and the first and/or second marine propulsion means through the first and/or second speed transmission.

10

34. An amphibian comprising the power train of any one of the preceding claims.

35. An amphibian as claimed in claim 34, wherein any one or
15 both of the first prime mover and/or the second prime mover are positioned substantially in line or parallel to a longitudinal axis of the amphibian.

36. An amphibian as claimed in claim 34 or claim 35, wherein
20 any one or both of the first power take off and/or the first speed transmission are located rearwardly of the first prime mover.

37. An amphibian as claimed in any one of claims 34 to 36,
25 wherein any one or both of the second power take off and/or the second speed transmission are located rearward of the second prime mover.

38. An amphibian as claimed in any one of claims 34 to 37,
30 wherein any one or both of the first prime mover and/or the second prime mover are positioned in the rear half lengthwise, from bow to stern, of the amphibian.

39. An amphibian as claimed in any one of claims 34 to 38,
35 wherein any one or both of the first and/or second prime movers is arranged in line in the amphibian in a North-South or South-North configuration.

40. An amphibian as claimed in any one of claims 34 to 39,
wherein one or more of the wheels may be retracted above the
water line for use on water, and protracted below the hull for
use on land.

5

41. An amphibian as claimed in any one of claims 34 to 40,
wherein when the amphibian is operated in the marine mode any one
or both of the first and second marine propulsion means can power
the amphibian to a speed where sufficient hydrodynamic lift is
10 achieved for the vehicle to plane.

42. An amphibian as claimed in any one of claims 34 to 41,
wherein when the amphibian is operated in the land mode it can be
driven in one, two, three or four wheel drive.

15