



(51) International Patent Classification:
G06F 9/44 (2006.01)

(21) International Application Number:
PCT/CN2013/079600

(22) International Filing Date:
18 July 2013 (18.07.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
201210252551.8 20 July 2012 (20.07.2012) CN

(71) Applicant: **TENCENT TECHNOLOGY (SHENZHEN) COMPANY LIMITED** [CN/CN]; Room 403, East Block 2, SEG Park, Zhenxing Road, Futian District, Shenzhen, Guangdong 518000 (CN).

(72) Inventor: **ZHANG, Lichun**; Room 403, East Block 2, SEG Park, Zhenxing Road, Futian District, Shenzhen, Guangdong 518000 (CN).

(74) Agent: **BEIJING SAN GAO YONG XIN INTELLECTUAL PROPERTY AGENCY CO., LTD.**; A-1-102, He Jing Yuan, Ji Men Li, Xueyuan Road, Haidian District, Beijing 100088 (CN).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD, DEVICE, AND MOBILE TERMINAL FOR API INTERCEPTION




FIG. 1

(57) Abstract: The present invention discloses an application programming interface interception method and device, and a mobile terminal. The method includes: monitoring, based on a process identifier of an API process, the API process in a virtual machine corresponding to a system in real time; when the API process is activated, obtaining a virtual machine instance corresponding to the API process from a memory according to the process identifier; according to identifier information of an API to be intercepted, replacing an address pointing to the code of a first API written in a first computer language corresponding to the API process with a stored address pointing to the code of a second API (or a replacement function) corresponding to the first API and written in a second computer language different from the first language; and implementing control on the API process through a second API function.