

Method for remote detection of gaseous substances in the atmosphere by the DIAL system with two lasers and a remote detector

Technical field

The invention relates to a method for the remote detection of gaseous substances in the atmosphere by a DIAL system with two lasers and to the construction of a remote detector of gaseous substances in the atmosphere using the DIAL (Differential Absorption LIDAR) technology with two lasers. The invention falls within the field of laser systems.

Background of the invention

The so-called “classic” arrangement of the DIAL system with two lasers has a single output aperture, where the laser beams from both lasers are merged by means of a semipermeable mirror so that they are coaxial. Therefore, the laser radiation from both lasers propagates towards the target – object that ends a particular measuring route, through the identical volume of the atmosphere. The obvious disadvantage of this arrangement is the 50% loss of energy from the lasers arising from the merging of beams (although this 50% of energy is used to synchronize the system and measure outgoing energies) which has a negative effect on the remote detector range, as its range drops to about 70%. If the output aperture is accidentally blocked, such DIAL system fails.

There is a DIAL system arrangement with two lasers and two output apertures, where each laser has a separate output aperture. In practice, there are for instance the DD-CWA and the F4G systems operating on this basis. As a result, the laser radiation from one laser propagates to the target to a certain distance through a different volume of the atmosphere than the radiation from the other laser. The laser beams gradually overlap, but they usually get coincident to about 50% on a halfway towards the target. The influence of optical atmospheric effects, the different aerosol content and also the different concentrations of the detected substance for one and the other laser in the initial part of the measuring route can fundamentally negatively affect the minimum detectable concentration. If one of the output apertures of such DIAL is accidentally blocked for a short period of time, it may either cause false detection or prevent the detection of the real cloud of substance to be detected.

Summary of the invention

The method for remote detection of gaseous substances in the atmosphere by the DIAL system with two lasers according to the invention largely eliminates these drawbacks, the essence of which consists in that the laser beam generated by the first laser impinges on a semipermeable mirror, where 50% of the laser beam power passes through the semipermeable mirror and proceeds through the first aperture towards the target and at the same time the remaining 50% of the laser beam power reflects from the semipermeable mirror, impinges on a totally reflecting mirror from which it is reflected and is directed through the second aperture to the same target. The delayed laser beam generated by the second laser impinges on the semipermeable mirror, where 50% of the laser beam power passes through the semipermeable mirror, impinges on the totally reflecting mirror from which it is reflected and is directed through the second aperture to the same target and at the same time the remaining 50% of the laser beam power reflects from the semipermeable mirror and proceeds through the first aperture towards the same target.

In essence, the laser beams from both lasers are merged by a semipermeable mirror, each beam being divided into two, each carrying 50% of the energy from the first and then also the second laser, and both beams are directed in parallel, one by semipermeable and the other one by totally reflecting mirror to the target.

The above stated method for remote detection of gaseous substances in the atmosphere by the DIAL system with two lasers is usable in a remote detector of gaseous substances in the atmosphere according to the invention, the essence of which is based on the presence of the first laser and the second laser, while at the intersection of the axes of their laser beams a semipermeable mirror is located. Behind the semipermeable mirror, a totally reflecting mirror is located in the forward direction of the laser beam advance generated by the second laser and also in the reflected direction from the semipermeable mirror of the laser beam advance generated by the first laser. The first aperture is located in a forward direction from the semipermeable mirror of the 50% laser beam advance from the first laser and of the reflected 50% laser beam advance from the second laser. The second aperture is located in the reflected direction from the totally reflecting mirror of the 50% laser beam advance from the first laser and of the 50% laser beam advance from the second laser.

The advantages of the method for remote detection of gaseous substances in the atmosphere by the DIAL system with two lasers and the construction of the remote detector of gaseous substances in the atmosphere according to the invention are evident from the effects which are manifested externally. The originality of the solution lies in the fact that by merging beams from both lasers using semipermeable mirror and at the same time by dividing each beam into two, each carrying 50% of energy from the first and then also the second laser, where both beams are directed in parallel to the target, there is no 50% loss of energy of lasers and therefore no decrease in the range of the DIAL and laser radiation from both lasers passes through the same volumes of atmosphere. Such arrangement of the DIAL system with two lasers with the division of laser beams into two minimizes the external influences of atmospheric effects on detection and ensures the maximum detection range. The solution with two output apertures brings other advantages here. One advantage is that even if one of the apertures is completely blocked, the range of the system will decrease, but the detection capability and DIAL sensitivity will be preserved. The second advantage is that division the laser beams into two will bring the power density reduction in the output apertures and thus vision safety increase, because although the total energy coming from the aperture remains approximately the same, it is divided into two pulses: the first from the first laser, and after a significant delay the second from the second laser.

Description of the drawings

The method for remote detection of gaseous substances in the atmosphere by the DIAL system with two lasers and a remote detector of gaseous substances in the atmosphere according to the invention is shown in the figure of the accompanying drawing.

Example of embodiment

In this example of a specific embodiment of the subject of the invention, a solution of a method for remote detection of gaseous substances in the atmosphere by the DIAL system with two lasers according to the invention is described. The method for remote detection is applied to a remote detector of gaseous substances in the atmosphere. It is based on the fact that the laser beam generated by the first laser impinges on a semipermeable mirror, where 50% of the laser beam power passes through the semipermeable mirror and proceeds through the first aperture towards the target and at the same time the remaining 50% of the laser beam power reflects from

the semipermeable mirror, impinges on a totally reflecting mirror from which it is reflected and is directed through the second aperture to the same target. The delayed laser beam generated by the second laser impinges on a semipermeable mirror, where 50% of the laser beam power passes through the semipermeable mirror, impinges on a totally reflecting mirror from which it is reflected and is directed through the second aperture to the same target and at the same time the remaining 50% of the laser beam power reflects from the semipermeable mirror and proceeds through the first aperture towards the same target.

In this example of a specific embodiment of the subject of the invention, a solution of a method for remote detector of gaseous substances in the atmosphere according to the invention is described, which is shown in the figure. It consists of the first laser 1 and the second laser 2, while at the intersection of the axes of their laser beams a semipermeable mirror 3 is located. Behind the semipermeable mirror 3, a totally reflecting mirror 5 is located in the forward direction of the laser beam advance generated by the second laser 2 and also in the reflected direction from the semipermeable mirror 3 of the laser beam advance generated by the first laser 1. The first aperture 4 is located in a forward direction from the semipermeable mirror 3 of the 50% laser beam advance from the first laser 1 and of the reflected 50% laser beam advance from the second laser 2. The second aperture 6 is located in the reflected direction from the totally reflecting mirror 5 of the 50% laser beam advance from the first laser 1 and of the 50% laser beam advance from the second laser 2. The device is complemented by a receiver 7 of reflected laser beams.

Industrial usability

The method for remote detection of gaseous substances in the atmosphere by the DIAL system with two lasers and a remote detector of gaseous substances in the atmosphere are usable in laser technology applications.

CLAIMS

1. Method for remote detection of gaseous substances in the atmosphere by a differential absorption LIDAR system with two lasers, wherein a laser beam generated by a first laser (1) impinges on a semipermeable mirror (3), where 50% of a laser beam power of the laser beam passes through the semipermeable mirror (3) and proceeds through a first aperture (4) towards a target and at the same time the remaining 50% of the laser beam power of the laser beam reflects from the semipermeable mirror (3), impinges on a totally reflecting mirror (5) from which it is reflected and is directed through a second aperture (6) to the same target; and a delayed laser beam generated by a second laser (2) impinges on the semipermeable mirror (3), where 50% of a laser beam power of the delayed laser beam passes through the semipermeable mirror (3), impinges on the totally reflecting mirror (5) from which it is reflected and is directed through the second aperture (6) to the same target and at the same time the remaining 50% of the laser beam power of the delayed laser beam reflects from the semipermeable mirror (3) and proceeds through the first aperture (4) towards the same target.

2. Differential absorption LIDAR system for remote detection of gaseous substances in the atmosphere consisting of two lasers,

wherein a first laser beam and a second laser beam advance from a first laser (1) and a second laser (2), respectively, and wherein the first and second lasers are arranged such that axes of the first and second laser beams intersect,

wherein at the intersection of the axes of the first and second laser beams, a semipermeable mirror (3) is located;

wherein behind the semipermeable mirror (3) in a first direction, which is a direction of undeflected travel of the second laser beam through the semipermeable mirror (3) which coincides with a direction of travel of the first laser beam reflected by the semipermeable mirror (3), a totally reflecting mirror (5) is located;

wherein a first aperture (4) is located behind the semipermeable mirror (3) in a second direction, which is a direction of undeflected travel of the first laser beam through the semipermeable mirror (3) which coincides with a direction of travel of the second laser beam reflected by the semipermeable mirror (3),

wherein the first aperture (4) receives a first merged beam comprising 50% of the first laser beam advance from the first laser (1) and 50% of the second laser beam advance from the second laser (2) which is reflected by the semipermeable mirror (3);

wherein a second merged beam travelling in the first direction is reflected by the totally reflecting mirror (5) into the second direction,

wherein the second merged beam comprises 50% of the first laser beam advance from the first laser (1) which is reflected by the semipermeable mirror (3) and 50% of the second laser beam advance from the second laser (2),

wherein a second aperture (6) is located in the second direction of travel of the second merged beam after the totally reflecting mirror (5) and receives the second merged beam, such that the first and second merged beams are directed in parallel to a target.