

9900965-6
IP0S



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B05C 11/02, B05D 1/40		A1	(11) International Publication Number: WO 98/13145
			(43) International Publication Date: 2 April 1998 (02.04.98)
(21) International Application Number: PCT/AU97/00637		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, <u>SG</u> , SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 25 September 1997 (25.09.97)			
(30) Priority Data: ① PO 2570 ✓ 25 September 1996 (25.09.96) AU ✓			
(71) Applicant (for all designated States except US): BHP STEEL (JLA) PTY. LTD. [AU/AU]; 600 Bourke Street, Melbourne, VIC 3000 (AU).			
(72) Inventors; and (75) Inventors/Applicants (for US only): ① BUECHER, Udo, Wolfgang [AU/AU]; 18 Aberdare Place, Farmborough Heights, NSW 2526 (AU); HORTON, Trevor, James [AU/AU]; 15 Burnett Place, Albion Park, NSW 2527 (AU). DAVIES, Mark, John [AU/AU]; Figtree Street, Albion Park Rail, NSW 2527 (AU).		Published With international search report. ✓	
(74) Agent: CARTER SMITH & BEADLE; Qantas House, 2 Railway Parade, Camberwell, VIC 3124 (AU).		③ 1 PD 1 appl. 3 inv.	
(54) Title: PRODUCTION OF STRIPED COATINGS ON STRIP ✓			
(57) Abstract			
An apparatus and method for producing a striped coating on a continuous moving strip. The apparatus has a smoothing device including a doctor roll (4) forming a nip with the strip (5). A stationary partition means (8) is provided dividing the nip into nip lengths. Upstream of the smoothing device (4, 5) is a means to deposit coating materials on the strip (5) for delivery into the respective nip lengths at predetermined rates. The deposit means maintain a bead (9) of coating material in each nip length and a stripe of coating material is formed on the strip from coating material escaping the respective nip length as the strip (5) passes through the nip.			