

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 October 2005 (27.10.2005)

PCT

(10) International Publication Number
WO 2005/099365 A2

(51) International Patent Classification: **Not classified**

(21) International Application Number:
PCT/US2005/010551

(22) International Filing Date: 31 March 2005 (31.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/560,825 8 April 2004 (08.04.2004) US

(71) Applicant and

(72) Inventor: AMPLATZ, Kurt [US/US]; 10 Evergreen
Road, North Oaks, MN 55127 (US).

(74) Agent: RAASCH, Kevin, W.; Muetting, Raasch & Geb-
hardt P.A., P.O. Box 581415, Minneapolis, MN 55454-
1415 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: FLANGE OCCLUSION DEVICES AND METHODS

(57) Abstract: Implantable occlusion devices that include one or more flanges extending from a tubular body are disclosed. The flange or flanges may assist in retention of the device within a vessel, cavity, appendage, etc. At least one flange on the occlusion device may include a concave surface proximate one end of a body. Because of the shape of the flange, e.g., its concavity, the occlusion device may resist dislocation due to e.g., the forces generated within the left atrial appendage during atrial fibrillation.



WO 2005/099365 A2