

LUBRICANTS WITH TITANIUM AND/OR TUNGSTEN AND THEIR USE FOR IMPROVING LOW SPEED PRE-IGNITION

TECHNICAL FIELD

[0001] The disclosure relates to lubricant compositions containing one or more oil soluble titanium-containing and/or tungsten-containing additives and methods for using such lubricating oil compositions to reduce low speed pre-ignition events.

BACKGROUND

[0002] Turbocharged or supercharged engines (i.e. boosted internal combustion engines) may exhibit an abnormal combustion phenomenon known as stochastic pre-ignition or low speed pre-ignition (or "LSPI"). LSPI is a pre-ignition event that may include very high pressure spikes, early combustion during an inappropriate crank angle, and knock. All of these, individually and in combination, have the potential to cause degradation and/or severe damage to the engine. However, because LSPI events occur only sporadically and in an uncontrolled fashion, it is difficult to identify the causes for this phenomenon and to develop solutions to suppress it.

[0003] Pre-ignition is a form of combustion that results of ignition of the air-fuel mixture in the combustion chamber prior to the desired ignition of the air-fuel mixture by the igniter. Pre-ignition has typically been a problem during high speed engine operation since heat from operation of the engine may heat a part of the combustion chamber to a sufficient temperature to ignite the air-fuel mixture upon contact. This type of pre-ignition is sometimes referred to as hot-spot pre-ignition.

[0004] More recently, intermittent abnormal combustion has been observed in boosted internal combustion engines at low speeds and medium-to-high loads. For example, during operation of the engine at 3,000 rpm or less, under load, with a brake mean effective pressure (BMEP) of at least 10 bar, low speed pre-ignition (LSPI) may occur in a random and stochastic fashion. During low speed engine operation, the compression stroke time is longest.

[0005] Several published studies have demonstrated that turbocharger use, engine design, engine coatings, piston shape, fuel choice, and/or engine oil additives may contribute

to an increase in LSPI events. One theory suggests that auto-ignition of engine oil droplets that enter the engine combustion chamber from the piston crevice (the space between the piston ring pack and cylinder liner) may be one cause of LSPI events. Accordingly, there is a need for engine oil additive components and/or combinations that are effective to reduce or eliminate LSPI in boosted internal combustion engines.

SUMMARY AND TERMS

[0006] The present disclosure relates to a lubricating oil composition and method of operating a boosted internal combustion engine. The lubricating oil composition includes greater than 50 wt.% of a base oil of lubricating viscosity, an amount of one or more overbased calcium-containing detergents having a total base number of greater than 225 mg KOH/g, measured by the method of ASTM D-2896 sufficient to provide greater than 900 ppm by weight to less than 2400 ppm by weight of calcium to the lubricating oil composition, based on a total weight of the lubricating oil composition, and a low speed pre-ignition reducing additive composition comprising an amount of one or more titanium-containing compounds sufficient to provide from 10 ppm to 3000 ppm by weight of titanium to the lubricating oil composition and/or an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition, both based on the total weight of the lubricating oil composition. The additive composition is effective to reduce low speed pre-ignition events in a boosted internal combustion engine lubricated with the lubricating oil composition relative to a number of low speed pre-ignition events in the same engine lubricated with a same lubricating oil composition without the one or more titanium-containing and/or the one or more tungsten-containing compounds.

[0006a] In one aspect of the present disclosure, there is provided a lubricating oil composition comprising:

greater than 50 wt.% of a base oil of lubricating viscosity,

an amount of one or more overbased calcium-containing detergents having a total base number of greater than 225 mg KOH/g, measured by the method of ASTM D-2896 sufficient to provide greater than 900 ppm by weight to 1800 ppm by weight of calcium to the lubricating oil composition, based on a total weight of the lubricating oil composition, and

a low speed pre-ignition reducing additive composition comprising one of the following a), b) or c):

a) an amount of one or more titanium-containing compounds sufficient to provide from 10 ppm to 3000 ppm by weight of titanium to the lubricating oil composition and at least one low-based/neutral calcium-containing detergent having a total base number of up to 175 mg KOH/gram measured by the method of ASTM D-2896 and optionally an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition based on the total weight of the lubricating oil composition;

b) an amount of one or more titanium-containing compounds sufficient to provide from 10 to 3000 ppm by weight of titanium to the lubricating oil composition and optionally an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition based on the total weight of the lubricating oil composition; and

c) an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition, based on the total weight of the lubricating oil composition, and an amount of one or more molybdenum containing components sufficient to provide from 0.5 to 300 ppm by weight of molybdenum to the lubricating oil composition based on the total weight of the lubricating oil composition, and

wherein said additive composition is effective to reduce low speed pre-ignition events in a boosted internal combustion engine lubricated with the lubricating oil composition relative to a number of low speed pre-ignition events in the same engine lubricated with a same lubricating oil composition without the one or more titanium-containing and/or the one or more tungsten-containing compounds, and the low speed pre-ignition events are low speed pre-ignition counts during 25,000 engine cycles, wherein the engine is operated at 2000 revolutions per minute with a brake mean effective pressure of 18,000 kPa.

[0006b] In another aspect of the present disclosure, there is provided a method for reducing low speed pre-ignition events in a boosted internal combustion engine comprising:

lubricating a boosted internal combustion engine with a lubricating oil composition comprising greater than 50 wt.% of a base oil of lubricating viscosity and an additive composition comprising:

an amount of one or more overbased calcium-containing detergents having a total base number of greater than 225 mg KOH/g, measured by the method of ASTM D-2896 sufficient to provide greater than 900 ppm by weight to 1800 ppm by weight of calcium to the lubricating oil composition, based on a total weight of the lubricating oil composition, and one of the following a), b) or c):

a) an amount of one or more titanium-containing compounds sufficient to provide from 10 ppm to 3000 ppm by weight of titanium to the lubricating oil composition and at least one low-based/neutral calcium-containing detergent having a total base number of up to 175 mg KOH/gram measured by the method of ASTM D-2896 and optionally an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition based on the total weight of the lubricating oil composition;

b) an amount of one or more titanium-containing compounds sufficient to provide from 10 to 3000 ppm by weight of titanium to the lubricating oil composition and optionally an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition based on the total weight of the lubricating oil composition; and

c) an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition, based on the total weight of the lubricating oil composition, and an amount of one or more molybdenum containing components sufficient to provide from 0.5 to 300 ppm by weight of molybdenum to the lubricating oil composition based on the total weight of the lubricating oil composition, and

operating the engine lubricated with the lubricating oil composition whereby the low speed pre-ignition events in the boosted internal combustion engine lubricated with the lubricating oil composition are reduced relative to a number of low speed pre-ignition

events in the same engine lubricated with a same lubricating oil composition without the one or more titanium-containing and/or the one or more tungsten-containing compounds, and the low speed pre-ignition events are low speed pre-ignition counts during 25,000 engine cycles, wherein the engine is operated at 2000 revolutions per minute with a brake mean effective pressure of 18,000 kPa.

[0007] In another embodiment, the disclosure provides a method for reducing low speed pre-ignition events in a boosted internal combustion engine. The method includes lubricating a boosted internal combustion engine with a lubricating oil composition that includes greater than 50 wt.% of a base oil of lubricating viscosity, an amount of one or more overbased calcium-containing detergents having a total base number of greater than 225 mg KOH/g, measured by the method of ASTM D-2896 sufficient to provide greater than 900 ppm by weight to less than 2400 ppm by weight of calcium to the lubricating oil composition, based on a total weight of the lubricating oil composition, and a low speed pre-ignition

reducing additive composition comprising an amount of one or more titanium-containing compounds sufficient to provide from 10 ppm to 3000 ppm by weight of titanium to the lubricating oil composition and/or an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition, both based on the total weight of the lubricating oil composition. The method is effective to reduce low speed pre-ignition events in a boosted internal combustion engine lubricated with the lubricating oil composition.

[0008] In each of the foregoing embodiments, the one or more overbased calcium-containing detergent(s) may be selected from an overbased calcium sulfonate detergent, an overbased calcium phenate detergent, and an overbased calcium salicylate detergent. In each of the foregoing embodiments, the one or more overbased calcium-containing detergent(s) may provide from about 1100 to about 1800 ppm by weight calcium to the lubricating oil composition based on a total weight of the lubricating oil composition.

[0009] In each of the foregoing embodiments, the lubricating oil composition may contain a titanium-containing compound. In each of the foregoing embodiments, the one or more titanium-containing compound(s) may comprise a reaction product of titanium isopropoxide and neodecanoic acid, titanium isopropoxide, a titanium-containing dispersant, and mixtures thereof.

[0010] In each of the foregoing embodiments, the one or more titanium-containing compound(s) may be present in an amount that provides from about 25 ppm to about 1000 ppm by weight titanium to the lubricating oil composition, based on the total weight of the lubricating composition.

[0011] In each of the foregoing embodiments, the lubricating oil composition may contain a tungsten-containing compound. In each of the foregoing embodiments, the one or more tungsten-containing compound(s) is an alkyl or aryl-substituted ammonium tungstate wherein the alkyl and aryl groups each have 6-30 carbon atoms.

[0012] In each of the foregoing embodiments, the one or more tungsten-containing compound(s) may be present in an amount that provides from about 200 ppm to about 1000 ppm by weight tungsten to the lubricating oil composition, based on the total weight of the lubricating composition.

[0013] In each of the foregoing embodiments, the lubricating oil composition may include one or more components selected from friction modifiers, antiwear agents, dispersants, antioxidants, and viscosity index improvers. In each of the foregoing embodiments, the lubricating oil composition may have a sulfated ash content of less than about 1 wt.%, and the SASH may be less than 0.8%.

[0014] In each of the foregoing embodiments, the LSPI events may be LSPI counts during 25,000 engine cycles, wherein the engine is operated at 2000 revolutions per minute with a brake mean effective pressure of 18,000 kPa. In each of the foregoing embodiments, the low speed pre-ignition reducing additive composition may reduce the number of LSPI events by at least 50% or by at least 75%.

[0015] In each of the foregoing embodiments, the greater than 50 wt.% of base oil may be selected from the group consisting of Group II, Group III, Group IV, or Group V base oils, and a combination of two or more of the foregoing, wherein the greater than 50 wt.% of the base oil is other than diluent oils that arise from provision of additive components or viscosity index improvers to the lubricating oil composition.

[0016] In each of the foregoing embodiments, the lubricating oil composition may comprise not more than 10 wt.% of a Group IV base oil, a Group V base oil, or a combination thereof. In each of the foregoing embodiments, the lubricating oil compositions comprises less than 5 wt.% of a Group V base oil.

[0017] In each of the foregoing embodiments, the overbased calcium-containing detergent may be an overbased calcium sulfonate detergent.

[0018] In each of the foregoing embodiments, the overbased calcium-containing detergent may optionally exclude overbased calcium salicylate detergents.

[0019] In each of the foregoing embodiments, the lubricating oil composition may optionally exclude any magnesium-containing detergents or the lubricating oil composition may be free of magnesium.

[0020] In each of the foregoing embodiments, the lubricating oil composition may not contain any Group IV base oils.

[0021] In each of the foregoing embodiments, the lubricating oil composition may not contain any Group V base oils.

[0022] In each of the foregoing embodiments, the lubricating oil composition may further contain a low-based/neutral detergent having a total base number of up to 175 mg KOH/g, measured by the method of ASTM D-2896. The low-based/neutral detergent may comprise at least 0.2 wt.% of the total lubricating oil composition. In each of the foregoing embodiments, the total detergent in the lubricating oil composition may range from about 0.6 wt.% to about 10 wt.% based on the total weight of the lubricating oil composition. In each of the foregoing embodiments, the total amount of calcium from the overbased calcium-containing detergent and the low-based/neutral detergent may range from 1100 ppm by weight to less than 2400 ppm by weight based on the total weight of the lubricating oil composition. In each of the foregoing embodiments, the low-based/neutral detergent may be a calcium sulfonate detergent.

[0023] The following definitions of terms are provided in order to clarify the meanings of certain terms as used herein.

[0024] The terms “oil composition,” “lubrication composition,” “lubricating oil composition,” “lubricating oil,” “lubricant composition,” “lubricating composition,” “fully formulated lubricant composition,” “lubricant,” “crankcase oil,” “crankcase lubricant,” “engine oil,” “engine lubricant,” “motor oil,” and “motor lubricant” are considered synonymous, fully interchangeable terminology referring to the finished lubrication product comprising greater than 50 wt.% of a base oil plus a minor amount of an additive composition.

[0025] As used herein, the terms “additive package,” “additive concentrate,” “additive composition,” “engine oil additive package,” “engine oil additive concentrate,” “crankcase additive package,” “crankcase additive concentrate,” “motor oil additive package,” “motor oil concentrate,” are considered synonymous, fully interchangeable terminology referring the portion of the lubricating oil composition excluding greater than 50 wt.% of the base oil stock mixture. The additive package may or may not include the viscosity index improver or pour point depressant.

[0026] The term “overbased” relates to metal salts, such as metal salts of sulfonates, carboxylates, salicylates, and/or phenates, wherein the amount of metal present exceeds the stoichiometric amount. Such salts may have a conversion level in excess of 100% (i.e., they may comprise more than 100% of the theoretical amount of metal needed to convert the acid

to its “normal,” “neutral” salt). The expression “metal ratio,” often abbreviated as MR, is used to designate the ratio of total chemical equivalents of metal in the overbased salt to chemical equivalents of the metal in a neutral salt according to known chemical reactivity and stoichiometry. In a normal or neutral salt, the metal ratio is one and in an overbased salt, MR, is greater than one. They are commonly referred to as overbased, hyperbased, or superbased salts and may be salts of organic sulfur acids, carboxylic acids, salicylates, and/or phenols. In the present disclosure, the overbased detergent has a TBN of greater than 225 mg KOH/g. The overbased detergent may be a combination of two or more overbased detergents each having a TBN of greater than 225 mg KOH/g.

[0027] In the present disclosure, the low-based/neutral detergent has a TBN of up to 175 mg KOH/g. The low-based/neutral detergent may be a combination of two or more low-based and/or neutral detergents each having a TBN up to 175 mg KOH/g. In some instances, “overbased” may be abbreviated “OB.” And in some instances, “low-based/neutral” may be abbreviated “LB/N.”

[0028] The term “total metal” refers to the total metal, metalloid or transition metal in the lubricating oil composition including the metal contributed by the detergent component(s) of the lubricating oil composition.

[0029] As used herein, the term “hydrocarbyl substituent” or “hydrocarbyl group” is used in its ordinary sense, which is well-known to those skilled in the art. Specifically, it refers to a group having a carbon atom directly attached to the remainder of the molecule and having predominantly hydrocarbon character. Examples of hydrocarbyl groups include:

- (a) hydrocarbon substituents, that is, aliphatic (e.g., alkyl or alkenyl), alicyclic (e.g., cycloalkyl, cycloalkenyl) substituents, and aromatic-, aliphatic-, and alicyclic-substituted aromatic substituents, as well as cyclic substituents wherein the ring is completed through another portion of the molecule (e.g., two substituents together form an alicyclic moiety);
- (b) substituted hydrocarbon substituents, that is, substituents containing non-hydrocarbon groups which, in the context of this disclosure, do not alter the predominantly hydrocarbon substituent (e.g., halo (especially chloro and fluoro), hydroxy, alkoxy, mercapto, alkylmercapto, nitro, nitroso, amino, alkylamino, and sulfoxy); and

(c) hetero substituents, that is, substituents which, while having a predominantly hydrocarbon character, in the context of this disclosure, contain other than carbon in a ring or chain otherwise composed of carbon atoms. Heteroatoms may include sulfur, oxygen, and nitrogen, and encompass substituents such as pyridyl, furyl, thienyl, and imidazolyl. In general, no more than two, for example, no more than one, non-hydrocarbon substituent will be present for every ten carbon atoms in the hydrocarbyl group; typically, there will be no non-hydrocarbon substituents in the hydrocarbyl group.

[0030] As used herein, the term "percent by weight", unless expressly stated otherwise, means the percentage the recited component represents to the weight of the entire composition.

[0031] The terms "soluble," "oil-soluble," or "dispersible" used herein may, but does not necessarily, indicate that the compounds or additives are soluble, dissolvable, miscible, or capable of being suspended in the oil in all proportions. The foregoing terms do mean, however, that they are, for instance, soluble, suspendable, dissolvable, or stably dispersible in oil to an extent sufficient to exert their intended effect in the environment in which the oil is employed. Moreover, the additional incorporation of other additives may also permit incorporation of higher levels of a particular additive, if desired.

[0032] The term "TBN" as employed herein is used to denote the Total Base Number in mg KOH/g composition as measured by the method of ASTM D2896.

[0033] The term "alkyl" as employed herein refers to straight, branched, cyclic, and/or substituted saturated chain moieties of from about 1 to about 100 carbon atoms.

[0034] The term "alkenyl" as employed herein refers to straight, branched, cyclic, and/or substituted unsaturated chain moieties of from about 3 to about 10 carbon atoms.

[0035] The term "aryl" as employed herein refers to single and multi-ring aromatic compounds that may include alkyl, alkenyl, alkylaryl, amino, hydroxyl, alkoxy, halo substituents, and/or heteroatoms including, but not limited to, nitrogen, oxygen, and sulfur.

[0036] Lubricants, combinations of components, or individual components of the present description may be suitable for use in various types of internal combustion engines. Suitable engine types may include, but are not limited to heavy duty diesel, passenger car, light duty diesel, medium speed diesel, marine engines, or motorcycle engines. An internal

combustion engine may be a diesel fueled engine, a gasoline fueled engine, a natural gas fueled engine, a bio-fueled engine, a mixed diesel/biofuel fueled engine, a mixed gasoline/biofuel fueled engine, an alcohol fueled engine, a mixed gasoline/alcohol fueled engine, a compressed natural gas (CNG) fueled engine, or mixtures thereof. A diesel engine may be a compression ignited engine. A diesel engine may be a compression ignited engine with a spark-ignition assist. A gasoline engine may be a spark-ignited engine. An internal combustion engine may also be used in combination with an electrical or battery source of power. An engine so configured is commonly known as a hybrid engine. The internal combustion engine may be a 2-stroke, 4-stroke, or rotary engine. Suitable internal combustion engines include marine diesel engines (such as inland marine), aviation piston engines, low-load diesel engines, and motorcycle, automobile, locomotive, and truck engines.

[0037] The internal combustion engine may contain components of one or more of an aluminum-alloy, lead, tin, copper, cast iron, magnesium, ceramics, stainless steel, composites, and/or mixtures thereof. The components may be coated, for example, with a diamond-like carbon coating, a lubricated coating, a phosphorus-containing coating, molybdenum-containing coating, a graphite coating, a nano-particle-containing coating, and/or mixtures thereof. The aluminum-alloy may include aluminum silicates, aluminum oxides, or other ceramic materials. In one embodiment the aluminum-alloy is an aluminum-silicate surface. As used herein, the term “aluminum alloy” is intended to be synonymous with “aluminum composite” and to describe a component or surface comprising aluminum and another component intermixed or reacted on a microscopic or nearly microscopic level, regardless of the detailed structure thereof. This would include any conventional alloys with metals other than aluminum as well as composite or alloy-like structures with non-metallic elements or compounds such with ceramic-like materials.

[0038] The lubricating oil composition for an internal combustion engine may be suitable for any engine irrespective of the sulfur, phosphorus, or sulfated ash (ASTM D-874) content. The sulfur content of the engine oil lubricant may be about 1 wt.% or less, or about 0.8 wt.% or less, or about 0.5 wt.% or less, or about 0.3 wt.% or less, or about 0.2 wt.% or less. In one embodiment the sulfur content may be in the range of about 0.001 wt.% to about 0.5 wt.%, or about 0.01 wt.% to about 0.3 wt.%. The phosphorus content may be about 0.2 wt.% or less, or about 0.1 wt.% or less, or about 0.085 wt.% or less, or about 0.08 wt.% or

less, or even about 0.06 wt.% or less, about 0.055 wt.% or less, or about 0.05 wt.% or less. In one embodiment the phosphorus content may be about 50 ppm to about 1000 ppm, or about 325 ppm to about 850 ppm. The total sulfated ash content may be about 2 wt.% or less, or about 1.5 wt.% or less, or about 1.1 wt.% or less, or about 1 wt.% or less, or about 0.8 wt.% or less, or about 0.5 wt.% or less. In one embodiment the sulfated ash content may be about 0.05 wt.% to about 0.9 wt.%, or about 0.1 wt.% or about 0.2 wt.% to about 0.45 wt.%. In another embodiment, the sulfur content may be about 0.4 wt.% or less, the phosphorus content may be about 0.08 wt.% or less, and the sulfated ash is about 1 wt.% or less. In yet another embodiment the sulfur content may be about 0.3 wt.% or less, the phosphorus content is about 0.05 wt.% or less, and the sulfated ash may be about 0.8 wt.% or less.

[0039] In one embodiment the lubricating oil composition is an engine oil, wherein the lubricating oil composition may have (i) a sulfur content of about 0.5 wt.% or less, (ii) a phosphorus content of about 0.1 wt.% or less, and (iii) a sulfated ash content of about 1.5 wt.% or less.

[0040] In some embodiments, the lubricating oil composition is suitable for use with engines powered by low sulfur fuels, such as fuels containing about 1 to about 5% sulfur. Highway vehicle fuels contain about 15 ppm sulfur (or about 0.0015% sulfur). The lubricating oil composition is suitable for use with boosted internal combustion engines including turbocharged or supercharged internal combustion engines.

[0041] Further, lubricants of the present description may be suitable to meet one or more industry specification requirements such as ILSAC GF-3, GF-4, GF-5, GF-6, PC-11, CI-4, CJ-4, ACEA A1/B1, A2/B2, A3/B3, A3/B4, A5/B5, C1, C2, C3, C4, C5, E4/E6/E7/E9, Euro 5/6, Jaso DL-1, Low SAPS, Mid SAPS, or original equipment manufacturer specifications such as DexosTM 1, DexosTM 2, MB-Approval 229.51/229.31, VW 502.00, 503.00/503.01, 504.00, 505.00, 506.00/506.01, 507.00, 508.00, 509.00, BMW Longlife-04, Porsche C30, Peugeot Citroën Automobiles B71 2290, B71 2296, B71 2297, B71 2300, B71 2302, B71 2312, B71 2007, B71 2008, Ford WSS-M2C153-H, WSS-M2C930-A, WSS-M2C945-A, WSS-M2C913A, WSS-M2C913-B, WSS-M2C913-C, GM 6094-M, Chrysler MS-6395, or any past or future PCMO or HDD specifications not mentioned herein. In some embodiments for passenger car motor oil (PCMO) applications, the amount of phosphorus in the finished fluid is 1000 ppm or less or 900 ppm or less or 800 ppm or less.

[0042] Other hardware may not be suitable for use with the disclosed lubricant. A “functional fluid” is a term which encompasses a variety of fluids including but not limited to tractor hydraulic fluids, power transmission fluids including automatic transmission fluids, continuously variable transmission fluids and manual transmission fluids, hydraulic fluids, including tractor hydraulic fluids, some gear oils, power steering fluids, fluids used in wind turbines, compressors, some industrial fluids, and fluids related to power train components. It should be noted that within each of these fluids such as, for example, automatic transmission fluids, there are a variety of different types of fluids due to the various transmissions having different designs which have led to the need for fluids of markedly different functional characteristics. This is contrasted by the term “lubricating fluid” which is not used to generate or transfer power.

[0043] With respect to tractor hydraulic fluids, for example, these fluids are all-purpose products used for all lubricant applications in a tractor except for lubricating the engine. These lubricating applications may include lubrication of gearboxes, power take-off and clutch(es), rear axles, reduction gears, wet brakes, and hydraulic accessories.

[0044] When a functional fluid is an automatic transmission fluid, the automatic transmission fluids must have enough friction for the clutch plates to transfer power. However, the friction coefficient of fluids has a tendency to decline due to the temperature effects as the fluid heats up during operation. It is important that the tractor hydraulic fluid or automatic transmission fluid maintain its high friction coefficient at elevated temperatures, otherwise brake systems or automatic transmissions may fail. This is not a function of an engine oil.

[0045] Tractor fluids, and for example Super Tractor Universal Oils (STUOs) or Universal Tractor Transmission Oils (UTTOs), may combine the performance of engine oils with transmissions, differentials, final-drive planetary gears, wet-brakes, and hydraulic performance. While many of the additives used to formulate a UTTO or a STUO fluid are similar in functionality, they may have deleterious effect if not incorporated properly. For example, some anti-wear and extreme pressure additives used in engine oils can be extremely corrosive to the copper components in hydraulic pumps. Detergents and dispersants used for gasoline or diesel engine performance may be detrimental to wet brake performance. Friction modifiers specific to quiet wet brake noise, may lack the thermal stability required for engine

oil performance. Each of these fluids, whether functional, tractor, or lubricating, are designed to meet specific and stringent manufacturer requirements.

[0046] The present disclosure provides novel lubricating oil blends formulated for use as automotive crankcase lubricants. Embodiments of the present disclosure may provide lubricating oils suitable for crankcase applications and having improvements in the following characteristics: air entrainment, alcohol fuel compatibility, antioxidancy, antiwear performance, biofuel compatibility, foam reducing properties, friction reduction, fuel economy, pre-ignition prevention, rust inhibition, sludge and/or soot dispersability, piston cleanliness, deposit formation, and water tolerance.

[0047] Additional details and advantages of the disclosure will be set forth in part in the description which follows, and/or may be learned by practice of the disclosure. The details and advantages of the disclosure may be realized and attained by means of the elements and combinations particularly pointed out in the appended claims. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the disclosure, as claimed.

DETAILED DESCRIPTION

[0048] Various embodiments of the disclosure provide a lubricating oil composition and methods for reducing low speed pre-ignition events (LSPI) in a boosted internal combustion engine. In particular, boosted internal combustion engines of the present disclosure include turbocharged and supercharged internal combustion engines. The boosted internal combustion engines include spark-ignited, direct injection and/or port-fuel injection engines. The spark-ignited internal combustion engines may be gasoline engines.

[0049] In one embodiment, the disclosure provides a lubricating oil composition and method of operating a boosted internal combustion engine. The lubricating oil composition includes greater than 50 wt.% of a base oil of lubricating viscosity, one or more calcium-containing overbased detergent(s) having a total base number greater than 225 mg KOH/g in an amount sufficient to provide greater than 900 ppm by weight to less than 2400 ppm by weight of calcium to the lubricating oil composition based on a total weight of the lubricating oil composition, and a low speed pre-ignition reducing additive composition comprising an amount of one or more titanium-containing compounds sufficient to provide from 10 ppm to

3000 ppm by weight of titanium to the lubricating oil composition and/or an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition, both based on the total weight of the lubricating oil composition. The additive composition and method are effective to reduce low speed pre-ignition events in a boosted internal combustion engine lubricated with the lubricating oil composition relative to a number of low speed pre-ignition events in the same engine lubricated with a same lubricating oil composition without the one or more titanium-containing and/or the one or more tungsten-containing compounds.

[0050] In another embodiment, the disclosure provides a method for reducing low speed pre-ignition events in a boosted internal combustion engine. The method includes lubricating a boosted internal combustion engine with a lubricating oil composition that includes greater than 50 wt.% of a base oil of lubricating viscosity, an amount of one or more overbased calcium-containing detergents having a total base number of greater than 225 mg KOH/g, measured by the method of ASTM D-2896 sufficient to provide greater than 900 ppm by weight to less than 2400 ppm by weight of calcium to the lubricating oil composition, based on a total weight of the lubricating oil composition, and a low speed pre-ignition reducing additive composition comprising an amount of one or more titanium-containing compounds sufficient to provide from 10 ppm to 3000 ppm by weight of titanium to the lubricating oil composition and/or an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition, both based on the total weight of the lubricating oil composition. The method is effective to reduce low speed pre-ignition events in a boosted internal combustion engine lubricated with the lubricating oil composition.

[0051] In some embodiments, the combustion chamber or cylinder walls of a spark-ignited direct injection engine or port fuel injected internal combustion engine provided with a turbocharger or a supercharger is operated and lubricated with the lubricating oil composition whereby the low-speed pre-ignition events in the engine lubricated with the lubricating oil composition may be reduced.

[0052] Optionally, the methods of the present invention may include a step of measuring low speed pre-ignition events of the internal combustion engine lubricated with the lubricating oil. In such methods, the internal combustion engine the reduction of LSPI

events is a 50% or greater reduction, or, more preferably, a 75% or greater reduction and the LSPI events are LSPI counts during 25,000 engine cycles, wherein the engine is operated at 2000 revolutions per minute with brake mean effective pressure of 18,000 kPa.

[0053] The composition of the invention includes a lubricating oil composition containing a base oil of lubricating viscosity and a particular additive composition. The methods of the present disclosure employ the lubricating oil composition containing the additive composition. As described in more detail below the lubricating oil composition is surprisingly effective for use in reducing low speed pre-ignition events in a boosted internal combustion engine lubricated with the lubricating oil composition.

Detergents

[0054] The lubricating oil composition comprises one or more overbased detergents alone, or in combination with one or more low-based/neutral detergents. Suitable detergent substrates include phenates, sulfur containing phenates, sulfonates, calixarates, salixarates, salicylates, carboxylic acids, phosphorus acids, mono- and/or di-thiophosphoric acids, alkyl phenols, sulfur coupled alkyl phenol compounds, or methylene bridged phenols. Suitable detergents and their methods of preparation are described in greater detail in numerous patent publications, including US 7,732,390 and references cited therein. The detergent substrate may be salted with an alkali or alkaline earth metal such as, but not limited to, calcium, magnesium, potassium, sodium, lithium, barium, or mixtures thereof. In some embodiments, the detergent is free of barium. A suitable detergent may include alkali or alkaline earth metal salts of petroleum sulfonic acids and long chain mono- or di-alkylarylsulfonic acids with the aryl group being benzyl, tolyl, and xylyl. Examples of suitable additional detergents include, but are not limited to, calcium phenates, calcium sulfur containing phenates, calcium sulfonates, calcium calixarates, calcium salixarates, calcium salicylates, calcium carboxylic acids, calcium phosphorus acids, calcium mono- and/or di-thiophosphoric acids, calcium alkyl phenols, calcium sulfur coupled alkyl phenol compounds, calcium methylene bridged phenols, magnesium phenates, magnesium sulfur containing phenates, magnesium sulfonates, magnesium calixarates, magnesium salixarates, magnesium salicylates, magnesium carboxylic acids, magnesium phosphorus acids, magnesium mono- and/or di-thiophosphoric acids, magnesium alkyl phenols, magnesium sulfur coupled alkyl phenol compounds,

magnesium methylene bridged phenols, sodium phenates, sodium sulfur containing phenates, sodium sulfonates, sodium calixarates, sodium salixarates, sodium salicylates, sodium carboxylic acids, sodium phosphorus acids, sodium mono- and/or di-thiophosphoric acids, sodium alkyl phenols, sodium sulfur coupled alkyl phenol compounds, or sodium methylene bridged phenols.

[0055] Overbased detergent additives are well known in the art and may be alkali or alkaline earth metal overbased detergent additives. Such detergent additives may be prepared by reacting a metal oxide or metal hydroxide with a substrate and carbon dioxide gas. The substrate is typically an acid, for example, an acid such as an aliphatic substituted sulfonic acid, an aliphatic substituted carboxylic acid, or an aliphatic substituted phenol.

[0056] The terminology “overbased” relates to metal salts, such as metal salts of sulfonates, carboxylates, and phenates, wherein the amount of metal present exceeds the stoichiometric amount. Such salts may have a conversion level in excess of 100% (i.e., they may comprise more than 100% of the theoretical amount of metal needed to convert the acid to its “normal,” “neutral” salt). The expression “metal ratio,” often abbreviated as MR, is used to designate the ratio of total chemical equivalents of metal in the overbased salt to chemical equivalents of the metal in a neutral salt according to known chemical reactivity and stoichiometry. In a normal or neutral salt, the metal ratio is one and in an overbased salt, MR, is greater than one. They are commonly referred to as overbased, hyperbased, or superbased salts and may be salts of organic sulfur acids, carboxylic acids, or phenols.

[0057] An overbased detergent has a TBN of greater 225 mg KOH/gram, or as further examples, a TBN of about 250 mg KOH/gram or greater, or a TBN of about 300 mg KOH/gram or greater, or a TBN of about 350 mg KOH/gram or greater, or a TBN of about 375 mg KOH/gram or greater, or a TBN of about 400 mg KOH/gram or greater.

[0058] Examples of suitable overbased detergents include, but are not limited to, overbased calcium phenates, overbased calcium sulfur containing phenates, overbased calcium sulfonates, overbased calcium calixarates, overbased calcium salixarates, overbased calcium salicylates, overbased calcium carboxylic acids, overbased calcium phosphorus acids, overbased calcium mono- and/or di-thiophosphoric acids, overbased calcium alkyl phenols, overbased calcium sulfur coupled alkyl phenol compounds, overbased calcium methylene bridged phenols, overbased magnesium phenates, overbased magnesium sulfur

containing phenates, overbased magnesium sulfonates, overbased magnesium calixarates, overbased magnesium salixarates, overbased magnesium salicylates, overbased magnesium carboxylic acids, overbased magnesium phosphorus acids, overbased magnesium mono- and/or di-thiophosphoric acids, overbased magnesium alkyl phenols, overbased magnesium sulfur coupled alkyl phenol compounds, or overbased magnesium methylene bridged phenols.

[0059] The overbased detergent may have a metal to substrate ratio of from 1.1:1, or from 2:1, or from 4:1, or from 5:1, or from 7:1, or from 10:1.

[0060] The total detergent may be present at up to about 10 wt.%, or up to about 8 wt.%, or up to about 4 wt.%, or greater than about 2 wt.% to about 8 wt.%, or from 4 wt.% to 8 wt.%, based on a total weight of the lubricating oil composition.

[0061] The total detergent may be present in an amount to provide from about 1100 to about 3500 ppm metal to the finished fluid. In other embodiments, the total detergent may provide from about 1100 to about 3000 ppm of metal, or about 1150 to about 2500 ppm of metal, or about 1200 to about 2400 ppm of metal to the finished fluid.

[0062] The additive compositions employed in the compositions and methods of the present disclosure include at least one overbased detergent having a TBN of greater than 225 mg KOH/gram alone, or in combination with at least one neutral/low-based detergent having a TBN of up to 175 mg KOH/gram.

[0063] The lubricating oil composition of the disclosure including the additive composition has a total amount of calcium in the lubricating oil composition from the at least one overbased detergent alone, or in combination with at least one low-based/neutral detergent ranges from greater than 900 ppm by weight to less than 2400 ppm by weight based on a total weight of the lubricating oil composition.

[0064] The overbased detergent may be an overbased calcium-containing detergent. The overbased calcium-containing detergent may be selected from an overbased calcium sulfonate detergent, an overbased calcium phenate detergent, and an overbased calcium salicylate detergent. In certain embodiments, the overbased calcium-containing detergent comprises an overbased calcium sulfonate detergent. In certain embodiments, the overbased detergent is one or more calcium-containing detergents, preferably the overbased detergent is a calcium sulfonate detergent.

[0065] In certain embodiments, the overbased detergent comprises at least 0.3 wt.% of the lubricating oil composition. In some embodiments, at least 0.5 wt.%, or at least 0.75 wt.%, or at least 0.9 wt.%, or at least 1.0 wt.% or at least 1.2 wt.% or at least 2.0 wt.% of the lubricating oil composition is overbased detergent

[0066] In certain embodiments, the overbased calcium-containing detergent provides from about 900 to about 2400 ppm calcium to the finished fluid. As a further example, the one or more overbased calcium detergents may be present in an amount to provide from about 900 to about 2000 ppm calcium to the finished fluid. As a further example, the one or more overbased calcium detergents may be present in an amount to provide from about 900 to about 2400 ppm calcium, or from about 900 to about 1800 ppm calcium, or from about 1100 to 1600 ppm calcium, or from about 1200 to 1500 ppm calcium to the finished fluid.

[0067] The optional low-based/neutral detergent has a TBN of up to 175 mg KOH/g, or up to 150 mg KOH/g. The low-based/neutral detergent may include a calcium-containing detergent. The low-based neutral calcium-containing detergent may be selected from a calcium sulfonate detergent, a calcium phenate detergent and a calcium salicylate detergent. In some embodiments, the low-based/neutral detergent is a calcium-containing detergent or a mixture of calcium-containing detergents. In some embodiments, the low-based/neutral detergent is a calcium sulfonate detergent or a calcium phenate detergent.

[0068] The low-based/neutral detergent comprises at least 0.2 wt.% of the lubricating oil composition. In some embodiments, at least 0.5 wt.%, or at least 0.75 wt.%, or at least 0.9 wt.%, or at least 1.0 wt.% or at least 1.2 wt.% or at least 2.0 wt.% of the lubricating oil composition is a low-based/neutral detergent which may optionally be a low-based/neutral calcium-containing detergent.

[0069] In certain embodiments, the low-based/neutral calcium-containing detergent provides from about 50 to about 1000 ppm calcium by weight to the lubricating oil composition based on a total weight of the lubricating oil composition. In some embodiments, the low-based/neutral calcium-containing detergent provides from 75 to less than 800 ppm, or from 100 to 600 ppm, or from 125 to 500 ppm by weight calcium to the lubricating oil composition based on a total weight of the lubricating oil composition.

[0070] In some embodiments, the lubricating oil composition has a ratio of total millimoles metal (M) to TBN of the lubricating oil composition ranging from greater than 4.5

to about 10.0. In some embodiments the ratio of total millimoles metal (M) to TBN of the lubricating oil composition ranges from greater than 8 to less than 10.0 or from 8 to 9.5 or from 8.1 to 9.0.

[0071] In some embodiments, when a low-based/neutral detergent used along with an overbased calcium detergent, the ratio of the ppm of calcium, by weight, provided to the lubricating oil composition by the low-based/neutral detergent to the ppm of calcium, by weight, provided to the lubricating oil composition by the overbased calcium detergent, is from about 0.01 to about 1, or from about 0.03 to about 0.7, or from about 0.05 to about 0.5, or from about 0.08 to about 0.4.

[0072] The overbased calcium-containing detergent may be an overbased calcium sulfonate detergent. The overbased calcium-containing detergent may optionally exclude overbased calcium salicylate detergents. The lubricating oil may optionally exclude any magnesium-containing detergents or be free of magnesium. In any of the embodiments of the disclosure, the amount of sodium in the lubricating composition may be limited to not more than 150 ppm of sodium, based on a total weight of the lubricating oil composition.

Titanium-containing compounds

[0073] The lubricating composition may also include one or more oil-soluble titanium compounds. The oil-soluble titanium compounds may function as antiwear agents, friction modifiers, antioxidants, deposit control additives, or have more than one of these functions. In certain embodiments the inclusion of titanium to the lubricating oil composition unexpectedly reduces the number of LSPI events and hence the LSPI Ratio. Titanium can be used in the lubricating oil composition to further enhance the reduction in LSPI events provided by reducing amount of calcium in the lubricating oil composition.


[0074] The titanium-containing compounds may function as antiwear agents, friction modifiers, antioxidants, deposit control additives, or more than one of these functions. Among the titanium containing compounds that may be used in, or which may be used for preparation of the oils-soluble materials of, the disclosed technology are various Ti (IV) compounds such as titanium (IV) oxide; titanium (IV) sulfide; titanium (IV) nitrate; titanium (IV) alkoxides such as titanium methoxide, titanium ethoxide, titanium propoxide, titanium isopropoxide, titanium butoxide, titanium 2-ethylhexoxide; and other titanium compounds or

complexes including but not limited to titanium phenates; titanium carboxylates such as titanium (IV) 2-ethyl-1-3-hexanedioate or titanium citrate or titanium oleate; and titanium (IV) (triethanolaminate)isopropoxide. Other forms of titanium encompassed within the disclosed technology include titanium phosphates such as titanium dithiophosphates (e.g., dialkyldithiophosphates) and titanium sulfonates (e.g., alkylbenzenesulfonates), or, generally, the reaction product of titanium compounds with various acid materials to form salts, such as oil-soluble salts. Titanium compounds can thus be derived from, among others, organic acids, alcohols, and glycols. Ti compounds may also exist in dimeric or oligomeric form, containing Ti--O--Ti structures. Such titanium materials are commercially available or can be readily prepared by appropriate synthesis techniques which will be apparent to the person skilled in the art. They may exist at room temperature as a solid or a liquid, depending on the particular compound. They may also be provided in a solution form in an appropriate inert solvent.


[0075] In one embodiment, the titanium can be supplied as a titanium-containing dispersant such as a titanium-modified dispersant, such as a succinimide dispersant. Such materials may be prepared by forming a titanium mixed anhydride between a titanium alkoxide and a hydrocarbyl-substituted succinic anhydride, such as an alkenyl- (or alkyl) succinic anhydride. The resulting titanate-succinate intermediate may be used directly or it may be reacted with any of a number of materials, such as (a) a polyamine-based succinimide/amide dispersant having free, condensable --NH functionality; (b) the components of a polyamine-based succinimide/amide dispersant, i.e., an alkenyl- (or alkyl-) succinic anhydride and a polyamine, (c) a hydroxy-containing polyester dispersant prepared by the reaction of a substituted succinic anhydride with a polyol, aminoalcohol, polyamine, or mixtures thereof. Alternatively, the titanate-succinate intermediate may be reacted with other agents such as alcohols, aminoalcohols, ether alcohols, polyether alcohols or polyols, or fatty acids, and the product thereof either used directly to impart Ti to a lubricant, or else further reacted with the succinic dispersants as described above. As an example, 1 part (by mole) of tetraisopropyl titanate may be reacted with about 2 parts (by mole) of a polyisobutene-substituted succinic anhydride at 140-150° C for 5 to 6 hours to provide a titanium modified dispersant or intermediate. The resulting material (30 g) may be further reacted with a succinimide dispersant from polyisobutene-substituted succinic anhydride and a

polyethylenepolyamine mixture (127 grams plus diluent oil) at 150° C for 1.5 hours, to produce a titanium-modified succinimide dispersant. Exemplary titanium-containing dispersants are disclosed in U.S Patent no. 8,008,237 and 8,268,759.

[0076] Another titanium-containing compound may be a reaction product of titanium alkoxide and a C₆ to C₂₅ carboxylic acid. This reaction product may be represented by the following formula:



wherein n is an integer selected from 2, 3 and 4, and R is a hydrocarbyl group containing from about 5 to about 24 carbon atoms, or this reaction product may be represented by the formula:



wherein each of R¹, R², R³, and R⁴ are the same or different and are selected from a hydrocarbyl group containing from about 5 to about 25 carbon atoms. Suitable carboxylic acids for use in the reaction may include, but are not limited to caproic acid, caprylic acid, lauric acid, myristic acid, palmitic acid, stearic acid, arachidic acid, oleic acid, erucic acid, linoleic acid, linolenic acid, cyclohexanecarboxylic acid, phenylacetic acid, benzoic acid, neodecanoic acid, and the like.

[0077] In the foregoing embodiments, the oil soluble titanium-containing compound may be present in the lubricating oil composition in an amount sufficient to provide from about 10 to about 3000 ppm titanium by weight or from about 25 to about 1500 ppm titanium by weight or from about 35 ppm to about 500 ppm titanium by weight or from about 50 ppm to about 350 ppm titanium by weight.

[0078] In one embodiment, the oil soluble titanium-containing compound is preferably a reaction product of titanium isopropoxide and neodecanoic acid. In another embodiment, the titanium compound is preferably titanium isopropoxide. In a further embodiment the titanium compound is preferably a titanium-containing dispersant.

[0079] In additional embodiments the oil soluble titanium compound may be a titanium (IV) alkoxide. The titanium alkoxide may be formed from a monohydric alcohol, a polyol, or mixtures thereof. The monohydric alkoxides may have 2 to 16, or 3 to 10 carbon atoms. In an embodiment, the titanium alkoxide may be titanium (IV) isopropoxide. In an embodiment, the titanium alkoxide may be titanium (IV) 2-ethylhexoxide. In an embodiment, the titanium compound may be the alkoxide of a 1,2-diol or polyol. In an embodiment, the 1,2-diol comprises a fatty acid mono-ester of glycerol, such as oleic acid. In an embodiment, the oil soluble titanium compound may be a titanium carboxylate. In an embodiment the titanium (IV) carboxylate may be titanium neodecanoate.

Tungsten-containing compounds

[0080] The lubricating composition may also include one or more tungsten-containing compounds. The tungsten-containing compounds are preferably oil soluble and may function as antiwear agents, friction modifiers, antioxidants, deposit control additives, or have more than one of these functions. In certain embodiments the inclusion of tungsten in the lubricating oil composition unexpectedly reduces the number of LSPI events and hence the LSPI Ratio. Tungsten can be used in the lubricating oil composition to further enhance the reduction in LSPI events provided by reducing the amount of calcium in the lubricating oil composition.

[0081] Tungsten compounds suitable for use in the lubricating oil composition may include elemental tungsten, organotungsten, tungsten oxide, sulphur-containing organotungsten, sulphur- and phosphorus-free tungsten sources, and the like.

[0082] These tungsten-containing compounds may include alkyl or aryl-substituted ammonium tungstate compounds. Suitable alkyl-substituted ammonium tungstate compounds are described in EP 1 618 172 B1. These are organo-ammonium metal compounds consist of polytungstate ions and dialkyl-ammonium ions of the type $R_2NH_2^+$, wherein the radicals —R are long-chain alkyl or aryl groups, such as C_6 - C_{30} or C_{10} - C_{24} alkyl

or aryl groups. One example for such group is di-tridecyl ammonium tungstate, which can be prepared by reacting tungstic acid hydrate with di-tridecylamine.

[0083] By way of further example, the sulphur-containing organotungsten compound may be prepared by a variety of methods. One method would include reacting a sulphur- and phosphorus-free tungsten source with an amino group and one or more sulphur sources. Sulfur-containing tungsten compounds might also be the reaction of a sulphur-free tungsten source with an amino group or a thiuram group and, optionally, a second sulphur source.

[0084] Examples of sulfur- and phosphorus-free tungsten sources include tungsten acid, tungsten trioxide, ammonium ortho tungstate, ammonium metal tungstate, ammonium paratungstate, sodium tungstate, potassium tungstate, and tungsten halides.

[0085] Still additional tungsten compounds include, without limitation, tungsten hexacarbonyl, tungsten ethoxide, tungsten oxychloride, tungsten pentacarbonyl-N-pentylisonitrile, tungsten silicide, tungsten acid, cyclomatic tungsten compounds, tungsten organoamines, tungsten phosphenes, organo-oxo-tungstenates.

[0086] Still additional tungsten compounds may be in the form of nanoalloy tungsten lubricant additive compounds such as, without limitation, MgWO_4 , CaWO_4 , ZnWO_4 , and the like.

[0087] The tungsten can be oil-soluble or dispersed or mixed in a lubricant. Available tungsten-containing compounds, and the production of the same, are illustrated in International Publication Number WO 20071009022.

[0088] The tungsten-containing additive may be added in a sufficient amount so as to produce a final concentration of at least 125 ppm, or at least 200 ppm. or at least 300 ppm of tungsten in the lubricating oil composition, based on a total weight of the lubricating oil composition. The tungsten-containing additive may be added in a sufficient amount so as to produce a final concentration of 125-3000 ppm, or 200-2000 ppm. or 300-1000 ppm of tungsten in the lubricating oil composition, based on a total weight of the lubricating oil composition.

[0089] A suitable example of a tungsten-containing compound which may be used includes a commercial dialkyl ammonium tungstate sold under the trade name VanLube™ W-324 (Vanderbilt Chemicals, LLC).

Base Oil

[0090] The base oil used in the lubricating oil compositions herein may be selected from any of the base oils in Groups I-V as specified in the American Petroleum Institute (API) Base Oil Interchangeability Guidelines. The five base oil groups are as follows:

Table 1

Base oil Category	Sulfur (%)		Saturates (%)	Viscosity Index
Group I	> 0.03	and/or	<90	80 to 120
Group II	≤0.03	and	≥90	80 to 120
Group III	≤0.03	and	≥90	≥120
Group IV	All polyalphaolefins (PAOs)			
Group V	All others not included in Groups I, II, III, or IV			

[0091] Groups I, II, and III are mineral oil process stocks. Group IV base oils contain true synthetic molecular species, which are produced by polymerization of olefinically unsaturated hydrocarbons. Many Group V base oils are also true synthetic products and may include diesters, polyol esters, polyalkylene glycols, alkylated aromatics, polyphosphate esters, polyvinyl ethers, and/or polyphenyl ethers, and the like, but may also be naturally occurring oils, such as vegetable oils. It should be noted that although Group III base oils are derived from mineral oil, the rigorous processing that these fluids undergo causes their physical properties to be very similar to some true synthetics, such as PAOs. Therefore, oils derived from Group III base oils may be referred to as synthetic fluids in the industry.

[0092] The base oil used in the disclosed lubricating oil composition may be a mineral oil, animal oil, vegetable oil, synthetic oil, or mixtures thereof. Suitable oils may be derived from hydrocracking, hydrogenation, hydrofinishing, unrefined, refined, and re-refined oils, and mixtures thereof.

[0093] Unrefined oils are those derived from a natural, mineral, or synthetic source without or with little further purification treatment. Refined oils are similar to the unrefined oils except that they have been treated in one or more purification steps, which may result in the improvement of one or more properties. Examples of suitable purification techniques are solvent extraction, secondary distillation, acid or base extraction, filtration, percolation, and the like. Oils refined to the quality of an edible may or may not be useful. Edible oils may

also be called white oils. In some embodiments, lubricating oil compositions are free of edible or white oils.

[0094] Re-refined oils are also known as reclaimed or reprocessed oils. These oils are obtained similarly to refined oils using the same or similar processes. Often these oils are additionally processed by techniques directed to removal of spent additives and oil breakdown products.

[0095] Mineral oils may include oils obtained by drilling or from plants and animals or any mixtures thereof. For example such oils may include, but are not limited to, castor oil, lard oil, olive oil, peanut oil, corn oil, soybean oil, and linseed oil, as well as mineral lubricating oils, such as liquid petroleum oils and solvent-treated or acid-treated mineral lubricating oils of the paraffinic, naphthenic or mixed paraffinic-naphthenic types. Such oils may be partially or fully hydrogenated, if desired. Oils derived from coal or shale may also be useful.

[0096] Useful synthetic lubricating oils may include hydrocarbon oils such as polymerized, oligomerized, or interpolymerized olefins (e.g., polybutylenes, polypropylenes, propylene/isobutylene copolymers); poly(1-hexenes), poly(1-octenes), trimers or oligomers of 1-decene, e.g., poly(1-decenes), such materials being often referred to as α -olefins, and mixtures thereof; alkyl-benzenes (e.g. dodecylbenzenes, tetradecylbenzenes, dinonylbenzenes, di-(2-ethylhexyl)-benzenes); polyphenyls (e.g., biphenyls, terphenyls, alkylated polyphenyls); diphenyl alkanes, alkylated diphenyl alkanes, alkylated diphenyl ethers and alkylated diphenyl sulfides and the derivatives, analogs and homologs thereof or mixtures thereof. Polyalphaolefins are typically hydrogenated materials.

[0097] Other synthetic lubricating oils include polyol esters, diesters, liquid esters of phosphorus-containing acids (e.g., tricresyl phosphate, trioctyl phosphate, and the diethyl ester of decane phosphonic acid), or polymeric tetrahydrofurans. Synthetic oils may be produced by Fischer-Tropsch reactions and typically may be hydroisomerized Fischer-Tropsch hydrocarbons or waxes. In one embodiment oils may be prepared by a Fischer-Tropsch gas-to-liquid synthetic procedure as well as other gas-to-liquid oils.

[0098] Greater than 50 wt.% of the base oil included in a lubricating composition may be selected from the group consisting of Group I, Group II, a Group III, a Group IV, a Group V, and a combination of two or more of the foregoing, and wherein greater than 50 wt.% of

the base oil is other than base oils that arise from provision of additive components or viscosity index improvers in the composition. In another embodiment, greater than 50 wt.% of the base oil included in a lubricating composition may be selected from the group consisting of Group II, a Group III, a Group IV, a Group V, and a combination of two or more of the foregoing, and wherein greater than 50 wt.% of the base oil is other than base oils that arise from provision of additive components or viscosity index improvers in the composition.

[0099] The amount of the oil of lubricating viscosity present may be the balance remaining after subtracting from 100 wt.% the sum of the amount of the performance additives inclusive of viscosity index improver(s) and/or pour point depressant(s) and/or other top treat additives. For example, the oil of lubricating viscosity that may be present in a finished fluid may be a major amount, such as greater than about 50 wt.%, greater than about 60 wt.%, greater than about 70 wt.%, greater than about 80 wt.%, greater than about 85 wt.%, or greater than about 90 wt.%.

[00100] The lubricating oil composition may comprise not more than 10 wt.% of a Group IV base oil, a Group V base oil, or a combination thereof. In each of the foregoing embodiments, the lubricating oil compositions comprises less than 5 wt.% of a Group V base oil. The lubricating oil composition does not contain any Group IV base oils. The lubricating oil composition does not contain any Group V base oils.

[00101] In other embodiments, the lubricating oil composition further includes one or more optional components selected from the various additives set forth below.

Antioxidants

[00102] The lubricating oil compositions herein also may optionally contain one or more antioxidants. Antioxidant compounds are known and include for example, phenates, phenate sulfides, sulfurized olefins, phosphosulfurized terpenes, sulfurized esters, aromatic amines, alkylated diphenylamines (e.g., nonyl diphenylamine, di-nonyl diphenylamine, octyl diphenylamine, di-octyl diphenylamine), phenyl-alpha-naphthylamines, alkylated phenyl-alpha-naphthylamines, hindered non-aromatic amines, phenols, hindered phenols, oil-soluble molybdenum compounds, macromolecular antioxidants, or mixtures thereof. Antioxidant compounds may be used alone or in combination.

[00103] The hindered phenol antioxidant may contain a secondary butyl and/or a tertiary butyl group as a sterically hindering group. The phenol group may be further substituted with a hydrocarbyl group and/or a bridging group linking to a second aromatic group. Examples of suitable hindered phenol antioxidants include 2,6-di-tert-butylphenol, 4-methyl-2,6-di-tert-butylphenol, 4-ethyl-2,6-di-tert-butylphenol, 4-propyl-2,6-di-tert-butylphenol or 4-butyl-2,6-di-tert-butylphenol, or 4-dodecyl-2,6-di-tert-butylphenol. In one embodiment the hindered phenol antioxidant may be an ester and may include, e.g., IRGANOX™ L-135 available from BASF or an addition product derived from 2,6-di-tert-butylphenol and an alkyl acrylate, wherein the alkyl group may contain about 1 to about 18, or about 2 to about 12, or about 2 to about 8, or about 2 to about 6, or about 4 carbon atoms. Another commercially available hindered phenol antioxidant may be an ester and may include ETHANOX™ 4716 available from Albemarle Corporation.

[00104] Useful antioxidants may include diarylamines and high molecular weight phenols. In an embodiment, the lubricating oil composition may contain a mixture of a diarylamine and a high molecular weight phenol, such that each antioxidant may be present in an amount sufficient to provide up to about 5%, by weight, based upon the final weight of the lubricating oil composition. In an embodiment, the antioxidant may be a mixture of about 0.3 to about 1.5% diarylamine and about 0.4 to about 2.5% high molecular weight phenol, by weight, based upon the final weight of the lubricating oil composition.

[00105] Examples of suitable olefins that may be sulfurized to form a sulfurized olefin include propylene, butylene, isobutylene, polyisobutylene, pentene, hexene, heptene, octene, nonene, decene, undecene, dodecene, tridecene, tetradecene, pentadecene, hexadecene, heptadecene, octadecene, nonadecene, eicosene or mixtures thereof. In one embodiment, hexadecene, heptadecene, octadecene, nonadecene, eicosene or mixtures thereof and their dimers, trimers and tetramers are especially useful olefins. Alternatively, the olefin may be a Diels-Alder adduct of a diene such as 1,3-butadiene and an unsaturated ester, such as, butylacrylate.

[00106] Another class of sulfurized olefin includes sulfurized fatty acids and their esters. The fatty acids are often obtained from vegetable oil or animal oil and typically contain about 4 to about 22 carbon atoms. Examples of suitable fatty acids and their esters include triglycerides, oleic acid, linoleic acid, palmitoleic acid or mixtures thereof. Often, the

fatty acids are obtained from lard oil, tall oil, peanut oil, soybean oil, cottonseed oil, sunflower seed oil or mixtures thereof. Fatty acids and/or ester may be mixed with olefins, such as α -olefins.

[00107] The one or more antioxidant(s) may be present in ranges about 0 wt.% to about 20 wt.%, or about 0.1 wt.% to about 10 wt.%, or about 1 wt.% to about 5 wt.%, of the lubricating oil composition.

Antiwear Agents

[00108] The lubricating oil compositions herein also may optionally contain one or more antiwear agents. Examples of suitable antiwear agents include, but are not limited to, a metal thiophosphate; a metal dialkyldithiophosphate; a phosphoric acid ester or salt thereof; a phosphate ester(s); a phosphite; a phosphorus-containing carboxylic ester, ether, or amide; a sulfurized olefin; thiocarbamate-containing compounds including, thiocarbamate esters, alkylene-coupled thiocarbamates, and bis(S-alkyldithiocarbamyl)disulfides; and mixtures thereof. A suitable antiwear agent may be a molybdenum dithiocarbamate. The phosphorus containing antiwear agents are more fully described in European Patent 612 839. The metal in the dialkyl dithiophosphate salts may be an alkali metal, alkaline earth metal, aluminum, lead, tin, molybdenum, manganese, nickel, copper, titanium, or zinc. A useful antiwear agent may be zinc dialkylthiophosphate.

[00109] Further examples of suitable antiwear agents include titanium compounds, tartrates, tartrides, oil soluble amine salts of phosphorus compounds, sulfurized olefins, phosphites (such as dibutyl phosphite), phosphonates, thiocarbamate-containing compounds, such as thiocarbamate esters, thiocarbamate amides, thiocarbamic ethers, alkylene-coupled thiocarbamates, and bis(S-alkyldithiocarbamyl) disulfides. The tartrate or tartride may contain alkyl-ester groups, where the sum of carbon atoms on the alkyl groups may be at least 8. The antiwear agent may in one embodiment include a citrate.

[00110] The antiwear agent may be present in ranges including about 0 wt.% to about 15 wt.%, or about 0.01 wt.% to about 10 wt.%, or about 0.05 wt.% to about 5 wt.%, or about 0.1 wt.% to about 3 wt.% of the lubricating oil composition.

[00111] An antiwear compound may be a zinc dihydrocarbyl dithiophosphate (ZDDP) having a P:Zn ratio of from about 1:0.8 to about 1:1.7.

Boron-Containing Compounds

[00112] The lubricating oil compositions herein may optionally contain one or more boron-containing compounds.

[00113] Examples of boron-containing compounds include borate esters, borated fatty amines, borated epoxides, borated detergents, and borated dispersants, such as borated succinimide dispersants, as disclosed in U.S. Patent No. 5,883,057.

[00114] The boron-containing compound, if present, can be used in an amount sufficient to provide up to about 8 wt.%, about 0.01 wt.% to about 7 wt.%, about 0.05 wt.% to about 5 wt.%, or about 0.1 wt.% to about 3 wt.% of the lubricating oil composition.

Dispersants

[00115] The lubricating oil composition may optionally further comprise one or more dispersants or mixtures thereof. Dispersants are often known as ashless-type dispersants because, prior to mixing in a lubricating oil composition, they do not contain ash-forming metals and they do not normally contribute any ash when added to a lubricant. Ashless type dispersants are characterized by a polar group attached to a relatively high molecular weight hydrocarbon chain. Typical ashless dispersants include N-substituted long chain alkenyl succinimides. Examples of N-substituted long chain alkenyl succinimides include polyisobutylene succinimide with number average molecular weight of the polyisobutylene substituent in the range about 350 to about 50,000, or to about 5,000, or to about 3,000. Succinimide dispersants and their preparation are disclosed, for instance in U.S. Pat. No. 7,897,696 or U.S. Pat. No. 4,234,435. The polyolefin may be prepared from polymerizable monomers containing about 2 to about 16, or about 2 to about 8, or about 2 to about 6 carbon atoms. Succinimide dispersants are typically the imide formed from a polyamine, typically a poly(ethyleneamine).

[00116] In an embodiment the present disclosure further comprises at least one polyisobutylene succinimide dispersant derived from polyisobutylene with number average molecular weight in the range about 350 to about 50,000, or to about 5000, or to about 3000. The polyisobutylene succinimide may be used alone or in combination with other dispersants.

[00117] In some embodiments, polyisobutylene, when included, may have greater than 50 mol%, greater than 60 mol%, greater than 70 mol%, greater than 80 mol%, or greater than 90 mol% content of terminal double bonds. Such PIB is also referred to as highly reactive PIB ("HR-PIB"). HR-PIB having a number average molecular weight ranging from about 800 to about 5000 is suitable for use in embodiments of the present disclosure. Conventional PIB typically has less than 50 mol%, less than 40 mol%, less than 30 mol%, less than 20 mol%, or less than 10 mol% content of terminal double bonds.

[00118] An HR-PIB having a number average molecular weight ranging from about 900 to about 3000 may be suitable. Such HR-PIB is commercially available, or can be synthesized by the polymerization of isobutene in the presence of a non-chlorinated catalyst such as boron trifluoride, as described in US Patent No. 4,152,499 to Boerzel, et al. and U.S. Patent No. 5,739,355 to Gateau, et al. When used in the aforementioned thermal ene reaction, HR-PIB may lead to higher conversion rates in the reaction, as well as lower amounts of sediment formation, due to increased reactivity. A suitable method is described in U.S. Patent No. 7,897,696.

[00119] In one embodiment the present disclosure further comprises at least one dispersant derived from polyisobutylene succinic anhydride ("PIBSA"). The PIBSA may have an average of between about 1.0 and about 2.0 succinic acid moieties per polymer.

[00120] The % actives of the alkenyl or alkyl succinic anhydride can be determined using a chromatographic technique. This method is described in column 5 and 6 in U.S. Pat. No. 5,334,321.

[00121] The percent conversion of the polyolefin is calculated from the % actives using the equation in column 5 and 6 in U.S. Pat. No. 5,334,321.

[00122] Unless stated otherwise, all percentages are in weight percent and all molecular weights are number average molecular weights.

[00123] In one embodiment, the dispersant may be derived from a polyalphaolefin (PAO) succinic anhydride.

[00124] In one embodiment, the dispersant may be derived from olefin maleic anhydride copolymer. As an example, the dispersant may be described as a poly-PIBSA.

[00125] In an embodiment, the dispersant may be derived from an anhydride which is grafted to an ethylene-propylene copolymer.

[00126] One class of suitable dispersants may be Mannich bases. Mannich bases are materials that are formed by the condensation of a higher molecular weight, alkyl substituted phenol, a polyalkylene polyamine, and an aldehyde such as formaldehyde. Mannich bases are described in more detail in U.S. Patent No. 3,634,515.

[00127] A suitable class of dispersants may be high molecular weight esters or half ester amides.

[00128] A suitable dispersant may also be post-treated by conventional methods by a reaction with any of a variety of agents. Among these are boron, urea, thiourea, dimercaptiothiadiazoles, carbon disulfide, aldehydes, ketones, carboxylic acids, hydrocarbon-substituted succinic anhydrides, maleic anhydride, nitriles, epoxides, carbonates, cyclic carbonates, hindered phenolic esters, and phosphorus compounds. US 7,645,726; US 7,214,649; and US 8,048,831 are incorporated herein by reference in their entireties.

[00129] In addition to the carbonate and boric acids post-treatments both the compounds may be post-treated, or further post-treatment, with a variety of post-treatments designed to improve or impart different properties. Such post-treatments include those summarized in columns 27-29 of U.S. Pat. No. 5,241,003, hereby incorporated by reference. Such treatments include, treatment with:

Inorganic phosphorus acids or anhydrides (e.g., U.S. Pat. Nos. 3,403,102 and 4,648,980);

Organic phosphorus compounds (e.g., U.S. Pat. No. 3,502,677);

Phosphorus pentasulfides;

Boron compounds as already noted above (e.g., U.S. Pat. Nos. 3,178,663 and 4,652,387);

Carboxylic acid, polycarboxylic acids, anhydrides and/or acid halides (e.g., U.S. Pat. Nos. 3,708,522 and 4,948,386);

Epoxides, polyepoxides or thioepoxides (e.g., U.S. Pat. Nos. 3,859,318 and 5,026,495);

Aldehyde or ketone (e.g., U.S. Pat. No. 3,458,530);

Carbon disulfide (e.g., U.S. Pat. No. 3,256,185);

Glycidol (e.g., U.S. Pat. No. 4,617,137);

Urea, thourea or guanidine (e.g., U.S. Pat. Nos. 3,312,619; 3,865,813; and British Patent GB 1,065,595);

Organic sulfonic acid (e.g., U.S. Pat. No. 3,189,544 and British Patent GB 2,140,811);

Alkenyl cyanide (e.g., U.S. Pat. Nos. 3,278,550 and 3,366,569);

Diketene (e.g., U.S. Pat. No. 3,546,243);

A diisocyanate (e.g., U.S. Pat. No. 3,573,205);

Alkane sultone (e.g., U.S. Pat. No. 3,749,695);

1,3-Dicarbonyl Compound (e.g., U.S. Pat. No. 4,579,675);

Sulfate of alkoxylated alcohol or phenol (e.g., U.S. Pat. No. 3,954,639);

Cyclic lactone (e.g., U.S. Pat. Nos. 4,617,138; 4,645,515; 4,668,246; 4,963,275; and 4,971,711);

Cyclic carbonate or thiocarbonate linear monocarbonate or polycarbonate, or chloroformate (e.g., U.S. Pat. Nos. 4,612,132; 4,647,390; 4,648,886; 4,670,170);

Nitrogen-containing carboxylic acid (e.g., U.S. Pat. 4,971,598 and British Patent GB 2,140,811);

Hydroxy-protected chlorodicarbonyloxy compound (e.g., U.S. Pat. No. 4,614,522);

Lactam, thiolactam, thiolactone or dithiolactone (e.g., U.S. Pat. Nos. 4,614,603 and 4,666,460);

Cyclic carbonate or thiocarbonate, linear monocarbonate or polycarbonate, or chloroformate (e.g., U.S. Pat. Nos. 4,612,132; 4,647,390; 4,646,886; and 4,670,170);

Nitrogen-containing carboxylic acid (e.g., U.S. Pat. No. 4,971,598 and British Patent GB 2,440,811);

Hydroxy-protected chlorodicarbonyloxy compound (e.g., U.S. Pat. No. 4,614,522);

Lactam, thiolactam, thiolactone or dithiolactone (e.g., U.S. Pat. Nos. 4,614,603, and 4,666,460);

Cyclic carbamate, cyclic thiocarbamate or cyclic dithiocarbamate (e.g., U.S. Pat. Nos. 4,663,062 and 4,666,459);

Hydroxyaliphatic carboxylic acid (e.g., U.S. Pat. Nos. 4,482,464; 4,521,318; 4,713,189);

Oxidizing agent (e.g., U.S. Pat. No. 4,379,064);

Combination of phosphorus pentasulfide and a polyalkylene polyamine (e.g., U.S. Pat. No. 3,185,647);

Combination of carboxylic acid or an aldehyde or ketone and sulfur or sulfur chloride (e.g., U.S. Pat. Nos. 3,390,086; 3,470,098);

Combination of a hydrazine and carbon disulfide (e.g. U.S. Pat. No. 3,519,564);

Combination of an aldehyde and a phenol (e.g., U.S. Pat. Nos. 3,649,229; 5,030,249; 5,039,307);

Combination of an aldehyde and an O-diester of dithiophosphoric acid (e.g., U.S. Pat. No. 3,865,740);

Combination of a hydroxyaliphatic carboxylic acid and a boric acid (e.g., U.S. Pat. No. 4,554,086);

Combination of a hydroxyaliphatic carboxylic acid, then formaldehyde and a phenol (e.g., U.S. Pat. No. 4,636,322);

Combination of a hydroxyaliphatic carboxylic acid and then an aliphatic dicarboxylic acid (e.g., U.S. Pat. No. 4,663,064);

Combination of formaldehyde and a phenol and then glycolic acid (e.g., U.S. Pat. No. 4,699,724);

Combination of a hydroxyaliphatic carboxylic acid or oxalic acid and then a diisocyanate (e.g. U.S. Pat. No.4,713,191);

Combination of inorganic acid or anhydride of phosphorus or a partial or total sulfur analog thereof and a boron compound (e.g., U.S. Pat. No. 4,857,214);

Combination of an organic diacid then an unsaturated fatty acid and then a nitrosoaromatic amine optionally followed by a boron compound and then a glycolating agent (e.g., U.S. Pat. No. 4,973,412);

Combination of an aldehyde and a triazole (e.g., U.S. Pat. No. 4,963,278);

Combination of an aldehyde and a triazole then a boron compound (e.g., U.S. Pat. No. 4,981,492);

Combination of cyclic lactone and a boron compound (e.g., U.S. Pat. No. 4,963,275 and 4,971,711). The above mentioned patents are herein incorporated in their entireties.

[00130] The TBN of a suitable dispersant may be from about 10 to about 65 on an oil-free basis, which is comparable to about 5 to about 30 TBN if measured on a dispersant sample containing about 50% diluent oil.

[00131] The dispersant, if present, can be used in an amount sufficient to provide up to about 20 wt.%, based upon the final weight of the lubricating oil composition. Another amount of the dispersant that can be used may be about 0.1 wt.% to about 15 wt.%, or about 0.1 wt.% to about 10 wt.%, or about 3 wt.% to about 10 wt.%, or about 1 wt.% to about 6 wt.%, or about 7 wt.% to about 12 wt.%, based upon the final weight of the lubricating oil composition. In some embodiments, the lubricating oil composition utilizes a mixed dispersant system. A single type or a mixture of two or more types of dispersants in any desired ratio may be used.

Friction Modifiers

[00132] The lubricating oil compositions herein also may optionally contain one or more friction modifiers. Suitable friction modifiers may comprise metal containing and metal-free friction modifiers and may include, but are not limited to, imidazolines, amides, amines, succinimides, alkoxyated amines, alkoxyated ether amines, amine oxides, amidoamines, nitriles, betaines, quaternary amines, imines, amine salts, amino guanadine, alkanolamides, phosphonates, metal-containing compounds, glycerol esters, sulfurized fatty compounds and olefins, sunflower oil other naturally occurring plant or animal oils, dicarboxylic acid esters, esters or partial esters of a polyol and one or more aliphatic or aromatic carboxylic acids, and the like.

[00133] Suitable friction modifiers may contain hydrocarbyl groups that are selected from straight chain, branched chain, or aromatic hydrocarbyl groups or mixtures thereof, and may be saturated or unsaturated. The hydrocarbyl groups may be composed of carbon and hydrogen or hetero atoms such as sulfur or oxygen. The hydrocarbyl groups may range from about 12 to about 25 carbon atoms. In some embodiments the friction modifier may be a long chain fatty acid ester. In another embodiment the long chain fatty acid ester may be a mono-ester, or a di-ester, or a (tri)glyceride. The friction modifier may be a long chain fatty amide, a long chain fatty ester, a long chain fatty epoxide derivatives, or a long chain imidazoline.

[00134] Other suitable friction modifiers may include organic, ashless (metal-free), nitrogen-free organic friction modifiers. Such friction modifiers may include esters formed by reacting carboxylic acids and anhydrides with alkanols and generally include a polar terminal group (e.g. carboxyl or hydroxyl) covalently bonded to an oleophilic hydrocarbon chain. An example of an organic ashless nitrogen-free friction modifier is known generally as glycerol monooleate (GMO) which may contain mono-, di-, and tri-esters of oleic acid. Other suitable friction modifiers are described in U.S. Pat. No. 6,723,685, herein incorporated by reference in its entirety.

[00135] Aminic friction modifiers may include amines or polyamines. Such compounds can have hydrocarbyl groups that are linear, either saturated or unsaturated, or a mixture thereof and may contain from about 12 to about 25 carbon atoms. Further examples of suitable friction modifiers include alkoxyated amines and alkoxyated ether amines. Such compounds may have hydrocarbyl groups that are linear, either saturated, unsaturated, or a mixture thereof. They may contain from about 12 to about 25 carbon atoms. Examples include ethoxyated amines and ethoxyated ether amines.

[00136] The amines and amides may be used as such or in the form of an adduct or reaction product with a boron compound such as a boric oxide, boron halide, metaborate, boric acid or a mono-, di- or tri-alkyl borate. Other suitable friction modifiers are described in U.S. Pat. No. 6,300,291, herein incorporated by reference in its entirety.

[00137] A friction modifier may optionally be present in ranges such as about 0 wt.% to about 10 wt.%, or about 0.01 wt.% to about 8 wt.%, or about 0.1 wt.% to about 4 wt.%.

Molybdenum-containing component

[00138] The lubricating oil compositions herein also may optionally contain one or more molybdenum-containing compounds. An oil-soluble molybdenum compound may have the functional performance of an antiwear agent, an antioxidant, a friction modifier, or mixtures thereof. An oil-soluble molybdenum compound may include molybdenum dithiocarbamates, molybdenum dialkyldithiophosphates, molybdenum dithiophosphinates, amine salts of molybdenum compounds, molybdenum xanthates, molybdenum thioxanthates, molybdenum sulfides, molybdenum carboxylates, molybdenum alkoxides, a trinuclear organo-molybdenum compound, and/or mixtures thereof. The molybdenum sulfides include

molybdenum disulfide. The molybdenum disulfide may be in the form of a stable dispersion. In one embodiment the oil-soluble molybdenum compound may be selected from the group consisting of molybdenum dithiocarbamates, molybdenum dialkyldithiophosphates, amine salts of molybdenum compounds, and mixtures thereof. In one embodiment the oil-soluble molybdenum compound may be a molybdenum dithiocarbamate.

[00139] Suitable examples of molybdenum compounds which may be used include commercial materials sold under the trade names such as Molyvan 822TM, MolyvanTM A, Molyvan 2000TM and Molyvan 855TM from R. T. Vanderbilt Co., Ltd., and Sakura-LubeTM S-165, S-200, S-300, S-310G, S-525, S-600, S-700, and S-710 available from Adeka Corporation, and mixtures thereof. Suitable molybdenum components are described in US 5,650,381; US RE 37,363 E1; US RE 38,929 E1; and US RE 40,595 E1, incorporated herein by reference in their entireties.

[00140] Additionally, the molybdenum compound may be an acidic molybdenum compound. Included are molybdic acid, ammonium molybdate, sodium molybdate, potassium molybdate, and other alkaline metal molybdates and other molybdenum salts, e.g., hydrogen sodium molybdate, MoOCl₄, MoO₂Br₂, Mo₂O₃Cl₆, molybdenum trioxide or similar acidic molybdenum compounds. Alternatively, the compositions can be provided with molybdenum by molybdenum/sulfur complexes of basic nitrogen compounds as described, for example, in U.S. Pat. Nos. 4,263,152; 4,285,822; 4,283,295; 4,272,387; 4,265,773; 4,261,843; 4,259,195 and 4,259,194; and US Patent Publication No. 2002/0038525, incorporated herein by reference in their entireties.

[00141] Another class of suitable organo-molybdenum compounds are trinuclear molybdenum compounds, such as those of the formula Mo₃S_kL_nQ_z and mixtures thereof, wherein S represents sulfur, L represents independently selected ligands having organo groups with a sufficient number of carbon atoms to render the compound soluble or dispersible in the oil, n is from 1 to 4, k varies from 4 through 7, Q is selected from the group of neutral electron donating compounds such as water, amines, alcohols, phosphines, and ethers, and z ranges from 0 to 5 and includes non-stoichiometric values. At least 21 total carbon atoms may be present among all the ligands' organo groups, such as at least 25, at least 30, or at least 35 carbon atoms. Additional suitable molybdenum compounds are described in U.S. Pat. No. 6,723,685, herein incorporated by reference in its entirety.

[00142] The oil-soluble molybdenum compound may be present in an amount sufficient to provide about 0.5 ppm to about 2000 ppm, about 1 ppm to about 700 ppm, about 1 ppm to about 550 ppm, about 5 ppm to about 300 ppm, or about 20 ppm to about 250 ppm of molybdenum.

Additional transition metal-containing compounds

[00143] In another embodiment, the oil-soluble compound may be an additional transition metal containing compound or a metalloid. The additional transition metals may include, but are not limited to, vanadium, copper, zinc, zirconium, molybdenum, tantalum, tungsten, and the like. Suitable metalloids include, but are not limited to, boron, silicon, antimony, tellurium, and the like.

Viscosity Index Improvers

[00144] The lubricating oil compositions herein also may optionally contain one or more viscosity index improvers. Suitable viscosity index improvers may include polyolefins, olefin copolymers, ethylene/propylene copolymers, polyisobutenes, hydrogenated styrene-isoprene polymers, styrene/maleic ester copolymers, hydrogenated styrene/butadiene copolymers, hydrogenated isoprene polymers, alpha-olefin maleic anhydride copolymers, polymethacrylates, polyacrylates, polyalkyl styrenes, hydrogenated alkenyl aryl conjugated diene copolymers, or mixtures thereof. Viscosity index improvers may include star polymers and suitable examples are described in US Patent No. 8,999,905 B2.

[00145] The lubricating oil compositions herein also may optionally contain one or more dispersant viscosity index improvers in addition to a viscosity index improver or in lieu of a viscosity index improver. Suitable viscosity index improvers may include functionalized polyolefins, for example, ethylene-propylene copolymers that have been functionalized with the reaction product of an acylating agent (such as maleic anhydride) and an amine; polymethacrylates functionalized with an amine, or esterified maleic anhydride-styrene copolymers reacted with an amine.

[00146] The total amount of viscosity index improver and/or dispersant viscosity index improver may be about 0 wt.% to about 20 wt.%, about 0.1 wt.% to about 15 wt.%, about 0.1

wt.% to about 12 wt.%, or about 0.5 wt.% to about 10 wt.%, of the lubricating oil composition.

Other Optional Additives

[00147] Other additives may be selected to perform one or more functions required of a lubricating fluid. Further, one or more of the mentioned additives may be multi-functional and provide functions in addition to or other than the function prescribed herein.

[00148] A lubricating oil composition according to the present disclosure may optionally comprise other performance additives. The other performance additives may be in addition to specified additives of the present disclosure and/or may comprise one or more of metal deactivators, viscosity index improvers, detergents, ashless TBN boosters, friction modifiers, antiwear agents, corrosion inhibitors, rust inhibitors, dispersants, dispersant viscosity index improvers, extreme pressure agents, antioxidants, foam inhibitors, demulsifiers, emulsifiers, pour point depressants, seal swelling agents and mixtures thereof. Typically, fully-formulated lubricating oil will contain one or more of these performance additives.

[00149] Suitable metal deactivators may include derivatives of benzotriazoles (typically tolyltriazole), dimercaptiothiadiazole derivatives, 1,2,4-triazoles, benzimidazoles, 2-alkyldithiobenzimidazoles, or 2-alkyldithiobenzothiazoles; foam inhibitors including copolymers of ethyl acrylate and 2-ethylhexylacrylate and optionally vinyl acetate; demulsifiers including trialkyl phosphates, polyethylene glycols, polyethylene oxides, polypropylene oxides and (ethylene oxide-propylene oxide) polymers; pour point depressants including esters of maleic anhydride-styrene, polymethacrylates, polyacrylates or polyacrylamides.

[00150] Suitable foam inhibitors include silicon-based compounds, such as siloxane.

[00151] Suitable pour point depressants may include a polymethylmethacrylates or mixtures thereof. Pour point depressants may be present in an amount sufficient to provide from about 0 wt.% to about 1 wt.%, about 0.01 wt.% to about 0.5 wt.%, or about 0.02 wt.% to about 0.04 wt.% based upon the final weight of the lubricating oil composition.

[00152] Suitable rust inhibitors may be a single compound or a mixture of compounds having the property of inhibiting corrosion of ferrous metal surfaces. Non-limiting examples

of rust inhibitors useful herein include oil-soluble high molecular weight organic acids, such as 2-ethylhexanoic acid, lauric acid, myristic acid, palmitic acid, oleic acid, linoleic acid, linolenic acid, behenic acid, and cerotic acid, as well as oil-soluble polycarboxylic acids including dimer and trimer acids, such as those produced from tall oil fatty acids, oleic acid, and linoleic acid. Other suitable corrosion inhibitors include long-chain alpha, omega-dicarboxylic acids in the molecular weight range of about 600 to about 3000 and alkenylsuccinic acids in which the alkenyl group contains about 10 or more carbon atoms such as, tetrapropenylsuccinic acid, tetradecenylsuccinic acid, and hexadecenylsuccinic acid. Another useful type of acidic corrosion inhibitors are the half esters of alkenyl succinic acids having about 8 to about 24 carbon atoms in the alkenyl group with alcohols such as the polyglycols. The corresponding half amides of such alkenyl succinic acids are also useful. A useful rust inhibitor is a high molecular weight organic acid. In some embodiments, an engine oil is devoid of a rust inhibitor.

[00153] The rust inhibitor, if present, can be used in an amount sufficient to provide about 0 wt.% to about 5 wt.%, about 0.01 wt.% to about 3 wt.%, about 0.1 wt.% to about 2 wt.%, based upon the final weight of the lubricating oil composition.

[00154] In general terms, a suitable crankcase lubricant may include additive components in the ranges listed in the following table.

Table 2

Component	Wt. % (Broad)	Wt. % (Typical)
Dispersant(s)	0.0 – 10%	1.0 – 8.5%
Antioxidant(s)	0.0 – 5.0	0.01 – 3.0
Metal Detergent(s)	0.1 – 15.0	0.2 – 8.0
Ashless TBN booster(s)	0.0 – 1.0	0.01 – 0.5
Corrosion Inhibitor(s)	0.0 – 5.0	0.0 – 2.0
Metal dihydrocarbyl dithiophosphate(s)	0.1 – 6.0	0.1 – 4.0
Ash-free amine phosphate salt(s)	0.0 – 3.0	0.0 – 1.5
Antifoaming agent(s)	0.0 – 5.0	0.001 – 0.15
Antiwear agent(s)	0.0 – 10.0	0.0 – 5.0
Pour point depressant(s)	0.0 – 5.0	0.01 – 1.5
Viscosity index improver(s)	0.0 – 20.00	0.25 – 10.0
Dispersant viscosity index improver(s)	0.0 - 10.0	0.0 - 5.0
Friction modifier(s)	0.01 – 5.0	0.05 - 2.0
Base oil(s)	Balance	Balance
Total	100	100

[00155] The percentages of each component above represent the weight percent of each component, based upon the weight of the final lubricating oil composition. The remainder of the lubricating oil composition consists of one or more base oils.

[00156] The lubricating oil compositions of the present invention may have a sulfated ash content of less than 1.0 wt.% or less than 0.8 wt.%, based on the total weight of the lubricating oil composition. In an embodiment the sulfated ash content may range from about 0.5 wt.% to about 1.0 wt.%, or from about 0.7 wt.% to about 1.0 wt.%, based on the total weight of the lubricating oil composition.

[00157] As described in more detail below, embodiments of the disclosure provide significant and unexpected improvement in reducing LSPI events while maintaining a relatively high calcium detergent concentration in the lubricating oil composition. In each of the foregoing embodiments, the low speed pre-ignition reducing additive composition may reduce the number of LSPI events by at least 50% or by at least 75%. In each of the foregoing embodiments, the LSPI events may be LSPI counts during 25,000 engine cycles, wherein the engine is operated at 2000 revolutions per minute with a brake mean effective pressure of 18,000 kPa.

[00158] Additives used in formulating the compositions described herein may be blended into the base oil individually or in various sub-combinations. However, it may be suitable to blend all of the components concurrently using an additive concentrate (i.e., additives plus a diluent, such as a hydrocarbon solvent). Additives used in formulating the compositions described herein may be blended into the base oil individually or in various sub-combinations. However, it may be suitable to blend all of the components concurrently using an additive concentrate (i.e., additives plus a diluent, such as a hydrocarbon solvent).

[00159] The present disclosure provides novel lubricating oil blends specifically formulated for use as automotive engine lubricants. Embodiments of the present disclosure may provide lubricating oils suitable for engine applications that provide improvements in one or more of the following characteristics: low speed pre-ignition events, antioxidancy, antiwear performance, rust inhibition, fuel economy, water tolerance, air entrainment, seal protection, deposit reduction, i.e. passing the TEOST 33 test, and foam reducing properties.

[00160] Fully formulated lubricants conventionally contain an additive package, referred to herein as a dispersant/inhibitor package or DI package, that will supply the characteristics that are required in the formulations. Suitable DI packages are described for example in U.S. Patent Nos. 5,204,012 and 6,034,040 for example. Among the types of additives included in the additive package may be dispersants, seal swell agents, antioxidants, foam inhibitors, lubricity agents, rust inhibitors, corrosion inhibitors, demulsifiers, viscosity index improvers, and the like. Several of these components are well known to those skilled in the art and are generally used in conventional amounts with the additives and compositions described herein.

[00161] The following examples are illustrative, but not limiting, of the methods and compositions of the present disclosure. Other suitable modifications and adaptations of the variety of conditions and parameters normally encountered in the field, and which are obvious to those skilled in the art, are within the spirit and scope of the disclosure. All patents and publications cited herein are fully incorporated by reference herein in their entirety.

EXAMPLES

[00162] Fully formulated lubricating oil compositions containing conventional additives were made and the low speed pre-ignition events of the lubricating oil compositions were measured. Each of the lubricating oil compositions contained a major amount of a base oil, a base conventional DI package and a viscosity index improver(s), wherein the base DI package (less the viscosity index improver) provided about 8 to 12 percent by weight of the lubricating oil composition. The base DI package contained conventional amounts of dispersant(s), antiwear additive(s), antifoam agent(s), and antioxidant(s) as set forth in Table 3 below. Specifically, the base DI package contained a succinimide dispersant, a borated succinimide dispersant, a molybdenum-containing compound in an amount to deliver about 80 ppm molybdenum to the lubricating oil composition, an organic friction modifier, one or more antioxidants, and one or more antiwear agents (unless specified otherwise). The base DI package was also blended with about 5 to about 10 wt.% of one or more viscosity index improvers. Group I base oil was used as a diluent. The major amount of base oil (about 78 to about 87 wt.%) was a Group III base oil. The components that were varied are specified in

the Tables and discussion of the Examples below. All the values listed are stated as weight percent of the component in the lubricating oil composition (i.e., active ingredient plus diluent oil, if any), unless specified otherwise.

Table 3 – Base DI Package Composition

<u>Component</u>	<u>Wt. %</u>
Antioxidant(s)	0.5 to 2.5
Antiwear agent(s), including any metal dihydrocarbyl dithiophosphate	0.7 to 5.0
Antifoaming agent(s)	0.001 to 0.01
Detergent(s)*	0.0
Dispersant (s)	2.0 to 6.0
Metal-containing friction modifier(s)	0.05 to 1.25
Metal free friction modifier(s)	0.01 to 0.5
Pour point depressant(s)	0.05 to 0.5
Process oil	0.25 to 1.0

*Detergent is varied in the following experiments, so for purposes of the base formulation, the detergent amount is set to zero in Table 3.

[00163] Low Speed Pre-Ignition (LSPI) events were measured in a GM 2.0 Liter, 4 cylinder Ecotec turbocharged gasoline direct injection (TGDi) engine. One complete LSPI fired engine test consisted of 4 test cycles. Within a single test cycle, two operational stages or segments are repeated in order to generate LSPI events. In stage A, when LSPI is most likely to occur, the engine is operated at about 2000 rpm and about 18,000 kPa brake mean effective pressure (BMEP). In stage B, when LSPI is not likely to occur, the engine is operated at about 1500 rpm and about 17,000 kPa BMEP. For each stage, data is collected over 25,000 engine cycles. The structure of a test cycle is as follows: stage A – stage A – stage B – stage B – stage A – stage A. Each stage is separated by an idle period. Because LSPI is statistically significant during stage A, the LSPI event data that was considered in the present examples only included LSPI generated during stage A operation. Thus, for one complete LSPI fired engine test, data was typically generated over a total of 16 stages and was used to evaluate performance of comparative and inventive oils.

[00164] LSPI events were determined by monitoring peak cylinder pressure (PP) and when 2% of the combustible material in the combustion chamber burns (MFB02). The threshold for peak cylinder pressure is calculated for each cylinder and for each stage and is

typically 65,000 to 85,000 kPa. The threshold for MFB02 is calculated for each cylinder and for each stage and typically ranges from about 3.0 to about 7.5 Crank Angle Degree (CAD) After Top Dead Center (ATDC). An LSPI was recorded when both the PP and MFB02 thresholds were exceeded in a single engine cycle. LSPI events can be reported in many ways. In order to remove ambiguity involved with reporting counts per engine cycles, where different fired engine tests can be conducted with a different number of engine cycles, the relative LSPI events of comparative and inventive oils was reported as an "LSPI Ratio". In this way improvement relative to some standard response is clearly demonstrated.

[00165] All of the reference oils are commercially available engine oils that meet all ILSAC GF-5 performance requirements.

[00166] In the following examples, combinations of an overbased calcium detergent and a neutral/low based calcium detergent were tested with the base formulation. The LSPI Ratio was reported as a ratio of the LSPI events of the test oil relative to the LSPI events of Reference Oil "R-1". R-1 was a lubricating oil composition formulated with the base DI package and an overbased calcium detergent in an amount sufficient to provide about 2400 ppm Ca to the lubricating oil composition. More detailed formulation information for reference oil R-1 is given below.

[00167] Considerable improvement in LSPI is recognized when there is greater than 50% reduction in LSPI events relative to R-1 (an LSPI Ratio of less than 0.5). A further improvement in LSPI is recognized when there is greater than 70% reduction in LSPI events (an LSPI Ratio of less than 0.3), an even further improvement in LSPI is recognized when there is greater than 75% reduction in LSPI events (an LSPI Ratio of less than 0.25), and an even further improvement in LSPI is recognized when there is greater than 80% reduction in LSPI events relative to R-1 (an LSPI Ratio of less than 0.20), and an even further improvement in LSPI is recognized when there is greater than 90% reduction in LSPI events relative to R-1 (an LSPI Ratio of less than 0.10). The LSPI Ratio for the R-1 reference oil is thus deemed to be 1.00.

[00168] Sulfated ash (SASH) content in the fully formulated lubricating oil composition was calculated by summing the SASH attributed to metallic elements that contribute to SASH in the lubricant composition according to the following factors that were multiplied by the amount of each metallic element in the lubricant composition according to:

<http://konnaris.com/portals/0/search/calculations.htm>.

Element	Factor	Element	Factor
Barium	1.70	Magnesium	4.95
Boron	3.22	Manganese	1.291
Calcium	3.40	Molybdenum	1.50
Copper	1.252	Potassium	2.33
Lead	1.464	Sodium	3.09
Lithium	7.92	Zinc	1.50
Titanium	1.67		

[00169] Commercial oils, R-1 and R-2, are included as reference oils to demonstrate the current state of the art. Reference oil R-1 was formulated from about 80.7 wt.% of a Group III base oil, 12.1 wt.% of HiTEC® 11150 PCMO Additive Package available from Afton Chemical Corporation and 7.2 wt.% of a 35 SSI ethylene/propylene copolymer viscosity index improver. HiTEC® 11150 passenger car motor oil additive package is an API SN, ILSAC-GF-5, and ACEA A5/B5 qualified DI package. R-1 also showed the following properties and partial elemental analysis:

Reference Oil R-1

10.9	Kinematic Viscosity at 100°C, (mm ² /sec)
3.3	TBS, APPARENT_VISCOSITY, cPa
2438	calcium (ppmw)
< 10	magnesium (ppmw)
80	molybdenum (ppmw)
772	phosphorus (ppmw)
855	zinc (ppmw)
9.0	Total Base Number ASTM D-2896 (mg KOH/g)
165	Viscosity Index

[00170] Reference oil R-2 contained an overbased calcium detergent at an amount to provide about 2600 ppm by weight Ca to the lubricating oil composition. R-2 also comprised a titanium compound and the amount of titanium present in the lubricating composition R-2 was measured by ICP analysis to be about 100 ppm by weight titanium.

Example 1

[00171] The impact on the LSPI Ratio by the incorporation of different amounts of titanium in the lubricating oil composition was tested. A combination of overbased calcium detergent (“OB”) and a titanium-containing compound were tested with the base formulation. Formulation R-1, as stated above, contained as the only detergent an overbased calcium detergent at an amount to provide about 2400 ppm by weight Ca to the lubricating oil composition. Formulation R-2 contained slightly more Calcium, as well as 100 ppm titanium.

[00172] Comparative formulation C-1 contained as the only detergent an overbased calcium detergent at an amount to provide 1600 ppm by weight of Ca to the lubricating oil composition. Comparative formulation C-2 contained an overbased calcium detergent at an amount to provide 2400 ppm by weight of Ca to the lubricating oil composition. Formulation C-2 also contained a reaction product of titanium isopropoxide and neodecanoic acid in an amount to provide about 300 ppm by weight of titanium to the lubricating oil composition.

[00173] In inventive formulations I-1, I-2, I-3 and I-4, an overbased calcium detergent was included in an amount to provide either 1600 or 1575 ppm by weight of calcium to the lubricating oil composition. A reaction product of titanium isopropoxide and neodecanoic acid was used to provide varying amounts of titanium to each of the compositions. The amounts of titanium and results are shown in the following table.

Table 4

	R-1	R-2	C-1	C-2	I-1	I-2	I-3	I-4
OB Ca, ppmw	2400	2600	1600	2400	1600	1575	1575	1600
Ti, ppmw	0	100	0	300	25	100	300	1000
LSPI Ratio	1	1.18	0.22	0.83	0.16	0.14	0.05	0.00
Sulfated Ash (SASH), wt. %	1.05	1.11	0.76	1.08	0.77	0.78	0.81	0.93

[00174] Commercial oils, R-1 and R-2 are included as reference oils to demonstrate the current state of the art. Formulations R-1 and R-2 both contain calcium-containing detergents having a high calcium content. R-1 and R-2 meet all performance requirements for ILSAC GF-5. Comparative examples C-1 and C-2 are lubricant compositions that were provided to show the effect on the LSPI Ratio caused by SASH and/or increased titanium content.

[00175] As shown in Table 4, formulations R-1 and R-2 demonstrate that merely adding titanium to a composition containing high amounts of Ca does not improve the LSPI Ratio. Comparative formulation C-1 demonstrates that reducing the amount of overbased calcium detergent, relative to the amount contained in formulations R-1, R-2 and C-2, reduced the LSPI Ratio. Inventive formulations I-1, I-2, I-3 and I-4, when compared to comparative formulation C-1 showed that addition of titanium to the formulations containing the reduced amount of calcium, further reduced the LSPI Ratio and that increasing the amount of titanium while maintaining the amount of calcium relatively constant, provided a significant, unexpected additional reduction in the LSPI Ratio.

[00176] A comparison of R-2, C-2 and I-2 demonstrates that the mere addition titanium to a composition does not necessarily result in a lower LSPI Ratio. Specifically, when very high amounts of overbased Ca detergent are included in the lubricant composition, such that the Ca content is at or above about 2400 ppm by weight, a large amount of titanium would be needed to offset the negative effect of the high Ca content on the LSPI Ratio in order to provide a sufficient reduction of the LSPI Ratio. The unacceptably high SASH content above 1 in formulations R-2 and C-2 indicates that this approach is not attractive. However, it was unexpected that increasing the amount of SASH does not have a negative impact the LSPI Ratio, as shown by comparing the results of inventive examples I-1 to I-4. As the SASH content of these Examples increased, the LSPI Ratio decreased.

Example 2

[00177] The impact of including titanium in the lubricating oil composition from different sources was determined in this example. Formulations R-1 and C-1, as described above in Example 1, were used for comparison purposes. Additionally, inventive example I-2 was also the same in this example 2 as in Example 1. In each of the experimental

compositions of Example 2, I-2, I-5, and I-6, overbased calcium detergent was included in an amount to supply about 1575 ppm by weight Ca to each lubricating oil composition. Formulation I-2 used a reaction product of titanium isopropoxide and neodecanoic acid as the source of titanium. Formulation I-5 used titanium isopropoxide as the source of titanium. In formulation I-6 a titanium-containing dispersant was used as the source of titanium. The results are shown in Table 5.

Table 5

	R-1	C-1	I-2	I-5	I-6
OB Ca, ppmw	2400	1600	1575	1575	1575
Ti, ppmw	0	0	100	100	100
LSPI Ratio	1	0.22	0.14	0.12	0.15

[00178] As shown in Table 5, each of the different sources of titanium used in the lubricating oil compositions were effective for reducing the LSPI Ratio.

Example 3

[00179] In this example, the effect of the addition of titanium to a composition including both an overbased calcium detergent and a low-based/neutral (“LB/N”) calcium detergent was determined. Formulations R-1, R-2, and C-1, as described above in Examples 1-2, were all used for this Example. Formulation C-3 was also included to test the effect of using overbased and low-based/neutral calcium detergents in combination, without the addition of titanium.

[00180] The inventive compositions I-7, I-8, and I-9 also included overbased and low-based/neutral calcium detergents. The tested amounts of detergents and titanium and the results of the tests for these compositions are shown in Table 6.

Table 6

	R-1	R-2	C-1	C-3	I-7	I-8	I-9
OB Ca, ppmw	2400	2600	1600	1350	1325	1300	1325
LB/N Ca, ppmw	0	0	0	125	125	125	125
Total Ca, ppmw	2400	2600	1600	1475	1450	1425	1450
Ti, ppmw	0	100	0	0	25	100	300
LSPI Ratio	1	1.18	0.22	0.24	0.03	0.07	0.01
Sulfated Ash, wt. %	1.05	1.11	0.76	0.723	0.727	0.74	0.773

[00181] A comparison of formulation C-3 with the results obtained with formulations I-7, I-8, and I-9 shows that adding titanium to a composition having both overbased and low-based/neutral calcium detergents provides a significant reduction in the LSPI Ratio.

Example 4

[00182] The impact on the LSPI Ratio of the incorporation of different amounts of tungsten in the lubricating oil composition was tested. The addition of a tungsten-containing compound was tested with the base formulation. Formulation R-1, as stated above, contained as the only detergent an overbased calcium detergent at an amount to provide about 2400 ppm by weight Ca to the lubricating oil composition. Comparative formulation C-1 contained as the only detergent an overbased calcium detergent at an amount to provide 1600 ppm by weight of Ca to the lubricating oil composition. Comparative formulation C-2 contained an amount of overbased calcium sulfonate that delivered 1600 ppm of calcium to the lubricating oil composition and an oil soluble tungsten-containing compound (VanLube™ W-324 available from Vanderbilt Chemicals, LLC) in an amount to provide about 100 ppm by weight of tungsten to the lubricating oil composition.

[00183] Inventive formulation I-1 contained an amount of overbased calcium sulfonate that delivered 1600 ppm of calcium to the lubrication oil composition and an oil soluble tungsten-containing compound (VanLube™ W-324 available from Vanderbilt Chemicals, LLC) in an amount sufficient to provide about 300 ppm by weight of tungsten to the lubricating oil composition. The amounts of tungsten and results are shown in the following table.

Table 7

	R-1	C-1	C-2	I-1
OB Ca, ppmw	2400	1600	1600	1600
Tungsten, ppmw	0	0	100	300
LSPI Ratio	1.000	0.218	0.213	0.087

[00184] Commercial oil, R-1 is included as a reference oil to demonstrate the current state of the art. R-1 meets all performance requirements for ILSAC GF-5. Comparative examples C-1 and C-2 are lubricant compositions provided to show the effect on the LSPI Ratio caused by tungsten at 100 ppm by weight of the total lubricating oil composition.

[00185] As shown in Table 7, comparative formulation C-1 demonstrates that reducing the amount of overbased calcium detergent, relative to the amount contained in formulation R-1, reduced the LSPI Ratio. Comparative formulation C-2 demonstrates that adding 100 ppm by weight of tungsten to a lubricating oil composition reduces the LSPI Ratio by a minimal amount. Inventive formulation I-1, when compared to comparative formulation C-1 showed that addition of 300 ppm by weight of tungsten to the formulation, further reduced the LSPI Ratio by an unexpected amount. This inventive composition showed that increasing the amount of tungsten while maintaining the amount of calcium relatively constant, provided a significant, unexpected additional reduction in the LSPI Ratio.

[00186] At numerous places throughout this specification, reference has been made to a number of U.S. Patents and other documents. All such cited documents are expressly incorporated in full into this disclosure as if fully set forth herein.

[00187] Other embodiments of the present disclosure will be apparent to those skilled in the art from consideration of the specification and practice of the embodiments disclosed herein. As used throughout the specification and claims, “a” and/or “an” may refer to one or more than one. Unless otherwise indicated, all numbers expressing quantities of ingredients,

properties such as molecular weight, percent, ratio, reaction conditions, and so forth used in the specification and claims are to be understood as being modified in all instances by the term "about," whether or not the term "about" is present. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the specification and claims are approximations that may vary depending upon the desired properties sought to be obtained by the present disclosure. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques. Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the disclosure are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the disclosure being indicated by the following claims.

[00188] The foregoing embodiments are susceptible to considerable variation in practice. Accordingly, the embodiments are not intended to be limited to the specific exemplifications set forth hereinabove. Rather, the foregoing embodiments are within the spirit and scope of the appended claims, including the equivalents thereof available as a matter of law.

[00189] The patentees do not intend to dedicate any disclosed embodiments to the public, and to the extent any disclosed modifications or alterations may not literally fall within the scope of the claims, they are considered to be part hereof under the doctrine of equivalents.

[00190] It is to be understood that each component, compound, substituent or parameter disclosed herein is to be interpreted as being disclosed for use alone or in combination with one or more of each and every other component, compound, substituent or parameter disclosed herein.

[00191] It is also to be understood that each amount/value or range of amounts/values for each component, compound, substituent or parameter disclosed herein is to be interpreted as also being disclosed in combination with each amount/value or range of amounts/values

disclosed for any other component(s), compounds(s), substituent(s) or parameter(s) disclosed herein and that any combination of amounts/values or ranges of amounts/values for two or more component(s), compounds(s), substituent(s) or parameters disclosed herein are thus also disclosed in combination with each other for the purposes of this description.

[00192] It is further understood that each range disclosed herein is to be interpreted as a disclosure of each specific value within the disclosed range that has the same number of significant digits. Thus, a range of from 1-4 is to be interpreted as an express disclosure of the values 1, 2, 3 and 4.

[00193] It is further understood that each lower limit of each range disclosed herein is to be interpreted as disclosed in combination with each upper limit of each range and each specific value within each range disclosed herein for the same component, compounds, substituent or parameter. Thus, this disclosure is to be interpreted as a disclosure of all ranges derived by combining each lower limit of each range with each upper limit of each range or with each specific value within each range, or by combining each upper limit of each range with each specific value within each range.

[00194] Furthermore, specific amounts/values of a component, compound, substituent or parameter disclosed in the description or an example is to be interpreted as a disclosure of either a lower or an upper limit of a range and thus can be combined with any other lower or upper limit of a range or specific amount/value for the same component, compound, substituent or parameter disclosed elsewhere in the application to form a range for that component, compound, substituent or parameter.

What is claimed is:

1. A lubricating oil composition comprising:

greater than 50 wt.% of a base oil of lubricating viscosity,

an amount of one or more overbased calcium-containing detergents having a total base number of greater than 225 mg KOH/g, measured by the method of ASTM D-2896 sufficient to provide greater than 900 ppm by weight to 1800 ppm by weight of calcium to the lubricating oil composition, based on a total weight of the lubricating oil composition, and

a low speed pre-ignition reducing additive composition comprising one of the following a), b) or c):

a) an amount of one or more titanium-containing compounds sufficient to provide from 10 ppm to 3000 ppm by weight of titanium to the lubricating oil composition and at least one low-based/neutral calcium-containing detergent having a total base number of up to 175 mg KOH/gram measured by the method of ASTM D-2896 and optionally an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition based on the total weight of the lubricating oil composition;

b) an amount of one or more titanium-containing compounds sufficient to provide from 10 to 3000 ppm by weight of titanium to the lubricating oil composition and optionally an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition based on the total weight of the lubricating oil composition; and

c) an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition, based on the total weight of the lubricating oil composition, and an amount of one or more molybdenum containing components sufficient to provide from 0.5 to 300 ppm by weight of molybdenum to the lubricating oil composition based on the total weight of the lubricating oil composition, and

wherein said additive composition is effective to reduce low speed pre-ignition events in a boosted internal combustion engine lubricated with the lubricating oil composition relative to a number of low speed pre-ignition events in the same engine lubricated with a same lubricating oil composition without the one or more titanium-containing and/or the one or more tungsten-containing compounds, and the low speed pre-ignition events are low speed pre-ignition counts during 25,000 engine cycles, wherein the engine is operated at 2000 revolutions per minute with a brake mean effective pressure of 18,000 kPa.

2. The lubricating oil composition of claim 1, wherein the one or more overbased calcium-containing detergents comprise a compound selected from: an overbased calcium sulfonate detergent, an overbased calcium phenate detergent, and an overbased calcium salicylate detergent.
3. The lubricating oil composition of claim 2, wherein the one or more overbased calcium-containing detergents provide from 1100 ppm to less than 1800 ppm by weight calcium to the lubricating oil composition based on the total weight of the lubricating oil composition.
4. The lubricating oil composition of claim 1, wherein the lubricating oil composition

comprises one or more titanium-containing compounds.

5. The lubricating oil composition of claim 4, wherein the one or more titanium-containing compounds is selected from the group consisting of a reaction product of titanium isopropoxide and neodecanoic acid; titanium isopropoxide; a titanium-containing dispersant and mixtures thereof.

6. The lubricating oil composition of claim 4, wherein the one or more titanium-containing compounds provide from 25 ppm to 1000 ppm by weight titanium to the lubricating oil composition based on the total weight of the lubricating oil composition.

7. The lubricating oil composition of claim 1, wherein the lubricating oil composition comprises one or more tungsten-containing compounds.

8. The lubricating oil composition of claim 7, wherein the one or more tungsten-containing compounds is an alkyl or aryl-substituted ammonium tungstate wherein the alkyl and aryl groups each have 6-30 carbon atoms.

9. The lubricating oil composition of claim 1, further comprising one or more components selected from the group consisting of friction modifiers, antiwear agents, dispersants, antioxidants, and viscosity index improvers.

10. The lubricating oil composition of claim 1, wherein the greater than 50 wt.% of base oil is selected from the group consisting of Group II, Group III, Group IV, Group V base oils, and a combination of two or more of the foregoing, and wherein greater than 50 wt.% of the base oil is other than diluent oils that arise from provision of additive components or viscosity index improvers in the composition.

11. The lubricating oil composition of claim 1, wherein the lubricating oil composition has a sulfated ash content less than 1.0 wt.%.

12. The lubricating oil composition of claim 1, wherein the low-based/neutral detergent having a total base number of up to 175 mg KOH/g, measured by the method of ASTM D-2896 is present in an amount of at least 0.2 wt.%, based on the weight of the lubricating oil composition.

13. The lubricating composition of claim 11, wherein the low-based/neutral detergent comprises a calcium sulfonate detergent.

14. A method for reducing low speed pre-ignition events in a boosted internal combustion engine comprising:

lubricating a boosted internal combustion engine with a lubricating oil composition comprising greater than 50 wt.% of a base oil of lubricating viscosity and an additive composition comprising:

an amount of one or more overbased calcium-containing detergents having a total base number of greater than 225 mg KOH/g, measured by the method of ASTM D-2896 sufficient to provide greater than 900 ppm by weight to 1800 ppm by weight of calcium to the lubricating oil composition, based on a total weight of the lubricating oil composition, and one of the following a), b) or c):

a) an amount of one or more titanium-containing compounds sufficient to provide from 10 ppm to 3000 ppm by weight of titanium to the lubricating oil composition and at least one low-based/neutral calcium-containing detergent having a total base number of up to 175 mg KOH/gram measured by the method of ASTM D-2896 and optionally an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition based on the total weight of the lubricating oil composition;

b) an amount of one or more titanium-containing compounds sufficient to provide from 10 to 3000 ppm by weight of titanium to the lubricating oil composition and optionally an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition based on the total weight of the lubricating oil composition; and

c) an amount of one or more tungsten-containing compounds sufficient to provide from 125 to 3000 ppm of tungsten to the lubricating oil composition, based on the total weight of the lubricating oil composition, and an amount of one or more molybdenum containing components sufficient to provide from 0.5 to 300 ppm by weight of molybdenum to the lubricating oil composition based on the total weight of the lubricating oil composition, and

operating the engine lubricated with the lubricating oil composition whereby the low speed pre-ignition events in the boosted internal combustion engine lubricated with the lubricating oil composition are reduced relative to a number of low speed pre-ignition events in the same engine lubricated with a same lubricating oil composition without the one or more titanium-containing and/or the one or more

tungsten-containing compounds, and the low speed pre-ignition events are low speed pre-ignition counts during 25,000 engine cycles, wherein the engine is operated at 2000 revolutions per minute with a brake mean effective pressure of 18,000 kPa.

15. The method of claim 14, wherein the lubricant composition has a sulfated ash content of less than 1.0 wt.%.

16. The method of claim 14, wherein the one or more overbased calcium-containing detergents comprise a compound selected from: an overbased calcium sulfonate detergent, an overbased calcium phenate detergent, and an overbased calcium salicylate detergent and the one or more overbased calcium-containing detergents provide from 1100 to less than 1800 ppm by weight calcium to the lubricating oil composition based on the total weight of the lubricating oil composition.

17. The method of claim 14, wherein the lubricating oil composition comprises one or more titanium-containing compounds.

18. The method of claim 14, wherein the lubricating oil composition comprises one or more tungsten-containing compounds.

19. The method of claim 14, wherein the additive composition comprises the low-based/neutral detergent having a total base number of up to 175 mg KOH/g, measured by the method of ASTM D-2896, the low-based/neutral detergent comprises a calcium-containing detergent, and a total amount of calcium from the overbased calcium-containing detergent and the low-based/neutral detergent ranges from greater than 1100 ppm by weight to less than 2400 ppm by weight based on a total weight of the lubricating oil composition, and the low-based/neutral detergent comprises at least 0.2 wt.% of the lubricating oil composition.

20. The method of claim 14, wherein the lubricating step lubricates a combustion chamber or

cylinder walls of a spark-ignited direct injection engine or port fuel injected internal combustion engine provided with a turbocharger or a supercharger.

21. The method of claim 14, further comprising a step of measuring low speed pre-ignition events of the internal combustion engine lubricated with the lubricating oil.