

**METHOD FOR RECORDING DATA ON
AND/OR REPRODUCING DATA FROM A HIGH DENSITY
OPTICAL DISC**

BACKGROUND OF THE INVENTION

5

This application claims the priority of Korean Patent Application No. 2002-27949 filed on 20 May 2002 in the Korean Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

10 1. Field of the Invention

○ The present invention relates to a high density optical disc and a method for recording data on and/or reproducing data from the high density optical disc, and more particularly, to a high density optical disc in which, when data is continuously recorded in an area including a defective area, information indicating an end of recording is recorded in an area that precedes the defective area and linking is performed in an area subsequent to the defective area, and a method for recording data on and/or reproducing data from the high density optical disc.

15

2. Description of the Related Art

○ In general, optical discs are widely used as information recording media for an optical pickup apparatus for recording and/or reproducing information in a non-contact manner and are classified as compact discs (CDs), digital versatile discs (DVDs), etc., according to information recording capacity. There are 650 MB CD-Rs, CD-RWs, 4.7 GB DVD+RWs, etc. as optical discs capable of being recorded on, erased, and reproduced from. Furthermore, an HD-DVD having a 23 GB recording capacity has been developed.

20

25

○ Here, in the case of a CD-RW capable of repetitive recording, a basic recording unit in which a predetermined amount of data can be recorded is referred to as a packet and the structure of the packet is shown in FIG. 1. A plurality of run-in blocks 103 and run-out blocks 105 are arranged before and after a user data block 105 where user data is recorded. Also, a link block 100 is provided at the leading portion of the basic recording unit to enable continuous recording. However, when the user data block 105 includes a defective area where recording is not possible, since data cannot be recorded in the defective area, recording must be terminated before the defective area. However, when the defective area is found,

30

there is no definition made with respect to a recording and/or reproduction method or the structure of an optical disc. Thus, it is likely that the defective area is processed differently according to the manufacturer of the disc or the recording and/or reproduction apparatus. Accordingly, a problem with the compatibility of a disc drive may occur.

Korean Patent Publication No. 2000-75374 filed by the present applicant discloses a defective area processing method and a recording medium in which a linking scheme of a predetermined rule is applied just behind a defective area with respect to a DVD-RW.

However, in the case of a high density optical disc having a capacity of 20 GB or more, to be introduced in the near future, when a defective area is found, there is no definition of a method and the structure of a disc to process the defective area at all. Thus, the above-described problem of the compatibility of a disc drive arises and, accordingly, recording and/or reproduction becomes unstable with respect to the disc. Therefore, for the case in which a defective area is found in the high density optical disc, a definition of a recording and/or reproduction method and the structure of a disc corresponding thereto is needed.

SUMMARY OF THE INVENTION

To solve the above and/or other problems, the present invention provides an optical disc in which, when a defective area is found during verification of the disc or recording and/or reproduction of data, recording end data indicating that recording is terminated is recorded just ahead of the defective area, and a method for recording data on and/or reproducing data from the optical disc. Thus, since the compatibility of a disc drive is ensured, recording and/or reproduction performance of a high density optical disc is improved.

Also, the present invention provides an optical disc and a method for recording data on and/or reproducing data from the optical disc in which recording and/or reproduction are performed smoothly and continuously by performing linking subsequent to the defective area.

According to one aspect of the present invention, an optical disc on which data is recorded and/or from which data is reproduced comprising a recording area where data is recorded in at least one physical cluster, a defective area where a defect that prevents recording and/or reproduction of data is present in the recording

area, and a recording end area where information indicating an end of recording is recorded before the defective area.

The defective area is found during verification of the disc before data is recorded or during recording and/or reproduction of data.

5 A run-in and a run-out are provided before and after a physical cluster, respectively, so that data can be accurately recorded in the physical cluster.

· A guard 3 where data indicating an end of recording is recorded is provided at an end portion of a basic recording unit where a predetermined amount of data is recorded.

10 The guard 3 has a length of at least 300 channel bits and is formed of a continuous pattern including at least 3T and 5T.

○ Recording is performed with respect to the defective area by lowering recording power of a light source to a power that does not incur recording.

15 The recoding power of the light source is maintained as a reproduction power with respect to the defective area.

The recording area comprises a recorded area in which data is already recorded and a blank area in which data is not recorded.

20 According to another aspect of the present invention, an optical disc on which data is recorded and/or from which data is reproduced comprising a recording area where data is recorded in at least one physical cluster, a defective area where a defect that prevents recording and/or reproduction of data is present in the recording area, and a recording end area where information indicating an end of recording is recorded before the defective area, wherein a linkage is set to occur subsequent to the defective area.

25 An additional guard 1 and guard 2 to protect user data are provided in the run-in and run-out, respectively. The guard 2 has the same length and pattern as a guard 3 indicating that recording ends.

○ According to yet another aspect of the present invention, a method for recording data on and/or reproducing data from a high density optical disc having a defective area, the method comprising recording data in a predetermined recording area including the defective area, and recording data indicating an end of recording before the defective area.

The method further comprises processing a linkage to occur subsequent to the defective area.

The data is recorded in units of physical clusters.

According to still yet another aspect of the present invention, a method for recording data on and/reproducing data from a high density optical disc having a defective area, the method comprising recording data in a predetermined recording area including the defective area, and processing a linkage to occur subsequent to the defective area.

BRIEF DESCRIPTION OF THE DRAWINGS

The above features of the present invention will become more apparent by describing in detail preferred embodiments thereof with reference to the attached drawings in which:

FIG. 1 is a view showing the structure of a basic recording unit applied to a conventional CD-RW;

FIG. 2A is a view showing a structure where data is recorded in a single physical cluster;

FIG. 2B is a view showing a recording structure where data is continuously recorded in a plurality of physical clusters;

FIG. 3A is a view showing a case in which a defective area is detected when data is continuously recorded in a plurality of physical clusters in an optical disc according to a preferred embodiment of the present invention;

FIG. 3B is a view showing an optical disc having a defective area, for explaining a method for recording and/or reproducing data by processing the defective area of the optical disc according to a preferred embodiment of the present invention;

FIG. 3C is a view showing the power of a light source when recording and/or reproduction are performed with respect to the optical disc according to the present invention;

FIGS. 4A and 4B are views showing the structure of run-in and run-out of the optical disc according to the present invention;

FIG. 5 is a view for explaining that a linkage is generated subsequent to a defective area according to the method for recording data on and/or reproducing data from an optical disc according to the present invention; and

FIGS. 6A and 6B are views for explaining an optical disc having a defective area according to another preferred embodiment of the present invention and a

method for recording and/or reproduction by processing the defective area of the optical disc.

DETAILED DESCRIPTION OF THE INVENTION

5 FIG. 2A shows a case in which data is recorded in a single physical cluster 5 in a high density optical disc capable of recording and/or reproducing data. FIG. 2B shows a case in which data is continuously recorded in a plurality of physical clusters 15. Run-ins 3 and 13 and run-outs 8 and 18 are disposed before and after the physical clusters 5 and 15, respectively. The run-ins 3 and 13 and the run-outs 8 and 18 are for accurately recording data in the physical clusters 5 and 15 during recording and/or reproducing data. That is, when data is recorded in the run-ins 3 and 13 or the run-outs 8 and 18, which is not the correct position for the data to be recorded, error correction is processed so that data can be smoothly recorded and/or reproduced.

15 Also, guard 3, 10, and 20 where information indicating an end of recording is stored are provided at in a portion where recording ends. The data recording and/or reproduction of a basic recording unit where a predetermined amount of data is recorded is completed by the guard 3. Here, although a physical cluster is explained as a minimum recording unit where user data is recorded, a sector, an ECC block, or a frame may be a minimum recording unit.

20 Referring to FIG. 3A, in an optical disc according to a preferred embodiment of the present invention, when recording and/or reproduction is continuously performed with respect to a basic recording unit having a predetermined capacity where user data is recorded, if a defective area 16 where data cannot be recorded and/or reproduced is found, an address corresponding to the defective area 16 is stored in a defect list area. The defective area 16 can also be found during verification of a disc before data is recorded, in addition to during the recording and/or reproduction of data. When the defective area 16 is found during the verification of a disc, meaningless data that cannot be reproduced is recorded and the defective area is detected by this recording.

30 Next, as shown in FIG. 3B, when recording is performed with respect to a predetermined recording area including the defective area 16, since recording cannot be performed in the defective area 16, a recording end area 14 where data indicating that recording is terminated is provided just before the defective area 16.

The recording end area 14 can be configured identically to the guard 3 (20). That is, the recording end area 14 can be configured to have the same length and pattern as the guard 3 (20). For example, when the guard 3 (20) has a length of at least 300 channel bits and a continuous pattern including at least 3T and 5T, the recording end area 14 is preferably configured to have the same length and pattern as the guard 3 (20). Here, 3T and 5T are units of a length of a mark recorded on a disc.

When data is recorded on an optical disc having the above structure, as shown in FIG. 3C, recording is performed by maintaining the power of a light source (not shown) as a recording power P_w . Starting from the rear portion of the recording end area 14, before the defective area 16 begins, the power of the light source is controlled to be lower than the recording power P_w so that recording cannot be performed. Preferably, the power of the light source can be reduced to a reproduction power P_r . Here, the power of the light source is preferably lowered before the recording end area 14 ends. As shown in FIG. 3B, the power is controlled to be the reproduction power P_r from a position indicated by a dotted line in the recording end area 14.

In the meantime, as shown in FIG. 4A, the run-in 13 may include a guard 1 (13a) having a predetermined pattern to overcome overwriting due to mismatch or change of a data recording start point, and a preamble 13b to perform signal processing such as locking or synchronizing. Also, as shown in FIG. 4B, the run-out 18 may include a post-amble 18a to perform signal processing and a guard 2 (18b) having a predetermined pattern to remove overwriting due to a change of the data recording start point. As a result, the guard 1 (13a) and guard 2 (18b) serve as a buffer to protect user data. Here, the guard 2 (18b) and guard 3 (20) can be configured to have the same lengths and patterns. For example, the guard 2 (18b) and guard 3 (20) may have lengths of at least 300 channel bits and may be formed by continuous patterns including at least 3T and 5T.

Next, a linkage is generated subsequent to the defective area 16 so that recording may resume from a physical cluster subsequent to the defective area 16. Thus, the power of the light source is raised back to the recording power P_w from the rear portion of a run-out 18' subsequent to the defective area 16 and data recording begins again. Referring back to FIG. 3B, an arrow between the run-out 18' and the run-in 13'' after the defective area 16 indicates that a linkage is generated.

A method for recording data on and/or reproducing data from an optical disc according to a preferred embodiment of the present invention will now be described below.

Referring to FIGS. 3A through 3C, when the defective area 16 where no data can be recorded is found during verification of a disc or during recording of data on or reproduction of data from the disc, data indicating that recording ends is recorded in an run-in area 13' disposed before the defective area 16. Thus, recording is not performed in the defective area 16 due to the recording end data. Here, the power of the light source in the defective area 16 is controlled to be lower than the recording power P_w , preferably, the reproduction power P_r , so as not to record data.

Next, a linkage is generated so that data can be recorded in the area subsequent to the defective area 16. That is, the run-out 18' and the run-in-13" subsequent to the defective area 16 are linked.

FIG. 5 shows that the run-out 18' and the run-in-13" subsequent to the defective area 16 are linked. When recording resumes after the defective area 16, data can be recorded overlapping a part of the run-out 18' and a part of the run-in 13" subsequent thereto, not in a desired position for recording. In this case, the linking is performed by correcting an error corresponding to a portion where recording overlaps. Here, the error correction is made in preparation for a case in which recording does not resume at an accurate recording start point when recording ends before the defective area 16 and resumes after the defective area 16.

In the meantime, when the guard 2 (18b') and the guard 3 (20) present in the run-out 18' have the same configuration, that is, the same length and pattern, it is advantageous to use the same linking scheme suggested for the guard 3 (20) as it is. As a result, recording and/or reproduction are smoothly performed after the defective area 16. Recording and/or reproduction are continuously performed up to a physical cluster 15" subsequent to the run-in 13". When another defective area is found during recording and/or reproduction, a recording end area is defined just before the defective area in the same manner as described above and a linkage is generated so that recording can resume in the area subsequent to the defective area. The physical cluster 15" is formed of, for example, 496 recording frames (Rec.Frame) (15"-1, 15"-2, ...). In FIG. 5, these recording frames are illustrated after the run-in 13". Here, cluster k denotes the k^{th} physical cluster.

Next, recording is performed as the power of the light source is maintained at the recording power P_w in the run-in 13" subsequent to the defective area 16. The guard 3 (20) indicating the end of recording is recorded at the end of a basic recording unit where a predetermined amount of data can be recorded. Here, the recording end data, that is, the guard 2, recorded before the defective area 16, is configured to be the same as the guard 3 (20). For example, the guard 3 (14 and 20) preferably have a length of at least 300 channel bits and are configured as a continuous pattern including at least 3T and 5T.

An optical disc and a method for recording data on and/or reproducing data from the optical disc according to another preferred embodiment of the present invention will now be described below.

FIG. 6A shows a state prior to recording is performed according to a method for recording data on and/or reproducing data from an optical disc according to another preferred embodiment of the present invention. Here, recording has been performed from an $(n-2)^{\text{th}}$ physical cluster 22 to an n^{th} block 28 and a blank area in which no data is recorded is present starting from an $(n+1)^{\text{th}}$ block 31. The $(n-2)^{\text{th}}$ through $(n+1)^{\text{th}}$ blocks 22, 25, 28, and 31 have run-ins 21, 24, and 27 and run-outs 23, 26, 29, and 32, respectively, and a defective area is found in the n^{th} block 28. Since recording is terminated in the n^{th} block 28, a guard 3 (30) indicating the end of recording is recorded in a run-in area disposed after the n^{th} block 28. Here, recording is performed from the $(n-2)^{\text{th}}$ block 22 to the $(n+1)^{\text{th}}$ block 31, part of a recording area is already recorded on and the remaining part is not recorded on. In this case, the method for recording and/or reproducing data with respect to an optical disc according to the present invention can be applied.

FIG. 6B shows a state in which recording has been performed according to a method for recording data on and/or reproducing data from an optical disc according to another preferred embodiment of the present invention.

Recording begins from the $(n-2)^{\text{th}}$ block 22 and ends before the n^{th} block 28, which is a defective area. Thus, a guard 3 (37') indicating the end of recording is recorded before the defective area 28. The run-out 29 and the run-in 30' subsequent to the defective area 28 are linked. A guard 3 (33') indicating the end of recording is recorded in the run-in subsequent to the $(n+1)^{\text{th}}$ block 31 where the recording ends.

When recording is performed in an area including a defective area found during continuous data recording and/or reproduction with respect to a high density optical disc or during verification of a blank disc, data indicating the end of recording is recorded just before the defective area and a linkage is defined to occur

5 subsequent to the defective area. Thus, more stable and reliable data recording and/or reproduction is possible.

In the optical disc and the method for recording data on and/or reproducing data from the optical disc according to the present invention, when a defective area is present, since data indicating the end of recording is recorded such that recording
10 ends before the defective area, recording is not performed in the defective area.

Furthermore, since a linkage is processed to occur in an area subsequent to the defective area, data is stably recorded and/or reproduced. In the high density optical disc where data is continuously recorded and/or reproduced, by proposing a standard to process the defective area, the compatibility of a disc drive is ensured
15 and, accordingly, reliability in recording and/or reproduction with respect to the high density optical disc is improved.

5

10



15

20



25

What is claimed is:

1. A method for recording data on and/or reproducing data from a high density optical disc having a defective area, the method comprising:
recording data in a predetermined recording area including the defective area;
and
recording data indicating an end of recording before the defective area.

30

2. The method as claimed in claim 1, further comprising processing a linkage to occur subsequent to the defective area.

3. The method as claimed in either claim 1 or claim 2, wherein the defective area is found during verification of the disc before the data is recorded or during recording and/or reproduction of the data.

4. The method as claimed in either claim 1 or claim 2, wherein the data is recorded in units of physical clusters.

5. The method as claimed in claim 3, wherein the data is recorded in units of physical clusters.

6. The method as claimed in claim 3, wherein a recording power of a light source is lowered to a power that does not incur recording with respect to the defective area.

7. The method as claimed in claim 6, wherein the recording power of the light source is maintained as a reproduction power with respect to the defective area.

8. The method as claimed in either claim 1 or claim 2, wherein a run-in and a run-out are provided before and after a physical cluster to accurately record data in the physical cluster.

9. The method as claimed in either claim 1, claim 2, claim 5, claim 6, or claim 7, wherein a guard 3 to record data indicating an end of recording is provided at an end portion of a basic recording unit where a predetermined amount of data is recorded.

10. The method as claimed in claim 9, wherein the data indicating the end of recording recorded before the defective area has the same length and pattern as the guard 3.

11. The method as claimed in claim 10, wherein a guard 1 and a guard 2 to protect user data are additionally provided at the run-in and run-out.

12. The method as claimed in claim 11., wherein the guard 2 and the guard 3 have the same length and pattern.

13. The method as claimed in either claim 10, claim 11, or claim 12, wherein the guard 3 has a length of at least 300 channel bits and is formed of a continuous pattern including at least 3T and 5T.

14. The method as claimed in either claim 1, claim 2, claim 5, claim 6, or claim 7, wherein the recording area comprises a recorded area in which data is already recorded and a blank area in which data is not recorded.

15. A method for recording data on and/reproducing data from a high density optical disc having a defective area, the method comprising:
recording data in a predetermined recording area including the defective area;
and
processing a linkage to occur subsequent to the defective area.

16. The method as claimed in claim 15., wherein the defective area is found during verification of the disc before data is recorded or during recording and/or reproduction of the data.

17. The method as claimed in either claim 15 or claim 16, wherein the data is recorded in units of physical clusters.

18. The method as claimed in either claim 15 or claim 16, wherein the recording area comprises a recorded area in which data is already recorded and a blank area in which data is not recorded.

19. The method as claimed in claim 17, wherein the recording area comprises a recorded area in which data is already recorded and a blank area in which data is not recorded.

20. The method as claimed in claim 19, wherein a run-out having a guard 2 to protect data is provided subsequent to the physical cluster, and the guard 2 has

the same length and pattern as a guard 3 in which data indicating an end of recording is recorded.

21. The method as claimed in claim 20 , wherein the guard 3 has a length
5 of at least 300 channel bits and is formed of a continuous pattern including at least 3T and 5T.