

CLAIM

5

1. A terminal comprising:
a reception unit configured to receive first
configuration information to be applied to communication
and second configuration information to be applied to
10 communication from a base station;
a control unit configured to, in a case where
a first information element configuring a lowest
subcarrier is included in the first configuration
information, configure a Bandwidth part (BWP) by not
15 using the first information element to configure the
BWP, and by using a second information element
configuring a lowest subcarrier included in the second
configuration information; and
a communication unit configured to communicate
20 with the base station by using the configured BWP,
wherein
the first information element is included in
an information element including a terminal-specific
carrier configuration per subcarrier spacing, and
25 indicates a usable lowest subcarrier, and
the second information element is included in
an information element configuring a cell-common
parameter, and indicates a usable lowest subcarrier.

30

2. A base station comprising:
a transmission unit configured to transmit
35 first configuration information to be applied to
communication and second configuration information to be
applied to communication to a terminal;
a control unit configured to, in a case where
a first information element configuring a lowest
40 subcarrier is included in the first configuration
information, configure a Bandwidth part (BWP) by not
using the first information element to configure the
BWP, and by using a second information element

configuring a lowest subcarrier included in the second configuration information; and

5 a communication unit configured to communicate with the terminal by using the configured BWP, wherein
the first information element is included in
an information element including a terminal-specific carrier configuration per subcarrier spacing, and indicates a usable lowest subcarrier, and
10 the second information element is included in
an information element configuring a cell-common parameter, and indicates a usable lowest subcarrier.

15 3. A communication method performed by a terminal, comprising:

receiving first configuration information to be applied to communication and second configuration information to be applied to communication from a base station;

20 in a case where a first information element configuring a lowest subcarrier is included in the first configuration information, configuring a Bandwidth part (BWP) by not using the first information element to configure the BWP, and by using a second information
25 element configuring a lowest subcarrier included in the second configuration information; and

communicating with the base station by using the configured BWP, wherein

30 the first information element is included in an information element including a terminal-specific carrier configuration per subcarrier spacing, and indicates a usable lowest subcarrier, and

35 the second information element is included in an information element configuring a cell-common parameter, and indicates a usable lowest subcarrier.

40 4. A wireless communication system comprising a terminal and a base station, wherein

the terminal comprises:

a reception unit configured to receive first configuration information to be applied to communication

and second configuration information to be applied to communication from a base station;

5 a control unit configured to, in a case where a first information element configuring a lowest subcarrier is included in the first configuration information, configure a Bandwidth part (BWP) by not using the first information element to configure the BWP, and by using a second information element configuring a lowest subcarrier included in the second configuration information; and

10 a communication unit configured to communicate with the base station by using the configured BWP, and the base station comprises:

15 a transmission unit configured to transmit first configuration information to be applied to communication and second configuration information to be applied to communication to a terminal;

20 a control unit configured to, in a case where a first information element configuring a lowest subcarrier is included in the first configuration information, configure a Bandwidth part (BWP) by not using the first information element to configure the BWP, and by using a second information element configuring a lowest subcarrier included in the second configuration information; and

25 a communication unit configured to communicate with the terminal by using the configured BWP, wherein. the first information element is included in an information element including a terminal-specific carrier configuration per subcarrier spacing, and indicates a usable lowest subcarrier, and

30 the second information element is included in an information element configuring a cell-common parameter, and indicates a usable lowest subcarrier.

35