

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

9901267-6

10:0

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C08G 18/22, C08K 5/00, B01J 31/38	A1	(11) International Publication Number: WO 98/15585 (43) International Publication Date: 16 April 1998 (16.04.98)
(21) International Application Number: PCT/GB97/02565 (22) International Filing Date: 19 September 1997 (19.09.97) (30) Priority Data: 9620808.7 5 October 1996 (05.10.96) GB 9701911.1 30 January 1997 (30.01.97) GB (71) Applicant (for all designated States except US): TIOXIDE SPECIALTIES LIMITED [GB/GB]; Lincoln House, 137-143 Hammersmith Road, London W14 0QL (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): SKINNER, Christopher, John [GB/GB]; 67 Alnwick Road, Newton Hall, Durham DH1 5NN (GB). RIDLAND, John [GB/GB]; 12 Oatlands Way, The Mount, Durham DH1 5GL (GB). (74) Agents: JACKSON, John, Derek et al.; ICI Group Intellectual Property, P.O. Box 90, Wilton, Middlesbrough, Cleveland TS90 8JE (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: CATALYSTS (57) Abstract A catalyst, suitable for use in polyurethane compositions comprises the reaction product of: (a) the reaction product of a titanium, zirconium, hafnium or aluminium orthoester and a β -diketone or β -ketoester and (b) a complexing agent selected from a mercapto compound, an oxazolidine or a tetrahydro-oxazine. The catalyst is particularly useful for preparing coating compositions which have a long pot life and can be cured at room temperature.		